TECHNOVA SOLUTIONS PVT. LTD.
DISASTER RECOVERY POLICY

Document ID	TN-ADM-POL-004
Document Type	Administration / Disaster Recovery Policy
Document Owner	Administration Department / Information Security
Approving Authority	Managing Director
Classification	Internal — Confidential
Version	1.0
Effective Date	01 April 2026
Review Cycle	Annual
Status	Active
Supersedes	New Policy

1. Purpose

This Disaster Recovery Policy establishes the framework TechNova Solutions Pvt. Ltd. (“TechNova” or “the Company”) uses to recover critical technology services, infrastructure, applications, data, and supporting capabilities following a major disruption.

The policy complements Business Continuity by focusing on the restoration and validation of technology capabilities required to support critical business operations.

2. Scope

This policy applies to Company-managed technology infrastructure, applications, databases, networks, cloud services, data stores, backup systems, identity services, critical integrations, and other technology dependencies designated as requiring disaster-recovery capability.

It applies to employees, contractors, Engineering, Operations, Information Security, system owners, service owners, and other personnel participating in recovery activities.

3. Disaster Recovery Objectives

- Protect people and information during recovery.
- Restore critical technology services according to approved priorities.
- Minimize data loss and service interruption.
- Provide controlled and repeatable recovery procedures.
- Maintain security controls during recovery.
- Validate recovered services before returning them to normal operation.
- Capture lessons learned and improve recovery capability.

4. Disaster Recovery Principles

- Safety first.
- Risk-based recovery priorities.
- Documented ownership.
- Tested recovery procedures.

- Controlled emergency access.
- Preservation of data integrity.
- Secure-by-default recovery.
- Clear communication and escalation.

5. Disaster Definition

For this policy, a disaster is a significant event that causes or threatens prolonged or widespread loss of critical technology capability and requires coordinated recovery beyond routine incident handling.

6. Examples of Disaster Scenarios

- Major data-center or facility loss
- Widespread infrastructure failure
- Extended cloud-service disruption
- Ransomware or destructive cyberattack
- Critical database corruption
- Major network or connectivity failure
- Loss of essential technology personnel
- Significant supplier or hosting failure
- Natural or environmental event affecting technology operations

7. Disaster Recovery Governance

Administration coordinates policy governance while Engineering and Operations coordinate technical recovery capabilities within their respective responsibilities. Information Security provides security oversight and supports cyber-recovery activities.

8. Roles and Responsibilities

Role	Primary Responsibility
Executive Management	Provides strategic direction, major risk decisions, resources, and authorization for significant recovery actions.
Recovery Coordinator	Coordinates recovery activities, priorities, communications, dependencies, and status.
Engineering / IT	Restores infrastructure, applications, networks, platforms, and technical services.
Operations	Coordinates business impact, operational dependencies, facilities, suppliers, and continuity activities.
Information Security	Supports secure recovery, cyber incident assessment, evidence preservation, and security validation.
Service Owner	Confirms service recovery requirements, dependencies, readiness, and business validation.
Data Owner	Confirms data requirements, integrity expectations, access, and recovery priorities.

9. Recovery Ownership

Every critical service must have an identifiable recovery owner or accountable service owner. Recovery ownership must not depend on a single individual where practical.

10. Critical Service Identification

Service owners should identify systems and services whose prolonged loss could materially affect customers, employees, financial operations, security, contractual obligations, or other critical business activities.

11. Recovery Tiering

Tier	Description	Recovery Approach
Tier 1 — Critical	Essential services where prolonged unavailability creates severe business impact.	Highest recovery priority and regularly tested recovery capability.
Tier 2 — High	Important services with significant operational consequences.	Recover after Tier 1 according to approved priorities.
Tier 3 — Standard	Services with manageable disruption or alternate processes.	Recover through standard recovery procedures.
Tier 4 — Low	Non-critical services with limited immediate impact.	Recover after higher-priority capabilities.

12. Recovery Time Objective

Each critical service should have an approved Recovery Time Objective (RTO) appropriate to business impact and technical capability. The RTO represents a recovery planning target and does not constitute an unconditional guarantee.

13. Recovery Point Objective

Where data recovery is required, the service owner should define an appropriate Recovery Point Objective (RPO), representing the targeted maximum amount of data loss measured in time.

14. Dependency Mapping

Recovery plans should document dependencies that could prevent successful restoration.

- Compute and infrastructure
- Network and connectivity
- Identity and authentication
- Databases and storage
- Backups
- Cloud or hosting providers
- External APIs and integrations
- Certificates, keys, and secrets
- Critical personnel
- Facilities and power

15. Recovery Strategy

A recovery strategy should define how critical services will be restored following a disaster. Strategies may include restoration from backup, alternate infrastructure, replicated environments, replacement equipment, cloud recovery, or other approved mechanisms.

16. Recovery Site / Alternate Environment

Where required by criticality, services may use an alternate environment or recovery location. The recovery environment should be capable of supporting the service at the level required by the approved recovery objectives.

17. Backup and Replication

Critical data and systems should have backup or replication arrangements appropriate to their RTO, RPO, risk, and technical architecture.

- Backups should be protected.
- Recovery copies should be logically separated where appropriate.
- Backup access should be restricted.

- Restoration capability should be tested.
- Failed backups should be investigated.

18. Backup Integrity

Backups should be monitored and periodically validated to provide reasonable confidence that required data can be recovered.

A backup that cannot be restored when needed must not be treated as a reliable recovery capability.

19. Recovery Documentation

Recovery documentation should provide sufficient information for an authorized recovery team to restore the service without relying solely on undocumented individual knowledge.

- Service architecture or recovery dependencies
- Recovery sequence
- Required credentials or access paths
- Configuration requirements
- Validation steps
- Escalation contacts

20. Recovery Runbooks

Critical systems should have documented recovery runbooks where the complexity or impact justifies them. Runbooks should be version-controlled and reviewed after significant changes.

21. Recovery Activation

Disaster recovery may be activated when normal recovery methods are insufficient or when the scale and expected duration of disruption meet established criteria.

Activation may occur through incident management, business continuity coordination, or management direction.

22. Disaster Declaration

A major disaster declaration should identify the affected services, expected impact, recovery priority, recovery coordinator, and decision authority.

23. Recovery Command

A coordinated recovery structure should be established for significant disasters. Responsibilities, communication channels, decision rights, and recovery priorities should be clear.

24. Recovery Communications

- Establish a recovery communication channel.
- Provide regular status updates.
- Communicate changes to recovery estimates.
- Escalate blockers promptly.
- Protect confidential technical details.

25. Internal Stakeholders

Recovery communications may include Engineering, Operations, Information Security, business owners, management, Finance, HR, Administration, and other stakeholders based on impact.

26. External Stakeholders

Only authorized personnel may communicate with customers, suppliers, regulators, or the public about a disaster or recovery effort.

27. Recovery Access

Recovery activities may require elevated access. Such access must be authorized, limited, protected, logged where appropriate, and reviewed after recovery.

28. Break-Glass Access

Emergency access mechanisms may be used when necessary to recover critical services. Credentials and access paths must be protected and returned to normal control after the emergency.

29. Credential Recovery

Recovery plans must account for situations in which ordinary authentication systems are unavailable. Emergency credentials must be protected and tested without creating unnecessary permanent privileges.

30. Network Recovery

Network recovery should restore essential connectivity in an order consistent with service dependencies.

- Core network infrastructure
- Identity and authentication dependencies
- Critical application connectivity
- External connectivity
- Monitoring and administrative access

31. Identity Recovery

Identity services are often foundational dependencies. Recovery planning should address authentication, authorization, privileged access, directory services, and emergency administrative access.

32. Application Recovery

Applications should be restored according to approved dependency and business priority.

Application recovery should include configuration, dependencies, databases, secrets, integrations, and required supporting services.

33. Database Recovery

Database recovery must protect data integrity and should include appropriate backup selection, restoration, validation, consistency checks, and application compatibility checks.

34. Data Integrity Validation

- Check restoration completeness.
- Validate critical records.
- Check database consistency.
- Confirm expected transaction behavior.
- Investigate unexplained differences.

35. Cloud Recovery

Cloud-based services should have documented recovery dependencies, ownership, access, configuration, backup or replication arrangements, and provider escalation paths.

36. Infrastructure as Code and Configuration

Where infrastructure is managed through approved automation or configuration repositories, recovery plans should identify the authoritative sources and required dependencies needed to recreate infrastructure.

37. Certificates, Keys, and Secrets

Recovery plans must account for certificates, encryption keys, service credentials, API keys, and other secrets required for service restoration. Secrets must be accessed through approved secure mechanisms.

38. Cyber Disaster Recovery

Following a destructive cyber incident, systems must not simply be restored into an environment that remains compromised.

- Coordinate with Information Security.
- Assess compromise before restoration.
- Preserve relevant evidence.
- Reset or rotate affected credentials.
- Validate security controls before production use.

39. Ransomware Recovery

Ransomware recovery should prioritize containment, evidence preservation, secure recovery sources, credential protection, and validation that restored systems are not immediately re-compromised.

40. Recovery from Data Corruption

When data corruption is detected, recovery should select an appropriate clean recovery point and validate data integrity before normal operations resume.

41. Supplier Recovery

If recovery depends on a supplier, the service owner should use approved escalation contacts and assess provider recovery commitments.

- Track supplier status.
- Document provider actions.
- Assess alternate options.
- Record material delays or deviations.

42. Facilities and Equipment

Where recovery requires replacement or relocation of physical equipment, Operations should coordinate facilities, logistics, asset accountability, and security.

43. Replacement Assets

Replacement devices and equipment must be authorized, registered, securely configured, and assigned through appropriate asset-management controls.

44. Recovery Testing

Disaster recovery capabilities must be tested periodically according to risk and criticality.

- Backup restoration tests
- Application recovery tests
- Infrastructure recovery tests
- Failover tests
- Communication exercises
- Cyber-recovery exercises

45. Test Objectives

Recovery tests should evaluate whether documented procedures, dependencies, people, tools, access, data, and recovery targets are realistically sufficient.

46. Test Evidence

Recovery exercises should retain appropriate evidence including date, scope, participants, systems tested, results, failures, recovery times, and corrective actions.

47. Recovery Test Failures

A failed recovery test must be treated as a capability gap. The owner should document the issue, assess risk, define corrective action, and track remediation.

48. Change Management

Material changes to critical systems should trigger review of disaster recovery procedures, dependencies, recovery objectives, and test requirements.

49. Recovery During Emergency Changes

Emergency changes used during disaster recovery must be documented and reviewed after stabilization. Emergency conditions do not remove the need for security and accountability.

50. Recovery Validation

A recovered service must be validated before it is declared operational.

- Technical functionality
- Data integrity
- Security controls
- Dependencies
- Monitoring
- Business functionality
- User access

51. Business Validation

The responsible business or service owner should confirm that critical business functionality is available before recovery is considered complete.

52. Return to Normal

Once primary capabilities are restored, the organization should transition from recovery infrastructure or temporary processes to normal operations in a controlled manner.

53. Failback

Failback to the primary environment should be planned and validated to prevent data divergence, service interruption, or loss of recovery capability.

54. Recovery Monitoring

Recovered services should receive enhanced monitoring for a reasonable stabilization period based on risk and incident severity.

55. Recovery Incident Escalation

If recovery fails, causes secondary impact, or reveals a new security or operational issue, the event must be escalated through the appropriate incident-response process.

56. Recovery Records

Recovery activities should be documented sufficiently to establish what was restored, when it was restored, who performed significant actions, what issues occurred, and whether recovery objectives were met.

57. Recovery Metrics

- RTO achievement
- RPO achievement
- Recovery test success rate
- Backup restoration success
- Number of recovery gaps
- Time to restore critical services
- Open corrective actions

58. Post-Recovery Review

Material disaster-recovery events and significant exercises should receive a post-recovery review.

- What worked?
- What failed?
- Were dependencies correctly identified?
- Were recovery targets realistic?
- Were communications effective?
- What controls or procedures should change?

59. Corrective Actions

Recovery gaps should be assigned to accountable owners with target dates and measurable outcomes. High-risk unresolved gaps should be escalated to management.

60. Confidentiality

Disaster recovery documentation may contain sensitive architecture, credentials, network information, recovery locations, supplier details, and other security-sensitive information. Access must be restricted to authorized personnel.

61. Exceptions

Exceptions to recovery requirements require documented justification, risk assessment, appropriate approval, and compensating measures where practical.

62. Governance

Administration owns this policy. Engineering, Operations, and Information Security are responsible for maintaining recovery capabilities within their areas. The policy must be reviewed at least annually and after significant changes or major recovery events.

63. Frequently Asked Questions

What is disaster recovery?

Disaster recovery is the capability to restore critical technology services, infrastructure, applications, and data after a major disruption.

How is disaster recovery different from business continuity?

Business continuity focuses on sustaining critical business operations; disaster recovery focuses primarily on restoring technology capabilities needed to support those operations.

What is an RTO?

A Recovery Time Objective is the targeted timeframe for restoring a service after disruption.

What is an RPO?

A Recovery Point Objective is the targeted maximum amount of data loss measured in time.

Why are recovery tests necessary?

They demonstrate whether people, procedures, access, backups, dependencies, and technology can actually support recovery.

What if the backup cannot be restored?

The failed recovery capability must be treated as a risk and investigated immediately, with alternative recovery options assessed.

Can emergency access be used during recovery?

Yes, when authorized and necessary. Emergency access must remain controlled, protected, logged where appropriate, and reviewed afterward.

Should compromised systems be restored immediately?

Not necessarily. Security assessment and containment should occur before restoration when compromise is suspected.

Who decides when recovery is complete?

Technical recovery must be validated by the responsible technical owner and critical business functionality should be confirmed by the relevant service or business owner.

What happens after a disaster recovery exercise fails?

The gap should be documented, assigned to an owner, risk-assessed, and tracked to remediation.

64. Revision History

Version	Effective Date	Description	Owner	Approval
1.0	01 April 2026	Initial release of Disaster Recovery Policy	Administration / Information Security	Managing Director

65. Related Documents

- Information Security Policy
- Access Control Policy

- Data Retention Policy
- Business Continuity
- Incident Response
- Asset Management
- Engineering Handbook
- Deployment Policy
- Testing Standards
- Operations Handbook

END OF DOCUMENT

TN-ADM-POL-004 | Version 1.0 | Internal — Confidential | Administration / Information Security