```
from sklearn.model_selection import train_test_split, GridSearchCV
from sklearn.preprocessing import StandardScaler
from sklearn.svm import SVC
from sklearn.metrics import (
    accuracy_score, precision_score, recall_score, f1_score,
    confusion_matrix, classification_report, roc_auc_score, roc_curve
)

# 2) Load dataset (binary classification)
data = load_breast_cancer()
X = pd.DataFrame(data.data, columns=data.feature_names)
y = pd.Series(data.target, name="target")  # 0 = malignant, 1 = benign

# 3) Train/test split
X_train,  X_test,  y_train,  y_test  = train_test_split(
    X, y, test_size=0.20, random_state=42, stratify=y
)

# 4) Standardize features (important for SVMs)
scaler = StandardScaler()
X_train_sc = scaler.fit_transform(X_train)
X_test_sc = scaler.transform(X_test)

# 5) Define model
svm = SVC(kernel='rbf', probability=True, random_state=42)

# 6) Hyperparameter grid & tuning
param_grid = {
    "C": [0.1, 1, 10, 100],
    "gamma": ["scale", 0.01, 0.001, 0.0001]
}
```

```
grid = GridSearchCV(
    estimator=svm,
    param_grid=param_grid,
    scoring='f1',  # You can change to 'accuracy' or 'roc_auc'
    cv=5,
    n_jobs=-1,
    verbose=0
)

grid.fit(X_train_sc, y_train)

print("Best Parameters from Grid Search:", grid.best_params_)
best_svm = grid.best_estimator_

# 7) Train final model & predict
best_svm.fit(X_train_sc, y_train)
y_pred = best_svm.predict(X_test_sc)
y_prob = best_svm.predict_proba(X_test_sc)[:, 1]

# 8) Evaluation
acc = accuracy_score(y_test, y_pred)
prec = precision_score(y_test, y_pred, zero_division=0)
rec = recall_score(y_test, y_pred)
f1 = f1_score(y_test, y_pred)
auc = roc_auc_score(y_test, y_prob)
cm = confusion_matrix(y_test, y_pred)

print("\n=== SVM (RBF) — Test Metrics ===")
print(f"Accuracy : {acc:.4f}")
print(f"Precision: {prec:.4f}")
```

```
print(f"Recall   : {rec:.4f}")
print(f"F1-Score : {f1:.4f}")
print(f"ROC-AUC  : {auc:.4f}")

print("\nConfusion Matrix:\n", cm)
print("\nClassification Report:\n", classification_report(y_test, y_pred, zero_division=0))

# 9) Plot ROC Curve
fpr, tpr, thresholds = roc_curve(y_test, y_prob)
plt.figure()
plt.plot(fpr, tpr, label=f"SVM (AUC = {auc:.3f})")
plt.plot([0, 1], [0, 1], linestyle="--", color='gray')
plt.xlabel("False Positive Rate")
plt.ylabel("True Positive Rate")
plt.title("ROC Curve — SVM (RBF)")
plt.legend()
plt.grid(True)
plt.show()
```

OUTPUT:

```
Best Parameters from Grid Search: {'C': 10, 'gamma': 0.01}


=== SVM (RBF) — Test Metrics ===
Accuracy : 0.9825
Precision: 0.9861
Recall   : 0.9861
F1-Score : 0.9861
ROC-AUC  : 0.9977

Confusion Matrix:
 [[41  1]
 [ 1 71]]

Classification Report:
              precision    recall  f1-score   support

           0       0.98      0.98      0.98        42
           1       0.99      0.99      0.99        72

    accuracy                           0.98       114
   macro avg       0.98      0.98      0.98       114
weighted avg       0.98      0.98      0.98       114
```



RESULT:

The Support Vector Machine (SVM) model was successfully implemented and evaluated on the given dataset. The model effectively classified the data by finding the optimal hyperplane that maximized the margin between different classes.

The SVM achieved high accuracy and demonstrated strong performance, especially in handling linearly and non-linearly separable data using kernel functions. This confirms that SVM is a powerful and reliable algorithm for classification tasks.

EXP NO: 4B	ENSEMBLE METHODS: RANDOM FOREST

AIM:

To implement a **Random Forest classifier** for a classification task, tune key hyperparameters, evaluate performance, and interpret **feature importance**.

ALGORITHM:

1. Import libraries.
2. Load data (use same dataset to compare with SVM).
3. Train/Test split with stratification.
4. (Optional) Preprocess: Random Forests don't require scaling; we'll use raw features.
5. Model: RandomForestClassifier.
6. Hyperparameter tuning: Grid search over n_estimators, max_depth, min_samples_split, min_samples_leaf.
7. Train the best model on training data.
8. Evaluate with accuracy, precision, recall, F1, confusion matrix, ROC-AUC.
9. Interpretation: Plot top feature importances.

CODE:

```
# ========================================
# EXPERIMENT 4B — Random Forest Classifier
# ========================================


# 1) Imports
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.datasets import load_breast_cancer
from sklearn.model_selection import train_test_split, GridSearchCV
```

```
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import (
    accuracy_score, precision_score, recall_score, f1_score,
    confusion_matrix, classification_report, roc_auc_score, roc_curve
)
# 2) Load dataset (same as 4A for comparison)
data = load_breast_cancer()
X = pd.DataFrame(data.data, columns=data.feature_names)
y = pd.Series(data.target, name="target")

# 3) Train/test split (no scaling needed for RF)
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.20, random_state=42, stratify=y
)

# 4) Define model
rf = RandomForestClassifier(random_state=42, n_jobs=-1)

# 5) Hyperparameter grid & tuning
param_grid = {
    "n_estimators": [100],
    "max_depth": [None, 10],
    "min_samples_split": [2],
    "min_samples_leaf": [1]
}
grid = GridSearchCV(
    estimator=rf,
    param_grid=param_grid,
    scoring="f1",
    cv=3,
    n_jobs=-1,
```

```
    verbose=0)
grid.fit(X_train, y_train)
print("Best Parameters (CV):", grid.best_params_)
best_rf = grid.best_estimator_

# 6) Train final model & predict
best_rf.fit(X_train, y_train)
y_pred = best_rf.predict(X_test)
y_prob = best_rf.predict_proba(X_test)[:, 1]

# 7) Evaluate
acc = accuracy_score(y_test, y_pred)
prec = precision_score(y_test, y_pred, zero_division=0)
rec = recall_score(y_test, y_pred)
f1 = f1_score(y_test, y_pred)
auc = roc_auc_score(y_test, y_prob)
cm = confusion_matrix(y_test, y_pred)

print("\n=== Random Forest — Test Metrics ===")
print(f"Accuracy : {acc:.4f}")
print(f"Precision: {prec:.4f}")
print(f"Recall   : {rec:.4f}")
print(f"F1-Score : {f1:.4f}")
print(f"ROC-AUC  : {auc:.4f}")

print("\nConfusion Matrix:\n", cm)
print("\nClassification Report:\n", classification_report(y_test, y_pred, zero_division=0))

# 8) Feature Importance (Top 10)
importances = pd.Series(best_rf.feature_importances_, index=X.columns)
top10 = importances.sort_values(ascending=False).head(10)
```

```
plt.figure()
top10[::-1].plot(kind="barh")
plt.xlabel("Importance")
plt.title("Top 10 Feature Importances — Random Forest")
plt.grid(axis="x", alpha=0.3)
plt.show()

# 9) ROC Curve
fpr, tpr, thresholds = roc_curve(y_test, y_prob)
plt.figure()
plt.plot(fpr, tpr, label=f"Random Forest (AUC = {auc:.3f})")
plt.plot([0, 1], [0, 1], linestyle="--", color='gray')
plt.xlabel("False Positive Rate")
plt.ylabel("True Positive Rate")
plt.title("ROC Curve — Random Forest")
plt.legend()
plt.grid(True)
plt.show()
```

OUTPUT:

```
Best Parameters (CV): {'max_depth': None, 'min_samples_leaf': 1, 'min_samples_split': 2, 'n_estimators': 100}
```


```
=== Random Forest — Test Metrics ===
Accuracy : 0.9561
Precision: 0.9589
Recall   : 0.9722
F1-Score : 0.9655
ROC-AUC  : 0.9937


Confusion Matrix:
 [[39  3]
 [ 2 70]]

Classification Report:
              precision    recall  f1-score   support

           0       0.95      0.93      0.94        42
           1       0.96      0.97      0.97        72

    accuracy                           0.96       114
   macro avg       0.96      0.95      0.95       114
weighted avg       0.96      0.96      0.96       114
```





RESULT:

The Random Forest ensemble model was successfully implemented and evaluated on the given dataset. The model combined multiple decision trees to improve prediction accuracy and reduce overfitting.

It achieved high classification accuracy and demonstrated strong generalization capability. The results confirmed that Random Forest provides stable and reliable predictions by leveraging the power of multiple decision trees through bagging and feature randomness.