
LUXE & THREAD · DOCUMENTATION

INTERNAL – for developers

Internal 04 · Razorpay, Shiprocket & Platform Configuration Guide

Audience	INTERNAL – developers / DevOps
Purpose	Which values to change during **testing** and **live**, how to validate each one, and what breaks if it is wrong
Version	2.0 · October 2026



Where settings live. Nothing is hard-coded. Values come from **environment variables**: `.env.local` (your computer), `.env.production.local` (server, `chmod 600`) or the host's settings. Template: `.env.example`. Validation: `lib/env.ts` (Zod) – a wrong value gives a clear message *when the feature is used*. After changing a value **restart** the app (`pm2 restart luxe-thread`). `NEXT_PUBLIC_*` values are baked in at **build** time – rebuild. ⚠️ Never put a secret in a `NEXT_PUBLIC_*` variable, a screenshot, e-mail or chat.

1 · Master table

Variable	Secret	Needed for	TEST value	LIVE value	Validate (see §5)
`NEXT_PUBLIC_SITE_URL`	no	links in e-mails, sitemap	`http://localhost:3000` / staging URL	`https://www.your-domain.in`	open `/sitemap.xml`, check links
`DATABASE_URL`	**yes**	everything	`postgres://luxe:…@localhost:5432/luxe_thread`	managed/own DB URL (`DATABASE_SSL=true` if required)	`GET /api/health` → `database:true`
`SESSION_SECRET`	**yes**	admin cookies	any 32+ chars	**new** `openssl rand -hex 32`	admin login works
`JOBS_SECRET`	**yes**	cron endpoints	any 16+ chars	**new** long random	`curl` job endpoint → 200
`RAZORPAY_KEY_ID`	no	online payment	`rzp_test_…`	`rzp_live_…`	§5.1
`RAZORPAY_KEY_SECRET`	**yes**	payment, verify, refund	test secret	live secret	§5.1
`RAZORPAY_WEBHOOK_SECRET`	**yes**	payment webhook	secret you typed in the **test** webhook	secret of the **live** webhook (new)	§5.2
`PAYMENT_FEE_PERCENT`	no	profit report estimate	2	your Razorpay plan % (e.g. 2)	report note
`SHIPROCKET_EMAIL` / `_PASSWORD`	**yes**	shipping	**API user**	same/dedicated API user	§5.3
`SHIPROCKET_PICKUP_LOCATION`	no	shipment	pickup **nickname** exactly	real warehouse nickname	§5.3
`SHIPROCKET_PICKUP_PINCODE`	no	PIN-code check	warehouse PIN	warehouse PIN	§5.3
`SHIPROCKET_WEBHOOK_TOKEN`	**yes**	courier webhook	any long text	**new** long text	§5.4
`SHIPROCKET_AUTO_CREATE`	no	auto shipment	`false` (avoid real bookings)	`true`	order flow
`COD_ENABLED` / `COD_MAX_ORDER_VALUE`	no	COD	`true` / 25000	your decision	checkout

Variable	Secret	Needed for	TEST value	LIVE value	Validate (see §5)
`SMTP_URL`, `MAIL_FROM`	**yes**	e-mail	MailHog/Mailpit or sandbox	real SMTP (`smtps://user:pass@host:465`)	§5.5
`SMS_ENABLED`, `SMS_GATEWAY_*`, `SMS_SENDER_ID`	**yes**	SMS	`false`	`true` after DLT approval	§5.5
`WHATSAPP_ENABLED`, `WHATSAPP_PHONE_NUMBER_ID`, `WHATSAPP_TOKEN`	**yes**	WhatsApp	`false`	`true` after template approval	§5.5
`UPLOAD_DIR`	no	photos	`./uploads`	`/var/lib/luxe-thread/uploads`	upload a photo

> **Shiprocket has no sandbox.** API calls create real entries. In TEST keep `SHIPROCKET_AUTO_CREATE=false`, or cancel the test orders in the panel.

2 · Razorpay – what to configure

Step	Where (verify on screen)	Result
Test keys	Dashboard in **Test Mode** → Account & Settings → **API Keys** → Generate	`rzp_test_…` id + secret (shown once)
Webhook	Account & Settings → **Webhooks** → Add	URL `https://<host>/api/webhooks/razorpay`; secret = *you invent it*; events ✅ `payment.captured` ✅ `payment.failed`
Capture mode	Settings → payment capture	**Automatic** (otherwise payments are auto-refunded)
Refunds	built-in (`refundRazorpayPayment`)	needs the same key pair
Live	KYC → switch to **Live Mode** → generate **live** keys → create a **new live webhook**	`rzp_live_…`; new secret

Test payment data: card `4111 1111 1111 1111`, any future expiry/CVV, choose *Success*/*Failure* on the mock page; UPI `success@razorpay` / `failure@razorpay`. **Locally** webhooks need a public URL: `npx ngrok http 3000` (or `cloudflared tunnel`).

3 · Shiprocket – what to configure

Step	Where	Result
KYC + wallet	Shiprocket panel	can book shipments
Pickup address	Settings → Pickup Addresses	note the **nickname** → `SHIPROCKET_PICKUP_LOCATION`
API user	Settings → API → Configure → **Create an API User**	e-mail + password → `SHIPROCKET_EMAIL/PASSWORD`
Courier priority	Settings → courier preferences	decides who auto-assign picks
Webhook	Settings → API → Webhooks	URL `https://<host>/api/webhooks/courier-updates`; token = `SHIPROCKET_WEBHOOK_TOKEN` (sent as `x-api-key`); **URL must not contain** `shiprocket`, `kartrocket`, `sr`, `kr`; must answer **200**
Box size	`lib/shiprocket.ts` (`length/breadth/height`)	measure your real box (cm) – wrong values cause weight-discrepancy charges
Product weight	each product `weight_kg`	packed weight

4 · Platform values (database, sessions, jobs, e-mail)

Value	How to create	Notes
`SESSION_SECRET`, `JOBS_SECRET`	`openssl rand -hex 32`	different values per environment; rotate on staff change
Admin user	`npm run admin:create -- owner@shop.in "Long Passphrase 123" "Owner" owner`	password ≥ 12 chars; `staff` role for helpers
Cron jobs	`* * * * * curl -fsS -X POST -H "x-jobs-secret: $JOBS_SECRET" https://host/api/jobs/notifications >/dev/null` and `*/5 * * * * … /api/jobs/expire-orders`	without them messages still send right after orders, but retries and expiry will not run

Value	How to create	Notes
SMTP	provider SMTP URL, port 465 TLS or 587 STARTTLS	SPF + DKIM + DMARC DNS records for deliverability

5 · Validation commands

5.1 Razorpay keys are valid

```
curl -s -o /dev/null -w "%{http_code}\n" -u "$RAZORPAY_KEY_ID:$RAZORPAY_KEY_SECRET" "https://api.razorpay.com/v1/orders?
count=1"
```

`200` = key id + secret match · `401` = wrong pair (test key with live secret, typo) · network error = firewall.

5.2 Webhook secret and signature

```
BODY='{"event":"payment.captured","payload":{"payment":{"entity":
{"id":"pay_TEST1","order_id":"order_DOESNOTEXIST","method":"upi"}}}}'
SIG=$(printf '%s' "$BODY" | openssl dgst -sha256 -hmac "$RAZORPAY_WEBHOOK_SECRET" | sed 's/^.* //')
curl -i -X POST https://<host>/api/webhooks/razorpay -H "Content-Type: application/json" -H "X-Razorpay-Signature: $SIG"
--data "$BODY"
```

`200 {"received":true}` (the unknown order is just logged) = secret matches · `400 INVALID_SIGNATURE` = secret differs. Then in the Razorpay dashboard open **Webhooks → event log** after a real test payment: delivery should show `200`.

5.3 Shiprocket login, pickup name, serviceability

```
TOKEN=$(curl -s -X POST https://apiv2.shiprocket.in/v1/external/auth/login -H "Content-Type: application/json" \
  -d "{\"email\":\"$SHIPROCKET_EMAIL\",\"password\":\"$SHIPROCKET_PASSWORD\"}" | sed 's/.*"token":"\([^"]*\)".*/\1/')
echo ${#TOKEN}                                  # a long number (>100) = login OK; 0/short = wrong API user
curl -s -H "Authorization: Bearer $TOKEN" https://apiv2.shiprocket.in/v1/external/settings/company/pickup   # lists
pickup nicknames — copy EXACTLY
curl -s -H "Authorization: Bearer $TOKEN" "https://apiv2.shiprocket.in/v1/external/courier/serviceability/?
pickup_postcode=$SHIPROCKET_PICKUP_PINCODE&delivery_postcode=600001&weight=1&cod=0" | head -c 400
```

5.4 Courier webhook token

```
curl -i -X POST https://<host>/api/webhooks/courier-updates -H "Content-Type: application/json" -H "x-api-key:
$SHIPROCKET_WEBHOOK_TOKEN" \
  -d '{"order_id":"LTXXXXXXXX","awb":"123","courier_name":"Test","current_status":"IN TRANSIT"}'
```

`200` = token OK · `401` = mismatch.

5.5 Messages

```
curl -s https://<host>/api/health        # integrations.email / sms / whatsapp = true when configured
# place a TEST order, then: Admin → Messages → status must become "sent"
curl -i -X POST -H "x-jobs-secret: $JOBS_SECRET" https://<host>/api/jobs/notifications   #
{"sent":n,"failed":0,"skipped":m}
```

5.6 Health & database

```
curl -s https://<host>/api/health | python3 -m json.tool
```

Expect `"status":"ok"`, `"database":true`, integrations matching what you configured. `503 degraded` = database unreachable.

6 · TEST → LIVE change list (copy into your ticket)

#	Item	Done
1	`NEXT_PUBLIC_SITE_URL` → live domain; **rebuild**	☐
2	`RAZORPAY_KEY_ID/SECRET` → live; verify with §5.1	☐
3	Create **live** Razorpay webhook (live URL, events, new secret) → `RAZORPAY_WEBHOOK_SECRET`; verify §5.2	☐
4	Shiprocket pickup nickname/PIN = real warehouse; verify §5.3	☐
5	Shiprocket webhook → live URL + **new** token; verify §5.4	☐

#	Item	Done
6	`SHIPROCKET_AUTO_CREATE=true`	☐
7	New `SESSION_SECRET`, `JOBS_SECRET`; admin users re-created with strong passwords	☐
8	`DATABASE_URL` → production DB; migrations applied; **no demo seed**	☐
9	SMTP live + SPF/DKIM; send one real e-mail	☐
10	SMS/WhatsApp only after DLT / template approval	☐
11	`UPLOAD_DIR` persistent & in backups	☐
12	Box size, product weights, GST rates/HSN confirmed by CA	☐
13	One real ₹ order → refund it	☐

7 · Things that go wrong (quick lookup)

Symptom	Likely value at fault
"Online payment is not configured yet"	`RAZORPAY_KEY_ID/SECRET` empty
Payment OK but order stays "Awaiting payment"	`RAZORPAY_WEBHOOK_SECRET` wrong **and** verify call failed
`INVALID_SIGNATURE` on verify	test key id with live secret (or the reverse)
"Wrong pickup location"	`SHIPROCKET_PICKUP_LOCATION` spelling/case
Shipping provider login failed	using your normal login instead of the **API user**
Webhook 401	token mismatch
Admin login "not configured"	`SESSION_SECRET` < 32 chars/missing, or `DATABASE_URL` missing
Messages stay `queued`	cron not running / SMTP wrong (see Admin → Messages → last error)