

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: NK-86MA BYPASS RATIO: 1.13 PRESSURE RATIO $(\pi_{\circ\circ})$: UNIQUE ID NUMBER: 1KK005 13.2 RATED OUTPUT $(F_{\circ\circ})$ (kN): 130.47 ENGINE TYPE: MTF

REGULATORY DATA

CHARACTERISTIC VALUE:	НС	СО	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	15.2	100.5	37.3	10.5
AS % OF ORIGINAL LIMIT	77.4 %	85.1 %	56.2 %	47.8 %
AS % OF CAEP/2 LIMIT (NOx)			70.2 %	
AS % OF CAEP/4 LIMIT (NOx)			93.0 %	
AS % OF CAEP/6 LIMIT (NOx)			105.7 %	
AS % OF CAEP/8 LIMIT (NOx)			140.9 %	

DATA STATUS

PRE-REGULATION

CERTIFICATION

REVISED (SEE REMARKS)

CURRENT ENGINE STATUS

TEST ENGINE STATUS

×

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

DEDICATED ENGINES TO PRODUCTION STANDARD

NEWLY MANUFACTURED ENGINES

OTHER (SEE REMARKS)

OUT OF PRODUCTION OUT OF SERVICE

EMISSIONS STATUS

DATA CORRECTED TO REFERENCE (ANNEX 16 VOLUME II)

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	2.050	0.16	1.55	13	-
CLIMB OUT	85	2.2	1.700	0.13	1.9	9.4	-
APPROACH	30	4.0	0.600	0.3	5.9	3.9	_
IDLE	7	26.0	0.235	4.6	29.8	2.3	_
LTO TOTAL FUEL (kg) or EMISSIONS (g) 821		1773	12334	4633	-		
NUMBER OF ENGINES			5	5	4	7	
NUMBER OF TESTS			7	7	4	10	
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)			13.5	94.6	35.5	9.9	
SIGMA $(D_p/F_{oo} \text{ in } g/kN, \text{ or } SN)$		3.7	22.5	2.3	2.9		
RANGE $(D_p/F_{oo} \text{ in } g/kN, \text{ or } SN)$			8.7-17.1	61.3-113	32-40.1	42522	

ACCESSORY LOADS

POWER EXTRACTION 0 (kW) AΤ POWER SETTINGS STAGE BLEED % CORE FLOW POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	101.2-102.4
TEMPERATURE (K)	260 - 298
ABS HUMIDITY (kg/kg)	.000790200

-		-	_
- 1	'U	H)	П
-	_	_	=

SPEC	TS-1
H/C	2
AROM (%)	18.6

MANUFACTURER: KKBM TEST ORGANIZATION: KKBM

TEST LOCATION: Samara City

FROM 18 Jul 87 TO 20 Jan 90 TEST DATES:

REMARKS

1. NK-86A with modified combustor.

2. For IL-86 aircraft.

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

('x' if complies, PR if pre-regulation)