

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: CF6-80A3 BYPASS RATIO: 5 UNIQUE ID NUMBER: 1GE013 PRESSURE RATIO (π_{oo}) : 30.1 ENGINE TYPE: TF RATED OUTPUT (F_{oo}) (kN): 217.8

REGULATORY DATA

CHARACTERISTIC VALUE:	НС	CO	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	11.6	41.7	64.0	15.6
AS % OF ORIGINAL LIMIT	59.2 %	35.3 %	63.9 %	81.6 %
AS % OF CAEP/2 LIMIT (NOx)			79.8 %	
AS % OF CAEP/4 LIMIT (NOx)			95.2 %	
AS % OF CAEP/6 LIMIT (NOx)			108.2 %	
AS % OF CAEP/8 LIMIT (NOx)			127.2 %	

DATA STATUS

x PRE-REGULATION

- CERTIFICATION

- REVISED (SEE REMARKS)

TEST ENGINE STATUS x NEWLY MAN

x NEWLY MANUFACTURED ENGINES

- DEDICATED ENGINES TO PRODUCTION STANDARD

- OTHER (SEE REMARKS)

EMISSIONS STATUS

x DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

x OUT OF PRODUCTION (DATE: -)

- OUT OF SERVICE

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	2.254	0.3	1	29.6	12
CLIMB OUT	85	2.2	1.885	0.37	1.1	26.6	10
APPROACH	30	4.0	0.641	0.45	2.8	10.8	2
IDLE	7	26.0	0.150	6.28	28.2	3.4	2
LTO TOTAL FUEL (kg) or EMISSIONS (g) 731			1659	7398	11878	-	
NUMBER OF ENGINES			1	1	1	1	
NUMBER OF TESTS			3	3	3	1	
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)			7.53	34	55.2	12	
SIGMA (D_p/F_{oo} in g/kN , or SN)			0.96	0.4	2.9	_	
RANGE (D _p /F _{oo} in g/kN, or SN)			6.87-8.64	33.6-34.3	52.1-57.7	-	

ACCESSORY LOADS

POWER EXTRACTION 0 (kW) AT - POWER SETTINGS STAGE BLEED 0 % CORE FLOW AT - POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	99.08-99.78
TEMPERATURE (K)	275 - 277
ABS HUMIDITY (kg/kg)	0.002

FUEL

SPEC	Jet A
H/C	1.93
AROM (%)	17.1

MANUFACTURER: GE Aircraft Engines
TEST ORGANIZATION: Production Engine Test
TEST LOCATION: Production Test Cells M35

TEST DATES: FROM 11 Nov 83 TO 12 Nov 83

REMARKS

1. Ref GE Report no R83AEB635.

2. Engine S/N 580214.

3. Smoke from Engine S/N 580005, report R81AEG513.

4. With approval of US FAA, idle power data were only acquired at the engine design setting of 3.69%.

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

0 ('x' if complies, PR if pre-regulation)