

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: BYPASS RATIO: 4.7 PW4x60 PRESSURE RATIO $(\pi_{\circ\circ})$: 30.68 UNIQUE ID NUMBER: 1 PW057 ENGINE TYPE: TF RATED OUTPUT (Foo) (kN): 266.9

REGULATORY DATA

CHARACTERISTIC VALUE:	НС	СО	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	7.7	42.6	63.1	12.4
AS % OF ORIGINAL LIMIT	39.3 %	36.1 %	62.2 %	68.3 %
AS % OF CAEP/2 LIMIT (NOx)			77.8 %	
AS % OF CAEP/4 LIMIT (NOx)			92.2 %	
AS % OF CAEP/6 LIMIT (NOx)			104.5 %	
AS % OF CAEP/8 LIMIT (NOx)			122.6 %	

DATA STATUS

PRE-REGIILATION

CERTIFICATION

REVISED (SEE REMARKS)

TEST ENGINE STATUS

NEWLY MANUFACTURED ENGINES

DEDICATED ENGINES TO PRODUCTION STANDARD

OTHER (SEE REMARKS)

EMISSIONS STATUS

DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

OUT OF PRODUCTION OUT OF SERVICE

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	2.623	0.08	0.4	34.89	9.6
CLIMB OUT	85	2.2	2.075	0.08	0.52	26.34	6.8
APPROACH	30	4.0	0.686	0.15	1.74	12.53	0.7
IDLE	7	26.0	0.218	3.73	25.83	4.07	0
LTO TOTAL FUEL (kg) or EMISSIONS (g) 889			1324	9257	14505	-	
NUMBER OF ENGINES				1	1	1	1
NUMBER OF TESTS				3	3	3	3
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)			5	34.7	54.4	9.6	
SIGMA $(D_p/F_{oo} \text{ in } g/kN, \text{ or } SN)$			1	_	1	-	
RANGE $(D_p/F_{oo} \text{ in g/kN, or SN})$			-	-	-	-	

ACCESSORY LOADS

POWER EXTRACTION 0 (kW) ΑT POWER SETTINGS STAGE BLEED % CORE FLOW POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	102
TEMPERATURE (K)	270
ABS HUMIDITY (kg/kg)	0.0015

FUEL

SPEC	Jet A
H/C	1.91
AROM (%)	21

MANUFACTURER: Pratt & Whitney TEST ORGANIZATION: Pratt & Whitney TEST LOCATION: Middletown, CT

FROM 15 Jan 93 TEST DATES: TO 19 Jan 93

REMARKS

1. Data from ${\tt X693-20}$ with Phase 3 reduced pressure loss combustor

2. Certification in accordance with Part III, Chapter 2, of Amendment 7 of ICAO Annex 16 Vol. II.

3. NOx levels in accordance with Part III, Chapter 2, 2.3.2 d) (CAEP/6)

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

('x' if complies, PR if pre-regulation)