

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: LEAP-1B21 BYPASS RATIO: 8.5 PRESSURE RATIO $(\pi_{\circ\circ})$: UNIQUE ID NUMBER: 20CM094 36.8 ENGINE TYPE: TF RATED OUTPUT (Foo) (kN): 111.3

REGULATORY DATA

CHARACTERISTIC VALUE:		СО	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	1.5	26.0	42.2	1.5
AS % OF ORIGINAL LIMIT	7.5 %	22.0 %	37.2 %	6.5 %
AS % OF CAEP/2 LIMIT (NOx)			46.4 %	
AS % OF CAEP/4 LIMIT (NOx)			52.4 %	
AS % OF CAEP/6 LIMIT (NOx)			58.2 %	
AS % OF CAEP/8 LIMIT (NOx)			66.2 %	

DATA STATUS

PRE-REGIILATION

CERTIFICATION

REVISED (SEE REMARKS)

TEST ENGINE STATUS

NEWLY MANUFACTURED ENGINES ×

DEDICATED ENGINES TO PRODUCTION STANDARD

OTHER (SEE REMARKS)

EMISSIONS STATUS

DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

OUT OF PRODUCTION OUT OF SERVICE

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	0.877	0.04	0.15	30.39	0.94
CLIMB OUT	85	2.2	0.722	0.04	0.16	17.53	0.85
APPROACH	30	4.0	0.245	0.05	1.49	10.26	1.07
IDLE	7	26.0	0.089	0.71	16.19	4.74	0.8
LTO TOTAL FUEL (kg) or EMISSIONS (g) 330			106	2358	4053	-	
NUMBER OF ENGINES			1	1	1	1	
NUMBER OF TESTS			3	3	3	3	
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)			0.96	21.19	36.42	1.16	
SIGMA (D_p/F_{oo} in g/kN , or SN)			0.09	0.77	1.38	0.29	
RANGE $(D_p/F_{00} \text{ in } g/kN, \text{ or } SN)$ 0.			0.66 to 0.8	16.97 to 18.38	56.39 to 59.15	0.34 to 0.90	

ACCESSORY LOADS

POWER EXTRACTION 0 (kW) ALL POWER SETTINGS % CORE FLOW ALL POWER SETTINGS STAGE BLEED

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	97.7 to 98.8
TEMPERATURE (K)	279.3 to 290.5
ABS HUMIDITY (kg/kg)	.0009 to .0084

Ę.	U	Ł	ь	

SPEC	JET A	
H/C	1.9	
AROM (%)	14.7	

MANUFACTURER: GE Aviation GE Aviation TEST ORGANIZATION: TEST LOCATION: PTO, Ohio, USA

FROM 08 Mar 16 TEST DATES: TO 09 Mar 16

REMARKS

1. Ref. GE REPORT R2013AE589 and CRL-0109b_7 Vol. 1/Rev. 0

2. Engine S/N 602-109/1

3. SN for each LTO mode is average of max SN for test points around that power setting

4. AVERAGE SN (MAX) is average of maximum SN measured from all points on each run

5. Certification in accordance with Part III, Chapter 2, of Amendment 8 of ICAO Annex 16 Vol. II.

6. NOx levels in accordance with Part III, Chapter 2, 2.3.2 e) (CAEP/8)

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

x ('x' if complies, PR if pre-regulation)