

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: LEAP-1B28BBJ2 BYPASS RATIO: 8.3 PRESSURE RATIO $(\pi_{\circ\circ})$: UNIQUE ID NUMBER: 20CM097 40.5 ENGINE TYPE: TF RATED OUTPUT (Foo) (kN): 124.7

REGULATORY DATA

CHARACTERISTIC VALUE:	НС	СО	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	1.1	21.9	58.8	1.5
AS % OF ORIGINAL LIMIT	5.4 %	18.5 %	48.6 %	6.7 %
AS % OF CAEP/2 LIMIT (NOx)			60.7 %	
AS % OF CAEP/4 LIMIT (NOx)			66.8 %	
AS % OF CAEP/6 LIMIT (NOx)			73.5 %	
AS % OF CAEP/8 LIMIT (NOx)			82.7 %	

DATA STATUS

PRE-REGULATION

CERTIFICATION

REVISED (SEE REMARKS)

TEST ENGINE STATUS

NEWLY MANUFACTURED ENGINES ×

DEDICATED ENGINES TO PRODUCTION STANDARD

OTHER (SEE REMARKS)

EMISSIONS STATUS

DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

OUT OF PRODUCTION OUT OF SERVICE

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	1.014	0.05	0.17	55.26	0.94
CLIMB OUT	85	2.2	0.826	0.04	0.14	23.26	0.85
APPROACH	30	4.0	0.273	0.05	1.11	11.59	1.07
IDLE	7	26.0	0.095	0.51	14.4	4.59	0.8
LTO TOTAL FUE:	L (kg) or EMIS	SIONS (g)	365	85	2221	6326	-
NUMBER OF ENG	INES			1	1	1	1
NUMBER OF TESTS			3	3	3	3	
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)			0.68	17.81	50.72	1.16	
SIGMA $(D_p/F_{oo}$ in g/kN, or SN)				0.09	0.77	1.38	0.29
RANGE $(D_p/F_{00} \text{ in } g/kN, \text{ or } SN)$ 0.			0.66 to 0.8	16.97 to 18.38	56.39 to 59.15	0.34 to 0.90	

ACCESSORY LOADS

(kW) % CORE FLOW POWER EXTRACTION 0 AΤ ALL POWER SETTINGS ALL POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	97.7 to 98.8
TEMPERATURE (K)	279.3 to 290.5
ABS HUMIDITY (kg/kg)	.0009 to .0084

TO	TITLE
£	UEL

SPEC	JET A
H/C	1.9
AROM (%)	14.7

MANUFACTURER: GE Aviation TEST ORGANIZATION: GE Aviation TEST LOCATION: PTO, Ohio, USA

FROM 08 Mar 16 TEST DATES: TO 09 Mar 16

REMARKS

1. Ref. GE REPORT R2013AE589 and CRL-0109b_7 Vol. 1/Rev. 0

2. Engine S/N 602-109/1

3. SN for each LTO mode is average of max SN for test points around that power setting

4. AVERAGE SN (MAX) is average of maximum SN measured from all points on each run

5. Certification in accordance with Part III, Chapter 2, of Amendment 8 of ICAO Annex 16 Vol. II.

6. NOx levels in accordance with Part III, Chapter 2, 2.3.2 e) (CAEP/8)

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

x ('x' if complies, PR if pre-regulation)