

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: AE3007A1/1 BYPASS RATIO: 4.77 PRESSURE RATIO $(\pi_{\circ\circ})$: 17.9 UNIQUE ID NUMBER: 6AT-010 ENGINE TYPE: MTF RATED OUTPUT (Foo) (kN): 34.74

REGULATORY DATA

CHARACTERISTIC VALUE:	НС	СО	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	12.4	109.1	44.5	0.0
AS % OF ORIGINAL LIMIT	63.5 %	92.5 %	58.7 %	0.0 %
AS % OF CAEP/2 LIMIT (NOx)			73.4 %	
AS % OF CAEP/4 LIMIT (NOx)			75.4 %	
AS % OF CAEP/6 LIMIT (NOx)			76.4 %	
AS % OF CAEP/8 LIMIT (NOx)			81.7 %	

DATA STATUS

PRE-REGULATION

CERTIFICATION

REVISED (SEE REMARKS)

TEST ENGINE STATUS

NEWLY MANUFACTURED ENGINES

DEDICATED ENGINES TO PRODUCTION STANDARD

OTHER (SEE REMARKS)

EMISSIONS STATUS

DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

OUT OF PRODUCTION OUT OF SERVICE

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	0.381	0.03	0.74	16.1	0.01
CLIMB OUT	85	2.2	0.316	0.03	0.55	14.01	0.01
APPROACH	30	4.0	0.113	0.03	6.8	7.12	0.01
IDLE	7	26.0	0.046	3.88	40.07	4.17	0.01
LTO TOTAL FUE	L (kg) or EMIS	SIONS (g)	156	280	3088	1333	_
NUMBER OF ENG	INES			1	1	1	1
NUMBER OF TES	TS			3	3	3	3
AVERAGE D _p /F _{oo}	(g/kN) or AVE	RAGE SN (MAX)		8.08	88.9	38.38	0.01
SIGMA (Dp/Foo	in g/kN, or SN)		_	-	-	_
RANGE (Dp/Foo	in g/kN, or SN)		-	-	-	-

ACCESSORY LOADS

(kW) POWER EXTRACTION 0 AΤ POWER SETTINGS % CORE FLOW STAGE BLEED POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	98.9 - 99.0
TEMPERATURE (K)	291 - 301
ABS HUMIDITY (kg/kg)	0.009 - 0.012

Ľί	JĿ	ш

SPEC	Jet A	
H/C	1.9	
AROM (%)	16 - 20	

MANUFACTURER: Rolls-Royce Corporation TEST ORGANIZATION: Rolls-Royce Corporation TEST LOCATION: Indianapolis, Indiana, USA

FROM 09 Jun 01 TEST DATES: TO 11 Jun 01

REMARKS

1. For effectivity see Rolls-Royce Notice to Operators No. AE3007A-076

2. Data in this form for AE3007A1/1 engine fitted with reduced emissions combustor & PAB fuel nozzles

3. Results based on Rolls-Royce report EDR 19587

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

('x' if complies, PR if pre-regulation)