

ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

ENGINE IDENTIFICATION: V2524-A5 SelectOne™ Upgrade BYPASS RATIO: PRESSURE RATIO $(\pi_{\circ\circ})$: UNIQUE ID NUMBER: 10IA012 2.7 ENGINE TYPE: MTF RATED OUTPUT (Foo) (kN): 108.9

REGULATORY DATA

CHARACTERISTIC VALUE:	НС	СО	NOx	SMOKE NUMBER
D_p/F_{oo} (g/kN) or SN	0.5	28.7	50.9	11.1
AS % OF ORIGINAL LIMIT	2.4 %	24.4 %	54.2 %	47.8 %
AS % OF CAEP/2 LIMIT (NOx)			67.7 %	
AS % OF CAEP/4 LIMIT (NOx)			81.8 %	
AS % OF CAEP/6 LIMIT (NOx)			93.0 %	
AS % OF CAEP/8 LIMIT (NOx)			110.9 %	

DATA STATUS

PRE-REGIILATION

CERTIFICATION

REVISED (SEE REMARKS)

TEST ENGINE STATUS

NEWLY MANUFACTURED ENGINES x

DEDICATED ENGINES TO PRODUCTION STANDARD

OTHER (SEE REMARKS)

EMISSIONS STATUS

DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

OUT OF PRODUCTION OUT OF SERVICE

MEASURED DATA

	POWER	TIME	FUEL FLOW	EMI	SSIONS INDICES	(g/kg)	
MODE	SETTING	minutes	kg/s	HC	CO	NOx	SMOKE NUMBER
	(%F ₀₀)						
TAKE-OFF	100	0.7	1.040	0.03	0.42	22.96	7
CLIMB OUT	85	2.2	0.867	0.04	0.44	19.25	7.8
APPROACH	30	4.0	0.326	0.07	2.28	9.69	3.7
IDLE	7	26.0	0.133	0.14	12.03	5.18	1.7
LTO TOTAL FUEL (kg) or EMISSIONS (g) 444		39	2747	5039	-		
NUMBER OF ENGINES			2	2	2	2	
NUMBER OF TESTS			4	4	4	4	
AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX)			0.4	25.2	46.3	9.4	
SIGMA $(D_p/F_{oo} \text{ in } g/kN, \text{ or } SN)$			1	1	1	-	
RANGE (D _p /F _{oo} in g/kN, or SN)			-	-	=	_	

ACCESSORY LOADS

POWER EXTRACTION 0 (kW) AT POWER SETTINGS STAGE BLEED % CORE FLOW POWER SETTINGS

ATMOSPHERIC CONDITIONS

BAROMETER (kPa)	100.35-102.88		
TEMPERATURE (K)	268.2-277.7		
ABS HUMIDITY (kg/kg)	0.00140-0.00359		

Ę.	U	Ł	ь	

SPEC	JET A
H/C	1.91
AROM (%)	17

MANUFACTURER: IAE International Aero Engines

TEST ORGANIZATION: Pratt & Whitney TEST LOCATION: East Hartford, CT

FROM 11 Dec 08 TEST DATES: TO 19 Jan 09

REMARKS

1. Engine performance reflects new SelectOne $^{\text{\tiny{TM}}}$ package upgrades.

2.Certification in accordance with Part III, Chapter 2, of Amendment 6 of ICAO Annex 16 Vol. II.

3. NOx levels in accordance with Part III, Chapter 2, 2.3.2 d) (CAEP/6)

If REVISED, this data supersedes databank UID Compliance with fuel venting requirements:

x ('x' if complies, PR if pre-regulation)