



Kotlin
КОТЛИН

wizeline.com | ademar.oliveira@wizeline.com

WIZELINE®



Contents

1. Introduction
2. How to start
3. Basics
 - a. Package & Import
 - b. Comments
 - c. Variables
 - d. Null Safety
 - e. Strings
 - f. Control Flow
 - i. If - Else
 - ii. For
 - iii. When
 - iv. While
 - g. Function
4. OOP
 - a. Classes
 - b. Constructor
 - c. Properties
 - d. Methods
 - e. Inheritance
 - f. Interfaces
 - g. Data Classes



Introduction



Introduction

- **Open Source (Apache 2)**
- **Started 2011; Version 1.0 2016; Currently 1.1.3-2**
- **Static; Inferred; Script; Functional; OOP**
- **Platform: JVM; JS; LLVM**
- **Concise; Safe; Interoperable; Tool-friendly**
- **Official Android Language**



How to start



How to start

- **Android Studio 2 Go to:**
 - Preferences
 - Plugins
 - Click on Install JetBrains plugin
 - Install Kotlin Language
 - Restart
- **Android Studio 3 ready out of the box.**



How to start



build.gradle

```
buildscript {  
    repositories { jcenter() }  
    dependencies {  
        classpath "com.android.tools.build:gradle:2.3.3"  
        classpath "org.jetbrains.kotlin:kotlin-gradle-plugin:x.y.z"  
    }  
}
```



How to start



app/build.gradle

```
apply plugin: "com.android.application"
apply plugin: "kotlin-android"

// If you're using annotation processor
apply plugin: "kotlin-kapt"

// A pro tip
apply plugin: "kotlin-android-extensions"
```




How to start



app/build.gradle

```
dependencies {  
  
    // Change any annotationProcessor or apt to kapt  
  
    compile "org.jetbrains.kotlin:kotlin-stdlib:x.y.z"  
  
}
```



You are ready!!!



Basics



Basics

Package & Import



Package & Import



Sample.kt

```
package com.wizeline.academy

import java.io.File
import java.util.*
import android.view.View.GONE
import android.support.v4.content.ContextCompat.getColor
import android.support.v7.app.AppCompatActivity as Activity
```




Basics

Comments



Package & Import



Sample.kt

```
// This is an end-of-line comment
```

```
/* This is a block comment  
   on multiple lines. */
```

```
/* This is /* a nested comment  
   on multiple */ lines. */
```



Basics

Variables



Val value :
immutable reference

Var variable :
mutable reference





Variables



Sample.kt

```
val message: String = "Hello World!"
```



Variables



Sample.kt

```
val message: String = "Hello World!"  
message = "Bye World!"
```



Variables



Sample.kt

```
val message: String = "Hello World!"  
message = "Bye World!" // Compile time error, value cannot be assigned
```




Variables



Sample.kt

```
var message: String = "Hello World!"
```



Variables



Sample.kt

```
var message: String = "Hello World!"  
message = "Bye World!"
```



Variables



Sample.kt

```
var message: String = "Hello World!"  
message = "Bye World!" // It is ok
```



Variables



Sample.kt

```
val message: String = "Hello World!"
```



Variables



Sample.kt

```
val message = "Hello World!"
```



Basics

Null Safety



Null Safety



Sample.kt

```
var message: String = "Hello World!"
```



Null Safety



Sample.kt

```
var message: String = "Hello World!"  
message = null
```



Null Safety



Sample.kt

```
var message: String = "Hello World!"  
message = null // Error: null can not be a value of a non-null type
```



Null Safety



Sample.kt

```
var message: String? = "Hello World!"
```



Null Safety



Sample.kt

```
var message: String? = "Hello World!"  
message = null
```



Null Safety



Sample.kt

```
var message: String? = "Hello World!"  
message = null // It is ok
```




Null Safety



Sample.kt

```
var message: String? = null
```



Null Safety



Sample.kt

```
var message: String? = null  
message.length
```



Null Safety



Sample.kt

```
var message: String? = null  
message.length // Error: Only safe or non-null asserted calls are  
                allowed on a nullable receiver of type String?
```



Null Safety



Sample.kt

```
var message: String? = null  
message?.length
```



Null Safety



Sample.kt

```
var message: String? = null  
message?.length // It is ok
```



Null Safety



Sample.kt

```
var message: String? = null  
message!!.length
```



Null Safety



Sample.kt

```
var message: String? = null  
message!!.length // Possible but don't do it unless you know what you're doing
```



Null Safety



Sample.kt

```
var message: String? = null
if (message != null) {
    message.length // It is ok. Spoiler: if syntax
}
```




Basics

Strings



Strings



Sample.kt

```
val message = "Hello World!"
```



Strings



Sample.kt

```
val message = """  
    Hello  
    World!  
    """
```



Strings



Sample.kt

```
val message = """  
|Hello  
|  World!  
|"""  
    .trimMargin()
```



Strings



Sample.kt

```
val message = "Hello World!"  
println("$message length is: ${message.length}")
```



Basics

Control Flow



Basics

Control Flow

IF - ELSE



Control Flow - If else



Sample.kt

```
val a = random()
val b = random()
if (a > b) {
    println("A is greater than b.")
} else if (a == b) {
    println("A is equal to b.")
} else {
    println("A is less than b.")
}
```




Basics
Control Flow
For



Control Flow - For



Sample.kt

```
val message = "Hello World!"  
for (character in message) {  
    println(character)  
}  
// Prints each letter
```



Control Flow - For



Sample.kt

```
for (number in 0..10) {  
    println(number)  
}  
// Prints 0, 1, ..., 10
```



Control Flow - For



Sample.kt

```
for (number in 0 until 10) {  
    println(number)  
}  
// Prints 0, 1, ..., 9
```



Control Flow - For



Sample.kt

```
for (number in 0..10 step 3) {  
    println(number)  
}  
// Prints 0, 3, 6, 9
```



Control Flow - For



Sample.kt

```
for (number in 10 downTo 0) {  
    println(number)  
}  
// Prints 10, 9, ..., 0
```



Control Flow - For



Sample.kt

```
val array: Array<String> = arrayOf<String>("Hello", "World!")  
// Spoiler: How to create an array
```



Control Flow - For



Sample.kt

```
val array = arrayOf("Hello", "World!")  
// Spoiler: How to create an array
```




Control Flow - For



Sample.kt

```
val array = arrayOf("Hello", "World!")  
for (item in array) {  
    println(item)  
}  
// Prints Hello and World!
```



Control Flow - For



Sample.kt

```
val array = arrayOf("Hello", "World!")  
for ((index, item) in array.withIndex()) {  
    println("$index $item")  
}  
// Prints 0 Hello and 1 World!
```



Basics
Control Flow
When



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when (clumpsOfSugar) {
    0 -> println("The right way to drink coffee")
    1 -> println("It is a sin, but I can ignore")
    else -> {
        println("Wait, $clumpsOfSugar clumps of sugar!?!")
        println("It is an unforgivable sin!!!")
    }
}
```



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when (clumpsOfSugar) {
    0 -> println("The right way to drink coffee")
    1, 2 -> println("It is a sin, but I can ignore")
    else -> {
        println("Wait, $clumpsOfSugar clumps of sugar!?!")
        println("It is an unforgivable sin!!!")
    }
}
```



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when (clumpsOfSugar) {
    0 -> println("The right way to drink coffee")
    1, 2 -> println("It is a sin, but I can ignore")
    in 3..5 -> println("Is it a kind of candy??")
    else -> {
        println("Wait, $clumpsOfSugar clumps of sugar!?!")
        println("It is an unforgivable sin!!!")
    }
}
```



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when (clumpsOfSugar) {
    0 -> println("The right way to drink coffee")
    1, 2 -> println("It is a sin, but I can ignore")
    !in 3..5 -> println("It is not 3, 4 or 5 :)")
    else -> {
        println("Wait, $clumpsOfSugar clumps of sugar!?!")
        println("It is an unforgivable sin!!!")
    }
}
```



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
val candyNumbers = arrayOf(3, 4, 5)
when (clumpsOfSugar) {
    0 -> println("The right way to drink coffee")
    1, 2 -> println("It is a sin, but I can ignore")
    in candyNumbers -> println("Is it a kind of candy??")
    else -> {
        println("Wait, $clumpsOfSugar clumps of sugar!?!")
        println("It is an unforgivable sin!!!")
    }
}
```




Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when (clumpsOfSugar) {
    0 -> println("The right way to drink coffee")
    1, 2 -> println("It is a sin, but I can ignore")
    randomInt() -> println("Are we still talking about coffee?")
    else -> {
        println("Wait, $clumpsOfSugar clumps of sugar!?!")
        println("It is an unforgivable sin!!!")
    }
}
```



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when {
    clumpsOfSugar % 2 == 1 -> println("An odd amount of sugar clumps")
    clumpsOfSugar % 2 == 0 -> println("An even amount of sugar clumps")
    else -> println("We have a really strange amount of sugar clumps")
}
```



Control Flow - When



Sample.kt

```
val clumpsOfSugar = 0
when {
    clumpsOfSugar.isOdd() -> println("An odd amount of sugar clumps")
    clumpsOfSugar.isEven() -> println("An even amount of sugar clumps")
    else -> println("We have a really strange amount of sugar clumps")
}
```



Basics
Control Flow
While





Control Flow - While



Sample.kt

```
var clumpsOfSugar = 10
while (clumpsOfSugar > 0) {
    clumpsOfSugar-- // yes we have -- and ++ syntax
}
println(clumpsOfSugar) // Prints 0
```



Control Flow - While



Sample.kt

```
var clumpsOfSugar = 10
do {
    clumpsOfSugar--
} while (clumpsOfSugar > 0)
println(clumpsOfSugar) // Prints 0
```



Basics

Function



Function



Sample.kt

```
fun sayHelloWorld() {  
    println("Hello World")  
}
```




Function



Sample.kt

```
fun sayHelloWorld() = println("Hello World")
```



Function



Sample.kt

```
fun say(message: String) {  
    println(message)  
}
```



Function



Sample.kt

```
fun say(message: String = "Hello World") {  
    println(message)  
}
```



Function



Sample.kt

```
fun sum(a: Int, b: Int): Int {  
    return a + b  
}
```



Function



Sample.kt

```
fun sum(a: Int, b: Int): Int = a + b
```



Function



Sample.kt

```
fun sum(a: Int, b: Int) = a + b
```



Function



Sample.kt

```
fun makeCoffee(ml: Int, concentration: Float, useSugar: Boolean = false)
```

```
makeCoffee(200, 0.8f)
```

```
makeCoffee(200, 0.8f, true)
```

```
makeCoffee(200, 0.8f, useSugar = true)
```

```
makeCoffee(ml = 200, concentration = 0.8f, useSugar = true)
```

```
makeCoffee(useSugar = true, ml = 200, concentration = 0.8f)
```



Function



Sample.kt

```
fun outside() {  
    fun inside() {  
        // Do something  
    }  
    // ...  
    inside() // we can call in this scope  
    // ...  
}
```




OOP



OOP

Classes



Classes



Coffee.kt

```
class Coffee {  
  
}
```



Classes



Coffee.kt

```
class Coffee
```



Classes



Coffee.kt

```
class Coffee
```

```
val coffee = Coffee()
```



OOP

Constructor





Constructor



Coffee.kt

```
class Coffee(type: String)
```



Constructor



Coffee.kt

```
class Coffee @Inject constructor(type: String)
```




Constructor



CustomView.kt

```
class CustomView : View { // Spoiler: Inheritance

    constructor(c: Context) : super(c) {}
    constructor(c: Context, a: AttributeSet?) : super(c, a) {}
    constructor(c: Context, a: AttributeSet?, d: Int) : super(c, a, d) {}
    constructor(c: Context, a: AttributeSet?, d: Int, r: Int) : super(c, a, d, r) {}

}
```



Constructor



Coffee.kt

```
class Coffee(type: String)
class Coffee(var type: String)
class Coffee(val type: String)
class Coffee(private val type: String)
class Coffee(private val type: String = "Espresso")
```



Constructor



Coffee.kt

```
class Coffee(type: String) {  
    private val name = "Coffee $type"  
}
```



Constructor



Coffee.kt

```
class Coffee(type: String) {  
  
    private val name: String  
  
    init {  
        name = "Coffee $type"  
    }  
  
}
```



Constructor



Coffee.kt

```
class Coffee {  
  
    private val name: String  
  
    constructor(type: String) {  
        name = "Coffee $type"  
    }  
  
}
```



Constructor



Coffee.kt

```
class Coffee(val type: String) {  
}
```



OOP

Properties





Properties



Coffee.kt

```
class Coffee {  
  
    val type = "Espresso"  
    var drunked = false  
    private val gourmet = true  
  
}
```




Properties



Coffee.kt

```
class Coffee {  
  
    var type = "Espresso"  
        get() {  
            return field  
        }  
        set(value) {  
            field = value  
        }  
  
}
```



Properties



Coffee.kt

```
class Coffee(context: Context) {  
  
    private val preferences = context.getSharedPreferences("Coffee", MODE_PRIVATE)  
  
    var type  
        get() = preferences.getString("TypeKey", "Default")  
        set(value) {  
            preferences.edit().putString("TypeKey", value).apply()  
        }  
  
}
```



Properties



Coffee.kt

```
class Coffee {  
  
    var type = "Espresso"  
    private set  
  
}
```



Properties



Coffee.kt

```
class Coffee {  
    @JsonField lateinit var type: String  
}
```



Properties



Coffee.kt

```
class Coffee {  
  
    val type: String by lazy {  
        println("You are running this code!")  
        "Hello"  
    }  
  
    val x = type // It prints "You are running this code!" 1 time  
    val y = type // It don't prints anything  
  
}
```



OOP

Methods



Kotlin methods are functions,
and you already know it.



OOP

Inheritance



Inheritance



Coffee.kt

```
open class Coffee
```

```
class Cappuccino : Coffee()
```



Inheritance



Coffee.kt

```
open class Coffee(type: String)

class Cappuccino : Coffee("Cappuccino")
```



Inheritance



Coffee.kt

```
open class Coffee(type: String)

class Cappuccino(type: String) : Coffee(type)
```



Inheritance



Coffee.kt

```
open class Coffee {  
    constructor(type: String)  
    constructor(type: String, temperature: Float)  
}  
  
class Cappuccino : Coffee {  
    constructor(type: String) : super(type)  
    constructor(type: String, temperature: Float) : super(type, temperature)  
}
```



Inheritance



Coffee.kt

```
open class Coffee {  
    open fun drink() {  
        println("So tasty")  
    }  
}  
  
class Cappuccino : Coffee() {  
    override fun drink() {  
        super.drink()  
    }  
}
```



OOP

Interfaces



Interfaces



Coffee.kt

```
interface Drinkable
```

```
class Coffee : Drinkable
```



Interfaces



Coffee.kt

```
interface Drinkable {  
    fun drink()  
}  
  
class Coffee : Drinkable {  
    override fun drink() {  
        println("So tasty")  
    }  
}
```




Interfaces



Coffee.kt

```
interface Drinkable {  
    fun drink() {  
        println("So tasty")  
    }  
}  
  
class Coffee : Drinkable
```



Interfaces



Coffee.kt

```
interface Drinkable {  
    val type: String  
}  
  
class Coffee : Drinkable {  
    override val type = "Coffee"  
}
```



Interfaces



Coffee.kt

```
open class Coffee

interface Drinkable {
    fun drink()
}

class Cappuccino : Coffee(), Drinkable {
    override fun drink() {
        println("So tasty")
    }
}
```



Interfaces



Coffee.kt

```
open class Coffee {  
    open fun drink() = println("So coffee")  
}  
  
interface Drinkable {  
    fun drink() = println("So tasty")  
}  
  
class Cappuccino : Coffee(), Drinkable {  
  
    // What happens here ?  
  
}
```



Interfaces



Coffee.kt

```
open class Coffee {  
    open fun drink() = println("So coffee")  
}  
  
interface Drinkable {  
    fun drink() = println("So tasty")  
}  
  
class Cappuccino : Coffee(), Drinkable {  
    override fun drink() {  
        super<Coffee>.drink()  
        super<Drinkable>.drink()  
    }  
}
```



OOP

Data Classes



Data Classes



Coffee.kt

```
data class Coffee(val type: String)
```



Data Classes - Equals & hashCode



Coffee.kt

```
data class Coffee(val type: String)
```

```
val a = Coffee("Cappuccino")
```

```
val b = Coffee("Cappuccino")
```

```
println(a == b) // Prints true
```




Data Classes - Equals & hashCode



Coffee.kt

```
data class Coffee(val type: String)
```

```
val a = Coffee("Cappuccino")
```

```
val b = Coffee("Ristretto")
```

```
println(a == b) // Prints false
```



Data Classes - toString()



Coffee.kt

```
data class Coffee(val type: String)

val a = Coffee("Cappuccino")

println(a.toString()) // Prints: Coffee(type=Cappuccino)
```



Data Classes - copy



Coffee.kt

```
data class Coffee(val type: String)
```

```
val a = Coffee("Cappuccino")
```

```
val b = a.copy()
```



Data Classes - copy



Coffee.kt

```
data class Coffee(val type: String)
```

```
val a = Coffee("Cappuccino")
```

```
val b = a.copy()
```

```
val c = a.copy(type = "Ristretto")
```

Now this is not the end. It is not even the beginning of the end. But it is, perhaps, the end of the beginning.





THANK YOU

WIZELINE[®]

ademar.oliveira@wizeline.com

