

The efficient toolbox of the Computational Scientist



Dr. Gábor Závodszy - *Computational Science Lab*

https://github.com/gzavo/CS_Assignment


"Never do a live demo" -- Every presenter ever


Structure of the lecture

- Domains of "The Computational Scientist"
 - Scientific writing and reading
 - Programming and visualization basics
 - Software development in a collaborative environment
 - Homework assignment
-
- Can be an information overload!
 - These slides contain the very basics.
 - Due to the structure of this MSc programme, you might not need *everything*.


- The most important things are marked: (!).
- Some things are there to hear at least once.
- You can use the pdf version as a list of useful tools.

Who is the Computational Scientist? - Domains and fundamental skills





General workflow of the Computational Scientist



CLS Activities - Reading

- UvA Library (!) (<http://uba.uva.nl/en>)
- You can also use it to get access to non-open access journal papers.
- Google Scholar (!) - <https://scholar.google.com>
 - Search for papers
 - export references
 - look at researcher profiles
 - E.g.: "Carbon monoxide, boldly goes where..."
- Web of Science, Scopus, ...
- Managing references: Mendeley, **Zotero** (!), Papers, etc.
 - Sync. paper database
 - Annotate pdfs, add notes and sync them as well
- Most students use Zotero (I use it as well).
- Mendeley gives more cloud space, but its less flexible.

CLS Activities - Writing


- LaTeX
 - Overleaf (!) - <https://www.overleaf.com/>
 - TexMaker
 - TeXmacs
 - latex2png - <http://latex2png.com/>
- Typist (modern LaTeX alternative written in Rust) <https://typst.app/>

-> Why is LaTeX useful?

- Not a WYSIWYG solution
- But often WYGIWYN
- Abundance of templates
- Literally a programming language for word processing

In []:

Remember...



Collaborative writing



- Markdown (!)
 - Use Pandoc (!) to turn it to .doc, .pdf, .html, you name it (<https://pandoc.org/>)
 - Zettlr (!) (<https://www.zettlr.com/>)
 - Typora (<https://typora.io/>)
 - Mark Text (<https://github.com/marktext/marktext>)
 - Basically everywhere (websites, forums, editors...really, everywhere)
 - Other supersets / alternatives (ASCIIDOC, ...)

Markdown

Write equations: $e^{i\pi} + 1 = 0$

Embed code:

```
def f(x):
    """docstring of this very useful function"""
    return x**2
```

Add tables:

This	is
a	table

Create lists:

- list item 1
- list item 2
- list item 3

Markdown syntax

Markdown is a simple way to format text that looks great on any device. It doesn't do anything fancy like change the font size, color, or type – just the essentials, using keyboard symbols you already know.

TRY OUR 10 MINUTE MARKDOWN TUTORIAL

Type	Or	... to Get
Italic	_Italic_	<i>Italic</i>
Bold	__Bold__	Bold
# Heading 1	Heading 1 =====	Heading 1
## Heading 2	Heading 2 -----	Heading 2
[Link](http://a.com)	[Link][1] : [1]: http://b.org	Link
![[Image]](http://url/a.png)	![[Image]][1] : [1]: http://url/b.jpg	
> Blockquote		Blockquote
* List * List * List	- List - List - List	• List • List • List
1. One 2. Two	1) One 2) Two	1. One 2. Two

CLS Activities - Writing - cont.

Pandoc a universal document converter

[Donate](#) [Flags](#) [C7](#)
[About](#)
[Installing](#)
[Getting started](#)
[Demos ▾](#)
[Documentation ▾](#)
[Help](#)
[Extras](#)
[Releases](#)

About pandoc

If you need to convert files from one markup format into another, pandoc is your swiss-army knife. Pandoc can convert documents in (several dialects of) Markdown, reStructuredText, textile, HTML, DocBook, LaTeX, MediaWiki markup, TWiki markup, TikiWiki markup, Creole 1.0, Vimwiki markup, OPML, Emacs Org-Mode, Emacs Muse, txt2tags, Microsoft Word docx, LibreOffice ODT, EPUB, or Haddock markup to

HTML formats

XHTML, HTML5, and HTML slide shows using Slidy, reveal.js, Slideous, S5, or DZSlides

Word processor formats

Microsoft Word docx, OpenOffice/LibreOffice ODT, OpenDocument XML, Microsoft PowerPoint.

Ebooks

EPUB version 2 or 3, FictionBook2

<https://automeris.io/WebPlotDigitizer/>

Web based tool to extract data from plots, images, and maps

Home Blog Tutorials Citation Privacy

Web Application
English
Launch Now!

Desktop Version
Windows macOS Linux

View Source
GitHub

It is often necessary to reverse engineer images of data visualizations to extract the underlying numerical data. WebPlotDigitizer is a semi-automated tool that makes this process extremely easy:

- Works with a wide variety of charts (XY, bar, polar, ternary, maps etc.)
- Automatic extraction algorithms make it easy to extract a large number of data points
- Free to use, opensource and cross-platform (web and desktop)
- Used in hundreds of published works by thousands of users
- Also useful for measuring distances or angles between various features
- More to come soon...

<http://www.phrasebank.manchester.ac.uk/>

MANCHESTER 1824
The University of Manchester

Academic Phrasebank

Introducing Work Referring to Sources Describing Methods Reporting Results Discussing Findings Writing Conclusions

Home Page

GENERAL LANGUAGE FUNCTIONS

- Being Cautious
- Being Critical
- Classifying and Listing
- Compare and Contrast
- Defining Terms
- Describing Trends
- Describing Quantities
- Explaining Causality
- Giving Examples
- Signalling Transition
- Writing about the Past

ABOUT PHRASEBANK

An enhanced and expanded version of PHRASEBANK can now be downloaded in PDF:

The Academic Phrasebank is a general resource for academic writers. It aims to provide you with examples of some of the phraseological 'nuts and bolts' of writing organised according to the main sections of a research paper or dissertation (see the top menu). Other phrases are listed under the more general communicative functions of academic writing (see the menu on the left). The resource should be particularly useful for writers who need to report their research work. The phrases, and the headings under which they are listed, can be used simply to assist you in thinking about the content and organisation of your own writing, or the phrases can be incorporated into your writing where this is appropriate. In most cases, a certain amount of creativity and adaptation will be necessary when a phrase is used. The items in the Academic Phrasebank are mostly content neutral and generic in nature; in using them, therefore, you are not stealing other people's ideas and this does not constitute plagiarism. For some of the entries, specific content words have been included for illustrative purposes, and these should be substituted when the phrases are used. The resource was designed primarily for academic and scientific writers who are non-native speakers of English. However, native speaker writers may still find much of the material helpful. In fact, recent data suggest that the majority of users are native speakers of English. More about [Academic Phrasebank](#).

This site was created by John Morley. If you could spare just two or three minutes of your time, I would be extremely grateful for any feedback on Academic Phrasebank: Please click [here](#) to access a very short questionnaire. Thank you.

CLS Activities - Programming

- programming languages
- editors

- examples

Programming languages

- Python (!)
- Julia (!) (C + Python + Lisp structures)
- C (!) (performance, hardware access)
- C++ (!) (If you need performance + OO)
- Rust (!) (performance and safety)
- Kotlin (primarily mobile development)
- Nim (Python, but C)
- R (statistics)
- Scala (data science)
- Go (Google's try)
- Javascript (too popular to leave out)
- Racket (for the gourmet)
- +1 Lobster lang. (<http://strlen.com/lobster/>)

Application domains can overlap, choose 2-3 and learn them well!


For instance, C/C++ and Python is a quite versatile combination.

Computer Language Benchmark Game (<https://benchmarksgame-team.pages.debian.net/benchmarksgame/index.html>)

Rosetta Code (<http://www.rosettacode.org>)

Julia programming language

<https://hva-uva.cloud.panopto.eu/Panopto/Pages/Viewer.aspx?id=00d4221b-42c8-4d3b-978b-b1e900b401d3>



In [1]:

General editors


- **Visual Studio Code** (!!)
- Zed (Editor, AI support) - <https://zed.dev/>
- Gram (Zed without AI)
- **Jupyter / JupyterLab** (!)
- Cursor, Roo, ... zoo of AI assisted IDEs
- Vi/Vim/Neo Vim
- Emacs (Spacemacs)
- Sublime Text
- Note++
- ... wide palett of other editors ...

Specific editors / IDEs

- Spyder (!) - <https://www.spyder-ide.org/>
- **Pluto** (for Julia) (!) - <https://plutojl.org/>
- PyCharm
- Juno (VSCode, Julia) - <https://www.julia-vscode.org/>
- Lazarus (UI for desktop) - <https://www.lazarus-ide.org/>

In practice

When people ask me to recommend a text editor:



Why is Jupyter important?

- HTML5 platform (kernel as backend, can run remotely on a different machine)
- Compatible with several languages (C++, Python, Julia, Haskell, ...)
- Important step in hosting and sharing codes (reproducibility)
- Towards reproducible science! (also see Jupyter Lab)

Careful: non-linear state, see next example! (Check out Pluto for linear state solution)

- Additional benefits of the separate backend: parallel execution, cluster management, remote execution

```
In [1]: b=2
        print(b)
```

2

```
In [2]: print(b)
        b=3
```

2

```
In [3]: %matplotlib notebook
import sympy as sp
sp.init_printing(use_latex='mathjax')
x,y,z = sp.symbols('x,y,z')
f = sp.sin(x*y)+sp.cos(y*z)
sp.integrate(f,x)
```


Out[3]:
$$x \cos(yz) + \begin{cases} -\frac{\cos(xy)}{y} & \text{for } y \neq 0 \\ 0 & \text{otherwise} \end{cases}$$

```
In [4]: import sympy as sm
from sympy.plotting import plot
x = sm.symbols('x', real=True)
h_ = sm.symbols('h_')

w = 3 * sm.sqrt(1 - (x / 7)**2)
l = ((x + 3) / 2 - sm.S(3) / 7 * sm.sqrt(10) * sm.sqrt(4 - (x + 1)**2) +
      sm.S(6) / 7 * sm.sqrt(10))
r = ((3 - x) / 2 - sm.S(3) / 7 * sm.sqrt(10) * sm.sqrt(4 - (x - 1)**2) +
      sm.S(6) / 7 * sm.sqrt(10))
h = (3*(sm.Abs(x - sm.S.Half) + sm.Abs(x + sm.S.Half) + 6) -
      11*(sm.Abs(x - sm.S(3)/4) + sm.Abs(x + sm.S(3)/4)))/2
f = ((h - l) * sm.Heaviside(x + 1, 0) +
      (r - h) * sm.Heaviside(x - 1, 0) +
      (l - w) * sm.Heaviside(x + 3, 0) +
      (w - r) * sm.Heaviside(x - 3, 0) +
      w)
g = (sm.S(1) / 2 * (sm.Abs(x / 2) + sm.sqrt(1 + (sm.Abs(sm.Abs(x) - 2) -
      1)**2) - sm.S(1) / 112 * (3 * sm.sqrt(33) - 7) * x**2 + 3 *
      sm.sqrt(1 - (sm.S(1) / 7 * x)**2) - 3) * ((x + 4) / sm.Abs(x + 4) -
      (x - 4) / sm.Abs(x - 4)) - 3 * sm.sqrt(1 - (x / 7)**2))
sm.plot(f, g)
```



```
In [5]: import matplotlib.pyplot as plt
from scipy.fftpack import fft; from scipy.io import wavfile
fs, data = wavfile.read('sound/sine440.wav') # load the data, 16 bit, 44.1 k
c = fft(data.T) # calculate fourier transform (complex numbers list)
d = len(c)//2 # you only need half of the fft list (real signal symmetry)
plt.figure(); plt.plot(abs(c[:d-1]), 'r'); plt.xlim((0,4000))
```




Out[5]: (0.0, 4000.0)

```
In [6]: import IPython
IPython.display.Audio('sound/sine440.wav')
# IPython.display.Audio('sound/sample.wav')
```

Out[6]: 0:00 / 0:01

```
In [7]: import matplotlib.pyplot as plt
import numpy as np
x = np.linspace(0,20,500)
plt.figure(); plt.plot(x, np.sin(x))
```




Out[7]: [<matplotlib.lines.Line2D at 0x15a380cb0>]

```
In [8]: import matplotlib.pyplot as plt
from ipywidgets import interact, IntSlider
from IPython.display import display, clear_output
plt.figure()

def f(freq):
    x = np.linspace(0,20,500)
    plt.plot(x, np.sin(x*freq))
    plt.show()
    #display(plt.figure)

interact(f, freq=IntSlider(min=1,max=5,step=1,value=1));
```



```
interactive(children=(IntSlider(value=1, description='freq', max=5, min=1),
Output()), _dom_classes=('widget-i...
```

```
In [9]: from IPython.display import display, Javascript
import ipywidgets as widgets


L = widgets.Label("Hello World")
display(L)
```

```
Label(value='Hello World')
```

```
In [10]: L.value = "Howdy World"
```

```
In [11]: from mpl_toolkits.mplot3d import Axes3D; import matplotlib.pyplot as plt;

fig = plt.figure(); ax = fig.add_subplot(111, projection='3d')
x = [1,2,3,4,5,6,7,8,9,10]; y = [5,6,2,3,13,4,1,2,4,8]; z = [2,3,3,3,5,7,9,11,9
ax.scatter(x, y, z, c='r', marker='o'); ax.set_xlabel('X Label'); ax.set_yla
```



Out[11]: Text(0.5, 0, 'Z Label')

```
In [ ]: import ipyvolume as ipv
import numpy as np
import ipyvolume.datasets
stream = ipyvolume.datasets.animated_stream.fetch()
fig = ipv.figure()
# instead of doing x=stream.data[0], y=stream.data[1], ... vz=stream.data[5]
# limit to 50 timesteps to avoid having a huge notebook
q = ipv.quiver(*stream.data[:,0:50,:200], color="red", size=7)
ipv.style.use("dark") # looks better
ipv.animation_control(q, interval=200)
ipv.show()
```

```
In [12]: import matplotlib.pyplot as plt
import pandas as pd
import seaborn as sns
df = sns.load_dataset("anscombe") #Anscombe's quartet, there are others (Tit
df.head()
```

```
Out[12]:
```


	dataset	x	y
0	I	10.0	8.04
1	I	8.0	6.95
2	I	13.0	7.58
3	I	9.0	8.81
4	I	11.0	8.33

```
In [13]: df.groupby(df.dataset).describe()
```

```
Out[13]:
```





		x										
		count	mean	std	min	25%	50%	75%	max	count	mean	
dataset												
	I	11.0	9.0	3.316625	4.0	6.5	9.0	11.5	14.0	11.0	7.500909	2.031
	II	11.0	9.0	3.316625	4.0	6.5	9.0	11.5	14.0	11.0	7.500909	2.031
	III	11.0	9.0	3.316625	4.0	6.5	9.0	11.5	14.0	11.0	7.500000	2.030
	IV	11.0	9.0	3.316625	8.0	8.0	8.0	8.0	19.0	11.0	7.500909	2.030


```
In [14]: sns.lmplot(x="x", y="y", col="dataset", hue="dataset", data=df, col_wrap=2,
                    scatter_kws={"s": 50, "alpha": 1}); plt.show()
```



Visualization practices

<https://interactions.acm.org/archive/view/july-august-2018/the-good-the-bad-and-the-biased>





Further visualization tools

Because our simulations produce a lot of data (big data?!), but the purpose of the computation is not numbers, but insight.

- python matplotlib (!) - (<https://matplotlib.org/>)
- ParaView (!) - VTK based parallel 3D visualization tool (<https://www.paraview.org/>)
- MayaVi - ParaView alternative, written in python (embeddable!) (<https://docs.enthought.com/mayavi/mayavi/>)
- PyVista - Practically the new VTK binding (<https://docs.pyvista.org/>)
- gnuplot (!) - Swiss army knife of plotters (<http://www.gnuplot.info/>)
- vedo - Simple visualization 2D/3D, simulation friendly (<https://github.com/marcomusy/vedo>)
- Processing - Programming language designed for 3D visualizations (<https://processing.org/>)
- Inkscape - For that nice poster. (<https://inkscape.org/>)
- Blender - (<https://www.blender.org/>)

Presentation tools

- MS PowerPoint (!)
- LaTeX (!) (e.g. Beamer)
- Reveal.js (<https://github.com/hakimel/reveal.js/>)
- Jupyter Notebook (sort of works...)
- TexMacs, LyX, ...

Further things to look at in the Python world

- <https://github.com/barbagroup/CFDPython>

- http://mbakker7.github.io/exploratory_computing_with_python
- <https://github.com/vinta/awesome-python>

Other tools to mention

- Desktop Jupyter: nteract (<https://nteract.io/>)
- Desktop JupyterLab: (<https://github.com/jupyterlab/jupyterlab-desktop>)
- Calculator: SpeedCrunch (<https://speedcrunch.org/>)
- CAS: Sympy (!) (www.sympy.org), Maxima (<http://maxima.sourceforge.net/>)
- Worksheet: SMATHStudio (<https://en.smath.com/view/SMATHStudio/summary>)
- Recording terminal session: ASCIInema (<https://asciinema.org/>)
- Collection of command line terminal tools (<https://www.wezm.net/technical/2019/10/useful-command-line-tools/>)

Software development in a collaborative environment

- Student-ware ('agile' method? - <https://www.atlassian.com/agile>)
- Guidelines PEP8
- Version control
- Tests

Software development as a student

The boundary conditions are a bit different compared to industrial development, but still aim to adopt good practices!

The typical situation:

- most often no preliminary design
- "let's see what happens" first version
- then the code is "grown" in incremental steps
- "backups" is some old version on a pendrive, or sent in email
- patchworky design in team development
- this is a natural process given the boundary conditions

Pro.:

- nothing really
- time efficiency on the short-term (*maybe*)

Con.:

- difficult collaboration with unnecessary friction
- quickly leads to decaying efficiency
- resulting code is not robust or future proof
- often difficult to extend (aka. rewrite to add a feature)


What can be improved?

Coding style (!)

- Style guides:
 - Python PEP8 (<https://www.python.org/dev/peps/>)
 - C++ Google Style guide (<https://google.github.io/styleguide/cppguide.html>)
 - C - Many, e.g. Rob Pike's (<https://www.maultech.com/chrislott/resources/cstyle/pikestyle.html>)
 - Most IDEs have builtin support for this.
- Documentation (proper README.md)
- Code comments and function documentation (e.g. docstring).

```
In [15]: print(''.join(map(lambda x: chr((lambda p, x: int(sum(map(lambda i: p[i]*x**
Hello world!
```

Version control - git (!)




```
In [16]: from IPython.display import IFrame
IFrame("doc/git_cheat_sheet.jpg", width=800, height=600) # from http://roger
```

Out[16]:

git cheat sheet

learn more about git the simple way at rogerdudler.github.com/git-guide/
cheat sheet created by Nina Jaeschke of ninajaeschke.com



Tools for git

- tig (!) (<https://github.com/jonas/tig>)
- sourcetree (<https://www.sourcetreeapp.com/>)
- GitUp (mac only :) (<https://gitup.co/>)
- gitKraken (not free, but part of GitHub Education :) (<https://www.gitkraken.com/>)
- most IDEs have built in support for git
- Free git service: github, bitbucket, gitlab

GitHub

<https://education.github.com/students>; <https://docs.github.com/en/get-started/start-your-journey/about-github-and-git>;
<https://git-scm.com/book/en/v2>; (!) <https://education.github.com/git-cheat-sheet->

[education.pdf](#)

Access to additional tools: GitHub Copilot, Copilot Chat, Git Kraken, Termius....

[Home](#) / [Students](#)

With GitHub Education, your work will speak for itself.

Build your portfolio, grow your network, and level up your skills.

[Get benefits for students](#)



**GitHub Student Developer
Pack**




GitHub Campus Expert

Grow your leadership skills



Learn more advanced git techniques visually

<https://learngitbranching.js.org/>



Git fame

<https://github.com/casperdcl/git-fame>

```
~$ git fame --cost hour,month --loc ins
Processing: 100% | 1/1 [00:00<00:00, 2.16repo/s]
Total commits: 1775
Total ctimes: 2770
Total files: 461
Total hours: 449.7
Total loc: 41659
Total months: 151.0
```

Author	hrs	mths	loc	coms	files	distribution
Casper da Costa-Luis	228	108	28572	1314	172	68.6/74.0/37.3
Stephen Larroque	28	18	5243	203	25	12.6/11.4/ 5.4
pgajdos	2	9	2606	2	18	6.3/ 0.1/ 3.9
Martin Zugnoni	2	5	1656	3	3	4.0/ 0.2/ 0.7
Kyle Altendorf	7	2	541	31	7	1.3/ 1.7/ 1.5
Hadrien Mary	5	1	469	31	17	1.1/ 1.7/ 3.7
Richard Sheridan	2	1	437	23	3	1.0/ 1.3/ 0.7
Guangshuo Chen	3	1	321	18	7	0.8/ 1.0/ 1.5
Noam Yorav-Raphael	4	1	229	11	6	0.5/ 0.6/ 1.3
github-actions[bot]	2	1	186	1	51	0.4/ 0.1/11.1

...

Testing

- Unit tests (!)
- doc tests
- Property-based testing
- CI (continuous integration) / CD (continuous delivery)

In [17]: `import unittest`

```
def fun(x):
    return x + 1

class MyTest(unittest.TestCase):
    def test(self):
        self.assertEqual(fun(4), 4)

# Testing
# Normally: unittest.main()
unittest.main(argv=['first-arg-is-ignored'], exit=False)
```

F:/opt/miniconda3/envs/a_skills_p12/lib/python3.12/site-packages/jupyter_client/session.py:203: DeprecationWarning: datetime.datetime.utcnow() is deprecated and scheduled for removal in a future version. Use timezone-aware objects to represent datetimes in UTC: datetime.datetime.now(datetime.UTC).
 return datetime.utcnow().replace(tzinfo=utc)

=====

FAIL: test (__main__.MyTest.test)

Traceback (most recent call last):

File "/var/folders/zn/xt40d6fn6mb26424g2frs6nw0000gn/T/ipykernel_23347/1354764667.py", line 8, in test
 self.assertEqual(fun(4), 4)
AssertionError: 5 != 4

Ran 1 test in 0.003s

FAILED (failures=1)

Out[17]: <unittest.main.TestProgram at 0x7020625df0>

In [18]: `def square(x):`
 `"""Return the square of x.`
 `>>> square(5)`
 `9`
 `>>> square(-2)`
 `4`
 `"""`
 `return x * x`

```
# Testing
import doctest
doctest.testmod()
```

```

*****
File "__main__", line 4, in __main__.square
Failed example:
    square(5)
Expected:
    9
Got:
    25
*****
1 items had failures:
  1 of  2 in __main__.square
***Test Failed*** 1 failures.

```

Out[18]: TestResults(failed=1, attempted=2)

<https://doi.org/10.25080/Majora-342d178e-016>

162

PROC. OF THE 19th PYTHON IN SCIENCE CONF. (SCIPY 2020)

Falsify your Software: validating scientific code with property-based testing

Zac Hatfield-Dodds[✉]

Abstract—Where traditional example-based tests check software using manually-specified input-output pairs, property-based tests exploit a general description of valid inputs and program behaviour to automatically search for falsifying examples. Given that Python has excellent property-based testing tools, such tests are often *easier* to work with and routinely find serious bugs that all other techniques have missed.

I present four categories of properties relevant to most scientific projects, demonstrate how each found real bugs in Numpy and Astropy, and propose that property-based testing should be adopted more widely across the SciPy ecosystem.

Index Terms—methods, software, validation, property-based testing

Introduction

Much research now depends on software for data collection, analysis, and reporting; including on software produced and maintained by researchers. This has empowered us enormously: it is hard to imagine an analysis that was possible *at all* a generation ago which could not be accomplished quickly by a graduate student today.

Unfortunately, this revolution in the power and sophistication of our software has largely outstripped work on validation. While

sible to non-experts in Python, and has added multiple features designed for testing scientific programs³ since 2019.

What is property-based testing?

Where example-based tests check for an exact expected output, property-based tests make *less precise* but *more general* assertions. By giving up hand-specification of the expected output, we gain tests that can be run on a wide range of inputs.


This generality also guides our tests to the right level of abstraction, and gives clear design feedback: where example-based tests map one input to one output regardless of complexity, every special case or interacting feature has to be addressed. Clean abstractions which allow you to say "for all ...", without caveats, stand in clear contrast and are a pleasure to test.

Tests which use random data are usually property-based, but using a library designed for the task has several advantages:

- a concise and expressive interface for describing inputs
- tests are never flaky - failing examples are cached and replayed, even if the test failed on a remote build server
- automatic shrinking facilitates debugging by presenting a minimal failing example for each distinct error

Data handling - FAIR principles

Publication in Nature Data Science - <https://doi.org/10.1038/sdata.2016.18>



Licensing your code

- You are the owner of the results you produce, unless you have a working contract (internship, student assistantship, waiver of ownership).
- You choose how you distribute your code, unless there are additional contracts (e.g. NDA) in place.
- If you don't choose a license: "no license" license applies. So <https://choosealicense.com/> !

Choose an open source license

An open source license protects contributors and users. Businesses and savvy developers won't touch a project without this protection.

Which of the following best describes your situation?

I need to work in a community.

Use the [license preferred by the community](#) you're contributing to or depending on. Your project will fit right in.

If you have a dependency that doesn't have a license, ask its maintainers to [add a license](#).

I want it simple and permissive.

The [MIT License](#) is short and to the point. It lets people do almost anything they want with your project, like making and distributing closed source versions.

[Babel](#), [.NET](#), and [Rails](#) use the MIT License.

I care about sharing improvements.

The [GNU GPLv3](#) also lets people do almost anything they want with your project, *except* distributing closed source versions.

[Ansible](#), [Niri](#), and [uBlock Origin](#) use the GNU GPLv3.

Compare available licenses

Recommended to choose an existing broadly accepted license form. See e.g., <https://choosealicense.com/appendix/>

License	Commercial use	Distribution	Modification	Patent use	Private use	Disclose source	License and copyright notice	Network use its distribution	Same license	State changes	Liability	Trademark use	Warranty
BSD Zero Clause License	✓	✓	✓		✓						✗		✗
Academic Free License v3.0	✓	✓	✓	✓	✓		①			①	✗	✗	✗
GNU Affero General Public License v3.0	✓	✓	✓	✓	✓	①	①	①	①	①	✗		✗
Apache License 2.0	✓	✓	✓	✓	✓		①			①	✗	✗	✗
Artistic License 2.0	✓	✓	✓	✓	✓		①			①	✗	✗	✗
Blue Oak Model License 1.0.0	✓	✓	✓	✓	✓		①				✗		✗
BSD-2-Clause Plus Patent License	✓	✓	✓	✓	✓		①				✗		✗
BSD 2-Clause "Simplified" License	✓	✓	✓		✓		①				✗		✗
BSD 3-Clause Clear License	✓	✓	✓	✗	✓		①				✗		✗
BSD 3-Clause "New" or "Revised" License	✓	✓	✓		✓		①				✗		✗
BSD 4-Clause "Original" or "Old" License	✓	✓	✓		✓		①				✗		✗
Boost Software	✓	✓	✓		✓		①				✗		✗

Code vs. Non-code assets

- Software licenses (like *MIT*, *GPL*, *Apache*) apply to source code
- Project deliverables like thesis text, slides, graphics, or raw datasets are better served by Creative Commons licenses (e.g., *CC BY 4.0*)



Who We Are What We Do Blog Support Us

Stay informed. Sign up for [CC's Newsletter](#).

Sharing Openly,
Sharing Globally



GenAI use - University guidelines (2026 fall)

Tools

- Officially standard commercial tools (like ChatGPT) are prohibited due to strict GDPR and privacy regulations.
- The UvA developed secure internal platform called UvA AI Chat is allowed. <https://aichat.uva.nl/>


Use of these tools

- *Permitted Use*: Brainstorming, language translation, and automated knowledge testing.
- *Prohibited Use*: Submitting AI-generated material as original student work is strictly classified as academic fraud under plagiarism regulations.


The general guideline document can be found at: <https://www.uva.nl/en/about-the-uva/policy-and-regulations/education/policy-framework-and-guidelines-on-genai-in-education.html>


Note: programmes and some courses might have their own rules on top of this. If unsure ask the course coordinator.

You are always fully responsible!




Some examples on what can go wrong





Use case - HemoCell (www.hemocell.eu)



Some highlights:

HemoCell is a high-cost code, it is in continuous development for 8 years. >20 developers, >20 associated scientific publications, one of the largest distributed execution in EU (330,000 cores).

Tools and techniques of interest:

- Developed in C++ with processing scripts in Python and Bash.
- The source code is version controlled under git (GitHub).
- Uses 2 CI/CD servers to test commits.
- Edited mostly in Visual Studio Code, Sublime Text, and NetBeans.
- The documentation is written in Markdown(-ish) text.
- The publications are written in Overleaf.
- Data visualization through ParaView and Blender.
- Data evaluation through Python (+ HDF5, VTK, ...).
- Presentations, posters done in PowerPoint.
- Illustrative graphics in Inkscape.

Take home message

0. You often work in teams: code quality helps collaboration!
1. Document well: "Will I understand my code completely by reading this 2 years from now?"
2. Use version control, even if you are the only developer.
3. Cover with tests as much as possible.
4. Visualize whenever possible, develop fast pipelines for visualization.
5. Create visualizations from different perspectives before you decide how will you present it.
6. Every statement you write down needs supporting evidence! I.e., data produced by you or references (scientific ones, not wikipedia).

Homework assignment

https://github.com/gzavo/CS_Assignment

1. Create a free github account if you don't already have one.
2. Fork this repository.
3. Create a markdown (.md) named "solution_.md" file that will contain the following:
4. The title of the following papers pivotal to our knowledge:
 - MCC Van Dyke et al., 2019
 - JT Harvey, Applied Ergonomics, 2002
 - DW Ziegler et al., 2005
5. Create 1 plot from the dataset "istherecorrelation.csv", with DPI=300. The objective is to visualize the data as you see fit. Include the resulting image in the markdown file (and you can also write a few lines of interpretation if you like).
6. Commit and push these two files to your fork.

7. Create a pull request for me to this (original) repo. (Hint: use "compare across forks").

Thank you for your attention!

Questions?

