



ULTRASIGHT™

MODULAR ULTRASONIC INTELLIGENT PIGGING SYSTEM



TOOL

Pig type	Multi-body, bi-directional, free-swimming
Construction	Aerospace-grade 7068 aluminium

OPERATING ENVELOPE

Diameter range	3 – 12 inch (75 – 300 mm)
Max run length	30 km
Min bend radius	1D / short radius
Temperature	-20 to +75°C
Max pressure	900 PSI

MEASUREMENT

Method	Multichannel pulse-echo UT · 60 MHz sampling
Accuracy	±0.1 mm wall thickness
Density	30,000+ measurements per lineal foot
Probability of detection	4 mm @ 95%
Thickness range	1 – 20 mm
Data	Full A-scan capture
Mapping	9DOF IMU + odometer wheels · ±50 mm axial

DATA & SOFTWARE

- Automated data analysis
- Automated defect classification
- 3D C-scans and 2D C-scans
- Linear plots
- 2D & 3D route plotting, overlaid on maps

REPORTING

Preliminary report	Within 24 hours
Final report	Within 4 days
Generation	Automated report generation

FITNESS FOR SERVICE

Assessment	Level 1, 2 & 3 to API 579
------------	---------------------------

APPLICATIONS

Pipelines · transfer lines · fired heaters · boilers · process piping

Specifications subject to change. Values current as of July 2026.