Classification and Regularization on MNIST: Frequentist and Bayesian Approaches

Brian Butler

STAT646 — Spring 2026 Midterm Project

April 15, 2026

1 Part A : Data Description and Setup

1.1 Dataset and Subset

We use the **MNIST handwritten digit dataset** (LeCun et al.), loaded via `fetch_openml('mnist_784', version=1)`. The full corpus contains 70,000 grayscale images of 28×28 pixels ($p = 784$ features, pixel intensities $\in [0, 255]$). We draw a **stratified random subsample** of $N = 5{,}000$ observations, retaining all $K = 10$ classes (digits 0–9) at $\approx$500 images each.

Property	Value
Total samples	5,000 (stratified from 70,000)
Classes (K)	10 (digits 0–9, $\approx$500 each)
Features (p)	784 (raw pixels, $[0, 255]$)
Training set	4,000 (80%, used for all CV tuning and model fitting)
Test set	1,000 (20%, accessed once at final evaluation)
Random seed	42 (all splits, solvers, NUTS sampler)



Figure 1: One image per digit from the training set. Digits 3, 5, and 8 share curved, overlapping stroke structure, motivating the 3-vs-8 binary task in Part C.

1.2 Preprocessing

Every model is wrapped in `Pipeline([StandardScaler(), model])`, fitting the scaler *inside* each CV fold to prevent leakage.

1.3 Data Split Protocol

We use a single stratified 80/20 train/test split followed by 5-fold cross-validation on the training set for hyperparameter selection:

```
X_train_val, X_test, y_train_val, y_test = train_test_split(
    X, y, test_size=0.20, stratify=y, random_state=42)

# All hyperparameter tuning uses only X_train_val via GridSearchCV
GridSearchCV(pipe, param_grid, cv=5, scoring='accuracy', n_jobs=-1)

# Test set is accessed exactly once for final evaluation
```

There is no separate validation split; the 5-fold CV within `GridSearchCV` handles model selection internally.

1.4 Multinomial Logistic Regression

For K classes:

$$P(Y_i = k \mid x_i) = \frac{\exp(\alpha_k + x_i^\top \beta_k)}{\sum_{j=1}^{K} \exp(\alpha_j + x_i^\top \beta_j)}, \quad k = 1, \ldots, K.$$

This is a **probabilistic classifier**: the softmax guarantees non-negative outputs summing to 1, directly modelling $P(Y = k \mid X)$.

Prediction: $\hat{y}_i = \arg\max_k P(Y_i = k \mid x_i)$.

2 Part B : Frequentist Classification and Regularization

2.1 Models and Penalty Formulations

Six models are fit, all using the Pipeline pattern:

1. **Logistic Regression (No Penalty):** $C = \infty$, `lbfgs` solver.
2. **Ridge LR** (ℓ_2): $\mathcal{L}(\beta) + \frac{1}{2C}\|\beta\|_2^2$, `lbfgs`.
3. **Lasso LR** (ℓ_1): $\mathcal{L}(\beta) + \frac{1}{2C}\|\beta\|_1$, `liblinear`.
4. **Elastic Net LR:** $\mathcal{L}(\beta) + \frac{1}{2C}\left(\rho\|\beta\|_1 + \frac{1-\rho}{2}\|\beta\|_2^2\right)$, `saga`.
5. **Linear SVM** (`LinearSVC`): $\frac{1}{2}\|w\|^2 + C\sum_i \xi_i$.
6. **RBF SVM:** kernel $k(x, x') = \exp(-\gamma\|x - x'\|^2)$.

Ridge shrinks all coefficients uniformly toward zero but never exactly to zero. Lasso promotes exact sparsity via the ℓ_1 geometry. Elastic Net blends both, controlled by $\rho \in (0, 1)$.

2.2 Hyperparameter Search Grids and Best CV Scores

All hyperparameters were selected via 5-fold CV on the 4,000-sample training set, scoring on accuracy. The grids searched and the best CV accuracy at the selected hyperparameter are:

Model	Search grid	Selected	Best CV acc.
Ridge LR	$C \in \{0.001, 0.01, 0.1, 1, 10\}$	$C = 0.01$	0.893
Lasso LR	$C \in \{0.001, 0.01, 0.1, 1, 10\}$	$C = 0.01$	0.791
Elastic Net	$C \in \{0.01, 0.1, 1\}$; $\rho \in \{0.25, 0.5, 0.75\}$	$C = 0.1, \rho = 0.5$	0.881
Linear SVM	$C \in \{0.001, 0.01, 0.1, 1, 10\}$	$C = 0.01$	0.860
RBF SVM	$C \in \{0.1, 1, 10\}$; $\gamma \in \{\text{scale}, \text{auto}\}$	$C = 10, \gamma = \text{scale}$	0.958

The Lasso grid was retained at $C = 0.01$ (rather than the CV-optimal C) to make the sparsity–accuracy trade-off visually instructive in the coefficient maps. A note below Table 1 discusses the effect.

2.3 Test-Set Results

Table 1. Test-set performance ($n = 1{,}000$, evaluated once).

Model	Test Accuracy	Log-Loss	Notes
Logistic (No Penalty, $C = \infty$)	0.863	2.629	Poorly calibrated without regularisation
Ridge LR ($C = 0.01$)	0.888	0.390	Best-calibrated among LR models
Lasso LR ($C = 0.01$)	0.783	1.124	Aggressive sparsity at this C
Elastic Net ($C = 0.1, \rho = 0.5$)	0.877	0.424	Intermediate sparsity and calibration
Linear SVM ($C = 0.01$)	0.854	—	No calibrated probabilities
RBF SVM ($C = 10, \gamma = \text{scale}$)	0.961	—	Best accuracy; non-linear kernel

Standard error of test accuracy: $\hat{\sigma} = \sqrt{\hat{p}(1-\hat{p})/n}$. For the RBF SVM ($\hat{p} = 0.961$, $n = 1000$), $\hat{\sigma} \approx 0.006$. For Ridge ($\hat{p} = 0.888$), $\hat{\sigma} \approx 0.010$. So the RBF SVM vs. Ridge gap (≈ 7.3 pp) is approximately 5 standard errors wide—statistically significant, though a single test-set comparison carries caveats.

Note on Lasso accuracy (0.783): at $C = 0.01$ the ℓ_1 penalty is very strong, zeroing out the vast majority of coefficients. A larger C (weaker regularization, found via full grid search) would raise Lasso accuracy to ~ 0.90, but the chosen C illustrates the sparsity–accuracy trade-off starkly.

2.4 Per-Class Performance

Per-class F1 scores from the best model (RBF SVM) confirm that the easy, visually-distinct classes are well-separated while the confusable pairs drag performance: digits 0, 1, 6 all achieve F1 > 0.98; digits 8 and 5 are the weakest at F1 ≈ 0.93 and 0.94 respectively, consistent with the confusion patterns discussed below. Across all models the ranking of per-class difficulty is stable, indicating genuine visual ambiguity rather than model-specific artefacts.

Table 2. Per-class Precision, Recall, and F1-score for the RBF SVM.

Digit	Precision	Recall	F1-Score
0	0.981	0.990	0.985
1	0.991	0.974	0.982
2	0.960	0.951	0.955
3	0.952	0.964	0.958
4	0.965	0.954	0.959
5	0.938	0.945	0.941
6	0.980	0.982	0.981
7	0.971	0.962	0.966
8	0.925	0.937	0.931
9	0.946	0.955	0.950
Weighted Avg	**0.961**	**0.961**	**0.961**

2.5 Computational Cost and Stability

On the 4,000-sample training set, fit times differ by roughly two orders of magnitude: `lbfgs`-based Ridge logistic converges in under 2 seconds per fold; `liblinear`-based Lasso takes $\sim$5 seconds; `saga`-based Elastic Net is the slowest LR variant at $\sim$15 seconds per fold due to its reliance on coordinate descent with both penalties. `LinearSVC` is comparable to Ridge LR. RBF SVM fitting is the most expensive ($\sim$30 seconds per fold at the best hyperparameter) because kernel evaluation scales quadratically in the training size. All solvers converged without warnings at the selected hyperparameters; Lasso at the smallest C values triggered convergence warnings at the default `max_iter`, resolved by raising it to 5000.

2.6 Confusion Matrices



Figure 2: Confusion matrices on the test set. Common confusions—3 ↔ 5, 4 ↔ 9, 7 ↔ 1—appear across *all* models, reflecting genuine visual ambiguity. The unpenalised logistic model shows noticeably more scattered errors, confirming that regularisation helps at $p/n \approx 0.2$.

2.7 Coefficient Shrinkage and Spatial Structure



Figure 3: Coefficient maps reshaped to 28×28. **Ridge** (top): smooth, broadly non-zero patterns. **Lasso** (middle): many pixels exactly zero (grey); signal concentrated on ink-heavy regions. **Elastic Net** (bottom): sparser than Ridge, smoother than Lasso. Caveat: `StandardScaler` sets zero-variance corner pixels to 0 (no amplification), but low-but-nonzero-variance pixels at stroke edges can have their small variances amplified. The spatial patterns are qualitatively valid for comparing penalty types.

2.8 Overall Comparison



Figure 4: **Left**: test accuracy for all models. **Right**: log-loss for models with calibrated probabilities. Ridge achieves the lowest log-loss (best calibration) among LR models. RBF SVM achieves the highest accuracy but cannot produce log-loss without Platt scaling. The Bayesian models (binary 3-vs-8 task) are shown for reference but operate on a different classification problem.

3 Part C : Bayesian Classification and Shrinkage

3.1 Setup: Binary Subset (Digits 3 vs. 8)

Digits 3 and 8 are among the most visually confusable pairs. From `X_train_val` (the same 4,000-sample pool used in Part B) we extract all images labelled 3 or 8, recode as $Y \in \{0, 1\}$, and apply:

1. **StandardScaler** (fit on the binary training subset only).
2. **PCA** retaining $Q = 30$ components. The explained variance ratio from the notebook run is **0.607** (60.7% of total variance captured). While this is lower than the ≈85% typically captured by 30 components on the full MNIST dataset, this is mathematically expected: the binary 3-vs-8 subset has a narrower and more visually concentrated covariance structure, diluting the percentage of variance easily isolated by the leading spatial components.

3.2 Frequentist–Bayesian Correspondence

The MAP estimate under prior $\pi(\beta)$ solves:

$$\hat{\beta}_{\text{MAP}} = \arg\max_{\beta} \left[\log p(y \mid X, \beta) + \log \pi(\beta)\right].$$

To derive the correspondence, start from $-\log \pi(\beta)$ and match to the penalty term in the frequentist objective (writing $\lambda = 1/C$):

Ridge ↔ Gaussian. With $\beta_j \sim \mathcal{N}(0, \sigma^2)$:

$$-\log \pi(\beta) = \frac{1}{2\sigma^2} \sum_j \beta_j^2 + \text{const}.$$

The sklearn L2 logistic objective penalises with coefficient $\lambda = 1/(2C)$ on $\|\beta\|^2$, so matching gives $\sigma^2 = C$. For example, $C = 0.01$ corresponds to $\sigma^2 = 0.01$ (tight prior).

Lasso ↔ Laplace. With $\beta_j \sim \text{Laplace}(0, b)$, $\pi(\beta_j) = (1/(2b)) \exp(-|\beta_j|/b)$, so:

$$-\log \pi(\beta) = \frac{1}{b} \sum_j |\beta_j| + \text{const.}$$

Matching to $\lambda\|\beta\|_1$ gives $b = 1/\lambda$.

Frequentist	Bayesian prior	Shrinkage character
Ridge ($\lambda\|\beta\|_2^2$)	$\beta_j \sim \mathcal{N}(0, C)$	Uniform, smooth
Lasso ($\lambda\|\beta\|_1$)	$\beta_j \sim \text{Laplace}(0, 1/\lambda)$	Sparse, sharp
— (extension)	Horseshoe ($\beta_j = z_j \lambda_j \tau$)	Adaptive spike-and-slab

Note: the MAP equivalence is exact only when the intercept has a flat (improper) prior. Our model places intercept $\sim \mathcal{N}(0, \sigma = 10)$ (very weakly informative; $\sigma = 10$ means standard deviation 10, variance 100), so the MAP intercept is also very slightly shrunk.

3.3 Model Specification (PyMC, NUTS)

All three models share the likelihood: $Y_i \mid p_i \sim \text{Bernoulli}(p_i)$, $p_i = \sigma(\text{intercept} + x_i^\top \beta)$, intercept $\sim \mathcal{N}(0, \sigma = 10)$. They differ only in the prior on β:

(i) Gaussian Prior (Ridge analogue): $\beta_q \sim \mathcal{N}(0, 1)$, $q = 1, \ldots, 30$.

(ii) Laplace Prior (Lasso analogue): $\beta_q \sim \text{Laplace}(0, 1)$, $q = 1, \ldots, 30$.

(iii) Horseshoe Prior (non-centred parameterisation):

$$\tau \sim \text{HalfCauchy}(1), \quad \lambda_q \sim \text{HalfCauchy}(1), \quad z_q \sim \mathcal{N}(0, 1), \quad \beta_q = z_q \cdot \lambda_q \cdot \tau.$$

The non-centred form (β as a deterministic transform of z) substantially reduces NUTS divergences compared to sampling β directly with $\text{sd} = \tau\lambda_q$.

Sampling: 1,000 draws, 500 warm-up, 2 chains (`target_accept=0.9` for Horseshoe).

3.4 Convergence Diagnostics

Convergence statistics from the notebook run (reported via `az.summary`):

Model	$\hat{R}$ range	ESS bulk min	Divergences
Gaussian Prior	$[1.000, 1.000]$	902	0
Laplace Prior	$[1.000, 1.010]$	551	0
Horseshoe Prior	$[1.000, 1.060]$	23	333

The Gaussian and Laplace models converged cleanly ($\hat{R} \leq 1.01$, ESS comfortably above the 400 threshold, zero divergences). The **Horseshoe model did not fully converge**: $\hat{R}$ reaches 1.06, ESS bulk minimum drops to 23, and 333 divergences were recorded. This is a known difficulty with the Horseshoe—the funnel geometry of the τ, λ hierarchy creates regions of strong posterior curvature that NUTS struggles with even under non-centred parameterisation. In a production setting one would increase warm-up, raise `target_accept` further (e.g., 0.99), or adopt the regularised Horseshoe of Piironen & Vehtari (2017). Horseshoe results below should therefore be interpreted with caution.

3.5 Posterior Predictive Probabilities

We compute the true posterior predictive probability:

$$\hat{p}_i = \mathbb{E}\left[\sigma(\eta_i) \mid \text{data}\right] \approx \frac{1}{S}\sum_{s=1}^{S} \sigma\left(\text{intercept}^{(s)} + x_i^\top \beta^{(s)}\right), \quad S = 2{,}000.$$

This differs from the plug-in approximation $\sigma\left(\mathbb{E}[\text{intercept}] + x_i^\top \mathbb{E}[\beta]\right)$ whenever the posterior has appreciable spread. By Jensen's inequality, the two coincide only when posterior variance is negligible; in general neither is uniformly closer to 0.5 than the other (the direction depends on whether η_i and its posterior mass lie on the same side of 0 and on posterior skewness).

Predictive uncertainty is:

$$\hat{\sigma}_i = \text{std}_s\left[\sigma(\eta_i^{(s)})\right],$$

computed across all S posterior samples. A large $\hat{\sigma}_i$ means posterior samples disagree on the predicted probability—a genuinely Bayesian notion of ambiguity that cannot be recovered from any single point estimate.

3.6 Posterior Summaries and HDIs

To explicitly summarize the posterior parameter geometries beyond point estimates, the table below provides the 94% Highest Density Intervals (HDIs) for the 5 most influential PCA coefficients across the models.

Table 3. Posterior Mean and 94% HDI bounds for top 5 coefficients.

	Gaussian Prior		**Laplace Prior**		**Horseshoe Prior**	
Dimension	Mean	94% HDI	Mean	94% HDI	Mean	94% HDI
β_1	1.044	$[0.853, 1.251]$	1.005	$[0.801, 1.191]$	0.808	$[0.664, 0.958]$
β_4	-0.855	$[-1.081, -0.616]$	-0.841	$[-1.074, -0.627]$	-0.705	$[-0.874, -0.537]$
β_9	-0.673	$[-0.913, -0.424]$	-0.628	$[-0.881, -0.402]$	-0.451	$[-0.619, -0.279]$
β_0	-0.626	$[-0.745, -0.505]$	-0.607	$[-0.735, -0.501]$	-0.500	$[-0.590, -0.401]$
β_{20}	0.648	$[0.394, 0.904]$	0.598	$[0.351, 0.840]$	0.422	$[0.230, 0.620]$

3.7 Performance on Binary Sub-task

Table 4. Bayesian results on the binary 3-vs-8 test set.

Model	Test Accuracy	Log-Loss	Shrinkage Character
Gaussian Prior	0.9378	0.1459	Uniform, smooth
Laplace Prior	0.9330	0.1452	Sparse, sharp
Horseshoe Prior	0.9234	0.1525	Adaptive (see caveat above)

All three priors achieve log-loss near 0.15, an order of magnitude better than Ridge LR's 0.390 on the 10-class task—unsurprising given the easier binary problem and the PCA dimensionality reduction. The Gaussian prior wins on accuracy (0.9378) while the Laplace prior wins marginally on log-loss (0.1452). The Horseshoe underperforms both, almost certainly reflecting the convergence issues noted above rather than any inherent weakness of adaptive shrinkage.

3.8 Shrinkage Comparison



Figure 5: Sorted $|\hat{\beta}_q|$ (posterior mean) across 30 PCA dimensions. **Gaussian:** smooth exponential decay—uniform shrinkage. **Laplace:** steeper initial drop, concentrating weight on the top "stroke-relevant" PCA directions. **Horseshoe:** pronounced spike-and-slab profile—near-zero shrinkage on dominant components, complete shrinkage on the rest.

3.9 Uncertainty for Difficult Examples

We identify the most uncertain test examples by sorting on $\hat{\sigma}_i$, the posterior predictive standard deviation computed from the $S = 2{,}000$ posterior samples of the Gaussian-prior model. This is fundamentally different from ranking by $|\hat{p}_i - 0.5|$, which uses only the point estimate.

Table 5. Five most uncertain predictions (Gaussian prior).

Rank	True label	$\hat{p}_i$	$\hat{\sigma}_i$	Predicted	Correct?
1	Digit 8	0.479	0.386	0	No
2	Digit 3	0.422	0.283	0	Yes
3	Digit 8	0.915	0.275	1	Yes
4	Digit 3	0.475	0.236	0	Yes
5	Digit 3	0.584	0.214	1	No

Note that example 3 has a high point estimate (0.915) yet still large posterior uncertainty (0.275)—the posterior is concentrated on the correct class but with meaningful spread. Three of the five most uncertain predictions are nevertheless correct, which illustrates the value of $\hat{\sigma}_i$: it flags ambiguous inputs regardless of whether the point estimate happens to land on the right side of 0.5.

4 Part D : Compare and Contrast

4.1 Which Model Performed Best as a Classifier?

On the 10-class test set, **RBF SVM** achieves the highest accuracy (0.961; SE $\approx$ 0.006), followed by Ridge LR (0.888; SE $\approx$ 0.010) and Elastic Net (0.877). The unpenalised logistic baseline (0.863) is noticeably worse, confirming that regularisation helps at $p/n \approx 0.2$. On the binary 3-vs-8 task, the Bayesian Gaussian prior wins (0.9378).

4.2 Did the Best Classifier Provide the Best Probabilistic Fit?

No. RBF SVM yields no calibrated probabilities. Among models that do, **Ridge LR** achieves the lowest log-loss (0.390) on the 10-class task. This is expected: multinomial logistic regression maximises the conditional log-likelihood, so minimising log-loss is its training objective; SVMs optimise the hinge loss, which has no direct connection to probability calibration.

4.3 Ridge vs. Lasso

Aspect	Ridge ($C = 0.01$)	Lasso ($C = 0.01$)
Test Accuracy	0.888	0.783
Log-Loss	0.390	1.124
Sparsity	0% (all non-zero)	High (most coefficients zero)
Stability	Handles correlated features well	Unstable with correlated pixels

At this strong regularisation strength ($C = 0.01$), Lasso's aggressive sparsity hurts accuracy. MNIST pixels are strongly correlated (adjacent pixels form smooth strokes), which favours Ridge. With a weaker penalty (larger C from grid search), Lasso accuracy improves to ~ 0.90, but the coefficient maps become less visually instructive about the sparsity mechanism. Elastic Net ($C = 0.1$, accuracy 0.877) demonstrates the practical middle ground: partial sparsity with some of Ridge's stability.

4.4 SVM vs. Multinomial Logistic Regression

Aspect	Logistic Regression	SVM
Training objective	Log-likelihood (probabilistic)	Margin maximisation (geometric)
Output	Calibrated probabilities	Hard labels
Loss	Cross-entropy	Hinge loss
Which samples matter	All, weighted by residuals	Support vectors only

The RBF SVM's advantage comes from two sources: (a) the implicit infinite-dimensional feature map captures non-linear structure that no linear model can represent; and (b) the best RBF result chose $C = 10$, the weakest regularisation in the grid, suggesting the data supports a complex decision boundary. To achieve this separation, the RBF SVM relies on **2,223 support vectors** (approximately 55% of the 4,000-sample training set), which is typical for MNIST-like data where the margin requires a dense geometric covering of the sample space. Logistic regression uses all samples (weighted by residuals) and its probabilistic output is indispensable when prediction confidence is needed downstream.

4.5 Gaussian vs. Laplace Priors as Bayesian Analogues

At the MAP level, Bayesian-with-Gaussian $\approx$ Ridge and Bayesian-with-Laplace $\approx$ Lasso (exactly equal only with a flat intercept prior; our weakly informative $\mathcal{N}(0, 10)$ intercept introduces negligible shrinkage). Empirically, on the binary 3-vs-8 task the Gaussian and Laplace posteriors agree to within 0.5 percentage points of accuracy and within 0.001 of log-loss—the ordering on log-loss actually reverses (Laplace 0.1452 vs. Gaussian 0.1459), though the difference is well within Monte Carlo noise.

The Bayesian framework adds three things the penalties cannot:

1. **Full posterior:** credible intervals on each β_q, not just a point estimate.
2. **Predictive uncertainty:** $\hat{\sigma}_i$ measures per-sample ambiguity, directly usable for flagging uncertain predictions (see Table 5).
3. **Adaptive shrinkage (Horseshoe):** neither Ridge nor Lasso adapts penalty strength per coefficient. The Horseshoe does, leaving dominant PCA directions essentially unpunished while aggressively shrinking noise directions—though this flexibility comes at the cost of much harder posterior geometry, as our convergence diagnostics demonstrated.

4.6 Role of Regularisation in Classification

Regularisation serves three complementary functions:

1. **Variance reduction:** shrinking $\|\beta\|$ prevents overfitting. Ridge LR (0.888) outperforms unpenalised LR (0.863) by 2.5 percentage points. Lasso at the same C sacrifices accuracy (0.783) because the strong ℓ_1 penalty over-sparsifies the correlated pixel features.
2. **Feature selection:** Lasso and Horseshoe identify which pixel or PCA dimensions are discriminative.
3. **Prior belief encoding:** in the Bayesian view, regularisation is a formal statement about plausible coefficient magnitudes before observing data.

The *form* of regularisation matters as much as its strength: the RBF SVM achieves the best accuracy by choosing a richer hypothesis class (implicit infinite-dimensional feature map via the RBF kernel) with the weakest per-grid-point regularisation ($C = 10$), not by stronger penalisation of a linear model.

5 MLOps Hygiene and Reproducibility

Key settings, reported for reproducibility:

Setting	Value
Random seed	42 (all splits, solvers, NUTS sampler)
Sample size	5,000 stratified from MNIST-70k
Train/test split	80 / 20 (4,000 / 1,000)
CV	5-fold GridSearchCV, scoring = accuracy
Preprocessing	`Pipeline(StandardScaler, model)` inside every fold
PyMC sampler	NUTS, draws = 1000, tune = 500, cores = 2
Horseshoe-specific	`target_accept = 0.9`, non-centred parameterisation
PCA (Part C)	$Q = 30$ components, explained variance = 0.607

Software: scikit-learn ≥ 1.5 (all deprecated `multi_class='multinomial'` arguments have been removed; the code is forward-compatible with 1.7+), PyMC ≥ 5, ArviZ, NumPy, Matplotlib, Seaborn.

Convergence: for each Bayesian model the notebook prints $\hat{R}$, ESS, and divergence count via `az.summary`; values are reported in Section 3.4. All figures are saved automatically to `outputs/`. The notebook is fully reproducible with Run All.

6 References

- LeCun, Y., Bottou, L., Bengio, Y., & Haffner, P. (1998). Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11), 2278-2324.
- Piironen, J., & Vehtari, A. (2017). Sparsity information and regularization in the horseshoe and other shrinkage priors. *Electronic Journal of Statistics*, 11(2), 5018-5051.