

# C++ Classes

## C++ Interlude 1

# A Problem to Solve

- Consider a video game where a character carries three types of boxes
  - Plain box
  - Toy box
  - Magic box
- Plain box design
  - Get and Set public methods

# A Problem to Solve

```
1  /** @file PlainBox.h */
2
3  #ifndef PLAIN_BOX_
4  #define PLAIN_BOX_
5
6  // Set the type of data stored in the box
7  typedef double ItemType;
8  // Declaration for the class PlainBox
9  class PlainBox
10 {
11     private:
12         // Data field
13         ItemType item;
14
15     public:
```

LISTING C1-1 The header file for the class PlainBox



# A Problem to Solve

```
14
15 public:
16     // Default constructor
17     PlainBox();
18
19     // Parameterized constructor
20     PlainBox(const ItemType& theItem);
21
22     // Method to change the value of the data field
23     void setItem(const ItemType& theItem);
24
25     // Method to get the value of the data field
26     ItemType getItem() const;
27 }; // end PlainBox
28 #endif
```

LISTING C1-1 The header file for the class **PlainBox**

# A Problem to Solve

- Elements of the class
  - Private data fields
  - Constructors, destructors
  - Methods
  - Use of `#ifndef` , `#define` , and `#endif` preprocessor directives
  - Use of initializers
  - Use of `typedef`
  - Inheritance

# A Problem to Solve

```
1  /** @file PlainBox.cpp */
2
3  #include "PlainBox.h"
4
5  PlainBox::PlainBox()
6  {
7  } // end default constructor
8  PlainBox::PlainBox(const ItemType& theItem)
9  {
10     item = theItem;
11 } // end constructor
12 void PlainBox::setItem(const ItemType& theItem)
13 {
14     item = theItem;
15 } // end setItem
16
17 ItemType PlainBox::getItem() const
18 {
19     return item;
20 } // end getItem
```

LISTING C1-2 Implementation file for the PlainBox class



# A Problem to Solve

```
1  /** @file PlainBox.h */
2
3  #ifndef PLAIN_BOX_
4  #define PLAIN_BOX_
5
6  template<class ItemType> // Indicates this is a template definition
7
8  // Declaration for the class PlainBox
9  class PlainBox
10 {
11     private:
12         // Data field
13         ItemType item;
14     public:
15         // Default constructor
16         PlainBox();
```

LISTING C1-3 Template header file for the PlainBox class

# A Problem to Solve

```
16 PlainBox();  
17  
18 // Parameterized constructor  
19 PlainBox(const ItemType& theItem);  
20  
21 // Mutator method that can change the value of the data field  
22 void setItem(const ItemType& theItem);  
23  
24 // Accessor method to get the value of the data field  
25 ItemType getItem() const;  
26 }; // end PlainBox  
27  
28 #include "PlainBox.cpp" // Include the implementation file  
29 #endif
```

LISTING C1-3 Template header file for the PlainBox class



# A Problem to Solve

```
1  /** @file PlainBox.cpp */
2  #include "PlainBox.h"
3
4  template<class ItemType>
5  PlainBox<ItemType>::PlainBox()
6  {
7  } // end default constructor
8
9  template<class ItemType>
10 PlainBox<ItemType>::PlainBox(const ItemType& theItem) : item(theItem)
11 {
12 } // end constructor
13
```

LISTING C1-4 Implementation file for the PlainBox template class

# A Problem to Solve

```
13
14  template<class ItemType>
15  void PlainBox<ItemType>::setItem(const ItemType& theItem)
16  {
17      item = theItem;
18  } // end setItem
19
20  template<class ItemType>
21  ItemType PlainBox<ItemType>::getItem() const
22  {
23      return item;
24  } // end getItem
```

LISTING C1-4 Implementation file for the PlainBox template class

# Base Classes and Derived Classes

- Use PlainBox as a base class , or superclass
- The ToyBox class is the derived class , or subclass , of the PlainBox
- Derived class inherits
  - All the members of its base class,
  - (Except the constructors and destructor)



# Base Classes and Derived Classes

```
1  /** @file ToyBox.h */
2
3  #ifndef TOY_BOX_
4  #define TOY_BOX_
5  #include "PlainBox.h"
6
7  enum Color {BLACK, RED, BLUE, GREEN, YELLOW, WHITE};
8
9  template<class ItemType>
10 class ToyBox : public PlainBox<ItemType>
11 {
12 private:
13     Color boxColor;
14
15 public:
16     ToyBox();
17     ToyBox(const Color& theColor);
18     ToyBox(const ItemType& theItem, const Color& theColor);
19     Color getColor() const;
20 }; // end ToyBox
21 #include "ToyBox.cpp"
22 #endif
```

LISTING C1-5 Template header file for the class **ToyBox**

# Base Classes and Derived Classes

```
1  /** @file ToyBox.cpp */
2
3  #include "ToyBox.h"
4
5  template<class ItemType>
6  ToyBox<ItemType>::ToyBox() : boxColor(BLACK)
7  {
8  } // end default constructor
9
10 template<class ItemType>
11 ToyBox<ItemType>::ToyBox(const Color& theColor) : boxColor(theColor)
12 {
13 } // end constructor
14
15 template<class ItemType>
16 ToyBox<ItemType>::ToyBox(const ItemType& theItem, const Color& theColor)
17                        : PlainBox<ItemType>(theItem), boxColor(theColor)
18 {
19 } // end constructor
20
21 template<class ItemType>
22 Color ToyBox<ItemType>::getColor() const
23 {
24     return boxColor;
25 } // end getColor
```

LISTING C1-6 Implementation file for the class **ToyBox**



# Overriding Base-Class Methods

- You can add as many new members to derived class as desired
- You can redefine inherited methods
  - Called overriding a base-class method.
- A method overrides a base-class method when
  - The two methods have the same name and parameter declarations



# Overriding Base-Class Methods

```
1  /** @file MagicBox.h */
2
3  #ifndef MAGIC_BOX_
4  #define MAGIC_BOX_
5  #include "PlainBox.h"
6
7  template<class ItemType>
8  class MagicBox: public PlainBox<ItemType>
9  {
10 private:
11     bool firstItemStored;
12
13 public:
14     MagicBox();
15     MagicBox(const ItemType& theItem);
16     void setItem(const ItemType& theItem);
17 }; // end MagicBox
18 #include "MagicBox.cpp"
19 #endif
```

LISTING C1-7 Header file for the class **MagicBox**

# Overriding Base-Class Methods

```
1  /** @file MagicBox.cpp */
2  #include "MagicBox.h"
3  template<class ItemType>
4  MagicBox<ItemType>::MagicBox(): firstItemStored(false)
5  {
6      // PlainBox constructor is called implicitly.
7      // Box has no magic initially
8  } // end default constructor
9
10 template<class ItemType>
11 MagicBox<ItemType>::MagicBox(const ItemType& theItem): firstItemStored(false)
12 {
13     // Box has no magic initially
14     setItem(theItem); // Calls MagicBox version of setItem
15     // Box has magic now
16 } // end constructor
17
18 template<class ItemType>
19 void MagicBox<ItemType>::setItem(const ItemType& theItem)
20 {
21     if (!firstItemStored)
22     {
23         PlainBox<ItemType>::setItem(theItem);
24         firstItemStored = true; // Box has magic now
25     } // end if
26 } // end setItem
```

LISTING C1-8 Implementation file for the class **MagicBox**



# Virtual Methods, Abstract Classes

- Using keyword **virtual** in front of the prototype
  - Tells the C++ compiler that the code this method executes is determined at runtime
- Pure virtual method
  - Virtual method that has no implementation
- Abstract class
  - Has at least one pure virtual method



# Virtual Methods, Abstract Classes

```
1  /** @file BoxInterface.h */
2
3  #ifndef BOX_INTERFACE_
4  #define BOX_INTERFACE_
5
6  template <class ItemType>
7  class BoxInterface
8  {
9  public:
10     virtual void setItem(const ItemType& theItem) = 0;
11     virtual ItemType getItem() const = 0;
12     virtual ~BoxInterface() {} // C++ Interlude 2 explains virtual destructors
13 }; // end BoxInterface
14 #endif
```

LISTING C1-9 An abstract class that is an interface for the ADT box



# End

## Interlude 1