

You are logged in as [C. O'Keefe](#) ([Logout](#))

# Core Ruby 41st Batch

Home ► PORPC101-41C ► 12 April - 18 April ► Some useful Ruby methods

## Navigation

Home

■ My home

Site pages

My profile

Current course


PORPC101-41C


Participants


General


5 April - 11 April

12 April - 18 April

 Week 2: Tutorial


 Week 2:  
Exercises

 Week 2: Forum

 **Some useful  
Ruby methods**

 Recipes

 THIMK

 \*PARALLEL  
TRACK\* Learn  
basic HTML and  
CSS

 Week 2: Quiz

19 April - 25 April

26 April - 2 May

3 May - 9 May

10 May - 16 May

17 May - 23 May

24 May - 30 May

31 May - 6 June

7 June - 13 June

## Some useful Ruby methods

### Method \*

**str \* int --> string**

The \* instance method of class **String**, returns a new **String** containing int copies of the receiver. Here's an example:

```
"Ruby! " * 3 # => "Ruby! Ruby! Ruby! "
```

### slice

The **String slice** method, if passed a single **Fixnum**, returns the code of the character at that position (**whereas in version 1.9, it returns the character at the position**). If passed two **Fixnum** objects, returns a substring starting at the offset given by the first, and a length given by the second.

See the following examples:

```
a = "hello there"
a.slice(1) # => "e"
a.slice(1,3) # => "ell"
a.slice(-3,2) # => "er"
a.slice(0) # => "h"
```

### strip

**str.strip -> string**

Returns a copy of *str* with leading and trailing whitespace removed.

```
" hello ".strip #=> "hello"
```

My courses

## Settings

Course administration

My profile settings

```
"\tgoodbye\r\n".strip #=> "goodbye"
```

### count

The **Stringcount** method counts the number of occurrences of any of a set of specified characters.

```
str.count( string + ) -> int
```

Each string parameter defines a *set* of characters to count. The *intersection of these sets* defines the characters to count in str.

```
a = "hello world"
a.count "lo" #=> 5
a.count "lo", "o" #=> 2
```

### length

You (or your users) frequently misremember the name of a method. To reduce the confusion, you want to make the same method accessible under multiple names. Alternatively, you're about to redefine a method and you'd like to keep the old version available.

It's difficult to pick the perfect name for a method: you must find the word or short phrase that best conveys an operation on a data structure, possibly an abstract operation that has different "meanings" depending on context. Sometimes there will be no good name for a method and you'll just have to pick one; sometimes there will be too many good names for a method and you'll just have to pick one. In either case, your users may have difficulty remembering the "right" name of the method. You can help them out by creating aliases.

Some languages use length or len to find the length of a string, and some use size.

Do you remember how you can achieve this? Of course with **alias**. Ruby itself uses aliases in its standard library.

```
str.length -> int
```

Returns the length of str, where str is a string.

```
str.size -> int
```

Synonym for **String#length**.

Last modified: Friday, 1 June 2012, 10:08 PM

You are logged in as [C. O'Keefe](#) ([Logout](#))



© 2008-2013 RubyLearning.org : A Ruby Learning Hub