

Core Ruby 41st Batch

Home ► PORPC101-41C ► 3 May - 9 May ► Some useful Ruby methods

Navigation

Home

■ My home

Site pages

My profile

Current course

PORPC101-41C

Participants

General

5 April - 11 April


12 April - 18 April

19 April - 25 April


26 April - 2 May


3 May - 9 May

 Week 5 Tutorial

 Week 5:
Exercises

 Week 5: Forum

 L5E2 Spec
Change

 **Some useful
Ruby methods**

 Week 5: Quiz

10 May - 16 May

17 May - 23 May

24 May - 30 May

31 May - 6 June

7 June - 13 June

My courses

Settings

Course administration

Some useful Ruby methods

`obj.inspect -> string`

The **Object** class has an **inspect** method that returns a string containing a human-readable representation of obj. If not overridden, uses the **to_s** method to generate the string.

```
puts [ 1, 2, 3..4, 'five' ].inspect
```

`ObjectSpace.each_object(h class_or_mod i) { | obj | block } -> fixnum`

The Ruby runtime system needs to keep track of all known objects. This information is made accessible via the **ObjectSpace.each_object** method. It returns the number of objects found. Objects of Fixnums, Symbols, true, false, and nil are never returned.

```
ObjectSpace.each_object do |obj|
```

```
  printf "%20s: %s\n", obj.class, obj.inspect
```

```
end
```

If you specify a class or module as a parameter to **each_object**, only objects of that type will be returned.

`enum.partition { | obj | block } -> [true_array, false_array]`

The **partition** method of module **Enumerable**, divides a collection into two parts.

When **partition** is called and passed a block, it returns two arrays, the first containing the elements of **enum** for which the block evaluates to true, the second containing the rest.

```
nums = [1,2,3,4,5,6,7,8,9]
```

```
odd_even = nums.partition { |x| x%2 == 1 }
```

```
puts odd_even
```

[My profile settings](#)

enum.any? h {l obj l block } -> true or false

The quantifier method **any?** of module **Enumerable** makes it easier to test the nature of a collection.

```
nums = [1,2,3,4,5,6,7,8,9,nil]
```

```
# Are any of these numbers even?
```

```
flag = nums.any? {|x| x%2 ==0}
```

```
puts flag # true
```

It passes each element of the collection to the given block. The method returns **true** if the block ever returns a value other than **false** or **nil**. In the absence of a block, this simply tests the truth value of each element. That is, a block **{|x| x}** is added implicitly.

```
flag1 =nums.any?
```

```
# list contains at least one true value
```

```
# (non-nil or non-false)
```

```
puts flag1 # true
```

enum.all? h {l obj l block } -> true or false

The quantifier method **all?** of module **Enumerable** makes it easier to test the nature of a collection.

```
nums = [1,2,3,4,5,6,7,8,9,nil]
```

```
# Are all of these numbers even?
```

```
flag = nums.all? {|x| x%2 ==0}
```

```
puts flag # false
```

It passes each element of the collection to the given block. The method returns **true** if the block never returns **false** or **nil**. In the absence of a block, this simply tests the truth value of each element. That is, a block **{|x| x}** is added implicitly.

```
flag1 =nums.all?
```

```
# list contains no falses or nils
```

```
puts flag1 # false
```

Last modified: Friday, 22 June 2012, 10:45 PM

You are logged in as [C. O'Keefe](#) ([Logout](#))



© 2008-2013 RubyLearning.org : A Ruby Learning Hub