FORPC101-10C: Lesson 4: Quiz 2/22/09 9:40 AM



1

Marks: 1

FORPC101-10C

You are logged in as Jason Noble (Logout)

RubyCourse ► FORPC101-10C ► Quizzes ► Lesson 4: Quiz ► Attempt 1

Lesson 4: Quiz - Attempt 1

Which one of the following method is used to convert ranges to arrays?

	Choose one answer.	○ A. to_arr		
		● B. to_a		
		○ C. to_r		
		O D. rtoa		
		○ E. to_rtoa		
2	less efficient than strings.			
Marks: 1				
	Answer:	OTrue		
		● False		
3	What's the output of the following Ruby script?			
Marks: 1	r1 = "7""10"			
	r1.each { x puts x}			
	Choose one answer.	A. Prints no output		
		B. Prints four lines		

4

The IO class inherits from the File class.

FORPC101-10C: Lesson 4: Quiz 2/22/09 9:40 AM

Marks:	1	
	Answer:	True
		○ False

```
If Fred is a constant in one context, a method in another, and a class in a third, the Symbol :Fred will be different objects in all the three contexts.

Answer: True

False
```

```
What would you use if the identity of the object is important?
Marks: 1
Choose one  A. symbol answer.
B. object
C. string
```

```
8   Assume we have defined an array:

Marks: 1 array = [1, 2, 3, 4, 5, 6, 7]

What element will be retrieved by the following expression:
    array[-3]
```

FORPC101–10C: Lesson 4: Quiz 2/22/09 9:40 AM

Choose one answer.	 A. Such an expression will raise an exception. It is legal to reference array elements with positive indexes only.
	○ B. 3
	O C. 1
	D. None. Element with index "-3" is empty. nil object will be returned.
	○ E. 5

10 Marks: 1	A symbol name refers to the same object throughout a Ruby program.		
	Answer:	TrueFalse	

Save without submitting Submit all and finish

You are logged in as Jason Noble (Logout)

FORPC101-10C

© 2008-2009 RubyLearning.org: A Ruby Learning Hub

Sunday, February 22, 2009 20:09 hrs India Time