BANGLAMARK Multicrop Combine Harvester
BM-52
70HP & Grain Tank 950L

BANGLAMARK

GLAMAR BM-52

BM-52

SPECIFICATION:

ITEM		PARAMETER
Brand		BANGLAMARK
Model		BM-52
Feeding Capacity	(kg/s)	3
Overall Dimension Length×Width×Heights	(mm)	4300×1980×2675
Weight	(kg)	2360
Productivity of Operating Hours	(hm²/h)	0.27 ～0.48
Engine	Engine Model	YN4H565-34VE Stage III Engine
	Rated Power) (kW/hp)	51KW/70HP
	Engine Type	Water-Cooled, 4-Cylinder, DI-Injection, Vertical Diesel.
	Rated Rotation Speed (r/min)	2400
	Fuel consumption (kg/hm²)	20
Driving System	Type of Gearbox	Hydraulic type + HST(3F, 3R)
	Steering	Clutch and Brake.
	Type of Brake	By Foot.
Traveling System	Rubber Track (mm)	400 x 90 x 46
	Gauge	920
	Track ground pressure	20
	Theoretical Operating Speed (km/h)	0～5.2
	Minimum Ground Clearance (mm)	280
Cutting header	Height Adjustment	Hydaulics.
	Cutting Width (mm) (mm)	1550
	Type of Blade	VI Type / Left and Right.
	Type of Header Auger	Telescopic Screw Conveying.
	Pickup Reel	Eccentric Tooth(off-centre), Diameter 823mm, Qty 5 pcs.
Threshing System	Threshing System	Spiked Tooth Axial Flow
	Threshing Cylinder Quantity	1
	Cylinder Diameter×Length (mm)	φ540 x 1521
	Concave sieve	Grid type, 4 pcs
	Cleaning Mechanism Type	Air and Screen Cleaning, Vibrating Sieve adjustable
	Fan	Centrifugal Type, Diameter 350, Qty 1 pcs
Grain Storing	Automatic Unloading	Grain Tank Capacity 950L with 360° Unloading Auger

*Note: Single Threshing Drum & Double Threshing Drum are available with suitable hp based on customer demand.