title: BTC Short Premium Agent — â®#ãŽ â>0á® ä %ã fÆðw
author: Trading Desk Documentation
date: June 2026

BTC Short Premium Agent

â®#ãŽ â>0á® áþ5ä âÞ#äÎ ã Ià~+â   ä %ã fÆðw à 2â> ã> ã.

ä. â>@àŽ á^L · btc-short-premium-agent
Deploy · https://btc-short-premium-agent.vercel.app/
Repo · Bankshadow/btc-short-premium-agent
**â¾%ã à 2â2¢¢ r   æ Ç—6—2ÖöæÇ' r aper trading · Human approval

1. â¾%ã à 2â>*ã> ã

â¾%ã à 2â2 r   â~2â +â 2â
Analysis-only · á~8à   vVçB ò Væv–æR Câ¾IàN3ä ã ã2 Dâ H execute àŽ#ãN á® exchange
Human approval · TRADE = á^IâÞ â 5â ãŽ)â.LâÞ ãŽ!ã ãN äŽ-áž@á~#áN â>4àp
Paper trading · àŽ3â^-à~-âÞ@áN-â>Lä> browser (+ sync Supabase äN ä'•
Risk veto · Risk Manager â 5â®4á~ ãNL veto àN ã â>#â ã.#
Memory / draft rules · ä ã ã> ã. á¾#ã 'ã ãB r Dâ H override hard no-trade rules

2. â®#ãŽ MVP á~5äŽ ã>Aâ^Iâp

MVP · áþ5ä âÞ#äÎ+â^1à
1 · Playbook engine 6 à.1äž , 8-check framework, no-trade rules, combination read
2 · Bull/Bear thesis, Spot/Futures/Options, Risk Manager, Investment Committee
3 · Decision log, resolve outcome, reflection, scoreboard, draft rules
4 · Desk memory àŽ2à ¦÷W nal + pinned notes !' inject ä äž2 agents
5 · Research: Market Data, Regime, Data Quality, Macro & News, ETH/BTC
6 · Portfolio milestones, session replay, journal Supabase sync, cron briefing
9 · Risk profile, alerts/webhooks, LLM narrator, operator override, desk APIs
**â^Hã.*ãŽ ** · Aggressive risk mode, paper API sync, ä -ã" Ö 7&òôFW ivatives UI âÞ-à
ä áž ã äN : MVP 7 (presets), MVP 8 (backtest â^6à Â 6 Æ–' ation export)

3. â® ã. ã â. â>#â #ã ã â®9àp

```
[Browser Dashboard]
    %   localStorage (log, paper, settings)
    %¼
[Next.js API] % % %º /api/analyze, /api/market, /api/paper/*, /api/journal/sync
    %
    % % % %º Playbook Engine (6 steps)
    % % % %º Multi-Agent Desk
    % % % %º Desk Narrator (MVP 9)

[External]
    Bybit Public API · Supabase · Telegram · Webhooks/Discord
```

4. Flow â¾%ã : ä ãN ä 'ä~ !' Analyze âÞ1á^Báž!ã ã@

1. áÎ9äžCà®Iä ãN â¾ äž2 (`macroView` ä #ãNHâ äž bearish)
2. Dashboard ä.+â^ journal, paper, settings àŽ2à Æö6 Å7F÷ age
3. Auto refresh á~8à   ò 2 ò R ã. ãR ŽDâ Há^IâÞ à   Analyze)
4. áN6àr UD, V÷FR ã. `GET /api/market` (ánIã.DáNI)
5. `POST /api/analyze` â®Hàs deskMemory, deskRiskProfile, ethQuote
6. Server áN6àr '–&—B Ž+â>7âÞCà®Ià.IâÞ!ãž%àŽ2à 6Æ–VçB äž2 server â^Iâ •
7. â>1á' Æ ybook engine !' Multi-agent desk !' Desk narrator
8. á®1áž ãn decision log + replay snapshot
9. ánIã" 6öÖÖ—GFVR TRADE + auto-open !' ä ãN paper order !' sync cloud

5. Flow: POST /api/analyze (â 2â.Cá'•

â^3áN1á¢ r   ã Iáž âÞ
1 · Normalize request (macro, overrides àNHã.@â>4äŽ!á^Iá'Â isk profile, memory)
2 · áN6àrþ#ã à.IâÞ!ãž%á^%ã. (Bybit)

3 · **runDecisionEngine** — 6 steps
4 · **runTradingDesk** — agents á^2â — VÆ–æP
5 · **enrichAnalyzeWithMvp9** — desk narrator
6 · â®Hàr ¥4ôâ â^1á¢ F 6†&ö &@

Playbook 6 à.1äž

1. Market snapshot
2. Eight-check framework
3. No-trade rules (hard skip)
4. Combination read
5. Verdict (TRADE / SKIP / WAIT) + confidence
6. Action plan (sell_call / sell_put / no_trade)

6. Flow: Multi-Agent Desk

â^3áN1á¢ — VÆ–æR …T' vVçB &÷7FW"“

```
Research Layer (MVP 5)
  !' Market Data !' Regime !' Data Quality !' Macro & News
Desk Memory (MVP 4)
Thesis
  !' Bull Thesis !' Bear Thesis
Strategies
  !' Spot !' Futures !' Options
Risk Manager (veto äN ä'•
Investment Committee !' TRADE | SKIP | WAIT
```

Committee áî4àŽ2â> ã. ã. :

- Majority à.-àr 7 ÷B ò gWGW&W2 ò ÷ F–öç2
- Risk Manager veto (hard rules, IV/HV, liquidation, macro…)
- Data quality score
- ä.+â aggressive (MVP 9): ä -á' TRADE ä !ã~HâÒ Æ ybook â®-áN â^lâÞ

7. Flow: Paper Trading

```
Analyze ä *â>Gà€
    %
    % %  Committee TRADE + autoOpenOnTrade !' â®#äž2àr    W" ÷&FW" ƒ  -âÞ@áN-â>Lä  ãN /àN#ã Iàr•
    %        % %  POST /api/paper/sync !' Supabase
    %
    % %  Committee SKIP/WAIT + â 5âÞ-ä  âÞ#äÎ@á¾4áB  "  WFòÖ6Æ÷6P
    %        % %  Sync PnL !' decision log
    %
    % %  á¾4áN!ã~- !' close + sync log
```

- GET `/api/paper/orders?status=open` — áN6à~-âÞ@áN-â>Lä ãN àŽ2à 6Æ÷VB
- Checkbox: Auto-open on TRADE, Mark-to-market, Sync to cloud

8. Flow: à 2â>@â>5â. â>9ä' „Õe 2•

```
Decision Log (á~8à   æ Ç–¦R•
    !' Resolve outcome (â 7âÒ'  " &VfÆV7F–öâ  vVç@
    !' Draft rules (advisory)
    !' Agent scoreboard
    !' Replay panel (snapshot â.IâÞ â¾%ã   äN!äŽ#ã   engine ä>+â H)
    !' Journal sync Supabase (optional)
```

9. Flow: Cron / ä äž ä ã~-á•

```
Vercel Cron !' GET /api/cron/analyze (+ CRON_SECRET)
    !' runAnalyzeRequest
    !' á®1äž ãn  analysis_runs (Supabase)
    !' Telegram (template á^2â  fW&F–7BÂ  V–WB †÷W'2 ##£  c ƒ£   $´²•
    !' DESK_WEBHOOK_URL (JSON event)
    !' DISCORD_WEBHOOK_URL (optional)
```

- Quiet hours: äN!ä, –ær ã Hâ~Dá¾ â^2à~ ã~ â. ä 'äž veto / TRADE ä ä~!
- Test: Operations !' Test automation â¾#ã~- `POST /api/alerts/test`

10. â¾ äž2 UI (Trading Floor)

ä. á' r +ážlã. ã^H
Top bar · â® ã. ã FW6²Â 6÷VçFFðwn refresh, toggle auto-refresh

Sidebar · Live BTC/ETH, analysis alerts
Main · Milestones, Paper trading, Trading desk, Narrator, Replay, Log preview
Operations · Operator (MVP 9), journal sync, scoreboard, log, rules, cron test

äN!äŽ!ã^ ãŽHâ æ Ç— e — desk â>1áž-ã ä. â 1á^4

11. API á~1äž â¾!á@

Endpoint · â¾ äž2á~5ä€
`POST /api/analyze` · Engine + desk + narrator
`GET /api/market` · BTC/ETH spot
`GET/POST /api/paper/sync` · Sync paper orders
`GET /api/paper/orders?status=open` · âÞ-ä âÞ#äÂ õ Tà
`GET/POST /api/journal/sync` · Decision log cloud
`GET /api/cron/analyze` · Cron + test
`GET /api/desk/status` · â® ã. ã –çFVprations
`GET /api/desk/health` · Health snapshot
`POST /api/alerts/test` · á~ â®-á¢ Telegram/Discord
`GET /api/admin/automation-status` · Cron/Telegram configured?

12. à.IâÞ!ãž% & Storage

á~5äŽ@à Gá¢ r @áž7äž-â¾2
localStorage · decision log, paper orders, desk settings, operator overrides, pins
Supabase · analysis_runs, paper_orders, decision_log_entries
Env · SUPABASE_*, CRON_SECRET, TELEGRAM_*, DESK_WEBHOOK_URL, OPENAI_API_KEY

Migrations: `001` !' `002` !' `003` ä> `supabase/migrations/`

13. Risk Profile (MVP 9)

ä.+â · áî$á^4à #â>!
aggressive (àNHã.@â>4äŽ!á^Iá'' r 6öÖÖ—GFVRöVæv–æR #ã TRADE à~Hã."à.6äž
balanced · ä> â^I playbook ä äž!à~'á@

á^1äž ä> Operations !' â®Hàr FW6µ&—6µ &öf–ÆV ãŽ analyze

14. Environment Variables

Variable · ä> äž*ã>+â>1á
`SUPABASE_URL` · Cloud storage
`SUPABASE_SERVICE_ROLE_KEY` · Server sync
`CRON_SECRET` · Cron auth
`TELEGRAM_BOT_TOKEN` / `TELEGRAM_CHAT_ID` · Alerts
`DESK_WEBHOOK_URL` · Webhook â¾%ã cron
`DISCORD_WEBHOOK_URL` · Discord (optional)
`DESK_RISK_PROFILE` · Server default risk
`DESK_ALERT_QUIET_HOURS` · `false` = á¾4áB V–WB †÷W'0
`OPENAI_API_KEY` · LLM narrator (optional)
`OPENAI_MODEL` · Default gpt-4o-mini

15. â®4äŽ á~5äŽ#ã á®Dâ Há~3

- äN!ä, Æ 6Rö6 æ6VÂ -âÞ@áN-â>LàŽ#ãN á® Bybit
- äN!ä, WFò×G ade àŽ#ãN àŽ2à 6öÖÖ—GFVR TRADE (â 5ä ä, W"'
- Operator override / draft rules äN!äŽ@á¾%ã^Hâ. Risk veto
- Macro desk / Derivatives manual overrides án9à @âÞ2âÞ-à ã. UI

16. ä áž ã áž2án1áNDá°

- MVP 7: Desk presets, health dashboard â^0ä -ã^"áB
- MVP 8: Backtest áÎHã. historical runs, calibration report, ETH correlation v2

*ä -à *ã.#áž5äž*â>Iã. àŽ2à *án2áž0 codebase â¾%ã MVP 9 — Analysis only, no live execution.*