ACES Managed Services
Complete Source Code Export

Generated 2026-08-23

Included:

- ACES Technician App (Expo / React Native)
- ACES Web Portal (React / Vite)
- API Server (Express / TypeScript)
- Shared API contracts, generated clients, and database schema

This PDF contains editable text source. Dependencies, build output,
binary assets, private keys, and credential files are intentionally omitted.

Use the file inventory after this page to locate each source file.

FILE INVENTORY

The following source files are included in this export:

001 App.js
002 app.json
003 app/_layout.tsx
004 app/index.tsx
005 artifacts/api-server/.replit-artifact/artifact.toml
006 artifacts/api-server/build.mjs
007 artifacts/api-server/package.json
008 artifacts/api-server/src/__tests__/technician-token.test.ts
009 artifacts/api-server/src/app.ts
010 artifacts/api-server/src/index.ts
011 artifacts/api-server/src/lib/logger.ts
012 artifacts/api-server/src/lib/objectAcl.ts
013 artifacts/api-server/src/lib/objectStorage.ts
014 artifacts/api-server/src/lib/startup-seed.ts
015 artifacts/api-server/src/lib/sync-scheduler.ts
016 artifacts/api-server/src/lib/techToken.ts
017 artifacts/api-server/src/routes/admins.ts
018 artifacts/api-server/src/routes/dashboard.ts
019 artifacts/api-server/src/routes/drivers.ts
020 artifacts/api-server/src/routes/generators.ts
021 artifacts/api-server/src/routes/health.ts
022 artifacts/api-server/src/routes/index.ts
023 artifacts/api-server/src/routes/missions.ts
024 artifacts/api-server/src/routes/notifications.ts
025 artifacts/api-server/src/routes/seed.ts
026 artifacts/api-server/src/routes/settings.ts
027 artifacts/api-server/src/routes/sites.ts
028 artifacts/api-server/src/routes/storage.ts
029 artifacts/api-server/src/routes/technicians.ts
030 artifacts/api-server/tsconfig.json
031 artifacts/mockup-sandbox/.replit-artifact/artifact.toml
032 artifacts/mockup-sandbox/components.json
033 artifacts/mockup-sandbox/index.html
034 artifacts/mockup-sandbox/mockupPreviewPlugin.ts
035 artifacts/mockup-sandbox/package.json
036 artifacts/mockup-sandbox/src/.generated/mockup-components.ts
037 artifacts/mockup-sandbox/src/App.tsx
038 artifacts/mockup-sandbox/src/components/ui/accordion.tsx
039 artifacts/mockup-sandbox/src/components/ui/alert-dialog.tsx
040 artifacts/mockup-sandbox/src/components/ui/alert.tsx
041 artifacts/mockup-sandbox/src/components/ui/aspect-ratio.tsx
042 artifacts/mockup-sandbox/src/components/ui/avatar.tsx
043 artifacts/mockup-sandbox/src/components/ui/badge.tsx
044 artifacts/mockup-sandbox/src/components/ui/breadcrumb.tsx
045 artifacts/mockup-sandbox/src/components/ui/button-group.tsx
046 artifacts/mockup-sandbox/src/components/ui/button.tsx
047 artifacts/mockup-sandbox/src/components/ui/calendar.tsx
048 artifacts/mockup-sandbox/src/components/ui/card.tsx

```
049 artifacts/mockup-sandbox/src/components/ui/carousel.tsx
050 artifacts/mockup-sandbox/src/components/ui/chart.tsx
051 artifacts/mockup-sandbox/src/components/ui/checkbox.tsx
052 artifacts/mockup-sandbox/src/components/ui/collapsible.tsx
053 artifacts/mockup-sandbox/src/components/ui/command.tsx
054 artifacts/mockup-sandbox/src/components/ui/context-menu.tsx
055 artifacts/mockup-sandbox/src/components/ui/dialog.tsx
056 artifacts/mockup-sandbox/src/components/ui/drawer.tsx
057 artifacts/mockup-sandbox/src/components/ui/dropdown-menu.tsx
058 artifacts/mockup-sandbox/src/components/ui/empty.tsx
059 artifacts/mockup-sandbox/src/components/ui/field.tsx
060 artifacts/mockup-sandbox/src/components/ui/form.tsx
061 artifacts/mockup-sandbox/src/components/ui/hover-card.tsx
062 artifacts/mockup-sandbox/src/components/ui/input-group.tsx
063 artifacts/mockup-sandbox/src/components/ui/input-otp.tsx
064 artifacts/mockup-sandbox/src/components/ui/input.tsx
065 artifacts/mockup-sandbox/src/components/ui/item.tsx
066 artifacts/mockup-sandbox/src/components/ui/kbd.tsx
067 artifacts/mockup-sandbox/src/components/ui/label.tsx
068 artifacts/mockup-sandbox/src/components/ui/menubar.tsx
069 artifacts/mockup-sandbox/src/components/ui/navigation-menu.tsx
070 artifacts/mockup-sandbox/src/components/ui/pagination.tsx
071 artifacts/mockup-sandbox/src/components/ui/popover.tsx
072 artifacts/mockup-sandbox/src/components/ui/progress.tsx
073 artifacts/mockup-sandbox/src/components/ui/radio-group.tsx
074 artifacts/mockup-sandbox/src/components/ui/resizable.tsx
075 artifacts/mockup-sandbox/src/components/ui/scroll-area.tsx
076 artifacts/mockup-sandbox/src/components/ui/select.tsx
077 artifacts/mockup-sandbox/src/components/ui/separator.tsx
078 artifacts/mockup-sandbox/src/components/ui/sheet.tsx
079 artifacts/mockup-sandbox/src/components/ui/sidebar.tsx
080 artifacts/mockup-sandbox/src/components/ui/skeleton.tsx
081 artifacts/mockup-sandbox/src/components/ui/slider.tsx
082 artifacts/mockup-sandbox/src/components/ui/sonner.tsx
083 artifacts/mockup-sandbox/src/components/ui/spinner.tsx
084 artifacts/mockup-sandbox/src/components/ui/switch.tsx
085 artifacts/mockup-sandbox/src/components/ui/table.tsx
086 artifacts/mockup-sandbox/src/components/ui/tabs.tsx
087 artifacts/mockup-sandbox/src/components/ui/textarea.tsx
088 artifacts/mockup-sandbox/src/components/ui/toast.tsx
089 artifacts/mockup-sandbox/src/components/ui/toaster.tsx
090 artifacts/mockup-sandbox/src/components/ui/toggle-group.tsx
091 artifacts/mockup-sandbox/src/components/ui/toggle.tsx
092 artifacts/mockup-sandbox/src/components/ui/tooltip.tsx
093 artifacts/mockup-sandbox/src/hooks/use-mobile.tsx
094 artifacts/mockup-sandbox/src/hooks/use-toast.ts
095 artifacts/mockup-sandbox/src/index.css
096 artifacts/mockup-sandbox/src/lib/utils.ts
097 artifacts/mockup-sandbox/src/main.tsx
098 artifacts/mockup-sandbox/tsconfig.json
099 artifacts/mockup-sandbox/vite.config.ts
100 artifacts/technician-app/.replit-artifact/artifact.toml
```

artifacts/technician-app/app.json
artifacts/technician-app/app/(tabs)/_layout.tsx
artifacts/technician-app/app/(tabs)/index.tsx
artifacts/technician-app/app/(tabs)/notifications.tsx
artifacts/technician-app/app/(tabs)/profile.tsx
artifacts/technician-app/app/+not-found.tsx
artifacts/technician-app/app/_layout.tsx
artifacts/technician-app/app/index.tsx
artifacts/technician-app/app/login.tsx
artifacts/technician-app/app/mission/[id].tsx
artifacts/technician-app/babel.config.js
artifacts/technician-app/components/ErrorBoundary.tsx
artifacts/technician-app/components/ErrorFallback.tsx
artifacts/technician-app/components/KeyboardAwareScrollViewCompat.tsx
artifacts/technician-app/constants/colors.ts
artifacts/technician-app/contexts/auth.tsx
artifacts/technician-app/eas.json
artifacts/technician-app/expo-env.d.ts
artifacts/technician-app/google-services.json
artifacts/technician-app/lib/api.ts
artifacts/technician-app/lib/push.ts
artifacts/technician-app/metro.config.js
artifacts/technician-app/package.json
artifacts/technician-app/README.md
artifacts/technician-app/scripts/build.js
artifacts/technician-app/server/serve.js
artifacts/technician-app/server/templates/landing-page.html
artifacts/technician-app/tsconfig.json
artifacts/web-portal/.replit-artifact/artifact.toml
artifacts/web-portal/components.json
artifacts/web-portal/index.html
artifacts/web-portal/package.json
artifacts/web-portal/requirements.yaml
artifacts/web-portal/src/App.tsx
artifacts/web-portal/src/components/layout/AdminLayout.tsx
artifacts/web-portal/src/components/layout/DriverLayout.tsx
artifacts/web-portal/src/components/ui/accordion.tsx
artifacts/web-portal/src/components/ui/alert-dialog.tsx
artifacts/web-portal/src/components/ui/alert.tsx
artifacts/web-portal/src/components/ui/aspect-ratio.tsx
artifacts/web-portal/src/components/ui/avatar.tsx
artifacts/web-portal/src/components/ui/badge.tsx
artifacts/web-portal/src/components/ui/breadcrumb.tsx
artifacts/web-portal/src/components/ui/button-group.tsx
artifacts/web-portal/src/components/ui/button.tsx
artifacts/web-portal/src/components/ui/calendar.tsx
artifacts/web-portal/src/components/ui/card.tsx
artifacts/web-portal/src/components/ui/carousel.tsx
artifacts/web-portal/src/components/ui/chart.tsx
artifacts/web-portal/src/components/ui/checkbox.tsx
artifacts/web-portal/src/components/ui/collapsible.tsx
artifacts/web-portal/src/components/ui/command.tsx

artifacts/web-portal/src/components/ui/context-menu.tsx
artifacts/web-portal/src/components/ui/dialog.tsx
artifacts/web-portal/src/components/ui/drawer.tsx
artifacts/web-portal/src/components/ui/dropdown-menu.tsx
artifacts/web-portal/src/components/ui/empty.tsx
artifacts/web-portal/src/components/ui/field.tsx
artifacts/web-portal/src/components/ui/form.tsx
artifacts/web-portal/src/components/ui/hover-card.tsx
artifacts/web-portal/src/components/ui/input-group.tsx
artifacts/web-portal/src/components/ui/input-otp.tsx
artifacts/web-portal/src/components/ui/input.tsx
artifacts/web-portal/src/components/ui/item.tsx
artifacts/web-portal/src/components/ui/kbd.tsx
artifacts/web-portal/src/components/ui/label.tsx
artifacts/web-portal/src/components/ui/menubar.tsx
artifacts/web-portal/src/components/ui/navigation-menu.tsx
artifacts/web-portal/src/components/ui/pagination.tsx
artifacts/web-portal/src/components/ui/popover.tsx
artifacts/web-portal/src/components/ui/progress.tsx
artifacts/web-portal/src/components/ui/radio-group.tsx
artifacts/web-portal/src/components/ui/resizable.tsx
artifacts/web-portal/src/components/ui/scroll-area.tsx
artifacts/web-portal/src/components/ui/select.tsx
artifacts/web-portal/src/components/ui/separator.tsx
artifacts/web-portal/src/components/ui/sheet.tsx
artifacts/web-portal/src/components/ui/sidebar.tsx
artifacts/web-portal/src/components/ui/skeleton.tsx
artifacts/web-portal/src/components/ui/slider.tsx
artifacts/web-portal/src/components/ui/sonner.tsx
artifacts/web-portal/src/components/ui/spinner.tsx
artifacts/web-portal/src/components/ui/switch.tsx
artifacts/web-portal/src/components/ui/table.tsx
artifacts/web-portal/src/components/ui/tabs.tsx
artifacts/web-portal/src/components/ui/textarea.tsx
artifacts/web-portal/src/components/ui/toast.tsx
artifacts/web-portal/src/components/ui/toaster.tsx
artifacts/web-portal/src/components/ui/toggle-group.tsx
artifacts/web-portal/src/components/ui/toggle.tsx
artifacts/web-portal/src/components/ui/tooltip.tsx
artifacts/web-portal/src/hooks/use-dashboard.ts
artifacts/web-portal/src/hooks/use-drivers.ts
artifacts/web-portal/src/hooks/use-missions.ts
artifacts/web-portal/src/hooks/use-mobile.tsx
artifacts/web-portal/src/hooks/use-sites.ts
artifacts/web-portal/src/hooks/use-toast.ts
artifacts/web-portal/src/index.css
artifacts/web-portal/src/lib/auth-context.tsx
artifacts/web-portal/src/lib/utils.ts
artifacts/web-portal/src/main.tsx
artifacts/web-portal/src/pages/admin/Admins.tsx
artifacts/web-portal/src/pages/admin/Dashboard.tsx
artifacts/web-portal/src/pages/admin/Drivers.tsx

artifacts/web-portal/src/pages/admin/Login.tsx
artifacts/web-portal/src/pages/admin/Missions.tsx
artifacts/web-portal/src/pages/admin/Notifications.tsx
artifacts/web-portal/src/pages/admin/Reports.tsx
artifacts/web-portal/src/pages/admin/Settings.tsx
artifacts/web-portal/src/pages/admin/Sites.tsx
artifacts/web-portal/src/pages/driver/DriverDashboard.tsx
artifacts/web-portal/src/pages/driver/DriverLogin.tsx
artifacts/web-portal/src/pages/driver/DriverMissionDetail.tsx
artifacts/web-portal/src/pages/driver/DriverNotifications.tsx
artifacts/web-portal/src/pages/driver/DriverSettings.tsx
artifacts/web-portal/src/pages/not-found.tsx
artifacts/web-portal/src/pages/PrivacyPolicy.tsx
artifacts/web-portal/tsconfig.json
artifacts/web-portal/vite.config.ts
babel.config.js
eas.json
lib/api-client-react/package.json
lib/api-client-react/src/custom-fetch.ts
lib/api-client-react/src/generated/api.schemas.ts
lib/api-client-react/src/generated/api.ts
lib/api-client-react/src/index.ts
lib/api-client-react/tsconfig.json
lib/api-spec/openapi.yaml
lib/api-spec/orval.config.ts
lib/api-spec/package.json
lib/api-zod/package.json
lib/api-zod/src/generated/api.ts
lib/api-zod/src/generated/types/admin.ts
lib/api-zod/src/generated/types/appSettings.ts
lib/api-zod/src/generated/types/createAdminInput.ts
lib/api-zod/src/generated/types/createDriverInput.ts
lib/api-zod/src/generated/types/createGeneratorInput.ts
lib/api-zod/src/generated/types/createMissionInput.ts
lib/api-zod/src/generated/types/createNotificationInput.ts
lib/api-zod/src/generated/types/createSiteInput.ts
lib/api-zod/src/generated/types/createTechnicianInput.ts
lib/api-zod/src/generated/types/dashboardKpis.ts
lib/api-zod/src/generated/types/dashboardKpisApprovedForInvoicingItem.ts
lib/api-zod/src/generated/types/dashboardKpisLitersByZoneItem.ts
lib/api-zod/src/generated/types/dashboardKpisMissionsByCategoryItem.ts
lib/api-zod/src/generated/types/dashboardKpisMissionsByStatusItem.ts
lib/api-zod/src/generated/types/dashboardKpisMissionsByZoneItem.ts
lib/api-zod/src/generated/types/driver.ts
lib/api-zod/src/generated/types/driverLoginInput.ts
lib/api-zod/src/generated/types/driverLoginResponse.ts
lib/api-zod/src/generated/types/driverNotification.ts
lib/api-zod/src/generated/types/driverTask.ts
lib/api-zod/src/generated/types/generator.ts
lib/api-zod/src/generated/types/healthStatus.ts
lib/api-zod/src/generated/types/index.ts
lib/api-zod/src/generated/types/listDriverNotificationsParams.ts

lib/api-zod/src/generated/types/listDriverTasksParams.ts
lib/api-zod/src/generated/types/listTechnicianMissionsParams.ts
lib/api-zod/src/generated/types/loginInput.ts
lib/api-zod/src/generated/types/loginResponse.ts
lib/api-zod/src/generated/types/mission.ts
lib/api-zod/src/generated/types/notification.ts
lib/api-zod/src/generated/types/requestUploadUrlBody.ts
lib/api-zod/src/generated/types/requestUploadUrlResponse.ts
lib/api-zod/src/generated/types/site.ts
lib/api-zod/src/generated/types/technician.ts
lib/api-zod/src/generated/types/technicianFollowUpInput.ts
lib/api-zod/src/generated/types/technicianLoginInput.ts
lib/api-zod/src/generated/types/technicianLoginResponse.ts
lib/api-zod/src/generated/types/updateAdminInput.ts
lib/api-zod/src/generated/types/updateDriverInput.ts
lib/api-zod/src/generated/types/updateDriverTaskInput.ts
lib/api-zod/src/generated/types/updateGeneratorInput.ts
lib/api-zod/src/generated/types/updateMissionInput.ts
lib/api-zod/src/generated/types/updateSiteInput.ts
lib/api-zod/src/generated/types/updateTechnicianInput.ts
lib/api-zod/src/index.ts
lib/api-zod/tsconfig.json
lib/db/drizzle.config.ts
lib/db/package.json
lib/db/src/index.ts
lib/db/src/schema/admins.ts
lib/db/src/schema/driver-entries.ts
lib/db/src/schema/drivers.ts
lib/db/src/schema/generators.ts
lib/db/src/schema/index.ts
lib/db/src/schema/missions.ts
lib/db/src/schema/notifications.ts
lib/db/src/schema/report-lines.ts
lib/db/src/schema/settings.ts
lib/db/src/schema/sites.ts
lib/db/src/schema/technicians.ts
lib/db/tsconfig.json
package.json
pnpm-workspace.yaml
replit.md
scripts/package.json
scripts/src/hello.ts
scripts/tsconfig.json
tsconfig.base.json
tsconfig.json

FILE: App.js
SIZE: 244 bytes

```
import { View, Text } from 'react-native';

export default function App() {
  return (
    <View style={{
      flex: 1,
      justifyContent: 'center',
      alignItems: 'center'
    }}>
      <Text>ACES-MSD Fuelling</Text>
    </View>
  );
}
```

FILE: app.json
SIZE: 571 bytes

```
{
  "expo": {
    "name": "ACES-MSD Fuelling",
    "slug": "workspace",
    "version": "1.0.0",
    "android": {
      "package": "com.aces.msdfuelling"
    },
    "extra": {
      "eas": {
        "projectId": "80041872-a4e7-48a5-b988-faf3da3b9052"
      }
    },
    "runtimeVersion": {
      "policy": "appVersion"
    },
    "updates": {
      "url": "https://u.expo.dev/80041872-a4e7-48a5-b988-faf3da3b9052"
    },
    "ios": {
      "bundleIdentifier": "com.aces.msdfuelling",
      "infoPlist": {
        "ITSAppUsesNonExemptEncryption": false
      }
    }
  }
}
```

FILE: app/_layout.tsx
SIZE: 95 bytes

```
import { Stack } from "expo-router";

export default function Layout() {
  return <Stack />;
}
```

FILE: app/index.tsx
SIZE: 144 bytes

```
import { View, Text } from "react-native";

export default function Home() {
  return (
    <View>
      <Text>App OK</Text>
    </View>
  );
}
```

FILE: artifacts/api-server/.replit-artifact/artifact.toml
SIZE: 784 bytes

```
kind = "api"
previewPath = "/api" # TODO - should be excluded from preview in the first place
title = "API Server"
version = "1.0.0"
id = "3B4_FFSkEVBkAeYMFRJ2e"

[[services]]
localPort = 8080
name = "API Server"
paths = ["/api"]

[services.development]
run = "pnpm --filter @workspace/api-server run dev"

[services.production]

[services.production.build]
args = ["pnpm", "--filter", "@workspace/api-server", "run", "build"]

[services.production.build.env]
NODE_ENV = "production"

[services.production.run]
# we don’t run through pnpm to make startup faster in production
args = ["node", "--enable-source-maps", "artifacts/api-server/dist/index.mjs"]

[services.production.run.env]
PORT = "8080"
NODE_ENV = "production"

[services.production.health.startup]
path = "/api/healthz"
```

FILE: artifacts/api-server/build.mjs
SIZE: 3,455 bytes

```
import { createRequire } from "node:module";
import path from "node:path";
import { fileURLToPath } from "node:url";
import { build as esbuild } from "esbuild";
import esbuildPluginPino from "esbuild-plugin-pino";
import { rm } from "node:fs/promises";

// Plugins (e.g. 'esbuild-plugin-pino') may use 'require' to resolve dependencies
globalThis.require = createRequire(import.meta.url);

const artifactDir = path.dirname(fileURLToPath(import.meta.url));

async function buildAll() {
  const distDir = path.resolve(artifactDir, "dist");
  await rm(distDir, { recursive: true, force: true });

  await esbuild({
    entryPoints: [path.resolve(artifactDir, "src/index.ts")],
    platform: "node",
    bundle: true,
    format: "esm",
    outdir: distDir,
    outExtension: { ".js": ".mjs" },
    logLevel: "info",
    // Some packages may not be bundleable, so we externalize them, we can add more here as needed.
    // Some of the packages below may not be imported or installed, but we're adding them in case they are in th
  e future.
    // Examples of unbundleable packages:
    // - uses native modules and loads them dynamically (e.g. sharp)
    // - use path traversal to read files (e.g. @google-cloud/secret-manager loads sibling .proto files)
    external: [
      "*.node",
      "sharp",
      "better-sqlite3",
      "sqlite3",
      "canvas",
      "bcrypt",
      "argon2",
      "fsevents",
      "re2",
      "farmhash",
      "xxhash-addon",
      "bufferutil",
      "utf-8-validate",
      "ssh2",
      "cpu-features",
      "dtrace-provider",
      "isolated-vm",
      "lightningcss",
```

```
    "pg-native",
    "oracledb",
    "mongodb-client-encryption",
    "nodemailer",
    "handlebars",
    "knex",
    "typeorm",
    "protobufjs",
    "onnxruntime-node",
    "@tensorflow/*",
    "@prisma/client",
    "@mikro-orm/*",
    "@grpc/*",
    "@swc/*",
    "@aws-sdk/*",
    "@azure/*",
    "@opentelemetry/*",
    "@google-cloud/*",
    "@google/*",
    "googleapis",
    "firebase-admin",
    "@parcel/watcher",
    "@sentry/profiling-node",
    "@tree-sitter/*",
    "aws-sdk",
    "classic-level",
    "dd-trace",
    "ffi-napi",
    "grpc",
    "hiredis",
    "kerberos",
    "leveldown",
    "miniflare",
    "mysql2",
    "newrelic",
    "odbc",
    "piscina",
    "realm",
    "ref-napi",
    "rocksdb",
    "sass-embedded",
    "sequelize",
    "serialport",
    "snappy",
    "tinypool",
    "usb",
    "workerd",
    "wrangler",
    "zeromq",
    "zeromq-prebuilt",
    "playwright",
    "puppeteer",
```

```
      "puppeteer-core",
      "electron",
    ],
    sourcemap: "linked",
    plugins: [
      // pino relies on workers to handle logging, instead of externalizing it we use a plugin to handle it
      esbuildPluginPino({ transports: ["pino-pretty"] })
    ],
    // Make sure packages that are cjs only (e.g. express) but are bundled continue to work in our esm output fi
  le
    banner: {
      js: 'import { createRequire as __bannerCrReq } from 'node:module';
import __bannerPath from 'node:path';
import __bannerUrl from 'node:url';

globalThis.require = __bannerCrReq(import.meta.url);
globalThis.__filename = __bannerUrl.fileURLToPath(import.meta.url);
globalThis.__dirname = __bannerPath.dirname(globalThis.__filename);
    ',
    },
  });
}

buildAll().catch((err) => {
  console.error(err);
  process.exit(1);
});
```

FILE: artifacts/api-server/package.json
SIZE: 1,029 bytes

```
{
  "name": "@workspace/api-server",
  "version": "0.0.0",
  "private": true,
  "type": "module",
  "scripts": {
    "dev": "export NODE_ENV=development && pnpm run build && pnpm run start",
    "build": "node ./build.mjs",
    "start": "node --enable-source-maps ./dist/index.mjs",
    "typecheck": "tsc -p tsconfig.json --noEmit",
    "test": "node --import tsx/esm --test src/__tests__/*.test.ts"
  },
  "dependencies": {
    "@google-cloud/storage": "^7.19.0",
    "@workspace/api-zod": "workspace:*",
    "@workspace/db": "workspace:*",
    "cookie-parser": "^1.4.7",
    "cors": "^2",
    "drizzle-orm": "catalog:",
    "express": "^5",
    "google-auth-library": "^10.6.2",
    "pino": "^9",
    "pino-http": "^10"
  },
  "devDependencies": {
    "@types/cookie-parser": "^1.4.10",
    "@types/cors": "^2.8.19",
    "@types/express": "^5.0.6",
    "@types/node": "catalog:",
    "esbuild": "^0.27.3",
    "esbuild-plugin-pino": "^2.3.3",
    "pino-pretty": "^13",
    "thread-stream": "3.1.0",
    "tsx": "catalog:"
  }
}
```

FILE: artifacts/api-server/src/__tests__/technician-token.test.ts
SIZE: 5,380 bytes

```
/**
 * Unit tests for technician bearer-token logic (src/lib/techToken.ts).
 * Run with: pnpm --filter @workspace/api-server test
 *
 * Covers: token generation, valid verification, forgery, tampered HMACs,
 * short HMAC (length-guard path), expired tokens, and missing inputs.
 */
import { test, describe } from "node:test";
import assert from "node:assert/strict";
import crypto from "node:crypto";
import { generateTechToken, verifyTechToken, TOKEN_MAX_AGE_MS } from "../lib/techToken";

const TEST_SECRET = "test-secret-for-unit-tests-only";

// Ensure tests use a known secret regardless of environment
process.env.SESSION_SECRET = TEST_SECRET;

// ?? generateTechToken ??????????????????????????????????????????????????????

describe("generateTechToken", () => {
  test("returns a token with correct tech-{id} prefix", () => {
    const token = generateTechToken(42);
    assert.ok(token.startsWith("tech-42-"), `Expected 'tech-42-' prefix, got: ${token}`);
  });

  test("token has exactly 4 dash-separated parts: tech, id, timestamp, hmac", () => {
    const token = generateTechToken(7);
    const firstDash = token.indexOf("-");
    const secondDash = token.indexOf("-", firstDash + 1);
    const thirdDash = token.indexOf("-", secondDash + 1);
    assert.ok(thirdDash > 0, "Token should have at least 4 dash-separated parts");
    const hmacPart = token.slice(thirdDash + 1);
    assert.equal(hmacPart.length, 64, `HMAC should be 64 hex chars, got ${hmacPart.length}`);
  });

  test("two calls at different times produce different tokens", (_, done) => {
    const t1 = generateTechToken(1);
    setTimeout(() => {
      const t2 = generateTechToken(1);
      assert.notEqual(t1, t2, "Tokens at different times must differ");
      done();
    }, 2);
  });
});

// ?? verifyTechToken   valid tokens ??????????????????????????????????????????

describe("verifyTechToken   valid tokens", () => {
  test("accepts a freshly generated token and returns the correct technician ID", () => {
```

```
    const techId = 5;
    const token = generateTechToken(techId);
    const result = verifyTechToken(`Bearer ${token}`);
    assert.equal(result, techId);
  });

  test("accepts technician ID 1 (minimum valid ID)", () => {
    const token = generateTechToken(1);
    assert.equal(verifyTechToken(`Bearer ${token}`), 1);
  });

  test("accepts a large technician ID", () => {
    const token = generateTechToken(99999);
    assert.equal(verifyTechToken(`Bearer ${token}`), 99999);
  });
});

// ?? verifyTechToken   invalid inputs ????????????????????????????????????????

describe("verifyTechToken   invalid inputs", () => {
  test("returns null for undefined authorization header", () => {
    assert.equal(verifyTechToken(undefined), null);
  });

  test("returns null for empty string", () => {
    assert.equal(verifyTechToken(""), null);
  });

  test("returns null when Bearer prefix is missing", () => {
    const token = generateTechToken(1);
    assert.equal(verifyTechToken(token), null);
  });

  test("returns null for old-style forgeable token (3 parts, no HMAC)", () => {
    assert.equal(verifyTechToken("Bearer tech-1-1234567890"), null);
  });

  test("returns null for wrong prefix (user- instead of tech-)", () => {
    assert.equal(verifyTechToken("Bearer user-1-1234567890-abc123"), null);
  });

  test("returns null for tampered HMAC (flipped last hex character)", () => {
    const token = generateTechToken(3);
    const flipped = token.slice(0, -1) + (token.endsWith("a") ? "b" : "a");
    assert.equal(verifyTechToken(`Bearer ${flipped}`), null);
  });

  test("returns null for short HMAC (triggers length-mismatch guard, not timingSafeEqual)", () => {
    const ts = Date.now();
    const shortHmac = "deadbeef";
    const fakeToken = `tech-1-${ts}-${shortHmac}`;
    assert.equal(verifyTechToken(`Bearer ${fakeToken}`), null);
```

```
  });

  test("returns null for HMAC signed with a different secret", () => {
    const ts = Date.now();
    const payload = `tech-1-${ts}`;
    const wrongHmac = crypto.createHmac("sha256", "wrong-secret").update(payload).digest("hex");
    const token = `${payload}-${wrongHmac}`;
    assert.equal(verifyTechToken(`Bearer ${token}`), null);
  });

  test("returns null for future-dated token (negative age)", () => {
    const futureTs = Date.now() + 60_000;
    const payload = `tech-1-${futureTs}`;
    const hmac = crypto.createHmac("sha256", TEST_SECRET).update(payload).digest("hex");
    const token = `${payload}-${hmac}`;
    assert.equal(verifyTechToken(`Bearer ${token}`), null);
  });

  test("returns null for expired token (age > TOKEN_MAX_AGE_MS)", () => {
    const expiredTs = Date.now() - (TOKEN_MAX_AGE_MS + 1000);
    const payload = `tech-1-${expiredTs}`;
    const hmac = crypto.createHmac("sha256", TEST_SECRET).update(payload).digest("hex");
    const token = `${payload}-${hmac}`;
    assert.equal(verifyTechToken(`Bearer ${token}`), null);
  });

  test("TOKEN_MAX_AGE_MS is exactly 30 days in milliseconds", () => {
    assert.equal(TOKEN_MAX_AGE_MS, 30 * 24 * 60 * 60 * 1000);
  });
});
```

FILE: artifacts/api-server/src/app.ts
SIZE: 688 bytes

```
import express, { type Express } from "express";
import cors from "cors";
import pinoHttp from "pino-http";
import router from "./routes";
import { logger } from "./lib/logger";

const app: Express = express();

app.use(
  pinoHttp({
    logger,
    serializers: {
      req(req) {
        return {
          id: req.id,
          method: req.method,
          url: req.url?.split("?")[0],
        };
      },
      res(res) {
        return {
          statusCode: res.statusCode,
        };
      },
    },
  }),
);
app.use(cors());
app.use(express.json({ limit: "50mb" }));
app.use(express.urlencoded({ extended: true, limit: "50mb" }));

app.use("/api", router);

export default app;
```

FILE: artifacts/api-server/src/index.ts
SIZE: 1,051 bytes

```
import app from "./app";
import { logger } from "./lib/logger";
import { runSeedIfEmpty } from "./lib/startup-seed";
import { startSiteSyncScheduler } from "./lib/sync-scheduler";

if (!process.env["SESSION_SECRET"]) {
  throw new Error(
    "SESSION_SECRET environment variable is required but was not provided. " +
    "Set it in the environment secrets before starting the server.",
  );
}

const rawPort = process.env["PORT"];

if (!rawPort) {
  throw new Error(
    "PORT environment variable is required but was not provided.",
  );
}

const port = Number(rawPort);

if (Number.isNaN(port) || port <= 0) {
  throw new Error(`Invalid PORT value: "${rawPort}"`);
}

app.listen(port, (err) => {
  if (err) {
    logger.error({ err }, "Error listening on port");
    process.exit(1);
  }

  logger.info({ port }, "Server listening");

  // Auto-seed production database if empty
  runSeedIfEmpty().catch((e) => logger.error({ err: e }, "Startup seed failed"));

  // Auto-sync sites from Google Sheets every 24 hours
  startSiteSyncScheduler();
});
```

FILE: artifacts/api-server/src/lib/logger.ts
SIZE: 421 bytes

```
import pino from "pino";

const isProduction = process.env.NODE_ENV === "production";

export const logger = pino({
  level: process.env.LOG_LEVEL ?? "info",
  redact: [
    "req.headers.authorization",
    "req.headers.cookie",
    "res.headers['set-cookie']",
  ],
  ...(isProduction
    ? {}
    : {
        transport: {
          target: "pino-pretty",
          options: { colorize: true },
        },
      }),
});
```

FILE: artifacts/api-server/src/lib/objectAcl.ts
SIZE: 3,427 bytes

```
import { File } from "@google-cloud/storage";

const ACL_POLICY_METADATA_KEY = "custom:aclPolicy";

// Can be flexibly defined according to the use case.
//
// Examples:
// - USER_LIST: the users from a list stored in the database;
// - EMAIL_DOMAIN: the users whose email is in a specific domain;
// - GROUP_MEMBER: the users who are members of a specific group;
// - SUBSCRIBER: the users who are subscribers of a specific service / content
//   creator.
export enum ObjectAccessGroupType {}

export interface ObjectAccessGroup {
  type: ObjectAccessGroupType;
  // The logic id that identifies qualified group members. Format depends on the
  // ObjectAccessGroupType   e.g. a user-list DB id, an email domain, a group id.
  id: string;
}

export enum ObjectPermission {
  READ = "read",
  WRITE = "write",
}

export interface ObjectAclRule {
  group: ObjectAccessGroup;
  permission: ObjectPermission;
}

// Stored as object custom metadata under "custom:aclPolicy" (JSON string).
export interface ObjectAclPolicy {
  owner: string;
  visibility: "public" | "private";
  aclRules?: Array<ObjectAclRule>;
}

function isPermissionAllowed(
  requested: ObjectPermission,
  granted: ObjectPermission,
): boolean {
  if (requested === ObjectPermission.READ) {
    return [ObjectPermission.READ, ObjectPermission.WRITE].includes(granted);
  }
  return granted === ObjectPermission.WRITE;
}

abstract class BaseObjectAccessGroup implements ObjectAccessGroup {
```

```
  constructor(
    public readonly type: ObjectAccessGroupType,
    public readonly id: string,
  ) {}

  public abstract hasMember(userId: string): Promise<boolean>;
}

function createObjectAccessGroup(
  group: ObjectAccessGroup,
): BaseObjectAccessGroup {
  switch (group.type) {
    // Implement per access group type, e.g.:
    // case "USER_LIST":
    //   return new UserListAccessGroup(group.id);
    default:
      throw new Error(`Unknown access group type: ${group.type}`);
  }
}

export async function setObjectAclPolicy(
  objectFile: File,
  aclPolicy: ObjectAclPolicy,
): Promise<void> {
  const [exists] = await objectFile.exists();
  if (!exists) {
    throw new Error(`Object not found: ${objectFile.name}`);
  }

  await objectFile.setMetadata({
    metadata: {
      [ACL_POLICY_METADATA_KEY]: JSON.stringify(aclPolicy),
    },
  });
}

export async function getObjectAclPolicy(
  objectFile: File,
): Promise<ObjectAclPolicy | null> {
  const [metadata] = await objectFile.getMetadata();
  const aclPolicy = metadata?.metadata?.[ACL_POLICY_METADATA_KEY];
  if (!aclPolicy) {
    return null;
  }
  return JSON.parse(aclPolicy as string);
}

export async function canAccessObject({
  userId,
  objectFile,
  requestedPermission,
}: {
```

```
  userId?: string;
  objectFile: File;
  requestedPermission: ObjectPermission;
}): Promise<boolean> {
  const aclPolicy = await getObjectAclPolicy(objectFile);
  if (!aclPolicy) {
    return false;
  }

  if (
    aclPolicy.visibility === "public" &&
    requestedPermission === ObjectPermission.READ
  ) {
    return true;
  }

  if (!userId) {
    return false;
  }

  if (aclPolicy.owner === userId) {
    return true;
  }

  for (const rule of aclPolicy.aclRules || []) {
    const accessGroup = createObjectAccessGroup(rule.group);
    if (
      (await accessGroup.hasMember(userId)) &&
      isPermissionAllowed(requestedPermission, rule.permission)
    ) {
      return true;
    }
  }

  return false;
}
```

FILE: artifacts/api-server/src/lib/objectStorage.ts
SIZE: 7,212 bytes

```
import { Storage, File } from "@google-cloud/storage";
import { Readable } from "stream";
import { randomUUID } from "crypto";
import {
  ObjectAclPolicy,
  ObjectPermission,
  canAccessObject,
  getObjectAclPolicy,
  setObjectAclPolicy,
} from "./objectAcl";

const REPLIT_SIDECAR_ENDPOINT = "http://127.0.0.1:1106";

export const objectStorageClient = new Storage({
  credentials: {
    audience: "replit",
    subject_token_type: "access_token",
    token_url: `${REPLIT_SIDECAR_ENDPOINT}/token`,
    type: "external_account",
    credential_source: {
      url: `${REPLIT_SIDECAR_ENDPOINT}/credential`,
      format: {
        type: "json",
        subject_token_field_name: "access_token",
      },
    },
    universe_domain: "googleapis.com",
  },
  projectId: "",
});

export class ObjectNotFoundError extends Error {
  constructor() {
    super("Object not found");
    this.name = "ObjectNotFoundError";
    Object.setPrototypeOf(this, ObjectNotFoundError.prototype);
  }
}

export class ObjectStorageService {
  constructor() {}

  getPublicObjectSearchPaths(): Array<string> {
    const pathsStr = process.env.PUBLIC_OBJECT_SEARCH_PATHS || "";
    const paths = Array.from(
      new Set(
        pathsStr
          .split(",")
          .map((path) => path.trim())
```

```
        .filter((path) => path.length > 0)
    )
  );
  if (paths.length === 0) {
    throw new Error(
      "PUBLIC_OBJECT_SEARCH_PATHS not set. Create a bucket in 'Object Storage' " +
        "tool and set PUBLIC_OBJECT_SEARCH_PATHS env var (comma-separated paths)."
    );
  }
  return paths;
}

getPrivateObjectDir(): string {
  const dir = process.env.PRIVATE_OBJECT_DIR || "";
  if (!dir) {
    throw new Error(
      "PRIVATE_OBJECT_DIR not set. Create a bucket in 'Object Storage' " +
        "tool and set PRIVATE_OBJECT_DIR env var."
    );
  }
  return dir;
}

async searchPublicObject(filePath: string): Promise<File | null> {
  for (const searchPath of this.getPublicObjectSearchPaths()) {
    const fullPath = `${searchPath}/${filePath}`;

    const { bucketName, objectName } = parseObjectPath(fullPath);
    const bucket = objectStorageClient.bucket(bucketName);
    const file = bucket.file(objectName);

    const [exists] = await file.exists();
    if (exists) {
      return file;
    }
  }

  return null;
}

async downloadObject(file: File, cacheTtlSec: number = 3600): Promise<Response> {
  const [metadata] = await file.getMetadata();
  const aclPolicy = await getObjectAclPolicy(file);
  const isPublic = aclPolicy?.visibility === "public";

  const nodeStream = file.createReadStream();
  const webStream = Readable.toWeb(nodeStream) as ReadableStream;

  const headers: Record<string, string> = {
    "Content-Type": (metadata.contentType as string) || "application/octet-stream",
    "Cache-Control": `${isPublic ? "public" : "private"}, max-age=${cacheTtlSec}`,
  };
```

```
    if (metadata.size) {
      headers["Content-Length"] = String(metadata.size);
    }

    return new Response(webStream, { headers });
  }

  async getObjectEntityUploadURL(): Promise<string> {
    const privateObjectDir = this.getPrivateObjectDir();
    if (!privateObjectDir) {
      throw new Error(
        "PRIVATE_OBJECT_DIR not set. Create a bucket in 'Object Storage' " +
          "tool and set PRIVATE_OBJECT_DIR env var."
      );
    }

    const objectId = randomUUID();
    const fullPath = `${privateObjectDir}/uploads/${objectId}`;

    const { bucketName, objectName } = parseObjectPath(fullPath);

    return signObjectURL({
      bucketName,
      objectName,
      method: "PUT",
      ttlSec: 900,
    });
  }

  async getObjectEntityFile(objectPath: string): Promise<File> {
    if (!objectPath.startsWith("/objects/")) {
      throw new ObjectNotFoundError();
    }

    const parts = objectPath.slice(1).split("/");
    if (parts.length < 2) {
      throw new ObjectNotFoundError();
    }

    const entityId = parts.slice(1).join("/");
    let entityDir = this.getPrivateObjectDir();
    if (!entityDir.endsWith("/")) {
      entityDir = `${entityDir}/`;
    }
    const objectEntityPath = `${entityDir}${entityId}`;
    const { bucketName, objectName } = parseObjectPath(objectEntityPath);
    const bucket = objectStorageClient.bucket(bucketName);
    const objectFile = bucket.file(objectName);
    const [exists] = await objectFile.exists();
    if (!exists) {
      throw new ObjectNotFoundError();
    }
```

```
    return objectFile;
  }

  normalizeObjectEntityPath(rawPath: string): string {
    if (!rawPath.startsWith("https://storage.googleapis.com/")) {
      return rawPath;
    }

    const url = new URL(rawPath);
    const rawObjectPath = url.pathname;

    let objectEntityDir = this.getPrivateObjectDir();
    if (!objectEntityDir.endsWith("/")) {
      objectEntityDir = `${objectEntityDir}/`;
    }

    if (!rawObjectPath.startsWith(objectEntityDir)) {
      return rawObjectPath;
    }

    const entityId = rawObjectPath.slice(objectEntityDir.length);
    return `/objects/${entityId}`;
  }

  async trySetObjectEntityAclPolicy(
    rawPath: string,
    aclPolicy: ObjectAclPolicy
  ): Promise<string> {
    const normalizedPath = this.normalizeObjectEntityPath(rawPath);
    if (!normalizedPath.startsWith("/")) {
      return normalizedPath;
    }

    const objectFile = await this.getObjectEntityFile(normalizedPath);
    await setObjectAclPolicy(objectFile, aclPolicy);
    return normalizedPath;
  }

  async canAccessObjectEntity({
    userId,
    objectFile,
    requestedPermission,
  }: {
    userId?: string;
    objectFile: File;
    requestedPermission?: ObjectPermission;
  }): Promise<boolean> {
    return canAccessObject({
      userId,
      objectFile,
      requestedPermission: requestedPermission ?? ObjectPermission.READ,
    });
```

```
  }
}

function parseObjectPath(path: string): {
  bucketName: string;
  objectName: string;
} {
  if (!path.startsWith("/")) {
    path = `/${path}`;
  }
  const pathParts = path.split("/");
  if (pathParts.length < 3) {
    throw new Error("Invalid path: must contain at least a bucket name");
  }

  const bucketName = pathParts[1];
  const objectName = pathParts.slice(2).join("/");

  return {
    bucketName,
    objectName,
  };
}

async function signObjectURL({
  bucketName,
  objectName,
  method,
  ttlSec,
}: {
  bucketName: string;
  objectName: string;
  method: "GET" | "PUT" | "DELETE" | "HEAD";
  ttlSec: number;
}): Promise<string> {
  const request = {
    bucket_name: bucketName,
    object_name: objectName,
    method,
    expires_at: new Date(Date.now() + ttlSec * 1000).toISOString(),
  };
  const response = await fetch(
    `${REPLIT_SIDECAR_ENDPOINT}/object-storage/signed-object-url`,
    {
      method: "POST",
      headers: {
        "Content-Type": "application/json",
      },
      body: JSON.stringify(request),
      signal: AbortSignal.timeout(30_000),
    }
  );
```

```
  if (!response.ok) {
    throw new Error(
      `Failed to sign object URL, errorcode: ${response.status}, ` +
        `make sure you're running on Replit`
    );
  }

  const { signed_url: signedURL } = await response.json();
  return signedURL;
}
```

FILE: artifacts/api-server/src/lib/startup-seed.ts
SIZE: 111,855 bytes

```
import { db } from "@workspace/db";
import { adminsTable, sitesTable, missionsTable, driversTable } from "@workspace/db/schema";
import { count, inArray } from "drizzle-orm";

const SEED_SITES = [
  {
    "name": "COW001",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.787048,
    "lng": 46.557983,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW002",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.902332,
    "lng": 46.52644,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW011",
    "district": "Riyadh District",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "Normal",
    "lat": 24.68431,
    "lng": 46.487648,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1901
  },
  {
    "name": "COW012",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 24.665045,
    "lng": 46.65332,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/28/2026",
    "last_fueling_qty": 1493
  },
  {
    "name": "COW013",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.55672,
    "lng": 46.28677,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1286
  },
  {
    "name": "COW015",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.76868,
    "lng": 46.63688,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW016",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.929005,
    "lng": 46.381664,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1244
  },
  {
    "name": "COW017",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.719574,
    "lng": 46.60797,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW019",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.738,
```

```
    "lng": 46.574318,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW020",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.79591,
    "lng": 46.54063,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1530
  },
  {
    "name": "COW054",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.718904,
    "lng": 46.644096,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW055",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.779305,
    "lng": 46.594463,
```

```
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW056",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.893806,
    "lng": 46.530388,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW057",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.86628,
    "lng": 46.5586,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1127
  },
  {
    "name": "COW058",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.871113,
    "lng": 46.573414,
    "next_fueling_plan": "04-07-2026",
```

```
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW059",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.695736,
    "lng": 46.58221,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1295
  },
  {
    "name": "COW061",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.106527,
    "lng": 46.387585,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW063",
    "district": "Riyadh District",
    "city": "Al kharaj",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.073214,
    "lng": 47.244053,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/4/2026",
```

```
    "last_fueling_qty": 1784
  },
  {
    "name": "COW303",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.56186,
    "lng": 47.71272,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1886
  },
  {
    "name": "COW304",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.410555,
    "lng": 50.080833,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1173
  },
  {
    "name": "COW305",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.12298,
    "lng": 45.67255,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "3/28/2026",
    "last_fueling_qty": 2298
```

```
  },
  {
    "name": "COW307",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.870815,
    "lng": 41.813095,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1397
  },
  {
    "name": "COW308",
    "district": "Riyadh District",
    "city": "al Ghat",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.06806,
    "lng": 44.902718,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 988
  },
  {
    "name": "COW309",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.81736,
    "lng": 41.68107,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1300
  },
```

```
{
  "name": "COW310",
  "district": "NORTHERN BORDER",
  "city": "ARAR",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 31.53616,
  "lng": 40.67132,
  "next_fueling_plan": "04-13-2026",
  "last_fueling_date": "4/4/2026",
  "last_fueling_qty": 1000
},
{
  "name": "COW312",
  "district": "DAMMAM",
  "city": "DAMMAM",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 25.940174,
  "lng": 50.10601,
  "next_fueling_plan": "SEC Site",
  "last_fueling_date": "1/26/2026",
  "last_fueling_qty": 1479
},
{
  "name": "COW510",
  "district": "Riyadh District",
  "city": "Riyadh District",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.900503,
  "lng": 46.13521,
  "next_fueling_plan": "04-16-2026",
  "last_fueling_date": "4/3/2026",
  "last_fueling_qty": 1394
},
{
```

```
    "name": "COW511",
    "district": "Riyadh District",
    "city": "Wadi Dawaseer",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 20.78241,
    "lng": 45.79936,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1903
  },
  {
    "name": "COW512",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.408138,
    "lng": 50.082993,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1034
  },
  {
    "name": "COW516",
    "district": "JUBAIL",
    "city": "Khafji",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.82347,
    "lng": 48.63208,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1718
  },
  {
    "name": "COW517",
```

```
    "district": "Riyadh District",
    "city": "Shaqra",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.16794,
    "lng": 45.039055,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1744
  },
  {
    "name": "COW518",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 25.172392,
    "lng": 46.60499,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/23/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW520",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.22129,
    "lng": 47.079773,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW527",
    "district": "NORTHERN BORDER",
```

```
    "city": "Al Uwayqilah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.35557,
    "lng": 42.24141,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1116
  },
  {
    "name": "COW528",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.9066,
    "lng": 48.65835,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1672
  },
  {
    "name": "COW529",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 25.3349,
    "lng": 46.458,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW530",
    "district": "Riyadh District",
    "city": "Muzahmiya",
```

```
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.33422,
    "lng": 46.087425,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 925
  },
  {
    "name": "COW531",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.436855,
    "lng": 46.26998,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW534",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.587582,
    "lng": 46.355427,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1411
  },
  {
    "name": "COW535",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
```

```
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 25.33344,
    "lng": 46.47846,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW536",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.87598,
    "lng": 46.855522,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW541",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.771683,
    "lng": 46.72872,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 863
  },
  {
    "name": "COW542",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.71627,
    "lng": 46.09091,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1563
  },
  {
    "name": "COW543",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.9558,
    "lng": 49.56972,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1033
  },
  {
    "name": "COW544",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.467182,
    "lng": 46.67115,
    "next_fueling_plan": "04-18-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1436
  },
  {
    "name": "COW546",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.23472,
    "lng": 48.1697,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW548",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.3002,
    "lng": 49.554195,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1683
  },
  {
    "name": "COW549",
    "district": "Dammam",
    "city": "Dammam",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW552",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/4/2026",
    "last_fueling_qty": 1989
  },
  {
    "name": "COW600",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.86842,
    "lng": 46.56649,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 817
  },
  {
    "name": "COW601",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 22.430492,
    "lng": 53.976357,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW608",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/29/2026",
    "last_fueling_qty": 1856
  },
  {
    "name": "COW611",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.598888,
    "lng": 46.304142,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1524
  },
  {
    "name": "COW612",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.89845,
    "lng": 46.655407,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW614",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW615",
    "district": "Riyadh District",
    "city": "Al Qamriyah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.53423,
    "lng": 46.043312,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW616",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.756826,
    "lng": 46.562176,
    "next_fueling_plan": "04-17-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1326
  },
  {
    "name": "COW617",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/28/2026",
    "last_fueling_qty": 1450
  },
  {
    "name": "COW618",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.090467,
    "lng": 49.51877,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1362
  },
  {
    "name": "COW619",
    "district": "NORTHERN BORDER",
    "city": "Arar",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "VIP",
    "lat": 30.805107,
    "lng": 40.944904,
    "next_fueling_plan": "04-03-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 450
  },
  {
    "name": "COW621",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.42355,
```

```
    "lng": 46.37908,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1743
  },
  {
    "name": "COW626",
    "district": "Riyadh District",
    "city": "Jilha",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.693,
    "lng": 45.61219,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1752
  },
  {
    "name": "COW627",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW628",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
```

```
    "next_fueling_plan": null,
    "last_fueling_date": "1/25/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW632",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.66057,
    "lng": 46.67427,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW634",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.201078,
    "lng": 46.378563,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW635",
    "district": "Jeddah",
    "city": "Jeddah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 21.458817,
    "lng": 39.21194,
    "next_fueling_plan": null,
```

```
    "last_fueling_date": "1/17/2026",
    "last_fueling_qty": 973
  },
  {
    "name": "COW636",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/30/2026",
    "last_fueling_qty": 803
  },
  {
    "name": "COW637",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW639",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": null,
    "lng": null,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
```

```
    "last_fueling_qty": null
  },
  {
    "name": "COW640",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW641",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.296738,
    "lng": 50.15904,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW642",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/16/2026",
    "last_fueling_qty": 1427
```

```
},
{
  "name": "COW643",
  "district": "Riyadh District",
  "city": "Riyadh",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.94298,
  "lng": 47.14723,
  "next_fueling_plan": "04-13-2026",
  "last_fueling_date": "3/31/2026",
  "last_fueling_qty": 1218
},
{
  "name": "COW645",
  "district": "Riyadh District",
  "city": "Muzahmiya",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.517206,
  "lng": 46.26815,
  "next_fueling_plan": null,
  "last_fueling_date": "1/19/2026",
  "last_fueling_qty": 1328
},
{
  "name": "COW647",
  "district": "Riyadh District",
  "city": "Shaqra",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 25.225864,
  "lng": 45.26588,
  "next_fueling_plan": "04-09-2026",
  "last_fueling_date": "3/27/2026",
  "last_fueling_qty": 1520
},
```

```
{
  "name": "COW652",
  "district": "DAMMAM",
  "city": "DAMMAM",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 26.201199,
  "lng": 49.947945,
  "next_fueling_plan": null,
  "last_fueling_date": "1/30/2026",
  "last_fueling_qty": 900
},
{
  "name": "COW653",
  "district": "Al-AHSA",
  "city": "Hofuf",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 25.30936,
  "lng": 49.77637,
  "next_fueling_plan": "04-19-2026",
  "last_fueling_date": "4/2/2026",
  "last_fueling_qty": 1827
},
{
  "name": "COW654",
  "district": "JUBAIL",
  "city": "hafir Al Baten",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 27.256273,
  "lng": 47.038742,
  "next_fueling_plan": "SEC Site",
  "last_fueling_date": "#N/A",
  "last_fueling_qty": null
},
{
```

```
    "name": "COW655",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.2322,
    "lng": 50.11099,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW660",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.333635,
    "lng": 43.84338,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW667",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/22/2026",
    "last_fueling_qty": 1024
  },
  {
    "name": "COW668",
```

```
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.2158,
    "lng": 46.36139,
    "next_fueling_plan": "04-17-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1506
  },
  {
    "name": "COW712",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/22/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW713",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.567574,
    "lng": 46.577183,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW714",
    "district": "Riyadh City",
```

```
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.67543,
    "lng": 46.64043,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW715",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.808441,
    "lng": 46.42955,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1348
  },
  {
    "name": "COW716",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.76892,
    "lng": 46.64425,
    "next_fueling_plan": "04-03-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW720",
    "district": "Riyadh City",
    "city": "Riyadh City",
```

```
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.84925,
    "lng": 46.66972,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW721",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/29/2026",
    "last_fueling_qty": 1513
  },
  {
    "name": "COW725",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.892042,
    "lng": 46.921047,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1718
  },
  {
    "name": "COW726",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
```

```
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/19/2026",
    "last_fueling_qty": 1314
  },
  {
    "name": "COW727",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.0721,
    "lng": 47.41716,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 841
  },
  {
    "name": "COW728",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.703505,
    "lng": 46.606056,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW729",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.669031,
    "lng": 46.630623,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW731",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "In Progress",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.239916,
    "lng": 46.374924,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 948
  },
  {
    "name": "COW732",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.769476,
    "lng": 46.71753,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW734",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.79189,
    "lng": 46.597862,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1200
  },
  {
    "name": "COW735",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.734922,
    "lng": 46.577446,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW736",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.146614,
    "lng": 47.19173,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1954
  },
  {
    "name": "COW737",
    "district": "Riyadh District",
    "city": "Wadi Dawaseer",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 20.480911,
    "lng": 45.082382,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1289
  },
  {
    "name": "COW738",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.96425,
    "lng": 47.101307,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW739",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.70187,
    "lng": 45.59598,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1767
  },
  {
    "name": "COW740",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.845575,
    "lng": 46.740055,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW741",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.712563,
    "lng": 46.596905,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1817
  },
  {
    "name": "COW742",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.5304,
    "lng": 46.40582,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1476
  },
  {
    "name": "COW743",
    "district": "Riyadh District",
    "city": "Shaqra",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "Normal",
    "lat": 25.358215,
    "lng": 45.27161,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1958
  },
  {
    "name": "COW744",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.524227,
    "lng": 46.410217,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW745",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.233732,
    "lng": 47.09924,
    "next_fueling_plan": null,
    "last_fueling_date": "2/2/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW746",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 25.52486,
    "lng": 47.088577,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW747",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVIP",
    "lat": 24.77327,
    "lng": 46.526894,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW748",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1943
  },
  {
    "name": "COW749",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.65517,
```

```
    "lng": 45.727234,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1685
  },
  {
    "name": "COW750",
    "district": "Al-AHSA",
    "city": "Shaybah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 22.600384,
    "lng": 53.998672,
    "next_fueling_plan": "04-27-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 3400
  },
  {
    "name": "COW751",
    "district": "Riyadh District",
    "city": "Al kharaj",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.058374,
    "lng": 47.55768,
    "next_fueling_plan": "04-03-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1214
  },
  {
    "name": "COW753",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.9678,
    "lng": 46.6159,
```

```
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1200
  },
  {
    "name": "COW757",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/18/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW758",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.058111,
    "lng": 47.30743,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1592
  },
  {
    "name": "COW763",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.25609,
    "lng": 47.07598,
    "next_fueling_plan": "04-13-2026",
```

```
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW764",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.858644,
    "lng": 46.736744,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1513
  },
  {
    "name": "COW767",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "In Progress",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.239916,
    "lng": 46.374924,
    "next_fueling_plan": "#N/A",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW768",
    "district": "Riyadh District",
    "city": "Dowadmi",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.29376,
    "lng": 44.62865,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/24/2026",
```

```
    "last_fueling_qty": 1462
  },
  {
    "name": "COW769",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.85803,
    "lng": 46.76889,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1712
  },
  {
    "name": "COW770",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.7377,
    "lng": 46.74686,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW771",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
```

```
  },
  {
    "name": "COW772",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 25.3548,
    "lng": 47.48777,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1732
  },
  {
    "name": "COW773",
    "district": "Riyadh District",
    "city": "Wadi Dawaseer",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 20.14477,
    "lng": 45.13062,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1967
  },
  {
    "name": "COW774",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.719557,
    "lng": 45.543076,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1843
  },
```

```
{
  "name": "COW775",
  "district": "Riyadh District",
  "city": "Al kharaj",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.168491,
  "lng": 47.332954,
  "next_fueling_plan": "04-14-2026",
  "last_fueling_date": "4/1/2026",
  "last_fueling_qty": 1516
},
{
  "name": "COW776",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VIP",
  "lat": 24.97483,
  "lng": 46.92809,
  "next_fueling_plan": "04-14-2026",
  "last_fueling_date": "4/1/2026",
  "last_fueling_qty": 1286
},
{
  "name": "COW778",
  "district": "Riyadh District",
  "city": "Muzahmiya",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.517206,
  "lng": 46.26815,
  "next_fueling_plan": null,
  "last_fueling_date": "#N/A",
  "last_fueling_qty": null
},
{
```

```
    "name": "COW779",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.875586,
    "lng": 46.45432,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1300
  },
  {
    "name": "COW781",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "12/23/2025",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW801",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/26/2026",
    "last_fueling_qty": 1497
  },
  {
    "name": "COW802",
```

```
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.90011,
    "lng": 46.948082,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1412
  },
  {
    "name": "COW803",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW805",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW820",
    "district": "Riyadh City",
```

```
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVIP",
    "lat": 24.798887,
    "lng": 46.540035,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1371
  },
  {
    "name": "COW822",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.41521,
    "lng": 46.8424,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1300
  },
  {
    "name": "COW823",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.782145,
    "lng": 46.605755,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1312
  },
  {
    "name": "COW840",
    "district": "Riyadh District",
    "city": "Muzahmiya",
```

```
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/3/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW841",
    "district": "Riyadh District",
    "city": "Dirab",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.425184,
    "lng": 46.58667,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW842",
    "district": "Riyadh District",
    "city": "Al kharaj",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.17474,
    "lng": 47.21005,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW845",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
```

```
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1503
  },
  {
    "name": "COW846",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/14/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW854",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.685259,
    "lng": 46.634216,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1956
  },
  {
    "name": "COW855",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.61786,
    "lng": 46.51344,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW856",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.77779,
    "lng": 46.608013,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW857",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.717707,
    "lng": 46.581295,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1200
  },
  {
    "name": "COW858",
    "district": "Riyadh District",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.482801,
    "lng": 46.682594,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1143
  },
  {
    "name": "COW859",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.824314,
    "lng": 46.856533,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1200
  },
  {
    "name": "COW861",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.4695,
    "lng": 46.667,
    "next_fueling_plan": "04-25-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1464
  },
  {
    "name": "COWA629",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.7374,
    "lng": 44.76935,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1355
  },
  {
    "name": "COWE02",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.236307,
    "lng": 46.51158,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COWE03",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COWE05",
    "district": "Riyadh District",
    "city": "Jilha",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.325356,
    "lng": 45.916676,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1767
  },
  {
    "name": "COWJN1",
    "district": "NORTHERN BORDER",
    "city": "Rafah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 29.003613,
    "lng": 44.72298,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/28/2026",
    "last_fueling_qty": 705
  },
  {
    "name": "COWPC",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.70158,
    "lng": 46.67866,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWA003",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 1186
  },
  {
    "name": "CWA004",
    "district": "NORTHERN BORDER",
    "city": "Al-Jouf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 29.9765,
    "lng": 40.16956,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1850
  },
  {
    "name": "CWA005",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH001",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
```

```
    "lat": 26.240911,
    "lng": 49.911407,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1023
  },
  {
    "name": "CWH004",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.11578,
    "lng": 47.36891,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1882
  },
  {
    "name": "CWH006",
    "district": "Riyadh District",
    "city": "Al Ghat",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVIP",
    "lat": 25.785212,
    "lng": 44.69304,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 1643
  },
  {
    "name": "CWH008",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.92507,
```

```
    "lng": 49.930458,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1025
  },
  {
    "name": "CWH011",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.46702,
    "lng": 50.06988,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1325
  },
  {
    "name": "CWH012",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 24.96059,
    "lng": 49.43982,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH013",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
```

```
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH019",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.67406,
    "lng": 43.97404,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH020",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH022",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
```

```
    "last_fueling_date": "1/30/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH023",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.9367,
    "lng": 41.1017,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1550
  },
  {
    "name": "CWH024",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.01686,
    "lng": 43.822987,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH028",
    "district": "JUBAIL",
    "city": "Nariyah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.51617,
    "lng": 48.36225,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/2/2026",
```

```
    "last_fueling_qty": 1786
  },
  {
    "name": "CWH029",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.95475,
    "lng": 39.00115,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/5/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH030",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.819874,
    "lng": 48.672424,
    "next_fueling_plan": null,
    "last_fueling_date": null,
    "last_fueling_qty": null
  },
  {
    "name": "CWH031",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.34032,
    "lng": 49.4875,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/17/2026",
    "last_fueling_qty": 1557
```

```
  },
  {
    "name": "CWH032",
    "district": "Riyadh District",
    "city": "Majma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.084793,
    "lng": 45.215034,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1861
  },
  {
    "name": "CWH033",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.858393,
    "lng": 39.046783,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/5/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH040",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1530
  },
```

```
  {
    "name": "CWH041",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.509485,
    "lng": 49.252956,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1660
  },
  {
    "name": "CWH043",
    "district": "Riyadh District",
    "city": "Majma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.07149,
    "lng": 45.32088,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH045",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.88407,
    "lng": 41.20339,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1000
  },
  {
```

```
    "name": "CWH076",
    "district": "NORTHERN BORDER",
    "city": "Rafah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.078861,
    "lng": 42.82277,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH077",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.321096,
    "lng": 49.558197,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1440
  },
  {
    "name": "CWH084",
    "district": "DAMMAM",
    "city": "Dammam",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.24154,
    "lng": 50.12894,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 978
  },
  {
    "name": "CWH086",
```

```
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.359797,
    "lng": 44.09448,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1001
  },
  {
    "name": "CWH088",
    "district": "Qassim",
    "city": "Buraida",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.352869,
    "lng": 43.984013,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1001
  },
  {
    "name": "CWH089",
    "district": "Riyadh District",
    "city": "Majma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.086123,
    "lng": 45.290672,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1548
  },
  {
    "name": "CWH091",
    "district": "Hail",
```

```
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.398066,
    "lng": 41.714825,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1150
  },
  {
    "name": "CWH093",
    "district": "Jubail",
    "city": "Jubail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.09718,
    "lng": 49.09373,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1476
  },
  {
    "name": "CWH094",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.67764,
    "lng": 46.85573,
    "next_fueling_plan": null,
    "last_fueling_date": "2/8/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH185",
    "district": "DAMMAM",
    "city": "DAMMAM",
```

```
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.94794,
    "next_fueling_plan": null,
    "last_fueling_date": "12/2/2025",
    "last_fueling_qty": 840
  },
  {
    "name": "CWH186",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.833,
    "lng": 48.8475,
    "next_fueling_plan": null,
    "last_fueling_date": "1/24/2026",
    "last_fueling_qty": 1522
  },
  {
    "name": "CWH187",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/17/2026",
    "last_fueling_qty": 1091
  },
  {
    "name": "CWH188",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
```

```
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/8/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH190",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.94794,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH193",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/19/2026",
    "last_fueling_qty": 1473
  },
  {
    "name": "CWH194",
    "district": "Riyadh District",
    "city": "Zulfi",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.326626,
    "lng": 44.581394,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 1574
  },
  {
    "name": "CWH316",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.4367,
    "lng": 45.91904,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1898
  },
  {
    "name": "CWH317",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.566307,
    "lng": 41.654743,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1477
  },
  {
    "name": "CWH352",
    "district": "DAMMAM",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "2/6/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH935",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/28/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH937",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/22/2026",
    "last_fueling_qty": 1813
  },
  {
    "name": "CWH940",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/29/2026",
    "last_fueling_qty": 1119
  },
  {
    "name": "CWH941",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.70092,
    "lng": 46.87303,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH942",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.72473,
    "lng": 46.89682,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH943",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "3/7/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH944",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.6327,
    "lng": 46.89008,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH945",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/7/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH971",
    "district": "Riyadh District",
    "city": "Riyadh ",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH972",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 25.127125,
    "lng": 47.809155,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1862
  },
  {
    "name": "CWH973",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.35124,
    "lng": 43.762722,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1002
  },
  {
    "name": "CWN056",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN058",
    "district": "Jubail",
    "city": "Jubail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "VIP",
    "lat": 26.966322,
    "lng": 49.498177,
    "next_fueling_plan": "04-02-2026",
    "last_fueling_date": "3/16/2026",
    "last_fueling_qty": 1745
  },
  {
    "name": "CWN911",
    "district": "NORTHERN BORDER",
    "city": "Rafha",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.35173,
    "lng": 44.25038,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1282
  },
  {
    "name": "CWN918",
    "district": "Riyadh district",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.12232,
```

```
    "lng": 47.63788,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWN963",
    "district": "Riyadh District",
    "city": "AL-HAYSYA",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.90069,
    "lng": 46.13858,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "CWN964",
    "district": "Riyadh District",
    "city": "Dirab",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.42661,
    "lng": 46.58741,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN973",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
```

```
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN975",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN986",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.46544,
    "lng": 42.64941,
    "next_fueling_plan": null,
    "last_fueling_date": null,
    "last_fueling_qty": null
  },
  {
    "name": "CWN987",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.00515,
    "lng": 47.41512,
    "next_fueling_plan": null,
```

```
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN988",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.88932,
    "lng": 39.65717,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWN990",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 19.4774,
    "lng": 53.23433,
    "next_fueling_plan": null,
    "last_fueling_date": null,
    "last_fueling_qty": null
  },
  {
    "name": "CWS605",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.843334,
    "lng": 49.8065,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/24/2026",
```

```
    "last_fueling_qty": 1374
  },
  {
    "name": "CWS800",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.865713,
    "lng": 40.32728,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 2000
  },
  {
    "name": "CWS805",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.840729,
    "lng": 39.112827,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWS806",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "1/13/2026",
    "last_fueling_qty": 1270
```

```
  },
  {
    "name": "CWS808",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/7/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWS813",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.59266,
    "lng": 48.93513,
    "next_fueling_plan": null,
    "last_fueling_date": "1/27/2026",
    "last_fueling_qty": 1119
  },
  {
    "name": "CWS814",
    "district": "JUBAIL",
    "city": "AFAR AL BATEN",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.44564,
    "lng": 45.98281,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1923
  },
```

```
{
  "name": "CWS816",
  "district": "Al-AHSA",
  "city": "Abqiq",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 25.940962,
  "lng": 49.42586,
  "next_fueling_plan": "04-09-2026",
  "last_fueling_date": "3/29/2026",
  "last_fueling_qty": 1016
},
{
  "name": "CWS820",
  "district": "Qassim",
  "city": "Qassim",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 25.813257,
  "lng": 43.093296,
  "next_fueling_plan": "SEC Site",
  "last_fueling_date": "1/16/2026",
  "last_fueling_qty": 1000
},
{
  "name": "CWS821",
  "district": "JUBAIL",
  "city": "JUBAIL",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 26.90673,
  "lng": 49.49295,
  "next_fueling_plan": "04-05-2026",
  "last_fueling_date": "3/24/2026",
  "last_fueling_qty": 1453
},
{
```

```
    "name": "CWS831",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.813784,
    "lng": 48.661148,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1577
  },
  {
    "name": "CWS834",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 24.92084,
    "lng": 50.37997,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1471
  },
  {
    "name": "CWS836",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.618732,
    "lng": 44.06827,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1658
  },
  {
    "name": "CWS833",
```

```
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.09436,
    "lng": 49.50581,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1357
  },
  {
    "name": "CWS835",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.49808,
    "lng": 41.665028,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1497
  }
];

const SEED_MISSIONS = [
  {
    "missionId": "MSN-20260405-COW017",
    "siteName": "COW017",
    "generator": "COW017",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW518",
    "siteName": "COW518",
    "generator": "COW518",
    "project": "stc COW",
    "city": "Thumama",
    "quantityAddedLastTask": 1500,
    "notes": "Auto-generated   plan date: 04-04-2026"
```

```
},
{
  "missionId": "MSN-20260405-COW530",
  "siteName": "COW530",
  "generator": "COW530",
  "project": "stc COW",
  "city": "Muzahmiya",
  "quantityAddedLastTask": 925,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW013",
  "siteName": "COW013",
  "generator": "COW013",
  "project": "stc COW",
  "city": "Riyadh District",
  "quantityAddedLastTask": 1286,
  "notes": "Auto-generated   plan date: 04-05-2026"
},
{
  "missionId": "MSN-20260405-COW054",
  "siteName": "COW054",
  "generator": "COW054",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW619",
  "siteName": "COW619",
  "generator": "COW619",
  "project": "stc COW",
  "city": "Arar",
  "quantityAddedLastTask": 450,
  "notes": "Auto-generated   plan date: 04-03-2026"
},
{
  "missionId": "MSN-20260405-COW621",
  "siteName": "COW621",
  "generator": "COW621",
  "project": "stc COW",
  "city": "Riyadh District",
  "quantityAddedLastTask": 1743,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW534",
  "siteName": "COW534",
  "generator": "COW534",
  "project": "stc COW",
  "city": "Riyadh District",
```

```
    "quantityAddedLastTask": 1411,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-COW536",
    "siteName": "COW536",
    "generator": "COW536",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW542",
    "siteName": "COW542",
    "generator": "COW542",
    "project": "stc COW",
    "city": "Durma",
    "quantityAddedLastTask": 1563,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW600",
    "siteName": "COW600",
    "generator": "COW600",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 817,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW611",
    "siteName": "COW611",
    "generator": "COW611",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1524,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-COW615",
    "siteName": "COW615",
    "generator": "COW615",
    "project": "stc COW",
    "city": "Al Qamriyah",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW716",
    "siteName": "COW716",
    "generator": "COW716",
```

```
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-03-2026"
},
{
  "missionId": "MSN-20260405-COW720",
  "siteName": "COW720",
  "generator": "COW720",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW728",
  "siteName": "COW728",
  "generator": "COW728",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW737",
  "siteName": "COW737",
  "generator": "COW737",
  "project": "stc COW",
  "city": "Wadi Dawaseer",
  "quantityAddedLastTask": 1289,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW741",
  "siteName": "COW741",
  "generator": "COW741",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1817,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW742",
  "siteName": "COW742",
  "generator": "COW742",
  "project": "stc COW",
  "city": "Riyadh District",
  "quantityAddedLastTask": 1476,
  "notes": "Auto-generated   plan date: 04-05-2026"
},
{
  "missionId": "MSN-20260405-COW744",
```

```
    "siteName": "COW744",
    "generator": "COW744",
    "project": "stc COW",
    "city": "Durma",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW747",
    "siteName": "COW747",
    "generator": "COW747",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW749",
    "siteName": "COW749",
    "generator": "COW749",
    "project": "stc COW",
    "city": "Durma",
    "quantityAddedLastTask": 1685,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW751",
    "siteName": "COW751",
    "generator": "COW751",
    "project": "stc COW",
    "city": "Al kharaj",
    "quantityAddedLastTask": 1214,
    "notes": "Auto-generated   plan date: 04-03-2026"
  },
  {
    "missionId": "MSN-20260405-COW758",
    "siteName": "COW758",
    "generator": "COW758",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1592,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW772",
    "siteName": "COW772",
    "generator": "COW772",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1732,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
```

```
{
  "missionId": "MSN-20260405-COW854",
  "siteName": "COW854",
  "generator": "COW854",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1956,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COWJN1",
  "siteName": "COWJN1",
  "generator": "COWJN1",
  "project": "stc COW",
  "city": "Rafah",
  "quantityAddedLastTask": 705,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COWPC",
  "siteName": "COWPC",
  "generator": "COWPC",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW770",
  "siteName": "COW770",
  "generator": "COW770",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW820",
  "siteName": "COW820",
  "generator": "COW820",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1371,
  "notes": "Auto-generated   plan date: 04-05-2026"
},
{
  "missionId": "MSN-20260405-CWH076",
  "siteName": "CWH076",
  "generator": "CWH076",
  "project": "stc COW",
  "city": "Rafah",
  "quantityAddedLastTask": 1000,
```

```
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-CWN058",
    "siteName": "CWN058",
    "generator": "CWN058",
    "project": "stc COW",
    "city": "Jubail",
    "quantityAddedLastTask": 1745,
    "notes": "Auto-generated   plan date: 04-02-2026"
  },
  {
    "missionId": "MSN-20260405-CWS805",
    "siteName": "CWS805",
    "generator": "CWS805",
    "project": "stc COW",
    "city": "TURAIF",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-CWS821",
    "siteName": "CWS821",
    "generator": "CWS821",
    "project": "stc COW",
    "city": "JUBAIL",
    "quantityAddedLastTask": 1453,
    "notes": "Auto-generated   plan date: 04-05-2026"
  }
];

export async function runSeedIfEmpty(): Promise<void> {
  const [siteCount] = await db.select({ value: count() }).from(sitesTable);
  if (siteCount.value > 0) {
    return;
  }

  // Seed admin
  const adminPasswordHash = process.env.SEED_ADMIN_PASSWORD_HASH;
  if (!adminPasswordHash) {
    throw new Error("SEED_ADMIN_PASSWORD_HASH environment variable is not set. Cannot seed admin account.");
  }
  await db.insert(adminsTable).values({
    name: "Administrator",
    username: "Bannaga",
    email: "admin@aces-sa.com",
    passwordHash: adminPasswordHash,
    position: "Admin",
  }).onConflictDoNothing();

  // Seed sites in batches of 50
  for (let i = 0; i < SEED_SITES.length; i += 50) {
```

```
  const batch = SEED_SITES.slice(i, i + 50);
  await db.insert(sitesTable).values(batch.map((s: any) => ({
    name: s.name,
    district: s.district || "",
    city: s.city || "",
    project: s.project || "stc COW",
    cowStatus: s.cow_status || "ON-AIR",
    active: s.active !== false,
    currentLiters: s.current_liters || 0,
    dailyVirtual: s.daily_virtual || 0,
    region: s.region || "",
    siteLabel: s.site_label || "",
    lat: s.lat || null,
    lng: s.lng || null,
    nextFuelingPlan: s.next_fueling_plan || "",
    lastFuelingDate: s.last_fueling_date || "",
    lastFuelingQty: s.last_fueling_qty || null,
  }))).onConflictDoNothing();
}

// Seed missions in batches of 20
for (let i = 0; i < SEED_MISSIONS.length; i += 20) {
  const batch = SEED_MISSIONS.slice(i, i + 20);
  await db.insert(missionsTable).values(batch.map((m: any) => ({
    missionId: m.missionId,
    siteName: m.siteName,
    generator: m.generator,
    project: m.project,
    city: m.city,
    quantityAddedLastTask: m.quantityAddedLastTask,
    notes: m.notes,
    missionStatus: "Creation",
    createdBy: "System",
  }))).onConflictDoNothing();
}

// Seed drivers
const driverPasswordHash = process.env.SEED_DRIVER_PASSWORD_HASH;
if (!driverPasswordHash) {
  throw new Error("SEED_DRIVER_PASSWORD_HASH environment variable is not set. Cannot seed driver accounts.");
}
const insertedDrivers = await db.insert(driversTable).values([
  {
    name: "Bannaga Altieb",
    email: "bannaga.altieb@aces-co.com",
    phone: "+966542966343",
    zone: "stc COW CR",
    active: true,
    passwordHash: driverPasswordHash,
  },
  {
    name: "Bannaga",
```

```
    email: "bannaga2@aces-co.com",
    phone: "+966542966343",
    zone: "Central Region",
    active: true,
    passwordHash: driverPasswordHash,
  },
  {
    name: "Alshafeea",
    email: "alshafeea@aces-co.com",
    phone: "530048763",
    zone: "Central Region",
    active: true,
    passwordHash: driverPasswordHash,
  },
  {
    name: "Ayman",
    email: "ayman@aces-co.com",
    phone: "549872597",
    zone: "Central Region",
    active: true,
    passwordHash: driverPasswordHash,
  },
  {
    name: "Baliqh",
    email: "baliqh@aces-co.com",
    phone: "509471245",
    zone: "Central Region",
    active: true,
    passwordHash: driverPasswordHash,
  },
  {
    name: "Ameen",
    email: "ameen@aces-co.com",
    phone: "500580235",
    zone: "Central Region",
    active: true,
    passwordHash: driverPasswordHash,
  },
]).returning({ id: driversTable.id, name: driversTable.name });

// Build driver name ? id map
const driverIdMap: Record<string, number> = {};
for (const d of insertedDrivers) {
  driverIdMap[d.name] = d.id;
}

// Site ? driver assignments
const SITE_DRIVER_MAP: Record<string, string> = {
  COW543: "Alshafeea", COW548: "Alshafeea", COW653: "Alshafeea", COW750: "Alshafeea",
  CWH077: "Alshafeea", CWS834: "Alshafeea", CWH935: "Alshafeea", CWH937: "Alshafeea",
  COW304: "Alshafeea",
  COW512: "Ayman", CWH001: "Ayman", CWH008: "Ayman", CWH011: "Ayman",
```

```
    CWH084: "Ayman", CWS816: "Ayman",
    COW303: "Baliqh", COW305: "Baliqh", COW516: "Baliqh", COW528: "Baliqh",
    COW618: "Baliqh", CWH004: "Baliqh", CWH028: "Baliqh", CWH041: "Baliqh",
    CWH093: "Baliqh", CWH316: "Baliqh", CWS605: "Baliqh", CWN058: "Baliqh",
    CWS814: "Baliqh", CWS821: "Baliqh", CWS831: "Baliqh", CWS833: "Baliqh",
    COW310: "Ameen", COW527: "Ameen", COW619: "Ameen", COWJN1: "Ameen",
    CWA004: "Ameen", CWH023: "Ameen", CWH029: "Ameen", CWH033: "Ameen",
    CWH045: "Ameen", CWH076: "Ameen", CWN988: "Ameen", CWN911: "Ameen",
    CWS805: "Ameen",
  };

  // Group sites by driver
  const sitesByDriver: Record<string, string[]> = {};
  for (const [siteName, driverName] of Object.entries(SITE_DRIVER_MAP)) {
    if (!sitesByDriver[driverName]) sitesByDriver[driverName] = [];
    sitesByDriver[driverName].push(siteName);
  }

  // Update sites with driver assignments
  for (const [driverName, siteNames] of Object.entries(sitesByDriver)) {
    const driverId = driverIdMap[driverName];
    if (!driverId) continue;
    await db.update(sitesTable)
      .set({ assignedTechnicianId: driverId })
      .where(inArray(sitesTable.name, siteNames));
  }

  // Update missions with driver names
  for (const [driverName, siteNames] of Object.entries(sitesByDriver)) {
    const driverId = driverIdMap[driverName];
    if (!driverId) continue;
    await db.update(missionsTable)
      .set({ driverName, assignedDriver: driverName, assignedTechnicianId: driverId })
      .where(inArray(missionsTable.siteName, siteNames));
  }
}
```

FILE: artifacts/api-server/src/lib/sync-scheduler.ts
SIZE: 4,513 bytes

```
import { db } from "@workspace/db";
import { sitesTable } from "@workspace/db/schema";
import { eq } from "drizzle-orm";
import { logger } from "./logger";

const GOOGLE_SHEETS_URL =
  "https://script.google.com/macros/s/AKfycbxU7WENKAEkhJnBvCPbcGqiwZbUr5ZTT93Gfpw6AmiP7lPYfGUobDpOZh1qvppYgF3RVw
  /exec";

const EXCLUDED_REGIONS = new Set(["west", "south"]);
const EXCLUDED_SITES = new Set(["cow301"]);

const INTERVAL_MS = 24 * 60 * 60 * 1000; // 24 hours

export async function syncSitesFromSheets(): Promise<{
  inserted: number;
  updated: number;
  skipped: number;
  errors: string[];
  total: number;
}> {
  const response = await fetch(GOOGLE_SHEETS_URL, { redirect: "follow" });
  if (!response.ok) throw new Error(`Google Sheets fetch failed: ${response.status}`);

  const json = await response.json() as {
    energyDashboard?: { headers: string[]; rows: (string | number)[][] };
  };

  const dashboard = json.energyDashboard;
  if (!dashboard?.headers || !dashboard?.rows) throw new Error("Unexpected response format");

  const hdrs = dashboard.headers.map((h) => h.trim().toLowerCase());
  const col = (name: string) => hdrs.findIndex((h) => h === name.toLowerCase());

  const idxName     = col("sitename");
  const idxRegion   = col("regionname");
  const idxDistrict = col("districtname");
  const idxCity     = col("cityname");
  const idxStatus   = col("cowstatus");
  const idxLabel    = col("sitelabel");
  const idxLat      = col("lat");
  const idxLng      = col("lng");
  const idxNextPlan = col("nextfuelingplan");
  const idxLastDate = col("lastfuelingdate");
  const idxLastQty  = col("lastfuelingqty");

  if (idxName === -1) throw new Error("Column 'siteName' not found in Google Sheet");

  const existing = await db.select({ id: sitesTable.id, name: sitesTable.name }).from(sitesTable);
```

```
  const byName = new Map(existing.map((s) => [s.name.toLowerCase(), s.id]));

  let inserted = 0, updated = 0, skipped = 0;
  const errors: string[] = [];

  const safeFloat = (v: string | number | undefined) => {
    const n = parseFloat(String(v ?? ""));
    return isNaN(n) ? undefined : n;
  };

  for (const row of dashboard.rows) {
    const name = String(row[idxName] ?? "").trim();
    if (!name) { skipped++; continue; }
    if (EXCLUDED_SITES.has(name.toLowerCase())) { skipped++; continue; }

    const rowRegion = idxRegion >= 0 ? String(row[idxRegion] ?? "").trim().toLowerCase() : "";
    if (EXCLUDED_REGIONS.has(rowRegion)) { skipped++; continue; }

    const payload = {
      name,
      region:          idxRegion   >= 0 ? String(row[idxRegion]   ?? "") : undefined,
      district:        idxDistrict >= 0 ? String(row[idxDistrict] ?? "") : undefined,
      city:            idxCity     >= 0 ? String(row[idxCity]     ?? "") : undefined,
      cowStatus:       idxStatus   >= 0 ? String(row[idxStatus]   ?? "ON-AIR") : undefined,
      siteLabel:       idxLabel    >= 0 ? String(row[idxLabel]    ?? "") : undefined,
      lat:             safeFloat(row[idxLat]  as string),
      lng:             safeFloat(row[idxLng]  as string),
      nextFuelingPlan: idxNextPlan >= 0 ? String(row[idxNextPlan] ?? "") : undefined,
      lastFuelingDate: idxLastDate >= 0 ? String(row[idxLastDate] ?? "") : undefined,
      lastFuelingQty:  safeFloat(row[idxLastQty] as string),
    };

    try {
      const existingId = byName.get(name.toLowerCase());
      if (existingId !== undefined) {
        await db.update(sitesTable).set(payload).where(eq(sitesTable.id, existingId));
        updated++;
      } else {
        await db.insert(sitesTable).values({ ...payload, active: true });
        byName.set(name.toLowerCase(), -1);
        inserted++;
      }
    } catch (err) {
      errors.push(`"${name}": ${err instanceof Error ? err.message : String(err)}`);
    }
  }

  return { inserted, updated, skipped, errors, total: dashboard.rows.length };
}

export function startSiteSyncScheduler(): void {
  const run = async () => {
```

```
    logger.info("Auto-sync: fetching sites from Google Sheets ");
    try {
      const result = await syncSitesFromSheets();
      logger.info(
        { inserted: result.inserted, updated: result.updated, skipped: result.skipped, errors: result.errors.len
  gth },
        "Auto-sync complete"
      );
    } catch (err) {
      logger.error({ err }, "Auto-sync failed");
    }
  };

  // Run immediately on startup then every 24 hours
  run();
  setInterval(run, INTERVAL_MS);
  logger.info({ intervalHours: 24 }, "Site auto-sync scheduler started");
}
```

FILE: artifacts/api-server/src/lib/techToken.ts
SIZE: 2,365 bytes

```
import crypto from "crypto";

export const TOKEN_MAX_AGE_MS = 30 * 24 * 60 * 60 * 1000; // 30 days

export function getSecret(): string {
  const secret = process.env.SESSION_SECRET;
  if (!secret) throw new Error("SESSION_SECRET is not configured");
  return secret;
}

/**
 * Generate a HMAC-SHA256 signed bearer token.
 * Format: tech-{id}-{timestamp}-{hmac64hex}
 */
export function generateTechToken(technicianId: number): string {
  const timestamp = Date.now();
  const payload = `tech-${technicianId}-${timestamp}`;
  const hmac = crypto.createHmac("sha256", getSecret()).update(payload).digest("hex");
  return `${payload}-${hmac}`;
}

/**
 * Verify a signed bearer token and return the technicianId, or null if invalid.
 * Rejects: missing/malformed tokens, bad HMAC signatures, expired tokens (> 30 days),
 * future-dated tokens (negative age).
 */
export function verifyTechToken(authHeader: string | undefined): number | null {
  if (!authHeader || !authHeader.startsWith("Bearer ")) return null;
  const token = authHeader.slice(7);

  // Format: tech-{id}-{timestamp}-{hmac64hex}
  const firstDash = token.indexOf("-");
  const secondDash = token.indexOf("-", firstDash + 1);
  const thirdDash = token.indexOf("-", secondDash + 1);
  if (firstDash < 0 || secondDash < 0 || thirdDash < 0) return null;

  const prefix = token.slice(0, firstDash);
  if (prefix !== "tech") return null;

  const id = parseInt(token.slice(firstDash + 1, secondDash), 10);
  const timestamp = token.slice(secondDash + 1, thirdDash);
  const providedHmac = token.slice(thirdDash + 1);

  const ts = parseInt(timestamp, 10);
  if (isNaN(id) || isNaN(ts) || !providedHmac) return null;

  // Reject tokens older than 30 days or from the future
  const age = Date.now() - ts;
  if (age < 0 || age > TOKEN_MAX_AGE_MS) return null;
```

```
  const payload = `tech-${id}-${timestamp}`;
  let expectedHmac: string;
  try {
    expectedHmac = crypto.createHmac("sha256", getSecret()).update(payload).digest("hex");
  } catch {
    return null;
  }

  // Guard length mismatch before timingSafeEqual (throws if buffers differ in length)
  if (providedHmac.length !== expectedHmac.length) return null;

  // Constant-time comparison to prevent timing attacks
  if (!crypto.timingSafeEqual(Buffer.from(providedHmac, "utf8"), Buffer.from(expectedHmac, "utf8"))) return null
  ;

  return id;
}
```

FILE: artifacts/api-server/src/routes/admins.ts
SIZE: 3,922 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { adminsTable } from "@workspace/db/schema";
import { eq } from "drizzle-orm";
import crypto from "crypto";

const router: IRouter = Router();

function hashPassword(password: string): string {
  return crypto.createHash("sha256").update(password).digest("hex");
}

router.get("/admins", async (req, res) => {
  try {
    const admins = await db.select().from(adminsTable).orderBy(adminsTable.name);
    res.json(admins.map((a) => ({
      id: a.id,
      name: a.name,
      username: a.username,
      email: a.email,
      position: a.position,
      role: a.role,
      region: a.region,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list admins");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.post("/admins", async (req, res) => {
  try {
    const body = req.body;
    const [admin] = await db.insert(adminsTable).values({
      name: body.name,
      username: body.username,
      email: body.email || "",
      passwordHash: body.password ? hashPassword(body.password) : "",
      position: body.position || "User",
      role: body.role || "superadmin",
      region: body.region || "",
    }).returning();
    res.status(201).json({ id: admin.id, name: admin.name, username: admin.username, email: admin.email, positio
  n: admin.position, role: admin.role, region: admin.region });
  } catch (err) {
    req.log.error({ err }, "Failed to create admin");
    res.status(500).json({ error: "Internal server error" });
  }
});
```

```
router.put("/admins/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;
    const updateData: any = {
      name: body.name,
      username: body.username,
      email: body.email,
      position: body.position,
      role: body.role,
      region: body.region ?? "",
    };
    if (body.password) updateData.passwordHash = hashPassword(body.password);
    const [admin] = await db.update(adminsTable).set(updateData).where(eq(adminsTable.id, id)).returning();
    if (!admin) return res.status(404).json({ error: "Not found" });
    res.json({ id: admin.id, name: admin.name, username: admin.username, email: admin.email, position: admin.pos
  ition, role: admin.role, region: admin.region });
  } catch (err) {
    req.log.error({ err }, "Failed to update admin");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.delete("/admins/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    await db.delete(adminsTable).where(eq(adminsTable.id, id));
    res.status(204).send();
  } catch (err) {
    req.log.error({ err }, "Failed to delete admin");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.post("/auth/login", async (req, res) => {
  try {
    const { username, password } = req.body;
    if (!username || !password) return res.status(400).json({ error: "Username and password required" });

    const admins = await db.select().from(adminsTable).where(eq(adminsTable.username, username));
    const admin = admins[0];

    if (admin) {
      const hash = hashPassword(password);
      if (admin.passwordHash !== hash) return res.status(401).json({ error: "Invalid credentials" });
      return res.json({
        success: true,
        role: admin.role || "superadmin",
        region: admin.region || "",
        username: admin.username,
      });
```

```
    }

    // Fallback: hardcoded default admin
    if (username === "Bannaga" && password === "Aces@6343") {
      return res.json({
        success: true,
        role: "superadmin",
        username: "Bannaga",
      });
    }

    res.status(401).json({ error: "Invalid credentials" });
  } catch (err) {
    req.log.error({ err }, "Failed to login admin");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/dashboard.ts
SIZE: 3,324 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { missionsTable, driversTable } from "@workspace/db/schema";
import { sql, and, gte, eq } from "drizzle-orm";

const router: IRouter = Router();

router.get("/dashboard/kpis", async (req, res) => {
  try {
    const now = new Date();
    const todayStart = new Date(now.getFullYear(), now.getMonth(), now.getDate());
    const thirtyDaysAgo = new Date(now.getTime() - 30 * 24 * 60 * 60 * 1000);

    const [litersToday] = await db
      .select({ total: sql<number>`COALESCE(SUM(${missionsTable.filledLiters}), 0)` })
      .from(missionsTable)
      .where(gte(missionsTable.createdDate, todayStart));

    const [liters30d] = await db
      .select({ total: sql<number>`COALESCE(SUM(${missionsTable.filledLiters}), 0)` })
      .from(missionsTable)
      .where(gte(missionsTable.createdDate, thirtyDaysAgo));

    const [activeMissions] = await db
      .select({ count: sql<number>`COUNT(*)` })
      .from(missionsTable)
      .where(eq(missionsTable.missionStatus, "Creation"));

    const [activeDrivers] = await db
      .select({ count: sql<number>`COUNT(*)` })
      .from(driversTable)
      .where(eq(driversTable.active, true));

    const missionsByStatus = await db
      .select({ status: missionsTable.missionStatus, count: sql<number>`COUNT(*)` })
      .from(missionsTable)
      .groupBy(missionsTable.missionStatus);

    const missionsByZone = await db
      .select({ zone: missionsTable.city, count: sql<number>`COUNT(*)` })
      .from(missionsTable)
      .groupBy(missionsTable.city);

    const litersByZone = await db
      .select({ zone: missionsTable.city, liters: sql<number>`COALESCE(SUM(${missionsTable.filledLiters}), 0)` }
  )
      .from(missionsTable)
      .groupBy(missionsTable.city);
```

```
    const missionsByCategory = await db
      .select({ category: missionsTable.project, count: sql<number>`COUNT(*)` })
      .from(missionsTable)
      .groupBy(missionsTable.project);

    const approvedForInvoicing = await db
      .select({
        siteName: missionsTable.siteName,
        liters: missionsTable.filledLiters,
        date: missionsTable.createdDate,
      })
      .from(missionsTable)
      .where(eq(missionsTable.missionStatus, "Task approved"))
      .limit(20);

    res.json({
      litersToday: Number(litersToday?.total ?? 0),
      liters30d: Number(liters30d?.total ?? 0),
      activeMissions: Number(activeMissions?.count ?? 0),
      activeDrivers: Number(activeDrivers?.count ?? 0),
      missionsByStatus: missionsByStatus.map((r) => ({ status: r.status, count: Number(r.count) })),
      missionsByZone: missionsByZone.map((r) => ({ zone: r.zone || "Unknown", count: Number(r.count) })),
      litersByZone: litersByZone.map((r) => ({ zone: r.zone || "Unknown", liters: Number(r.liters) })),
      missionsByCategory: missionsByCategory.map((r) => ({ category: r.category || "Unknown", count: Number(r.co
  unt) })),
      approvedForInvoicing: approvedForInvoicing.map((r) => ({
        siteName: r.siteName,
        liters: r.liters,
        date: r.date?.toISOString() ?? null,
      })),
    });
  } catch (err) {
    req.log.error({ err }, "Failed to get dashboard KPIs");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/drivers.ts
SIZE: 13,493 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { driversTable, driverTasksTable, driverNotificationsTable, missionsTable, sitesTable, driverEntriesTable
   } from "@workspace/db/schema";
import { eq, desc, or, isNull } from "drizzle-orm";
import crypto from "crypto";

const router: IRouter = Router();

function hashPassword(password: string): string {
  return crypto.createHash("sha256").update(password).digest("hex");
}

function driverToJson(d: typeof driversTable.$inferSelect) {
  return {
    id: d.id,
    name: d.name,
    phone: d.phone,
    email: d.email,
    zone: d.zone,
    active: d.active,
    imageUrl: d.imageUrl ?? "",
  };
}

// List drivers
router.get("/drivers", async (req, res) => {
  try {
    const drivers = await db.select().from(driversTable).orderBy(driversTable.name);
    res.json(drivers.map(driverToJson));
  } catch (err) {
    req.log.error({ err }, "Failed to list drivers");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Create driver
router.post("/drivers", async (req, res) => {
  try {
    const body = req.body;
    const [driver] = await db.insert(driversTable).values({
      name: body.name,
      phone: body.phone || "",
      email: body.email || "",
      zone: body.zone || "",
      active: body.active !== undefined ? body.active : true,
      passwordHash: body.password ? hashPassword(body.password) : "",
      imageUrl: body.imageUrl || "",
    }).returning();
```

```
    res.status(201).json(driverToJson(driver));
  } catch (err) {
    req.log.error({ err }, "Failed to create driver");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Update driver
router.put("/drivers/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;
    const updateData: Partial<typeof driversTable.$inferInsert> = {
      name: body.name,
      phone: body.phone,
      email: body.email,
      zone: body.zone,
      active: body.active,
    };
    if (body.password) updateData.passwordHash = hashPassword(body.password);
    if (body.imageUrl !== undefined) updateData.imageUrl = body.imageUrl;
    const [driver] = await db.update(driversTable).set(updateData).where(eq(driversTable.id, id)).returning();
    if (!driver) return res.status(404).json({ error: "Not found" });
    res.json(driverToJson(driver));
  } catch (err) {
    req.log.error({ err }, "Failed to update driver");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Delete driver
router.delete("/drivers/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    await db.delete(driversTable).where(eq(driversTable.id, id));
    res.status(204).send();
  } catch (err) {
    req.log.error({ err }, "Failed to delete driver");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Driver login
router.post("/driver/login", async (req, res) => {
  try {
    const { email, password } = req.body;
    if (!email || !password) return res.status(400).json({ error: "Email and password required" });

    const [driver] = await db.select().from(driversTable).where(eq(driversTable.email, email));
    if (!driver) return res.status(401).json({ error: "Invalid credentials" });
    if (!driver.active) return res.status(401).json({ error: "Account is inactive" });
```

```
    const hash = hashPassword(password);
    if (driver.passwordHash !== hash) return res.status(401).json({ error: "Invalid credentials" });

    res.json({
      success: true,
      driverId: driver.id,
      name: driver.name,
      email: driver.email,
      phone: driver.phone,
      zone: driver.zone,
      imageUrl: driver.imageUrl ?? "",
      token: `driver-${driver.id}-${Date.now()}`,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to login driver");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Get driver tasks
router.get("/driver/tasks", async (req, res) => {
  try {
    const driverId = parseInt(String(req.query.driverId));
    const tasks = await db.select().from(driverTasksTable).where(eq(driverTasksTable.driverId, driverId)).orderB
  y(desc(driverTasksTable.scheduledAt));
    res.json(tasks.map((t) => ({
      id: t.id,
      driverId: t.driverId,
      siteId: t.siteId,
      siteName: t.siteName,
      missionId: t.missionId,
      scheduledAt: t.scheduledAt?.toISOString() ?? null,
      status: t.status,
      requiredLiters: t.requiredLiters,
      actualInTank: t.actualInTank,
      quantityAdded: t.quantityAdded,
      notes: t.notes,
      createdAt: t.createdAt?.toISOString() ?? null,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list driver tasks");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Get single driver task
router.get("/driver/tasks/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const [task] = await db.select().from(driverTasksTable).where(eq(driverTasksTable.id, id));
    if (!task) return res.status(404).json({ error: "Not found" });
    res.json({
```

```
      id: task.id,
      driverId: task.driverId,
      siteId: task.siteId,
      siteName: task.siteName,
      missionId: task.missionId,
      scheduledAt: task.scheduledAt?.toISOString() ?? null,
      status: task.status,
      requiredLiters: task.requiredLiters,
      actualInTank: task.actualInTank,
      quantityAdded: task.quantityAdded,
      notes: task.notes,
      createdAt: task.createdAt?.toISOString() ?? null,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to get driver task");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Update driver task
router.put("/driver/tasks/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;
    const [task] = await db.update(driverTasksTable).set({
      status: body.status,
      actualInTank: body.actualInTank,
      quantityAdded: body.quantityAdded,
      notes: body.notes,
      observations: body.observations,
    }).where(eq(driverTasksTable.id, id)).returning();
    if (!task) return res.status(404).json({ error: "Not found" });
    res.json(task);
  } catch (err) {
    req.log.error({ err }, "Failed to update driver task");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Get driver notifications
router.get("/driver/notifications", async (req, res) => {
  try {
    const driverId = parseInt(String(req.query.driverId));
    const notifs = await db.select().from(driverNotificationsTable)
      .where(eq(driverNotificationsTable.driverId, driverId))
      .orderBy(desc(driverNotificationsTable.createdAt));
    res.json(notifs.map((n) => ({
      id: n.id,
      driverId: n.driverId,
      title: n.title,
      message: n.message,
      type: n.type,
```

```
      read: n.read,
      createdAt: n.createdAt?.toISOString() ?? null,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list driver notifications");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Get all missions for driver app (filtered by driverId if provided)
router.get("/driver/missions", async (req, res) => {
  try {
    const driverId = req.query.driverId ? parseInt(String(req.query.driverId)) : null;
    const query = db.select().from(missionsTable);
    const missions = driverId
      ? await query.where(eq(missionsTable.assignedTechnicianId, driverId)).orderBy(desc(missionsTable.createdAt
  ))
      : await query.orderBy(desc(missionsTable.createdAt));
    res.json(missions.map((m) => ({
      id: m.id,
      missionId: m.missionId,
      siteName: m.siteName,
      generator: m.generator,
      project: m.project,
      driverName: m.driverName,
      assignedDriver: m.assignedDriver,
      city: m.city,
      filledLiters: m.filledLiters,
      virtualCalculated: m.virtualCalculated,
      actualInTank: m.actualInTank,
      quantityAddedLastTask: m.quantityAddedLastTask,
      notes: m.notes,
      missionStatus: m.missionStatus,
      createdBy: m.createdBy,
      createdDate: m.createdDate?.toISOString() ?? null,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list driver missions");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Get single mission for driver app (includes site lat/lng)
router.get("/driver/missions/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const [mission] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));
    if (!mission) return res.status(404).json({ error: "Mission not found" });
    let siteLat: number | null = null;
    let siteLng: number | null = null;
    if (mission.siteName) {
      const [site] = await db.select({ lat: sitesTable.lat, lng: sitesTable.lng })
```

```
        .from(sitesTable).where(eq(sitesTable.name, mission.siteName));
      if (site) { siteLat = site.lat; siteLng = site.lng; }
    }
    res.json({
      id: mission.id,
      missionId: mission.missionId,
      siteName: mission.siteName,
      generator: mission.generator,
      project: mission.project,
      driverName: mission.driverName,
      assignedDriver: mission.assignedDriver,
      city: mission.city,
      filledLiters: mission.filledLiters,
      virtualCalculated: mission.virtualCalculated,
      actualInTank: mission.actualInTank,
      quantityAddedLastTask: mission.quantityAddedLastTask,
      notes: mission.notes,
      missionStatus: mission.missionStatus,
      createdBy: mission.createdBy,
      createdDate: mission.createdDate?.toISOString() ?? null,
      siteLat,
      siteLng,
      litersBefore: mission.litersBefore ?? null,
      litersAdded: mission.litersAdded ?? null,
      completionDate: mission.completionDate?.toISOString() ?? null,
      odoBeforePhoto: mission.odoBeforePhoto ?? null,
      odoAfterPhoto: mission.odoAfterPhoto ?? null,
      tankBeforePhoto: mission.tankBeforePhoto ?? null,
      tankAfterPhoto: mission.tankAfterPhoto ?? null,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to get driver mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Driver updates mission status, entries, and photos
router.put("/driver/missions/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const {
      missionStatus, notes, driverName,
      litersBefore, litersAdded, completionDate,
      odoBeforePhoto, odoAfterPhoto, tankBeforePhoto, tankAfterPhoto,
    } = req.body;
    const [updated] = await db
      .update(missionsTable)
      .set({
        ...(missionStatus && { missionStatus }),
        ...(notes !== undefined && { notes }),
        ...(driverName && { driverName }),
        ...(litersBefore !== undefined && litersBefore !== null && { litersBefore: parseFloat(litersBefore) }),
```

```
        ...(litersAdded !== undefined && litersAdded !== null && { litersAdded: parseFloat(litersAdded) }),
        ...(completionDate && { completionDate: new Date(completionDate) }),
        ...(odoBeforePhoto !== undefined && { odoBeforePhoto }),
        ...(odoAfterPhoto !== undefined && { odoAfterPhoto }),
        ...(tankBeforePhoto !== undefined && { tankBeforePhoto }),
        ...(tankAfterPhoto !== undefined && { tankAfterPhoto }),
      })
      .where(eq(missionsTable.id, id))
      .returning();
    if (!updated) return res.status(404).json({ error: "Mission not found" });

    if (missionStatus === "Finished by Driver") {
      const [existingEntry] = await db.select({ id: driverEntriesTable.id })
        .from(driverEntriesTable).where(eq(driverEntriesTable.missionId, id));
      if (existingEntry) {
        await db.update(driverEntriesTable).set({
          driverName: driverName || updated.driverName,
          litersBefore: litersBefore != null ? parseFloat(litersBefore) : undefined,
          litersAdded: litersAdded != null ? parseFloat(litersAdded) : undefined,
          completionDate: completionDate ? new Date(completionDate) : undefined,
          notes: notes || "",
          ...(odoBeforePhoto !== undefined && { odoBeforePhoto }),
          ...(odoAfterPhoto !== undefined && { odoAfterPhoto }),
          ...(tankBeforePhoto !== undefined && { tankBeforePhoto }),
          ...(tankAfterPhoto !== undefined && { tankAfterPhoto }),
        }).where(eq(driverEntriesTable.id, existingEntry.id));
      } else {
        await db.insert(driverEntriesTable).values({
          missionId: id,
          missionRef: updated.missionId || `MSN-${id}`,
          siteName: updated.siteName,
          driverId: updated.assignedTechnicianId ?? undefined,
          driverName: driverName || updated.driverName,
          litersBefore: litersBefore != null ? parseFloat(litersBefore) : undefined,
          litersAdded: litersAdded != null ? parseFloat(litersAdded) : undefined,
          completionDate: completionDate ? new Date(completionDate) : undefined,
          notes: notes || "",
          odoBeforePhoto: odoBeforePhoto ?? undefined,
          odoAfterPhoto: odoAfterPhoto ?? undefined,
          tankBeforePhoto: tankBeforePhoto ?? undefined,
          tankAfterPhoto: tankAfterPhoto ?? undefined,
        });
      }
    }

    res.json({ success: true, id: updated.id, missionStatus: updated.missionStatus });
  } catch (err) {
    req.log.error({ err }, "Failed to update driver mission");
    res.status(500).json({ error: "Internal server error" });
  }
});
```

```
export default router;
```

FILE: artifacts/api-server/src/routes/generators.ts
SIZE: 2,441 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { generatorsTable } from "@workspace/db/schema";
import { eq } from "drizzle-orm";

const router: IRouter = Router();

router.get("/generators", async (req, res) => {
  try {
    const generators = await db.select().from(generatorsTable).orderBy(generatorsTable.name);
    res.json(generators.map((g) => ({
      id: g.id,
      name: g.name,
      site: g.site,
      siteId: g.siteId,
      dailyVirtual: g.dailyVirtual,
      lastAvg: g.lastAvg,
      rateOk: g.rateOk,
      active: g.active,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list generators");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.post("/generators", async (req, res) => {
  try {
    const body = req.body;
    const [generator] = await db.insert(generatorsTable).values({
      name: body.name,
      site: body.site || "",
      siteId: body.siteId || 0,
      dailyVirtual: body.dailyVirtual || 0,
      lastAvg: body.lastAvg || 0,
      rateOk: body.rateOk !== undefined ? body.rateOk : true,
      active: body.active !== undefined ? body.active : true,
    }).returning();
    res.status(201).json(generator);
  } catch (err) {
    req.log.error({ err }, "Failed to create generator");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.put("/generators/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;
```

```
    const [generator] = await db.update(generatorsTable).set({
      name: body.name,
      site: body.site,
      siteId: body.siteId,
      dailyVirtual: body.dailyVirtual,
      lastAvg: body.lastAvg,
      rateOk: body.rateOk,
      active: body.active,
    }).where(eq(generatorsTable.id, id)).returning();
    if (!generator) return res.status(404).json({ error: "Not found" });
    res.json(generator);
  } catch (err) {
    req.log.error({ err }, "Failed to update generator");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.delete("/generators/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    await db.delete(generatorsTable).where(eq(generatorsTable.id, id));
    res.status(204).send();
  } catch (err) {
    req.log.error({ err }, "Failed to delete generator");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/health.ts
SIZE: 288 bytes

```
import { Router, type IRouter } from "express";
import { HealthCheckResponse } from "@workspace/api-zod";

const router: IRouter = Router();

router.get("/healthz", (_req, res) => {
  const data = HealthCheckResponse.parse({ status: "ok" });
  res.json(data);
});

export default router;
```

FILE: artifacts/api-server/src/routes/index.ts
SIZE: 930 bytes

```
import { Router, type IRouter } from "express";
import healthRouter from "./health";
import seedRouter from "./seed";
import missionsRouter from "./missions";
import driversRouter from "./drivers";
import sitesRouter from "./sites";
import generatorsRouter from "./generators";
import notificationsRouter from "./notifications";
import settingsRouter from "./settings";
import adminsRouter from "./admins";
import techniciansRouter from "./technicians";
import dashboardRouter from "./dashboard";
import storageRouter from "./storage";

const router: IRouter = Router();

router.use(healthRouter);
router.use(seedRouter);
router.use(missionsRouter);
router.use(driversRouter);
router.use(sitesRouter);
router.use(generatorsRouter);
router.use(notificationsRouter);
router.use(settingsRouter);
router.use(adminsRouter);
router.use(techniciansRouter);
router.use(dashboardRouter);
router.use(storageRouter);

export default router;
```

FILE: artifacts/api-server/src/routes/missions.ts
SIZE: 16,307 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { missionsTable, techniciansTable, sitesTable, driverEntriesTable, reportLinesTable } from "@workspace/db
  /schema";
import { eq, desc, ne, and } from "drizzle-orm";
import { logger } from "../lib/logger";

const router: IRouter = Router();

async function sendExpoPushNotification(token: string, title: string, body: string, data?: Record<string, unknow
  n>) {
  // Accept both "ExponentPushToken[...]" (Expo Go) and "ExpoPushToken[...]" (EAS builds)
  if (!token || !(token.startsWith("ExponentPushToken") || token.startsWith("ExpoPushToken"))) return;
  try {
    const response = await fetch("https://exp.host/--/api/v2/push/send", {
      method: "POST",
      headers: {
        "Content-Type": "application/json",
        Accept: "application/json",
      },
      body: JSON.stringify({ to: token, title, body, data: data ?? {} }),
    });
    if (!response.ok) {
      const text = await response.text().catch(() => "");
      logger.warn({ status: response.status, body: text }, "Expo push send returned non-OK status");
    }
  } catch (err) {
    // Non-critical: push failures should not break the mission update request
    logger.warn({ err }, "Expo push notification failed (network/timeout)");
  }
}

router.get("/missions", async (req, res) => {
  try {
    const missions = await db
      .select({ mission: missionsTable, siteRegion: sitesTable.region })
      .from(missionsTable)
      .leftJoin(sitesTable, eq(missionsTable.siteName, sitesTable.name))
      .orderBy(desc(missionsTable.createdAt));
    const result = missions.map(({ mission: m, siteRegion }) => ({
      id: m.id,
      missionId: m.missionId,
      siteName: m.siteName,
      generator: m.generator,
      project: m.project,
      driverName: m.driverName,
      assignedDriver: m.assignedDriver,
      createdDate: m.createdDate?.toISOString() ?? null,
      filledLiters: m.filledLiters,
```

```
      virtualCalculated: m.virtualCalculated,
      actualInTank: m.actualInTank,
      quantityAddedLastTask: m.quantityAddedLastTask,
      city: m.city,
      region: siteRegion || m.city || "",
      notes: m.notes,
      missionStatus: m.missionStatus,
      createdBy: m.createdBy,
      technicianRemark: m.technicianRemark,
      technicianStatus: m.technicianStatus,
      reviewedBy: m.reviewedBy,
      reviewedAt: m.reviewedAt?.toISOString() ?? null,
      assignedTechnicianId: m.assignedTechnicianId,
    }));
    res.json(result);
  } catch (err) {
    req.log.error({ err }, "Failed to list missions");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.post("/missions", async (req, res) => {
  try {
    const body = req.body;
    const missionId = `MSN-${Date.now()}`;
    const [mission] = await db.insert(missionsTable).values({
      missionId,
      siteName: body.siteName || "",
      generator: body.generator || "",
      project: body.project || "stc COW",
      driverName: body.driverName || "",
      assignedDriver: body.assignedDriver || "",
      filledLiters: body.filledLiters || 0,
      virtualCalculated: body.virtualCalculated || 0,
      actualInTank: body.actualInTank || 0,
      quantityAddedLastTask: body.quantityAddedLastTask || 0,
      city: body.city || "",
      notes: body.notes || "",
      missionStatus: body.missionStatus || "Creation",
      createdBy: body.createdBy || "",
      assignedTechnicianId: body.assignedTechnicianId ?? null,
    }).returning();
    // Send push notification if a technician was assigned at creation time
    if (mission.assignedTechnicianId) {
      const [tech] = await db.select().from(techniciansTable)
        .where(eq(techniciansTable.id, mission.assignedTechnicianId));
      const pushToken = tech?.fcmToken ?? tech?.expoPushToken ?? null;
      if (pushToken) {
        sendExpoPushNotification(
          pushToken,
          "New Mission Assigned",
          `Site: ${mission.siteName}   ${mission.missionId}`,
```

```
          { missionId: mission.id },
        );
      }
    }

    res.status(201).json(mission);
  } catch (err) {
    req.log.error({ err }, "Failed to create mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.get("/missions/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const [mission] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));
    if (!mission) return res.status(404).json({ error: "Not found" });
    res.json(mission);
  } catch (err) {
    req.log.error({ err }, "Failed to get mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.put("/missions/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;

    const [before] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));

    const updateData: Partial<typeof missionsTable.$inferInsert> = {
      siteName: body.siteName,
      generator: body.generator,
      project: body.project,
      driverName: body.driverName,
      assignedDriver: body.assignedDriver,
      filledLiters: body.filledLiters,
      virtualCalculated: body.virtualCalculated,
      actualInTank: body.actualInTank,
      quantityAddedLastTask: body.quantityAddedLastTask,
      city: body.city,
      notes: body.notes,
      missionStatus: body.missionStatus,
    };

    if (body.assignedTechnicianId !== undefined) {
      updateData.assignedTechnicianId = body.assignedTechnicianId ?? null;
    }

    const [updated] = await db.update(missionsTable).set(updateData).where(eq(missionsTable.id, id)).returning()
  ;
```

```
    if (!updated) return res.status(404).json({ error: "Not found" });

    // Send push notification if a technician was newly assigned
    const newTechId = body.assignedTechnicianId;
    const oldTechId = before?.assignedTechnicianId;
    if (newTechId && newTechId !== oldTechId) {
      const [tech] = await db.select().from(techniciansTable).where(eq(techniciansTable.id, newTechId));
      const pushToken = tech?.fcmToken ?? tech?.expoPushToken ?? null;
      if (pushToken) {
        sendExpoPushNotification(
          pushToken,
          "New Mission Assigned",
          `Site: ${updated.siteName}   ${updated.missionId}`,
          { missionId: updated.id },
        );
      }
    }

    res.json(updated);
  } catch (err) {
    req.log.error({ err }, "Failed to update mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.delete("/missions/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    await db.delete(missionsTable).where(eq(missionsTable.id, id));
    res.status(204).send();
  } catch (err) {
    req.log.error({ err }, "Failed to delete mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

/**
 * POST /missions/generate-from-sites
 * Creates missions for every site whose nextFuelingPlan is today or overdue,
 * skipping any site that already has an open (non-Canceled) mission.
 */
router.post("/missions/generate-from-sites", async (req, res) => {
  try {
    const today = new Date();
    today.setHours(0, 0, 0, 0);

    // Fetch all sites with a fueling plan date
    const sites = await db.select().from(sitesTable);

    // Fetch existing open missions (not Canceled) to avoid duplicates
    const openMissions = await db
      .select({ siteName: missionsTable.siteName })
```

```
    .from(missionsTable)
    .where(ne(missionsTable.missionStatus, "Canceled"));
  const openSiteNames = new Set(openMissions.map((m) => m.siteName.toLowerCase()));

  let created = 0;
  let skipped = 0;
  const errors: string[] = [];

  // Date stamp for mission IDs: YYYYMMDD
  const stamp = today.toISOString().slice(0, 10).replace(/-/g, "");

  for (const site of sites) {
    const planStr = (site.nextFuelingPlan ?? "").trim();
    if (!planStr || planStr === "#N/A") { skipped++; continue; }

    // Parse MM-DD-YYYY format
    const parts = planStr.split("-");
    if (parts.length !== 3) { skipped++; continue; }
    const [mm, dd, yyyy] = parts;
    const planDate = new Date(Number(yyyy), Number(mm) - 1, Number(dd));
    planDate.setHours(0, 0, 0, 0);
    if (isNaN(planDate.getTime()) || planDate > today) { skipped++; continue; }

    // Skip if an open mission already exists for this site
    if (openSiteNames.has(site.name.toLowerCase())) { skipped++; continue; }

    try {
      const missionId = `MSN-${stamp}-${site.name}`;
      await db.insert(missionsTable).values({
        missionId,
        siteName:              site.name,
        generator:             site.name,
        project:               site.project || "stc COW",
        city:                  site.city || "",
        driverName:            "",
        assignedDriver:        "",
        filledLiters:          0,
        virtualCalculated:     0,
        actualInTank:          0,
        quantityAddedLastTask: site.lastFuelingQty ?? 0,
        missionStatus:         "Creation",
        createdBy:             "System",
        notes:                 `Auto-generated   plan date: ${planStr}`,
        assignedTechnicianId:  site.assignedTechnicianId ?? undefined,
      });
      openSiteNames.add(site.name.toLowerCase()); // prevent double-insert in same run
      created++;
    } catch (err) {
      errors.push(`"${site.name}": ${err instanceof Error ? err.message : String(err)}`);
    }
  }
```

```
    res.json({ created, skipped, errors, total: sites.length });
  } catch (err) {
    req.log.error({ err }, "Failed to generate missions from sites");
    res.status(500).json({ error: "Internal server error" });
  }
});

// GET driver entry submission for a mission
router.get("/missions/:id/entry", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const [entry] = await db.select().from(driverEntriesTable)
      .where(eq(driverEntriesTable.missionId, id));
    if (!entry) {
      // Fallback: read from missions table directly (legacy data)
      const [m] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));
      if (!m) return res.status(404).json({ error: "Not found" });
      return res.json({
        missionId: id,
        missionRef: m.missionId,
        siteName: m.siteName,
        driverName: m.driverName,
        litersBefore: m.litersBefore,
        litersAdded: m.litersAdded,
        completionDate: m.completionDate?.toISOString() ?? null,
        notes: m.notes,
        odoBeforePhoto: m.odoBeforePhoto,
        odoAfterPhoto: m.odoAfterPhoto,
        tankBeforePhoto: m.tankBeforePhoto,
        tankAfterPhoto: m.tankAfterPhoto,
        submittedAt: null,
      });
    }
    res.json({
      id: entry.id,
      missionId: entry.missionId,
      missionRef: entry.missionRef,
      siteName: entry.siteName,
      driverName: entry.driverName,
      litersBefore: entry.litersBefore,
      litersAdded: entry.litersAdded,
      completionDate: entry.completionDate?.toISOString() ?? null,
      notes: entry.notes,
      odoBeforePhoto: entry.odoBeforePhoto,
      odoAfterPhoto: entry.odoAfterPhoto,
      tankBeforePhoto: entry.tankBeforePhoto,
      tankAfterPhoto: entry.tankAfterPhoto,
      submittedAt: entry.submittedAt?.toISOString() ?? null,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to get driver entry");
    res.status(500).json({ error: "Internal server error" });
```

```
  }
});

// Approve a mission ? set status + create report_line
router.post("/missions/:id/approve", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const { approvedBy = "Admin", unitPrice } = req.body ?? {};
    const [mission] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));
    if (!mission) return res.status(404).json({ error: "Mission not found" });
    // Update mission status
    await db.update(missionsTable)
      .set({ missionStatus: "Task approved", reviewedBy: approvedBy, reviewedAt: new Date() })
      .where(eq(missionsTable.id, id));
    // Get site region
    const [site] = await db.select({ city: sitesTable.city, region: sitesTable.region })
      .from(sitesTable).where(eq(sitesTable.name, mission.siteName));
    const region = site?.region || site?.city || mission.city || "";
    // Create report_line
    const litersAdded = mission.litersAdded ?? mission.quantityAddedLastTask ?? 0;
    await db.insert(reportLinesTable).values({
      missionId: id,
      missionRef: mission.missionId || `MSN-${id}`,
      siteName: mission.siteName,
      region,
      project: mission.project || "stc COW",
      driverName: mission.driverName,
      litersAdded,
      completionDate: mission.completionDate ?? mission.createdDate ?? new Date(),
      approvedBy,
      unitPrice: unitPrice ?? 0.63,
    });
    res.json({ success: true, missionStatus: "Task approved" });
  } catch (err) {
    req.log.error({ err }, "Failed to approve mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Reject a mission
router.post("/missions/:id/reject", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const { rejectedBy = "Admin" } = req.body ?? {};
    const [mission] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));
    if (!mission) return res.status(404).json({ error: "Mission not found" });
    await db.update(missionsTable)
      .set({ missionStatus: "Canceled", reviewedBy: rejectedBy, reviewedAt: new Date() })
      .where(eq(missionsTable.id, id));
    res.json({ success: true, missionStatus: "Canceled" });
  } catch (err) {
    req.log.error({ err }, "Failed to reject mission");
```

```
    res.status(500).json({ error: "Internal server error" });
  }
});

// Send mission back to driver
router.post("/missions/:id/send-back", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const [mission] = await db.select().from(missionsTable).where(eq(missionsTable.id, id));
    if (!mission) return res.status(404).json({ error: "Mission not found" });
    await db.update(missionsTable)
      .set({ missionStatus: "Creation", reviewedAt: new Date() })
      .where(eq(missionsTable.id, id));
    res.json({ success: true, missionStatus: "Creation" });
  } catch (err) {
    req.log.error({ err }, "Failed to send mission back");
    res.status(500).json({ error: "Internal server error" });
  }
});

// GET report lines (for invoice preparation)
router.put("/report-lines/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;
    const updateData: any = {};
    if (body.litersAdded !== undefined) updateData.litersAdded = body.litersAdded;
    if (body.driverName !== undefined) updateData.driverName = body.driverName;
    const [updated] = await db.update(reportLinesTable).set(updateData).where(eq(reportLinesTable.id, id)).retur
  ning();
    if (!updated) return res.status(404).json({ error: "Not found" });
    res.json({ id: updated.id, missionRef: updated.missionRef, siteName: updated.siteName, litersAdded: updated.
  litersAdded });
  } catch (err) {
    req.log.error({ err }, "Failed to update report line");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.get("/report-lines", async (req, res) => {
  try {
    const lines = await db.select().from(reportLinesTable)
      .orderBy(desc(reportLinesTable.approvedAt));
    res.json(lines.map((l) => ({
      id: l.id,
      missionId: l.missionId,
      missionRef: l.missionRef,
      siteName: l.siteName,
      region: l.region,
      project: l.project,
      driverName: l.driverName,
      litersAdded: l.litersAdded,
```

```
      completionDate: l.completionDate?.toISOString() ?? null,
      approvedAt: l.approvedAt?.toISOString() ?? null,
      approvedBy: l.approvedBy,
      unitPrice: l.unitPrice,
      invoicePeriodStart: l.invoicePeriodStart?.toISOString() ?? null,
      invoicePeriodEnd: l.invoicePeriodEnd?.toISOString() ?? null,
      invoiceExported: l.invoiceExported,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to get report lines");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/notifications.ts
SIZE: 1,260 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { notificationsTable } from "@workspace/db/schema";
import { desc } from "drizzle-orm";

const router: IRouter = Router();

router.get("/notifications", async (req, res) => {
  try {
    const notifs = await db.select().from(notificationsTable).orderBy(desc(notificationsTable.createdAt));
    res.json(notifs.map((n) => ({
      id: n.id,
      title: n.title,
      message: n.message,
      driverName: n.driverName,
      sentBy: n.sentBy,
      createdAt: n.createdAt?.toISOString() ?? null,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list notifications");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.post("/notifications", async (req, res) => {
  try {
    const body = req.body;
    const [notif] = await db.insert(notificationsTable).values({
      title: body.title,
      message: body.message,
      driverName: body.driverName || null,
      sentBy: body.sentBy || "Admin",
    }).returning();
    res.status(201).json(notif);
  } catch (err) {
    req.log.error({ err }, "Failed to create notification");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/seed.ts
SIZE: 109,679 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { adminsTable, sitesTable, missionsTable, driversTable } from "@workspace/db/schema";
import { count } from "drizzle-orm";
import crypto from "crypto";

const router: IRouter = Router();

function hashPassword(password: string): string {
  return crypto.createHash("sha256").update(password).digest("hex");
}

const adminPasswordHash = hashPassword(process.env.SEED_ADMIN_PASSWORD ?? "Admin@1234");
const driverPasswordHash = hashPassword(process.env.SEED_DRIVER_PASSWORD ?? "Driver@1234");

const SEED_SITES = [
  {
    "name": "COW001",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.787048,
    "lng": 46.557983,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW002",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.902332,
    "lng": 46.52644,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
```

```
  },
  {
    "name": "COW011",
    "district": "Riyadh District",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.68431,
    "lng": 46.487648,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1901
  },
  {
    "name": "COW012",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 24.665045,
    "lng": 46.65332,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/28/2026",
    "last_fueling_qty": 1493
  },
  {
    "name": "COW013",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.55672,
    "lng": 46.28677,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1286
  },
```

```
{
  "name": "COW015",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.76868,
  "lng": 46.63688,
  "next_fueling_plan": "04-16-2026",
  "last_fueling_date": "4/4/2026",
  "last_fueling_qty": 1500
},
{
  "name": "COW016",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VIP",
  "lat": 24.929005,
  "lng": 46.381664,
  "next_fueling_plan": "04-12-2026",
  "last_fueling_date": "3/30/2026",
  "last_fueling_qty": 1244
},
{
  "name": "COW017",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.719574,
  "lng": 46.60797,
  "next_fueling_plan": "04-04-2026",
  "last_fueling_date": "3/27/2026",
  "last_fueling_qty": 1000
},
{
```

```
    "name": "COW019",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.738,
    "lng": 46.574318,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW020",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.79591,
    "lng": 46.54063,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1530
  },
  {
    "name": "COW054",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.718904,
    "lng": 46.644096,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW055",
```

```
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.779305,
    "lng": 46.594463,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW056",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.893806,
    "lng": 46.530388,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW057",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.86628,
    "lng": 46.5586,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1127
  },
  {
    "name": "COW058",
    "district": "Riyadh City",
```

```
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.871113,
    "lng": 46.573414,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW059",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.695736,
    "lng": 46.58221,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1295
  },
  {
    "name": "COW061",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.106527,
    "lng": 46.387585,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW063",
    "district": "Riyadh District",
    "city": "Al kharaj",
```

```
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.073214,
    "lng": 47.244053,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1784
  },
  {
    "name": "COW303",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.56186,
    "lng": 47.71272,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1886
  },
  {
    "name": "COW304",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.410555,
    "lng": 50.080833,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1173
  },
  {
    "name": "COW305",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
```

```
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.12298,
    "lng": 45.67255,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "3/28/2026",
    "last_fueling_qty": 2298
  },
  {
    "name": "COW307",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.870815,
    "lng": 41.813095,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1397
  },
  {
    "name": "COW308",
    "district": "Riyadh District",
    "city": "al Ghat",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.06806,
    "lng": 44.902718,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 988
  },
  {
    "name": "COW309",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.81736,
    "lng": 41.68107,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1300
  },
  {
    "name": "COW310",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.53616,
    "lng": 40.67132,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW312",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.940174,
    "lng": 50.10601,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/26/2026",
    "last_fueling_qty": 1479
  },
  {
    "name": "COW510",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.900503,
    "lng": 46.13521,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1394
  },
  {
    "name": "COW511",
    "district": "Riyadh District",
    "city": "Wadi Dawaseer",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 20.78241,
    "lng": 45.79936,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1903
  },
  {
    "name": "COW512",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.408138,
    "lng": 50.082993,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1034
  },
  {
    "name": "COW516",
    "district": "JUBAIL",
    "city": "Khafji",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.82347,
    "lng": 48.63208,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1718
  },
  {
    "name": "COW517",
    "district": "Riyadh District",
    "city": "Shaqra",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.16794,
    "lng": 45.039055,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1744
  },
  {
    "name": "COW518",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 25.172392,
    "lng": 46.60499,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/23/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW520",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.22129,
    "lng": 47.079773,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW527",
    "district": "NORTHERN BORDER",
    "city": "Al Uwayqilah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.35557,
    "lng": 42.24141,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1116
  },
  {
    "name": "COW528",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.9066,
    "lng": 48.65835,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1672
  },
  {
    "name": "COW529",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "VVVIP",
    "lat": 25.3349,
    "lng": 46.458,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW530",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.33422,
    "lng": 46.087425,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 925
  },
  {
    "name": "COW531",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.436855,
    "lng": 46.26998,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW534",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.587582,
    "lng": 46.355427,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1411
  },
  {
    "name": "COW535",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVVIP",
    "lat": 25.33344,
    "lng": 46.47846,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW536",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.87598,
    "lng": 46.855522,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW541",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.771683,
```

```
    "lng": 46.72872,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 863
  },
  {
    "name": "COW542",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.71627,
    "lng": 46.09091,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1563
  },
  {
    "name": "COW543",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.9558,
    "lng": 49.56972,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1033
  },
  {
    "name": "COW544",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.467182,
    "lng": 46.67115,
```

```
    "next_fueling_plan": "04-18-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1436
  },
  {
    "name": "COW546",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.23472,
    "lng": 48.1697,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW548",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.3002,
    "lng": 49.554195,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1683
  },
  {
    "name": "COW549",
    "district": "Dammam",
    "city": "Dammam",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
```

```
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW552",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/4/2026",
    "last_fueling_qty": 1989
  },
  {
    "name": "COW600",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.86842,
    "lng": 46.56649,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 817
  },
  {
    "name": "COW601",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 22.430492,
    "lng": 53.976357,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
```

```
    "last_fueling_qty": null
  },
  {
    "name": "COW608",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/29/2026",
    "last_fueling_qty": 1856
  },
  {
    "name": "COW611",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.598888,
    "lng": 46.304142,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1524
  },
  {
    "name": "COW612",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.89845,
    "lng": 46.655407,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
```

```
},
{
  "name": "COW614",
  "district": "Riyadh District",
  "city": "Muzahmiya",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.517206,
  "lng": 46.26815,
  "next_fueling_plan": null,
  "last_fueling_date": "#N/A",
  "last_fueling_qty": null
},
{
  "name": "COW615",
  "district": "Riyadh District",
  "city": "Al Qamriyah",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VIP",
  "lat": 24.53423,
  "lng": 46.043312,
  "next_fueling_plan": "04-04-2026",
  "last_fueling_date": "3/27/2026",
  "last_fueling_qty": 1000
},
{
  "name": "COW616",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VIP",
  "lat": 24.756826,
  "lng": 46.562176,
  "next_fueling_plan": "04-17-2026",
  "last_fueling_date": "4/4/2026",
  "last_fueling_qty": 1326
},
```

```
{
  "name": "COW617",
  "district": "Riyadh District",
  "city": "Muzahmiya",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.517206,
  "lng": 46.26815,
  "next_fueling_plan": null,
  "last_fueling_date": "1/28/2026",
  "last_fueling_qty": 1450
},
{
  "name": "COW618",
  "district": "JUBAIL",
  "city": "JUBAIL",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 27.090467,
  "lng": 49.51877,
  "next_fueling_plan": "04-06-2026",
  "last_fueling_date": "3/24/2026",
  "last_fueling_qty": 1362
},
{
  "name": "COW619",
  "district": "NORTHERN BORDER",
  "city": "Arar",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "VIP",
  "lat": 30.805107,
  "lng": 40.944904,
  "next_fueling_plan": "04-03-2026",
  "last_fueling_date": "3/30/2026",
  "last_fueling_qty": 450
},
{
```

```
    "name": "COW621",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.42355,
    "lng": 46.37908,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1743
  },
  {
    "name": "COW626",
    "district": "Riyadh District",
    "city": "Jilha",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.693,
    "lng": 45.61219,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1752
  },
  {
    "name": "COW627",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW628",
```

```
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/25/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW632",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.66057,
    "lng": 46.67427,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW634",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.201078,
    "lng": 46.378563,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW635",
    "district": "Jeddah",
```

```
    "city": "Jeddah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 21.458817,
    "lng": 39.21194,
    "next_fueling_plan": null,
    "last_fueling_date": "1/17/2026",
    "last_fueling_qty": 973
  },
  {
    "name": "COW636",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/30/2026",
    "last_fueling_qty": 803
  },
  {
    "name": "COW637",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW639",
    "district": "DAMMAM",
    "city": "DAMMAM",
```

```
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": null,
    "lng": null,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW640",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW641",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.296738,
    "lng": 50.15904,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW642",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
```

```
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/16/2026",
    "last_fueling_qty": 1427
  },
  {
    "name": "COW643",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.94298,
    "lng": 47.14723,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1218
  },
  {
    "name": "COW645",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/19/2026",
    "last_fueling_qty": 1328
  },
  {
    "name": "COW647",
    "district": "Riyadh District",
    "city": "Shaqra",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.225864,
    "lng": 45.26588,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1520
  },
  {
    "name": "COW652",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "1/30/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "COW653",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.30936,
    "lng": 49.77637,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1827
  },
  {
    "name": "COW654",
    "district": "JUBAIL",
    "city": "hafir Al Baten",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.256273,
    "lng": 47.038742,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW655",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.2322,
    "lng": 50.11099,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW660",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.333635,
    "lng": 43.84338,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW667",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/22/2026",
    "last_fueling_qty": 1024
  },
  {
    "name": "COW668",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.2158,
    "lng": 46.36139,
    "next_fueling_plan": "04-17-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1506
  },
  {
    "name": "COW712",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/22/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW713",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.567574,
    "lng": 46.577183,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW714",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.67543,
    "lng": 46.64043,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW715",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.808441,
    "lng": 46.42955,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1348
  },
  {
    "name": "COW716",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "VIP",
    "lat": 24.76892,
    "lng": 46.64425,
    "next_fueling_plan": "04-03-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW720",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.84925,
    "lng": 46.66972,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW721",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/29/2026",
    "last_fueling_qty": 1513
  },
  {
    "name": "COW725",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.892042,
    "lng": 46.921047,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1718
  },
  {
    "name": "COW726",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/19/2026",
    "last_fueling_qty": 1314
  },
  {
    "name": "COW727",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.0721,
    "lng": 47.41716,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 841
  },
  {
    "name": "COW728",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.703505,
```

```
    "lng": 46.606056,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW729",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.669031,
    "lng": 46.630623,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW731",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "In Progress",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.239916,
    "lng": 46.374924,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 948
  },
  {
    "name": "COW732",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.769476,
    "lng": 46.71753,
```

```
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW734",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.79189,
    "lng": 46.597862,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1200
  },
  {
    "name": "COW735",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.734922,
    "lng": 46.577446,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW736",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.146614,
    "lng": 47.19173,
    "next_fueling_plan": "04-21-2026",
```

```
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1954
  },
  {
    "name": "COW737",
    "district": "Riyadh District",
    "city": "Wadi Dawaseer",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 20.480911,
    "lng": 45.082382,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1289
  },
  {
    "name": "COW738",
    "district": "Riyadh District",
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.96425,
    "lng": 47.101307,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW739",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.70187,
    "lng": 45.59598,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
```

```
    "last_fueling_qty": 1767
  },
  {
    "name": "COW740",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.845575,
    "lng": 46.740055,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW741",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.712563,
    "lng": 46.596905,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1817
  },
  {
    "name": "COW742",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.5304,
    "lng": 46.40582,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1476
```

```
},
{
  "name": "COW743",
  "district": "Riyadh District",
  "city": "Shaqra",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 25.358215,
  "lng": 45.27161,
  "next_fueling_plan": "04-13-2026",
  "last_fueling_date": "3/27/2026",
  "last_fueling_qty": 1958
},
{
  "name": "COW744",
  "district": "Riyadh District",
  "city": "Durma",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.524227,
  "lng": 46.410217,
  "next_fueling_plan": "04-04-2026",
  "last_fueling_date": "3/27/2026",
  "last_fueling_qty": 1000
},
{
  "name": "COW745",
  "district": "Riyadh District",
  "city": "Rumah",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 25.233732,
  "lng": 47.09924,
  "next_fueling_plan": null,
  "last_fueling_date": "2/2/2026",
  "last_fueling_qty": 1500
},
```

```
{
  "name": "COW746",
  "district": "Riyadh District",
  "city": "Riyadh District",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 25.52486,
  "lng": 47.088577,
  "next_fueling_plan": "04-07-2026",
  "last_fueling_date": "3/30/2026",
  "last_fueling_qty": 1000
},
{
  "name": "COW747",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VVIP",
  "lat": 24.77327,
  "lng": 46.526894,
  "next_fueling_plan": "04-04-2026",
  "last_fueling_date": "3/27/2026",
  "last_fueling_qty": 1000
},
{
  "name": "COW748",
  "district": "Riyadh District",
  "city": "Riyadh District",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.51704,
  "lng": 46.26763,
  "next_fueling_plan": null,
  "last_fueling_date": "1/15/2026",
  "last_fueling_qty": 1943
},
{
```

```
    "name": "COW749",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.65517,
    "lng": 45.727234,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1685
  },
  {
    "name": "COW750",
    "district": "Al-AHSA",
    "city": "Shaybah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 22.600384,
    "lng": 53.998672,
    "next_fueling_plan": "04-27-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 3400
  },
  {
    "name": "COW751",
    "district": "Riyadh District",
    "city": "Al kharaj",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.058374,
    "lng": 47.55768,
    "next_fueling_plan": "04-03-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1214
  },
  {
    "name": "COW753",
```

```
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.9678,
    "lng": 46.6159,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1200
  },
  {
    "name": "COW757",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/18/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW758",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.058111,
    "lng": 47.30743,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1592
  },
  {
    "name": "COW763",
    "district": "Riyadh District",
```

```
    "city": "Riyadh",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.25609,
    "lng": 47.07598,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW764",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.858644,
    "lng": 46.736744,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1513
  },
  {
    "name": "COW767",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "In Progress",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.239916,
    "lng": 46.374924,
    "next_fueling_plan": "#N/A",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW768",
    "district": "Riyadh District",
    "city": "Dowadmi",
```

```
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.29376,
    "lng": 44.62865,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/24/2026",
    "last_fueling_qty": 1462
  },
  {
    "name": "COW769",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.85803,
    "lng": 46.76889,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1712
  },
  {
    "name": "COW770",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.7377,
    "lng": 46.74686,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW771",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
```

```
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW772",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 25.3548,
    "lng": 47.48777,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1732
  },
  {
    "name": "COW773",
    "district": "Riyadh District",
    "city": "Wadi Dawaseer",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 20.14477,
    "lng": 45.13062,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1967
  },
  {
    "name": "COW774",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.719557,
    "lng": 45.543076,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1843
  },
  {
    "name": "COW775",
    "district": "Riyadh District",
    "city": "Al kharaj",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.168491,
    "lng": 47.332954,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1516
  },
  {
    "name": "COW776",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.97483,
    "lng": 46.92809,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1286
  },
  {
    "name": "COW778",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW779",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.875586,
    "lng": 46.45432,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1300
  },
  {
    "name": "COW781",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "12/23/2025",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW801",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/26/2026",
    "last_fueling_qty": 1497
  },
  {
    "name": "COW802",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.90011,
    "lng": 46.948082,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1412
  },
  {
    "name": "COW803",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW805",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW820",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VVIP",
    "lat": 24.798887,
    "lng": 46.540035,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/19/2026",
    "last_fueling_qty": 1371
  },
  {
    "name": "COW822",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.41521,
    "lng": 46.8424,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1300
  },
  {
    "name": "COW823",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "VIP",
    "lat": 24.782145,
    "lng": 46.605755,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1312
  },
  {
    "name": "COW840",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/3/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW841",
    "district": "Riyadh District",
    "city": "Dirab",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.425184,
    "lng": 46.58667,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW842",
    "district": "Riyadh District",
    "city": "Al kharaj",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.17474,
    "lng": 47.21005,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COW845",
    "district": "Riyadh District",
    "city": "Durma",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1503
  },
  {
    "name": "COW846",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/14/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW854",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.685259,
```

```
    "lng": 46.634216,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/18/2026",
    "last_fueling_qty": 1956
  },
  {
    "name": "COW855",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.61786,
    "lng": 46.51344,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "COW856",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.77779,
    "lng": 46.608013,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "COW857",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.717707,
    "lng": 46.581295,
```

```
  "next_fueling_plan": "04-10-2026",
  "last_fueling_date": "3/31/2026",
  "last_fueling_qty": 1200
},
{
  "name": "COW858",
  "district": "Riyadh District",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.482801,
  "lng": 46.682594,
  "next_fueling_plan": "04-14-2026",
  "last_fueling_date": "4/1/2026",
  "last_fueling_qty": 1143
},
{
  "name": "COW859",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.824314,
  "lng": 46.856533,
  "next_fueling_plan": "04-10-2026",
  "last_fueling_date": "3/31/2026",
  "last_fueling_qty": 1200
},
{
  "name": "COW861",
  "district": "Riyadh City",
  "city": "Riyadh City",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.4695,
  "lng": 46.667,
  "next_fueling_plan": "04-25-2026",
```

```
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1464
  },
  {
    "name": "COWA629",
    "district": "Riyadh District",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.7374,
    "lng": 44.76935,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1355
  },
  {
    "name": "COWE02",
    "district": "Riyadh District",
    "city": "Thumama",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.236307,
    "lng": 46.51158,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "COWE03",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
```

```
    "last_fueling_qty": null
  },
  {
    "name": "COWE05",
    "district": "Riyadh District",
    "city": "Jilha",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.325356,
    "lng": 45.916676,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/17/2026",
    "last_fueling_qty": 1767
  },
  {
    "name": "COWJN1",
    "district": "NORTHERN BORDER",
    "city": "Rafah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 29.003613,
    "lng": 44.72298,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/28/2026",
    "last_fueling_qty": 705
  },
  {
    "name": "COWPC",
    "district": "Riyadh City",
    "city": "Riyadh City",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "VIP",
    "lat": 24.70158,
    "lng": 46.67866,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/27/2026",
    "last_fueling_qty": 1000
```

```
},
{
  "name": "CWA003",
  "district": "Riyadh District",
  "city": "Muzahmiya",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.517206,
  "lng": 46.26815,
  "next_fueling_plan": null,
  "last_fueling_date": "3/29/2026",
  "last_fueling_qty": 1186
},
{
  "name": "CWA004",
  "district": "NORTHERN BORDER",
  "city": "Al-Jouf",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 29.9765,
  "lng": 40.16956,
  "next_fueling_plan": "04-16-2026",
  "last_fueling_date": "3/30/2026",
  "last_fueling_qty": 1850
},
{
  "name": "CWA005",
  "district": "DAMMAM",
  "city": "DAMMAM",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 26.201199,
  "lng": 49.947945,
  "next_fueling_plan": null,
  "last_fueling_date": "#N/A",
  "last_fueling_qty": null
},
```

```
{
  "name": "CWH001",
  "district": "DAMMAM",
  "city": "DAMMAM",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 26.240911,
  "lng": 49.911407,
  "next_fueling_plan": "04-12-2026",
  "last_fueling_date": "4/2/2026",
  "last_fueling_qty": 1023
},
{
  "name": "CWH004",
  "district": "JUBAIL",
  "city": "JUBAIL",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 27.11578,
  "lng": 47.36891,
  "next_fueling_plan": "04-21-2026",
  "last_fueling_date": "4/3/2026",
  "last_fueling_qty": 1882
},
{
  "name": "CWH006",
  "district": "Riyadh District",
  "city": "Al Ghat",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VVIP",
  "lat": 25.785212,
  "lng": 44.69304,
  "next_fueling_plan": "04-12-2026",
  "last_fueling_date": "3/29/2026",
  "last_fueling_qty": 1643
},
{
```

```
    "name": "CWH008",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.92507,
    "lng": 49.930458,
    "next_fueling_plan": "04-11-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1025
  },
  {
    "name": "CWH011",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.46702,
    "lng": 50.06988,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/1/2026",
    "last_fueling_qty": 1325
  },
  {
    "name": "CWH012",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 24.96059,
    "lng": 49.43982,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH013",
```

```
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH019",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.67406,
    "lng": 43.97404,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH020",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH022",
    "district": "DAMMAM",
```

```
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "1/30/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH023",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.9367,
    "lng": 41.1017,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1550
  },
  {
    "name": "CWH024",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.01686,
    "lng": 43.822987,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH028",
    "district": "JUBAIL",
    "city": "Nariyah",
```

```
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.51617,
    "lng": 48.36225,
    "next_fueling_plan": "04-21-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1786
  },
  {
    "name": "CWH029",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.95475,
    "lng": 39.00115,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/5/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH030",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.819874,
    "lng": 48.672424,
    "next_fueling_plan": null,
    "last_fueling_date": null,
    "last_fueling_qty": null
  },
  {
    "name": "CWH031",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
```

```
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.34032,
    "lng": 49.4875,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/17/2026",
    "last_fueling_qty": 1557
  },
  {
    "name": "CWH032",
    "district": "Riyadh District",
    "city": "Majma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.084793,
    "lng": 45.215034,
    "next_fueling_plan": "04-19-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1861
  },
  {
    "name": "CWH033",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.858393,
    "lng": 39.046783,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/5/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH040",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/15/2026",
    "last_fueling_qty": 1530
  },
  {
    "name": "CWH041",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.509485,
    "lng": 49.252956,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1660
  },
  {
    "name": "CWH043",
    "district": "Riyadh District",
    "city": "Majma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.07149,
    "lng": 45.32088,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH045",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.88407,
    "lng": 41.20339,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH076",
    "district": "NORTHERN BORDER",
    "city": "Rafah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.078861,
    "lng": 42.82277,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH077",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.321096,
    "lng": 49.558197,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1440
  },
  {
    "name": "CWH084",
    "district": "DAMMAM",
    "city": "Dammam",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.24154,
    "lng": 50.12894,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 978
  },
  {
    "name": "CWH086",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.359797,
    "lng": 44.09448,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1001
  },
  {
    "name": "CWH088",
    "district": "Qassim",
    "city": "Buraida",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.352869,
    "lng": 43.984013,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1001
  },
  {
    "name": "CWH089",
    "district": "Riyadh District",
    "city": "Majma",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
```

```
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.086123,
    "lng": 45.290672,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1548
  },
  {
    "name": "CWH091",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.398066,
    "lng": 41.714825,
    "next_fueling_plan": "04-08-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1150
  },
  {
    "name": "CWH093",
    "district": "Jubail",
    "city": "Jubail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.09718,
    "lng": 49.09373,
    "next_fueling_plan": "04-13-2026",
    "last_fueling_date": "3/31/2026",
    "last_fueling_qty": 1476
  },
  {
    "name": "CWH094",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
```

```
    "site_label": "Normal",
    "lat": 25.67764,
    "lng": 46.85573,
    "next_fueling_plan": null,
    "last_fueling_date": "2/8/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH185",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.94794,
    "next_fueling_plan": null,
    "last_fueling_date": "12/2/2025",
    "last_fueling_qty": 840
  },
  {
    "name": "CWH186",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.833,
    "lng": 48.8475,
    "next_fueling_plan": null,
    "last_fueling_date": "1/24/2026",
    "last_fueling_qty": 1522
  },
  {
    "name": "CWH187",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
```

```
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/17/2026",
    "last_fueling_qty": 1091
  },
  {
    "name": "CWH188",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/8/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH190",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.94794,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWH193",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
```

```
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "1/19/2026",
    "last_fueling_qty": 1473
  },
  {
    "name": "CWH194",
    "district": "Riyadh District",
    "city": "Zulfi",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.326626,
    "lng": 44.581394,
    "next_fueling_plan": "04-12-2026",
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 1574
  },
  {
    "name": "CWH316",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.4367,
    "lng": 45.91904,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1898
  },
  {
    "name": "CWH317",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.566307,
    "lng": 41.654743,
```

```
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1477
  },
  {
    "name": "CWH352",
    "district": "DAMMAM",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "2/6/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH935",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "2/28/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH937",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
```

```
    "last_fueling_date": "2/22/2026",
    "last_fueling_qty": 1813
  },
  {
    "name": "CWH940",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "1/29/2026",
    "last_fueling_qty": 1119
  },
  {
    "name": "CWH941",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.70092,
    "lng": 46.87303,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH942",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.72473,
    "lng": 46.89682,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
```

```
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH943",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.51704,
    "lng": 46.26763,
    "next_fueling_plan": null,
    "last_fueling_date": "3/7/2026",
    "last_fueling_qty": 900
  },
  {
    "name": "CWH944",
    "district": "Riyadh District",
    "city": "Rumah",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.6327,
    "lng": 46.89008,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWH945",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/7/2026",
    "last_fueling_qty": 900
```

```
},
{
  "name": "CWH971",
  "district": "Riyadh District",
  "city": "Riyadh ",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.51704,
  "lng": 46.26763,
  "next_fueling_plan": null,
  "last_fueling_date": "#N/A",
  "last_fueling_qty": null
},
{
  "name": "CWH972",
  "district": "Riyadh District",
  "city": "Riyadh District",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "VIP",
  "lat": 25.127125,
  "lng": 47.809155,
  "next_fueling_plan": "04-21-2026",
  "last_fueling_date": "4/4/2026",
  "last_fueling_qty": 1862
},
{
  "name": "CWH973",
  "district": "Qassim",
  "city": "Qassim",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 26.35124,
  "lng": 43.762722,
  "next_fueling_plan": "04-07-2026",
  "last_fueling_date": "3/30/2026",
  "last_fueling_qty": 1002
},
```

```
{
  "name": "CWN056",
  "district": "Riyadh District",
  "city": "Muzahmiya",
  "project": "stc COW",
  "cow_status": "OFF-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "Central",
  "site_label": "Normal",
  "lat": 24.51704,
  "lng": 46.26763,
  "next_fueling_plan": null,
  "last_fueling_date": "#N/A",
  "last_fueling_qty": null
},
{
  "name": "CWN058",
  "district": "Jubail",
  "city": "Jubail",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "VIP",
  "lat": 26.966322,
  "lng": 49.498177,
  "next_fueling_plan": "04-02-2026",
  "last_fueling_date": "3/16/2026",
  "last_fueling_qty": 1745
},
{
  "name": "CWN911",
  "district": "NORTHERN BORDER",
  "city": "Rafha",
  "project": "stc COW",
  "cow_status": "ON-AIR",
  "active": true,
  "current_liters": 0,
  "daily_virtual": 0,
  "region": "EAST",
  "site_label": "Normal",
  "lat": 28.35173,
  "lng": 44.25038,
  "next_fueling_plan": "04-12-2026",
  "last_fueling_date": "3/30/2026",
  "last_fueling_qty": 1282
},
{
```

```
    "name": "CWN918",
    "district": "Riyadh district",
    "city": "Riyadh District",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.12232,
    "lng": 47.63788,
    "next_fueling_plan": "04-07-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWN963",
    "district": "Riyadh District",
    "city": "AL-HAYSYA",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.90069,
    "lng": 46.13858,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/3/2026",
    "last_fueling_qty": 1500
  },
  {
    "name": "CWN964",
    "district": "Riyadh District",
    "city": "Dirab",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.42661,
    "lng": 46.58741,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN973",
```

```
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN975",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN986",
    "district": "NORTHERN BORDER",
    "city": "ARAR",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 30.46544,
    "lng": 42.64941,
    "next_fueling_plan": null,
    "last_fueling_date": null,
    "last_fueling_qty": null
  },
  {
    "name": "CWN987",
    "district": "JUBAIL",
```

```
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.00515,
    "lng": 47.41512,
    "next_fueling_plan": null,
    "last_fueling_date": "#N/A",
    "last_fueling_qty": null
  },
  {
    "name": "CWN988",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.88932,
    "lng": 39.65717,
    "next_fueling_plan": "04-14-2026",
    "last_fueling_date": "4/4/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWN990",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 19.4774,
    "lng": 53.23433,
    "next_fueling_plan": null,
    "last_fueling_date": null,
    "last_fueling_qty": null
  },
  {
    "name": "CWS605",
    "district": "JUBAIL",
    "city": "JUBAIL",
```

```
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.843334,
    "lng": 49.8065,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1374
  },
  {
    "name": "CWS800",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 26.865713,
    "lng": 40.32728,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 2000
  },
  {
    "name": "CWS805",
    "district": "NORTHERN BORDER",
    "city": "TURAIF",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 31.840729,
    "lng": 39.112827,
    "next_fueling_plan": "04-04-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWS806",
    "district": "DAMMAM",
    "city": "DAMMAM",
    "project": "stc COW",
```

```
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.201199,
    "lng": 49.947945,
    "next_fueling_plan": null,
    "last_fueling_date": "1/13/2026",
    "last_fueling_qty": 1270
  },
  {
    "name": "CWS808",
    "district": "Riyadh District",
    "city": "Muzahmiya",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 24.517206,
    "lng": 46.26815,
    "next_fueling_plan": null,
    "last_fueling_date": "3/7/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWS813",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "OFF-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.59266,
    "lng": 48.93513,
    "next_fueling_plan": null,
    "last_fueling_date": "1/27/2026",
    "last_fueling_qty": 1119
  },
  {
    "name": "CWS814",
    "district": "JUBAIL",
    "city": "AFAR AL BATEN",
    "project": "stc COW",
    "cow_status": "ON-AIR",
```

```
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 28.44564,
    "lng": 45.98281,
    "next_fueling_plan": "04-16-2026",
    "last_fueling_date": "3/30/2026",
    "last_fueling_qty": 1923
  },
  {
    "name": "CWS816",
    "district": "Al-AHSA",
    "city": "Abqiq",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 25.940962,
    "lng": 49.42586,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/29/2026",
    "last_fueling_qty": 1016
  },
  {
    "name": "CWS820",
    "district": "Qassim",
    "city": "Qassim",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 25.813257,
    "lng": 43.093296,
    "next_fueling_plan": "SEC Site",
    "last_fueling_date": "1/16/2026",
    "last_fueling_qty": 1000
  },
  {
    "name": "CWS821",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
```

```
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.90673,
    "lng": 49.49295,
    "next_fueling_plan": "04-05-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1453
  },
  {
    "name": "CWS831",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.813784,
    "lng": 48.661148,
    "next_fueling_plan": "04-10-2026",
    "last_fueling_date": "3/26/2026",
    "last_fueling_qty": 1577
  },
  {
    "name": "CWS834",
    "district": "Al-AHSA",
    "city": "Hofuf",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 24.92084,
    "lng": 50.37997,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1471
  },
  {
    "name": "CWS836",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
```

```
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 26.618732,
    "lng": 44.06827,
    "next_fueling_plan": "04-09-2026",
    "last_fueling_date": "3/25/2026",
    "last_fueling_qty": 1658
  },
  {
    "name": "CWS833",
    "district": "JUBAIL",
    "city": "JUBAIL",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "EAST",
    "site_label": "Normal",
    "lat": 27.09436,
    "lng": 49.50581,
    "next_fueling_plan": "04-06-2026",
    "last_fueling_date": "3/24/2026",
    "last_fueling_qty": 1357
  },
  {
    "name": "CWS835",
    "district": "Hail",
    "city": "Hail",
    "project": "stc COW",
    "cow_status": "ON-AIR",
    "active": true,
    "current_liters": 0,
    "daily_virtual": 0,
    "region": "Central",
    "site_label": "Normal",
    "lat": 27.49808,
    "lng": 41.665028,
    "next_fueling_plan": "04-15-2026",
    "last_fueling_date": "4/2/2026",
    "last_fueling_qty": 1497
  }
];

const SEED_MISSIONS = [
  {
    "missionId": "MSN-20260405-COW017",
    "siteName": "COW017",
    "generator": "COW017",
    "project": "stc COW",
    "city": "Riyadh City",
```

```
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW518",
    "siteName": "COW518",
    "generator": "COW518",
    "project": "stc COW",
    "city": "Thumama",
    "quantityAddedLastTask": 1500,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW530",
    "siteName": "COW530",
    "generator": "COW530",
    "project": "stc COW",
    "city": "Muzahmiya",
    "quantityAddedLastTask": 925,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW013",
    "siteName": "COW013",
    "generator": "COW013",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1286,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-COW054",
    "siteName": "COW054",
    "generator": "COW054",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW619",
    "siteName": "COW619",
    "generator": "COW619",
    "project": "stc COW",
    "city": "Arar",
    "quantityAddedLastTask": 450,
    "notes": "Auto-generated   plan date: 04-03-2026"
  },
  {
    "missionId": "MSN-20260405-COW621",
    "siteName": "COW621",
    "generator": "COW621",
```

```
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1743,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW534",
    "siteName": "COW534",
    "generator": "COW534",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1411,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-COW536",
    "siteName": "COW536",
    "generator": "COW536",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW542",
    "siteName": "COW542",
    "generator": "COW542",
    "project": "stc COW",
    "city": "Durma",
    "quantityAddedLastTask": 1563,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW600",
    "siteName": "COW600",
    "generator": "COW600",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 817,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW611",
    "siteName": "COW611",
    "generator": "COW611",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1524,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-COW615",
```

```
    "siteName": "COW615",
    "generator": "COW615",
    "project": "stc COW",
    "city": "Al Qamriyah",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW716",
    "siteName": "COW716",
    "generator": "COW716",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-03-2026"
  },
  {
    "missionId": "MSN-20260405-COW720",
    "siteName": "COW720",
    "generator": "COW720",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW728",
    "siteName": "COW728",
    "generator": "COW728",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW737",
    "siteName": "COW737",
    "generator": "COW737",
    "project": "stc COW",
    "city": "Wadi Dawaseer",
    "quantityAddedLastTask": 1289,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW741",
    "siteName": "COW741",
    "generator": "COW741",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1817,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
```

```
{
  "missionId": "MSN-20260405-COW742",
  "siteName": "COW742",
  "generator": "COW742",
  "project": "stc COW",
  "city": "Riyadh District",
  "quantityAddedLastTask": 1476,
  "notes": "Auto-generated   plan date: 04-05-2026"
},
{
  "missionId": "MSN-20260405-COW744",
  "siteName": "COW744",
  "generator": "COW744",
  "project": "stc COW",
  "city": "Durma",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW747",
  "siteName": "COW747",
  "generator": "COW747",
  "project": "stc COW",
  "city": "Riyadh City",
  "quantityAddedLastTask": 1000,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW749",
  "siteName": "COW749",
  "generator": "COW749",
  "project": "stc COW",
  "city": "Durma",
  "quantityAddedLastTask": 1685,
  "notes": "Auto-generated   plan date: 04-04-2026"
},
{
  "missionId": "MSN-20260405-COW751",
  "siteName": "COW751",
  "generator": "COW751",
  "project": "stc COW",
  "city": "Al kharaj",
  "quantityAddedLastTask": 1214,
  "notes": "Auto-generated   plan date: 04-03-2026"
},
{
  "missionId": "MSN-20260405-COW758",
  "siteName": "COW758",
  "generator": "COW758",
  "project": "stc COW",
  "city": "Riyadh District",
  "quantityAddedLastTask": 1592,
```

```
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW772",
    "siteName": "COW772",
    "generator": "COW772",
    "project": "stc COW",
    "city": "Riyadh District",
    "quantityAddedLastTask": 1732,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-COW854",
    "siteName": "COW854",
    "generator": "COW854",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1956,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COWJN1",
    "siteName": "COWJN1",
    "generator": "COWJN1",
    "project": "stc COW",
    "city": "Rafah",
    "quantityAddedLastTask": 705,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COWPC",
    "siteName": "COWPC",
    "generator": "COWPC",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW770",
    "siteName": "COW770",
    "generator": "COW770",
    "project": "stc COW",
    "city": "Riyadh City",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-COW820",
    "siteName": "COW820",
    "generator": "COW820",
    "project": "stc COW",
```

```
    "city": "Riyadh City",
    "quantityAddedLastTask": 1371,
    "notes": "Auto-generated   plan date: 04-05-2026"
  },
  {
    "missionId": "MSN-20260405-CWH076",
    "siteName": "CWH076",
    "generator": "CWH076",
    "project": "stc COW",
    "city": "Rafah",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-CWN058",
    "siteName": "CWN058",
    "generator": "CWN058",
    "project": "stc COW",
    "city": "Jubail",
    "quantityAddedLastTask": 1745,
    "notes": "Auto-generated   plan date: 04-02-2026"
  },
  {
    "missionId": "MSN-20260405-CWS805",
    "siteName": "CWS805",
    "generator": "CWS805",
    "project": "stc COW",
    "city": "TURAIF",
    "quantityAddedLastTask": 1000,
    "notes": "Auto-generated   plan date: 04-04-2026"
  },
  {
    "missionId": "MSN-20260405-CWS821",
    "siteName": "CWS821",
    "generator": "CWS821",
    "project": "stc COW",
    "city": "JUBAIL",
    "quantityAddedLastTask": 1453,
    "notes": "Auto-generated   plan date: 04-05-2026"
  }
];

const SEED_ADMINS = [
  {
    name: "Administrator",
    username: "Bannaga",
    email: "admin@aces-sa.com",
    passwordHash: adminPasswordHash,
    position: "Admin",
  },
];
```

```
const SEED_DRIVERS = [
  {
    name: "Bannaga Altieb",
    email: "bannaga.altieb@aces-co.com",
    phone: "+966542966343",
    zone: "stc COW CR",
    active: true,
    passwordHash: driverPasswordHash,
  },
  {
    name: "Bannaga",
    email: "bannaga2@aces-co.com",
    phone: "+966542966343",
    zone: "Central Region",
    active: true,
    passwordHash: driverPasswordHash,
  },
];

router.post("/seed", async (req, res) => {
  try {
    const results: Record<string, number> = {};

    // Check existing data
    const [siteCount] = await db.select({ value: count() }).from(sitesTable);
    if (siteCount.value > 0) {
      return res.json({ message: "Already seeded", sites: siteCount.value });
    }

    // Seed admins
    for (const admin of SEED_ADMINS) {
      await db.insert(adminsTable).values(admin).onConflictDoNothing();
    }
    results.admins = SEED_ADMINS.length;

    // Seed sites in batches of 50
    for (let i = 0; i < SEED_SITES.length; i += 50) {
      const batch = SEED_SITES.slice(i, i + 50);
      await db.insert(sitesTable).values(batch.map((s: any) => ({
        name: s.name,
        district: s.district || "",
        city: s.city || "",
        project: s.project || "stc COW",
        cowStatus: s.cow_status || "ON-AIR",
        active: s.active !== false,
        currentLiters: s.current_liters || 0,
        dailyVirtual: s.daily_virtual || 0,
        region: s.region || "",
        siteLabel: s.site_label || "",
        lat: s.lat || null,
        lng: s.lng || null,
        nextFuelingPlan: s.next_fueling_plan || "",
```

```
        lastFuelingDate: s.last_fueling_date || "",
        lastFuelingQty: s.last_fueling_qty || null,
      }))).onConflictDoNothing();
    }
    results.sites = SEED_SITES.length;

    // Seed missions
    for (let i = 0; i < SEED_MISSIONS.length; i += 20) {
      const batch = SEED_MISSIONS.slice(i, i + 20);
      await db.insert(missionsTable).values(batch.map((m: any) => ({
        missionId: m.missionId,
        siteName: m.siteName,
        generator: m.generator,
        project: m.project,
        city: m.city,
        quantityAddedLastTask: m.quantityAddedLastTask,
        notes: m.notes,
        missionStatus: "Creation",
        createdBy: "System",
      }))).onConflictDoNothing();
    }
    results.missions = SEED_MISSIONS.length;

    // Seed drivers
    for (const driver of SEED_DRIVERS) {
      await db.insert(driversTable).values(driver).onConflictDoNothing();
    }
    results.drivers = SEED_DRIVERS.length;

    res.json({ success: true, seeded: results });
  } catch (err) {
    req.log.error({ err }, "Seed failed");
    res.status(500).json({ error: "Seed failed", detail: String(err) });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/settings.ts
SIZE: 2,648 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { settingsTable } from "@workspace/db/schema";
import { eq } from "drizzle-orm";

const router: IRouter = Router();

router.get("/settings", async (req, res) => {
  try {
    const [settings] = await db.select().from(settingsTable).limit(1);
    if (!settings) {
      const [created] = await db.insert(settingsTable).values({}).returning();
      return res.json({
        id: created.id,
        fuelUnitPrice: created.fuelUnitPrice,
        vatRate: created.vatRate,
        supplierName: created.supplierName,
        supplierAddress: created.supplierAddress,
        invoicePrefix: created.invoicePrefix,
        invoiceSequence: created.invoiceSequence,
      });
    }
    res.json({
      id: settings.id,
      fuelUnitPrice: settings.fuelUnitPrice,
      vatRate: settings.vatRate,
      supplierName: settings.supplierName,
      supplierAddress: settings.supplierAddress,
      invoicePrefix: settings.invoicePrefix,
      invoiceSequence: settings.invoiceSequence,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to get settings");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.put("/settings", async (req, res) => {
  try {
    const body = req.body;
    const [existing] = await db.select().from(settingsTable).limit(1);
    if (!existing) {
      const [created] = await db.insert(settingsTable).values({
        fuelUnitPrice: body.fuelUnitPrice ?? 0.63,
        vatRate: body.vatRate ?? 0.15,
        supplierName: body.supplierName ?? "",
        supplierAddress: body.supplierAddress ?? "",
        invoicePrefix: body.invoicePrefix ?? "INV-SEC-",
        invoiceSequence: body.invoiceSequence ?? 1,
```

```
      }).returning();
      return res.json(created);
    }
    const [updated] = await db.update(settingsTable).set({
      fuelUnitPrice: body.fuelUnitPrice,
      vatRate: body.vatRate,
      supplierName: body.supplierName,
      supplierAddress: body.supplierAddress,
      invoicePrefix: body.invoicePrefix,
      invoiceSequence: body.invoiceSequence,
    }).where(eq(settingsTable.id, existing.id)).returning();
    res.json({
      id: updated.id,
      fuelUnitPrice: updated.fuelUnitPrice,
      vatRate: updated.vatRate,
      supplierName: updated.supplierName,
      supplierAddress: updated.supplierAddress,
      invoicePrefix: updated.invoicePrefix,
      invoiceSequence: updated.invoiceSequence,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to update settings");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/sites.ts
SIZE: 7,229 bytes

```
import { Router, type IRouter } from "express";
import { db } from "@workspace/db";
import { sitesTable } from "@workspace/db/schema";
import { eq } from "drizzle-orm";
import { syncSitesFromSheets } from "../lib/sync-scheduler";

const router: IRouter = Router();

function mapSite(s: typeof sitesTable.$inferSelect) {
  return {
    id: s.id,
    name: s.name,
    region: s.region ?? "",
    district: s.district,
    city: s.city,
    project: s.project,
    cowStatus: s.cowStatus,
    siteLabel: s.siteLabel ?? "",
    lat: s.lat ?? null,
    lng: s.lng ?? null,
    nextFuelingPlan: s.nextFuelingPlan ?? "",
    lastFuelingDate: s.lastFuelingDate ?? "",
    lastFuelingQty: s.lastFuelingQty ?? null,
    active: s.active,
    currentLiters: s.currentLiters,
    dailyVirtual: s.dailyVirtual,
    assignedTechnicianId: s.assignedTechnicianId ?? null,
  };
}

/** Normalise a raw CSV/sheet header to a lowercase key without spaces */
function normHeader(h: string) {
  return h.trim().toLowerCase().replace(/\s+/g, "");
}

/** Resolve aliases ? canonical field names */
function resolveAlias(key: string): string {
  const aliases: Record<string, string> = {
    latitude: "lat",
    longitude: "lng",
    "cow status": "cowstatus",
    status: "cowstatus",
  };
  return aliases[key] ?? key;
}

/** Parse a CSV string (with quoted fields) into an array of row-objects */
function parseCsv(csv: string): Record<string, string>[] {
  const lines = csv.split(/\r?\n/).filter((l) => l.trim());
```

```
  if (lines.length < 2) return [];

  const rawHeaders = lines[0].split(",").map((h) => h.replace(/^"|"$/g, "").trim());
  const headers = rawHeaders.map((h) => resolveAlias(normHeader(h)));

  return lines.slice(1).map((line) => {
    const values = line.split(",").map((v) => v.replace(/^"|"$/g, "").trim());
    const row: Record<string, string> = {};
    headers.forEach((h, i) => { row[h] = values[i] ?? ""; });
    return row;
  });
}

router.get("/sites", async (req, res) => {
  try {
    const sites = await db.select().from(sitesTable).orderBy(sitesTable.name);
    res.json(sites.map(mapSite));
  } catch (err) {
    req.log.error({ err }, "Failed to list sites");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.post("/sites", async (req, res) => {
  try {
    const body = req.body;
    const [site] = await db.insert(sitesTable).values({
      name: body.name,
      region: body.region || "",
      district: body.district || "",
      city: body.city || "",
      project: body.project || "stc COW",
      cowStatus: body.cowStatus || "ON-AIR",
      siteLabel: body.siteLabel || "",
      lat: body.lat != null ? parseFloat(body.lat) : undefined,
      lng: body.lng != null ? parseFloat(body.lng) : undefined,
      nextFuelingPlan: body.nextFuelingPlan || "",
      lastFuelingDate: body.lastFuelingDate || "",
      lastFuelingQty: body.lastFuelingQty != null ? parseFloat(body.lastFuelingQty) : undefined,
      active: body.active !== undefined ? body.active : true,
      assignedTechnicianId: body.assignedTechnicianId ? parseInt(body.assignedTechnicianId) : undefined,
    }).returning();
    res.status(201).json(mapSite(site));
  } catch (err) {
    req.log.error({ err }, "Failed to create site");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.put("/sites/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
```

```
    const body = req.body;
    const [site] = await db.update(sitesTable).set({
      name: body.name,
      region: body.region,
      district: body.district,
      city: body.city,
      project: body.project,
      cowStatus: body.cowStatus,
      siteLabel: body.siteLabel,
      lat: body.lat != null ? parseFloat(body.lat) : undefined,
      lng: body.lng != null ? parseFloat(body.lng) : undefined,
      nextFuelingPlan: body.nextFuelingPlan,
      lastFuelingDate: body.lastFuelingDate,
      lastFuelingQty: body.lastFuelingQty != null ? parseFloat(body.lastFuelingQty) : undefined,
      active: body.active,
      assignedTechnicianId: body.assignedTechnicianId != null
        ? parseInt(body.assignedTechnicianId) : undefined,
    }).where(eq(sitesTable.id, id)).returning();
    if (!site) return res.status(404).json({ error: "Not found" });
    res.json(mapSite(site));
  } catch (err) {
    req.log.error({ err }, "Failed to update site");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.delete("/sites/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    await db.delete(sitesTable).where(eq(sitesTable.id, id));
    res.status(204).send();
  } catch (err) {
    req.log.error({ err }, "Failed to delete site");
    res.status(500).json({ error: "Internal server error" });
  }
});

/**
 * POST /sites/import-csv
 * Body: { csv: string }
 * Accepts the CSV format described in the Google Sheets spec.
 * Returns { inserted, skipped, errors }.
 */
router.post("/sites/import-csv", async (req, res) => {
  try {
    const { csv } = req.body as { csv?: string };
    if (!csv || typeof csv !== "string") {
      return res.status(400).json({ error: "Request body must include a 'csv' string field" });
    }

    const rows = parseCsv(csv);
    if (rows.length === 0) {
```

```
      return res.status(400).json({ error: "No data rows found in CSV" });
    }

    let inserted = 0;
    let skipped = 0;
    const errors: string[] = [];

    for (const row of rows) {
      const name = row["sitename"];
      if (!name) { skipped++; continue; }

      try {
        const lat = row["lat"] ? parseFloat(row["lat"]) : undefined;
        const lng = row["lng"] ? parseFloat(row["lng"]) : undefined;
        const lastQty = row["lastfuelingqty"] ? parseFloat(row["lastfuelingqty"]) : undefined;

        await db.insert(sitesTable).values({
          name,
          region: row["regionname"] || "",
          district: row["districtname"] || "",
          city: row["cityname"] || "",
          cowStatus: row["cowstatus"] || "ON-AIR",
          siteLabel: row["sitelabel"] || "",
          lat: isNaN(lat!) ? undefined : lat,
          lng: isNaN(lng!) ? undefined : lng,
          nextFuelingPlan: row["nextfuelingplan"] || "",
          lastFuelingDate: row["lastfuelingdate"] || "",
          lastFuelingQty: lastQty != null && !isNaN(lastQty) ? lastQty : undefined,
          active: true,
        }).onConflictDoNothing();
        inserted++;
      } catch (err) {
        errors.push(`Row "${name}": ${err instanceof Error ? err.message : String(err)}`);
      }
    }

    res.json({ inserted, skipped, errors, total: rows.length });
  } catch (err) {
    req.log.error({ err }, "Failed to import sites CSV");
    res.status(500).json({ error: "Internal server error" });
  }
});

/**
 * POST /sites/sync-sheets
 * Manually trigger a Google Sheets sync (also runs automatically every 24h).
 */
router.post("/sites/sync-sheets", async (req, res) => {
  try {
    const result = await syncSitesFromSheets();
    res.json(result);
  } catch (err) {
```

```
    req.log.error({ err }, "Failed to sync sites from Google Sheets");
    res.status(502).json({ error: err instanceof Error ? err.message : "Sync failed" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/storage.ts
SIZE: 4,375 bytes

```
import { Router, type IRouter, type Request, type Response } from "express";
import { Readable } from "stream";
import {
  RequestUploadUrlBody,
  RequestUploadUrlResponse,
} from "@workspace/api-zod";
import { ObjectStorageService, ObjectNotFoundError } from "../lib/objectStorage";
import { ObjectPermission } from "../lib/objectAcl";

const router: IRouter = Router();
const objectStorageService = new ObjectStorageService();

/**
 * POST /storage/uploads/request-url
 *
 * Request a presigned URL for file upload.
 * The client sends JSON metadata (name, size, contentType)   NOT the file.
 * Then uploads the file directly to the returned presigned URL.
 */
router.post("/storage/uploads/request-url", async (req: Request, res: Response) => {
  const parsed = RequestUploadUrlBody.safeParse(req.body);
  if (!parsed.success) {
    res.status(400).json({ error: "Missing or invalid required fields" });
    return;
  }

  try {
    const { name, size, contentType } = parsed.data;

    const uploadURL = await objectStorageService.getObjectEntityUploadURL();
    const objectPath = objectStorageService.normalizeObjectEntityPath(uploadURL);

    res.json(
      RequestUploadUrlResponse.parse({
        uploadURL,
        objectPath,
        metadata: { name, size, contentType },
      }),
    );
  } catch (error) {
    req.log.error({ err: error }, "Error generating upload URL");
    res.status(500).json({ error: "Failed to generate upload URL" });
  }
});

/**
 * GET /storage/public-objects/*
 *
 * Serve public assets from PUBLIC_OBJECT_SEARCH_PATHS.
```

```
 * These are unconditionally public   no authentication or ACL checks.
 * IMPORTANT: Always provide this endpoint when object storage is set up.
 */
router.get("/storage/public-objects/*filePath", async (req: Request, res: Response) => {
  try {
    const raw = req.params.filePath;
    const filePath = Array.isArray(raw) ? raw.join("/") : raw;
    const file = await objectStorageService.searchPublicObject(filePath);
    if (!file) {
      res.status(404).json({ error: "File not found" });
      return;
    }

    const response = await objectStorageService.downloadObject(file);

    res.status(response.status);
    response.headers.forEach((value, key) => res.setHeader(key, value));

    if (response.body) {
      const nodeStream = Readable.fromWeb(response.body as ReadableStream<Uint8Array>);
      nodeStream.pipe(res);
    } else {
      res.end();
    }
  } catch (error) {
    req.log.error({ err: error }, "Error serving public object");
    res.status(500).json({ error: "Failed to serve public object" });
  }
});

/**
 * GET /storage/objects/*
 *
 * Serve object entities from PRIVATE_OBJECT_DIR.
 * These are served from a separate path from /public-objects and can optionally
 * be protected with authentication or ACL checks based on the use case.
 */
router.get("/storage/objects/*path", async (req: Request, res: Response) => {
  try {
    const raw = req.params.path;
    const wildcardPath = Array.isArray(raw) ? raw.join("/") : raw;
    const objectPath = `/objects/${wildcardPath}`;
    const objectFile = await objectStorageService.getObjectEntityFile(objectPath);

    // --- Protected route example (uncomment when using replit-auth) ---
    // if (!req.isAuthenticated()) {
    //   res.status(401).json({ error: "Unauthorized" });
    //   return;
    // }
    // const canAccess = await objectStorageService.canAccessObjectEntity({
    //   userId: req.user.id,
    //   objectFile,
```

```
    //   requestedPermission: ObjectPermission.READ,
    // });
    // if (!canAccess) {
    //   res.status(403).json({ error: "Forbidden" });
    //   return;
    // }

    const response = await objectStorageService.downloadObject(objectFile);

    res.status(response.status);
    response.headers.forEach((value, key) => res.setHeader(key, value));

    if (response.body) {
      const nodeStream = Readable.fromWeb(response.body as ReadableStream<Uint8Array>);
      nodeStream.pipe(res);
    } else {
      res.end();
    }
  } catch (error) {
    if (error instanceof ObjectNotFoundError) {
      req.log.warn({ err: error }, "Object not found");
      res.status(404).json({ error: "Object not found" });
      return;
    }
    req.log.error({ err: error }, "Error serving object");
    res.status(500).json({ error: "Failed to serve object" });
  }
});

export default router;
```

FILE: artifacts/api-server/src/routes/technicians.ts
SIZE: 11,414 bytes

```
import { Router, type IRouter, type Request, type Response } from "express";
import { db } from "@workspace/db";
import { techniciansTable, missionsTable } from "@workspace/db/schema";
import { eq, desc } from "drizzle-orm";
import crypto from "crypto";
import { generateTechToken, verifyTechToken } from "../lib/techToken";

const router: IRouter = Router();

function hashPassword(password: string): string {
  return crypto.createHash("sha256").update(password).digest("hex");
}

/**
 * Validate the Authorization header for technician app routes.
 * Returns the verified technicianId or sends a 401/403 response.
 */
async function requireTechnicianAuth(req: Request, res: Response): Promise<number | null> {
  const id = verifyTechToken(req.headers.authorization);
  if (!id) {
    res.status(401).json({ error: "Authentication required" });
    return null;
  }
  const [tech] = await db.select({ id: techniciansTable.id, active: techniciansTable.active })
    .from(techniciansTable)
    .where(eq(techniciansTable.id, id));
  if (!tech || !tech.active) {
    res.status(401).json({ error: "Invalid or inactive account" });
    return null;
  }
  return id;
}

// ?? Admin CRUD Routes ????????????????????????????????????????????????????

router.get("/technicians", async (req, res) => {
  try {
    const technicians = await db.select().from(techniciansTable).orderBy(techniciansTable.name);
    res.json(technicians.map((t) => ({
      id: t.id,
      name: t.name,
      phone: t.phone,
      email: t.email,
      zone: t.zone,
      active: t.active,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list technicians");
    res.status(500).json({ error: "Internal server error" });
```

```
  }
});

router.post("/technicians", async (req, res) => {
  try {
    const body = req.body;
    const [technician] = await db.insert(techniciansTable).values({
      name: body.name,
      phone: body.phone || "",
      email: body.email || "",
      zone: body.zone || "",
      active: body.active !== undefined ? body.active : true,
      passwordHash: body.password ? hashPassword(body.password) : hashPassword("Tech@1234"),
    }).returning();
    res.status(201).json({
      id: technician.id,
      name: technician.name,
      phone: technician.phone,
      email: technician.email,
      zone: technician.zone,
      active: technician.active,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to create technician");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.put("/technicians/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    const body = req.body;
    const updateData: Record<string, unknown> = {
      name: body.name,
      phone: body.phone,
      email: body.email,
      zone: body.zone,
      active: body.active,
    };
    if (body.password) updateData.passwordHash = hashPassword(body.password);
    const [technician] = await db.update(techniciansTable)
      .set(updateData)
      .where(eq(techniciansTable.id, id))
      .returning();
    if (!technician) return res.status(404).json({ error: "Not found" });
    res.json({
      id: technician.id,
      name: technician.name,
      phone: technician.phone,
      email: technician.email,
      zone: technician.zone,
      active: technician.active,
```

```
    });
  } catch (err) {
    req.log.error({ err }, "Failed to update technician");
    res.status(500).json({ error: "Internal server error" });
  }
});

router.delete("/technicians/:id", async (req, res) => {
  try {
    const id = parseInt(req.params.id);
    await db.delete(techniciansTable).where(eq(techniciansTable.id, id));
    res.status(204).send();
  } catch (err) {
    req.log.error({ err }, "Failed to delete technician");
    res.status(500).json({ error: "Internal server error" });
  }
});

// ?? Technician App Routes ??????????????????????????????????????????????????

// Technician login   returns a HMAC-signed bearer token
router.post("/technician/login", async (req, res) => {
  try {
    const { email, password } = req.body;
    if (!email || !password) return res.status(400).json({ error: "Email and password required" });

    const [tech] = await db.select().from(techniciansTable).where(eq(techniciansTable.email, email));
    if (!tech) return res.status(401).json({ error: "Invalid credentials" });
    if (!tech.active) return res.status(401).json({ error: "Account is inactive" });
    if (tech.passwordHash !== hashPassword(password)) {
      return res.status(401).json({ error: "Invalid credentials" });
    }

    const token = generateTechToken(tech.id);
    res.json({
      success: true,
      technicianId: tech.id,
      name: tech.name,
      email: tech.email,
      zone: tech.zone,
      token,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to login technician");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Register device push token   authenticated, ownership-checked
// Accepts { token: string }   works with both Expo push tokens and FCM tokens.
router.put("/technicians/:id/fcm-token", async (req, res) => {
  try {
```

```
    const technicianId = await requireTechnicianAuth(req, res);
    if (technicianId === null) return;

    const requestedId = parseInt(req.params.id);
    if (requestedId !== technicianId) {
      return res.status(403).json({ error: "Cannot update another technician's push token" });
    }

    const { token } = req.body;
    if (!token || typeof token !== "string") {
      return res.status(400).json({ error: "token (string) is required" });
    }

    const [tech] = await db.update(techniciansTable)
      .set({ fcmToken: token, expoPushToken: token })
      .where(eq(techniciansTable.id, technicianId))
      .returning();
    if (!tech) return res.status(404).json({ error: "Not found" });
    res.json({ success: true });
  } catch (err) {
    req.log.error({ err }, "Failed to register push token");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Technician missions list   filtered by the authenticated technician's ID only
router.get("/technician/missions", async (req, res) => {
  try {
    const technicianId = await requireTechnicianAuth(req, res);
    if (technicianId === null) return;

    const statusFilter = req.query.status as string | undefined;

    let missions = await db.select().from(missionsTable)
      .where(eq(missionsTable.assignedTechnicianId, technicianId))
      .orderBy(desc(missionsTable.createdAt));

    if (statusFilter) {
      missions = missions.filter((m) => m.missionStatus === statusFilter);
    }

    res.json(missions.map((m) => ({
      id: m.id,
      missionId: m.missionId,
      siteName: m.siteName,
      generator: m.generator,
      project: m.project,
      driverName: m.driverName,
      assignedDriver: m.assignedDriver,
      createdDate: m.createdDate?.toISOString() ?? null,
      filledLiters: m.filledLiters,
      virtualCalculated: m.virtualCalculated,
```

```
      actualInTank: m.actualInTank,
      quantityAddedLastTask: m.quantityAddedLastTask,
      city: m.city,
      notes: m.notes,
      missionStatus: m.missionStatus,
      createdBy: m.createdBy,
      technicianRemark: m.technicianRemark,
      technicianStatus: m.technicianStatus,
      reviewedBy: m.reviewedBy,
      reviewedAt: m.reviewedAt?.toISOString() ?? null,
    })));
  } catch (err) {
    req.log.error({ err }, "Failed to list technician missions");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Technician mission detail   authenticated, filtered to assigned mission
router.get("/technician/missions/:id", async (req, res) => {
  try {
    const technicianId = await requireTechnicianAuth(req, res);
    if (technicianId === null) return;

    const missionId = parseInt(req.params.id);
    const [mission] = await db.select().from(missionsTable)
      .where(eq(missionsTable.id, missionId));

    if (!mission) return res.status(404).json({ error: "Mission not found" });
    if (mission.assignedTechnicianId !== technicianId) {
      return res.status(403).json({ error: "Not assigned to this mission" });
    }

    res.json({
      id: mission.id,
      missionId: mission.missionId,
      siteName: mission.siteName,
      generator: mission.generator,
      project: mission.project,
      driverName: mission.driverName,
      assignedDriver: mission.assignedDriver,
      createdDate: mission.createdDate?.toISOString() ?? null,
      filledLiters: mission.filledLiters,
      virtualCalculated: mission.virtualCalculated,
      actualInTank: mission.actualInTank,
      quantityAddedLastTask: mission.quantityAddedLastTask,
      city: mission.city,
      notes: mission.notes,
      missionStatus: mission.missionStatus,
      createdBy: mission.createdBy,
      technicianRemark: mission.technicianRemark,
      technicianStatus: mission.technicianStatus,
      reviewedBy: mission.reviewedBy,
```

```
      reviewedAt: mission.reviewedAt?.toISOString() ?? null,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to get technician mission detail");
    res.status(500).json({ error: "Internal server error" });
  }
});

// Technician follow-up submission   authenticated + assignment verified
router.put("/technician/missions/:id/followup", async (req, res) => {
  try {
    const technicianId = await requireTechnicianAuth(req, res);
    if (technicianId === null) return;

    const missionId = parseInt(req.params.id);

    const [existing] = await db.select({ assignedTechnicianId: missionsTable.assignedTechnicianId })
      .from(missionsTable)
      .where(eq(missionsTable.id, missionId));

    if (!existing) return res.status(404).json({ error: "Mission not found" });
    if (existing.assignedTechnicianId !== technicianId) {
      return res.status(403).json({ error: "Not assigned to this mission" });
    }

    const { technicianRemark, technicianStatus, reviewedBy } = req.body;

    const [mission] = await db.update(missionsTable).set({
      technicianRemark: technicianRemark ?? "",
      technicianStatus: technicianStatus ?? "Reviewed",
      reviewedBy: reviewedBy ?? "",
      reviewedAt: new Date(),
    }).where(eq(missionsTable.id, missionId)).returning();

    res.json({
      id: mission.id,
      missionId: mission.missionId,
      siteName: mission.siteName,
      generator: mission.generator,
      project: mission.project,
      driverName: mission.driverName,
      filledLiters: mission.filledLiters,
      virtualCalculated: mission.virtualCalculated,
      actualInTank: mission.actualInTank,
      quantityAddedLastTask: mission.quantityAddedLastTask,
      city: mission.city,
      notes: mission.notes,
      missionStatus: mission.missionStatus,
      createdBy: mission.createdBy,
      technicianRemark: mission.technicianRemark,
      technicianStatus: mission.technicianStatus,
      reviewedBy: mission.reviewedBy,
```

```
      reviewedAt: mission.reviewedAt?.toISOString() ?? null,
    });
  } catch (err) {
    req.log.error({ err }, "Failed to follow up on mission");
    res.status(500).json({ error: "Internal server error" });
  }
});

export default router;
```

FILE: artifacts/api-server/tsconfig.json
SIZE: 271 bytes

```
{
  "extends": "../../tsconfig.base.json",
  "compilerOptions": {
    "outDir": "dist",
    "rootDir": "src",
    "types": ["node"]
  },
  "include": ["src"],
  "references": [
    {
      "path": "../../lib/db"
    },
    {
      "path": "../../lib/api-zod"
    }
  ]
}
```

FILE: artifacts/mockup-sandbox/.replit-artifact/artifact.toml
SIZE: 327 bytes

```
kind = "design"
previewPath = "/__mockup"
title = "Canvas"
version = "1.0.0"
id = "XegfDyZt7HqfW2Bb8Ghoy"

[[services]]
localPort = 8081
name = "Component Preview Server"
paths = ["/__mockup"]

[services.env]
PORT = "8081"
BASE_PATH = "/__mockup"

[services.development]
run = "pnpm --filter @workspace/mockup-sandbox run dev"
```

FILE: artifacts/mockup-sandbox/components.json
SIZE: 426 bytes

```
{
  "$schema": "https://ui.shadcn.com/schema.json",
  "style": "new-york",
  "rsc": false,
  "tsx": true,
  "tailwind": {
    "config": "",
    "css": "src/index.css",
    "baseColor": "neutral",
    "cssVariables": true,
    "prefix": ""
  },
  "iconLibrary": "lucide",
  "aliases": {
    "components": "@/components",
    "utils": "@/lib/utils",
    "ui": "@/components/ui",
    "lib": "@/lib",
    "hooks": "@/hooks"
  }
}
```

FILE: artifacts/mockup-sandbox/index.html
SIZE: 4,325 bytes

```
<!DOCTYPE html>
<!--
  This file is the entry for ALL routes, including /preview/* canvas iframes.
  Fonts are loaded here as non-blocking <link> tags (not CSS @import, which is render-blocking).
-->
<html lang="en" style="height: 100%">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0, maximum-scale=1" />

    <meta property="og:title" content="Mockup Canvas" />
    <meta property="og:description" content="UI prototyping sandbox with infinite canvas" />
    <meta property="og:type" content="website" />
    <meta name="twitter:card" content="summary_large_image" />
    <meta name="twitter:title" content="Mockup Canvas" />
    <meta name="twitter:description" content="UI prototyping sandbox with infinite canvas" />

    <title>Mockup Canvas</title>
    <link rel="icon" href="data:image/svg+xml,<svg xmlns='http://www.w3.org/2000/svg' viewBox='0 0 100 100'><tex
  t y='.9em' font-size='90'>?</text></svg>">
    <!-- Non-blocking font bundle: renders with fallback fonts immediately, swaps in when loaded -->
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link rel="stylesheet" media="print" onload="this.media='all'"
          href="https://fonts.googleapis.com/css2?family=Architects+Daughter&family=DM+Sans:ital,opsz,wght@0,9..
  40,100..1000;1,9..40,100..1000&family=Fira+Code:wght@300..700&family=Geist+Mono:wght@100..900&family=Geist:wght@
  100..900&family=IBM+Plex+Mono:ital,wght@0,100;0,200;0,300;0,400;0,500;0,600;0,700;1,100;1,200;1,300;1,400;1,500;
  1,600;1,700&family=IBM+Plex+Sans:ital,wght@0,100..700;1,100..700&family=Inter:ital,opsz,wght@0,14..32,100..900;1
  ,14..32,100..900&family=JetBrains+Mono:ital,wght@0,100..800;1,100..800&family=Libre+Baskerville:ital,wght@0,400;
  0,700;1,400&family=Lora:ital,wght@0,400..700;1,400..700&family=Merriweather:ital,opsz,wght@0,18..144,300..900;1,
  18..144,300..900&family=Montserrat:ital,wght@0,100..900;1,100..900&family=Open+Sans:ital,wght@0,300..800;1,300..
  800&family=Outfit:wght@100..900&family=Oxanium:wght@200..800&family=Playfair+Display:ital,wght@0,400..900;1,400.
  .900&family=Plus+Jakarta+Sans:ital,wght@0,200..800;1,200..800&family=Poppins:ital,wght@0,100;0,200;0,300;0,400;0
  ,500;0,600;0,700;0,800;0,900;1,100;1,200;1,300;1,400;1,500;1,600;1,700;1,800;1,900&family=Roboto+Mono:ital,wght@
  0,100..700;1,100..700&family=Roboto:ital,wght@0,100..900;1,100..900&family=Source+Code+Pro:ital,wght@0,200..900;
  1,200..900&family=Source+Serif+4:ital,opsz,wght@0,8..60,200..900;1,8..60,200..900&family=Space+Grotesk:wght@300.
  .700&family=Space+Mono:ital,wght@0,400;0,700;1,400;1,700&display=swap">
    <noscript><link rel="stylesheet" href="https://fonts.googleapis.com/css2?family=Architects+Daughter&family=D
  M+Sans:ital,opsz,wght@0,9..40,100..1000;1,9..40,100..1000&family=Fira+Code:wght@300..700&family=Geist+Mono:wght@
  100..900&family=Geist:wght@100..900&family=IBM+Plex+Mono:ital,wght@0,100;0,200;0,300;0,400;0,500;0,600;0,700;1,1
  00;1,200;1,300;1,400;1,500;1,600;1,700&family=IBM+Plex+Sans:ital,wght@0,100..700;1,100..700&family=Inter:ital,op
  sz,wght@0,14..32,100..900;1,14..32,100..900&family=JetBrains+Mono:ital,wght@0,100..800;1,100..800&family=Libre+B
  askerville:ital,wght@0,400;0,700;1,400&family=Lora:ital,wght@0,400..700;1,400..700&family=Merriweather:ital,opsz
  ,wght@0,18..144,300..900;1,18..144,300..900&family=Montserrat:ital,wght@0,100..900;1,100..900&family=Open+Sans:i
  tal,wght@0,300..800;1,300..800&family=Outfit:wght@100..900&family=Oxanium:wght@200..800&family=Playfair+Display:
  ital,wght@0,400..900;1,400..900&family=Plus+Jakarta+Sans:ital,wght@0,200..800;1,200..800&family=Poppins:ital,wgh
  t@0,100;0,200;0,300;0,400;0,500;0,600;0,700;0,800;0,900;1,100;1,200;1,300;1,400;1,500;1,600;1,700;1,800;1,900&fa
  mily=Roboto+Mono:ital,wght@0,100..700;1,100..700&family=Roboto:ital,wght@0,100..900;1,100..900&family=Source+Cod
  e+Pro:ital,wght@0,200..900;1,200..900&family=Source+Serif+4:ital,opsz,wght@0,8..60,200..900;1,8..60,200..900&fam
```

```
  ily=Space+Grotesk:wght@300..700&family=Space+Mono:ital,wght@0,400;0,700;1,400;1,700&display=swap"></noscript>
  </head>
  <body style="height: 100%; margin: 0">
    <div id="root" style="height: 100%"></div>
    <script type="module" src="/src/main.tsx"></script>
  </body>
</html>
```

FILE: artifacts/mockup-sandbox/mockupPreviewPlugin.ts
SIZE: 4,639 bytes

```
import { mkdirSync, writeFileSync } from "fs";
import path from "path";
import glob from "fast-glob";
import chokidar from "chokidar";
import type { FSWatcher } from "chokidar";
import type { Plugin } from "vite";

const MOCKUPS_DIR = "src/components/mockups";
const GENERATED_MODULE = "src/.generated/mockup-components.ts";

interface DiscoveredComponent {
  globKey: string;
  importPath: string;
}

export function mockupPreviewPlugin(): Plugin {
  let root = "";
  let currentSource = "";
  let watcher: FSWatcher | null = null;

  function getMockupsAbsDir(): string {
    return path.join(root, MOCKUPS_DIR);
  }

  function getGeneratedModuleAbsPath(): string {
    return path.join(root, GENERATED_MODULE);
  }

  function isMockupFile(absolutePath: string): boolean {
    const rel = path.relative(getMockupsAbsDir(), absolutePath);
    return (
      !rel.startsWith("..") && !path.isAbsolute(rel) && rel.endsWith(".tsx")
    );
  }

  function isPreviewTarget(relativeToMockups: string): boolean {
    return relativeToMockups
      .split(path.sep)
      .every((segment) => !segment.startsWith("_"));
  }

  async function discoverComponents(): Promise<Array<DiscoveredComponent>> {
    const files = await glob(`${MOCKUPS_DIR}/**/*.tsx`, {
      cwd: root,
      ignore: ["**/_*/**", "**/_*.tsx"],
    });

    return files.map((f) => ({
      globKey: "./" + f.slice("src/".length),
```

```
    importPath: path.posix.relative("src/.generated", f),
  }));
}

function generateSource(components: Array<DiscoveredComponent>): string {
  const entries = components
    .map(
      (c) =>
        `  ${JSON.stringify(c.globKey)}: () => import(${JSON.stringify(c.importPath)})`,
    )
    .join(",\n");

  return [
    "// This file is auto-generated by mockupPreviewPlugin.ts.",
    "type ModuleMap = Record<string, () => Promise<Record<string, unknown>>>;",
    "export const modules: ModuleMap = {",
    entries,
    "};",
    "",
  ].join("\n");
}

function shouldAutoRescan(pathname: string): boolean {
  return (
    pathname.includes("/components/mockups/") ||
    pathname.includes("/.generated/mockup-components")
  );
}

let refreshInFlight = false;
let refreshQueued = false;

async function refresh(): Promise<boolean> {
  if (refreshInFlight) {
    refreshQueued = true;
    return false;
  }

  refreshInFlight = true;
  let changed = false;
  try {
    const components = await discoverComponents();
    const newSource = generateSource(components);
    if (newSource !== currentSource) {
      currentSource = newSource;
      const generatedModuleAbsPath = getGeneratedModuleAbsPath();
      mkdirSync(path.dirname(generatedModuleAbsPath), { recursive: true });
      writeFileSync(generatedModuleAbsPath, currentSource);
      changed = true;
    }
  } finally {
    refreshInFlight = false;
```

```
  }

  if (refreshQueued) {
    refreshQueued = false;
    const followUp = await refresh();
    return changed || followUp;
  }

  return changed;
}

async function onFileAddedOrRemoved(): Promise<void> {
  await refresh();
}

return {
  name: "mockup-preview",
  enforce: "pre",

  configResolved(config) {
    root = config.root;
  },

  async buildStart() {
    await refresh();
  },

  async configureServer(viteServer) {
    await refresh();

    const mockupsAbsDir = getMockupsAbsDir();
    mkdirSync(mockupsAbsDir, { recursive: true });

    watcher = chokidar.watch(mockupsAbsDir, {
      ignoreInitial: true,
      awaitWriteFinish: {
        stabilityThreshold: 100,
        pollInterval: 50,
      },
    });

    watcher.on("add", (file) => {
      if (
        isMockupFile(file) &&
        isPreviewTarget(path.relative(mockupsAbsDir, file))
      ) {
        void onFileAddedOrRemoved();
      }
    });

    watcher.on("unlink", (file) => {
      if (isMockupFile(file)) {
```

```
          void onFileAddedOrRemoved();
        }
      });

      viteServer.middlewares.use((req, res, next) => {
        const requestUrl = new URL(req.url ?? "/", "http://127.0.0.1");
        const pathname = requestUrl.pathname;
        const originalEnd = res.end.bind(res);

        res.end = ((...args: Parameters<typeof originalEnd>) => {
          if (res.statusCode === 404 && shouldAutoRescan(pathname)) {
            void refresh();
          }
          return originalEnd(...args);
        }) as typeof res.end;

        next();
      });
    },

    async closeWatcher() {
      if (watcher) {
        await watcher.close();
      }
    },
  };
}
```

FILE: artifacts/mockup-sandbox/package.json
SIZE: 2,511 bytes

```
{
  "name": "@workspace/mockup-sandbox",
  "version": "2.0.0",
  "type": "module",
  "private": true,
  "scripts": {
    "dev": "vite dev",
    "build": "vite build",
    "preview": "vite preview",
    "typecheck": "tsc -p tsconfig.json --noEmit"
  },
  "devDependencies": {
    "@hookform/resolvers": "^3.10.0",
    "@radix-ui/react-accordion": "^1.2.12",
    "@radix-ui/react-alert-dialog": "^1.1.15",
    "@radix-ui/react-aspect-ratio": "^1.1.8",
    "@radix-ui/react-avatar": "^1.1.11",
    "@radix-ui/react-checkbox": "^1.3.3",
    "@radix-ui/react-collapsible": "^1.1.12",
    "@radix-ui/react-context-menu": "^2.2.16",
    "@radix-ui/react-dialog": "^1.1.15",
    "@radix-ui/react-dropdown-menu": "^2.1.16",
    "@radix-ui/react-hover-card": "^1.1.15",
    "@radix-ui/react-label": "^2.1.8",
    "@radix-ui/react-menubar": "^1.1.16",
    "@radix-ui/react-navigation-menu": "^1.2.14",
    "@radix-ui/react-popover": "^1.1.15",
    "@radix-ui/react-progress": "^1.1.8",
    "@radix-ui/react-radio-group": "^1.3.8",
    "@radix-ui/react-scroll-area": "^1.2.10",
    "@radix-ui/react-select": "^2.2.6",
    "@radix-ui/react-separator": "^1.1.8",
    "@radix-ui/react-slider": "^1.3.6",
    "@radix-ui/react-slot": "^1.2.4",
    "@radix-ui/react-switch": "^1.2.6",
    "@radix-ui/react-tabs": "^1.1.13",
    "@radix-ui/react-toast": "^1.2.7",
    "@radix-ui/react-toggle": "^1.1.10",
    "@radix-ui/react-toggle-group": "^1.1.11",
    "@radix-ui/react-tooltip": "^1.2.8",
    "@replit/vite-plugin-cartographer": "catalog:",
    "@replit/vite-plugin-runtime-error-modal": "catalog:",
    "@tailwindcss/vite": "catalog:",
    "@types/node": "catalog:",
    "@types/react": "catalog:",
    "@types/react-dom": "catalog:",
    "@vitejs/plugin-react": "catalog:",
    "chokidar": "^4.0.3",
    "class-variance-authority": "catalog:",
```

```
    "clsx": "catalog:",
    "cmdk": "^1.1.1",
    "date-fns": "^3.6.0",
    "embla-carousel-react": "^8.6.0",
    "fast-glob": "^3.3.3",
    "framer-motion": "catalog:",
    "input-otp": "^1.4.2",
    "lucide-react": "catalog:",
    "next-themes": "^0.4.6",
    "react": "catalog:",
    "react-day-picker": "^9.11.1",
    "react-dom": "catalog:",
    "react-hook-form": "^7.66.0",
    "react-resizable-panels": "^2.1.9",
    "recharts": "^2.15.4",
    "sonner": "^2.0.7",
    "tailwind-merge": "catalog:",
    "tailwindcss": "catalog:",
    "tailwindcss-animate": "^1.0.7",
    "tw-animate-css": "^1.4.0",
    "vaul": "^1.1.2",
    "vite": "catalog:",
    "zod": "catalog:"
  }
}
```

FILE: artifacts/mockup-sandbox/src/.generated/mockup-components.ts
SIZE: 171 bytes

```
// This file is auto-generated by mockupPreviewPlugin.ts.
type ModuleMap = Record<string, () => Promise<Record<string, unknown>>>;
export const modules: ModuleMap = {

};
```

FILE: artifacts/mockup-sandbox/src/App.tsx
SIZE: 3,654 bytes

```
import { useEffect, useState, type ComponentType } from "react";

import { modules as discoveredModules } from "./.generated/mockup-components";

type ModuleMap = Record<string, () => Promise<Record<string, unknown>>>;

function _resolveComponent(
  mod: Record<string, unknown>,
  name: string,
): ComponentType | undefined {
  const fns = Object.values(mod).filter(
    (v) => typeof v === "function",
  ) as ComponentType[];
  return (
    (mod.default as ComponentType) ||
    (mod.Preview as ComponentType) ||
    (mod[name] as ComponentType) ||
    fns[fns.length - 1]
  );
}

function PreviewRenderer({
  componentPath,
  modules,
}: {
  componentPath: string;
  modules: ModuleMap;
}) {
  const [Component, setComponent] = useState<ComponentType | null>(null);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    let cancelled = false;

    setComponent(null);
    setError(null);

    async function loadComponent(): Promise<void> {
      const key = `./components/mockups/${componentPath}.tsx`;
      const loader = modules[key];
      if (!loader) {
        setError(`No component found at ${componentPath}.tsx`);
        return;
      }

      try {
        const mod = await loader();
        if (cancelled) {
          return;
```

```
        }
        const name = componentPath.split("/").pop()!;
        const comp = _resolveComponent(mod, name);
        if (!comp) {
          setError(
            'No exported React component found in ${componentPath}.tsx\n\nMake sure the file has at least one ex
  ported function component.',
          );
          return;
        }
        setComponent(() => comp);
      } catch (e) {
        if (cancelled) {
          return;
        }

        const message = e instanceof Error ? e.message : String(e);
        setError('Failed to load preview.\n${message}');
      }
    }

    void loadComponent();

    return () => {
      cancelled = true;
    };
  }, [componentPath, modules]);

  if (error) {
    return (
      <pre style={{ color: "red", padding: "2rem", fontFamily: "system-ui" }}>
        {error}
      </pre>
    );
  }

  if (!Component) return null;

  return <Component />;
}

function getBasePath(): string {
  return import.meta.env.BASE_URL.replace(/\/$/, "");
}

function getPreviewExamplePath(): string {
  const basePath = getBasePath();
  return '${basePath}/preview/ComponentName';
}

function Gallery() {
  return (
```

```
    <div className="min-h-screen bg-gray-50 flex items-center justify-center p-8">
      <div className="text-center max-w-md">
        <h1 className="text-2xl font-semibold text-gray-900 mb-3">
          Component Preview Server
        </h1>
        <p className="text-gray-500 mb-4">
          This server renders individual components for the workspace canvas.
        </p>
        <p className="text-sm text-gray-400">
          Access component previews at{" "}
          <code className="bg-gray-100 px-1.5 py-0.5 rounded text-gray-600">
            {getPreviewExamplePath()}
          </code>
        </p>
      </div>
    </div>
  );
}

function getPreviewPath(): string | null {
  const basePath = getBasePath();
  const { pathname } = window.location;
  const local =
    basePath && pathname.startsWith(basePath)
      ? pathname.slice(basePath.length) || "/"
      : pathname;
  const match = local.match(/^\/preview\/(.+)$/);
  return match ? match[1] : null;
}

function App() {
  const previewPath = getPreviewPath();

  if (previewPath) {
    return (
      <PreviewRenderer
        componentPath={previewPath}
        modules={discoveredModules}
      />
    );
  }

  return <Gallery />;
}

export default App;
```

FILE: artifacts/mockup-sandbox/src/components/ui/accordion.tsx
SIZE: 2,001 bytes

```
import * as React from "react"
import * as AccordionPrimitive from "@radix-ui/react-accordion"
import { ChevronDown } from "lucide-react"

import { cn } from "@/lib/utils"

const Accordion = AccordionPrimitive.Root

const AccordionItem = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Item>
>(({ className, ...props }, ref) => (
  <AccordionPrimitive.Item
    ref={ref}
    className={cn("border-b", className)}
    {...props}
  />
))
AccordionItem.displayName = "AccordionItem"

const AccordionTrigger = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Header className="flex">
    <AccordionPrimitive.Trigger
      ref={ref}
      className={cn(
        "flex flex-1 items-center justify-between py-4 text-sm font-medium transition-all hover:underline text-l
  eft [&[data-state=open]>svg]:rotate-180",
        className
      )}
      {...props}
    >
      {children}
      <ChevronDown className="h-4 w-4 shrink-0 text-muted-foreground transition-transform duration-200" />
    </AccordionPrimitive.Trigger>
  </AccordionPrimitive.Header>
))
AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName

const AccordionContent = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Content
    ref={ref}
    className="overflow-hidden text-sm data-[state=closed]:animate-accordion-up data-[state=open]:animate-accord
  ion-down"
```

```
    {...props}
  >
    <div className={cn("pb-4 pt-0", className)}>{children}</div>
  </AccordionPrimitive.Content>
))
AccordionContent.displayName = AccordionPrimitive.Content.displayName

export { Accordion, AccordionItem, AccordionTrigger, AccordionContent }
```

FILE: artifacts/mockup-sandbox/src/components/ui/alert-dialog.tsx
SIZE: 4,419 bytes

```
import * as React from "react"
import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog"

import { cn } from "@/lib/utils"
import { buttonVariants } from "@/components/ui/button"

const AlertDialog = AlertDialogPrimitive.Root

const AlertDialogTrigger = AlertDialogPrimitive.Trigger

const AlertDialogPortal = AlertDialogPrimitive.Portal

const AlertDialogOverlay = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=c
  losed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
    ref={ref}
  />
))
AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName

const AlertDialogContent = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Content>
>(({ className, ...props }, ref) => (
  <AlertDialogPortal>
    <AlertDialogOverlay />
    <AlertDialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
   bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-[state=closed]:animate-out data-[sta
  te=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 d
  ata-[state=closed]:slide-out-to-left-1/2 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-f
  rom-left-1/2 data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
        className
      )}
      {...props}
    />
  </AlertDialogPortal>
))
AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName
```

```
const AlertDialogHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-2 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
AlertDialogHeader.displayName = "AlertDialogHeader"

const AlertDialogFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
AlertDialogFooter.displayName = "AlertDialogFooter"

const AlertDialogTitle = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold", className)}
    {...props}
  />
))
AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName

const AlertDialogDescription = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
AlertDialogDescription.displayName =
```

```
  AlertDialogPrimitive.Description.displayName

const AlertDialogAction = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Action>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Action>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Action
    ref={ref}
    className={cn(buttonVariants(), className)}
    {...props}
  />
))
AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName

const AlertDialogCancel = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Cancel>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Cancel>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Cancel
    ref={ref}
    className={cn(
      buttonVariants({ variant: "outline" }),
      "mt-2 sm:mt-0",
      className
    )}
    {...props}
  />
))
AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName

export {
  AlertDialog,
  AlertDialogPortal,
  AlertDialogOverlay,
  AlertDialogTrigger,
  AlertDialogContent,
  AlertDialogHeader,
  AlertDialogFooter,
  AlertDialogTitle,
  AlertDialogDescription,
  AlertDialogAction,
  AlertDialogCancel,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/alert.tsx
SIZE: 1,598 bytes

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const alertVariants = cva(
  "relative w-full rounded-lg border px-4 py-3 text-sm [&>svg+div]:translate-y-[-3px] [&>svg]:absolute [&>svg]:l
  eft-4 [&>svg]:top-4 [&>svg]:text-foreground [&>svg~*]:pl-7",
  {
    variants: {
      variant: {
        default: "bg-background text-foreground",
        destructive:
          "border-destructive/50 text-destructive dark:border-destructive [&>svg]:text-destructive",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Alert = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement> & VariantProps<typeof alertVariants>
>(({ className, variant, ...props }, ref) => (
  <div
    ref={ref}
    role="alert"
    className={cn(alertVariants({ variant }), className)}
    {...props}
  />
))
Alert.displayName = "Alert"

const AlertTitle = React.forwardRef<
  HTMLParagraphElement,
  React.HTMLAttributes<HTMLHeadingElement>
>(({ className, ...props }, ref) => (
  <h5
    ref={ref}
    className={cn("mb-1 font-medium leading-none tracking-tight", className)}
    {...props}
  />
))
AlertTitle.displayName = "AlertTitle"

const AlertDescription = React.forwardRef<
  HTMLParagraphElement,
```

```
  React.HTMLAttributes<HTMLParagraphElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("text-sm [&_p]:leading-relaxed", className)}
    {...props}
  />
))
AlertDescription.displayName = "AlertDescription"

export { Alert, AlertTitle, AlertDescription }
```

FILE: artifacts/mockup-sandbox/src/components/ui/aspect-ratio.tsx
SIZE: 140 bytes

```
import * as AspectRatioPrimitive from "@radix-ui/react-aspect-ratio"

const AspectRatio = AspectRatioPrimitive.Root

export { AspectRatio }
```

FILE: artifacts/mockup-sandbox/src/components/ui/avatar.tsx
SIZE: 1,419 bytes

```
"use client"

import * as React from "react"
import * as AvatarPrimitive from "@radix-ui/react-avatar"

import { cn } from "@/lib/utils"

const Avatar = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Root
    ref={ref}
    className={cn(
      "relative flex h-10 w-10 shrink-0 overflow-hidden rounded-full",
      className
    )}
    {...props}
  />
))
Avatar.displayName = AvatarPrimitive.Root.displayName

const AvatarImage = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Image>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Image>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Image
    ref={ref}
    className={cn("aspect-square h-full w-full", className)}
    {...props}
  />
))
AvatarImage.displayName = AvatarPrimitive.Image.displayName

const AvatarFallback = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Fallback>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Fallback>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Fallback
    ref={ref}
    className={cn(
      "flex h-full w-full items-center justify-center rounded-full bg-muted",
      className
    )}
    {...props}
  />
))
AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName
```

```
export { Avatar, AvatarImage, AvatarFallback }
```

FILE: artifacts/mockup-sandbox/src/components/ui/badge.tsx
SIZE: 1,163 bytes

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const badgeVariants = cva(
  "whitespace-nowrap inline-flex items-center rounded-md border px-2.5 py-0.5 text-xs font-semibold transition-c
  olors focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2" +
  " hover-elevate ",
  {
    variants: {
      variant: {
        default:
          "border-transparent bg-primary text-primary-foreground shadow-xs",
        secondary:
          "border-transparent bg-secondary text-secondary-foreground",
        destructive:
          "border-transparent bg-destructive text-destructive-foreground shadow-xs",
        outline: "text-foreground border [border-color:var(--badge-outline)]",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

export interface BadgeProps
  extends React.HTMLAttributes<HTMLDivElement>,
    VariantProps<typeof badgeVariants> {}

function Badge({ className, variant, ...props }: BadgeProps) {
  return (
    <div className={cn(badgeVariants({ variant }), className)} {...props} />
  )
}

export { Badge, badgeVariants }
```

FILE: artifacts/mockup-sandbox/src/components/ui/breadcrumb.tsx
SIZE: 2,712 bytes

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { ChevronRight, MoreHorizontal } from "lucide-react"

import { cn } from "@/lib/utils"

const Breadcrumb = React.forwardRef<
  HTMLElement,
  React.ComponentPropsWithoutRef<"nav"> & {
    separator?: React.ReactNode
  }
>(({ ...props }, ref) => <nav ref={ref} aria-label="breadcrumb" {...props} />)
Breadcrumb.displayName = "Breadcrumb"

const BreadcrumbList = React.forwardRef<
  HTMLOListElement,
  React.ComponentPropsWithoutRef<"ol">
>(({ className, ...props }, ref) => (
  <ol
    ref={ref}
    className={cn(
      "flex flex-wrap items-center gap-1.5 break-words text-sm text-muted-foreground sm:gap-2.5",
      className
    )}
    {...props}
  />
))
BreadcrumbList.displayName = "BreadcrumbList"

const BreadcrumbItem = React.forwardRef<
  HTMLLIElement,
  React.ComponentPropsWithoutRef<"li">
>(({ className, ...props }, ref) => (
  <li
    ref={ref}
    className={cn("inline-flex items-center gap-1.5", className)}
    {...props}
  />
))
BreadcrumbItem.displayName = "BreadcrumbItem"

const BreadcrumbLink = React.forwardRef<
  HTMLAnchorElement,
  React.ComponentPropsWithoutRef<"a"> & {
    asChild?: boolean
  }
>(({ asChild, className, ...props }, ref) => {
  const Comp = asChild ? Slot : "a"
```

```
  return (
    <Comp
      ref={ref}
      className={cn("transition-colors hover:text-foreground", className)}
      {...props}
    />
  )
})
BreadcrumbLink.displayName = "BreadcrumbLink"

const BreadcrumbPage = React.forwardRef<
  HTMLSpanElement,
  React.ComponentPropsWithoutRef<"span">
>(({ className, ...props }, ref) => (
  <span
    ref={ref}
    role="link"
    aria-disabled="true"
    aria-current="page"
    className={cn("font-normal text-foreground", className)}
    {...props}
  />
))
BreadcrumbPage.displayName = "BreadcrumbPage"

const BreadcrumbSeparator = ({
  children,
  className,
  ...props
}: React.ComponentProps<"li">) => (
  <li
    role="presentation"
    aria-hidden="true"
    className={cn("[&>svg]:w-3.5 [&>svg]:h-3.5", className)}
    {...props}
  >
    {children ?? <ChevronRight />}
  </li>
)
BreadcrumbSeparator.displayName = "BreadcrumbSeparator"

const BreadcrumbEllipsis = ({
  className,
  ...props
}: React.ComponentProps<"span">) => (
  <span
    role="presentation"
    aria-hidden="true"
    className={cn("flex h-9 w-9 items-center justify-center", className)}
    {...props}
  >
    <MoreHorizontal className="h-4 w-4" />
```

```
    <span className="sr-only">More</span>
  </span>
)
BreadcrumbEllipsis.displayName = "BreadcrumbElipssis"

export {
  Breadcrumb,
  BreadcrumbList,
  BreadcrumbItem,
  BreadcrumbLink,
  BreadcrumbPage,
  BreadcrumbSeparator,
  BreadcrumbEllipsis,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/button-group.tsx
SIZE: 2,209 bytes

```
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Separator } from "@/components/ui/separator"

const buttonGroupVariants = cva(
  "flex w-fit items-stretch has-[>[data-slot=button-group]]:gap-2 [&>*]:focus-visible:relative [&>*]:focus-visib
  le:z-10 has-[select[aria-hidden=true]:last-child]:[&>[data-slot=select-trigger]:last-of-type]:rounded-r-md [&>[d
  ata-slot=select-trigger]:not([class*='w-'])]:w-fit [&>input]:flex-1",
  {
    variants: {
      orientation: {
        horizontal:
          "[&>*:not(:first-child)]:rounded-l-none [&>*:not(:first-child)]:border-l-0 [&>*:not(:last-child)]:roun
  ded-r-none",
        vertical:
          "flex-col [&>*:not(:first-child)]:rounded-t-none [&>*:not(:first-child)]:border-t-0 [&>*:not(:last-chi
  ld)]:rounded-b-none",
      },
    },
    defaultVariants: {
      orientation: "horizontal",
    },
  }
)

function ButtonGroup({
  className,
  orientation,
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof buttonGroupVariants>) {
  return (
    <div
      role="group"
      data-slot="button-group"
      data-orientation={orientation}
      className={cn(buttonGroupVariants({ orientation }), className)}
      {...props}
    />
  )
}

function ButtonGroupText({
  className,
  asChild = false,
  ...props
}: React.ComponentProps<"div"> & {
  asChild?: boolean
```

```
}) {
  const Comp = asChild ? Slot : "div"

  return (
    <Comp
      className={cn(
        "bg-muted shadow-xs flex items-center gap-2 rounded-md border px-4 text-sm font-medium [&_svg:not([class
  *='size-'])]:size-4 [&_svg]:pointer-events-none",
        className
      )}
      {...props}
    />
  )
}

function ButtonGroupSeparator({
  className,
  orientation = "vertical",
  ...props
}: React.ComponentProps<typeof Separator>) {
  return (
    <Separator
      data-slot="button-group-separator"
      orientation={orientation}
      className={cn(
        "bg-input relative !m-0 self-stretch data-[orientation=vertical]:h-auto",
        className
      )}
      {...props}
    />
  )
}

export {
  ButtonGroup,
  ButtonGroupSeparator,
  ButtonGroupText,
  buttonGroupVariants,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/button.tsx
SIZE: 1,925 bytes

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const buttonVariants = cva(
  "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium transition-col
  ors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:pointer-events-none disable
  d:opacity-50 [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0" +
" hover-elevate active-elevate-2",
  {
    variants: {
      variant: {
        default:
          "bg-primary text-primary-foreground border border-primary-border",
        destructive:
          "bg-destructive text-destructive-foreground shadow-sm border-destructive-border",
        outline:
          "border [border-color:var(--button-outline)] shadow-xs active:shadow-none",
        secondary:
          "border bg-secondary text-secondary-foreground border border-secondary-border",
        ghost: "border border-transparent",
        link: "text-primary underline-offset-4 hover:underline",
      },
      size: {
        default: "min-h-9 px-4 py-2",
        sm: "min-h-8 rounded-md px-3 text-xs",
        lg: "min-h-10 rounded-md px-8",
        icon: "h-9 w-9",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
)

export interface ButtonProps
  extends React.ButtonHTMLAttributes<HTMLButtonElement>,
    VariantProps<typeof buttonVariants> {
  asChild?: boolean
}

const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
  ({ className, variant, size, asChild = false, ...props }, ref) => {
    const Comp = asChild ? Slot : "button"
    return (
```

```
      <Comp
        className={cn(buttonVariants({ variant, size, className }))}
        ref={ref}
        {...props}
      />
    )
  }
)
Button.displayName = "Button"

export { Button, buttonVariants }
```

FILE: artifacts/mockup-sandbox/src/components/ui/calendar.tsx
SIZE: 7,569 bytes

```
"use client"

import * as React from "react"
import {
  ChevronDownIcon,
  ChevronLeftIcon,
  ChevronRightIcon,
} from "lucide-react"
import { DayButton, DayPicker, getDefaultClassNames } from "react-day-picker"

import { cn } from "@/lib/utils"
import { Button, buttonVariants } from "@/components/ui/button"

function Calendar({
  className,
  classNames,
  showOutsideDays = true,
  captionLayout = "label",
  buttonVariant = "ghost",
  formatters,
  components,
  ...props
}: React.ComponentProps<typeof DayPicker> & {
  buttonVariant?: React.ComponentProps<typeof Button>["variant"]
}) {
  const defaultClassNames = getDefaultClassNames()

  return (
    <DayPicker
      showOutsideDays={showOutsideDays}
      className={cn(
        "bg-background group/calendar p-3 [--cell-size:2rem] [[data-slot=card-content]_&]:bg-transparent [[data-
slot=popover-content]_&]:bg-transparent",
        String.raw`rtl:**:[.rdp-button\_next>svg]:rotate-180`,
        String.raw`rtl:**:[.rdp-button\_previous>svg]:rotate-180`,
        className
      )}
      captionLayout={captionLayout}
      formatters={{
        formatMonthDropdown: (date) =>
          date.toLocaleString("default", { month: "short" }),
        ...formatters,
      }}
      classNames={{
        root: cn("w-fit", defaultClassNames.root),
        months: cn(
          "relative flex flex-col gap-4 md:flex-row",
          defaultClassNames.months
        ),
```

```
      month: cn("flex w-full flex-col gap-4", defaultClassNames.month),
      nav: cn(
        "absolute inset-x-0 top-0 flex w-full items-center justify-between gap-1",
        defaultClassNames.nav
      ),
      button_previous: cn(
        buttonVariants({ variant: buttonVariant }),
        "h-[--cell-size] w-[--cell-size] select-none p-0 aria-disabled:opacity-50",
        defaultClassNames.button_previous
      ),
      button_next: cn(
        buttonVariants({ variant: buttonVariant }),
        "h-[--cell-size] w-[--cell-size] select-none p-0 aria-disabled:opacity-50",
        defaultClassNames.button_next
      ),
      month_caption: cn(
        "flex h-[--cell-size] w-full items-center justify-center px-[--cell-size]",
        defaultClassNames.month_caption
      ),
      dropdowns: cn(
        "flex h-[--cell-size] w-full items-center justify-center gap-1.5 text-sm font-medium",
        defaultClassNames.dropdowns
      ),
      dropdown_root: cn(
        "has-focus:border-ring border-input shadow-xs has-focus:ring-ring/50 has-focus:ring-[3px] relative rou
nded-md border",
        defaultClassNames.dropdown_root
      ),
      dropdown: cn(
        "bg-popover absolute inset-0 opacity-0",
        defaultClassNames.dropdown
      ),
      caption_label: cn(
        "select-none font-medium",
        captionLayout === "label"
          ? "text-sm"
          : "[&>svg]:text-muted-foreground flex h-8 items-center gap-1 rounded-md pl-2 pr-1 text-sm [&>svg]:si
ze-3.5",
        defaultClassNames.caption_label
      ),
      table: "w-full border-collapse",
      weekdays: cn("flex", defaultClassNames.weekdays),
      weekday: cn(
        "text-muted-foreground flex-1 select-none rounded-md text-[0.8rem] font-normal",
        defaultClassNames.weekday
      ),
      week: cn("mt-2 flex w-full", defaultClassNames.week),
      week_number_header: cn(
        "w-[--cell-size] select-none",
        defaultClassNames.week_number_header
      ),
      week_number: cn(
```

```
        "text-muted-foreground select-none text-[0.8rem]",
        defaultClassNames.week_number
      ),
      day: cn(
        "group/day relative aspect-square h-full w-full select-none p-0 text-center [&:first-child[data-select
ed=true]_button]:rounded-l-md [&:last-child[data-selected=true]_button]:rounded-r-md",
        defaultClassNames.day
      ),
      range_start: cn(
        "bg-accent rounded-l-md",
        defaultClassNames.range_start
      ),
      range_middle: cn("rounded-none", defaultClassNames.range_middle),
      range_end: cn("bg-accent rounded-r-md", defaultClassNames.range_end),
      today: cn(
        "bg-accent text-accent-foreground rounded-md data-[selected=true]:rounded-none",
        defaultClassNames.today
      ),
      outside: cn(
        "text-muted-foreground aria-selected:text-muted-foreground",
        defaultClassNames.outside
      ),
      disabled: cn(
        "text-muted-foreground opacity-50",
        defaultClassNames.disabled
      ),
      hidden: cn("invisible", defaultClassNames.hidden),
      ...classNames,
    }}
    components={{
      Root: ({ className, rootRef, ...props }) => {
        return (
          <div
            data-slot="calendar"
            ref={rootRef}
            className={cn(className)}
            {...props}
          />
        )
      },
      Chevron: ({ className, orientation, ...props }) => {
        if (orientation === "left") {
          return (
            <ChevronLeftIcon className={cn("size-4", className)} {...props} />
          )
        }

        if (orientation === "right") {
          return (
            <ChevronRightIcon
              className={cn("size-4", className)}
              {...props}
```

```
              />
            )
          }

          return (
            <ChevronDownIcon className={cn("size-4", className)} {...props} />
          )
        },
        DayButton: CalendarDayButton,
        WeekNumber: ({ children, ...props }) => {
          return (
            <td {...props}>
              <div className="flex size-[--cell-size] items-center justify-center text-center">
                {children}
              </div>
            </td>
          )
        },
        ...components,
      }}
      {...props}
    />
  )
}

function CalendarDayButton({
  className,
  day,
  modifiers,
  ...props
}: React.ComponentProps<typeof DayButton>) {
  const defaultClassNames = getDefaultClassNames()

  const ref = React.useRef<HTMLButtonElement>(null)
  React.useEffect(() => {
    if (modifiers.focused) ref.current?.focus()
  }, [modifiers.focused])

  return (
    <Button
      ref={ref}
      variant="ghost"
      size="icon"
      data-day={day.date.toLocaleDateString()}
      data-selected-single={
        modifiers.selected &&
        !modifiers.range_start &&
        !modifiers.range_end &&
        !modifiers.range_middle
      }
      data-range-start={modifiers.range_start}
      data-range-end={modifiers.range_end}
```

```
      data-range-middle={modifiers.range_middle}
      className={cn(
        "data-[selected-single=true]:bg-primary data-[selected-single=true]:text-primary-foreground data-[range-
  middle=true]:bg-accent data-[range-middle=true]:text-accent-foreground data-[range-start=true]:bg-primary data-[
  range-start=true]:text-primary-foreground data-[range-end=true]:bg-primary data-[range-end=true]:text-primary-fo
  reground group-data-[focused=true]/day:border-ring group-data-[focused=true]/day:ring-ring/50 flex aspect-square
   h-auto w-full min-w-[--cell-size] flex-col gap-1 font-normal leading-none data-[range-end=true]:rounded-md data
  -[range-middle=true]:rounded-none data-[range-start=true]:rounded-md group-data-[focused=true]/day:relative grou
  p-data-[focused=true]/day:z-10 group-data-[focused=true]/day:ring-[3px] [&>span]:text-xs [&>span]:opacity-70",
        defaultClassNames.day,
        className
      )}
      {...props}
    />
  )
}

export { Calendar, CalendarDayButton }
```

FILE: artifacts/mockup-sandbox/src/components/ui/card.tsx
SIZE: 1,828 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Card = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn(
      "rounded-xl border bg-card text-card-foreground shadow",
      className
    )}
    {...props}
  />
))
Card.displayName = "Card"

const CardHeader = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("flex flex-col space-y-1.5 p-6", className)}
    {...props}
  />
))
CardHeader.displayName = "CardHeader"

const CardTitle = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("font-semibold leading-none tracking-tight", className)}
    {...props}
  />
))
CardTitle.displayName = "CardTitle"

const CardDescription = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
```

```
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
CardDescription.displayName = "CardDescription"

const CardContent = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
))
CardContent.displayName = "CardContent"

const CardFooter = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("flex items-center p-6 pt-0", className)}
    {...props}
  />
))
CardFooter.displayName = "CardFooter"

export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent }
```

FILE: artifacts/mockup-sandbox/src/components/ui/carousel.tsx
SIZE: 6,210 bytes

```
import * as React from "react"
import useEmblaCarousel, {
  type UseEmblaCarouselType,
} from "embla-carousel-react"
import { ArrowLeft, ArrowRight } from "lucide-react"

import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"

type CarouselApi = UseEmblaCarouselType[1]
type UseCarouselParameters = Parameters<typeof useEmblaCarousel>
type CarouselOptions = UseCarouselParameters[0]
type CarouselPlugin = UseCarouselParameters[1]

type CarouselProps = {
  opts?: CarouselOptions
  plugins?: CarouselPlugin
  orientation?: "horizontal" | "vertical"
  setApi?: (api: CarouselApi) => void
}

type CarouselContextProps = {
  carouselRef: ReturnType<typeof useEmblaCarousel>[0]
  api: ReturnType<typeof useEmblaCarousel>[1]
  scrollPrev: () => void
  scrollNext: () => void
  canScrollPrev: boolean
  canScrollNext: boolean
} & CarouselProps

const CarouselContext = React.createContext<CarouselContextProps | null>(null)

function useCarousel() {
  const context = React.useContext(CarouselContext)

  if (!context) {
    throw new Error("useCarousel must be used within a <Carousel />")
  }

  return context
}

const Carousel = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement> & CarouselProps
>(
  (
    {
      orientation = "horizontal",
```

```
      opts,
      setApi,
      plugins,
      className,
      children,
      ...props
    },
    ref
  ) => {
    const [carouselRef, api] = useEmblaCarousel(
      {
        ...opts,
        axis: orientation === "horizontal" ? "x" : "y",
      },
      plugins
    )
    const [canScrollPrev, setCanScrollPrev] = React.useState(false)
    const [canScrollNext, setCanScrollNext] = React.useState(false)

    const onSelect = React.useCallback((api: CarouselApi) => {
      if (!api) {
        return
      }

      setCanScrollPrev(api.canScrollPrev())
      setCanScrollNext(api.canScrollNext())
    }, [])

    const scrollPrev = React.useCallback(() => {
      api?.scrollPrev()
    }, [api])

    const scrollNext = React.useCallback(() => {
      api?.scrollNext()
    }, [api])

    const handleKeyDown = React.useCallback(
      (event: React.KeyboardEvent<HTMLDivElement>) => {
        if (event.key === "ArrowLeft") {
          event.preventDefault()
          scrollPrev()
        } else if (event.key === "ArrowRight") {
          event.preventDefault()
          scrollNext()
        }
      },
      [scrollPrev, scrollNext]
    )

    React.useEffect(() => {
      if (!api || !setApi) {
        return
```

```
      }

      setApi(api)
    }, [api, setApi])

    React.useEffect(() => {
      if (!api) {
        return
      }

      onSelect(api)
      api.on("reInit", onSelect)
      api.on("select", onSelect)

      return () => {
        api?.off("select", onSelect)
      }
    }, [api, onSelect])

    return (
      <CarouselContext.Provider
        value={{
          carouselRef,
          api: api,
          opts,
          orientation:
            orientation || (opts?.axis === "y" ? "vertical" : "horizontal"),
          scrollPrev,
          scrollNext,
          canScrollPrev,
          canScrollNext,
        }}
      >
        <div
          ref={ref}
          onKeyDownCapture={handleKeyDown}
          className={cn("relative", className)}
          role="region"
          aria-roledescription="carousel"
          {...props}
        >
          {children}
        </div>
      </CarouselContext.Provider>
    )
  }
)
Carousel.displayName = "Carousel"

const CarouselContent = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
```

```
>(({ className, ...props }, ref) => {
  const { carouselRef, orientation } = useCarousel()

  return (
    <div ref={carouselRef} className="overflow-hidden">
      <div
        ref={ref}
        className={cn(
          "flex",
          orientation === "horizontal" ? "-ml-4" : "-mt-4 flex-col",
          className
        )}
        {...props}
      />
    </div>
  )
})
CarouselContent.displayName = "CarouselContent"

const CarouselItem = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => {
  const { orientation } = useCarousel()

  return (
    <div
      ref={ref}
      role="group"
      aria-roledescription="slide"
      className={cn(
        "min-w-0 shrink-0 grow-0 basis-full",
        orientation === "horizontal" ? "pl-4" : "pt-4",
        className
      )}
      {...props}
    />
  )
})
CarouselItem.displayName = "CarouselItem"

const CarouselPrevious = React.forwardRef<
  HTMLButtonElement,
  React.ComponentProps<typeof Button>
>(({ className, variant = "outline", size = "icon", ...props }, ref) => {
  const { orientation, scrollPrev, canScrollPrev } = useCarousel()

  return (
    <Button
      ref={ref}
      variant={variant}
      size={size}
```

```
      className={cn(
        "absolute  h-8 w-8 rounded-full",
        orientation === "horizontal"
          ? "-left-12 top-1/2 -translate-y-1/2"
          : "-top-12 left-1/2 -translate-x-1/2 rotate-90",
        className
      )}
      disabled={!canScrollPrev}
      onClick={scrollPrev}
      {...props}
    >
      <ArrowLeft className="h-4 w-4" />
      <span className="sr-only">Previous slide</span>
    </Button>
  )
})
CarouselPrevious.displayName = "CarouselPrevious"

const CarouselNext = React.forwardRef<
  HTMLButtonElement,
  React.ComponentProps<typeof Button>
>(({ className, variant = "outline", size = "icon", ...props }, ref) => {
  const { orientation, scrollNext, canScrollNext } = useCarousel()

  return (
    <Button
      ref={ref}
      variant={variant}
      size={size}
      className={cn(
        "absolute h-8 w-8 rounded-full",
        orientation === "horizontal"
          ? "-right-12 top-1/2 -translate-y-1/2"
          : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90",
        className
      )}
      disabled={!canScrollNext}
      onClick={scrollNext}
      {...props}
    >
      <ArrowRight className="h-4 w-4" />
      <span className="sr-only">Next slide</span>
    </Button>
  )
})
CarouselNext.displayName = "CarouselNext"

export {
  type CarouselApi,
  Carousel,
  CarouselContent,
  CarouselItem,
```

```
  CarouselPrevious,
  CarouselNext,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/chart.tsx
SIZE: 10,674 bytes

```
import * as React from "react"
import * as RechartsPrimitive from "recharts"

import { cn } from "@/lib/utils"

const THEMES = { light: "", dark: ".dark" } as const

export type ChartConfig = {
  [k in string]: {
    label?: React.ReactNode
    icon?: React.ComponentType
  } & (
    | { color?: string; theme?: never }
    | { color?: never; theme: Record<keyof typeof THEMES, string> }
  )
}

type ChartContextProps = {
  config: ChartConfig
}

const ChartContext = React.createContext<ChartContextProps | null>(null)

function useChart() {
  const context = React.useContext(ChartContext)

  if (!context) {
    throw new Error("useChart must be used within a <ChartContainer />")
  }

  return context
}

const ChartContainer = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<"div"> & {
    config: ChartConfig
    children: React.ComponentProps<
      typeof RechartsPrimitive.ResponsiveContainer
    >["children"]
  }
>(({ id, className, children, config, ...props }, ref) => {
  const uniqueId = React.useId()
  const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`

  return (
    <ChartContext.Provider value={{ config }}>
      <div
        data-chart={chartId}
```

```
        ref={ref}
        className={cn(
          "flex aspect-video justify-center text-xs [&_.recharts-cartesian-axis-tick_text]:fill-muted-foreground
   [&_.recharts-cartesian-grid_line[stroke='#ccc']]:stroke-border/50 [&_.recharts-curve.recharts-tooltip-cursor]:s
  troke-border [&_.recharts-dot[stroke='#fff']]:stroke-transparent [&_.recharts-layer]:outline-none [&_.recharts-p
  olar-grid_[stroke='#ccc']]:stroke-border [&_.recharts-radial-bar-background-sector]:fill-muted [&_.recharts-rect
  angle.recharts-tooltip-cursor]:fill-muted [&_.recharts-reference-line_[stroke='#ccc']]:stroke-border [&_.rechart
  s-sector[stroke='#fff']]:stroke-transparent [&_.recharts-sector]:outline-none [&_.recharts-surface]:outline-none
  ",
          className
        )}
        {...props}
      >
        <ChartStyle id={chartId} config={config} />
        <RechartsPrimitive.ResponsiveContainer>
          {children}
        </RechartsPrimitive.ResponsiveContainer>
      </div>
    </ChartContext.Provider>
  )
})
ChartContainer.displayName = "Chart"

const ChartStyle = ({ id, config }: { id: string; config: ChartConfig }) => {
  const colorConfig = Object.entries(config).filter(
    ([, config]) => config.theme || config.color
  )

  if (!colorConfig.length) {
    return null
  }

  return (
    <style
      dangerouslySetInnerHTML={{
        __html: Object.entries(THEMES)
          .map(
            ([theme, prefix]) => `
${prefix} [data-chart=${id}] {
${colorConfig
  .map(([key, itemConfig]) => {
    const color =
      itemConfig.theme?.[theme as keyof typeof itemConfig.theme] ||
      itemConfig.color
    return color ? `  --color-${key}: ${color};` : null
  })
  .join("\n")}
}
`
          )
          .join("\n"),
      }}
```

```
    />
  )
}

const ChartTooltip = RechartsPrimitive.Tooltip

const ChartTooltipContent = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<typeof RechartsPrimitive.Tooltip> &
    React.ComponentProps<"div"> & {
      hideLabel?: boolean
      hideIndicator?: boolean
      indicator?: "line" | "dot" | "dashed"
      nameKey?: string
      labelKey?: string
    }
>(
  (
    {
      active,
      payload,
      className,
      indicator = "dot",
      hideLabel = false,
      hideIndicator = false,
      label,
      labelFormatter,
      labelClassName,
      formatter,
      color,
      nameKey,
      labelKey,
    },
    ref
  ) => {
    const { config } = useChart()

    const tooltipLabel = React.useMemo(() => {
      if (hideLabel || !payload?.length) {
        return null
      }

      const [item] = payload
      const key = `${labelKey || item?.dataKey || item?.name || "value"}`
      const itemConfig = getPayloadConfigFromPayload(config, item, key)
      const value =
        !labelKey && typeof label === "string"
          ? config[label as keyof typeof config]?.label || label
          : itemConfig?.label

      if (labelFormatter) {
        return (
```

```
        <div className={cn("font-medium", labelClassName)}>
          {labelFormatter(value, payload)}
        </div>
      )
    }

    if (!value) {
      return null
    }

    return <div className={cn("font-medium", labelClassName)}>{value}</div>
  }, [
    label,
    labelFormatter,
    payload,
    hideLabel,
    labelClassName,
    config,
    labelKey,
  ])

  if (!active || !payload?.length) {
    return null
  }

  const nestLabel = payload.length === 1 && indicator !== "dot"

  return (
    <div
      ref={ref}
      className={cn(
        "grid min-w-[8rem] items-start gap-1.5 rounded-lg border border-border/50 bg-background px-2.5 py-1.5
text-xs shadow-xl",
        className
      )}
    >
      {!nestLabel ? tooltipLabel : null}
      <div className="grid gap-1.5">
        {payload
          .filter((item) => item.type !== "none")
          .map((item, index) => {
            const key = `${nameKey || item.name || item.dataKey || "value"}`
            const itemConfig = getPayloadConfigFromPayload(config, item, key)
            const indicatorColor = color || item.payload.fill || item.color

            return (
              <div
                key={item.dataKey}
                className={cn(
                  "flex w-full flex-wrap items-stretch gap-2 [&>svg]:h-2.5 [&>svg]:w-2.5 [&>svg]:text-muted-fo
reground",
                  indicator === "dot" && "items-center"
```

```
      )}
    >
      {formatter && item?.value !== undefined && item.name ? (
        formatter(item.value, item.name, item, index, item.payload)
      ) : (
        <>
          {itemConfig?.icon ? (
            <itemConfig.icon />
          ) : (
            !hideIndicator && (
              <div
                className={cn(
                  "shrink-0 rounded-[2px] border-[--color-border] bg-[--color-bg]",
                  {
                    "h-2.5 w-2.5": indicator === "dot",
                    "w-1": indicator === "line",
                    "w-0 border-[1.5px] border-dashed bg-transparent":
                      indicator === "dashed",
                    "my-0.5": nestLabel && indicator === "dashed",
                  }
                )}
                style={
                  {
                    "--color-bg": indicatorColor,
                    "--color-border": indicatorColor,
                  } as React.CSSProperties
                }
              />
            )
          )}
          <div
            className={cn(
              "flex flex-1 justify-between leading-none",
              nestLabel ? "items-end" : "items-center"
            )}
          >
            <div className="grid gap-1.5">
              {nestLabel ? tooltipLabel : null}
              <span className="text-muted-foreground">
                {itemConfig?.label || item.name}
              </span>
            </div>
            {item.value && (
              <span className="font-mono font-medium tabular-nums text-foreground">
                {item.value.toLocaleString()}
              </span>
            )}
          </div>
        </>
      )}
    </div>
  )
```

```
            })}
          </div>
        </div>
      )
    }
)
ChartTooltipContent.displayName = "ChartTooltip"

const ChartLegend = RechartsPrimitive.Legend

const ChartLegendContent = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<"div"> &
    Pick<RechartsPrimitive.LegendProps, "payload" | "verticalAlign"> & {
      hideIcon?: boolean
      nameKey?: string
    }
>(
  (
    { className, hideIcon = false, payload, verticalAlign = "bottom", nameKey },
    ref
  ) => {
    const { config } = useChart()

    if (!payload?.length) {
      return null
    }

    return (
      <div
        ref={ref}
        className={cn(
          "flex items-center justify-center gap-4",
          verticalAlign === "top" ? "pb-3" : "pt-3",
          className
        )}
      >
        {payload
          .filter((item) => item.type !== "none")
          .map((item) => {
            const key = `${nameKey || item.dataKey || "value"}`
            const itemConfig = getPayloadConfigFromPayload(config, item, key)

            return (
              <div
                key={item.value}
                className={cn(
                  "flex items-center gap-1.5 [&>svg]:h-3 [&>svg]:w-3 [&>svg]:text-muted-foreground"
                )}
              >
                {itemConfig?.icon && !hideIcon ? (
                  <itemConfig.icon />
```

```
                ) : (
                  <div
                    className="h-2 w-2 shrink-0 rounded-[2px]"
                    style={{
                      backgroundColor: item.color,
                    }}
                  />
                )}
                {itemConfig?.label}
              </div>
            )
          })}
      </div>
    )
  }
)
ChartLegendContent.displayName = "ChartLegend"

function getPayloadConfigFromPayload(
  config: ChartConfig,
  payload: unknown,
  key: string
) {
  if (typeof payload !== "object" || payload === null) {
    return undefined
  }

  const payloadPayload =
    "payload" in payload &&
    typeof payload.payload === "object" &&
    payload.payload !== null
      ? payload.payload
      : undefined

  let configLabelKey: string = key

  if (
    key in payload &&
    typeof payload[key as keyof typeof payload] === "string"
  ) {
    configLabelKey = payload[key as keyof typeof payload] as string
  } else if (
    payloadPayload &&
    key in payloadPayload &&
    typeof payloadPayload[key as keyof typeof payloadPayload] === "string"
  ) {
    configLabelKey = payloadPayload[
      key as keyof typeof payloadPayload
    ] as string
  }

  return configLabelKey in config
```

```
    ? config[configLabelKey]
    : config[key as keyof typeof config]
}

export {
  ChartContainer,
  ChartTooltip,
  ChartTooltipContent,
  ChartLegend,
  ChartLegendContent,
  ChartStyle,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/checkbox.tsx
SIZE: 1,031 bytes

```
import * as React from "react"
import * as CheckboxPrimitive from "@radix-ui/react-checkbox"
import { Check } from "lucide-react"

import { cn } from "@/lib/utils"

const Checkbox = React.forwardRef<
  React.ElementRef<typeof CheckboxPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof CheckboxPrimitive.Root>
>(({ className, ...props }, ref) => (
  <CheckboxPrimitive.Root
    ref={ref}
    className={cn(
      "grid place-content-center peer h-4 w-4 shrink-0 rounded-sm border border-primary shadow focus-visible:out
  line-none focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50 data-[sta
  te=checked]:bg-primary data-[state=checked]:text-primary-foreground",
      className
    )}
    {...props}
  >
    <CheckboxPrimitive.Indicator
      className={cn("grid place-content-center text-current")}
    >
      <Check className="h-4 w-4" />
    </CheckboxPrimitive.Indicator>
  </CheckboxPrimitive.Root>
))
Checkbox.displayName = CheckboxPrimitive.Root.displayName

export { Checkbox }
```

FILE: artifacts/mockup-sandbox/src/components/ui/collapsible.tsx
SIZE: 329 bytes

```
"use client"

import * as CollapsiblePrimitive from "@radix-ui/react-collapsible"

const Collapsible = CollapsiblePrimitive.Root

const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger

const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent

export { Collapsible, CollapsibleTrigger, CollapsibleContent }
```

FILE: artifacts/mockup-sandbox/src/components/ui/command.tsx
SIZE: 4,887 bytes

```
"use client"

import * as React from "react"
import { type DialogProps } from "@radix-ui/react-dialog"
import { Command as CommandPrimitive } from "cmdk"
import { Search } from "lucide-react"

import { cn } from "@/lib/utils"
import { Dialog, DialogContent } from "@/components/ui/dialog"

const Command = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive>
>(({ className, ...props }, ref) => (
  <CommandPrimitive
    ref={ref}
    className={cn(
      "flex h-full w-full flex-col overflow-hidden rounded-md bg-popover text-popover-foreground",
      className
    )}
    {...props}
  />
))
Command.displayName = CommandPrimitive.displayName

const CommandDialog = ({ children, ...props }: DialogProps) => {
  return (
    <Dialog {...props}>
      <DialogContent className="overflow-hidden p-0">
        <Command className="[&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-he
  ading]]:text-muted-foreground [&_[cmdk-group]:not([hidden])_~[cmdk-group]]:pt-0 [&_[cmdk-group]]:px-2 [&_[cmdk-i
  nput-wrapper]_svg]:h-5 [&_[cmdk-input-wrapper]_svg]:w-5 [&_[cmdk-input]]:h-12 [&_[cmdk-item]]:px-2 [&_[cmdk-item
  ]]:py-3 [&_[cmdk-item]_svg]:h-5 [&_[cmdk-item]_svg]:w-5">
          {children}
        </Command>
      </DialogContent>
    </Dialog>
  )
}

const CommandInput = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Input>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Input>
>(({ className, ...props }, ref) => (
  <div className="flex items-center border-b px-3" cmdk-input-wrapper="">
    <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
    <CommandPrimitive.Input
      ref={ref}
      className={cn(
```

```
        "flex h-10 w-full rounded-md bg-transparent py-3 text-sm outline-none placeholder:text-muted-foreground
  disabled:cursor-not-allowed disabled:opacity-50",
        className
      )}
      {...props}
    />
  </div>
))

CommandInput.displayName = CommandPrimitive.Input.displayName

const CommandList = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.List>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.List
    ref={ref}
    className={cn("max-h-[300px] overflow-y-auto overflow-x-hidden", className)}
    {...props}
  />
))

CommandList.displayName = CommandPrimitive.List.displayName

const CommandEmpty = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Empty>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Empty>
>((props, ref) => (
  <CommandPrimitive.Empty
    ref={ref}
    className="py-6 text-center text-sm"
    {...props}
  />
))

CommandEmpty.displayName = CommandPrimitive.Empty.displayName

const CommandGroup = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Group>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Group>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Group
    ref={ref}
    className={cn(
      "overflow-hidden p-1 text-foreground [&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:py-1.5 [&_[cmd
  k-group-heading]]:text-xs [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-heading]]:text-muted-foreground",
      className
    )}
    {...props}
  />
))
```

```
CommandGroup.displayName = CommandPrimitive.Group.displayName

const CommandSeparator = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 h-px bg-border", className)}
    {...props}
  />
))
CommandSeparator.displayName = CommandPrimitive.Separator.displayName

const CommandItem = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Item>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default gap-2 select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none d
  ata-[disabled=true]:pointer-events-none data-[selected=true]:bg-accent data-[selected=true]:text-accent-foregrou
  nd data-[disabled=true]:opacity-50 [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
      className
    )}
    {...props}
  />
))

CommandItem.displayName = CommandPrimitive.Item.displayName

const CommandShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
CommandShortcut.displayName = "CommandShortcut"

export {
  Command,
  CommandDialog,
  CommandInput,
```

```
  CommandList,
  CommandEmpty,
  CommandGroup,
  CommandItem,
  CommandShortcut,
  CommandSeparator,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/context-menu.tsx
SIZE: 7,406 bytes

```
import * as React from "react"
import * as ContextMenuPrimitive from "@radix-ui/react-context-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const ContextMenu = ContextMenuPrimitive.Root

const ContextMenuTrigger = ContextMenuPrimitive.Trigger

const ContextMenuGroup = ContextMenuPrimitive.Group

const ContextMenuPortal = ContextMenuPrimitive.Portal

const ContextMenuSub = ContextMenuPrimitive.Sub

const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup

const ContextMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <ContextMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
  focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-accent-foreground",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </ContextMenuPrimitive.SubTrigger>
))
ContextMenuSubTrigger.displayName = ContextMenuPrimitive.SubTrigger.displayName

const ContextMenuSubContent = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data
  -[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-i
```

```
  n-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[si
  de=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 ori
  gin-[--radix-context-menu-content-transform-origin]",
      className
    )}
    {...props}
  />
))
ContextMenuSubContent.displayName = ContextMenuPrimitive.SubContent.displayName

const ContextMenuContent = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Content>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.Portal>
    <ContextMenuPrimitive.Content
      ref={ref}
      className={cn(
        "z-50 max-h-[--radix-context-menu-content-available-height] min-w-[8rem] overflow-y-auto overflow-x-hidd
  en rounded-md border bg-popover p-1 text-popover-foreground shadow-md data-[state=open]:animate-in data-[state=c
  losed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 da
  ta-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[s
  ide=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-context-menu-content-tran
  sform-origin]",
        className
      )}
      {...props}
    />
  </ContextMenuPrimitive.Portal>
))
ContextMenuContent.displayName = ContextMenuPrimitive.Content.displayName

const ContextMenuItem = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <ContextMenuPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:b
  g-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
ContextMenuItem.displayName = ContextMenuPrimitive.Item.displayName

const ContextMenuCheckboxItem = React.forwardRef<
```

```
  React.ElementRef<typeof ContextMenuPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <ContextMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <ContextMenuPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </ContextMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </ContextMenuPrimitive.CheckboxItem>
))
ContextMenuCheckboxItem.displayName =
  ContextMenuPrimitive.CheckboxItem.displayName

const ContextMenuRadioItem = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <ContextMenuPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <ContextMenuPrimitive.ItemIndicator>
        <Circle className="h-4 w-4 fill-current" />
      </ContextMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </ContextMenuPrimitive.RadioItem>
))
ContextMenuRadioItem.displayName = ContextMenuPrimitive.RadioItem.displayName

const ContextMenuLabel = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Label> & {
    inset?: boolean
  }
```

```
>(({ className, inset, ...props }, ref) => (
  <ContextMenuPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold text-foreground",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
ContextMenuLabel.displayName = ContextMenuPrimitive.Label.displayName

const ContextMenuSeparator = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-border", className)}
    {...props}
  />
))
ContextMenuSeparator.displayName = ContextMenuPrimitive.Separator.displayName

const ContextMenuShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
ContextMenuShortcut.displayName = "ContextMenuShortcut"

export {
  ContextMenu,
  ContextMenuTrigger,
  ContextMenuContent,
  ContextMenuItem,
  ContextMenuCheckboxItem,
  ContextMenuRadioItem,
  ContextMenuLabel,
  ContextMenuSeparator,
  ContextMenuShortcut,
  ContextMenuGroup,
```

```
  ContextMenuPortal,
  ContextMenuSub,
  ContextMenuSubContent,
  ContextMenuSubTrigger,
  ContextMenuRadioGroup,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/dialog.tsx
SIZE: 3,835 bytes

```
import * as React from "react"
import * as DialogPrimitive from "@radix-ui/react-dialog"
import { X } from "lucide-react"

import { cn } from "@/lib/utils"

const Dialog = DialogPrimitive.Root

const DialogTrigger = DialogPrimitive.Trigger

const DialogPortal = DialogPrimitive.Portal

const DialogClose = DialogPrimitive.Close

const DialogOverlay = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Overlay
    ref={ref}
    className={cn(
      "fixed inset-0 z-50 bg-black/80  data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=
  closed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
  />
))
DialogOverlay.displayName = DialogPrimitive.Overlay.displayName

const DialogContent = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DialogPortal>
    <DialogOverlay />
    <DialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
   bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-[state=closed]:animate-out data-[sta
  te=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 d
  ata-[state=closed]:slide-out-to-left-1/2 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-f
  rom-left-1/2 data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
        className
      )}
      {...props}
    >
      {children}
```

```
      <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background tran
  sition-opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:po
  inter-events-none data-[state=open]:bg-accent data-[state=open]:text-muted-foreground">
        <X className="h-4 w-4" />
        <span className="sr-only">Close</span>
      </DialogPrimitive.Close>
    </DialogPrimitive.Content>
  </DialogPortal>
))
DialogContent.displayName = DialogPrimitive.Content.displayName

const DialogHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-1.5 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
DialogHeader.displayName = "DialogHeader"

const DialogFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
DialogFooter.displayName = "DialogFooter"

const DialogTitle = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Title
    ref={ref}
    className={cn(
      "text-lg font-semibold leading-none tracking-tight",
      className
    )}
    {...props}
  />
))
```

```
DialogTitle.displayName = DialogPrimitive.Title.displayName

const DialogDescription = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
DialogDescription.displayName = DialogPrimitive.Description.displayName

export {
  Dialog,
  DialogPortal,
  DialogOverlay,
  DialogTrigger,
  DialogClose,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/drawer.tsx
SIZE: 3,007 bytes

```
import * as React from "react"
import { Drawer as DrawerPrimitive } from "vaul"

import { cn } from "@/lib/utils"

const Drawer = ({
  shouldScaleBackground = true,
  ...props
}: React.ComponentProps<typeof DrawerPrimitive.Root>) => (
  <DrawerPrimitive.Root
    shouldScaleBackground={shouldScaleBackground}
    {...props}
  />
)
Drawer.displayName = "Drawer"

const DrawerTrigger = DrawerPrimitive.Trigger

const DrawerPortal = DrawerPrimitive.Portal

const DrawerClose = DrawerPrimitive.Close

const DrawerOverlay = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Overlay
    ref={ref}
    className={cn("fixed inset-0 z-50 bg-black/80", className)}
    {...props}
  />
))
DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName

const DrawerContent = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DrawerPortal>
    <DrawerOverlay />
    <DrawerPrimitive.Content
      ref={ref}
      className={cn(
        "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-background",
        className
      )}
      {...props}
    >
      <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />
```

```
      {children}
    </DrawerPrimitive.Content>
  </DrawerPortal>
))
DrawerContent.displayName = "DrawerContent"

const DrawerHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)}
    {...props}
  />
)
DrawerHeader.displayName = "DrawerHeader"

const DrawerFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn("mt-auto flex flex-col gap-2 p-4", className)}
    {...props}
  />
)
DrawerFooter.displayName = "DrawerFooter"

const DrawerTitle = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Title
    ref={ref}
    className={cn(
      "text-lg font-semibold leading-none tracking-tight",
      className
    )}
    {...props}
  />
))
DrawerTitle.displayName = DrawerPrimitive.Title.displayName

const DrawerDescription = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
```

```
))
DrawerDescription.displayName = DrawerPrimitive.Description.displayName

export {
  Drawer,
  DrawerPortal,
  DrawerOverlay,
  DrawerTrigger,
  DrawerClose,
  DrawerContent,
  DrawerHeader,
  DrawerFooter,
  DrawerTitle,
  DrawerDescription,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/dropdown-menu.tsx
SIZE: 7,606 bytes

```
"use client"

import * as React from "react"
import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const DropdownMenu = DropdownMenuPrimitive.Root

const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger

const DropdownMenuGroup = DropdownMenuPrimitive.Group

const DropdownMenuPortal = DropdownMenuPrimitive.Portal

const DropdownMenuSub = DropdownMenuPrimitive.Sub

const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup

const DropdownMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <DropdownMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-a
  ccent data-[state=open]:bg-accent [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto" />
  </DropdownMenuPrimitive.SubTrigger>
))
DropdownMenuSubTrigger.displayName =
  DropdownMenuPrimitive.SubTrigger.displayName

const DropdownMenuSubContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.SubContent
    ref={ref}
```

```
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data
  -[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-i
  n-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[si
  de=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 ori
  gin-[--radix-dropdown-menu-content-transform-origin]",
      className
    )}
    {...props}
  />
))
DropdownMenuSubContent.displayName =
  DropdownMenuPrimitive.SubContent.displayName

const DropdownMenuContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Content>
>(({ className, sideOffset = 4, ...props }, ref) => (
  <DropdownMenuPrimitive.Portal>
    <DropdownMenuPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 max-h-[var(--radix-dropdown-menu-content-available-height)] min-w-[8rem] overflow-y-auto overflow-
  x-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md",
        "data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state
  =open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-t
  op-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from
  -bottom-2 origin-[--radix-dropdown-menu-content-transform-origin]",
        className
      )}
      {...props}
    />
  </DropdownMenuPrimitive.Portal>
))
DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName

const DropdownMenuItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <DropdownMenuPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm outline-none t
  ransition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled
  ]:opacity-50 [&>svg]:size-4 [&>svg]:shrink-0",
      inset && "pl-8",
      className
    )}
```

```
    {...props}
  />
))
DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName

const DropdownMenuCheckboxItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <DropdownMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none tr
  ansition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]
  :opacity-50",
      className
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.CheckboxItem>
))
DropdownMenuCheckboxItem.displayName =
  DropdownMenuPrimitive.CheckboxItem.displayName

const DropdownMenuRadioItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <DropdownMenuPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none tr
  ansition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]
  :opacity-50",
      className
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Circle className="h-2 w-2 fill-current" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.RadioItem>
```

```
))
DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName

const DropdownMenuLabel = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Label> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <DropdownMenuPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName

const DropdownMenuSeparator = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-muted", className)}
    {...props}
  />
))
DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName

const DropdownMenuShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn("ml-auto text-xs tracking-widest opacity-60", className)}
      {...props}
    />
  )
}
DropdownMenuShortcut.displayName = "DropdownMenuShortcut"

export {
  DropdownMenu,
  DropdownMenuTrigger,
  DropdownMenuContent,
  DropdownMenuItem,
  DropdownMenuCheckboxItem,
```

```
  DropdownMenuRadioItem,
  DropdownMenuLabel,
  DropdownMenuSeparator,
  DropdownMenuShortcut,
  DropdownMenuGroup,
  DropdownMenuPortal,
  DropdownMenuSub,
  DropdownMenuSubContent,
  DropdownMenuSubTrigger,
  DropdownMenuRadioGroup,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/empty.tsx
SIZE: 2,396 bytes

```
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

function Empty({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty"
      className={cn(
        "flex min-w-0 flex-1 flex-col items-center justify-center gap-6 text-balance rounded-lg border-dashed p-
  6 text-center md:p-12",
        className
      )}
      {...props}
    />
  )
}

function EmptyHeader({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty-header"
      className={cn(
        "flex max-w-sm flex-col items-center gap-2 text-center",
        className
      )}
      {...props}
    />
  )
}

const emptyMediaVariants = cva(
  "mb-2 flex shrink-0 items-center justify-center [&_svg]:pointer-events-none [&_svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        icon: "bg-muted text-foreground flex size-10 shrink-0 items-center justify-center rounded-lg [&_svg:not(
  [class*='size-'])]:size-6",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

function EmptyMedia({
  className,
```

```
  variant = "default",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof emptyMediaVariants>) {
  return (
    <div
      data-slot="empty-icon"
      data-variant={variant}
      className={cn(emptyMediaVariants({ variant, className }))}
      {...props}
    />
  )
}

function EmptyTitle({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty-title"
      className={cn("text-lg font-medium tracking-tight", className)}
      {...props}
    />
  )
}

function EmptyDescription({ className, ...props }: React.ComponentProps<"p">) {
  return (
    <div
      data-slot="empty-description"
      className={cn(
        "text-muted-foreground [&>a:hover]:text-primary text-sm/relaxed [&>a]:underline [&>a]:underline-offset-4
  ",
        className
      )}
      {...props}
    />
  )
}

function EmptyContent({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty-content"
      className={cn(
        "flex w-full min-w-0 max-w-sm flex-col items-center gap-4 text-balance text-sm",
        className
      )}
      {...props}
    />
  )
}

export {
  Empty,
```

```
  EmptyHeader,
  EmptyTitle,
  EmptyDescription,
  EmptyContent,
  EmptyMedia,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/field.tsx
SIZE: 6,044 bytes

```
"use client"

import { useMemo } from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Label } from "@/components/ui/label"
import { Separator } from "@/components/ui/separator"

function FieldSet({ className, ...props }: React.ComponentProps<"fieldset">) {
  return (
    <fieldset
      data-slot="field-set"
      className={cn(
        "flex flex-col gap-6",
        "has-[>[data-slot=checkbox-group]]:gap-3 has-[>[data-slot=radio-group]]:gap-3",
        className
      )}
      {...props}
    />
  )
}

function FieldLegend({
  className,
  variant = "legend",
  ...props
}: React.ComponentProps<"legend"> & { variant?: "legend" | "label" }) {
  return (
    <legend
      data-slot="field-legend"
      data-variant={variant}
      className={cn(
        "mb-3 font-medium",
        "data-[variant=legend]:text-base",
        "data-[variant=label]:text-sm",
        className
      )}
      {...props}
    />
  )
}

function FieldGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="field-group"
      className={cn(
        "group/field-group @container/field-group flex w-full flex-col gap-7 data-[slot=checkbox-group]:gap-3 [&
```

```
  >[data-slot=field-group]]:gap-4",
        className
      )}
      {...props}
    />
  )
}

const fieldVariants = cva(
  "group/field data-[invalid=true]:text-destructive flex w-full gap-3",
  {
    variants: {
      orientation: {
        vertical: ["flex-col [&>*]:w-full [&>.sr-only]:w-auto"],
        horizontal: [
          "flex-row items-center",
          "[&>[data-slot=field-label]]:flex-auto",
          "has-[>[data-slot=field-content]]:[&>[role=checkbox],[role=radio]]:mt-px has-[>[data-slot=field-conten
  t]]:items-start",
        ],
        responsive: [
          "@md/field-group:flex-row @md/field-group:items-center @md/field-group:[&>*]:w-auto flex-col [&>*]:w-f
  ull [&>.sr-only]:w-auto",
          "@md/field-group:[&>[data-slot=field-label]]:flex-auto",
          "@md/field-group:has-[>[data-slot=field-content]]:items-start @md/field-group:has-[>[data-slot=field-c
  ontent]]:[&>[role=checkbox],[role=radio]]:mt-px",
        ],
      },
    },
    defaultVariants: {
      orientation: "vertical",
    },
  }
)

function Field({
  className,
  orientation = "vertical",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof fieldVariants>) {
  return (
    <div
      role="group"
      data-slot="field"
      data-orientation={orientation}
      className={cn(fieldVariants({ orientation }), className)}
      {...props}
    />
  )
}

function FieldContent({ className, ...props }: React.ComponentProps<"div">) {
```

```
  return (
    <div
      data-slot="field-content"
      className={cn(
        "group/field-content flex flex-1 flex-col gap-1.5 leading-snug",
        className
      )}
      {...props}
    />
  )
}

function FieldLabel({
  className,
  ...props
}: React.ComponentProps<typeof Label>) {
  return (
    <Label
      data-slot="field-label"
      className={cn(
        "group/field-label peer/field-label flex w-fit gap-2 leading-snug group-data-[disabled=true]/field:opaci
  ty-50",
        "has-[>[data-slot=field]]:w-full has-[>[data-slot=field]]:flex-col has-[>[data-slot=field]]:rounded-md h
  as-[>[data-slot=field]]:border [&>[data-slot=field]]:p-4",
        "has-data-[state=checked]:bg-primary/5 has-data-[state=checked]:border-primary dark:has-data-[state=chec
  ked]:bg-primary/10",
        className
      )}
      {...props}
    />
  )
}

function FieldTitle({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="field-label"
      className={cn(
        "flex w-fit items-center gap-2 text-sm font-medium leading-snug group-data-[disabled=true]/field:opacity
  -50",
        className
      )}
      {...props}
    />
  )
}

function FieldDescription({ className, ...props }: React.ComponentProps<"p">) {
  return (
    <p
      data-slot="field-description"
      className={cn(
```

```
        "text-muted-foreground text-sm font-normal leading-normal group-has-[[data-orientation=horizontal]]/fiel
  d:text-balance",
        "nth-last-2:-mt-1 last:mt-0 [[data-variant=legend]+&]:-mt-1.5",
        "[&>a:hover]:text-primary [&>a]:underline [&>a]:underline-offset-4",
        className
      )}
      {...props}
    />
  )
}

function FieldSeparator({
  children,
  className,
  ...props
}: React.ComponentProps<"div"> & {
  children?: React.ReactNode
}) {
  return (
    <div
      data-slot="field-separator"
      data-content={!!children}
      className={cn(
        "relative -my-2 h-5 text-sm group-data-[variant=outline]/field-group:-mb-2",
        className
      )}
      {...props}
    >
      <Separator className="absolute inset-0 top-1/2" />
      {children && (
        <span
          className="bg-background text-muted-foreground relative mx-auto block w-fit px-2"
          data-slot="field-separator-content"
        >
          {children}
        </span>
      )}
    </div>
  )
}

function FieldError({
  className,
  children,
  errors,
  ...props
}: React.ComponentProps<"div"> & {
  errors?: Array<{ message?: string } | undefined>
}) {
  const content = useMemo(() => {
    if (children) {
      return children
```

```
    }

    if (!errors) {
      return null
    }

    if (errors?.length === 1 && errors[0]?.message) {
      return errors[0].message
    }

    return (
      <ul className="ml-4 flex list-disc flex-col gap-1">
        {errors.map(
          (error, index) =>
            error?.message && <li key={index}>{error.message}</li>
        )}
      </ul>
    )
  }, [children, errors])

  if (!content) {
    return null
  }

  return (
    <div
      role="alert"
      data-slot="field-error"
      className={cn("text-destructive text-sm font-normal", className)}
      {...props}
    >
      {content}
    </div>
  )
}

export {
  Field,
  FieldLabel,
  FieldDescription,
  FieldError,
  FieldGroup,
  FieldLegend,
  FieldSeparator,
  FieldSet,
  FieldContent,
  FieldTitle,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/form.tsx
SIZE: 4,175 bytes

```
import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { Slot } from "@radix-ui/react-slot"
import {
  Controller,
  FormProvider,
  useFormContext,
  type ControllerProps,
  type FieldPath,
  type FieldValues,
} from "react-hook-form"

import { cn } from "@/lib/utils"
import { Label } from "@/components/ui/label"

const Form = FormProvider

type FormFieldContextValue<
  TFieldValues extends FieldValues = FieldValues,
  TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>
> = {
  name: TName
}

const FormFieldContext = React.createContext<FormFieldContextValue | null>(null)

const FormField = <
  TFieldValues extends FieldValues = FieldValues,
  TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>
>({
  ...props
}: ControllerProps<TFieldValues, TName>) => {
  return (
    <FormFieldContext.Provider value={{ name: props.name }}>
      <Controller {...props} />
    </FormFieldContext.Provider>
  )
}

const useFormField = () => {
  const fieldContext = React.useContext(FormFieldContext)
  const itemContext = React.useContext(FormItemContext)
  const { getFieldState, formState } = useFormContext()

  if (!fieldContext) {
    throw new Error("useFormField should be used within <FormField>")
  }

  if (!itemContext) {
```

```
    throw new Error("useFormField should be used within <FormItem>")
  }

  const fieldState = getFieldState(fieldContext.name, formState)

  const { id } = itemContext

  return {
    id,
    name: fieldContext.name,
    formItemId: `${id}-form-item`,
    formDescriptionId: `${id}-form-item-description`,
    formMessageId: `${id}-form-item-message`,
    ...fieldState,
  }
}

type FormItemContextValue = {
  id: string
}

const FormItemContext = React.createContext<FormItemContextValue | null>(null)

const FormItem = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => {
  const id = React.useId()

  return (
    <FormItemContext.Provider value={{ id }}>
      <div ref={ref} className={cn("space-y-2", className)} {...props} />
    </FormItemContext.Provider>
  )
})
FormItem.displayName = "FormItem"

const FormLabel = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root>
>(({ className, ...props }, ref) => {
  const { error, formItemId } = useFormField()

  return (
    <Label
      ref={ref}
      className={cn(error && "text-destructive", className)}
      htmlFor={formItemId}
      {...props}
    />
  )
})
```

```
FormLabel.displayName = "FormLabel"

const FormControl = React.forwardRef<
  React.ElementRef<typeof Slot>,
  React.ComponentPropsWithoutRef<typeof Slot>
>(({ ...props }, ref) => {
  const { error, formItemId, formDescriptionId, formMessageId } = useFormField()

  return (
    <Slot
      ref={ref}
      id={formItemId}
      aria-describedby={
        !error
          ? `${formDescriptionId}`
          : `${formDescriptionId} ${formMessageId}`
      }
      aria-invalid={!!error}
      {...props}
    />
  )
})
FormControl.displayName = "FormControl"

const FormDescription = React.forwardRef<
  HTMLParagraphElement,
  React.HTMLAttributes<HTMLParagraphElement>
>(({ className, ...props }, ref) => {
  const { formDescriptionId } = useFormField()

  return (
    <p
      ref={ref}
      id={formDescriptionId}
      className={cn("text-[0.8rem] text-muted-foreground", className)}
      {...props}
    />
  )
})
FormDescription.displayName = "FormDescription"

const FormMessage = React.forwardRef<
  HTMLParagraphElement,
  React.HTMLAttributes<HTMLParagraphElement>
>(({ className, children, ...props }, ref) => {
  const { error, formMessageId } = useFormField()
  const body = error ? String(error?.message ?? "") : children

  if (!body) {
    return null
  }
```

```
  return (
    <p
      ref={ref}
      id={formMessageId}
      className={cn("text-[0.8rem] font-medium text-destructive", className)}
      {...props}
    >
      {body}
    </p>
  )
})
FormMessage.displayName = "FormMessage"

export {
  useFormField,
  Form,
  FormItem,
  FormLabel,
  FormControl,
  FormDescription,
  FormMessage,
  FormField,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/hover-card.tsx
SIZE: 1,237 bytes

```
import * as React from "react"
import * as HoverCardPrimitive from "@radix-ui/react-hover-card"

import { cn } from "@/lib/utils"

const HoverCard = HoverCardPrimitive.Root

const HoverCardTrigger = HoverCardPrimitive.Trigger

const HoverCardContent = React.forwardRef<
  React.ElementRef<typeof HoverCardPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof HoverCardPrimitive.Content>
>(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  <HoverCardPrimitive.Content
    ref={ref}
    align={align}
    sideOffset={sideOffset}
    className={cn(
      "z-50 w-64 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-[state=ope
  n]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[s
  tate=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:sl
  ide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radi
  x-hover-card-content-transform-origin]",
      className
    )}
    {...props}
  />
))
HoverCardContent.displayName = HoverCardPrimitive.Content.displayName

export { HoverCard, HoverCardTrigger, HoverCardContent }
```

FILE: artifacts/mockup-sandbox/src/components/ui/input-group.tsx
SIZE: 4,883 bytes

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"
import { Input } from "@/components/ui/input"
import { Textarea } from "@/components/ui/textarea"

function InputGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="input-group"
      role="group"
      className={cn(
        "group/input-group border-input dark:bg-input/30 shadow-xs relative flex w-full items-center rounded-md
  border outline-none transition-[color,box-shadow]",
        "h-9 has-[>textarea]:h-auto",

        "has-[>[data-align=inline-start]]:[&>input]:pl-2",
        "has-[>[data-align=inline-end]]:[&>input]:pr-2",
        "has-[>[data-align=block-start]]:h-auto has-[>[data-align=block-start]]:flex-col has-[>[data-align=block
  -start]]:[&>input]:pb-3",
        "has-[>[data-align=block-end]]:h-auto has-[>[data-align=block-end]]:flex-col has-[>[data-align=block-end
  ]]:[&>input]:pt-3",

        "has-[[data-slot=input-group-control]:focus-visible]:ring-ring has-[[data-slot=input-group-control]:focu
  s-visible]:ring-1",

        "has-[[data-slot][aria-invalid=true]]:ring-destructive/20 has-[[data-slot][aria-invalid=true]]:border-de
  structive dark:has-[[data-slot][aria-invalid=true]]:ring-destructive/40",

        className
      )}
      {...props}
    />
  )
}

const inputGroupAddonVariants = cva(
  "text-muted-foreground flex h-auto cursor-text select-none items-center justify-center gap-2 py-1.5 text-sm fo
  nt-medium group-data-[disabled=true]/input-group:opacity-50 [&>kbd]:rounded-[calc(var(--radius)-5px)] [&>svg:not
  ([class*='size-'])]:size-4",
  {
    variants: {
      align: {
        "inline-start":
          "order-first pl-3 has-[>button]:ml-[-0.45rem] has-[>kbd]:ml-[-0.35rem]",
        "inline-end":
          "order-last pr-3 has-[>button]:mr-[-0.4rem] has-[>kbd]:mr-[-0.35rem]",
```

```
        "block-start":
          "[.border-b]:pb-3 order-first w-full justify-start px-3 pt-3 group-has-[>input]/input-group:pt-2.5",
        "block-end":
          "[.border-t]:pt-3 order-last w-full justify-start px-3 pb-3 group-has-[>input]/input-group:pb-2.5",
      },
    },
    defaultVariants: {
      align: "inline-start",
    },
  }
)

function InputGroupAddon({
  className,
  align = "inline-start",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof inputGroupAddonVariants>) {
  return (
    <div
      role="group"
      data-slot="input-group-addon"
      data-align={align}
      className={cn(inputGroupAddonVariants({ align }), className)}
      onClick={(e) => {
        if ((e.target as HTMLElement).closest("button")) {
          return
        }
        e.currentTarget.parentElement?.querySelector("input")?.focus()
      }}
      {...props}
    />
  )
}

const inputGroupButtonVariants = cva(
  "flex items-center gap-2 text-sm shadow-none",
  {
    variants: {
      size: {
        xs: "h-6 gap-1 rounded-[calc(var(--radius)-5px)] px-2 has-[>svg]:px-2 [&>svg:not([class*='size-'])]:size
  -3.5",
        sm: "h-8 gap-1.5 rounded-md px-2.5 has-[>svg]:px-2.5",
        "icon-xs":
          "size-6 rounded-[calc(var(--radius)-5px)] p-0 has-[>svg]:p-0",
        "icon-sm": "size-8 p-0 has-[>svg]:p-0",
      },
    },
    defaultVariants: {
      size: "xs",
    },
  }
)
```

```
function InputGroupButton({
  className,
  type = "button",
  variant = "ghost",
  size = "xs",
  ...props
}: Omit<React.ComponentProps<typeof Button>, "size"> &
  VariantProps<typeof inputGroupButtonVariants>) {
  return (
    <Button
      type={type}
      data-size={size}
      variant={variant}
      className={cn(inputGroupButtonVariants({ size }), className)}
      {...props}
    />
  )
}

function InputGroupText({ className, ...props }: React.ComponentProps<"span">) {
  return (
    <span
      className={cn(
        "text-muted-foreground flex items-center gap-2 text-sm [&_svg:not([class*='size-'])]:size-4 [&_svg]:poin
  ter-events-none",
        className
      )}
      {...props}
    />
  )
}

function InputGroupInput({
  className,
  ...props
}: React.ComponentProps<"input">) {
  return (
    <Input
      data-slot="input-group-control"
      className={cn(
        "flex-1 rounded-none border-0 bg-transparent shadow-none focus-visible:ring-0 dark:bg-transparent",
        className
      )}
      {...props}
    />
  )
}

function InputGroupTextarea({
  className,
  ...props
```

```
}: React.ComponentProps<"textarea">) {
  return (
    <Textarea
      data-slot="input-group-control"
      className={cn(
        "flex-1 resize-none rounded-none border-0 bg-transparent py-3 shadow-none focus-visible:ring-0 dark:bg-t
  ransparent",
        className
      )}
      {...props}
    />
  )
}

export {
  InputGroup,
  InputGroupAddon,
  InputGroupButton,
  InputGroupText,
  InputGroupInput,
  InputGroupTextarea,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/input-otp.tsx
SIZE: 2,143 bytes

```
import * as React from "react"
import { OTPInput, OTPInputContext } from "input-otp"
import { Minus } from "lucide-react"

import { cn } from "@/lib/utils"

const InputOTP = React.forwardRef<
  React.ElementRef<typeof OTPInput>,
  React.ComponentPropsWithoutRef<typeof OTPInput>
>(({ className, containerClassName, ...props }, ref) => (
  <OTPInput
    ref={ref}
    containerClassName={cn(
      "flex items-center gap-2 has-[:disabled]:opacity-50",
      containerClassName
    )}
    className={cn("disabled:cursor-not-allowed", className)}
    {...props}
  />
))
InputOTP.displayName = "InputOTP"

const InputOTPGroup = React.forwardRef<
  React.ElementRef<"div">,
  React.ComponentPropsWithoutRef<"div">
>(({ className, ...props }, ref) => (
  <div ref={ref} className={cn("flex items-center", className)} {...props} />
))
InputOTPGroup.displayName = "InputOTPGroup"

const InputOTPSlot = React.forwardRef<
  React.ElementRef<"div">,
  React.ComponentPropsWithoutRef<"div"> & { index: number }
>(({ index, className, ...props }, ref) => {
  const inputOTPContext = React.useContext(OTPInputContext)
  const { char, hasFakeCaret, isActive } = inputOTPContext.slots[index]

  return (
    <div
      ref={ref}
      className={cn(
        "relative flex h-9 w-9 items-center justify-center border-y border-r border-input text-sm shadow-sm tran
  sition-all first:rounded-l-md first:border-l last:rounded-r-md",
        isActive && "z-10 ring-1 ring-ring",
        className
      )}
      {...props}
    >
      {char}
```

```
      {hasFakeCaret && (
        <div className="pointer-events-none absolute inset-0 flex items-center justify-center">
          <div className="h-4 w-px animate-caret-blink bg-foreground duration-1000" />
        </div>
      )}
    </div>
  )
})
InputOTPSlot.displayName = "InputOTPSlot"

const InputOTPSeparator = React.forwardRef<
  React.ElementRef<"div">,
  React.ComponentPropsWithoutRef<"div">
>(({ ...props }, ref) => (
  <div ref={ref} role="separator" {...props}>
    <Minus />
  </div>
))
InputOTPSeparator.displayName = "InputOTPSeparator"

export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator }
```

FILE: artifacts/mockup-sandbox/src/components/ui/input.tsx
SIZE: 768 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Input = React.forwardRef<HTMLInputElement, React.ComponentProps<"input">>(
  ({ className, type, ...props }, ref) => {
    return (
      <input
        type={type}
        className={cn(
          "flex h-9 w-full rounded-md border border-input bg-transparent px-3 py-1 text-base shadow-sm transitio
  n-colors file:border-0 file:bg-transparent file:text-sm file:font-medium file:text-foreground placeholder:text-m
  uted-foreground focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allo
  wed disabled:opacity-50 md:text-sm",
          className
        )}
        ref={ref}
        {...props}
      />
    )
  }
)
Input.displayName = "Input"

export { Input }
```

FILE: artifacts/mockup-sandbox/src/components/ui/item.tsx
SIZE: 4,494 bytes

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Separator } from "@/components/ui/separator"

function ItemGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      role="list"
      data-slot="item-group"
      className={cn("group/item-group flex flex-col", className)}
      {...props}
    />
  )
}

function ItemSeparator({
  className,
  ...props
}: React.ComponentProps<typeof Separator>) {
  return (
    <Separator
      data-slot="item-separator"
      orientation="horizontal"
      className={cn("my-0", className)}
      {...props}
    />
  )
}

const itemVariants = cva(
  "group/item [a]:hover:bg-accent/50 focus-visible:border-ring focus-visible:ring-ring/50 [a]:transition-colors
  flex flex-wrap items-center rounded-md border border-transparent text-sm outline-none transition-colors duration
  -100 focus-visible:ring-[3px]",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        outline: "border-border",
        muted: "bg-muted/50",
      },
      size: {
        default: "gap-4 p-4 ",
        sm: "gap-2.5 px-4 py-3",
      },
    },
    defaultVariants: {
```

```
      variant: "default",
      size: "default",
    },
  }
)

function Item({
  className,
  variant = "default",
  size = "default",
  asChild = false,
  ...props
}: React.ComponentProps<"div"> &
  VariantProps<typeof itemVariants> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "div"
  return (
    <Comp
      data-slot="item"
      data-variant={variant}
      data-size={size}
      className={cn(itemVariants({ variant, size, className }))}
      {...props}
    />
  )
}

const itemMediaVariants = cva(
  "flex shrink-0 items-center justify-center gap-2 group-has-[[data-slot=item-description]]/item:translate-y-0.5
   group-has-[[data-slot=item-description]]/item:self-start [&_svg]:pointer-events-none",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        icon: "bg-muted size-8 rounded-sm border [&_svg:not([class*='size-'])]:size-4",
        image:
          "size-10 overflow-hidden rounded-sm [&_img]:size-full [&_img]:object-cover",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

function ItemMedia({
  className,
  variant = "default",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof itemMediaVariants>) {
  return (
    <div
      data-slot="item-media"
```

```
      data-variant={variant}
      className={cn(itemMediaVariants({ variant, className }))}
      {...props}
    />
  )
}

function ItemContent({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-content"
      className={cn(
        "flex flex-1 flex-col gap-1 [&+[data-slot=item-content]]:flex-none",
        className
      )}
      {...props}
    />
  )
}

function ItemTitle({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-title"
      className={cn(
        "flex w-fit items-center gap-2 text-sm font-medium leading-snug",
        className
      )}
      {...props}
    />
  )
}

function ItemDescription({ className, ...props }: React.ComponentProps<"p">) {
  return (
    <p
      data-slot="item-description"
      className={cn(
        "text-muted-foreground line-clamp-2 text-balance text-sm font-normal leading-normal",
        "[&>a:hover]:text-primary [&>a]:underline [&>a]:underline-offset-4",
        className
      )}
      {...props}
    />
  )
}

function ItemActions({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-actions"
      className={cn("flex items-center gap-2", className)}
```

```
      {...props}
    />
  )
}

function ItemHeader({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-header"
      className={cn(
        "flex basis-full items-center justify-between gap-2",
        className
      )}
      {...props}
    />
  )
}

function ItemFooter({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-footer"
      className={cn(
        "flex basis-full items-center justify-between gap-2",
        className
      )}
      {...props}
    />
  )
}

export {
  Item,
  ItemMedia,
  ItemContent,
  ItemActions,
  ItemGroup,
  ItemSeparator,
  ItemTitle,
  ItemDescription,
  ItemHeader,
  ItemFooter,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/kbd.tsx
SIZE: 862 bytes

```
import { cn } from "@/lib/utils"

function Kbd({ className, ...props }: React.ComponentProps<"kbd">) {
  return (
    <kbd
      data-slot="kbd"
      className={cn(
        "bg-muted text-muted-foreground pointer-events-none inline-flex h-5 w-fit min-w-5 select-none items-cent
  er justify-center gap-1 rounded-sm px-1 font-sans text-xs font-medium",
        "[&_svg:not([class*='size-'])]:size-3",
        "[[data-slot=tooltip-content]_&]:bg-background/20 [[data-slot=tooltip-content]_&]:text-background dark:[
  [data-slot=tooltip-content]_&]:bg-background/10",
        className
      )}
      {...props}
    />
  )
}

function KbdGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <kbd
      data-slot="kbd-group"
      className={cn("inline-flex items-center gap-1", className)}
      {...props}
    />
  )
}

export { Kbd, KbdGroup }
```

FILE: artifacts/mockup-sandbox/src/components/ui/label.tsx
SIZE: 724 bytes

```
"use client"

import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const labelVariants = cva(
  "text-sm font-medium leading-none peer-disabled:cursor-not-allowed peer-disabled:opacity-70"
)

const Label = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root> &
    VariantProps<typeof labelVariants>
>(({ className, ...props }, ref) => (
  <LabelPrimitive.Root
    ref={ref}
    className={cn(labelVariants(), className)}
    {...props}
  />
))
Label.displayName = LabelPrimitive.Root.displayName

export { Label }
```

FILE: artifacts/mockup-sandbox/src/components/ui/menubar.tsx
SIZE: 8,608 bytes

```
import * as React from "react"
import * as MenubarPrimitive from "@radix-ui/react-menubar"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

function MenubarMenu({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Menu>) {
  return <MenubarPrimitive.Menu {...props} />
}

function MenubarGroup({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Group>) {
  return <MenubarPrimitive.Group {...props} />
}

function MenubarPortal({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Portal>) {
  return <MenubarPrimitive.Portal {...props} />
}

function MenubarRadioGroup({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.RadioGroup>) {
  return <MenubarPrimitive.RadioGroup {...props} />
}

function MenubarSub({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Sub>) {
  return <MenubarPrimitive.Sub data-slot="menubar-sub" {...props} />
}

const Menubar = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Root
    ref={ref}
    className={cn(
      "flex h-9 items-center space-x-1 rounded-md border bg-background p-1 shadow-sm",
      className
    )}
    {...props}
  />
))
```

```
Menubar.displayName = MenubarPrimitive.Root.displayName

const MenubarTrigger = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Trigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-3 py-1 text-sm font-medium outline-none focus:
  bg-accent focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-accent-foreground",
      className
    )}
    {...props}
  />
))
MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName

const MenubarSubTrigger = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <MenubarPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
  focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-accent-foreground",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </MenubarPrimitive.SubTrigger>
))
MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName

const MenubarSubContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data
  -[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-i
  n-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[si
  de=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 ori
  gin-[--radix-menubar-content-transform-origin]",
```

```
      className
    )}
    {...props}
  />
))
MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName

const MenubarContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Content>
>(
  (
    { className, align = "start", alignOffset = -4, sideOffset = 8, ...props },
    ref
  ) => (
    <MenubarPrimitive.Portal>
      <MenubarPrimitive.Content
        ref={ref}
        align={align}
        alignOffset={alignOffset}
        sideOffset={sideOffset}
        className={cn(
          "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md
   data-[state=open]:animate-in data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoo
  m-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-righ
  t-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-menubar-conten
  t-transform-origin]",
          className
        )}
        {...props}
      />
    </MenubarPrimitive.Portal>
  )
)
MenubarContent.displayName = MenubarPrimitive.Content.displayName

const MenubarItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <MenubarPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:b
  g-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      inset && "pl-8",
      className
    )}
    {...props}
  />
```

```
))
MenubarItem.displayName = MenubarPrimitive.Item.displayName

const MenubarCheckboxItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <MenubarPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.CheckboxItem>
))
MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName

const MenubarRadioItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <MenubarPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Circle className="h-4 w-4 fill-current" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.RadioItem>
))
MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName

const MenubarLabel = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Label>,
```

```
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Label> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <MenubarPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
MenubarLabel.displayName = MenubarPrimitive.Label.displayName

const MenubarSeparator = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-muted", className)}
    {...props}
  />
))
MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName

const MenubarShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
MenubarShortcut.displayname = "MenubarShortcut"

export {
  Menubar,
  MenubarMenu,
  MenubarTrigger,
  MenubarContent,
  MenubarItem,
  MenubarSeparator,
  MenubarLabel,
```

```
  MenubarCheckboxItem,
  MenubarRadioGroup,
  MenubarRadioItem,
  MenubarPortal,
  MenubarSubContent,
  MenubarSubTrigger,
  MenubarGroup,
  MenubarSub,
  MenubarShortcut,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/navigation-menu.tsx
SIZE: 5,124 bytes

```
import * as React from "react"
import * as NavigationMenuPrimitive from "@radix-ui/react-navigation-menu"
import { cva } from "class-variance-authority"
import { ChevronDown } from "lucide-react"

import { cn } from "@/lib/utils"

const NavigationMenu = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Root>
>(({ className, children, ...props }, ref) => (
  <NavigationMenuPrimitive.Root
    ref={ref}
    className={cn(
      "relative z-10 flex max-w-max flex-1 items-center justify-center",
      className
    )}
    {...props}
  >
    {children}
    <NavigationMenuViewport />
  </NavigationMenuPrimitive.Root>
))
NavigationMenu.displayName = NavigationMenuPrimitive.Root.displayName

const NavigationMenuList = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.List>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.List
    ref={ref}
    className={cn(
      "group flex flex-1 list-none items-center justify-center space-x-1",
      className
    )}
    {...props}
  />
))
NavigationMenuList.displayName = NavigationMenuPrimitive.List.displayName

const NavigationMenuItem = NavigationMenuPrimitive.Item

const navigationMenuTriggerStyle = cva(
  "group inline-flex h-9 w-max items-center justify-center rounded-md bg-background px-4 py-2 text-sm font-mediu
  m transition-colors hover:bg-accent hover:text-accent-foreground focus:bg-accent focus:text-accent-foreground fo
  cus:outline-none disabled:pointer-events-none disabled:opacity-50 data-[state=open]:text-accent-foreground data-
  [state=open]:bg-accent/50 data-[state=open]:hover:bg-accent data-[state=open]:focus:bg-accent"
)
```

```
const NavigationMenuTrigger = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <NavigationMenuPrimitive.Trigger
    ref={ref}
    className={cn(navigationMenuTriggerStyle(), "group", className)}
    {...props}
  >
    {children}{" "}
    <ChevronDown
      className="relative top-[1px] ml-1 h-3 w-3 transition duration-300 group-data-[state=open]:rotate-180"
      aria-hidden="true"
    />
  </NavigationMenuPrimitive.Trigger>
))
NavigationMenuTrigger.displayName = NavigationMenuPrimitive.Trigger.displayName

const NavigationMenuContent = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Content>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.Content
    ref={ref}
    className={cn(
      "left-0 top-0 w-full data-[motion^=from-]:animate-in data-[motion^=to-]:animate-out data-[motion^=from-]:f
  ade-in data-[motion^=to-]:fade-out data-[motion=from-end]:slide-in-from-right-52 data-[motion=from-start]:slide-
  in-from-left-52 data-[motion=to-end]:slide-out-to-right-52 data-[motion=to-start]:slide-out-to-left-52 md:absolu
  te md:w-auto ",
      className
    )}
    {...props}
  />
))
NavigationMenuContent.displayName = NavigationMenuPrimitive.Content.displayName

const NavigationMenuLink = NavigationMenuPrimitive.Link

const NavigationMenuViewport = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Viewport>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Viewport>
>(({ className, ...props }, ref) => (
  <div className={cn("absolute left-0 top-full flex justify-center")}>
    <NavigationMenuPrimitive.Viewport
      className={cn(
        "origin-top-center relative mt-1.5 h-[var(--radix-navigation-menu-viewport-height)] w-full overflow-hidd
  en rounded-md border bg-popover text-popover-foreground shadow data-[state=open]:animate-in data-[state=closed]:
  animate-out data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-90 md:w-[var(--radix-navigation-menu-viewp
  ort-width)]",
        className
      )}
      ref={ref}
```

```
      {...props}
    />
  </div>
))
NavigationMenuViewport.displayName =
  NavigationMenuPrimitive.Viewport.displayName

const NavigationMenuIndicator = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Indicator>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Indicator>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.Indicator
    ref={ref}
    className={cn(
      "top-full z-[1] flex h-1.5 items-end justify-center overflow-hidden data-[state=visible]:animate-in data-[
  state=hidden]:animate-out data-[state=hidden]:fade-out data-[state=visible]:fade-in",
      className
    )}
    {...props}
  >
    <div className="relative top-[60%] h-2 w-2 rotate-45 rounded-tl-sm bg-border shadow-md" />
  </NavigationMenuPrimitive.Indicator>
))
NavigationMenuIndicator.displayName =
  NavigationMenuPrimitive.Indicator.displayName

export {
  navigationMenuTriggerStyle,
  NavigationMenu,
  NavigationMenuList,
  NavigationMenuItem,
  NavigationMenuContent,
  NavigationMenuTrigger,
  NavigationMenuLink,
  NavigationMenuIndicator,
  NavigationMenuViewport,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/pagination.tsx
SIZE: 2,751 bytes

```
import * as React from "react"
import { ChevronLeft, ChevronRight, MoreHorizontal } from "lucide-react"

import { cn } from "@/lib/utils"
import { ButtonProps, buttonVariants } from "@/components/ui/button"

const Pagination = ({ className, ...props }: React.ComponentProps<"nav">) => (
  <nav
    role="navigation"
    aria-label="pagination"
    className={cn("mx-auto flex w-full justify-center", className)}
    {...props}
  />
)
Pagination.displayName = "Pagination"

const PaginationContent = React.forwardRef<
  HTMLUListElement,
  React.ComponentProps<"ul">
>(({ className, ...props }, ref) => (
  <ul
    ref={ref}
    className={cn("flex flex-row items-center gap-1", className)}
    {...props}
  />
))
PaginationContent.displayName = "PaginationContent"

const PaginationItem = React.forwardRef<
  HTMLLIElement,
  React.ComponentProps<"li">
>(({ className, ...props }, ref) => (
  <li ref={ref} className={cn("", className)} {...props} />
))
PaginationItem.displayName = "PaginationItem"

type PaginationLinkProps = {
  isActive?: boolean
} & Pick<ButtonProps, "size"> &
  React.ComponentProps<"a">

const PaginationLink = ({
  className,
  isActive,
  size = "icon",
  ...props
}: PaginationLinkProps) => (
  <a
    aria-current={isActive ? "page" : undefined}
```

```
    className={cn(
      buttonVariants({
        variant: isActive ? "outline" : "ghost",
        size,
      }),
      className
    )}
    {...props}
  />
)
PaginationLink.displayName = "PaginationLink"

const PaginationPrevious = ({
  className,
  ...props
}: React.ComponentProps<typeof PaginationLink>) => (
  <PaginationLink
    aria-label="Go to previous page"
    size="default"
    className={cn("gap-1 pl-2.5", className)}
    {...props}
  >
    <ChevronLeft className="h-4 w-4" />
    <span>Previous</span>
  </PaginationLink>
)
PaginationPrevious.displayName = "PaginationPrevious"

const PaginationNext = ({
  className,
  ...props
}: React.ComponentProps<typeof PaginationLink>) => (
  <PaginationLink
    aria-label="Go to next page"
    size="default"
    className={cn("gap-1 pr-2.5", className)}
    {...props}
  >
    <span>Next</span>
    <ChevronRight className="h-4 w-4" />
  </PaginationLink>
)
PaginationNext.displayName = "PaginationNext"

const PaginationEllipsis = ({
  className,
  ...props
}: React.ComponentProps<"span">) => (
  <span
    aria-hidden
    className={cn("flex h-9 w-9 items-center justify-center", className)}
    {...props}
```

```
  >
    <MoreHorizontal className="h-4 w-4" />
    <span className="sr-only">More pages</span>
  </span>
)
PaginationEllipsis.displayName = "PaginationEllipsis"

export {
  Pagination,
  PaginationContent,
  PaginationLink,
  PaginationItem,
  PaginationPrevious,
  PaginationNext,
  PaginationEllipsis,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/popover.tsx
SIZE: 1,342 bytes

```
import * as React from "react"
import * as PopoverPrimitive from "@radix-ui/react-popover"

import { cn } from "@/lib/utils"

const Popover = PopoverPrimitive.Root

const PopoverTrigger = PopoverPrimitive.Trigger

const PopoverAnchor = PopoverPrimitive.Anchor

const PopoverContent = React.forwardRef<
  React.ElementRef<typeof PopoverPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof PopoverPrimitive.Content>
>(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  <PopoverPrimitive.Portal>
    <PopoverPrimitive.Content
      ref={ref}
      align={align}
      sideOffset={sideOffset}
      className={cn(
        "z-50 w-72 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-[state=o
  pen]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
  [state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:
  slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--ra
  dix-popover-content-transform-origin]",
        className
      )}
      {...props}
    />
  </PopoverPrimitive.Portal>
))
PopoverContent.displayName = PopoverPrimitive.Content.displayName

export { Popover, PopoverTrigger, PopoverContent, PopoverAnchor }
```

FILE: artifacts/mockup-sandbox/src/components/ui/progress.tsx
SIZE: 792 bytes

```
"use client"

import * as React from "react"
import * as ProgressPrimitive from "@radix-ui/react-progress"

import { cn } from "@/lib/utils"

const Progress = React.forwardRef<
  React.ElementRef<typeof ProgressPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ProgressPrimitive.Root>
>(({ className, value, ...props }, ref) => (
  <ProgressPrimitive.Root
    ref={ref}
    className={cn(
      "relative h-2 w-full overflow-hidden rounded-full bg-primary/20",
      className
    )}
    {...props}
  >
    <ProgressPrimitive.Indicator
      className="h-full w-full flex-1 bg-primary transition-all"
      style={{ transform: `translateX(-${100 - (value || 0)}%)` }}
    />
  </ProgressPrimitive.Root>
))
Progress.displayName = ProgressPrimitive.Root.displayName

export { Progress }
```

FILE: artifacts/mockup-sandbox/src/components/ui/radio-group.tsx
SIZE: 1,410 bytes

```
import * as React from "react"
import * as RadioGroupPrimitive from "@radix-ui/react-radio-group"
import { Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const RadioGroup = React.forwardRef<
  React.ElementRef<typeof RadioGroupPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Root>
>(({ className, ...props }, ref) => {
  return (
    <RadioGroupPrimitive.Root
      className={cn("grid gap-2", className)}
      {...props}
      ref={ref}
    />
  )
})
RadioGroup.displayName = RadioGroupPrimitive.Root.displayName

const RadioGroupItem = React.forwardRef<
  React.ElementRef<typeof RadioGroupPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Item>
>(({ className, ...props }, ref) => {
  return (
    <RadioGroupPrimitive.Item
      ref={ref}
      className={cn(
        "aspect-square h-4 w-4 rounded-full border border-primary text-primary shadow focus:outline-none focus-v
  isible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50",
        className
      )}
      {...props}
    >
      <RadioGroupPrimitive.Indicator className="flex items-center justify-center">
        <Circle className="h-3.5 w-3.5 fill-primary" />
      </RadioGroupPrimitive.Indicator>
    </RadioGroupPrimitive.Item>
  )
})
RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName

export { RadioGroup, RadioGroupItem }
```

FILE: artifacts/mockup-sandbox/src/components/ui/resizable.tsx
SIZE: 1,723 bytes

```
"use client"

import { GripVertical } from "lucide-react"
import * as ResizablePrimitive from "react-resizable-panels"

import { cn } from "@/lib/utils"

const ResizablePanelGroup = ({
  className,
  ...props
}: React.ComponentProps<typeof ResizablePrimitive.PanelGroup>) => (
  <ResizablePrimitive.PanelGroup
    className={cn(
      "flex h-full w-full data-[panel-group-direction=vertical]:flex-col",
      className
    )}
    {...props}
  />
)

const ResizablePanel = ResizablePrimitive.Panel

const ResizableHandle = ({
  withHandle,
  className,
  ...props
}: React.ComponentProps<typeof ResizablePrimitive.PanelResizeHandle> & {
  withHandle?: boolean
}) => (
  <ResizablePrimitive.PanelResizeHandle
    className={cn(
      "relative flex w-px items-center justify-center bg-border after:absolute after:inset-y-0 after:left-1/2 af
  ter:w-1 after:-translate-x-1/2 focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring focus-vis
  ible:ring-offset-1 data-[panel-group-direction=vertical]:h-px data-[panel-group-direction=vertical]:w-full data-
  [panel-group-direction=vertical]:after:left-0 data-[panel-group-direction=vertical]:after:h-1 data-[panel-group-
  direction=vertical]:after:w-full data-[panel-group-direction=vertical]:after:-translate-y-1/2 data-[panel-group-
  direction=vertical]:after:translate-x-0 [&[data-panel-group-direction=vertical]>div]:rotate-90",
      className
    )}
    {...props}
  >
    {withHandle && (
      <div className="z-10 flex h-4 w-3 items-center justify-center rounded-sm border bg-border">
        <GripVertical className="h-2.5 w-2.5" />
      </div>
    )}
  </ResizablePrimitive.PanelResizeHandle>
)
```

```
export { ResizablePanelGroup, ResizablePanel, ResizableHandle }
```

FILE: artifacts/mockup-sandbox/src/components/ui/scroll-area.tsx
SIZE: 1,642 bytes

```
import * as React from "react"
import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area"

import { cn } from "@/lib/utils"

const ScrollArea = React.forwardRef<
  React.ElementRef<typeof ScrollAreaPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.Root>
>(({ className, children, ...props }, ref) => (
  <ScrollAreaPrimitive.Root
    ref={ref}
    className={cn("relative overflow-hidden", className)}
    {...props}
  >
    <ScrollAreaPrimitive.Viewport className="h-full w-full rounded-[inherit]">
      {children}
    </ScrollAreaPrimitive.Viewport>
    <ScrollBar />
    <ScrollAreaPrimitive.Corner />
  </ScrollAreaPrimitive.Root>
))
ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName

const ScrollBar = React.forwardRef<
  React.ElementRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>,
  React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>
>(({ className, orientation = "vertical", ...props }, ref) => (
  <ScrollAreaPrimitive.ScrollAreaScrollbar
    ref={ref}
    orientation={orientation}
    className={cn(
      "flex touch-none select-none transition-colors",
      orientation === "vertical" &&
        "h-full w-2.5 border-l border-l-transparent p-[1px]",
      orientation === "horizontal" &&
        "h-2.5 flex-col border-t border-t-transparent p-[1px]",
      className
    )}
    {...props}
  >
    <ScrollAreaPrimitive.ScrollAreaThumb className="relative flex-1 rounded-full bg-border" />
  </ScrollAreaPrimitive.ScrollAreaScrollbar>
))
ScrollBar.displayName = ScrollAreaPrimitive.ScrollAreaScrollbar.displayName

export { ScrollArea, ScrollBar }
```

FILE: artifacts/mockup-sandbox/src/components/ui/select.tsx
SIZE: 5,745 bytes

```
"use client"

import * as React from "react"
import * as SelectPrimitive from "@radix-ui/react-select"
import { Check, ChevronDown, ChevronUp } from "lucide-react"

import { cn } from "@/lib/utils"

const Select = SelectPrimitive.Root

const SelectGroup = SelectPrimitive.Group

const SelectValue = SelectPrimitive.Value

const SelectTrigger = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <SelectPrimitive.Trigger
    ref={ref}
    className={cn(
      "flex h-9 w-full items-center justify-between whitespace-nowrap rounded-md border border-input bg-transpar
  ent px-3 py-2 text-sm shadow-sm ring-offset-background data-[placeholder]:text-muted-foreground focus:outline-no
  ne focus:ring-1 focus:ring-ring disabled:cursor-not-allowed disabled:opacity-50 [&>span]:line-clamp-1",
      className
    )}
    {...props}
  >
    {children}
    <SelectPrimitive.Icon asChild>
      <ChevronDown className="h-4 w-4 opacity-50" />
    </SelectPrimitive.Icon>
  </SelectPrimitive.Trigger>
))
SelectTrigger.displayName = SelectPrimitive.Trigger.displayName

const SelectScrollUpButton = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.ScrollUpButton>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollUpButton>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.ScrollUpButton
    ref={ref}
    className={cn(
      "flex cursor-default items-center justify-center py-1",
      className
    )}
    {...props}
  >
    <ChevronUp className="h-4 w-4" />
```

```
  </SelectPrimitive.ScrollUpButton>
))
SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName

const SelectScrollDownButton = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.ScrollDownButton>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollDownButton>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.ScrollDownButton
    ref={ref}
    className={cn(
      "flex cursor-default items-center justify-center py-1",
      className
    )}
    {...props}
  >
    <ChevronDown className="h-4 w-4" />
  </SelectPrimitive.ScrollDownButton>
))
SelectScrollDownButton.displayName =
  SelectPrimitive.ScrollDownButton.displayName

const SelectContent = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Content>
>(({ className, children, position = "popper", ...props }, ref) => (
  <SelectPrimitive.Portal>
    <SelectPrimitive.Content
      ref={ref}
      className={cn(
        "relative z-50 max-h-[--radix-select-content-available-height] min-w-[8rem] overflow-y-auto overflow-x-h
  idden rounded-md border bg-popover text-popover-foreground shadow-md data-[state=open]:animate-in data-[state=cl
  osed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 dat
  a-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[si
  de=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-select-content-transform-o
  rigin]",
        position === "popper" &&
          "data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-[side=right]:translate-x-1 data
  -[side=top]:-translate-y-1",
        className
      )}
      position={position}
      {...props}
    >
      <SelectScrollUpButton />
      <SelectPrimitive.Viewport
        className={cn(
          "p-1",
          position === "popper" &&
            "h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-width)]"
        )}
      >
```

```
        {children}
      </SelectPrimitive.Viewport>
      <SelectScrollDownButton />
    </SelectPrimitive.Content>
  </SelectPrimitive.Portal>
))
SelectContent.displayName = SelectPrimitive.Content.displayName

const SelectLabel = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Label>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.Label
    ref={ref}
    className={cn("px-2 py-1.5 text-sm font-semibold", className)}
    {...props}
  />
))
SelectLabel.displayName = SelectPrimitive.Label.displayName

const SelectItem = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Item>
>(({ className, children, ...props }, ref) => (
  <SelectPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-2 pr-8 text-sm outline-
  none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50
  ",
      className
    )}
    {...props}
  >
    <span className="absolute right-2 flex h-3.5 w-3.5 items-center justify-center">
      <SelectPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </SelectPrimitive.ItemIndicator>
    </span>
    <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>
  </SelectPrimitive.Item>
))
SelectItem.displayName = SelectPrimitive.Item.displayName

const SelectSeparator = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-muted", className)}
    {...props}
```

```
  />
))
SelectSeparator.displayName = SelectPrimitive.Separator.displayName

export {
  Select,
  SelectGroup,
  SelectValue,
  SelectTrigger,
  SelectContent,
  SelectLabel,
  SelectItem,
  SelectSeparator,
  SelectScrollUpButton,
  SelectScrollDownButton,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/separator.tsx
SIZE: 756 bytes

```
import * as React from "react"
import * as SeparatorPrimitive from "@radix-ui/react-separator"

import { cn } from "@/lib/utils"

const Separator = React.forwardRef<
  React.ElementRef<typeof SeparatorPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof SeparatorPrimitive.Root>
>(
  (
    { className, orientation = "horizontal", decorative = true, ...props },
    ref
  ) => (
    <SeparatorPrimitive.Root
      ref={ref}
      decorative={decorative}
      orientation={orientation}
      className={cn(
        "shrink-0 bg-border",
        orientation === "horizontal" ? "h-[1px] w-full" : "h-full w-[1px]",
        className
      )}
      {...props}
    />
  )
)
Separator.displayName = SeparatorPrimitive.Root.displayName

export { Separator }
```

FILE: artifacts/mockup-sandbox/src/components/ui/sheet.tsx
SIZE: 4,280 bytes

```
"use client"

import * as React from "react"
import * as SheetPrimitive from "@radix-ui/react-dialog"
import { cva, type VariantProps } from "class-variance-authority"
import { X } from "lucide-react"

import { cn } from "@/lib/utils"

const Sheet = SheetPrimitive.Root

const SheetTrigger = SheetPrimitive.Trigger

const SheetClose = SheetPrimitive.Close

const SheetPortal = SheetPrimitive.Portal

const SheetOverlay = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80  data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=
  closed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
    ref={ref}
  />
))
SheetOverlay.displayName = SheetPrimitive.Overlay.displayName

const sheetVariants = cva(
  "fixed z-50 gap-4 bg-background p-6 shadow-lg transition ease-in-out data-[state=closed]:duration-300 data-[st
  ate=open]:duration-500 data-[state=open]:animate-in data-[state=closed]:animate-out",
  {
    variants: {
      side: {
        top: "inset-x-0 top-0 border-b data-[state=closed]:slide-out-to-top data-[state=open]:slide-in-from-top"
  ,
        bottom:
          "inset-x-0 bottom-0 border-t data-[state=closed]:slide-out-to-bottom data-[state=open]:slide-in-from-b
  ottom",
        left: "inset-y-0 left-0 h-full w-3/4 border-r data-[state=closed]:slide-out-to-left data-[state=open]:sl
  ide-in-from-left sm:max-w-sm",
        right:
          "inset-y-0 right-0 h-full w-3/4 border-l data-[state=closed]:slide-out-to-right data-[state=open]:slid
  e-in-from-right sm:max-w-sm",
```

```
      },
    },
    defaultVariants: {
      side: "right",
    },
  }
)

interface SheetContentProps
  extends React.ComponentPropsWithoutRef<typeof SheetPrimitive.Content>,
    VariantProps<typeof sheetVariants> {}

const SheetContent = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Content>,
  SheetContentProps
>(({ side = "right", className, children, ...props }, ref) => (
  <SheetPortal>
    <SheetOverlay />
    <SheetPrimitive.Content
      ref={ref}
      className={cn(sheetVariants({ side }), className)}
      {...props}
    >
      <SheetPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background trans
  ition-opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:poi
  nter-events-none data-[state=open]:bg-secondary">
        <X className="h-4 w-4" />
        <span className="sr-only">Close</span>
      </SheetPrimitive.Close>
      {children}
    </SheetPrimitive.Content>
  </SheetPortal>
))
SheetContent.displayName = SheetPrimitive.Content.displayName

const SheetHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-2 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
SheetHeader.displayName = "SheetHeader"

const SheetFooter = ({
  className,
  ...props
```

```
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
SheetFooter.displayName = "SheetFooter"

const SheetTitle = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Title>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold text-foreground", className)}
    {...props}
  />
))
SheetTitle.displayName = SheetPrimitive.Title.displayName

const SheetDescription = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Description>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
SheetDescription.displayName = SheetPrimitive.Description.displayName

export {
  Sheet,
  SheetPortal,
  SheetOverlay,
  SheetTrigger,
  SheetClose,
  SheetContent,
  SheetHeader,
  SheetFooter,
  SheetTitle,
  SheetDescription,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/sidebar.tsx
SIZE: 21,056 bytes

```
"use client"

import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, VariantProps } from "class-variance-authority"
import { PanelLeftIcon } from "lucide-react"

import { useIsMobile } from "@/hooks/use-mobile"
import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"
import { Input } from "@/components/ui/input"
import { Separator } from "@/components/ui/separator"
import {
  Sheet,
  SheetContent,
  SheetDescription,
  SheetHeader,
  SheetTitle,
} from "@/components/ui/sheet"
import { Skeleton } from "@/components/ui/skeleton"
import {
  Tooltip,
  TooltipContent,
  TooltipProvider,
  TooltipTrigger,
} from "@/components/ui/tooltip"

const SIDEBAR_COOKIE_NAME = "sidebar_state"
const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7
const SIDEBAR_WIDTH = "16rem"
const SIDEBAR_WIDTH_MOBILE = "18rem"
const SIDEBAR_WIDTH_ICON = "3rem"
const SIDEBAR_KEYBOARD_SHORTCUT = "b"

type SidebarContextProps = {
  state: "expanded" | "collapsed"
  open: boolean
  setOpen: (open: boolean) => void
  openMobile: boolean
  setOpenMobile: (open: boolean) => void
  isMobile: boolean
  toggleSidebar: () => void
}

const SidebarContext = React.createContext<SidebarContextProps | null>(null)

function useSidebar() {
  const context = React.useContext(SidebarContext)
  if (!context) {
```

```
    throw new Error("useSidebar must be used within a SidebarProvider.")
  }

  return context
}

function SidebarProvider({
  defaultOpen = true,
  open: openProp,
  onOpenChange: setOpenProp,
  className,
  style,
  children,
  ...props
}: React.ComponentProps<"div"> & {
  defaultOpen?: boolean
  open?: boolean
  onOpenChange?: (open: boolean) => void
}) {
  const isMobile = useIsMobile()
  const [openMobile, setOpenMobile] = React.useState(false)

  const [_open, _setOpen] = React.useState(defaultOpen)
  const open = openProp ?? _open
  const setOpen = React.useCallback(
    (value: boolean | ((value: boolean) => boolean)) => {
      const openState = typeof value === "function" ? value(open) : value
      if (setOpenProp) {
        setOpenProp(openState)
      } else {
        _setOpen(openState)
      }

      document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState}; path=/; max-age=${SIDEBAR_COOKIE_MAX_AGE}`
    },
    [setOpenProp, open]
  )

  const toggleSidebar = React.useCallback(() => {
    return isMobile ? setOpenMobile((open) => !open) : setOpen((open) => !open)
  }, [isMobile, setOpen, setOpenMobile])

  React.useEffect(() => {
    const handleKeyDown = (event: KeyboardEvent) => {
      if (
        event.key === SIDEBAR_KEYBOARD_SHORTCUT &&
        (event.metaKey || event.ctrlKey)
      ) {
        event.preventDefault()
        toggleSidebar()
      }
    }
```

```
    window.addEventListener("keydown", handleKeyDown)
    return () => window.removeEventListener("keydown", handleKeyDown)
  }, [toggleSidebar])

  const state = open ? "expanded" : "collapsed"

  const contextValue = React.useMemo<SidebarContextProps>(
    () => ({
      state,
      open,
      setOpen,
      isMobile,
      openMobile,
      setOpenMobile,
      toggleSidebar,
    }),
    [state, open, setOpen, isMobile, openMobile, setOpenMobile, toggleSidebar]
  )

  return (
    <SidebarContext.Provider value={contextValue}>
      <TooltipProvider delayDuration={0}>
        <div
          data-slot="sidebar-wrapper"
          style={
            {
              "--sidebar-width": SIDEBAR_WIDTH,
              "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,
              ...style,
            } as React.CSSProperties
          }
          className={cn(
            "group/sidebar-wrapper has-data-[variant=inset]:bg-sidebar flex min-h-svh w-full",
            className
          )}
          {...props}
        >
          {children}
        </div>
      </TooltipProvider>
    </SidebarContext.Provider>
  )
}

function Sidebar({
  side = "left",
  variant = "sidebar",
  collapsible = "offcanvas",
  className,
  children,
  ...props
```

```
}: React.ComponentProps<"div"> & {
  side?: "left" | "right"
  variant?: "sidebar" | "floating" | "inset"
  collapsible?: "offcanvas" | "icon" | "none"
}) {
  const { isMobile, state, openMobile, setOpenMobile } = useSidebar()

  if (collapsible === "none") {
    return (
      <div
        data-slot="sidebar"
        className={cn(
          "bg-sidebar text-sidebar-foreground flex h-full w-[var(--sidebar-width)] flex-col",
          className
        )}
        {...props}
      >
        {children}
      </div>
    )
  }

  if (isMobile) {
    return (
      <Sheet open={openMobile} onOpenChange={setOpenMobile} {...props}>
        <SheetContent
          data-sidebar="sidebar"
          data-slot="sidebar"
          data-mobile="true"
          className="bg-sidebar text-sidebar-foreground w-[var(--sidebar-width)] p-0 [&>button]:hidden"
          style={
            {
              "--sidebar-width": SIDEBAR_WIDTH_MOBILE,
            } as React.CSSProperties
          }
          side={side}
        >
          <SheetHeader className="sr-only">
            <SheetTitle>Sidebar</SheetTitle>
            <SheetDescription>Displays the mobile sidebar.</SheetDescription>
          </SheetHeader>
          <div className="flex h-full w-full flex-col">{children}</div>
        </SheetContent>
      </Sheet>
    )
  }

  return (
    <div
      className="group peer text-sidebar-foreground hidden md:block"
      data-state={state}
      data-collapsible={state === "collapsed" ? collapsible : ""}
```

```
      data-variant={variant}
      data-side={side}
      data-slot="sidebar"
    >
      <div
        data-slot="sidebar-gap"
        className={cn(
          "relative w-[var(--sidebar-width)] bg-transparent transition-[width] duration-200 ease-linear",
          "group-data-[collapsible=offcanvas]:w-0",
          "group-data-[side=right]:rotate-180",
          variant === "floating" || variant === "inset"
            ? "group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)+var(--spacing-4))]"
            : "group-data-[collapsible=icon]:w-[var(--sidebar-width-icon)]"
        )}
      />
      <div
        data-slot="sidebar-container"
        className={cn(
          "fixed inset-y-0 z-10 hidden h-svh w-[var(--sidebar-width)] transition-[left,right,width] duration-200
   ease-linear md:flex",
          side === "left"
            ? "left-0 group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"
            : "right-0 group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar-width)*-1)]",
          variant === "floating" || variant === "inset"
            ? "p-2 group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)+var(--spacing-4)+2px)]"
            : "group-data-[collapsible=icon]:w-[var(--sidebar-width-icon)] group-data-[side=left]:border-r group
  -data-[side=right]:border-l",
          className
        )}
        {...props}
      >
        <div
          data-sidebar="sidebar"
          data-slot="sidebar-inner"
          className="bg-sidebar group-data-[variant=floating]:border-sidebar-border flex h-full w-full flex-col
  group-data-[variant=floating]:rounded-lg group-data-[variant=floating]:border group-data-[variant=floating]:shad
  ow-sm"
        >
          {children}
        </div>
      </div>
    </div>
  )
}

function SidebarTrigger({
  className,
  onClick,
  ...props
}: React.ComponentProps<typeof Button>) {
  const { toggleSidebar } = useSidebar()
```

```
  return (
    <Button
      data-sidebar="trigger"
      data-slot="sidebar-trigger"
      variant="ghost"
      size="icon"
      className={cn("h-7 w-7", className)}
      onClick={(event) => {
        onClick?.(event)
        toggleSidebar()
      }}
      {...props}
    >
      <PanelLeftIcon />
      <span className="sr-only">Toggle Sidebar</span>
    </Button>
  )
}

function SidebarRail({ className, ...props }: React.ComponentProps<"button">) {
  const { toggleSidebar } = useSidebar()

  return (
    <button
      data-sidebar="rail"
      data-slot="sidebar-rail"
      aria-label="Toggle Sidebar"
      tabIndex={-1}
      onClick={toggleSidebar}
      title="Toggle Sidebar"
      className={cn(
        "hover:after:bg-sidebar-border absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2 transition-all ease-l
  inear group-data-[side=left]:-right-4 group-data-[side=right]:left-0 after:absolute after:inset-y-0 after:left-1
  /2 after:w-[2px] sm:flex",
        "in-data-[side=left]:cursor-w-resize in-data-[side=right]:cursor-e-resize",
        "[[data-side=left][data-state=collapsed]_&]:cursor-e-resize [[data-side=right][data-state=collapsed]_&]:
  cursor-w-resize",
        "hover:group-data-[collapsible=offcanvas]:bg-sidebar group-data-[collapsible=offcanvas]:translate-x-0 gr
  oup-data-[collapsible=offcanvas]:after:left-full",
        "[[data-side=left][data-collapsible=offcanvas]_&]:-right-2",
        "[[data-side=right][data-collapsible=offcanvas]_&]:-left-2",
        className
      )}
      {...props}
    />
  )
}

function SidebarInset({ className, ...props }: React.ComponentProps<"main">) {
  return (
    <main
      data-slot="sidebar-inset"
```

```
      className={cn(
        "bg-background relative flex w-full flex-1 flex-col",
        "md:peer-data-[variant=inset]:m-2 md:peer-data-[variant=inset]:ml-0 md:peer-data-[variant=inset]:rounded
  -xl md:peer-data-[variant=inset]:shadow-sm md:peer-data-[variant=inset]:peer-data-[state=collapsed]:ml-2",
        className
      )}
      {...props}
    />
  )
}

function SidebarInput({
  className,
  ...props
}: React.ComponentProps<typeof Input>) {
  return (
    <Input
      data-slot="sidebar-input"
      data-sidebar="input"
      className={cn("bg-background h-8 w-full shadow-none", className)}
      {...props}
    />
  )
}

function SidebarHeader({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-header"
      data-sidebar="header"
      className={cn("flex flex-col gap-2 p-2", className)}
      {...props}
    />
  )
}

function SidebarFooter({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-footer"
      data-sidebar="footer"
      className={cn("flex flex-col gap-2 p-2", className)}
      {...props}
    />
  )
}

function SidebarSeparator({
  className,
  ...props
}: React.ComponentProps<typeof Separator>) {
  return (
```

```
    <Separator
      data-slot="sidebar-separator"
      data-sidebar="separator"
      className={cn("bg-sidebar-border mx-2 w-auto", className)}
      {...props}
    />
  )
}

function SidebarContent({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-content"
      data-sidebar="content"
      className={cn(
        "flex min-h-0 flex-1 flex-col gap-2 overflow-auto group-data-[collapsible=icon]:overflow-hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-group"
      data-sidebar="group"
      className={cn("relative flex w-full min-w-0 flex-col p-2", className)}
      {...props}
    />
  )
}

function SidebarGroupLabel({
  className,
  asChild = false,
  ...props
}: React.ComponentProps<"div"> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "div"

  return (
    <Comp
      data-slot="sidebar-group-label"
      data-sidebar="group-label"
      className={cn(
        "text-sidebar-foreground/70 ring-sidebar-ring flex h-8 shrink-0 items-center rounded-md px-2 text-xs fon
  t-medium outline-hidden transition-[margin,opacity] duration-200 ease-linear focus-visible:ring-2 [&>svg]:h-4 [&
  >svg]:w-4 [&>svg]:shrink-0",
        "group-data-[collapsible=icon]:-mt-8 group-data-[collapsible=icon]:opacity-0",
        className
      )}
```

```
      {...props}
    />
  )
}

function SidebarGroupAction({
  className,
  asChild = false,
  ...props
}: React.ComponentProps<"button"> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "button"

  return (
    <Comp
      data-slot="sidebar-group-action"
      data-sidebar="group-action"
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
  absolute top-3.5 right-3 flex aspect-square w-5 items-center justify-center rounded-md p-0 outline-hidden transi
  tion-transform focus-visible:ring-2 [&>svg]:size-4 [&>svg]:shrink-0",
        "after:absolute after:-inset-2 md:after:hidden",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarGroupContent({
  className,
  ...props
}: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-group-content"
      data-sidebar="group-content"
      className={cn("w-full text-sm", className)}
      {...props}
    />
  )
}

function SidebarMenu({ className, ...props }: React.ComponentProps<"ul">) {
  return (
    <ul
      data-slot="sidebar-menu"
      data-sidebar="menu"
      className={cn("flex w-full min-w-0 flex-col gap-1", className)}
      {...props}
    />
  )
```

```
}

function SidebarMenuItem({ className, ...props }: React.ComponentProps<"li">) {
  return (
    <li
      data-slot="sidebar-menu-item"
      data-sidebar="menu-item"
      className={cn("group/menu-item relative", className)}
      {...props}
    />
  )
}

const sidebarMenuButtonVariants = cva(
  "peer/menu-button flex w-full items-center gap-2 overflow-hidden rounded-md p-2 text-left text-sm outline-hidd
  en ring-sidebar-ring transition-[width,height,padding] hover:bg-sidebar-accent hover:text-sidebar-accent-foregro
  und focus-visible:ring-2 active:bg-sidebar-accent active:text-sidebar-accent-foreground disabled:pointer-events-
  none disabled:opacity-50 group-has-data-[sidebar=menu-action]/menu-item:pr-8 aria-disabled:pointer-events-none a
  ria-disabled:opacity-50 data-[active=true]:bg-sidebar-accent data-[active=true]:font-medium data-[active=true]:t
  ext-sidebar-accent-foreground data-[state=open]:hover:bg-sidebar-accent data-[state=open]:hover:text-sidebar-acc
  ent-foreground group-data-[collapsible=icon]:w-8! group-data-[collapsible=icon]:h-8! group-data-[collapsible=ico
  n]:p-2! [&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "hover:bg-sidebar-accent hover:text-sidebar-accent-foreground",
        outline:
          "bg-background shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent hover:text-sideba
  r-accent-foreground hover:shadow-[0_0_0_1px_hsl(var(--sidebar-accent))]",
      },
      size: {
        default: "h-8 text-sm",
        sm: "h-7 text-xs",
        lg: "h-12 text-sm group-data-[collapsible=icon]:p-0!",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
)

function SidebarMenuButton({
  asChild = false,
  isActive = false,
  variant = "default",
  size = "default",
  tooltip,
  className,
  ...props
}: React.ComponentProps<"button"> & {
```

```
  asChild?: boolean
  isActive?: boolean
  tooltip?: string | React.ComponentProps<typeof TooltipContent>
} & VariantProps<typeof sidebarMenuButtonVariants>) {
  const Comp = asChild ? Slot : "button"
  const { isMobile, state } = useSidebar()

  const button = (
    <Comp
      data-slot="sidebar-menu-button"
      data-sidebar="menu-button"
      data-size={size}
      data-active={isActive}
      className={cn(sidebarMenuButtonVariants({ variant, size }), className)}
      {...props}
    />
  )

  if (!tooltip) {
    return button
  }

  if (typeof tooltip === "string") {
    tooltip = {
      children: tooltip,
    }
  }

  return (
    <Tooltip>
      <TooltipTrigger asChild>{button}</TooltipTrigger>
      <TooltipContent
        side="right"
        align="center"
        hidden={state !== "collapsed" || isMobile}
        {...tooltip}
      />
    </Tooltip>
  )
}

function SidebarMenuAction({
  className,
  asChild = false,
  showOnHover = false,
  ...props
}: React.ComponentProps<"button"> & {
  asChild?: boolean
  showOnHover?: boolean
}) {
  const Comp = asChild ? Slot : "button"
```

```
  return (
    <Comp
      data-slot="sidebar-menu-action"
      data-sidebar="menu-action"
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
  peer-hover/menu-button:text-sidebar-accent-foreground absolute top-1.5 right-1 flex aspect-square w-5 items-cent
  er justify-center rounded-md p-0 outline-hidden transition-transform focus-visible:ring-2 [&>svg]:size-4 [&>svg]
  :shrink-0",
        "after:absolute after:-inset-2 md:after:hidden",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        showOnHover &&
          "peer-data-[active=true]/menu-button:text-sidebar-accent-foreground group-focus-within/menu-item:opaci
  ty-100 group-hover/menu-item:opacity-100 data-[state=open]:opacity-100 md:opacity-0",
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuBadge({
  className,
  ...props
}: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-menu-badge"
      data-sidebar="menu-badge"
      className={cn(
        "text-sidebar-foreground pointer-events-none absolute right-1 flex h-5 min-w-5 items-center justify-cent
  er rounded-md px-1 text-xs font-medium tabular-nums select-none",
        "peer-hover/menu-button:text-sidebar-accent-foreground peer-data-[active=true]/menu-button:text-sidebar-
  accent-foreground",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuSkeleton({
  className,
  showIcon = false,
  ...props
```

```
}: React.ComponentProps<"div"> & {
  showIcon?: boolean
}) {
  const width = React.useMemo(() => {
    return `${Math.floor(Math.random() * 40) + 50}%`
  }, [])

  return (
    <div
      data-slot="sidebar-menu-skeleton"
      data-sidebar="menu-skeleton"
      className={cn("flex h-8 items-center gap-2 rounded-md px-2", className)}
      {...props}
    >
      {showIcon && (
        <Skeleton
          className="size-4 rounded-md"
          data-sidebar="menu-skeleton-icon"
        />
      )}
      <Skeleton
        className="h-4 max-w-[var(--skeleton-width)] flex-1"
        data-sidebar="menu-skeleton-text"
        style={
          {
            "--skeleton-width": width,
          } as React.CSSProperties
        }
      />
    </div>
  )
}

function SidebarMenuSub({ className, ...props }: React.ComponentProps<"ul">) {
  return (
    <ul
      data-slot="sidebar-menu-sub"
      data-sidebar="menu-sub"
      className={cn(
        "border-sidebar-border mx-3.5 flex min-w-0 translate-x-px flex-col gap-1 border-l px-2.5 py-0.5",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuSubItem({
  className,
  ...props
}: React.ComponentProps<"li">) {
```

```
  return (
    <li
      data-slot="sidebar-menu-sub-item"
      data-sidebar="menu-sub-item"
      className={cn("group/menu-sub-item relative", className)}
      {...props}
    />
  )
}

function SidebarMenuSubButton({
  asChild = false,
  size = "md",
  isActive = false,
  className,
  ...props
}: React.ComponentProps<"a"> & {
  asChild?: boolean
  size?: "sm" | "md"
  isActive?: boolean
}) {
  const Comp = asChild ? Slot : "a"

  return (
    <Comp
      data-slot="sidebar-menu-sub-button"
      data-sidebar="menu-sub-button"
      data-size={size}
      data-active={isActive}
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
  active:bg-sidebar-accent active:text-sidebar-accent-foreground [&>svg]:text-sidebar-accent-foreground flex h-7 m
  in-w-0 -translate-x-px items-center gap-2 overflow-hidden rounded-md px-2 outline outline-2 outline-transparent
  outline-offset-2 focus-visible:ring-2 disabled:pointer-events-none disabled:opacity-50 aria-disabled:pointer-eve
  nts-none aria-disabled:opacity-50 [&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0",
        "data-[active=true]:bg-sidebar-accent data-[active=true]:text-sidebar-accent-foreground",
        size === "sm" && "text-xs",
        size === "md" && "text-sm",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

export {
  Sidebar,
  SidebarContent,
  SidebarFooter,
  SidebarGroup,
  SidebarGroupAction,
```

```
  SidebarGroupContent,
  SidebarGroupLabel,
  SidebarHeader,
  SidebarInput,
  SidebarInset,
  SidebarMenu,
  SidebarMenuAction,
  SidebarMenuBadge,
  SidebarMenuButton,
  SidebarMenuItem,
  SidebarMenuSkeleton,
  SidebarMenuSub,
  SidebarMenuSubButton,
  SidebarMenuSubItem,
  SidebarProvider,
  SidebarRail,
  SidebarSeparator,
  SidebarTrigger,
  useSidebar,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/skeleton.tsx
SIZE: 266 bytes

```
import { cn } from "@/lib/utils"

function Skeleton({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) {
  return (
    <div
      className={cn("animate-pulse rounded-md bg-primary/10", className)}
      {...props}
    />
  )
}

export { Skeleton }
```

FILE: artifacts/mockup-sandbox/src/components/ui/slider.tsx
SIZE: 1,037 bytes

```
import * as React from "react"
import * as SliderPrimitive from "@radix-ui/react-slider"

import { cn } from "@/lib/utils"

const Slider = React.forwardRef<
  React.ElementRef<typeof SliderPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof SliderPrimitive.Root>
>(({ className, ...props }, ref) => (
  <SliderPrimitive.Root
    ref={ref}
    className={cn(
      "relative flex w-full touch-none select-none items-center",
      className
    )}
    {...props}
  >
    <SliderPrimitive.Track className="relative h-1.5 w-full grow overflow-hidden rounded-full bg-primary/20">
      <SliderPrimitive.Range className="absolute h-full bg-primary" />
    </SliderPrimitive.Track>
    <SliderPrimitive.Thumb className="block h-4 w-4 rounded-full border border-primary/50 bg-background shadow t
  ransition-colors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:pointer-events
  -none disabled:opacity-50" />
  </SliderPrimitive.Root>
))
Slider.displayName = SliderPrimitive.Root.displayName

export { Slider }
```

FILE: artifacts/mockup-sandbox/src/components/ui/sonner.tsx
SIZE: 894 bytes

```
"use client"

import { useTheme } from "next-themes"
import { Toaster as Sonner } from "sonner"

type ToasterProps = React.ComponentProps<typeof Sonner>

const Toaster = ({ ...props }: ToasterProps) => {
  const { theme = "system" } = useTheme()

  return (
    <Sonner
      theme={theme as ToasterProps["theme"]}
      className="toaster group"
      toastOptions={{
        classNames: {
          toast:
            "group toast group-[.toaster]:bg-background group-[.toaster]:text-foreground group-[.toaster]:border
  -border group-[.toaster]:shadow-lg",
          description: "group-[.toast]:text-muted-foreground",
          actionButton:
            "group-[.toast]:bg-primary group-[.toast]:text-primary-foreground",
          cancelButton:
            "group-[.toast]:bg-muted group-[.toast]:text-muted-foreground",
        },
      }}
      {...props}
    />
  )
}

export { Toaster }
```

FILE: artifacts/mockup-sandbox/src/components/ui/spinner.tsx
SIZE: 331 bytes

```
import { Loader2Icon } from "lucide-react"

import { cn } from "@/lib/utils"

function Spinner({ className, ...props }: React.ComponentProps<"svg">) {
  return (
    <Loader2Icon
      role="status"
      aria-label="Loading"
      className={cn("size-4 animate-spin", className)}
      {...props}
    />
  )
}

export { Spinner }
```

FILE: artifacts/mockup-sandbox/src/components/ui/switch.tsx
SIZE: 1,148 bytes

```
import * as React from "react"
import * as SwitchPrimitives from "@radix-ui/react-switch"

import { cn } from "@/lib/utils"

const Switch = React.forwardRef<
  React.ElementRef<typeof SwitchPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof SwitchPrimitives.Root>
>(({ className, ...props }, ref) => (
  <SwitchPrimitives.Root
    className={cn(
      "peer inline-flex h-5 w-9 shrink-0 cursor-pointer items-center rounded-full border-2 border-transparent sh
  adow-sm transition-colors focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:
  ring-offset-2 focus-visible:ring-offset-background disabled:cursor-not-allowed disabled:opacity-50 data-[state=c
  hecked]:bg-primary data-[state=unchecked]:bg-input",
      className
    )}
    {...props}
    ref={ref}
  >
    <SwitchPrimitives.Thumb
      className={cn(
        "pointer-events-none block h-4 w-4 rounded-full bg-background shadow-lg ring-0 transition-transform data
  -[state=checked]:translate-x-4 data-[state=unchecked]:translate-x-0"
      )}
    />
  </SwitchPrimitives.Root>
))
Switch.displayName = SwitchPrimitives.Root.displayName

export { Switch }
```

FILE: artifacts/mockup-sandbox/src/components/ui/table.tsx
SIZE: 2,859 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Table = React.forwardRef<
  HTMLTableElement,
  React.HTMLAttributes<HTMLTableElement>
>(({ className, ...props }, ref) => (
  <div className="relative w-full overflow-auto">
    <table
      ref={ref}
      className={cn("w-full caption-bottom text-sm", className)}
      {...props}
    />
  </div>
))
Table.displayName = "Table"

const TableHeader = React.forwardRef<
  HTMLTableSectionElement,
  React.HTMLAttributes<HTMLTableSectionElement>
>(({ className, ...props }, ref) => (
  <thead ref={ref} className={cn("[&_tr]:border-b", className)} {...props} />
))
TableHeader.displayName = "TableHeader"

const TableBody = React.forwardRef<
  HTMLTableSectionElement,
  React.HTMLAttributes<HTMLTableSectionElement>
>(({ className, ...props }, ref) => (
  <tbody
    ref={ref}
    className={cn("[&_tr:last-child]:border-0", className)}
    {...props}
  />
))
TableBody.displayName = "TableBody"

const TableFooter = React.forwardRef<
  HTMLTableSectionElement,
  React.HTMLAttributes<HTMLTableSectionElement>
>(({ className, ...props }, ref) => (
  <tfoot
    ref={ref}
    className={cn(
      "border-t bg-muted/50 font-medium [&>tr]:last:border-b-0",
      className
    )}
    {...props}
```

```
  />
))
TableFooter.displayName = "TableFooter"

const TableRow = React.forwardRef<
  HTMLTableRowElement,
  React.HTMLAttributes<HTMLTableRowElement>
>(({ className, ...props }, ref) => (
  <tr
    ref={ref}
    className={cn(
      "border-b transition-colors hover:bg-muted/50 data-[state=selected]:bg-muted",
      className
    )}
    {...props}
  />
))
TableRow.displayName = "TableRow"

const TableHead = React.forwardRef<
  HTMLTableCellElement,
  React.ThHTMLAttributes<HTMLTableCellElement>
>(({ className, ...props }, ref) => (
  <th
    ref={ref}
    className={cn(
      "h-10 px-2 text-left align-middle font-medium text-muted-foreground [&:has([role=checkbox])]:pr-0 [&>[role
  =checkbox]]:translate-y-[2px]",
      className
    )}
    {...props}
  />
))
TableHead.displayName = "TableHead"

const TableCell = React.forwardRef<
  HTMLTableCellElement,
  React.TdHTMLAttributes<HTMLTableCellElement>
>(({ className, ...props }, ref) => (
  <td
    ref={ref}
    className={cn(
      "p-2 align-middle [&:has([role=checkbox])]:pr-0 [&>[role=checkbox]]:translate-y-[2px]",
      className
    )}
    {...props}
  />
))
TableCell.displayName = "TableCell"

const TableCaption = React.forwardRef<
  HTMLTableCaptionElement,
```

```
  React.HTMLAttributes<HTMLTableCaptionElement>
>(({ className, ...props }, ref) => (
  <caption
    ref={ref}
    className={cn("mt-4 text-sm text-muted-foreground", className)}
    {...props}
  />
))
TableCaption.displayName = "TableCaption"

export {
  Table,
  TableHeader,
  TableBody,
  TableFooter,
  TableHead,
  TableRow,
  TableCell,
  TableCaption,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/tabs.tsx
SIZE: 1,877 bytes

```
import * as React from "react"
import * as TabsPrimitive from "@radix-ui/react-tabs"

import { cn } from "@/lib/utils"

const Tabs = TabsPrimitive.Root

const TabsList = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.List>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.List
    ref={ref}
    className={cn(
      "inline-flex h-9 items-center justify-center rounded-lg bg-muted p-1 text-muted-foreground",
      className
    )}
    {...props}
  />
))
TabsList.displayName = TabsPrimitive.List.displayName

const TabsTrigger = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Trigger
    ref={ref}
    className={cn(
      "inline-flex items-center justify-center whitespace-nowrap rounded-md px-3 py-1 text-sm font-medium ring-o
  ffset-background transition-all focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-vi
  sible:ring-offset-2 disabled:pointer-events-none disabled:opacity-50 data-[state=active]:bg-background data-[sta
  te=active]:text-foreground data-[state=active]:shadow",
      className
    )}
    {...props}
  />
))
TabsTrigger.displayName = TabsPrimitive.Trigger.displayName

const TabsContent = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Content>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Content
    ref={ref}
    className={cn(
      "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus
  -visible:ring-offset-2",
```

```
      className
    )}
    {...props}
  />
))
TabsContent.displayName = TabsPrimitive.Content.displayName

export { Tabs, TabsList, TabsTrigger, TabsContent }
```

FILE: artifacts/mockup-sandbox/src/components/ui/textarea.tsx
SIZE: 649 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Textarea = React.forwardRef<
  HTMLTextAreaElement,
  React.ComponentProps<"textarea">
>(({ className, ...props }, ref) => {
  return (
    <textarea
      className={cn(
        "flex min-h-[60px] w-full rounded-md border border-input bg-transparent px-3 py-2 text-base shadow-sm pl
  aceholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled
  :cursor-not-allowed disabled:opacity-50 md:text-sm",
        className
      )}
      ref={ref}
      {...props}
    />
  )
})
Textarea.displayName = "Textarea"

export { Textarea }
```

FILE: artifacts/mockup-sandbox/src/components/ui/toast.tsx
SIZE: 4,845 bytes

```
import * as React from "react"
import * as ToastPrimitives from "@radix-ui/react-toast"
import { cva, type VariantProps } from "class-variance-authority"
import { X } from "lucide-react"

import { cn } from "@/lib/utils"

const ToastProvider = ToastPrimitives.Provider

const ToastViewport = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Viewport>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Viewport
    ref={ref}
    className={cn(
      "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto sm:f
  lex-col md:max-w-[420px]",
      className
    )}
    {...props}
  />
))
ToastViewport.displayName = ToastPrimitives.Viewport.displayName

const toastVariants = cva(
  "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-hidden rounded
  -md border p-6 pr-8 shadow-lg transition-all data-[swipe=cancel]:translate-x-0 data-[swipe=end]:translate-x-[var
  (--radix-toast-swipe-end-x)] data-[swipe=move]:translate-x-[var(--radix-toast-swipe-move-x)] data-[swipe=move]:t
  ransition-none data-[state=open]:animate-in data-[state=closed]:animate-out data-[swipe=end]:animate-out data-[s
  tate=closed]:fade-out-80 data-[state=closed]:slide-out-to-right-full data-[state=open]:slide-in-from-top-full da
  ta-[state=open]:sm:slide-in-from-bottom-full",
  {
    variants: {
      variant: {
        default: "border bg-background text-foreground",
        destructive:
          "destructive group border-destructive bg-destructive text-destructive-foreground",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Toast = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> &
```

```
    VariantProps<typeof toastVariants>
>(({ className, variant, ...props }, ref) => {
  return (
    <ToastPrimitives.Root
      ref={ref}
      className={cn(toastVariants({ variant }), className)}
      {...props}
    />
  )
})
Toast.displayName = ToastPrimitives.Root.displayName

const ToastAction = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Action>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Action
    ref={ref}
    className={cn(
      "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3 text-sm font-m
  edium ring-offset-background transition-colors hover:bg-secondary focus:outline-none focus:ring-2 focus:ring-rin
  g focus:ring-offset-2 disabled:pointer-events-none disabled:opacity-50 group-[.destructive]:border-muted/40 grou
  p-[.destructive]:hover:border-destructive/30 group-[.destructive]:hover:bg-destructive group-[.destructive]:hove
  r:text-destructive-foreground group-[.destructive]:focus:ring-destructive",
      className
    )}
    {...props}
  />
))
ToastAction.displayName = ToastPrimitives.Action.displayName

const ToastClose = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Close>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Close
    ref={ref}
    className={cn(
      "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity hover:text-foregrou
  nd focus:opacity-100 focus:outline-none focus:ring-2 group-hover:opacity-100 group-[.destructive]:text-red-300 g
  roup-[.destructive]:hover:text-red-50 group-[.destructive]:focus:ring-red-400 group-[.destructive]:focus:ring-of
  fset-red-600",
      className
    )}
    toast-close=""
    {...props}
  >
    <X className="h-4 w-4" />
  </ToastPrimitives.Close>
))
ToastClose.displayName = ToastPrimitives.Close.displayName
```

```
const ToastTitle = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Title>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Title
    ref={ref}
    className={cn("text-sm font-semibold", className)}
    {...props}
  />
))
ToastTitle.displayName = ToastPrimitives.Title.displayName

const ToastDescription = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Description>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Description
    ref={ref}
    className={cn("text-sm opacity-90", className)}
    {...props}
  />
))
ToastDescription.displayName = ToastPrimitives.Description.displayName

type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>

type ToastActionElement = React.ReactElement<typeof ToastAction>

export {
  type ToastProps,
  type ToastActionElement,
  ToastProvider,
  ToastViewport,
  Toast,
  ToastTitle,
  ToastDescription,
  ToastClose,
  ToastAction,
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/toaster.tsx
SIZE: 772 bytes

```
import { useToast } from "@/hooks/use-toast"
import {
  Toast,
  ToastClose,
  ToastDescription,
  ToastProvider,
  ToastTitle,
  ToastViewport,
} from "@/components/ui/toast"

export function Toaster() {
  const { toasts } = useToast()

  return (
    <ToastProvider>
      {toasts.map(function ({ id, title, description, action, ...props }) {
        return (
          <Toast key={id} {...props}>
            <div className="grid gap-1">
              {title && <ToastTitle>{title}</ToastTitle>}
              {description && (
                <ToastDescription>{description}</ToastDescription>
              )}
            </div>
            {action}
            <ToastClose />
          </Toast>
        )
      })}
      <ToastViewport />
    </ToastProvider>
  )
}
```

FILE: artifacts/mockup-sandbox/src/components/ui/toggle-group.tsx
SIZE: 1,753 bytes

```
"use client"

import * as React from "react"
import * as ToggleGroupPrimitive from "@radix-ui/react-toggle-group"
import { type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { toggleVariants } from "@/components/ui/toggle"

const ToggleGroupContext = React.createContext<
  VariantProps<typeof toggleVariants>
>({
  size: "default",
  variant: "default",
})

const ToggleGroup = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Root> &
    VariantProps<typeof toggleVariants>
>(({ className, variant, size, children, ...props }, ref) => (
  <ToggleGroupPrimitive.Root
    ref={ref}
    className={cn("flex items-center justify-center gap-1", className)}
    {...props}
  >
    <ToggleGroupContext.Provider value={{ variant, size }}>
      {children}
    </ToggleGroupContext.Provider>
  </ToggleGroupPrimitive.Root>
))

ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName

const ToggleGroupItem = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Item> &
    VariantProps<typeof toggleVariants>
>(({ className, children, variant, size, ...props }, ref) => {
  const context = React.useContext(ToggleGroupContext)

  return (
    <ToggleGroupPrimitive.Item
      ref={ref}
      className={cn(
        toggleVariants({
          variant: context.variant || variant,
          size: context.size || size,
        }),
```

```
        className
      )}
      {...props}
    >
      {children}
    </ToggleGroupPrimitive.Item>
  )
})

ToggleGroupItem.displayName = ToggleGroupPrimitive.Item.displayName

export { ToggleGroup, ToggleGroupItem }
```

FILE: artifacts/mockup-sandbox/src/components/ui/toggle.tsx
SIZE: 1,486 bytes

```
import * as React from "react"
import * as TogglePrimitive from "@radix-ui/react-toggle"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const toggleVariants = cva(
  "inline-flex items-center justify-center gap-2 rounded-md text-sm font-medium transition-colors hover:bg-muted
   hover:text-muted-foreground focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:po
  inter-events-none disabled:opacity-50 data-[state=on]:bg-accent data-[state=on]:text-accent-foreground [&_svg]:p
  ointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        outline:
          "border border-input bg-transparent shadow-sm hover:bg-accent hover:text-accent-foreground",
      },
      size: {
        default: "h-9 px-2 min-w-9",
        sm: "h-8 px-1.5 min-w-8",
        lg: "h-10 px-2.5 min-w-10",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
)

const Toggle = React.forwardRef<
  React.ElementRef<typeof TogglePrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof TogglePrimitive.Root> &
    VariantProps<typeof toggleVariants>
>(({ className, variant, size, ...props }, ref) => (
  <TogglePrimitive.Root
    ref={ref}
    className={cn(toggleVariants({ variant, size, className }))}
    {...props}
  />
))

Toggle.displayName = TogglePrimitive.Root.displayName

export { Toggle, toggleVariants }
```

FILE: artifacts/mockup-sandbox/src/components/ui/tooltip.tsx
SIZE: 1,267 bytes

```
"use client"

import * as React from "react"
import * as TooltipPrimitive from "@radix-ui/react-tooltip"

import { cn } from "@/lib/utils"

const TooltipProvider = TooltipPrimitive.Provider

const Tooltip = TooltipPrimitive.Root

const TooltipTrigger = TooltipPrimitive.Trigger

const TooltipContent = React.forwardRef<
  React.ElementRef<typeof TooltipPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof TooltipPrimitive.Content>
>(({ className, sideOffset = 4, ...props }, ref) => (
  <TooltipPrimitive.Portal>
    <TooltipPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 overflow-hidden rounded-md bg-primary px-3 py-1.5 text-xs text-primary-foreground animate-in fade-
  in-0 zoom-in-95 data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=closed]:zoom-out-95 d
  ata-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-lef
  t-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-tooltip-content-transform-origin]",
        className
      )}
      {...props}
    />
  </TooltipPrimitive.Portal>
))
TooltipContent.displayName = TooltipPrimitive.Content.displayName

export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider }
```

FILE: artifacts/mockup-sandbox/src/hooks/use-mobile.tsx
SIZE: 565 bytes

```
import * as React from "react"

const MOBILE_BREAKPOINT = 768

export function useIsMobile() {
  const [isMobile, setIsMobile] = React.useState<boolean | undefined>(undefined)

  React.useEffect(() => {
    const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`)
    const onChange = () => {
      setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    }
    mql.addEventListener("change", onChange)
    setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    return () => mql.removeEventListener("change", onChange)
  }, [])

  return !!isMobile
}
```

FILE: artifacts/mockup-sandbox/src/hooks/use-toast.ts
SIZE: 3,767 bytes

```
import * as React from "react"

import type {
  ToastActionElement,
  ToastProps,
} from "@/components/ui/toast"

const TOAST_LIMIT = 1
const TOAST_REMOVE_DELAY = 1000000

type ToasterToast = ToastProps & {
  id: string
  title?: React.ReactNode
  description?: React.ReactNode
  action?: ToastActionElement
}

const actionTypes = {
  ADD_TOAST: "ADD_TOAST",
  UPDATE_TOAST: "UPDATE_TOAST",
  DISMISS_TOAST: "DISMISS_TOAST",
  REMOVE_TOAST: "REMOVE_TOAST",
} as const

let count = 0

function genId() {
  count = (count + 1) % Number.MAX_SAFE_INTEGER
  return count.toString()
}

type ActionType = typeof actionTypes

type Action =
  | {
      type: ActionType["ADD_TOAST"]
      toast: ToasterToast
    }
  | {
      type: ActionType["UPDATE_TOAST"]
      toast: Partial<ToasterToast>
    }
  | {
      type: ActionType["DISMISS_TOAST"]
      toastId?: ToasterToast["id"]
    }
  | {
      type: ActionType["REMOVE_TOAST"]
      toastId?: ToasterToast["id"]
```

```
    }

interface State {
  toasts: ToasterToast[]
}

const toastTimeouts = new Map<string, ReturnType<typeof setTimeout>>()

const addToRemoveQueue = (toastId: string) => {
  if (toastTimeouts.has(toastId)) {
    return
  }

  const timeout = setTimeout(() => {
    toastTimeouts.delete(toastId)
    dispatch({
      type: "REMOVE_TOAST",
      toastId: toastId,
    })
  }, TOAST_REMOVE_DELAY)

  toastTimeouts.set(toastId, timeout)
}

export const reducer = (state: State, action: Action): State => {
  switch (action.type) {
    case "ADD_TOAST":
      return {
        ...state,
        toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
      }

    case "UPDATE_TOAST":
      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === action.toast.id ? { ...t, ...action.toast } : t
        ),
      }

    case "DISMISS_TOAST": {
      const { toastId } = action

      if (toastId) {
        addToRemoveQueue(toastId)
      } else {
        state.toasts.forEach((toast) => {
          addToRemoveQueue(toast.id)
        })
      }

      return {
```

```
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === toastId || toastId === undefined
            ? {
                ...t,
                open: false,
              }
            : t
        ),
      }
    }
    case "REMOVE_TOAST":
      if (action.toastId === undefined) {
        return {
          ...state,
          toasts: [],
        }
      }
      return {
        ...state,
        toasts: state.toasts.filter((t) => t.id !== action.toastId),
      }
  }
}

const listeners: Array<(state: State) => void> = []

let memoryState: State = { toasts: [] }

function dispatch(action: Action) {
  memoryState = reducer(memoryState, action)
  listeners.forEach((listener) => {
    listener(memoryState)
  })
}

type Toast = Omit<ToasterToast, "id">

function toast({ ...props }: Toast) {
  const id = genId()

  const update = (props: ToasterToast) =>
    dispatch({
      type: "UPDATE_TOAST",
      toast: { ...props, id },
    })
  const dismiss = () => dispatch({ type: "DISMISS_TOAST", toastId: id })

  dispatch({
    type: "ADD_TOAST",
    toast: {
      ...props,
```

```
      id,
      open: true,
      onOpenChange: (open) => {
        if (!open) dismiss()
      },
    },
  })

  return {
    id: id,
    dismiss,
    update,
  }
}

function useToast() {
  const [state, setState] = React.useState<State>(memoryState)

  React.useEffect(() => {
    listeners.push(setState)
    return () => {
      const index = listeners.indexOf(setState)
      if (index > -1) {
        listeners.splice(index, 1)
      }
    }
  }, [state])

  return {
    ...state,
    toast,
    dismiss: (toastId?: string) => dispatch({ type: "DISMISS_TOAST", toastId }),
  }
}

export { useToast, toast }
```

FILE: artifacts/mockup-sandbox/src/index.css
SIZE: 4,967 bytes

```
@import "tailwindcss";
@import "tw-animate-css";

@custom-variant dark (&:is(.dark *));

@theme inline {
  --radius-sm: calc(var(--radius) - 4px);
  --radius-md: calc(var(--radius) - 2px);
  --radius-lg: var(--radius);
  --radius-xl: calc(var(--radius) + 4px);
  --color-background: hsl(var(--background));
  --color-foreground: hsl(var(--foreground));
  --color-card: hsl(var(--card));
  --color-card-foreground: hsl(var(--card-foreground));
  --color-popover: hsl(var(--popover));
  --color-popover-foreground: hsl(var(--popover-foreground));
  --color-primary: hsl(var(--primary));
  --color-primary-foreground: hsl(var(--primary-foreground));
  --color-secondary: hsl(var(--secondary));
  --color-secondary-foreground: hsl(var(--secondary-foreground));
  --color-muted: hsl(var(--muted));
  --color-muted-foreground: hsl(var(--muted-foreground));
  --color-accent: hsl(var(--accent));
  --color-accent-foreground: hsl(var(--accent-foreground));
  --color-destructive: hsl(var(--destructive));
  --color-destructive-foreground: hsl(var(--destructive-foreground));
  --color-border: hsl(var(--border));
  --color-input: hsl(var(--input));
  --color-ring: hsl(var(--ring));
  --color-chart-1: hsl(var(--chart-1));
  --color-chart-2: hsl(var(--chart-2));
  --color-chart-3: hsl(var(--chart-3));
  --color-chart-4: hsl(var(--chart-4));
  --color-chart-5: hsl(var(--chart-5));
  --color-sidebar: hsl(var(--sidebar));
  --color-sidebar-foreground: hsl(var(--sidebar-foreground));
  --color-sidebar-primary: hsl(var(--sidebar-primary));
  --color-sidebar-primary-foreground: hsl(var(--sidebar-primary-foreground));
  --color-sidebar-accent: hsl(var(--sidebar-accent));
  --color-sidebar-accent-foreground: hsl(var(--sidebar-accent-foreground));
  --color-sidebar-border: hsl(var(--sidebar-border));
  --color-sidebar-ring: hsl(var(--sidebar-ring));
}

/* LIGHT MODE - Default theme with placeholder values */
:root {
  --button-outline: rgba(0,0,0, .10);
  --badge-outline: rgba(0,0,0, .05);
  --opaque-button-border-intensity: -8;
```

```
  --elevate-1: rgba(0,0,0, .03);
  --elevate-2: rgba(0,0,0, .08);

  --background: 0 0% 100%;
  --foreground: 240 10% 3.9%;
  --card: 0 0% 100%;
  --card-foreground: 240 10% 3.9%;
  --popover: 0 0% 100%;
  --popover-foreground: 240 10% 3.9%;
  --primary: 240 5.9% 10%;
  --primary-foreground: 0 0% 98%;
  --secondary: 240 4.8% 95.9%;
  --secondary-foreground: 240 5.9% 10%;
  --muted: 240 4.8% 95.9%;
  --muted-foreground: 240 3.8% 46.1%;
  --accent: 240 4.8% 95.9%;
  --accent-foreground: 240 5.9% 10%;
  --destructive: 0 84.2% 60.2%;
  --destructive-foreground: 0 0% 98%;
  --border: 240 5.9% 90%;
  --input: 240 5.9% 90%;
  --ring: 240 5.9% 10%;
  --chart-1: 12 76% 61%;
  --chart-2: 173 58% 39%;
  --chart-3: 197 37% 24%;
  --chart-4: 43 74% 66%;
  --chart-5: 27 87% 67%;
  --sidebar: 0 0% 98%;
  --sidebar-foreground: 240 5.3% 26.1%;
  --sidebar-primary: 240 5.9% 10%;
  --sidebar-primary-foreground: 0 0% 98%;
  --sidebar-accent: 240 4.8% 95.9%;
  --sidebar-accent-foreground: 240 5.9% 10%;
  --sidebar-border: 220 13% 91%;
  --sidebar-ring: 240 5.9% 10%;

  --font-sans: 'Inter', sans-serif;
  --font-serif: Georgia, serif;
  --font-mono: Menlo, monospace;
  --radius: .5rem;
  --spacing: 0.25rem;
}

/* DARK MODE */
.dark {
  --button-outline: rgba(255,255,255, .10);
  --badge-outline: rgba(255,255,255, .05);
  --opaque-button-border-intensity: 9;

  --elevate-1: rgba(255,255,255, .04);
  --elevate-2: rgba(255,255,255, .09);
```

```
  --background: 240 10% 3.9%;
  --foreground: 0 0% 98%;
  --card: 240 10% 3.9%;
  --card-foreground: 0 0% 98%;
  --popover: 240 10% 3.9%;
  --popover-foreground: 0 0% 98%;
  --primary: 0 0% 98%;
  --primary-foreground: 240 5.9% 10%;
  --secondary: 240 3.7% 15.9%;
  --secondary-foreground: 0 0% 98%;
  --muted: 240 3.7% 15.9%;
  --muted-foreground: 240 5% 64.9%;
  --accent: 240 3.7% 15.9%;
  --accent-foreground: 0 0% 98%;
  --destructive: 0 62.8% 30.6%;
  --destructive-foreground: 0 0% 98%;
  --border: 240 3.7% 15.9%;
  --input: 240 3.7% 15.9%;
  --ring: 240 4.9% 83.9%;
  --chart-1: 220 70% 50%;
  --chart-2: 160 60% 45%;
  --chart-3: 30 80% 55%;
  --chart-4: 280 65% 60%;
  --chart-5: 340 75% 55%;
  --sidebar: 240 5.9% 10%;
  --sidebar-foreground: 240 4.8% 95.9%;
  --sidebar-primary: 224.3 76.3% 48%;
  --sidebar-primary-foreground: 0 0% 100%;
  --sidebar-accent: 240 3.7% 15.9%;
  --sidebar-accent-foreground: 240 4.8% 95.9%;
  --sidebar-border: 240 3.7% 15.9%;
  --sidebar-ring: 240 4.9% 83.9%;
}

@layer base {
  * {
    @apply border-border;
  }
  body {
    @apply font-sans antialiased bg-background text-foreground;
  }
}

@layer utilities {
  /* Hide ugly search cancel button in Chrome */
  input[type="search"]::-webkit-search-cancel-button {
    @apply hidden;
  }

  /* Placeholder styling for contentEditable div */
  [contenteditable][data-placeholder]:empty::before {
```

```
    content: attr(data-placeholder);
    color: hsl(var(--muted-foreground));
    pointer-events: none;
  }
}
```

FILE: artifacts/mockup-sandbox/src/lib/utils.ts
SIZE: 166 bytes

```
import { clsx, type ClassValue } from "clsx"
import { twMerge } from "tailwind-merge"

export function cn(...inputs: ClassValue[]) {
  return twMerge(clsx(inputs))
}
```

FILE: artifacts/mockup-sandbox/src/main.tsx
SIZE: 157 bytes

```
import { createRoot } from "react-dom/client";
import App from "./App";
import "./index.css";

createRoot(document.getElementById("root")!).render(<App />);
```

FILE: artifacts/mockup-sandbox/tsconfig.json
SIZE: 449 bytes

```
{
  "extends": "../../tsconfig.base.json",
  "include": ["src/**/*", "mockupPreviewPlugin.ts", "vite.config.ts"],
  "exclude": ["node_modules", "build", "dist", "**/*.test.ts"],
  "compilerOptions": {
    "noEmit": true,
    "lib": ["es2022", "dom", "dom.iterable"],
    "jsx": "preserve",
    "esModuleInterop": true,
    "allowImportingTsExtensions": true,
    "types": ["node", "vite/client"],
    "paths": {
      "@/*": ["./src/*"]
    }
  }
}
```

FILE: artifacts/mockup-sandbox/vite.config.ts
SIZE: 1,615 bytes

```
import { defineConfig } from "vite";
import react from "@vitejs/plugin-react";
import tailwindcss from "@tailwindcss/vite";
import path from "path";
import runtimeErrorOverlay from "@replit/vite-plugin-runtime-error-modal";
import { mockupPreviewPlugin } from "./mockupPreviewPlugin";

const rawPort = process.env.PORT;

if (!rawPort) {
  throw new Error(
    "PORT environment variable is required but was not provided.",
  );
}

const port = Number(rawPort);

if (Number.isNaN(port) || port <= 0) {
  throw new Error(`Invalid PORT value: "${rawPort}"`);
}

const basePath = process.env.BASE_PATH;

if (!basePath) {
  throw new Error(
    "BASE_PATH environment variable is required but was not provided.",
  );
}

export default defineConfig({
  base: basePath,
  plugins: [
    mockupPreviewPlugin(),
    react(),
    tailwindcss(),
    runtimeErrorOverlay(),
    ...(process.env.NODE_ENV !== "production" &&
    process.env.REPL_ID !== undefined
      ? [
          await import("@replit/vite-plugin-cartographer").then((m) =>
            m.cartographer({
              root: path.resolve(import.meta.dirname, ".."),
            }),
          ),
        ]
      : []),
  ],
  resolve: {
    alias: {
```

```
      "@": path.resolve(import.meta.dirname, "src"),
    },
  },
  root: path.resolve(import.meta.dirname),
  build: {
    outDir: path.resolve(import.meta.dirname, "dist"),
    emptyOutDir: true,
  },
  server: {
    port,
    host: "0.0.0.0",
    allowedHosts: true,
    fs: {
      strict: true,
      deny: ["**/.*"],
    },
  },
  preview: {
    port,
    host: "0.0.0.0",
    allowedHosts: true,
  },
});
```

FILE: artifacts/technician-app/.replit-artifact/artifact.toml
SIZE: 633 bytes

```
kind = "mobile"
previewPath = "/technician-app/"
title = "ACES Technician App"
version = "1.0.0"
id = "artifacts/technician-app"
router = "expo-domain"

[[integratedSkills]]
name = "expo"
version = "1.0.0"

[[services]]
ensurePreviewReachable = "/status"
name = "expo"
paths = [ "/technician-app/" ]
localPort = 22134

[services.development]
run = "pnpm --filter @workspace/technician-app run dev"

[services.production]
build = [ "pnpm", "--filter", "@workspace/technician-app", "run", "build" ]
run = [ "pnpm", "--filter", "@workspace/technician-app", "run", "serve" ]

[services.env]
PORT = "22134"
BASE_PATH = "/technician-app/"
```

FILE: artifacts/technician-app/app.json
SIZE: 2,389 bytes


```
{
  "expo": {
    "name": "ACES-MSD Fueling",
    "slug": "aces-technician-app",
    "owner": "advanced-communications-and-electronics-systems-company",
    "version": "1.4.0",
    "orientation": "portrait",
    "icon": "./assets/images/icon.png",
    "scheme": "technician-app",
    "userInterfaceStyle": "automatic",
    "newArchEnabled": true,
    "splash": {
      "image": "./assets/images/splash-icon.png",
      "resizeMode": "contain",
      "backgroundColor": "#0B1E3E"
    },
    "ios": {
      "supportsTablet": false,
      "bundleIdentifier": "com.aces.msdfuelling",
      "buildNumber": "3",
      "infoPlist": {
        "UIBackgroundModes": [
          "remote-notification"
        ],
        "NSCameraUsageDescription": "Used to photograph ODO meter and tank readings for mission documentation.",
        "NSPhotoLibraryUsageDescription": "Used to attach photos of fuel tank and ODO meter readings.",
        "NSLocationWhenInUseUsageDescription": "Used to record the location of fuel delivery activities.",
        "NSLocationAlwaysAndWhenInUseUsageDescription": "Used to record the location of fuel delivery activities
  .",
        "ITSAppUsesNonExemptEncryption": false
      }
    },
    "android": {
      "package": "com.acessa.technician",
      "versionCode": 1,
      "permissions": [
        "android.permission.RECEIVE_BOOT_COMPLETED",
        "android.permission.VIBRATE",
        "android.permission.CAMERA",
        "android.permission.READ_EXTERNAL_STORAGE",
        "android.permission.WRITE_EXTERNAL_STORAGE",
        "android.permission.ACCESS_FINE_LOCATION",
        "android.permission.ACCESS_COARSE_LOCATION",
        "android.permission.RECORD_AUDIO"
      ]
    },
    "web": {
      "favicon": "./assets/images/icon.png"
    },
```

```
    "plugins": [
      "expo-router",
      "expo-font",
      "expo-web-browser",
      "expo-image-picker",
      [
        "expo-location",
        {
          "locationAlwaysAndWhenInUsePermission": "Used to record the location of fuel delivery activities."
        }
      ],
      [
        "expo-notifications",
        {
          "icon": "./assets/images/icon.png",
          "color": "#0B1E3E"
        }
      ]
    ],
    "experiments": {
      "typedRoutes": true,
      "reactCompiler": true
    },
    "extra": {
      "eas": {
        "projectId": "860a0677-c225-4ed3-8e6b-f722b1be6a0d"
      }
    }
  }
}
```

FILE: artifacts/technician-app/app/(tabs)/_layout.tsx
SIZE: 3,374 bytes

```
import { BlurView } from "expo-blur";
import { isLiquidGlassAvailable } from "expo-glass-effect";
import { Tabs } from "expo-router";
import { Icon, Label, NativeTabs } from "expo-router/unstable-native-tabs";
import { SymbolView } from "expo-symbols";
import { Feather } from "@expo/vector-icons";
import React from "react";
import { Platform, StyleSheet, View } from "react-native";
import COLORS from "@/constants/colors";

function NativeTabLayout() {
  return (
    <NativeTabs>
      <NativeTabs.Trigger name="index">
        <Icon sf={{ default: "checklist", selected: "checklist" }} />
        <Label>Tasks</Label>
      </NativeTabs.Trigger>
      <NativeTabs.Trigger name="notifications">
        <Icon sf={{ default: "bell", selected: "bell.fill" }} />
        <Label>Alerts</Label>
      </NativeTabs.Trigger>
      <NativeTabs.Trigger name="profile">
        <Icon sf={{ default: "person.circle", selected: "person.circle.fill" }} />
        <Label>Profile</Label>
      </NativeTabs.Trigger>
    </NativeTabs>
  );
}

function ClassicTabLayout() {
  const isIOS = Platform.OS === "ios";
  const isWeb = Platform.OS === "web";

  return (
    <Tabs
      screenOptions={{
        headerShown: false,
        tabBarActiveTintColor: COLORS.red,
        tabBarInactiveTintColor: COLORS.gray,
        tabBarLabelStyle: {
          fontSize: 11,
          fontFamily: "Inter_500Medium",
        },
        tabBarStyle: {
          position: "absolute",
          backgroundColor: isIOS ? "transparent" : COLORS.white,
          borderTopWidth: 1,
          borderTopColor: COLORS.cardBorder,
          elevation: 0,
```

```
        shadowColor: COLORS.navy,
        shadowOffset: { width: 0, height: -4 },
        shadowOpacity: 0.06,
        shadowRadius: 12,
        ...(isWeb ? { height: 84 } : {}),
      },
      tabBarBackground: () =>
        isIOS ? (
          <BlurView
            intensity={85}
            tint="light"
            style={StyleSheet.absoluteFill}
          />
        ) : isWeb ? (
          <View style={[StyleSheet.absoluteFill, { backgroundColor: COLORS.white }]} />
        ) : null,
    }}
  >
    <Tabs.Screen
      name="index"
      options={{
        title: "Missions",
        tabBarIcon: ({ color, size }) =>
          isIOS ? (
            <SymbolView name="checklist" tintColor={color} size={size} />
          ) : (
            <Feather name="clipboard" size={size} color={color} />
          ),
      }}
    />
    <Tabs.Screen
      name="notifications"
      options={{
        title: "Alerts",
        tabBarIcon: ({ color, size }) =>
          isIOS ? (
            <SymbolView name="bell" tintColor={color} size={size} />
          ) : (
            <Feather name="bell" size={size} color={color} />
          ),
      }}
    />
    <Tabs.Screen
      name="profile"
      options={{
        title: "Profile",
        tabBarIcon: ({ color, size }) =>
          isIOS ? (
            <SymbolView name="person.circle" tintColor={color} size={size} />
          ) : (
            <Feather name="user" size={size} color={color} />
          ),
```

```
        }}
      />
    </Tabs>
  );
}

export default function TabLayout() {
  if (isLiquidGlassAvailable()) {
    return <NativeTabLayout />;
  }
  return <ClassicTabLayout />;
}
```

FILE: artifacts/technician-app/app/(tabs)/index.tsx
SIZE: 13,290 bytes

```
import React, { useState, useCallback, useMemo } from "react";
import {
  View, Text, FlatList, TouchableOpacity, StyleSheet,
  RefreshControl, TextInput, Platform,
} from "react-native";
import { useRouter } from "expo-router";
import { useQuery } from "@tanstack/react-query";
import { useSafeAreaInsets } from "react-native-safe-area-context";
import { Feather } from "@expo/vector-icons";
import { useAuth } from "@/contexts/auth";
import { apiFetch } from "@/lib/api";
import COLORS from "@/constants/colors";

interface Mission {
  id: number;
  missionId: string;
  siteName: string;
  generator: string;
  project: string;
  driverName: string;
  city: string;
  filledLiters: number;
  virtualCalculated: number;
  actualInTank: number;
  quantityAddedLastTask: number;
  missionStatus: string;
  notes: string;
  createdDate: string | null;
}

const MISSION_STATUS: Record<string, { label: string; bg: string; text: string }> = {
  "Creation":            { label: "New",       bg: COLORS.amberMuted, text: COLORS.amber },
  "Finished by Driver":  { label: "Finished",  bg: COLORS.skyMuted,   text: COLORS.sky },
  "Task approved":       { label: "Approved",  bg: COLORS.greenMuted, text: COLORS.green },
  "Reported by driver":  { label: "Reported",  bg: COLORS.roseMuted,  text: COLORS.rose },
  "Canceled":            { label: "Canceled",  bg: COLORS.grayMuted,  text: COLORS.gray },
};

const FILTER_TABS = ["All", "New", "Finished", "Approved"] as const;
type FilterTab = typeof FILTER_TABS[number];

const FILTER_MAP: Record<FilterTab, string | null> = {
  All: null,
  New: "Creation",
  Finished: "Finished by Driver",
  Approved: "Task approved",
};

function MissionCard({ mission, onPress }: { mission: Mission; onPress: () => void }) {
```

```
  const ms = MISSION_STATUS[mission.missionStatus] ?? { label: mission.missionStatus, bg: COLORS.grayMuted, text
  : COLORS.gray };
  const isNew = mission.missionStatus === "Creation";

  return (
    <TouchableOpacity
      style={[styles.card, isNew && styles.cardNew]}
      onPress={onPress}
      activeOpacity={0.72}
      testID={`mission-card-${mission.id}`}
    >
      <View style={styles.cardHeader}>
        <View style={styles.missionIdBadge}>
          <Feather name="hash" size={10} color={COLORS.gray} />
          <Text style={styles.missionIdText}>{mission.missionId || `MSN-${mission.id}`}</Text>
        </View>
        <View style={[styles.badge, { backgroundColor: ms.bg }]}>
          <Text style={[styles.badgeText, { color: ms.text }]}>{ms.label}</Text>
        </View>
      </View>

      <Text style={styles.siteName} numberOfLines={1}>{mission.siteName}</Text>
      <Text style={styles.generator} numberOfLines={1}>{mission.generator} • {mission.project}</Text>

      <View style={styles.cardMeta}>
        <View style={styles.metaItem}>
          <Feather name="map-pin" size={12} color={COLORS.red} />
          <Text style={styles.metaText}>{mission.city || " "}</Text>
        </View>
        <View style={styles.metaItem}>
          <Feather name="droplet" size={12} color={COLORS.sky} />
          <Text style={styles.metaText}>{mission.quantityAddedLastTask ?? 0} L last fill</Text>
        </View>
      </View>

      <View style={styles.cardFooter}>
        <Text style={styles.footerDate}>
          {mission.createdDate ? new Date(mission.createdDate).toLocaleDateString() : " "}
        </Text>
        <View style={styles.arrowBtn}>
          <Feather name="chevron-right" size={14} color={COLORS.navy} />
        </View>
      </View>
    </TouchableOpacity>
  );
}

export default function TasksScreen() {
  const { user } = useAuth();
  const router = useRouter();
  const insets = useSafeAreaInsets();
  const [search, setSearch] = useState("");
```

```
  const [activeTab, setActiveTab] = useState<FilterTab>("All");

  const { data = [], isLoading, refetch } = useQuery<Mission[]>({
    queryKey: ["driver-missions", user?.driverId],
    queryFn: async () => {
      const res = await apiFetch(`/api/driver/missions?driverId=${user?.driverId ?? ""}`);
      if (!res.ok) throw new Error("Failed to load");
      return res.json();
    },
    enabled: !!user?.driverId,
    refetchInterval: 30000,
  });

  const filtered = useMemo(() => {
    return data
      .filter((m) => {
        if (!search) return true;
        const q = search.toLowerCase();
        return m.siteName?.toLowerCase().includes(q) || m.missionId?.toLowerCase().includes(q);
      })
      .filter((m) => {
        const statusFilter = FILTER_MAP[activeTab];
        if (!statusFilter) return true;
        return m.missionStatus === statusFilter;
      });
  }, [data, search, activeTab]);

  const counts = useMemo(() => ({
    New: data.filter((m) => m.missionStatus === "Creation").length,
    Finished: data.filter((m) => m.missionStatus === "Finished by Driver").length,
    Approved: data.filter((m) => m.missionStatus === "Task approved").length,
  }), [data]);

  const topPad = Platform.OS === "web" ? 67 : insets.top;

  return (
    <View style={[styles.root, { paddingTop: topPad }]}>
      {/* Header */}
      <View style={styles.header}>
        <View>
          <Text style={styles.headerTitle}>My Missions</Text>
          <Text style={styles.headerSub}>{data.length} total • {user?.zone}</Text>
        </View>
        <View style={styles.headerBadge}>
          <Text style={styles.headerBadgeText}>{counts.New} new</Text>
        </View>
      </View>

      {/* Stats row */}
      <View style={styles.statsRow}>
        <View style={[styles.statCard, { borderLeftColor: COLORS.amber }]}>
          <Text style={[styles.statNum, { color: COLORS.amber }]}>{counts.New}</Text>
```

```
      <Text style={styles.statLabel}>New</Text>
    </View>
    <View style={[styles.statCard, { borderLeftColor: COLORS.sky }]}>
      <Text style={[styles.statNum, { color: COLORS.sky }]}>{counts.Finished}</Text>
      <Text style={styles.statLabel}>Finished</Text>
    </View>
    <View style={[styles.statCard, { borderLeftColor: COLORS.green }]}>
      <Text style={[styles.statNum, { color: COLORS.green }]}>{counts.Approved}</Text>
      <Text style={styles.statLabel}>Approved</Text>
    </View>
  </View>

  {/* Search */}
  <View style={styles.searchWrap}>
    <Feather name="search" size={15} color={COLORS.gray} style={{ marginRight: 10 }} />
    <TextInput
      style={styles.searchInput}
      value={search}
      onChangeText={setSearch}
      placeholder="Search site or mission ID..."
      placeholderTextColor={COLORS.textMuted}
      testID="search-input"
    />
    {!!search && (
      <TouchableOpacity onPress={() => setSearch("")} style={styles.clearBtn}>
        <Feather name="x" size={14} color={COLORS.gray} />
      </TouchableOpacity>
    )}
  </View>

  {/* Filter chips */}
  <View style={styles.chipRow}>
    {FILTER_TABS.map((tab) => (
      <TouchableOpacity
        key={tab}
        onPress={() => setActiveTab(tab)}
        style={[styles.chip, activeTab === tab && styles.chipActive]}
        activeOpacity={0.7}
      >
        <Text style={[styles.chipText, activeTab === tab && styles.chipTextActive]}>
          {tab}
        </Text>
      </TouchableOpacity>
    ))}
  </View>

  {/* List */}
  <FlatList
    data={filtered}
    keyExtractor={(m) => String(m.id)}
    renderItem={({ item }) => (
      <MissionCard
```

```
            mission={item}
            onPress={() => router.push(`/mission/${item.id}`)}
          />
        )}
        contentContainerStyle={styles.list}
        showsVerticalScrollIndicator={false}
        refreshControl={
          <RefreshControl refreshing={isLoading} onRefresh={refetch} tintColor={COLORS.red} />
        }
        scrollEnabled={filtered.length > 0}
        ListEmptyComponent={
          <View style={styles.empty}>
            <View style={styles.emptyIcon}>
              <Feather name="clipboard" size={32} color={COLORS.gray} />
            </View>
            <Text style={styles.emptyTitle}>No missions found</Text>
            <Text style={styles.emptyText}>
              {isLoading ? "Loading your missions..." : "Pull down to refresh"}
            </Text>
          </View>
        }
      />
    </View>
  );
}

const styles = StyleSheet.create({
  root: {
    flex: 1,
    backgroundColor: COLORS.bg,
  },
  header: {
    paddingHorizontal: 20,
    paddingBottom: 14,
    paddingTop: 10,
    flexDirection: "row",
    justifyContent: "space-between",
    alignItems: "center",
  },
  headerTitle: {
    fontSize: 26,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
    letterSpacing: -0.5,
  },
  headerSub: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
    marginTop: 2,
  },
  headerBadge: {
```

```
    backgroundColor: COLORS.redMuted,
    borderRadius: 20,
    paddingHorizontal: 12,
    paddingVertical: 6,
  },
  headerBadgeText: {
    fontSize: 12,
    fontFamily: "Inter_700Bold",
    color: COLORS.red,
  },
  statsRow: {
    flexDirection: "row",
    gap: 10,
    paddingHorizontal: 20,
    marginBottom: 14,
  },
  statCard: {
    flex: 1,
    backgroundColor: COLORS.white,
    borderRadius: 14,
    paddingVertical: 12,
    paddingHorizontal: 14,
    borderLeftWidth: 4,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 2 },
    shadowOpacity: 0.05,
    shadowRadius: 8,
    elevation: 2,
  },
  statNum: {
    fontSize: 22,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
  },
  statLabel: {
    fontSize: 11,
    fontFamily: "Inter_500Medium",
    color: COLORS.textSecondary,
    marginTop: 2,
  },
  searchWrap: {
    flexDirection: "row",
    alignItems: "center",
    backgroundColor: COLORS.white,
    borderWidth: 1.5,
    borderColor: COLORS.inputBorder,
    borderRadius: 14,
    paddingHorizontal: 14,
    height: 44,
    marginHorizontal: 20,
    marginBottom: 12,
  },
```

```
  searchInput: {
    flex: 1,
    fontSize: 14,
    fontFamily: "Inter_400Regular",
    color: COLORS.text,
  },
  clearBtn: {
    padding: 4,
  },
  chipRow: {
    flexDirection: "row",
    gap: 8,
    paddingHorizontal: 20,
    marginBottom: 14,
  },
  chip: {
    paddingHorizontal: 16,
    paddingVertical: 7,
    borderRadius: 20,
    backgroundColor: COLORS.white,
    borderWidth: 1.5,
    borderColor: COLORS.cardBorder,
  },
  chipActive: {
    backgroundColor: COLORS.navy,
    borderColor: COLORS.navy,
  },
  chipText: {
    fontSize: 12,
    fontFamily: "Inter_600SemiBold",
    color: COLORS.textSecondary,
  },
  chipTextActive: {
    color: COLORS.white,
  },
  list: {
    paddingHorizontal: 20,
    paddingBottom: 100,
    gap: 12,
  },
  card: {
    backgroundColor: COLORS.white,
    borderRadius: 18,
    borderWidth: 1.5,
    borderColor: COLORS.cardBorder,
    padding: 16,
    gap: 6,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 2 },
    shadowOpacity: 0.05,
    shadowRadius: 10,
    elevation: 2,
```

```
  },
  cardNew: {
    borderColor: COLORS.amber,
    borderLeftWidth: 4,
  },
  cardHeader: {
    flexDirection: "row",
    alignItems: "center",
    justifyContent: "space-between",
    marginBottom: 4,
  },
  missionIdBadge: {
    flexDirection: "row",
    alignItems: "center",
    gap: 4,
    backgroundColor: COLORS.grayMuted,
    borderRadius: 8,
    paddingHorizontal: 8,
    paddingVertical: 4,
  },
  missionIdText: {
    fontSize: 11,
    fontFamily: "Inter_500Medium",
    color: COLORS.textSecondary,
    letterSpacing: 0.3,
  },
  badge: {
    borderRadius: 8,
    paddingHorizontal: 10,
    paddingVertical: 4,
  },
  badgeText: {
    fontSize: 11,
    fontFamily: "Inter_700Bold",
    textTransform: "uppercase",
    letterSpacing: 0.5,
  },
  siteName: {
    fontSize: 16,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
  },
  generator: {
    fontSize: 12,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
  },
  cardMeta: {
    flexDirection: "row",
    gap: 16,
    marginTop: 4,
  },
```

```
  metaItem: {
    flexDirection: "row",
    alignItems: "center",
    gap: 4,
  },
  metaText: {
    fontSize: 12,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
  },
  cardFooter: {
    flexDirection: "row",
    alignItems: "center",
    justifyContent: "space-between",
    marginTop: 6,
    paddingTop: 10,
    borderTopWidth: 1,
    borderTopColor: COLORS.divider,
  },
  footerDate: {
    fontSize: 11,
    fontFamily: "Inter_400Regular",
    color: COLORS.textMuted,
  },
  arrowBtn: {
    width: 26,
    height: 26,
    borderRadius: 8,
    backgroundColor: COLORS.bg,
    alignItems: "center",
    justifyContent: "center",
  },
  empty: {
    alignItems: "center",
    justifyContent: "center",
    paddingVertical: 60,
    gap: 10,
  },
  emptyIcon: {
    width: 72,
    height: 72,
    borderRadius: 20,
    backgroundColor: COLORS.grayMuted,
    alignItems: "center",
    justifyContent: "center",
    marginBottom: 4,
  },
  emptyTitle: {
    fontSize: 16,
    fontFamily: "Inter_600SemiBold",
    color: COLORS.text,
  },
```

```
  emptyText: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
  },
});
```

FILE: artifacts/technician-app/app/(tabs)/notifications.tsx
SIZE: 5,203 bytes

```
import React from "react";
import {
  View, Text, FlatList, StyleSheet, RefreshControl, Platform,
} from "react-native";
import { useQuery } from "@tanstack/react-query";
import { useSafeAreaInsets } from "react-native-safe-area-context";
import { Feather } from "@expo/vector-icons";
import { apiFetch } from "@/lib/api";
import COLORS from "@/constants/colors";

interface Notification {
  id: number;
  title: string;
  message: string;
  driverName?: string;
  sentBy: string;
  createdAt: string;
}

function NotifCard({ item }: { item: Notification }) {
  const date = item.createdAt ? new Date(item.createdAt).toLocaleDateString() : "";
  return (
    <View style={styles.card}>
      <View style={styles.iconBox}>
        <Feather name="bell" size={16} color={COLORS.sky} />
      </View>
      <View style={styles.cardRight}>
        <View style={styles.cardTopRow}>
          <Text style={styles.title} numberOfLines={1}>{item.title}</Text>
          <Text style={styles.date}>{date}</Text>
        </View>
        <Text style={styles.message} numberOfLines={3}>{item.message}</Text>
        {!!item.driverName && (
          <View style={styles.tag}>
            <Feather name="user" size={10} color={COLORS.textSecondary} />
            <Text style={styles.tagText}>{item.driverName}</Text>
          </View>
        )}
      </View>
    </View>
  );
}

export default function NotificationsScreen() {
  const insets = useSafeAreaInsets();
  const topPad = Platform.OS === "web" ? 67 : insets.top;

  const { data = [], isLoading, refetch } = useQuery<Notification[]>({
    queryKey: ["notifications"],
```

```
    queryFn: async () => {
      const res = await apiFetch("/api/notifications");
      if (!res.ok) throw new Error("Failed");
      return res.json();
    },
  });

  return (
    <View style={[styles.root, { paddingTop: topPad }]}>
      <View style={styles.header}>
        <Text style={styles.headerTitle}>Alerts</Text>
        <Text style={styles.headerSub}>{data.length} notifications</Text>
      </View>

      <FlatList
        data={data.slice(0, 30)}
        keyExtractor={(n) => String(n.id)}
        renderItem={({ item }) => <NotifCard item={item} />}
        contentContainerStyle={styles.list}
        showsVerticalScrollIndicator={false}
        refreshControl={
          <RefreshControl refreshing={isLoading} onRefresh={refetch} tintColor={COLORS.red} />
        }
        scrollEnabled={data.length > 0}
        ListEmptyComponent={
          <View style={styles.empty}>
            <View style={styles.emptyIcon}>
              <Feather name="bell-off" size={32} color={COLORS.gray} />
            </View>
            <Text style={styles.emptyTitle}>No alerts yet</Text>
            <Text style={styles.emptyText}>Notifications will appear here</Text>
          </View>
        }
      />
    </View>
  );
}

const styles = StyleSheet.create({
  root: {
    flex: 1,
    backgroundColor: COLORS.bg,
  },
  header: {
    paddingHorizontal: 20,
    paddingBottom: 14,
    paddingTop: 10,
  },
  headerTitle: {
    fontSize: 26,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
```

```
    letterSpacing: -0.5,
  },
  headerSub: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
    marginTop: 2,
  },
  list: {
    paddingHorizontal: 20,
    paddingBottom: 100,
    gap: 10,
  },
  card: {
    flexDirection: "row",
    gap: 12,
    backgroundColor: COLORS.white,
    borderRadius: 16,
    borderWidth: 1.5,
    borderColor: COLORS.cardBorder,
    padding: 14,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 2 },
    shadowOpacity: 0.04,
    shadowRadius: 8,
    elevation: 2,
  },
  iconBox: {
    width: 38,
    height: 38,
    borderRadius: 11,
    backgroundColor: COLORS.skyMuted,
    alignItems: "center",
    justifyContent: "center",
    flexShrink: 0,
  },
  cardRight: {
    flex: 1,
    gap: 4,
  },
  cardTopRow: {
    flexDirection: "row",
    justifyContent: "space-between",
    alignItems: "flex-start",
    gap: 8,
  },
  title: {
    fontSize: 14,
    fontFamily: "Inter_600SemiBold",
    color: COLORS.text,
    flex: 1,
  },
```

```
  date: {
    fontSize: 11,
    fontFamily: "Inter_400Regular",
    color: COLORS.textMuted,
    flexShrink: 0,
  },
  message: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
    lineHeight: 19,
  },
  tag: {
    flexDirection: "row",
    alignItems: "center",
    gap: 4,
    alignSelf: "flex-start",
    backgroundColor: COLORS.grayMuted,
    borderRadius: 6,
    paddingHorizontal: 8,
    paddingVertical: 3,
    marginTop: 2,
  },
  tagText: {
    fontSize: 11,
    fontFamily: "Inter_500Medium",
    color: COLORS.textSecondary,
  },
  empty: {
    alignItems: "center",
    paddingVertical: 60,
    gap: 10,
  },
  emptyIcon: {
    width: 72,
    height: 72,
    borderRadius: 20,
    backgroundColor: COLORS.grayMuted,
    alignItems: "center",
    justifyContent: "center",
    marginBottom: 4,
  },
  emptyTitle: {
    fontSize: 16,
    fontFamily: "Inter_600SemiBold",
    color: COLORS.text,
  },
  emptyText: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
  },
```

```
});
```

FILE: artifacts/technician-app/app/(tabs)/profile.tsx
SIZE: 9,768 bytes

```
import React, { useState } from "react";
import {
  View, Text, StyleSheet, TouchableOpacity, Alert, Platform, Image, ActivityIndicator, ScrollView,
} from "react-native";
import { useSafeAreaInsets } from "react-native-safe-area-context";
import * as Haptics from "expo-haptics";
import * as ImagePicker from "expo-image-picker";
import { Feather } from "@expo/vector-icons";
import type { ComponentProps } from "react";
import { useAuth } from "@/contexts/auth";
import { useRouter } from "expo-router";
import COLORS from "@/constants/colors";
import { getBaseUrl } from "@/lib/api";

type FeatherIconName = ComponentProps<typeof Feather>["name"];

function InfoRow({ icon, label, value }: { icon: FeatherIconName; label: string; value: string }) {
  return (
    <View style={styles.infoRow}>
      <View style={styles.infoIconBox}>
        <Feather name={icon} size={15} color={COLORS.navy} />
      </View>
      <Text style={styles.infoLabel}>{label}</Text>
      <Text style={styles.infoValue} numberOfLines={1}>{value}</Text>
    </View>
  );
}

export default function ProfileScreen() {
  const { user, logout, updateUser } = useAuth();
  const router = useRouter();
  const insets = useSafeAreaInsets();
  const topPad = Platform.OS === "web" ? 67 : insets.top;
  const bottomPad = Platform.OS === "web" ? 34 : insets.bottom;
  const [uploading, setUploading] = useState(false);

  const handleLogout = () => {
    const doLogout = async () => {
      Haptics.notificationAsync(Haptics.NotificationFeedbackType.Warning);
      await logout();
      router.replace("/login");
    };

    if (Platform.OS === "web") {
      doLogout();
    } else {
      Alert.alert("Sign Out", "Are you sure you want to sign out?", [
        { text: "Cancel", style: "cancel" },
        { text: "Sign Out", style: "destructive", onPress: doLogout },
```

```
    ]);
  }
};

const handleChangePhoto = async () => {
  const { status } = await ImagePicker.requestMediaLibraryPermissionsAsync();
  if (status !== "granted") {
    Alert.alert("Permission needed", "Please allow access to your photo library to upload a profile image.");
    return;
  }

  const result = await ImagePicker.launchImageLibraryAsync({
    mediaTypes: ["images"],
    allowsEditing: true,
    aspect: [1, 1],
    quality: 0.7,
  });

  if (result.canceled || !result.assets[0]) return;

  try {
    setUploading(true);
    const asset = result.assets[0];
    const fileName = `driver-${user?.driverId}-${Date.now()}.jpg`;

    const urlRes = await fetch(`${getBaseUrl()}/api/storage/uploads/request-url`, {
      method: "POST",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ name: fileName, size: asset.fileSize ?? 100000, contentType: "image/jpeg" }),
    });
    if (!urlRes.ok) throw new Error("Failed to get upload URL");
    const { uploadURL, objectPath } = await urlRes.json();

    const imgRes = await fetch(asset.uri);
    const blob = await imgRes.blob();
    await fetch(uploadURL, { method: "PUT", headers: { "Content-Type": "image/jpeg" }, body: blob });

    const imageUrl = `/api/storage${objectPath}`;
    await fetch(`${getBaseUrl()}/api/drivers/${user?.driverId}`, {
      method: "PUT",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ imageUrl }),
    });

    await updateUser({ imageUrl });
    Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
  } catch {
    Alert.alert("Upload failed", "Could not upload profile image. Please try again.");
  } finally {
    setUploading(false);
  }
};
```

```
const initials = user?.name
  ?.split(" ")
  .map((n) => n[0])
  .slice(0, 2)
  .join("")
  .toUpperCase() ?? "D";

const imageUrl = user?.imageUrl
  ? user.imageUrl.startsWith("/api/")
    ? `${getBaseUrl()}${user.imageUrl}`
    : user.imageUrl
  : null;

return (
  <ScrollView style={styles.rootScroll} contentContainerStyle={[styles.root, { paddingTop: topPad, paddingBott
om: bottomPad + 16 }]} showsVerticalScrollIndicator={false}>
    <View style={styles.header}>
      <Text style={styles.headerTitle}>Profile</Text>
    </View>

    <View style={styles.avatarSection}>
      <TouchableOpacity onPress={handleChangePhoto} activeOpacity={0.8} style={styles.avatarWrapper}>
        {imageUrl ? (
          <Image source={{ uri: imageUrl }} style={styles.avatarImage} />
        ) : (
          <View style={styles.avatarBox}>
            <Text style={styles.avatarText}>{initials}</Text>
          </View>
        )}
        <View style={styles.cameraOverlay}>
          {uploading ? (
            <ActivityIndicator size="small" color={COLORS.white} />
          ) : (
            <Feather name="camera" size={14} color={COLORS.white} />
          )}
        </View>
      </TouchableOpacity>
      <Text style={styles.name}>{user?.name ?? "Driver"}</Text>
      <View style={styles.rolePill}>
        <Feather name="truck" size={12} color={COLORS.navy} />
        <Text style={styles.role}>Field Driver</Text>
      </View>
    </View>

    <View style={styles.card}>
      <Text style={styles.cardTitle}>Account Details</Text>
      <InfoRow icon="mail" label="Email" value={user?.email ?? " "} />
      <View style={styles.divider} />
      <InfoRow icon="phone" label="Phone" value={user?.phone ?? " "} />
      <View style={styles.divider} />
      <InfoRow icon="map-pin" label="Zone" value={user?.zone ?? " "} />
```

```
        <View style={styles.divider} />
        <InfoRow icon="hash" label="Driver ID" value={String(user?.driverId ?? " ")} />
      </View>

      <View style={styles.card}>
        <Text style={styles.cardTitle}>Application</Text>
        <InfoRow icon="cpu" label="Platform" value="ACES Managed Services" />
        <View style={styles.divider} />
        <InfoRow icon="truck" label="Module" value="Driver Operations" />
        <View style={styles.divider} />
        <InfoRow icon="info" label="Version" value="1.0.0" />
      </View>

      <TouchableOpacity
        style={styles.logoutBtn}
        onPress={handleLogout}
        activeOpacity={0.8}
        testID="logout-button"
      >
        <Feather name="log-out" size={17} color={COLORS.rose} />
        <Text style={styles.logoutText}>Sign Out</Text>
      </TouchableOpacity>
    </ScrollView>
  );
}

const styles = StyleSheet.create({
  rootScroll: {
    flex: 1,
    backgroundColor: COLORS.bg,
  },
  root: {
    flexGrow: 1,
    backgroundColor: COLORS.bg,
    paddingHorizontal: 20,
  },
  header: {
    paddingBottom: 14,
    paddingTop: 10,
  },
  headerTitle: {
    fontSize: 26,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
    letterSpacing: -0.5,
  },
  avatarSection: {
    alignItems: "center",
    marginBottom: 22,
    gap: 8,
  },
  avatarWrapper: {
```

```
    position: "relative",
  },
  avatarBox: {
    width: 88,
    height: 88,
    borderRadius: 26,
    backgroundColor: COLORS.navy,
    alignItems: "center",
    justifyContent: "center",
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 6 },
    shadowOpacity: 0.25,
    shadowRadius: 14,
    elevation: 8,
  },
  avatarImage: {
    width: 88,
    height: 88,
    borderRadius: 26,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 6 },
    shadowOpacity: 0.2,
    shadowRadius: 14,
  },
  avatarText: {
    fontSize: 28,
    fontFamily: "Inter_700Bold",
    color: COLORS.white,
  },
  cameraOverlay: {
    position: "absolute",
    bottom: 0,
    right: 0,
    width: 28,
    height: 28,
    borderRadius: 9,
    backgroundColor: COLORS.navy,
    alignItems: "center",
    justifyContent: "center",
    borderWidth: 2,
    borderColor: COLORS.bg,
  },
  name: {
    fontSize: 20,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
    letterSpacing: -0.3,
  },
  rolePill: {
    flexDirection: "row",
    alignItems: "center",
    gap: 5,
```

```
    backgroundColor: COLORS.grayMuted,
    borderRadius: 20,
    paddingHorizontal: 12,
    paddingVertical: 5,
  },
  role: {
    fontSize: 13,
    fontFamily: "Inter_500Medium",
    color: COLORS.navy,
  },
  card: {
    backgroundColor: COLORS.white,
    borderRadius: 18,
    borderWidth: 1.5,
    borderColor: COLORS.cardBorder,
    paddingHorizontal: 16,
    paddingTop: 14,
    paddingBottom: 4,
    marginBottom: 14,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 2 },
    shadowOpacity: 0.05,
    shadowRadius: 10,
    elevation: 2,
  },
  cardTitle: {
    fontSize: 11,
    fontFamily: "Inter_700Bold",
    color: COLORS.textMuted,
    textTransform: "uppercase",
    letterSpacing: 0.8,
    marginBottom: 8,
  },
  infoRow: {
    flexDirection: "row",
    alignItems: "center",
    gap: 10,
    paddingVertical: 12,
  },
  infoIconBox: {
    width: 32,
    height: 32,
    borderRadius: 9,
    backgroundColor: COLORS.grayMuted,
    alignItems: "center",
    justifyContent: "center",
  },
  infoLabel: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
    flex: 1,
```

```
  },
  infoValue: {
    fontSize: 13,
    fontFamily: "Inter_600SemiBold",
    color: COLORS.text,
    maxWidth: "55%",
    textAlign: "right" as const,
  },
  divider: {
    height: 1,
    backgroundColor: COLORS.divider,
    marginLeft: 42,
  },
  logoutBtn: {
    flexDirection: "row",
    alignItems: "center",
    justifyContent: "center",
    gap: 10,
    height: 52,
    borderRadius: 16,
    backgroundColor: COLORS.roseMuted,
    borderWidth: 1.5,
    borderColor: `${COLORS.rose}30`,
    marginTop: 4,
  },
  logoutText: {
    fontSize: 15,
    fontFamily: "Inter_700Bold",
    color: COLORS.rose,
  },
});
```

FILE: artifacts/technician-app/app/+not-found.tsx
SIZE: 802 bytes

```
import { Link, Stack } from "expo-router";
import { StyleSheet, Text, View } from "react-native";

export default function NotFoundScreen() {
  return (
    <>
      <Stack.Screen options={{ title: "Oops!" }} />
      <View style={styles.container}>
        <Text style={styles.title}>This screen doesn&apos;t exist.</Text>

        <Link href="/" style={styles.link}>
          <Text style={styles.linkText}>Go to home screen!</Text>
        </Link>
      </View>
    </>
  );
}

const styles = StyleSheet.create({
  container: {
    flex: 1,
    alignItems: "center",
    justifyContent: "center",
    padding: 20,
  },
  title: {
    fontSize: 20,
    fontWeight: "bold",
  },
  link: {
    marginTop: 15,
    paddingVertical: 15,
  },
  linkText: {
    fontSize: 14,
    color: "#2e78b7",
  },
});
```

FILE: artifacts/technician-app/app/_layout.tsx
SIZE: 2,123 bytes

```
import {
  Inter_400Regular,
  Inter_500Medium,
  Inter_600SemiBold,
  Inter_700Bold,
  useFonts,
} from "@expo-google-fonts/inter";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { Stack } from "expo-router";
import * as SplashScreen from "expo-splash-screen";
import React, { useEffect } from "react";
import { GestureHandlerRootView } from "react-native-gesture-handler";
import { KeyboardProvider } from "react-native-keyboard-controller";
import { SafeAreaProvider } from "react-native-safe-area-context";

import { ErrorBoundary } from "@/components/ErrorBoundary";
import { AuthProvider } from "@/contexts/auth";
import COLORS from "@/constants/colors";

SplashScreen.preventAutoHideAsync();

const queryClient = new QueryClient({
  defaultOptions: {
    queries: {
      retry: 1,
      staleTime: 30000,
    },
  },
});

function RootLayoutNav() {
  return (
    <Stack
      screenOptions={{
        headerShown: false,
        contentStyle: { backgroundColor: COLORS.navy },
        animation: "slide_from_right",
      }}
    >
      <Stack.Screen name="index" />
      <Stack.Screen name="login" />
      <Stack.Screen name="(tabs)" />
      <Stack.Screen
        name="mission/[id]"
        options={{
          animation: "slide_from_right",
        }}
      />
    </Stack>
```

```
  );
}

export default function RootLayout() {
  const [fontsLoaded, fontError] = useFonts({
    Inter_400Regular,
    Inter_500Medium,
    Inter_600SemiBold,
    Inter_700Bold,
  });

  useEffect(() => {
    if (fontsLoaded || fontError) {
      SplashScreen.hideAsync();
    }
  }, [fontsLoaded, fontError]);

  if (!fontsLoaded && !fontError) return null;

  return (
    <SafeAreaProvider>
      <ErrorBoundary>
        <QueryClientProvider client={queryClient}>
          <GestureHandlerRootView style={{ flex: 1 }}>
            <KeyboardProvider>
              <AuthProvider>
                <RootLayoutNav />
              </AuthProvider>
            </KeyboardProvider>
          </GestureHandlerRootView>
        </QueryClientProvider>
      </ErrorBoundary>
    </SafeAreaProvider>
  );
}
```

FILE: artifacts/technician-app/app/index.tsx
SIZE: 575 bytes

```
import { Redirect } from "expo-router";
import { useAuth } from "@/contexts/auth";
import { View, ActivityIndicator } from "react-native";
import COLORS from "@/constants/colors";

export default function Index() {
  const { user, isLoading } = useAuth();

  if (isLoading) {
    return (
      <View style={{ flex: 1, alignItems: "center", justifyContent: "center", backgroundColor: COLORS.navy }}>
        <ActivityIndicator color={COLORS.red} size="large" />
      </View>
    );
  }

  if (user) return <Redirect href="/(tabs)" />;
  return <Redirect href="/login" />;
}
```

FILE: artifacts/technician-app/app/login.tsx
SIZE: 8,644 bytes

```
import React, { useState } from "react";
import {
  View, Text, TextInput, TouchableOpacity, StyleSheet,
  ActivityIndicator, KeyboardAvoidingView, Platform, ScrollView,
  Image,
} from "react-native";
import { useRouter } from "expo-router";
import { useSafeAreaInsets } from "react-native-safe-area-context";
import * as Haptics from "expo-haptics";
import { Feather } from "@expo/vector-icons";
import { useAuth } from "@/contexts/auth";
import { apiFetch } from "@/lib/api";
import COLORS from "@/constants/colors";

export default function LoginScreen() {
  const { login } = useAuth();
  const router = useRouter();
  const insets = useSafeAreaInsets();
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [showPassword, setShowPassword] = useState(false);
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);

  const handleLogin = async () => {
    if (!email.trim() || !password) return;
    setError("");
    setLoading(true);
    Haptics.impactAsync(Haptics.ImpactFeedbackStyle.Light);
    try {
      const res = await apiFetch("/api/driver/login", {
        method: "POST",
        body: JSON.stringify({ email: email.trim(), password }),
      });
      const data = await res.json();
      if (res.ok && data.success) {
        await login({
          driverId: data.driverId,
          name: data.name,
          email: data.email,
          phone: data.phone,
          zone: data.zone,
          token: data.token,
        });
        Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
        router.replace("/(tabs)");
      } else {
        setError(data.error || "Invalid email or password");
        Haptics.notificationAsync(Haptics.NotificationFeedbackType.Error);
```

```
    }
  } catch {
    setError("Connection error. Please try again.");
    Haptics.notificationAsync(Haptics.NotificationFeedbackType.Error);
  } finally {
    setLoading(false);
  }
};

const topPad = Platform.OS === "web" ? 67 : insets.top;
const bottomPad = Platform.OS === "web" ? 34 : insets.bottom;

return (
  <View style={[styles.root, { paddingTop: topPad }]}>
    <KeyboardAvoidingView
      style={{ flex: 1 }}
      behavior={Platform.OS === "ios" ? "padding" : "height"}
    >
      <ScrollView
        contentContainerStyle={[styles.scroll, { paddingBottom: bottomPad + 24 }]}
        keyboardShouldPersistTaps="handled"
        showsVerticalScrollIndicator={false}
      >
        {/* Top brand stripe */}
        <View style={styles.topStripe} />

        {/* Logo */}
        <View style={styles.logoSection}>
          <Image
            source={require("../assets/images/login-logo.png")}
            style={styles.logoImg}
            resizeMode="contain"
          />
          <Text style={styles.appTitle}>Driver Portal</Text>
          <Text style={styles.subtitle}>Daily Fueling Operations</Text>
        </View>

        {/* Form card */}
        <View style={styles.formCard}>
          <Text style={styles.formTitle}>Sign In</Text>

          {!!error && (
            <View style={styles.errorBox}>
              <Feather name="alert-circle" size={15} color={COLORS.rose} />
              <Text style={styles.errorText}>{error}</Text>
            </View>
          )}

          {/* Email */}
          <View style={styles.fieldWrap}>
            <Text style={styles.fieldLabel}>Email Address</Text>
            <View style={styles.inputWrap}>
```

```
    <Feather name="mail" size={16} color={COLORS.gray} style={styles.inputIcon} />
    <TextInput
      style={styles.input}
      value={email}
      onChangeText={setEmail}
      placeholder="your@email.com"
      placeholderTextColor={COLORS.textMuted}
      autoCapitalize="none"
      keyboardType="email-address"
      autoComplete="email"
      testID="email-input"
    />
  </View>
</View>

{/* Password */}
<View style={styles.fieldWrap}>
  <Text style={styles.fieldLabel}>Password</Text>
  <View style={styles.inputWrap}>
    <Feather name="lock" size={16} color={COLORS.gray} style={styles.inputIcon} />
    <TextInput
      style={[styles.input, { paddingRight: 48 }]}
      value={password}
      onChangeText={setPassword}
      placeholder="        "
      placeholderTextColor={COLORS.textMuted}
      secureTextEntry={!showPassword}
      autoComplete="current-password"
      testID="password-input"
    />
    <TouchableOpacity
      onPress={() => setShowPassword((v) => !v)}
      style={styles.eyeBtn}
      activeOpacity={0.7}
    >
      <Feather name={showPassword ? "eye-off" : "eye"} size={16} color={COLORS.gray} />
    </TouchableOpacity>
  </View>
</View>

<TouchableOpacity
  onPress={handleLogin}
  disabled={loading || !email || !password}
  style={[styles.loginBtn, (loading || !email || !password) && styles.loginBtnDisabled]}
  activeOpacity={0.85}
  testID="login-button"
>
  {loading ? (
    <ActivityIndicator color="#fff" size="small" />
  ) : (
    <>
      <Text style={styles.loginBtnText}>Sign In</Text>
```

```
                <Feather name="arrow-right" size={18} color="#fff" />
              </>
            )}
          </TouchableOpacity>
        </View>

        <Text style={styles.footer}>ACES Managed Services • Secure Driver Access</Text>
      </ScrollView>
    </KeyboardAvoidingView>
  </View>
 );
}

const styles = StyleSheet.create({
 root: {
  flex: 1,
  backgroundColor: COLORS.bg,
 },
 topStripe: {
  height: 6,
  backgroundColor: COLORS.red,
  marginBottom: 0,
 },
 scroll: {
  flexGrow: 1,
  paddingHorizontal: 24,
  justifyContent: "center",
  minHeight: 600,
 },
 logoSection: {
  alignItems: "center",
  marginBottom: 28,
  marginTop: 32,
  gap: 6,
 },
 logoImg: {
  width: 220,
  height: 85,
 },
 appTitle: {
  fontSize: 22,
  fontFamily: "Inter_700Bold",
  color: COLORS.navy,
  letterSpacing: -0.3,
 },
 subtitle: {
  fontSize: 13,
  fontFamily: "Inter_400Regular",
  color: COLORS.textSecondary,
 },
 formCard: {
  backgroundColor: COLORS.white,
```

```
    borderRadius: 24,
    padding: 24,
    gap: 16,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 4 },
    shadowOpacity: 0.07,
    shadowRadius: 20,
    elevation: 3,
  },
  formTitle: {
    fontSize: 20,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
    marginBottom: 4,
  },
  errorBox: {
    flexDirection: "row",
    alignItems: "center",
    gap: 8,
    backgroundColor: COLORS.roseMuted,
    borderRadius: 12,
    padding: 12,
  },
  errorText: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.rose,
    flex: 1,
  },
  fieldWrap: {
    gap: 6,
  },
  fieldLabel: {
    fontSize: 12,
    fontFamily: "Inter_600SemiBold",
    color: COLORS.textSecondary,
    letterSpacing: 0.3,
  },
  inputWrap: {
    flexDirection: "row",
    alignItems: "center",
    backgroundColor: COLORS.inputBg,
    borderWidth: 1.5,
    borderColor: COLORS.inputBorder,
    borderRadius: 14,
    paddingHorizontal: 14,
    height: 52,
  },
  inputIcon: {
    marginRight: 10,
  },
  input: {
```

```
    flex: 1,
    fontSize: 15,
    fontFamily: "Inter_400Regular",
    color: COLORS.text,
    height: 52,
  },
  eyeBtn: {
    position: "absolute",
    right: 14,
    height: 52,
    justifyContent: "center",
  },
  loginBtn: {
    height: 54,
    borderRadius: 14,
    backgroundColor: COLORS.red,
    alignItems: "center",
    justifyContent: "center",
    marginTop: 4,
    flexDirection: "row",
    gap: 8,
    shadowColor: COLORS.red,
    shadowOffset: { width: 0, height: 6 },
    shadowOpacity: 0.3,
    shadowRadius: 12,
    elevation: 6,
  },
  loginBtnDisabled: {
    opacity: 0.45,
  },
  loginBtnText: {
    fontSize: 16,
    fontFamily: "Inter_700Bold",
    color: COLORS.white,
  },
  footer: {
    fontSize: 12,
    fontFamily: "Inter_400Regular",
    color: COLORS.textMuted,
    textAlign: "center",
    marginTop: 32,
  },
});
```

FILE: artifacts/technician-app/app/mission/[id].tsx
SIZE: 32,196 bytes

```
import React, { useState, useEffect } from "react";
import {
  View, Text, ScrollView, StyleSheet, TouchableOpacity,
  TextInput, Alert, ActivityIndicator, Platform, Linking,
  Image,
} from "react-native";
import { useLocalSearchParams, useRouter } from "expo-router";
import { useQuery, useMutation, useQueryClient } from "@tanstack/react-query";
import { useSafeAreaInsets } from "react-native-safe-area-context";
import * as Haptics from "expo-haptics";
import * as ImagePicker from "expo-image-picker";
import { Feather } from "@expo/vector-icons";
import { useAuth } from "@/contexts/auth";
import { apiFetch } from "@/lib/api";
import COLORS from "@/constants/colors";

interface Mission {
  id: number;
  missionId: string;
  siteName: string;
  generator: string;
  project: string;
  driverName: string;
  assignedDriver: string;
  city: string;
  filledLiters: number;
  virtualCalculated: number;
  actualInTank: number;
  quantityAddedLastTask: number;
  notes: string;
  missionStatus: string;
  createdBy: string;
  createdDate: string | null;
  siteLat: number | null;
  siteLng: number | null;
  litersBefore: number | null;
  litersAdded: number | null;
  completionDate: string | null;
  odoBeforePhoto: string | null;
  odoAfterPhoto: string | null;
  tankBeforePhoto: string | null;
  tankAfterPhoto: string | null;
}


const MISSION_STATUS_COLORS: Record<string, { bg: string; text: string }> = {
  "Creation":           { bg: COLORS.amberMuted, text: COLORS.amber },
  "Finished by Driver": { bg: COLORS.skyMuted,   text: COLORS.sky },
  "Task approved":      { bg: COLORS.greenMuted, text: COLORS.green },
```

```
  "Reported by driver": { bg: COLORS.roseMuted,  text: COLORS.rose },
  "Canceled":           { bg: COLORS.grayMuted,  text: COLORS.gray },
};

function FuelBar({ label, value, max, color }: { label: string; value: number; max: number; color: string }) {
  const pct = max > 0 ? Math.min((value / max) * 100, 100) : 0;
  return (
    <View style={styles.fuelRow}>
      <View style={styles.fuelLabelRow}>
        <Text style={styles.fuelLabel}>{label}</Text>
        <Text style={[styles.fuelValue, { color }]}>{value.toLocaleString()} L</Text>
      </View>
      <View style={styles.fuelTrack}>
        <View style={[styles.fuelFill, { width: `${Math.round(pct)}%` as `${number}%`, backgroundColor: color }]
  } />
      </View>
    </View>
  );
}

function PhotoField({
  label,
  icon,
  value,
  onCapture,
  onRetake,
}: {
  label: string;
  icon: string;
  value: string | null;
  onCapture: () => void;
  onRetake: () => void;
}) {
  return (
    <View style={styles.photoField}>
      <View style={styles.photoLabelRow}>
        <View style={[styles.photoIcon, { backgroundColor: COLORS.navyMuted ?? COLORS.grayMuted }]}>
          <Feather name={icon as any} size={13} color={COLORS.navy} />
        </View>
        <Text style={styles.photoLabel}>{label}</Text>
        {value && (
          <TouchableOpacity onPress={onRetake} style={styles.retakeBtn}>
            <Feather name="refresh-cw" size={12} color={COLORS.textMuted} />
            <Text style={styles.retakeBtnText}>Retake</Text>
          </TouchableOpacity>
        )}
      </View>
      {value ? (
        <Image source={{ uri: value }} style={styles.photoPreview} resizeMode="cover" />
      ) : (
        <TouchableOpacity style={styles.cameraBtn} onPress={onCapture} activeOpacity={0.8}>
          <Feather name="camera" size={22} color={COLORS.textMuted} />
```

```
          <Text style={styles.cameraBtnText}>Tap to open camera</Text>
        </TouchableOpacity>
      )}
    </View>
  );
}

export default function MissionDetailScreen() {
  const { id } = useLocalSearchParams<{ id: string }>();
  const { user } = useAuth();
  const router = useRouter();
  const insets = useSafeAreaInsets();
  const queryClient = useQueryClient();

  const [notes, setNotes] = useState("");
  const [litersBefore, setLitersBefore] = useState("");
  const [litersAdded, setLitersAdded] = useState("");
  const [completionDate, setCompletionDate] = useState(
    new Date().toLocaleDateString("en-CA")
  );
  const [odoBeforePhoto, setOdoBeforePhoto] = useState<string | null>(null);
  const [odoAfterPhoto, setOdoAfterPhoto] = useState<string | null>(null);
  const [tankBeforePhoto, setTankBeforePhoto] = useState<string | null>(null);
  const [tankAfterPhoto, setTankAfterPhoto] = useState<string | null>(null);
  const [saved, setSaved] = useState(false);

  const topPad = Platform.OS === "web" ? 67 : insets.top;
  const bottomPad = Platform.OS === "web" ? 34 : insets.bottom;

  const { data: mission, isLoading, error } = useQuery<Mission>({
    queryKey: ["driver-mission", id],
    queryFn: async () => {
      const res = await apiFetch(`/api/driver/missions/${id}`);
      if (!res.ok) throw new Error("Failed to fetch mission");
      return res.json() as Promise<Mission>;
    },
  });

  useEffect(() => {
    if (!mission) return;
    if (mission.notes) setNotes(mission.notes);
    if (mission.litersBefore != null) setLitersBefore(String(mission.litersBefore));
    if (mission.litersAdded != null) setLitersAdded(String(mission.litersAdded));
    if (mission.completionDate) {
      setCompletionDate(new Date(mission.completionDate).toLocaleDateString("en-CA"));
    }
    if (mission.odoBeforePhoto) setOdoBeforePhoto(mission.odoBeforePhoto);
    if (mission.odoAfterPhoto) setOdoAfterPhoto(mission.odoAfterPhoto);
    if (mission.tankBeforePhoto) setTankBeforePhoto(mission.tankBeforePhoto);
    if (mission.tankAfterPhoto) setTankAfterPhoto(mission.tankAfterPhoto);
  }, [mission?.id]);
```

```
  const takePhoto = async (setter: (v: string | null) => void) => {
    if (Platform.OS === "web") {
      const result = await ImagePicker.launchImageLibraryAsync({
        mediaTypes: ["images"],
        quality: 0.6,
        base64: true,
      });
      if (!result.canceled && result.assets[0]?.base64) {
        setter(`${result.assets[0].base64}`);
        Haptics.selectionAsync();
      }
      return;
    }
    const { status } = await ImagePicker.requestCameraPermissionsAsync();
    if (status !== "granted") {
      Alert.alert("Permission Required", "Camera access is required to take photos.");
      return;
    }
    const result = await ImagePicker.launchCameraAsync({
      mediaTypes: ["images"],
      quality: 0.6,
      base64: true,
      allowsEditing: false,
    });
    if (!result.canceled && result.assets[0]?.base64) {
      setter(`${result.assets[0].base64}`);
      Haptics.selectionAsync();
    }
  };

  const openNavigation = () => {
    if (!mission?.siteLat || !mission?.siteLng) {
      Alert.alert("No location data", "This site does not have GPS coordinates recorded.");
      return;
    }
    const { siteLat: lat, siteLng: lng } = mission;
    const googleMapsWeb = `https://www.google.com/maps/search/?api=1&query=${lat},${lng}`;
    const googleMapsApp = Platform.select({
      ios: `comgooglemaps://?q=${lat},${lng}&center=${lat},${lng}&zoom=17`,
      android: `google.navigation:q=${lat},${lng}`,
      default: googleMapsWeb,
    });
    Linking.canOpenURL(googleMapsApp).then((supported) => {
      Linking.openURL(supported ? googleMapsApp : googleMapsWeb);
    }).catch(() => {
      Linking.openURL(googleMapsWeb);
    });
  };

  const mutation = useMutation({
    mutationFn: async () => {
      const res = await apiFetch(`/api/driver/missions/${id}`, {
```

```
      method: "PUT",
      body: JSON.stringify({
        missionStatus: "Finished by Driver",
        notes,
        driverName: user?.name ?? "",
        litersBefore: litersBefore ? parseFloat(litersBefore) : null,
        litersAdded: litersAdded ? parseFloat(litersAdded) : null,
        completionDate: completionDate ? new Date(completionDate).toISOString() : null,
        odoBeforePhoto,
        odoAfterPhoto,
        tankBeforePhoto,
        tankAfterPhoto,
      }),
    });
    if (!res.ok) throw new Error("Failed");
    return res.json();
  },
  onSuccess: () => {
    Haptics.notificationAsync(Haptics.NotificationFeedbackType.Success);
    queryClient.invalidateQueries({ queryKey: ["driver-missions"] });
    queryClient.invalidateQueries({ queryKey: ["driver-mission", id] });
    setSaved(true);
    setTimeout(() => {
      setSaved(false);
      router.back();
    }, 1200);
  },
  onError: () => {
    Haptics.notificationAsync(Haptics.NotificationFeedbackType.Error);
    Alert.alert("Error", "Failed to update mission. Please try again.");
  },
});

if (isLoading) {
  return (
    <View style={[styles.loadingRoot, { paddingTop: topPad }]}>
      <ActivityIndicator color={COLORS.red} size="large" />
      <Text style={styles.loadingText}>Loading mission...</Text>
    </View>
  );
}

if (error || !mission) {
  return (
    <View style={[styles.loadingRoot, { paddingTop: topPad }]}>
      <View style={styles.errorIcon}>
        <Feather name="alert-circle" size={32} color={COLORS.rose} />
      </View>
      <Text style={styles.errorTitle}>Mission not found</Text>
      <TouchableOpacity onPress={() => router.back()} style={styles.backBtn}>
        <Text style={styles.backBtnText}>Go Back</Text>
      </TouchableOpacity>
```

```
    </View>
  );
}

const maxL = Math.max(mission.filledLiters, mission.virtualCalculated, mission.actualInTank, mission.quantityA
ddedLastTask, 1);
const missionColors = MISSION_STATUS_COLORS[mission.missionStatus] ?? { bg: COLORS.grayMuted, text: COLORS.gra
y };
const canUpdate = mission.missionStatus === "Creation" || mission.missionStatus === "Task approved";
const hasLocation = !!mission.siteLat && !!mission.siteLng;

return (
  <View style={[styles.root, { paddingTop: topPad }]}>
    {/* Header */}
    <View style={styles.topHeader}>
      <TouchableOpacity
        onPress={() => router.back()}
        style={styles.backButton}
        hitSlop={{ top: 10, bottom: 10, left: 10, right: 10 }}
      >
        <Feather name="arrow-left" size={20} color={COLORS.navy} />
      </TouchableOpacity>
      <Text style={styles.pageTitle} numberOfLines={1}>Mission Detail</Text>
      <TouchableOpacity
        style={[styles.navBtn, !hasLocation && styles.navBtnDisabled]}
        onPress={openNavigation}
        activeOpacity={hasLocation ? 0.8 : 1}
      >
        <Feather name="navigation" size={14} color={hasLocation ? COLORS.white : COLORS.textMuted} />
        <Text style={[styles.navBtnText, !hasLocation && styles.navBtnTextDisabled]}>Navigate</Text>
      </TouchableOpacity>
    </View>

    <ScrollView
      style={styles.scroll}
      contentContainerStyle={[styles.scrollContent, { paddingBottom: bottomPad + 100 }]}
      showsVerticalScrollIndicator={false}
      keyboardShouldPersistTaps="handled"
    >
      {/* Mission header card */}
      <View style={styles.card}>
        <View style={styles.cardTopRow}>
          <View style={styles.missionIdBox}>
            <Feather name="hash" size={10} color={COLORS.gray} />
            <Text style={styles.missionIdText}>{mission.missionId || `MSN-${mission.id}`}</Text>
          </View>
          <View style={[styles.statusBadge, { backgroundColor: missionColors.bg }]}>
            <Text style={[styles.statusBadgeText, { color: missionColors.text }]}>
              {mission.missionStatus}
            </Text>
          </View>
        </View>
```

```
        <Text style={styles.siteName}>{mission.siteName}</Text>
        <Text style={styles.generator}>{mission.generator} • {mission.project}</Text>
        <View style={styles.metaRow}>
          <View style={styles.metaItem}>
            <Feather name="map-pin" size={13} color={COLORS.red} />
            <Text style={styles.metaText}>{mission.city || " "}</Text>
          </View>
          <View style={styles.metaItem}>
            <Feather name="user" size={13} color={COLORS.navy} />
            <Text style={styles.metaText}>{mission.driverName || mission.assignedDriver || "Unassigned"}</Text
>
          </View>
        </View>
        {hasLocation && (
          <View style={styles.coordRow}>
            <Feather name="crosshair" size={11} color={COLORS.textMuted} />
            <Text style={styles.coordText}>{mission.siteLat?.toFixed(5)}, {mission.siteLng?.toFixed(5)}</Text>
          </View>
        )}
      </View>

      {/* Fuel readings */}
      <View style={styles.card}>
        <View style={styles.cardTitleRow}>
          <View style={[styles.cardTitleIcon, { backgroundColor: COLORS.skyMuted }]}>
            <Feather name="droplet" size={14} color={COLORS.sky} />
          </View>
          <Text style={styles.cardTitle}>Fuel Readings</Text>
        </View>
        <FuelBar label="Filled Liters"        value={mission.filledLiters}          max={maxL} color={COLORS.s
ky} />
        <FuelBar label="Virtual Calculated"   value={mission.virtualCalculated}     max={maxL} color={COLORS.i
ndigo} />
        <FuelBar label="Actual in Tank"       value={mission.actualInTank}          max={maxL} color={COLORS.g
reen} />
        <FuelBar label="Qty Added Last Task"  value={mission.quantityAddedLastTask} max={maxL} color={COLORS.a
mber} />
      </View>

      {/* Details */}
      <View style={styles.card}>
        <View style={styles.cardTitleRow}>
          <View style={[styles.cardTitleIcon, { backgroundColor: COLORS.grayMuted }]}>
            <Feather name="file-text" size={14} color={COLORS.gray} />
          </View>
          <Text style={styles.cardTitle}>Details</Text>
        </View>
        <View style={styles.detailRow}>
          <Text style={styles.detailLabel}>Created by</Text>
          <Text style={styles.detailValue}>{mission.createdBy || " "}</Text>
        </View>
        <View style={styles.divider} />
```

```
          <View style={styles.detailRow}>
            <Text style={styles.detailLabel}>Date</Text>
            <Text style={styles.detailValue}>
              {mission.createdDate ? new Date(mission.createdDate).toLocaleDateString() : " "}
            </Text>
          </View>
          {!!mission.notes && (
            <>
              <View style={styles.divider} />
              <View style={[styles.detailRow, { alignItems: "flex-start" }]}>
                <Text style={styles.detailLabel}>Driver Notes</Text>
                <Text style={[styles.detailValue, { maxWidth: "65%", textAlign: "right" }]}>{mission.notes}</Tex
t>
              </View>
            </>
          )}
        </View>

        {/* Driver action form */}
        {canUpdate ? (
          <>
            {/* Photo Documentation */}
            <View style={styles.card}>
              <View style={styles.cardTitleRow}>
                <View style={[styles.cardTitleIcon, { backgroundColor: COLORS.amberMuted }]}>
                  <Feather name="camera" size={14} color={COLORS.amber} />
                </View>
                <Text style={styles.cardTitle}>Photo Documentation</Text>
              </View>

              <PhotoField
                label="ODO Meter   Before"
                icon="activity"
                value={odoBeforePhoto}
                onCapture={() => takePhoto(setOdoBeforePhoto)}
                onRetake={() => takePhoto(setOdoBeforePhoto)}
              />
              <View style={styles.photoDivider} />
              <PhotoField
                label="ODO Meter   After"
                icon="activity"
                value={odoAfterPhoto}
                onCapture={() => takePhoto(setOdoAfterPhoto)}
                onRetake={() => takePhoto(setOdoAfterPhoto)}
              />
              <View style={styles.photoDivider} />
              <PhotoField
                label="Tank   Before"
                icon="droplet"
                value={tankBeforePhoto}
                onCapture={() => takePhoto(setTankBeforePhoto)}
                onRetake={() => takePhoto(setTankBeforePhoto)}
```

```
  />
  <View style={styles.photoDivider} />
  <PhotoField
    label="Tank   After"
    icon="droplet"
    value={tankAfterPhoto}
    onCapture={() => takePhoto(setTankAfterPhoto)}
    onRetake={() => takePhoto(setTankAfterPhoto)}
  />
</View>

{/* Driver Entries */}
<View style={styles.card}>
  <View style={styles.cardTitleRow}>
    <View style={[styles.cardTitleIcon, { backgroundColor: COLORS.greenMuted }]}>
      <Feather name="edit-3" size={14} color={COLORS.green} />
    </View>
    <Text style={styles.cardTitle}>Driver Entries</Text>
  </View>

  <View style={styles.entryRow}>
    <View style={styles.entryField}>
      <Text style={styles.entryLabel}>Liters Before</Text>
      <TextInput
        style={styles.entryInput}
        value={litersBefore}
        onChangeText={setLitersBefore}
        placeholder="0"
        placeholderTextColor={COLORS.textMuted}
        keyboardType="numeric"
        testID="liters-before-input"
      />
    </View>
    <View style={styles.entrySpacer} />
    <View style={styles.entryField}>
      <Text style={styles.entryLabel}>Added Liters</Text>
      <TextInput
        style={styles.entryInput}
        value={litersAdded}
        onChangeText={setLitersAdded}
        placeholder="0"
        placeholderTextColor={COLORS.textMuted}
        keyboardType="numeric"
        testID="liters-added-input"
      />
    </View>
  </View>

  <Text style={styles.entryLabel}>Date of Completion</Text>
  <TextInput
    style={styles.entryInput}
    value={completionDate}
```

```
            onChangeText={setCompletionDate}
            placeholder="YYYY-MM-DD"
            placeholderTextColor={COLORS.textMuted}
            keyboardType={Platform.OS === "ios" ? "numbers-and-punctuation" : "default"}
            testID="completion-date-input"
          />
        </View>

        {/* Update Mission */}
        <View style={styles.card}>
          <View style={styles.cardTitleRow}>
            <View style={[styles.cardTitleIcon, { backgroundColor: COLORS.redMuted }]}>
              <Feather name="truck" size={14} color={COLORS.red} />
            </View>
            <Text style={styles.cardTitle}>Update Mission</Text>
          </View>

          <Text style={styles.fieldLabel}>Notes / Remarks</Text>
          <TextInput
            style={styles.textarea}
            value={notes}
            onChangeText={setNotes}
            placeholder="Add fueling notes or observations..."
            placeholderTextColor={COLORS.textMuted}
            multiline
            numberOfLines={4}
            textAlignVertical="top"
            testID="remark-input"
          />

          <TouchableOpacity
            style={[styles.submitBtn, saved && styles.submitBtnSaved, mutation.isPending && styles.submitBtn
Loading]}
            onPress={() => mutation.mutate()}
            disabled={mutation.isPending || saved}
            activeOpacity={0.85}
            testID="submit-button"
          >
            {mutation.isPending ? (
              <ActivityIndicator color={COLORS.white} size="small" />
            ) : saved ? (
              <>
                <Feather name="check" size={18} color={COLORS.white} />
                <Text style={styles.submitBtnText}>Updated!</Text>
              </>
            ) : (
              <>
                <Text style={styles.submitBtnText}>Submit Task</Text>
                <Feather name="send" size={16} color={COLORS.white} />
              </>
            )}
          </TouchableOpacity>
```

```
          </View>
        </>
      ) : (
        <View style={[styles.card, { borderLeftWidth: 4, borderLeftColor: COLORS.green }]}>
          <View style={styles.cardTitleRow}>
            <View style={[styles.cardTitleIcon, { backgroundColor: COLORS.greenMuted }]}>
              <Feather name="check-circle" size={14} color={COLORS.green} />
            </View>
            <Text style={[styles.cardTitle, { color: COLORS.green }]}>Mission Completed</Text>
          </View>
          <Text style={styles.completedText}>
            This mission has been {mission.missionStatus.toLowerCase()} and is no longer editable.
          </Text>
          {/* Show submitted photos if any */}
          {(mission.odoBeforePhoto || mission.odoAfterPhoto || mission.tankBeforePhoto || mission.tankAfterPho
to) && (
            <View style={{ marginTop: 12, gap: 10 }}>
              <Text style={styles.fieldLabel}>Submitted Photos</Text>
              <ScrollView horizontal showsHorizontalScrollIndicator={false} contentContainerStyle={{ gap: 10 }
}>
                {mission.odoBeforePhoto && (
                  <View style={styles.thumbWrap}>
                    <Image source={{ uri: mission.odoBeforePhoto }} style={styles.thumb} resizeMode="cover" />
                    <Text style={styles.thumbLabel}>ODO Before</Text>
                  </View>
                )}
                {mission.odoAfterPhoto && (
                  <View style={styles.thumbWrap}>
                    <Image source={{ uri: mission.odoAfterPhoto }} style={styles.thumb} resizeMode="cover" />
                    <Text style={styles.thumbLabel}>ODO After</Text>
                  </View>
                )}
                {mission.tankBeforePhoto && (
                  <View style={styles.thumbWrap}>
                    <Image source={{ uri: mission.tankBeforePhoto }} style={styles.thumb} resizeMode="cover" /
>
                    <Text style={styles.thumbLabel}>Tank Before</Text>
                  </View>
                )}
                {mission.tankAfterPhoto && (
                  <View style={styles.thumbWrap}>
                    <Image source={{ uri: mission.tankAfterPhoto }} style={styles.thumb} resizeMode="cover" />
                    <Text style={styles.thumbLabel}>Tank After</Text>
                  </View>
                )}
              </ScrollView>
            </View>
          )}
          {/* Show submitted entries if any */}
          {(mission.litersBefore != null || mission.litersAdded != null || mission.completionDate) && (
            <View style={{ marginTop: 8, gap: 6 }}>
              {mission.litersBefore != null && (
```

```
                <View style={styles.detailRow}>
                  <Text style={styles.detailLabel}>Liters Before</Text>
                  <Text style={styles.detailValue}>{mission.litersBefore} L</Text>
                </View>
              )}
              {mission.litersAdded != null && (
                <View style={styles.detailRow}>
                  <Text style={styles.detailLabel}>Added Liters</Text>
                  <Text style={styles.detailValue}>{mission.litersAdded} L</Text>
                </View>
              )}
              {mission.completionDate && (
                <View style={styles.detailRow}>
                  <Text style={styles.detailLabel}>Completion Date</Text>
                  <Text style={styles.detailValue}>{new Date(mission.completionDate).toLocaleDateString()}</Te
  xt>
                </View>
              )}
            </View>
          )}
        </View>
      )}
    </ScrollView>
  </View>
  );
}

const styles = StyleSheet.create({
  root: { flex: 1, backgroundColor: COLORS.bg },
  loadingRoot: {
    flex: 1,
    backgroundColor: COLORS.bg,
    alignItems: "center",
    justifyContent: "center",
    gap: 16,
  },
  loadingText: { fontSize: 14, fontFamily: "Inter_400Regular", color: COLORS.textSecondary },
  errorIcon: {
    width: 72,
    height: 72,
    borderRadius: 20,
    backgroundColor: COLORS.roseMuted,
    alignItems: "center",
    justifyContent: "center",
  },
  errorTitle: { fontSize: 16, fontFamily: "Inter_600SemiBold", color: COLORS.text },
  backBtn: {
    backgroundColor: COLORS.navy,
    paddingHorizontal: 24,
    paddingVertical: 12,
    borderRadius: 12,
  },
```

```
  backBtnText: { fontSize: 14, fontFamily: "Inter_600SemiBold", color: COLORS.white },
  topHeader: {
    flexDirection: "row",
    alignItems: "center",
    paddingHorizontal: 16,
    paddingVertical: 10,
    gap: 10,
    backgroundColor: COLORS.white,
    borderBottomWidth: 1,
    borderBottomColor: COLORS.divider,
  },
  backButton: {
    width: 38,
    height: 38,
    borderRadius: 11,
    backgroundColor: COLORS.grayMuted,
    alignItems: "center",
    justifyContent: "center",
  },
  pageTitle: {
    flex: 1,
    fontSize: 17,
    fontFamily: "Inter_700Bold",
    color: COLORS.text,
    textAlign: "center",
    letterSpacing: -0.2,
  },
  navBtn: {
    flexDirection: "row",
    alignItems: "center",
    gap: 5,
    backgroundColor: COLORS.navy,
    paddingHorizontal: 12,
    paddingVertical: 8,
    borderRadius: 10,
  },
  navBtnDisabled: { backgroundColor: COLORS.grayMuted },
  navBtnText: { fontSize: 12, fontFamily: "Inter_600SemiBold", color: COLORS.white },
  navBtnTextDisabled: { color: COLORS.textMuted },
  scroll: { flex: 1 },
  scrollContent: { paddingHorizontal: 16, paddingTop: 14, gap: 12 },
  card: {
    backgroundColor: COLORS.white,
    borderRadius: 18,
    borderWidth: 1.5,
    borderColor: COLORS.cardBorder,
    padding: 16,
    gap: 6,
    shadowColor: COLORS.navy,
    shadowOffset: { width: 0, height: 2 },
    shadowOpacity: 0.05,
    shadowRadius: 10,
```

```
    elevation: 2,
  },
  cardTopRow: {
    flexDirection: "row",
    justifyContent: "space-between",
    alignItems: "center",
    marginBottom: 8,
  },
  missionIdBox: {
    flexDirection: "row",
    alignItems: "center",
    gap: 4,
    backgroundColor: COLORS.grayMuted,
    borderRadius: 8,
    paddingHorizontal: 8,
    paddingVertical: 4,
  },
  missionIdText: {
    fontSize: 11,
    fontFamily: "Inter_500Medium",
    color: COLORS.textSecondary,
    letterSpacing: 0.3,
  },
  statusBadge: { borderRadius: 8, paddingHorizontal: 10, paddingVertical: 4 },
  statusBadgeText: {
    fontSize: 11,
    fontFamily: "Inter_700Bold",
    textTransform: "uppercase",
    letterSpacing: 0.5,
  },
  siteName: { fontSize: 18, fontFamily: "Inter_700Bold", color: COLORS.text },
  generator: { fontSize: 13, fontFamily: "Inter_400Regular", color: COLORS.textSecondary },
  metaRow: { flexDirection: "row", gap: 16, marginTop: 8 },
  metaItem: { flexDirection: "row", alignItems: "center", gap: 5 },
  metaText: { fontSize: 12, fontFamily: "Inter_400Regular", color: COLORS.textSecondary },
  coordRow: {
    flexDirection: "row",
    alignItems: "center",
    gap: 5,
    marginTop: 6,
  },
  coordText: { fontSize: 11, fontFamily: "Inter_400Regular", color: COLORS.textMuted },
  cardTitleRow: { flexDirection: "row", alignItems: "center", gap: 10, marginBottom: 10 },
  cardTitleIcon: {
    width: 30,
    height: 30,
    borderRadius: 9,
    alignItems: "center",
    justifyContent: "center",
  },
  cardTitle: { fontSize: 14, fontFamily: "Inter_700Bold", color: COLORS.text },
  fuelRow: { gap: 6, marginBottom: 10 },
```

```
  fuelLabelRow: { flexDirection: "row", justifyContent: "space-between" },
  fuelLabel: { fontSize: 12, fontFamily: "Inter_400Regular", color: COLORS.textSecondary },
  fuelValue: { fontSize: 12, fontFamily: "Inter_700Bold" },
  fuelTrack: {
    height: 7,
    backgroundColor: COLORS.grayMuted,
    borderRadius: 4,
    overflow: "hidden",
  },
  fuelFill: { height: 7, borderRadius: 4 },
  detailRow: {
    flexDirection: "row",
    justifyContent: "space-between",
    alignItems: "center",
    paddingVertical: 10,
  },
  detailLabel: { fontSize: 13, fontFamily: "Inter_400Regular", color: COLORS.textSecondary },
  detailValue: { fontSize: 13, fontFamily: "Inter_600SemiBold", color: COLORS.text, textAlign: "right" },
  divider: { height: 1, backgroundColor: COLORS.divider },
  // Photo documentation
  photoField: { gap: 8 },
  photoDivider: { height: 1, backgroundColor: COLORS.divider, marginVertical: 4 },
  photoLabelRow: {
    flexDirection: "row",
    alignItems: "center",
    gap: 8,
  },
  photoIcon: {
    width: 26,
    height: 26,
    borderRadius: 8,
    alignItems: "center",
    justifyContent: "center",
  },
  photoLabel: { flex: 1, fontSize: 13, fontFamily: "Inter_600SemiBold", color: COLORS.text },
  retakeBtn: {
    flexDirection: "row",
    alignItems: "center",
    gap: 4,
    paddingHorizontal: 8,
    paddingVertical: 4,
    borderRadius: 8,
    backgroundColor: COLORS.grayMuted,
  },
  retakeBtnText: { fontSize: 11, fontFamily: "Inter_500Medium", color: COLORS.textMuted },
  cameraBtn: {
    flexDirection: "column",
    alignItems: "center",
    justifyContent: "center",
    gap: 8,
    borderWidth: 1.5,
    borderColor: COLORS.inputBorder,
```

```
  borderStyle: "dashed",
  borderRadius: 14,
  height: 100,
  backgroundColor: COLORS.inputBg,
},
cameraBtnText: {
  fontSize: 13,
  fontFamily: "Inter_400Regular",
  color: COLORS.textMuted,
},
photoPreview: {
  width: "100%",
  height: 180,
  borderRadius: 12,
  backgroundColor: COLORS.grayMuted,
},
// Driver entries
entryRow: { flexDirection: "row", alignItems: "flex-start" },
entryField: { flex: 1 },
entrySpacer: { width: 12 },
entryLabel: {
  fontSize: 11,
  fontFamily: "Inter_700Bold",
  color: COLORS.textMuted,
  textTransform: "uppercase",
  letterSpacing: 0.8,
  marginBottom: 6,
  marginTop: 10,
},
entryInput: {
  backgroundColor: COLORS.inputBg,
  borderWidth: 1.5,
  borderColor: COLORS.inputBorder,
  borderRadius: 12,
  paddingHorizontal: 14,
  paddingVertical: 12,
  fontSize: 15,
  fontFamily: "Inter_500Medium",
  color: COLORS.text,
},
// Update mission
fieldLabel: {
  fontSize: 11,
  fontFamily: "Inter_700Bold",
  color: COLORS.textMuted,
  textTransform: "uppercase",
  letterSpacing: 0.8,
  marginTop: 8,
  marginBottom: 8,
},
statusRow: { flexDirection: "row", gap: 8, marginBottom: 16 },
statusOption: {
```

```
    flex: 1,
    flexDirection: "row",
    alignItems: "center",
    justifyContent: "center",
    gap: 6,
    paddingVertical: 12,
    borderRadius: 12,
    borderWidth: 1.5,
    backgroundColor: COLORS.white,
  },
  statusOptionText: { fontSize: 12, fontFamily: "Inter_600SemiBold" },
  textarea: {
    backgroundColor: COLORS.inputBg,
    borderWidth: 1.5,
    borderColor: COLORS.inputBorder,
    borderRadius: 14,
    padding: 14,
    fontSize: 14,
    fontFamily: "Inter_400Regular",
    color: COLORS.text,
    minHeight: 100,
    marginBottom: 14,
  },
  submitBtn: {
    flexDirection: "row",
    alignItems: "center",
    justifyContent: "center",
    gap: 8,
    height: 54,
    borderRadius: 14,
    backgroundColor: COLORS.red,
    shadowColor: COLORS.red,
    shadowOffset: { width: 0, height: 4 },
    shadowOpacity: 0.28,
    shadowRadius: 10,
    elevation: 5,
  },
  submitBtnSaved: { backgroundColor: COLORS.green, shadowColor: COLORS.green },
  submitBtnLoading: { opacity: 0.7 },
  submitBtnText: { fontSize: 16, fontFamily: "Inter_700Bold", color: COLORS.white },
  completedText: {
    fontSize: 13,
    fontFamily: "Inter_400Regular",
    color: COLORS.textSecondary,
    lineHeight: 20,
  },
  // Submitted photos (read-only)
  thumbWrap: { alignItems: "center", gap: 4 },
  thumb: { width: 100, height: 80, borderRadius: 10 },
  thumbLabel: { fontSize: 10, fontFamily: "Inter_500Medium", color: COLORS.textMuted },
});
```

FILE: artifacts/technician-app/babel.config.js
SIZE: 199 bytes

```
module.exports = function (api) {
  api.cache(true);
  return {
    presets: [["babel-preset-expo", { unstable_transformImportMeta: true }]],
    plugins: ["react-native-reanimated/plugin"],
  };
};
```

FILE: artifacts/technician-app/components/ErrorBoundary.tsx
SIZE: 1,674 bytes

```
import React, { Component, ComponentType, PropsWithChildren } from "react";

import { ErrorFallback, ErrorFallbackProps } from "@/components/ErrorFallback";

export type ErrorBoundaryProps = PropsWithChildren<{
  FallbackComponent?: ComponentType<ErrorFallbackProps>;
  onError?: (error: Error, stackTrace: string) => void;
}>;

type ErrorBoundaryState = { error: Error | null };

/**
 * This is a special case for for using the class components. Error boundaries must be class components because
  React only provides error boundary functionality through lifecycle methods (componentDidCatch and getDerivedStat
  eFromError) which are not available in functional components.
 * https://react.dev/reference/react/Component#catching-rendering-errors-with-an-error-boundary
 */
export class ErrorBoundary extends Component<
  ErrorBoundaryProps,
  ErrorBoundaryState
> {
  state: ErrorBoundaryState = { error: null };

  static defaultProps: {
    FallbackComponent: ComponentType<ErrorFallbackProps>;
  } = {
    FallbackComponent: ErrorFallback,
  };

  static getDerivedStateFromError(error: Error): ErrorBoundaryState {
    return { error };
  }

  componentDidCatch(error: Error, info: { componentStack: string }): void {
    if (typeof this.props.onError === "function") {
      this.props.onError(error, info.componentStack);
    }
  }

  resetError = (): void => {
    this.setState({ error: null });
  };

  render() {
    const { FallbackComponent } = this.props;

    return this.state.error && FallbackComponent ? (
      <FallbackComponent
        error={this.state.error}
```

```
        resetError={this.resetError}
      />
    ) : (
      this.props.children
    );
  }
}
```

FILE: artifacts/technician-app/components/ErrorFallback.tsx
SIZE: 7,103 bytes

```
import { Feather } from "@expo/vector-icons";
import { reloadAppAsync } from "expo";
import React, { useState } from "react";
import {
  Modal,
  Platform,
  Pressable,
  ScrollView,
  StyleSheet,
  Text,
  View,
  useColorScheme,
} from "react-native";
import { useSafeAreaInsets } from "react-native-safe-area-context";

export type ErrorFallbackProps = {
  error: Error;
  resetError: () => void;
};

export function ErrorFallback({ error, resetError }: ErrorFallbackProps) {
  const colorScheme = useColorScheme();
  const isDark = colorScheme === "dark";
  const insets = useSafeAreaInsets();

  const theme = {
    background: isDark ? "#000000" : "#FFFFFF",
    backgroundSecondary: isDark ? "#1C1C1E" : "#F2F2F7",
    text: isDark ? "#FFFFFF" : "#000000",
    textSecondary: isDark ? "rgba(255, 255, 255, 0.7)" : "rgba(0, 0, 0, 0.7)",
    link: "#007AFF",
    buttonText: "#FFFFFF",
  };

  const [isModalVisible, setIsModalVisible] = useState(false);

  const handleRestart = async () => {
    try {
      await reloadAppAsync();
    } catch (restartError) {
      console.error("Failed to restart app:", restartError);
      resetError();
    }
  };

  const formatErrorDetails = (): string => {
    let details = `Error: ${error.message}\n\n`;
    if (error.stack) {
      details += `Stack Trace:\n${error.stack}`;
```

```
  }
  return details;
};

const monoFont = Platform.select({
  ios: "Menlo",
  android: "monospace",
  default: "monospace",
});

return (
  <View style={[styles.container, { backgroundColor: theme.background }]}>
    {__DEV__ ? (
      <Pressable
        onPress={() => setIsModalVisible(true)}
        accessibilityLabel="View error details"
        accessibilityRole="button"
        style={({ pressed }) => [
          styles.topButton,
          {
            top: insets.top + 16,
            backgroundColor: theme.backgroundSecondary,
            opacity: pressed ? 0.8 : 1,
          },
        ]}
      >
        <Feather name="alert-circle" size={20} color={theme.text} />
      </Pressable>
    ) : null}

    <View style={styles.content}>
      <Text style={[styles.title, { color: theme.text }]}>
        Something went wrong
      </Text>

      <Text style={[styles.message, { color: theme.textSecondary }]}>
        Please reload the app to continue.
      </Text>

      <Pressable
        onPress={handleRestart}
        style={({ pressed }) => [
          styles.button,
          {
            backgroundColor: theme.link,
            opacity: pressed ? 0.9 : 1,
            transform: [{ scale: pressed ? 0.98 : 1 }],
          },
        ]}
      >
        <Text style={[styles.buttonText, { color: theme.buttonText }]}>
          Try Again
```

```
    </Text>
  </Pressable>
</View>

{__DEV__ ? (
  <Modal
    visible={isModalVisible}
    animationType="slide"
    transparent={true}
    onRequestClose={() => setIsModalVisible(false)}
  >
    <View style={styles.modalOverlay}>
      <View
        style={[
          styles.modalContainer,
          { backgroundColor: theme.background },
        ]}
      >
        <View
          style={[
            styles.modalHeader,
            {
              borderBottomColor: isDark
                ? "rgba(255, 255, 255, 0.1)"
                : "rgba(0, 0, 0, 0.1)",
            },
          ]}
        >
          <Text style={[styles.modalTitle, { color: theme.text }]}>
            Error Details
          </Text>
          <Pressable
            onPress={() => setIsModalVisible(false)}
            accessibilityLabel="Close error details"
            accessibilityRole="button"
            style={({ pressed }) => [
              styles.closeButton,
              { opacity: pressed ? 0.6 : 1 },
            ]}
          >
            <Feather name="x" size={24} color={theme.text} />
          </Pressable>
        </View>

        <ScrollView
          style={styles.modalScrollView}
          contentContainerStyle={[
            styles.modalScrollContent,
            { paddingBottom: insets.bottom + 16 },
          ]}
          showsVerticalScrollIndicator
        >
```

```
                <View
                  style={[
                    styles.errorContainer,
                    { backgroundColor: theme.backgroundSecondary },
                  ]}
                >
                  <Text
                    style={[
                      styles.errorText,
                      {
                        color: theme.text,
                        fontFamily: monoFont,
                      },
                    ]}
                    selectable
                  >
                    {formatErrorDetails()}
                  </Text>
                </View>
              </ScrollView>
            </View>
          </View>
        </Modal>
      ) : null}
    </View>
  );
}

const styles = StyleSheet.create({
  container: {
    flex: 1,
    width: "100%",
    height: "100%",
    justifyContent: "center",
    alignItems: "center",
    padding: 24,
  },
  content: {
    alignItems: "center",
    justifyContent: "center",
    gap: 16,
    width: "100%",
    maxWidth: 600,
  },
  title: {
    fontSize: 28,
    fontWeight: "700",
    textAlign: "center",
    lineHeight: 40,
  },
  message: {
    fontSize: 16,
```

```
    textAlign: "center",
    lineHeight: 24,
  },
  topButton: {
    position: "absolute",
    right: 16,
    width: 44,
    height: 44,
    borderRadius: 8,
    flexDirection: "row",
    alignItems: "center",
    justifyContent: "center",
    zIndex: 10,
  },
  button: {
    paddingVertical: 16,
    borderRadius: 8,
    paddingHorizontal: 24,
    minWidth: 200,
    shadowColor: "#000",
    shadowOffset: {
      width: 0,
      height: 2,
    },
    shadowOpacity: 0.1,
    shadowRadius: 4,
    elevation: 3,
  },
  buttonText: {
    fontWeight: "600",
    textAlign: "center",
    fontSize: 16,
  },
  modalOverlay: {
    flex: 1,
    backgroundColor: "rgba(0, 0, 0, 0.5)",
    justifyContent: "flex-end",
  },
  modalContainer: {
    width: "100%",
    height: "90%",
    borderTopLeftRadius: 16,
    borderTopRightRadius: 16,
  },
  modalHeader: {
    flexDirection: "row",
    justifyContent: "space-between",
    alignItems: "center",
    paddingHorizontal: 16,
    paddingTop: 16,
    paddingBottom: 12,
    borderBottomWidth: 1,
```

```
  },
  modalTitle: {
    fontSize: 20,
    fontWeight: "600",
  },
  closeButton: {
    width: 44,
    height: 44,
    alignItems: "center",
    justifyContent: "center",
  },
  modalScrollView: {
    flex: 1,
  },
  modalScrollContent: {
    padding: 16,
  },
  errorContainer: {
    width: "100%",
    borderRadius: 8,
    overflow: "hidden",
    padding: 16,
  },
  errorText: {
    fontSize: 12,
    lineHeight: 18,
    width: "100%",
  },
});
```

FILE: artifacts/technician-app/components/KeyboardAwareScrollViewCompat.tsx
SIZE: 724 bytes

```
import {
  KeyboardAwareScrollView,
  KeyboardAwareScrollViewProps,
} from "react-native-keyboard-controller";
import { Platform, ScrollView, ScrollViewProps } from "react-native";

type Props = KeyboardAwareScrollViewProps & ScrollViewProps;

export function KeyboardAwareScrollViewCompat({
  children,
  keyboardShouldPersistTaps = "handled",
  ...props
}: Props) {
  if (Platform.OS === "web") {
    return (
      <ScrollView keyboardShouldPersistTaps={keyboardShouldPersistTaps} {...props}>
        {children}
      </ScrollView>
    );
  }
  return (
    <KeyboardAwareScrollView
      keyboardShouldPersistTaps={keyboardShouldPersistTaps}
      {...props}
    >
      {children}
    </KeyboardAwareScrollView>
  );
}
```

FILE: artifacts/technician-app/constants/colors.ts
SIZE: 893 bytes

```
const COLORS = {
  // Brand
  navy: "#0B1E3E",
  navyDark: "#061428",
  navyLight: "#1A3A6B",
  navyMuted: "#E8EDF5",
  red: "#E30613",
  redDark: "#b00510",
  redMuted: "rgba(227, 6, 19, 0.10)",

  // Light backgrounds
  bg: "#F4F6FA",
  surface: "#FFFFFF",
  surfaceAlt: "#F8FAFD",

  // Card / border
  card: "#FFFFFF",
  cardBorder: "#E4EAF2",
  divider: "#ECF0F7",

  // Status colors (kept vivid for badges)
  green: "#16A34A",
  greenMuted: "#DCFCE7",
  amber: "#D97706",
  amberMuted: "#FEF3C7",
  sky: "#0284C7",
  skyMuted: "#E0F2FE",
  rose: "#E11D48",
  roseMuted: "#FFE4E6",
  indigo: "#4F46E5",
  indigoMuted: "#EEF2FF",
  gray: "#64748B",
  grayMuted: "#F1F5F9",

  // Text
  text: "#0F172A",
  textSecondary: "#475569",
  textMuted: "#94A3B8",
  textOnDark: "#FFFFFF",

  // Input
  inputBg: "#F8FAFD",
  inputBorder: "#D4DCE8",

  white: "#FFFFFF",
};

export default COLORS;
```

FILE: artifacts/technician-app/contexts/auth.tsx
SIZE: 2,122 bytes

```
import AsyncStorage from "@react-native-async-storage/async-storage";
import React, { createContext, useContext, useState, useEffect, useMemo, ReactNode } from "react";
import { setAuthToken } from "@/lib/api";

const AUTH_KEY = "aces_driver_auth";

interface DriverUser {
  driverId: number;
  name: string;
  email: string;
  phone?: string;
  zone: string;
  token: string;
  imageUrl?: string;
}

interface AuthContextValue {
  user: DriverUser | null;
  isLoading: boolean;
  login: (user: DriverUser) => Promise<void>;
  logout: () => Promise<void>;
  updateUser: (partial: Partial<DriverUser>) => Promise<void>;
}

const AuthContext = createContext<AuthContextValue | null>(null);

export function AuthProvider({ children }: { children: ReactNode }) {
  const [user, setUser] = useState<DriverUser | null>(null);
  const [isLoading, setIsLoading] = useState(true);

  useEffect(() => {
    const load = async () => {
      try {
        const stored = await AsyncStorage.getItem(AUTH_KEY);
        if (stored) {
          const parsed: DriverUser = JSON.parse(stored);
          setUser(parsed);
          setAuthToken(parsed.token);
        }
      } catch {
        // ignore storage errors
      }
      setIsLoading(false);
    };
    load();
  }, []);

  const login = async (u: DriverUser) => {
    await AsyncStorage.setItem(AUTH_KEY, JSON.stringify(u));
```

```
    setUser(u);
    setAuthToken(u.token);
  };

  const logout = async () => {
    await AsyncStorage.removeItem(AUTH_KEY);
    setUser(null);
    setAuthToken(null);
  };

  const updateUser = async (partial: Partial<DriverUser>) => {
    if (!user) return;
    const updated = { ...user, ...partial };
    await AsyncStorage.setItem(AUTH_KEY, JSON.stringify(updated));
    setUser(updated);
  };

  const value = useMemo(
    () => ({ user, isLoading, login, logout, updateUser }),
    [user, isLoading],
  );

  return <AuthContext.Provider value={value}>{children}</AuthContext.Provider>;
}

export function useAuth() {
  const ctx = useContext(AuthContext);
  if (!ctx) throw new Error("useAuth must be used within AuthProvider");
  return ctx;
}
```

FILE: artifacts/technician-app/eas.json
SIZE: 693 bytes


```
{
  "cli": {
    "version": ">= 14.0.0"
  },
  "build": {
    "development": {
      "developmentClient": true,
      "distribution": "internal",
      "android": {
        "buildType": "apk"
      }
    },
    "preview": {
      "distribution": "internal",
      "android": {
        "buildType": "apk"
      },
      "ios": {
        "simulator": false
      }
    },
    "production": {
      "android": {
        "buildType": "app-bundle"
      },
      "env": {
        "EXPO_PUBLIC_DOMAIN": "web-portal-bannagaaltieb.replit.app"
      }
    }
  },
  "submit": {
    "production": {
      "ios": {
        "appleTeamId": "7V975V396R",
        "ascAppId": "6770050434"
      }
    }
  }
}
```

FILE: artifacts/technician-app/expo-env.d.ts
SIZE: 110 bytes

```
/// <reference types="expo/types" />

// NOTE: This file should not be edited and should be in your git ignore
```

FILE: artifacts/technician-app/google-services.json
SIZE: 905 bytes


```
{
  "_instructions": "Replace this file with your real google-services.json from the Firebase Console. See README.
  md for full setup instructions.",
  "project_info": {
    "project_number": "TODO_REPLACE_WITH_YOUR_FIREBASE_PROJECT_NUMBER",
    "firebase_url": "https://TODO_REPLACE.firebaseio.com",
    "project_id": "TODO_REPLACE_WITH_YOUR_PROJECT_ID",
    "storage_bucket": "TODO_REPLACE.appspot.com"
  },
  "client": [
    {
      "client_info": {
        "mobilesdk_app_id": "TODO_REPLACE_WITH_YOUR_APP_ID",
        "android_info": {
          "package_name": "com.acessa.technician"
        }
      },
      "oauth_client": [],
      "api_key": [
        {
          "current_key": "TODO_REPLACE_WITH_YOUR_FIREBASE_API_KEY"
        }
      ],
      "services": {
        "appinvite_service": {
          "other_platform_oauth_client": []
        }
      }
    }
  ],
  "configuration_version": "1"
}
```

FILE: artifacts/technician-app/lib/api.ts
SIZE: 690 bytes

```
const BASE = `https://${process.env.EXPO_PUBLIC_DOMAIN}`;

export function getBaseUrl(): string {
  return BASE;
}

let _authToken: string | null = null;

export function setAuthToken(token: string | null) {
  _authToken = token;
}

export function getAuthToken(): string | null {
  return _authToken;
}

export async function apiFetch(path: string, init?: RequestInit) {
  const headers: Record<string, string> = {
    "Content-Type": "application/json",
    ...(init?.headers as Record<string, string> ?? {}),
  };
  if (_authToken) {
    headers["Authorization"] = `Bearer ${_authToken}`;
  }
  const res = await fetch(`${BASE}${path}`, {
    ...init,
    headers,
  });
  return res;
}
```

FILE: artifacts/technician-app/lib/push.ts
SIZE: 316 bytes

```
/**
 * Push notification registration   stub for driver app.
 * Push notifications for drivers are managed server-side.
 * This module is kept for compatibility but is a no-op.
 */
export async function registerPushToken(_driverId: number): Promise<void> {
  // No-op: driver push tokens are managed server-side
}
```

FILE: artifacts/technician-app/metro.config.js
SIZE: 600 bytes

```
const { getDefaultConfig } = require("expo/metro-config");

const config = getDefaultConfig(__dirname);

// Block temporary directories created by expo-notifications post-install scripts.
// These directories are created and immediately deleted during pnpm install;
// Metro’s FallbackWatcher must not attempt to watch them.
const defaultBlockList = config.resolver.blockList ?? [];
const blockListArr = Array.isArray(defaultBlockList)
  ? defaultBlockList
  : [defaultBlockList];

config.resolver.blockList = [
  ...blockListArr,
  /.*\/expo-notifications_tmp_\d+\/.*/,
];

module.exports = config;
```

FILE: artifacts/technician-app/package.json
SIZE: 2,370 bytes

```
{
  "name": "@workspace/technician-app",
  "version": "0.0.0",
  "private": true,
  "main": "expo-router/entry",
  "scripts": {
    "dev": "EXPO_TOKEN= EXPO_PACKAGER_PROXY_URL=https://$REPLIT_EXPO_DEV_DOMAIN EXPO_PUBLIC_DOMAIN=$REPLIT_DEV_D
  OMAIN EXPO_PUBLIC_REPL_ID=$REPL_ID REACT_NATIVE_PACKAGER_HOSTNAME=$REPLIT_DEV_DOMAIN pnpm exec expo start --loca
  lhost --port $PORT --non-interactive",
    "build": "node scripts/build.js",
    "serve": "node server/serve.js",
    "typecheck": "tsc -p tsconfig.json --noEmit",
    "android": "expo run:android",
    "ios": "expo run:ios"
  },
  "devDependencies": {
    "@babel/core": "^7.25.2",
    "@expo-google-fonts/inter": "^0.4.0",
    "@expo/cli": "54.0.23",
    "@expo/ngrok": "^4.1.0",
    "@expo/vector-icons": "^15.0.3",
    "@react-native-async-storage/async-storage": "2.2.0",
    "@stardazed/streams-text-encoding": "^1.0.2",
    "@tanstack/react-query": "catalog:",
    "@types/react": "~19.1.10",
    "@types/react-dom": "~19.1.7",
    "@ungap/structured-clone": "^1.3.0",
    "@workspace/api-client-react": "workspace:*",
    "babel-plugin-react-compiler": "^19.0.0-beta-e993439-20250117",
    "eas-cli": "^18.9.1",
    "expo": "~54.0.27",
    "expo-blur": "~15.0.8",
    "expo-constants": "~18.0.11",
    "expo-font": "~14.0.10",
    "expo-glass-effect": "~0.1.4",
    "expo-haptics": "~15.0.8",
    "expo-image": "~3.0.11",
    "expo-image-picker": "~17.0.9",
    "expo-linear-gradient": "~15.0.8",
    "expo-linking": "~8.0.10",
    "expo-location": "~19.0.8",
    "expo-router": "~6.0.17",
    "expo-splash-screen": "~31.0.12",
    "expo-status-bar": "~3.0.9",
    "expo-symbols": "~1.0.8",
    "expo-system-ui": "~6.0.9",
    "expo-web-browser": "~15.0.10",
    "react": "catalog:",
    "react-dom": "catalog:",
```

```
    "react-native": "0.81.5",
    "react-native-gesture-handler": "~2.28.0",
    "react-native-keyboard-controller": "^1.20.6",
    "react-native-reanimated": "~4.1.1",
    "react-native-safe-area-context": "~5.6.0",
    "react-native-screens": "~4.16.0",
    "react-native-svg": "15.12.1",
    "react-native-web": "^0.21.0",
    "react-native-worklets": "0.5.1",
    "typescript": "~5.9.2",
    "zod": "catalog:",
    "zod-validation-error": "^3.4.0"
  },
  "dependencies": {
    "expo-notifications": "~0.32.16",
    "expo": "~54.0.33",
    "react": "19.1.0",
    "react-native": "0.81.5"
  }
}
```

FILE: artifacts/technician-app/README.md
SIZE: 5,965 bytes

ACES Technician App — Build & Distribution Guide

Overview

A React Native (Expo) mobile app for field technicians to:
- Receive mission assignments and push notifications
- View fueling task details (fuel readings, site info, driver notes)
- Submit daily follow-up reports (reviewed / issue / pending)
- Connect to the ACES Managed Services API

Quick Start (Testing via Expo Go)

Technicians can test the app immediately on their phones without installing an APK:

1. Install **Expo Go** from the App Store (iOS) or Google Play (Android)
2. Scan the QR code shown in the Replit preview sidebar
3. Log in with your technician credentials (email + password)

> **Note:** Push notifications are not active in Expo Go. All other features (login, missions, follow-ups) work fully.

Firebase Setup (Required for Push Notifications)

Push notifications use the **Expo Push API** backed by Firebase Cloud Messaging (FCM). You need a Firebase project for Android push delivery.

Step 1 — Create a Firebase project

1. Go to console.firebase.google.com
2. Click **Add project** → name it (e.g., `ACES Technician`)
3. Disable Google Analytics (optional) → **Create project**

Step 2 — Add an Android app to Firebase

1. In your project overview, click the **Android** icon
2. Set **Android package name**: `com.acessa.technician`
3. Click **Register app**
4. Download the `google-services.json` file

Step 3 — Replace the placeholder google-services.json

Copy the downloaded file into the project:

```bash
cp ~/Downloads/google-services.json artifacts/technician-app/google-services.json
```

```

The placeholder at `artifacts/technician-app/google-services.json` must be replaced before building.

### Step 4 — Add FCM key to Expo

1. In Firebase Console → Project settings → **Cloud Messaging** tab
2. Copy the **Server key** (Legacy) or create a Cloud Messaging API (V1) key
3. In [expo.dev](https://expo.dev) → your project → **Credentials** → Android → set the FCM key

---

## Building the APK (Android)

### Prerequisites

1. Create a free account at [expo.dev](https://expo.dev)
2. Install EAS CLI:
   ```bash
   npm install -g eas-cli
   eas login
   ```
3. Complete the Firebase Setup above and ensure `google-services.json` is replaced.

Steps

```bash
cd artifacts/technician-app

# Initialize your EAS project (first time only)
eas project:init

# Install expo-notifications for the native build
pnpm add expo-notifications@~0.32.16

# Build APK for internal distribution (no Play Store)
eas build --platform android --profile preview
```

The build runs in Expo's cloud (~10-15 minutes). When done, you'll get a download link for the `.apk` file.

Installing on Android devices

1. Download the `.apk` from the EAS dashboard
2. Send the file to technicians via email or WhatsApp
3. On Android: Settings → Security → Enable "Install from unknown sources"
4. Open the `.apk` file to install

Building for iOS (iPhone/iPad)
```

Prerequisites

- Apple Developer Program membership ($99/year) at developer.apple.com
- macOS with Xcode (for local builds) or EAS Build (cloud)

Steps

```bash
# Build for iOS via EAS (cloud, recommended)
eas build --platform ios --profile preview

# This will ask for your Apple credentials
# Output: a .ipa file that can be distributed via TestFlight or Ad Hoc
```

Distribution via TestFlight (recommended for iOS)

1. Build the `.ipa` using EAS
2. Upload to App Store Connect ? TestFlight
3. Add testers by email
4. Testers receive an email to install TestFlight, then the app

---

Push Notifications How It Works

1. On login (in a native EAS build), the app calls `registerPushToken()` which:
   - Requests notification permissions from the OS
   - Gets an Expo Push Token from the Expo service
   - Registers it with the ACES API at `PUT /api/technicians/:id/fcm-token`
2. When an admin assigns a mission in the web portal, the API sends a push notification via `https://exp.host/--/api/v2/push/send`
3. The technician receives the notification even if the app is in the background

> The push notification delivery code (`lib/push.ts`) uses a dynamic import so it gracefully skips registration in Expo Go and web previews, avoiding any runtime errors.

Environment Variables

The app uses `EXPO_PUBLIC_DOMAIN` to connect to the API. This is automatically set in the Replit environment. For production builds, configure it in `eas.json`:

```json
{
  "build": {
    "production": {
      "env": {
        "EXPO_PUBLIC_DOMAIN": "your-production-domain.replit.app"
      }
    }
```

```
  }
}
```

App Identifiers

Platform	Identifier
iOS	`com.acessa.technician`
Android	`com.acessa.technician`

Technician Accounts

Technician accounts are managed by the administrator via the ACES Admin Portal ? Technicians section.

Contact your administrator for your login credentials (email + password) before using the app.

Architecture

```
artifacts/technician-app/
  app/
    _layout.tsx          # Root layout (auth context, providers)
    index.tsx            # Redirect to login or tabs
    login.tsx            # Login screen
    (tabs)/
      _layout.tsx        # Bottom tab bar (NativeTabs + BlurView fallback)
      index.tsx          # Tasks (mission list)
      notifications.tsx  # Alerts
      profile.tsx        # Profile & sign out
    mission/
      [id].tsx           # Mission detail + follow-up form
  contexts/auth.tsx      # Auth state (AsyncStorage)
  lib/api.ts             # API fetch helper
  lib/push.ts            # Push token registration (graceful fallback)
  constants/colors.ts    # ACES brand colors
  google-services.json   # Firebase config placeholder (replace before EAS build)
  eas.json               # EAS Build profiles
```

FILE: artifacts/technician-app/scripts/build.js
SIZE: 15,525 bytes

```
const fs = require("fs");
const path = require("path");
const { spawn } = require("child_process");
const { Readable } = require("stream");
const { pipeline } = require("stream/promises");

let metroProcess = null;

const projectRoot = path.resolve(__dirname, "..");

function findWorkspaceRoot(startDir) {
  let dir = startDir;
  while (dir !== path.dirname(dir)) {
    if (fs.existsSync(path.join(dir, "pnpm-workspace.yaml"))) {
      return dir;
    }
    dir = path.dirname(dir);
  }
  throw new Error("Could not find workspace root (no pnpm-workspace.yaml found)");
}

const workspaceRoot = findWorkspaceRoot(projectRoot);
const basePath = (process.env.BASE_PATH || "/").replace(/\/+$/, "");

function exitWithError(message) {
  console.error(message);
  if (metroProcess) {
    metroProcess.kill();
  }
  process.exit(1);
}

function setupSignalHandlers() {
  const cleanup = () => {
    if (metroProcess) {
      console.log("Cleaning up Metro process...");
      metroProcess.kill();
    }
    process.exit(0);
  };

  process.on("SIGINT", cleanup);
  process.on("SIGTERM", cleanup);
  process.on("SIGHUP", cleanup);
}

function stripProtocol(domain) {
  let urlString = domain.trim();
```

```
  if (!/^https?:\/\//i.test(urlString)) {
    urlString = `https://${urlString}`;
  }

  return new URL(urlString).host;
}

function getDeploymentDomain() {
  if (process.env.REPLIT_INTERNAL_APP_DOMAIN) {
    return stripProtocol(process.env.REPLIT_INTERNAL_APP_DOMAIN);
  }

  if (process.env.REPLIT_DEV_DOMAIN) {
    return stripProtocol(process.env.REPLIT_DEV_DOMAIN);
  }

  if (process.env.EXPO_PUBLIC_DOMAIN) {
    return stripProtocol(process.env.EXPO_PUBLIC_DOMAIN);
  }

  console.error(
    "ERROR: No deployment domain found. Set REPLIT_INTERNAL_APP_DOMAIN, REPLIT_DEV_DOMAIN, or EXPO_PUBLIC_DOMAIN
  ",
  );
  process.exit(1);
}

function prepareDirectories(timestamp) {
  console.log("Preparing build directories...");

  const staticBuild = path.join(projectRoot, "static-build");
  if (fs.existsSync(staticBuild)) {
    fs.rmSync(staticBuild, { recursive: true });
  }

  const dirs = [
    path.join(staticBuild, timestamp, "_expo", "static", "js", "ios"),
    path.join(staticBuild, timestamp, "_expo", "static", "js", "android"),
    path.join(staticBuild, "ios"),
    path.join(staticBuild, "android"),
  ];

  for (const dir of dirs) {
    fs.mkdirSync(dir, { recursive: true });
  }

  console.log("Build:", timestamp);
}

function clearMetroCache() {
  console.log("Clearing Metro cache...");
```

```
  const cacheDirs = [
    path.join(projectRoot, ".metro-cache"),
    path.join(projectRoot, "node_modules/.cache/metro"),
  ];

  for (const dir of cacheDirs) {
    if (fs.existsSync(dir)) {
      fs.rmSync(dir, { recursive: true, force: true });
    }
  }

  console.log("Cache cleared");
}

async function checkMetroHealth() {
  try {
    const response = await fetch("http://localhost:8081/status", {
      signal: AbortSignal.timeout(5000),
    });
    return response.ok;
  } catch {
    return false;
  }
}

function getExpoPublicReplId() {
  return process.env.REPL_ID || process.env.EXPO_PUBLIC_REPL_ID;
}

async function startMetro(expoPublicDomain, expoPublicReplId) {
  const isRunning = await checkMetroHealth();
  if (isRunning) {
    console.log("Metro already running");
    return;
  }

  console.log("Starting Metro...");
  console.log(`Setting EXPO_PUBLIC_DOMAIN=${expoPublicDomain}`);
  const env = {
    ...process.env,
    EXPO_PUBLIC_DOMAIN: expoPublicDomain,
    EXPO_PUBLIC_REPL_ID: expoPublicReplId,
  };
  delete env.EXPO_TOKEN;

  if (expoPublicReplId) {
    console.log(`Setting EXPO_PUBLIC_REPL_ID=${expoPublicReplId}`);
  }

  metroProcess = spawn(
    "pnpm",
    [
```

```
      "exec",
      "expo",
      "start",
      "--no-dev",
      "--minify",
      "--localhost",
    ],
    {
      stdio: ["ignore", "pipe", "pipe"],
      detached: false,
      cwd: projectRoot,
      env,
    },
  );

  if (metroProcess.stdout) {
    metroProcess.stdout.on("data", (data) => {
      const output = data.toString().trim();
      if (output) console.log(`[Metro] ${output}`);
    });
  }
  if (metroProcess.stderr) {
    metroProcess.stderr.on("data", (data) => {
      const output = data.toString().trim();
      if (output) console.error(`[Metro Error] ${output}`);
    });
  }

  for (let i = 0; i < 60; i++) {
    await new Promise((resolve) => setTimeout(resolve, 1000));

    const healthy = await checkMetroHealth();
    if (healthy) {
      console.log("Metro ready");
      return;
    }
  }

  console.error("Metro timeout");
  process.exit(1);
}

async function downloadFile(url, outputPath) {
  const controller = new AbortController();
  const fiveMinMS = 5 * 60 * 1_000;
  const timeoutId = setTimeout(() => controller.abort(), fiveMinMS);

  try {
    console.log(`Downloading: ${url}`);
    const response = await fetch(url, { signal: controller.signal });

    if (!response.ok) {
```

```
      throw new Error(‘HTTP ${response.status}‘);
    }

    const file = fs.createWriteStream(outputPath);
    await pipeline(Readable.fromWeb(response.body), file);

    const fileSize = fs.statSync(outputPath).size;

    if (fileSize === 0) {
      fs.unlinkSync(outputPath);
      throw new Error("Downloaded file is empty");
    }
  } catch (error) {
    if (fs.existsSync(outputPath)) {
      fs.unlinkSync(outputPath);
    }

    if (error.name === "AbortError") {
      throw new Error(‘Download timeout after 5m: ${url}‘);
    }
    throw error;
  } finally {
    clearTimeout(timeoutId);
  }
}

async function downloadBundle(platform, timestamp) {
  const entryPath = path.resolve(projectRoot, "node_modules", "expo-router", "entry");
  const bundlePath = path.relative(workspaceRoot, entryPath);
  const url = new URL(‘http://localhost:8081/${bundlePath}.bundle‘);
  url.searchParams.set("platform", platform);
  url.searchParams.set("dev", "false");
  url.searchParams.set("hot", "false");
  url.searchParams.set("lazy", "false");
  url.searchParams.set("minify", "true");

  const output = path.join(
    "static-build",
    timestamp,
    "_expo",
    "static",
    "js",
    platform,
    "bundle.js",
  );

  console.log(‘Fetching ${platform} bundle...‘);
  await downloadFile(url.toString(), output);
  console.log(‘${platform} bundle ready‘);
}

async function downloadManifest(platform) {
```

```
  const controller = new AbortController();
  const timeoutId = setTimeout(() => controller.abort(), 300_000);

  try {
    console.log(‘Fetching ${platform} manifest...‘);
    const response = await fetch("http://localhost:8081/manifest", {
      headers: { "expo-platform": platform },
      signal: controller.signal,
    });

    if (!response.ok) {
      throw new Error(‘HTTP ${response.status}‘);
    }

    const manifest = await response.json();
    console.log(‘${platform} manifest ready‘);
    return manifest;
  } catch (error) {
    if (error.name === "AbortError") {
      throw new Error(
        ‘Manifest download timeout after 5m for platform: ${platform}‘,
      );
    }
    throw error;
  } finally {
    clearTimeout(timeoutId);
  }
}

async function downloadBundlesAndManifests(timestamp) {
  console.log("Downloading bundles and manifests...");
  console.log("This may take several minutes for production builds...");

  try {
    // Bundles are sequential   Metro can’t handle both platforms simultaneously
    // without stalling. Manifests are cheap and run in parallel after.
    await downloadBundle("ios", timestamp);
    await downloadBundle("android", timestamp);

    const [iosManifest, androidManifest] = await Promise.all([
      downloadManifest("ios"),
      downloadManifest("android"),
    ]);

    console.log("All downloads completed successfully");
    return { ios: iosManifest, android: androidManifest };
  } catch (error) {
    exitWithError(‘Download failed: ${error.message}‘);
  }
}

function extractAssets(timestamp) {
```

```
  const staticBuild = path.join(projectRoot, "static-build");
  const bundles = {
    ios: fs.readFileSync(
      path.join(staticBuild, timestamp, "_expo", "static", "js", "ios", "bundle.js"),
      "utf-8",
    ),
    android: fs.readFileSync(
      path.join(staticBuild, timestamp, "_expo", "static", "js", "android", "bundle.js"),
      "utf-8",
    ),
  };

  const assetsMap = new Map();
  const assetPattern =
    /httpServerLocation:"([^"]+)"[^}]*hash:"([^"]+)"[^}]*name:"([^"]+)"[^}]*type:"([^"]+)"/g;

  const extractFromBundle = (bundle, platform) => {
    for (const match of bundle.matchAll(assetPattern)) {
      const originalPath = match[1];
      const filename = match[3] + "." + match[4];

      const tempUrl = new URL(`http://localhost:8081${originalPath}`);
      const unstablePath = tempUrl.searchParams.get("unstable_path");

      if (!unstablePath) {
        throw new Error(`Asset missing unstable_path: ${originalPath}`);
      }

      const decodedPath = decodeURIComponent(unstablePath);
      const key = path.posix.join(decodedPath, filename);

      if (!assetsMap.has(key)) {
        const asset = {
          url: path.posix.join("/", decodedPath, filename),
          originalPath: originalPath,
          filename: filename,
          relativePath: decodedPath,
          hash: match[2],
          platforms: new Set(),
        };

        assetsMap.set(key, asset);
      }
      assetsMap.get(key).platforms.add(platform);
    }
  };

  extractFromBundle(bundles.ios, "ios");
  extractFromBundle(bundles.android, "android");

  return Array.from(assetsMap.values());
}
```

```
async function downloadAssets(assets, timestamp) {
  if (assets.length === 0) {
    return 0;
  }

  console.log("Copying assets...");
  let successCount = 0;
  const failures = [];

  const downloadPromises = assets.map(async (asset) => {
    const tempUrl = new URL(`http://localhost:8081${asset.originalPath}`);
    const unstablePath = tempUrl.searchParams.get("unstable_path");

    if (!unstablePath) {
      throw new Error(`Asset missing unstable_path: ${asset.originalPath}`);
    }

    const decodedPath = decodeURIComponent(unstablePath);

    const outputDir = path.join(
      projectRoot,
      "static-build",
      timestamp,
      "_expo",
      "static",
      "js",
      asset.relativePath,
    );
    fs.mkdirSync(outputDir, { recursive: true });
    const output = path.join(outputDir, asset.filename);

    try {
      const candidates = [
        path.join(projectRoot, decodedPath, asset.filename),
        path.join(workspaceRoot, decodedPath, asset.filename),
      ];
      const found = candidates.find((p) => fs.existsSync(p));
      if (!found) {
        throw new Error(`Asset not found on disk: ${asset.filename}`);
      }
      fs.copyFileSync(found, output);
      successCount++;
    } catch (error) {
      failures.push({
        filename: asset.filename,
        error: error.message,
        url: asset.originalPath,
      });
    }
  });
```

```
  await Promise.all(downloadPromises);

  if (failures.length > 0) {
    const errorMsg =
      `Failed to download ${failures.length} asset(s):\n` +
      failures
        .map((f) => `  - ${f.filename}: ${f.error} (${f.url})`)
        .join("\n");
    exitWithError(errorMsg);
  }

  console.log(`Copied ${successCount} assets`);
  return successCount;
}

function updateBundleUrls(timestamp, baseUrl) {
  const updateForPlatform = (platform) => {
    const bundlePath = path.join(
      projectRoot,
      "static-build",
      timestamp,
      "_expo",
      "static",
      "js",
      platform,
      "bundle.js",
    );
    let bundle = fs.readFileSync(bundlePath, "utf-8");

    bundle = bundle.replace(
      /httpServerLocation:"(\/[^"]+)"/g,
      (_match, capturedPath) => {
        const tempUrl = new URL(`http://localhost:8081${capturedPath}`);
        const unstablePath = tempUrl.searchParams.get("unstable_path");

        if (!unstablePath) {
          throw new Error(
            `Asset missing unstable_path in bundle: ${capturedPath}`,
          );
        }

        const decodedPath = decodeURIComponent(unstablePath);
        return `httpServerLocation:"${baseUrl}${basePath}/${timestamp}/_expo/static/js/${decodedPath}"`;
      },
    );

    fs.writeFileSync(bundlePath, bundle);
  };

  updateForPlatform("ios");
  updateForPlatform("android");
  console.log("Updated bundle URLs");
```

```
}

function updateManifests(manifests, timestamp, baseUrl, assetsByHash) {
  const updateForPlatform = (platform, manifest) => {
    if (!manifest.launchAsset || !manifest.extra) {
      exitWithError(‘Malformed manifest for ${platform}‘);
    }

    manifest.launchAsset.url = ‘${baseUrl}${basePath}/${timestamp}/_expo/static/js/${platform}/bundle.js‘;
    manifest.launchAsset.key = ‘bundle-${timestamp}‘;
    manifest.createdAt = new Date(
      Number(timestamp.split("-")[0]),
    ).toISOString();
    manifest.extra.expoClient.hostUri =
      baseUrl.replace("https://", "") + "/" + platform;
    manifest.extra.expoGo.debuggerHost =
      baseUrl.replace("https://", "") + "/" + platform;
    manifest.extra.expoGo.packagerOpts.dev = false;

    if (manifest.assets && manifest.assets.length > 0) {
      manifest.assets.forEach((asset) => {
        if (!asset.url) return;

        const hash = asset.hash;
        if (!hash) return;

        const assetInfo = assetsByHash.get(hash);
        if (!assetInfo) return;

        asset.url = ‘${baseUrl}${basePath}/${timestamp}/_expo/static/js/${assetInfo.relativePath}/${assetInfo.fi
  lename}‘;
      });
    }

    fs.writeFileSync(
      path.join(projectRoot, "static-build", platform, "manifest.json"),
      JSON.stringify(manifest, null, 2),
    );
  };

  updateForPlatform("ios", manifests.ios);
  updateForPlatform("android", manifests.android);
  console.log("Manifests updated");
}

async function main() {
  console.log("Building static Expo Go deployment...");

  setupSignalHandlers();

  const domain = getDeploymentDomain();
  const expoPublicReplId = getExpoPublicReplId();
```

```
  const baseUrl = `https://${domain}`;
  const timestamp = `${Date.now()}-${process.pid}`;

  prepareDirectories(timestamp);
  clearMetroCache();

  await startMetro(domain, expoPublicReplId);

  const downloadTimeout = 600000;
  const downloadPromise = downloadBundlesAndManifests(timestamp);
  const timeoutPromise = new Promise((_, reject) => {
    setTimeout(() => {
      reject(
        new Error(
          `Overall download timeout after ${downloadTimeout / 1000} seconds. ` +
            "Metro may be struggling to generate bundles. Check Metro logs above.",
        ),
      );
    }, downloadTimeout);
  });

  const manifests = await Promise.race([downloadPromise, timeoutPromise]);

  console.log("Processing assets...");
  const assets = extractAssets(timestamp);
  console.log("Found", assets.length, "unique asset(s)");

  const assetsByHash = new Map();
  for (const asset of assets) {
    assetsByHash.set(asset.hash, {
      relativePath: asset.relativePath,
      filename: asset.filename,
    });
  }

  const assetCount = await downloadAssets(assets, timestamp);

  if (assetCount > 0) {
    updateBundleUrls(timestamp, baseUrl);
  }

  console.log("Updating manifests and creating landing page...");
  updateManifests(manifests, timestamp, baseUrl, assetsByHash);

  console.log("Build complete! Deploy to:", baseUrl);

  if (metroProcess) {
    metroProcess.kill();
  }
  process.exit(0);
}
```

```
main().catch((error) => {
  console.error("Build failed:", error.message);
  if (metroProcess) {
    metroProcess.kill();
  }
  process.exit(1);
});
```

FILE: artifacts/technician-app/server/serve.js
SIZE: 4,162 bytes

```
/**
 * Standalone production server for Expo static builds.
 *
 * Serves the output of build.js (static-build/) with two special routes:
 * - GET / or /manifest with expo-platform header ? platform manifest JSON
 * - GET / without expo-platform ? landing page HTML
 * Everything else falls through to static file serving from ./static-build/.
 *
 * Zero external dependencies   uses only Node.js built-ins (http, fs, path).
 */

const http = require("http");
const fs = require("fs");
const path = require("path");

const STATIC_ROOT = path.resolve(__dirname, "..", "static-build");
const TEMPLATE_PATH = path.resolve(__dirname, "templates", "landing-page.html");
const basePath = (process.env.BASE_PATH || "/").replace(/\/+$/, "");

const MIME_TYPES = {
  ".html": "text/html; charset=utf-8",
  ".js": "application/javascript; charset=utf-8",
  ".json": "application/json; charset=utf-8",
  ".css": "text/css; charset=utf-8",
  ".png": "image/png",
  ".jpg": "image/jpeg",
  ".jpeg": "image/jpeg",
  ".gif": "image/gif",
  ".svg": "image/svg+xml",
  ".ico": "image/x-icon",
  ".woff": "font/woff",
  ".woff2": "font/woff2",
  ".ttf": "font/ttf",
  ".otf": "font/otf",
  ".map": "application/json",
};

function getAppName() {
  try {
    const appJsonPath = path.resolve(__dirname, "..", "app.json");
    const appJson = JSON.parse(fs.readFileSync(appJsonPath, "utf-8"));
    return appJson.expo?.name || "App Landing Page";
  } catch {
    return "App Landing Page";
  }
}

function serveManifest(platform, res) {
  const manifestPath = path.join(STATIC_ROOT, platform, "manifest.json");
```

```
  if (!fs.existsSync(manifestPath)) {
    res.writeHead(404, { "content-type": "application/json" });
    res.end(
      JSON.stringify({ error: `Manifest not found for platform: ${platform}` }),
    );
    return;
  }

  const manifest = fs.readFileSync(manifestPath, "utf-8");
  res.writeHead(200, {
    "content-type": "application/json",
    "expo-protocol-version": "1",
    "expo-sfv-version": "0",
  });
  res.end(manifest);
}

function serveLandingPage(req, res, landingPageTemplate, appName) {
  const forwardedProto = req.headers["x-forwarded-proto"];
  const protocol = forwardedProto || "https";
  const host = req.headers["x-forwarded-host"] || req.headers["host"];
  const baseUrl = `${protocol}://${host}`;
  const expsUrl = `${host}`;

  const html = landingPageTemplate
    .replace(/BASE_URL_PLACEHOLDER/g, baseUrl)
    .replace(/EXPS_URL_PLACEHOLDER/g, expsUrl)
    .replace(/APP_NAME_PLACEHOLDER/g, appName);

  res.writeHead(200, { "content-type": "text/html; charset=utf-8" });
  res.end(html);
}

function serveStaticFile(urlPath, res) {
  const safePath = path.normalize(urlPath).replace(/^(\.\.(\/|\\|$))+/, "");
  const filePath = path.join(STATIC_ROOT, safePath);

  if (!filePath.startsWith(STATIC_ROOT)) {
    res.writeHead(403);
    res.end("Forbidden");
    return;
  }

  if (!fs.existsSync(filePath) || fs.statSync(filePath).isDirectory()) {
    res.writeHead(404);
    res.end("Not Found");
    return;
  }

  const ext = path.extname(filePath).toLowerCase();
  const contentType = MIME_TYPES[ext] || "application/octet-stream";
```

```
  const content = fs.readFileSync(filePath);
  res.writeHead(200, { "content-type": contentType });
  res.end(content);
}

const landingPageTemplate = fs.readFileSync(TEMPLATE_PATH, "utf-8");
const appName = getAppName();

const server = http.createServer((req, res) => {
  const url = new URL(req.url || "/", `http://${req.headers.host}`);
  let pathname = url.pathname;

  if (basePath && pathname.startsWith(basePath)) {
    pathname = pathname.slice(basePath.length) || "/";
  }

  if (pathname === "/" || pathname === "/manifest") {
    const platform = req.headers["expo-platform"];
    if (platform === "ios" || platform === "android") {
      return serveManifest(platform, res);
    }

    if (pathname === "/") {
      return serveLandingPage(req, res, landingPageTemplate, appName);
    }
  }

  serveStaticFile(pathname, res);
});

const port = parseInt(process.env.PORT || "3000", 10);
server.listen(port, "0.0.0.0", () => {
  console.log(`Serving static Expo build on port ${port}`);
});
```

FILE: artifacts/technician-app/server/templates/landing-page.html
SIZE: 12,442 bytes

```
<!doctype html>
<html>
  <head>
    <title>APP_NAME_PLACEHOLDER</title>
    <meta charset="utf-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1" />
    <link rel="icon" type="image/svg+xml" href="data:image/svg+xml,%3Csvg width='180' height='180' viewBox='0 0
  180 180' fill='none' xmlns='http://www.w3.org/2000/svg'%3E%3Crect width='180' height='180' rx='36' fill='%23FF3C
  00'/%3E%3C/svg%3E" />
    <style>
      * {
        box-sizing: border-box;
      }
      body {
        font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif;
        margin: 0;
        padding: 32px 20px;
        text-align: center;
        background: #fff;
        color: #222;
        line-height: 1.5;
        min-height: 100vh;
      }
      .wrapper {
        max-width: 480px;
        margin: 0 auto;
      }
      h1 {
        font-size: 26px;
        font-weight: 600;
        margin: 0;
        color: #111;
      }
      .subtitle {
        font-size: 15px;
        color: #666;
        margin-top: 8px;
        margin-bottom: 32px;
      }
      .loading {
        display: none;
        margin: 60px 0;
      }
      .spinner {
        border: 2px solid #ddd;
        border-top-color: #333;
        border-radius: 50%;
        width: 32px;
        height: 32px;
```

```
  animation: spin 0.8s linear infinite;
  margin: 20px auto;
}
@keyframes spin {
  to {
    transform: rotate(360deg);
  }
}
.loading-text {
  font-size: 16px;
  color: #444;
}
.content {
  display: block;
}

.steps-container {
  display: flex;
  flex-direction: column;
  gap: 20px;
}

.step {
  padding: 24px;
  border: 1px solid #ddd;
  border-radius: 12px;
  text-align: center;
  background: #fafafa;
}
.step-header {
  display: flex;
  align-items: center;
  justify-content: center;
  gap: 10px;
  margin-bottom: 12px;
}
.step-number {
  width: 28px;
  height: 28px;
  border: 1px solid #999;
  border-radius: 50%;
  display: flex;
  align-items: center;
  justify-content: center;
  font-weight: 600;
  font-size: 14px;
  flex-shrink: 0;
  color: #555;
}
.step-title {
  font-size: 18px;
  font-weight: 600;
```

```
  margin: 0;
  color: #222;
}
.step-description {
  font-size: 14px;
  margin-bottom: 16px;
  color: #666;
}

.store-buttons {
  display: flex;
  flex-direction: column;
  gap: 6px;
  justify-content: center;
  flex-wrap: wrap;
}
.store-button {
  display: inline-flex;
  align-items: center;
  justify-content: center;
  gap: 8px;
  padding: 12px 20px;
  font-size: 14px;
  font-weight: 500;
  border: 1px solid #ccc;
  border-radius: 8px;
  text-decoration: none;
  color: #333;
  background: #fff;
  transition: all 0.15s;
}
.store-button:hover {
  background: #f5f5f5;
  border-color: #999;
}
.store-link {
  display: inline-flex;
  align-items: center;
  justify-content: center;
  gap: 6px;
  padding: 8px 0;
  font-size: 13px;
  font-weight: 400;
  text-decoration: underline;
  text-underline-offset: 2px;
  color: #666;
  background: none;
  border: none;
  transition: color 0.15s;
}
.store-link:hover {
  color: #333;
```

```
}
.store-link .store-icon {
  width: 14px;
  height: 14px;
}
.store-icon {
  width: 18px;
  height: 18px;
}

.qr-section {
  background: #333;
  color: #fff;
  border-color: #333;
}
.qr-section .step-number {
  border-color: rgba(255, 255, 255, 0.5);
  color: #fff;
}
.qr-section .step-title {
  color: #fff;
}
.qr-section .step-description {
  color: rgba(255, 255, 255, 0.7);
}
.qr-code {
  width: 180px;
  height: 180px;
  margin: 0 auto 16px;
  background: #fff;
  border-radius: 8px;
  padding: 12px;
}
.qr-code canvas {
  width: 100%;
  height: 100%;
}
.open-button {
  display: inline-block;
  padding: 12px 24px;
  font-size: 14px;
  font-weight: 500;
  border: 1px solid rgba(255, 255, 255, 0.3);
  border-radius: 8px;
  text-decoration: none;
  color: #333;
  background: #fff;
  transition: opacity 0.15s;
}
.open-button:hover {
  opacity: 0.9;
}
```

```
/* Desktop styles */
@media (min-width: 768px) {
  body {
    padding: 48px 32px;
    display: flex;
    align-items: center;
    justify-content: center;
  }
  .wrapper {
    max-width: 720px;
  }
  h1 {
    font-size: 32px;
    margin-bottom: 10px;
  }
  .subtitle {
    font-size: 16px;
    margin-bottom: 40px;
  }
  .steps-container {
    flex-direction: row;
    gap: 20px;
    align-items: stretch;
  }
  .step {
    flex: 1;
    display: flex;
    flex-direction: column;
    padding: 28px;
  }
  .step-description {
    flex-grow: 1;
  }
  .store-buttons {
    flex-direction: column;
    gap: 10px;
  }
  .qr-code {
    width: 200px;
    height: 200px;
  }
}

/* Large desktop */
@media (min-width: 1024px) {
  .wrapper {
    max-width: 800px;
  }
  h1 {
    font-size: 36px;
  }
```

```
  .steps-container {
    gap: 28px;
  }
  .step {
    padding: 32px;
  }
}

/* Dark mode */
@media (prefers-color-scheme: dark) {
  body {
    background: #0d0d0d;
    color: #e0e0e0;
  }
  h1 {
    color: #f5f5f5;
  }
  .subtitle {
    color: #999;
  }
  .spinner {
    border-color: #444;
    border-top-color: #ccc;
  }
  .loading-text {
    color: #aaa;
  }
  .step {
    border-color: #333;
    background: #1a1a1a;
  }
  .step-number {
    border-color: #666;
    color: #bbb;
  }
  .step-title {
    color: #f0f0f0;
  }
  .step-description {
    color: #888;
  }
  .store-button {
    border-color: #444;
    color: #e0e0e0;
    background: #222;
  }
  .store-button:hover {
    background: #2a2a2a;
    border-color: #666;
  }
  .store-link {
    color: #888;
```

```
      }
      .store-link:hover {
        color: #ccc;
      }
      .qr-section {
        background: #111;
        border-color: #333;
      }
      .qr-section .step-number {
        border-color: rgba(255, 255, 255, 0.4);
      }
      .qr-section .step-description {
        color: rgba(255, 255, 255, 0.6);
      }
      .open-button {
        background: #f0f0f0;
        color: #111;
      }
      .open-button:hover {
        background: #e0e0e0;
      }
    }
  </style>
</head>
<body>
  <div class="wrapper">
    <div class="loading" id="loading">
      <div class="spinner"></div>
      <div class="loading-text">Opening in Expo Go...</div>
    </div>

    <div class="content" id="content">
      <h1>APP_NAME_PLACEHOLDER</h1>
      <p class="subtitle">Preview this app on your phone</p>

      <div class="steps-container">
        <div class="step">
          <div class="step-header">
            <div class="step-number">1</div>
            <h2 class="step-title">Download Expo Go</h2>
          </div>
          <p class="step-description">
            Expo Go is a free app to test mobile apps
          </p>
          <div class="store-buttons" id="store-buttons">
            <a
              id="app-store-btn"
              href="https://apps.apple.com/app/id982107779"
              class="store-button"
              target="_blank"
            >
              <svg class="store-icon" viewBox="0 0 24 24" fill="currentColor">
```

```
                <path
                  d="M18.71 19.5c-.83 1.24-1.71 2.45-3.05 2.47-1.34.03-1.77-.79-3.29-.79-1.53 0-2 .77-3.27.82-
1.31.05-2.3-1.32-3.14-2.53C4.25 17 2.94 12.45 4.7 9.39c.87-1.52 2.43-2.48 4.12-2.51 1.28-.02 2.5.87 3.29.87.78 0
 2.26-1.07 3.81-.91.65.03 2.47.26 3.64 1.98-.09.06-2.17 1.28-2.15 3.81.03 3.02 2.65 4.03 2.68 4.04-.03.07-.42 1.
44-1.38 2.83M13 3.5c.73-.83 1.94-1.46 2.94-1.5.13 1.17-.34 2.35-1.04 3.19-.69.85-1.83 1.51-2.95 1.42-.15-1.15.41
-2.35 1.05-3.11z"
                />
              </svg>
              App Store
            </a>
            <a
              id="play-store-btn"
              href="https://play.google.com/store/apps/details?id=host.exp.exponent"
              class="store-button"
              target="_blank"
            >
              <svg class="store-icon" viewBox="0 0 24 24" fill="currentColor">
                <path
                  d="M3,20.5V3.5C3,2.91 3.34,2.39 3.84,2.15L13.69,12L3.84,21.85C3.34,21.6 3,21.09 3,20.5M16.81
,15.12L6.05,21.34L14.54,12.85L16.81,15.12M20.16,10.81C20.5,11.08 20.75,11.5 20.75,12C20.75,12.5 20.53,12.9 20.18
,13.18L17.89,14.5L15.39,12L17.89,9.5L20.16,10.81M6.05,2.66L16.81,8.88L14.54,11.15L6.05,2.66Z"
                />
              </svg>
              Google Play
            </a>
          </div>
        </div>

        <div class="step qr-section">
          <div class="step-header">
            <div class="step-number">2</div>
            <h2 class="step-title">Scan QR Code</h2>
          </div>
          <p class="step-description">Use your phone’s camera or Expo Go</p>
          <div class="qr-code" id="qr-code"></div>
          <a href="exps://EXPS_URL_PLACEHOLDER" class="open-button"
            >Open in Expo Go</a
          >
        </div>
      </div>
    </div>
  </div>

  <script src="https://unpkg.com/qr-code-styling@1.6.0/lib/qr-code-styling.js"></script>
  <script>
    (function () {
      const ua = navigator.userAgent;
      const loadingEl = document.getElementById("loading");
      const contentEl = document.getElementById("content");

      const isAndroid = /Android/i.test(ua);
      const isIOS =
```

```
    /iPhone|iPad|iPod/i.test(ua) ||
    (navigator.platform === "MacIntel" && navigator.maxTouchPoints > 1);

  const deepLink = "exps://EXPS_URL_PLACEHOLDER";

  // Adjust store buttons based on platform
  const appStoreBtn = document.getElementById("app-store-btn");
  const playStoreBtn = document.getElementById("play-store-btn");
  const storeButtonsContainer = document.getElementById("store-buttons");

  if (isIOS) {
    playStoreBtn.className = "store-link";
    storeButtonsContainer.appendChild(playStoreBtn);
  } else if (isAndroid) {
    appStoreBtn.className = "store-link";
    storeButtonsContainer.insertBefore(playStoreBtn, appStoreBtn);
  }

  const qrCode = new QRCodeStyling({
    width: 400,
    height: 400,
    data: deepLink,
    dotsOptions: {
      color: "#333333",
      type: "rounded",
    },
    backgroundOptions: {
      color: "#ffffff",
    },
    cornersSquareOptions: {
      type: "extra-rounded",
    },
    cornersDotOptions: {
      type: "dot",
    },
    qrOptions: {
      errorCorrectionLevel: "H",
    },
  });

  qrCode.append(document.getElementById("qr-code"));

  if (isAndroid || isIOS) {
    loadingEl.style.display = "block";
    contentEl.style.display = "none";
    window.location.href = deepLink;
    setTimeout(function () {
      loadingEl.style.display = "none";
      contentEl.style.display = "block";
    }, 500);
  }
})();
```

```
    </script>
  </body>
</html>
```

FILE: artifacts/technician-app/tsconfig.json
SIZE: 340 bytes

```
{
  "extends": "expo/tsconfig.base",
  "compilerOptions": {
    "baseUrl": ".",
    "strict": true,
    "paths": {
      "@/*": [
        "./*"
      ]
    }
  },
  "include": [
    "**/*.ts",
    "**/*.tsx",
    ".expo/types/**/*.ts",
    "expo-env.d.ts"
  ],
  "references": [
    {
      "path": "../../lib/api-client-react"
    }
  ]
}
```

FILE: artifacts/web-portal/.replit-artifact/artifact.toml
SIZE: 587 bytes

```
kind = "web"
previewPath = "/"
title = "ACES Web Portal"
version = "1.0.0"
id = "artifacts/web-portal"
router = "path"

[[integratedSkills]]
name = "react-vite"
version = "1.0.0"

[[services]]
name = "web"
paths = [ "/" ]
localPort = 21464

[services.development]
run = "pnpm --filter @workspace/web-portal run dev"

[services.production]
build = [ "pnpm", "--filter", "@workspace/web-portal", "run", "build" ]
publicDir = "artifacts/web-portal/dist/public"
serve = "static"

[[services.production.rewrites]]
from = "/*"
to = "/index.html"

[services.env]
PORT = "21464"
BASE_PATH = "/"
```

FILE: artifacts/web-portal/components.json
SIZE: 434 bytes

```
{
    "$schema": "https://ui.shadcn.com/schema.json",
    "style": "new-york",
    "rsc": false,
    "tsx": true,
    "tailwind": {
      "config": "",
      "css": "src/index.css",
      "baseColor": "neutral",
      "cssVariables": true,
      "prefix": ""
    },
    "aliases": {
      "components": "@/components",
      "utils": "@/lib/utils",
      "ui": "@/components/ui",
      "lib": "@/lib",
      "hooks": "@/hooks"
    }
}
```

FILE: artifacts/web-portal/index.html
SIZE: 649 bytes

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0, maximum-scale=1" />
    <title>ACES-MSD Fueling Web Portal</title>
    <link rel="icon" type="image/svg+xml" href="/favicon.svg" />
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700&display=swap" rel="styleshee
  t">
  </head>
  <body>
    <div id="root"></div>
    <script type="module" src="/src/main.tsx"></script>
  </body>
</html>
```

FILE: artifacts/web-portal/package.json
SIZE: 2,734 bytes

```
{
  "name": "@workspace/web-portal",
  "version": "0.0.0",
  "private": true,
  "type": "module",
  "scripts": {
    "dev": "vite --config vite.config.ts --host 0.0.0.0",
    "build": "vite build --config vite.config.ts",
    "serve": "vite preview --config vite.config.ts --host 0.0.0.0",
    "typecheck": "tsc -p tsconfig.json --noEmit"
  },
  "devDependencies": {
    "@hookform/resolvers": "^3.10.0",
    "@radix-ui/react-accordion": "^1.2.4",
    "@radix-ui/react-alert-dialog": "^1.1.7",
    "@radix-ui/react-aspect-ratio": "^1.1.3",
    "@radix-ui/react-avatar": "^1.1.4",
    "@radix-ui/react-checkbox": "^1.1.5",
    "@radix-ui/react-collapsible": "^1.1.4",
    "@radix-ui/react-context-menu": "^2.2.7",
    "@radix-ui/react-dialog": "^1.1.7",
    "@radix-ui/react-dropdown-menu": "^2.1.7",
    "@radix-ui/react-hover-card": "^1.1.7",
    "@radix-ui/react-label": "^2.1.3",
    "@radix-ui/react-menubar": "^1.1.7",
    "@radix-ui/react-navigation-menu": "^1.2.6",
    "@radix-ui/react-popover": "^1.1.7",
    "@radix-ui/react-progress": "^1.1.3",
    "@radix-ui/react-radio-group": "^1.2.4",
    "@radix-ui/react-scroll-area": "^1.2.4",
    "@radix-ui/react-select": "^2.1.7",
    "@radix-ui/react-separator": "^1.1.3",
    "@radix-ui/react-slider": "^1.2.4",
    "@radix-ui/react-slot": "^1.2.0",
    "@radix-ui/react-switch": "^1.1.4",
    "@radix-ui/react-tabs": "^1.1.4",
    "@radix-ui/react-toast": "^1.2.7",
    "@radix-ui/react-toggle": "^1.1.3",
    "@radix-ui/react-toggle-group": "^1.1.3",
    "@radix-ui/react-tooltip": "^1.2.0",
    "@replit/vite-plugin-cartographer": "catalog:",
    "@replit/vite-plugin-dev-banner": "catalog:",
    "@replit/vite-plugin-runtime-error-modal": "catalog:",
    "@tailwindcss/typography": "^0.5.15",
    "@tailwindcss/vite": "catalog:",
    "@tanstack/react-query": "catalog:",
    "@types/node": "catalog:",
    "@types/react": "catalog:",
    "@types/react-dom": "catalog:",
```

```
    "@vitejs/plugin-react": "catalog:",
    "@workspace/api-client-react": "workspace:*",
    "class-variance-authority": "catalog:",
    "clsx": "catalog:",
    "cmdk": "^1.1.1",
    "date-fns": "^3.6.0",
    "embla-carousel-react": "^8.6.0",
    "framer-motion": "catalog:",
    "input-otp": "^1.4.2",
    "lucide-react": "catalog:",
    "next-themes": "^0.4.6",
    "react": "catalog:",
    "react-day-picker": "^9.11.1",
    "react-dom": "catalog:",
    "react-hook-form": "^7.55.0",
    "react-icons": "^5.4.0",
    "react-resizable-panels": "^2.1.7",
    "recharts": "^2.15.2",
    "sonner": "^2.0.7",
    "tailwind-merge": "catalog:",
    "tailwindcss": "catalog:",
    "tw-animate-css": "^1.4.0",
    "vaul": "^1.1.2",
    "vite": "catalog:",
    "wouter": "^3.3.5",
    "zod": "catalog:"
  }
}
```

FILE: artifacts/web-portal/requirements.yaml
SIZE: 1,477 bytes

```
packages:
  "recharts": "Dashboard analytics charts and data visualization"
  "date-fns": "Human-readable date formatting"
  "lucide-react": "Beautiful consistent icons"
  "react-hook-form": "Form state management"
  "@hookform/resolvers": "Zod validation resolver for forms"
  "zod": "Schema validation"
  "clsx": "Utility for constructing className strings conditionally"
  "tailwind-merge": "Utility for merging tailwind classes without style conflicts"

images:
  - path: "artifacts/web-portal/public/images/logo.png"
    description: "Modern geometric corporate logo for ACES Managed Services, using deep navy blue (#002D62) and
  sharp red (#E30613) accents, clean typography, transparent background"
    aspect_ratio: "1:1"
  - path: "artifacts/web-portal/public/images/auth-bg.png"
    description: "Abstract premium background with soft gradients in dark navy blue and subtle red light leaks,
  professional enterprise tech feel"
    aspect_ratio: "16:9"
  - path: "artifacts/web-portal/public/images/driver-bg.png"
    description: "Dynamic fluid gradient background in dark mode with energetic blue and subtle red waves, optim
  ized for mobile app background"
    aspect_ratio: "9:16"

notes:
  - Backend uses standard REST patterns via @workspace/api-client-react
  - Auth is simulated via localStorage tokens since true session cookies aren’t strictly defined in the provided
   endpoints beyond simple 200 OK responses
  - Wouter is used for routing per project standards
```

FILE: artifacts/web-portal/src/App.tsx
SIZE: 3,969 bytes

```
import { Switch, Route, Router as WouterRouter, useLocation } from "wouter";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { Toaster } from "@/components/ui/toaster";
import { TooltipProvider } from "@/components/ui/tooltip";
import { AuthProvider, useAuth } from "@/lib/auth-context";

import { AdminLayout } from "@/components/layout/AdminLayout";
import { DriverLayout } from "@/components/layout/DriverLayout";
import NotFound from "@/pages/not-found";
import PrivacyPolicy from "@/pages/PrivacyPolicy";

// Admin Pages
import AdminLogin from "@/pages/admin/Login";
import AdminDashboard from "@/pages/admin/Dashboard";
import AdminMissions from "@/pages/admin/Missions";
import AdminSites from "@/pages/admin/Sites";
import AdminDrivers from "@/pages/admin/Drivers";
import AdminReports from "@/pages/admin/Reports";
import AdminNotifications from "@/pages/admin/Notifications";
import AdminSettings from "@/pages/admin/Settings";
import AdminAdmins from "@/pages/admin/Admins";

// Driver Pages
import DriverLogin from "@/pages/driver/DriverLogin";
import DriverDashboard from "@/pages/driver/DriverDashboard";
import DriverMissionDetail from "@/pages/driver/DriverMissionDetail";
import DriverNotifications from "@/pages/driver/DriverNotifications";
import DriverSettings from "@/pages/driver/DriverSettings";

const queryClient = new QueryClient({
  defaultOptions: {
    queries: {
      retry: false,
      refetchOnWindowFocus: false,
    },
  },
});

function AuthGuard({ children, type }: { children: React.ReactNode, type: "admin" | "driver" }) {
  const { user } = useAuth();
  const [, setLocation] = useLocation();

  if (!user || user.type !== type) {
    const loginPath = type === "admin" ? "/login" : "/driver/login";
    setTimeout(() => setLocation(loginPath), 0);
    return null;
  }

  return <>{children}</>;
```

```
}

function Router() {
  return (
    <Switch>
      {/* Public */}
      <Route path="/privacy-policy" component={PrivacyPolicy} />

      {/* Admin Public */}
      <Route path="/login" component={AdminLogin} />

      {/* Driver Public */}
      <Route path="/driver/login" component={DriverLogin} />

      {/* Driver Protected */}
      <Route path="/driver/*">
        <AuthGuard type="driver">
          <DriverLayout>
            <Switch>
              <Route path="/driver/dashboard" component={DriverDashboard} />
              <Route path="/driver/mission/:id" component={DriverMissionDetail} />
              <Route path="/driver/notifications" component={DriverNotifications} />
              <Route path="/driver/settings" component={DriverSettings} />
              <Route path="/driver/*" component={DriverDashboard} />
            </Switch>
          </DriverLayout>
        </AuthGuard>
      </Route>

      {/* Admin Protected */}
      <Route path="*">
        <AuthGuard type="admin">
          <AdminLayout>
            <Switch>
              <Route path="/" component={AdminDashboard} />
              <Route path="/missions" component={AdminMissions} />
              <Route path="/sites" component={AdminSites} />
              <Route path="/drivers" component={AdminDrivers} />
              <Route path="/reports" component={AdminReports} />
              <Route path="/notifications" component={AdminNotifications} />
              <Route path="/settings" component={AdminSettings} />
              <Route path="/admins" component={AdminAdmins} />
              <Route component={NotFound} />
            </Switch>
          </AdminLayout>
        </AuthGuard>
      </Route>
    </Switch>
  );
}

function App() {
```

```
  return (
    <QueryClientProvider client={queryClient}>
      <TooltipProvider>
        <WouterRouter base={import.meta.env.BASE_URL.replace(/\/$/, "")}>
          <AuthProvider>
            <Router />
          </AuthProvider>
        </WouterRouter>
        <Toaster />
      </TooltipProvider>
    </QueryClientProvider>
  );
}

export default App;
```

FILE: artifacts/web-portal/src/components/layout/AdminLayout.tsx
SIZE: 5,297 bytes

```
import React from "react";
import { Link, useLocation } from "wouter";
import { useAuth } from "@/lib/auth-context";
import {
  LayoutDashboard,
  MapPin,
  Users,
  Settings,
  LogOut,
  Bell,
  FileText,
  ShieldCheck,
  UserCog,
} from "lucide-react";
import { Button } from "@/components/ui/button";
import { Avatar, AvatarFallback } from "@/components/ui/avatar";

interface NavItemProps {
  href: string;
  icon: React.ElementType;
  label: string;
  isActive: boolean;
}

function NavItem({ href, icon: Icon, label, isActive }: NavItemProps) {
  return (
    <Link
      href={href}
      className={`flex items-center gap-3 px-4 py-3 rounded-xl transition-all duration-200 group ${
        isActive
          ? "bg-primary text-white shadow-md shadow-primary/20"
          : "text-slate-600 hover:bg-slate-100 hover:text-primary"
      }`}
    >
      <Icon className={`w-5 h-5 ${isActive ? "text-white" : "text-slate-400 group-hover:text-primary"}`} />
      <span className="font-medium">{label}</span>
      {isActive && <div className="ml-auto w-1.5 h-5 bg-white rounded-full rounded-r-none -mr-4" />}
    </Link>
  );
}

export function AdminLayout({ children }: { children: React.ReactNode }) {
  const [location] = useLocation();
  const { user, logout } = useAuth();

  if (!user || user.type !== "admin") {
    return null;
  }
```

```
  const isSuperAdmin = user.role === "superadmin";
  const isSupervisor = user.role === "supervisor";

  const allNavItems = [
    { href: "/", icon: LayoutDashboard, label: "Dashboard", supervisorAllowed: true },
    { href: "/missions", icon: FileText, label: "Missions", supervisorAllowed: true },
    { href: "/sites", icon: MapPin, label: "Sites", supervisorAllowed: true },
    { href: "/drivers", icon: Users, label: "Drivers", supervisorAllowed: true },
    { href: "/reports", icon: FileText, label: "Reports", supervisorAllowed: true },
    { href: "/notifications", icon: Bell, label: "Notifications", supervisorAllowed: true },
    { href: "/admins", icon: ShieldCheck, label: "Admins", supervisorAllowed: false },
    { href: "/settings", icon: Settings, label: "Settings", supervisorAllowed: false },
  ];

  const navItems = allNavItems.filter((item) => !isSupervisor || item.supervisorAllowed);

  const roleLabel = isSuperAdmin
    ? "Super Admin"
    : isSupervisor
    ? "Region Supervisor"
    : "Admin";

  return (
    <div className="min-h-screen bg-slate-50/50 flex">
      {/* Sidebar */}
      <aside className="fixed inset-y-0 left-0 w-72 bg-white border-r border-slate-200 shadow-xl shadow-slate-20
0/20 z-30 flex flex-col">
        <div className="h-20 flex items-center px-8 border-b border-slate-100">
          <img
            src={`${import.meta.env.BASE_URL}images/aces-logo-main.png`}
            alt="ACES Logo"
            className="h-10 object-contain"
          />
        </div>

        <div className="flex-1 overflow-y-auto py-6 px-4 space-y-1">
          <div className="px-4 text-xs font-bold tracking-wider text-slate-400 uppercase mb-4 mt-2">Main Menu</d
iv>
          {navItems.map((item) => (
            <NavItem
              key={item.href}
              href={item.href}
              icon={item.icon}
              label={item.label}
              isActive={location === item.href}
            />
          ))}
        </div>

        <div className="p-4 border-t border-slate-100 bg-slate-50/50">
          <div className="flex items-center gap-3 px-4 py-3 bg-white rounded-xl shadow-sm border border-slate-20
0">
```

```
            <Avatar className="h-10 w-10 border-2 border-primary/10">
              <AvatarFallback className="bg-primary/5 text-primary font-bold">
                {user.username?.charAt(0).toUpperCase()}
              </AvatarFallback>
            </Avatar>
            <div className="flex-1 min-w-0">
              <p className="text-sm font-bold text-slate-900 truncate">{user.username}</p>
              <p className="text-xs text-slate-500">{roleLabel}</p>
            </div>
            <button
              onClick={logout}
              className="p-2 text-slate-400 hover:text-destructive hover:bg-destructive/10 rounded-lg transition
  -colors"
              title="Logout"
            >
              <LogOut className="w-4 h-4" />
            </button>
          </div>
        </div>
      </aside>

      {/* Main Content */}
      <main className="flex-1 ml-72 flex flex-col min-h-screen">
        {/* Header */}
        <header className="h-20 glass-panel border-b border-slate-200/50 flex items-center justify-between px-8
  sticky top-0 z-20">
          <h1 className="text-xl font-display font-bold text-slate-800 capitalize">
            {location === "/" ? "Dashboard" : location.split('/')[1].replace('-', ' ')}
          </h1>
          <div className="flex items-center gap-4">
            <Button variant="outline" size="icon" className="rounded-full bg-white shadow-sm border-slate-200 te
  xt-slate-600 hover:text-primary">
              <Bell className="w-5 h-5" />
            </Button>
          </div>
        </header>

        {/* Page Content */}
        <div className="flex-1 p-8">
          <div className="max-w-7xl mx-auto space-y-8">
            {children}
          </div>
        </div>
      </main>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/components/layout/DriverLayout.tsx
SIZE: 3,445 bytes

```
import React from "react";
import { Link, useLocation } from "wouter";
import { useAuth } from "@/lib/auth-context";
import { ClipboardList, Bell, User, LogOut } from "lucide-react";

export function DriverLayout({ children }: { children: React.ReactNode }) {
  const [location] = useLocation();
  const { user, logout } = useAuth();

  if (!user || user.type !== "driver") return null;

  return (
    <div className="min-h-screen bg-slate-900 text-slate-100 flex justify-center">
      {/* Mobile container constraint for driver app */}
      <div className="w-full max-w-md bg-slate-950 h-screen flex flex-col relative shadow-2xl overflow-hidden">

        {/* Background Effects */}
        <div className="absolute top-0 left-0 w-full h-64 bg-gradient-to-b from-primary/20 to-transparent pointe
  r-events-none" />
        <div className="absolute -top-32 -right-32 w-64 h-64 bg-accent/10 rounded-full blur-3xl pointer-events-n
  one" />

        {/* Header */}
        <header className="px-6 py-6 flex items-center justify-between z-10">
          <div>
            <h1 className="text-2xl font-display font-bold text-white">ACES-MSD Fueling</h1>
            <p className="text-sm text-slate-400">Welcome, {user.username}</p>
          </div>
          <button
            onClick={logout}
            className="w-10 h-10 rounded-full bg-slate-800 flex items-center justify-center text-slate-400 hover
  :text-white transition-colors"
          >
            <LogOut className="w-5 h-5" />
          </button>
        </header>

        {/* Scrollable Content */}
        <main className="flex-1 overflow-y-auto px-6 pb-24 z-10 custom-scrollbar">
          {children}
        </main>

        {/* Bottom Navigation */}
        <nav className="absolute bottom-0 w-full bg-slate-900/90 backdrop-blur-xl border-t border-slate-800 z-20
   pb-safe">
          <div className="flex justify-around items-center p-4">
            <Link
              href="/driver/dashboard"
              className={`flex flex-col items-center gap-1 transition-colors ${location === '/driver/dashboard'
```

```
  ? 'text-primary-foreground' : 'text-slate-500 hover:text-slate-300'}`}
            >
              <ClipboardList className="w-6 h-6" />
              <span className="text-[10px] font-medium uppercase tracking-wider">Tasks</span>
            </Link>

            <Link
              href="/driver/notifications"
              className={`flex flex-col items-center gap-1 transition-colors ${location === '/driver/notificatio
  ns' ? 'text-primary-foreground' : 'text-slate-500 hover:text-slate-300'}`}
            >
              <div className="relative">
                <Bell className="w-6 h-6" />
                <span className="absolute -top-1 -right-1 w-3 h-3 bg-destructive rounded-full border-2 border-sl
  ate-900" />
              </div>
              <span className="text-[10px] font-medium uppercase tracking-wider">Alerts</span>
            </Link>

            <Link
              href="/driver/settings"
              className={`flex flex-col items-center gap-1 transition-colors ${location === '/driver/settings' ?
   'text-primary-foreground' : 'text-slate-500 hover:text-slate-300'}`}
            >
              <User className="w-6 h-6" />
              <span className="text-[10px] font-medium uppercase tracking-wider">Profile</span>
            </Link>
          </div>
        </nav>
      </div>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/components/ui/accordion.tsx
SIZE: 2,001 bytes

```
import * as React from "react"
import * as AccordionPrimitive from "@radix-ui/react-accordion"
import { ChevronDown } from "lucide-react"

import { cn } from "@/lib/utils"

const Accordion = AccordionPrimitive.Root

const AccordionItem = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Item>
>(({ className, ...props }, ref) => (
  <AccordionPrimitive.Item
    ref={ref}
    className={cn("border-b", className)}
    {...props}
  />
))
AccordionItem.displayName = "AccordionItem"

const AccordionTrigger = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Header className="flex">
    <AccordionPrimitive.Trigger
      ref={ref}
      className={cn(
        "flex flex-1 items-center justify-between py-4 text-sm font-medium transition-all hover:underline text-l
  eft [&[data-state=open]>svg]:rotate-180",
        className
      )}
      {...props}
    >
      {children}
      <ChevronDown className="h-4 w-4 shrink-0 text-muted-foreground transition-transform duration-200" />
    </AccordionPrimitive.Trigger>
  </AccordionPrimitive.Header>
))
AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName

const AccordionContent = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Content
    ref={ref}
    className="overflow-hidden text-sm data-[state=closed]:animate-accordion-up data-[state=open]:animate-accord
  ion-down"
```

```
    {...props}
  >
    <div className={cn("pb-4 pt-0", className)}>{children}</div>
  </AccordionPrimitive.Content>
))
AccordionContent.displayName = AccordionPrimitive.Content.displayName

export { Accordion, AccordionItem, AccordionTrigger, AccordionContent }
```

FILE: artifacts/web-portal/src/components/ui/alert-dialog.tsx
SIZE: 4,419 bytes

```
import * as React from "react"
import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog"

import { cn } from "@/lib/utils"
import { buttonVariants } from "@/components/ui/button"

const AlertDialog = AlertDialogPrimitive.Root

const AlertDialogTrigger = AlertDialogPrimitive.Trigger

const AlertDialogPortal = AlertDialogPrimitive.Portal

const AlertDialogOverlay = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=c
  losed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
    ref={ref}
  />
))
AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName

const AlertDialogContent = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Content>
>(({ className, ...props }, ref) => (
  <AlertDialogPortal>
    <AlertDialogOverlay />
    <AlertDialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
   bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-[state=closed]:animate-out data-[sta
  te=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 d
  ata-[state=closed]:slide-out-to-left-1/2 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-f
  rom-left-1/2 data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
        className
      )}
      {...props}
    />
  </AlertDialogPortal>
))
AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName
```

```
const AlertDialogHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-2 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
AlertDialogHeader.displayName = "AlertDialogHeader"

const AlertDialogFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
AlertDialogFooter.displayName = "AlertDialogFooter"

const AlertDialogTitle = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold", className)}
    {...props}
  />
))
AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName

const AlertDialogDescription = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
AlertDialogDescription.displayName =
```

```
  AlertDialogPrimitive.Description.displayName

const AlertDialogAction = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Action>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Action>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Action
    ref={ref}
    className={cn(buttonVariants(), className)}
    {...props}
  />
))
AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName

const AlertDialogCancel = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Cancel>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Cancel>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Cancel
    ref={ref}
    className={cn(
      buttonVariants({ variant: "outline" }),
      "mt-2 sm:mt-0",
      className
    )}
    {...props}
  />
))
AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName

export {
  AlertDialog,
  AlertDialogPortal,
  AlertDialogOverlay,
  AlertDialogTrigger,
  AlertDialogContent,
  AlertDialogHeader,
  AlertDialogFooter,
  AlertDialogTitle,
  AlertDialogDescription,
  AlertDialogAction,
  AlertDialogCancel,
}
```

FILE: artifacts/web-portal/src/components/ui/alert.tsx
SIZE: 1,598 bytes

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const alertVariants = cva(
  "relative w-full rounded-lg border px-4 py-3 text-sm [&>svg+div]:translate-y-[-3px] [&>svg]:absolute [&>svg]:l
  eft-4 [&>svg]:top-4 [&>svg]:text-foreground [&>svg~*]:pl-7",
  {
    variants: {
      variant: {
        default: "bg-background text-foreground",
        destructive:
          "border-destructive/50 text-destructive dark:border-destructive [&>svg]:text-destructive",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Alert = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement> & VariantProps<typeof alertVariants>
>(({ className, variant, ...props }, ref) => (
  <div
    ref={ref}
    role="alert"
    className={cn(alertVariants({ variant }), className)}
    {...props}
  />
))
Alert.displayName = "Alert"

const AlertTitle = React.forwardRef<
  HTMLParagraphElement,
  React.HTMLAttributes<HTMLHeadingElement>
>(({ className, ...props }, ref) => (
  <h5
    ref={ref}
    className={cn("mb-1 font-medium leading-none tracking-tight", className)}
    {...props}
  />
))
AlertTitle.displayName = "AlertTitle"

const AlertDescription = React.forwardRef<
  HTMLParagraphElement,
```

```
  React.HTMLAttributes<HTMLParagraphElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("text-sm [&_p]:leading-relaxed", className)}
    {...props}
  />
))
AlertDescription.displayName = "AlertDescription"

export { Alert, AlertTitle, AlertDescription }
```

FILE: artifacts/web-portal/src/components/ui/aspect-ratio.tsx
SIZE: 140 bytes

```
import * as AspectRatioPrimitive from "@radix-ui/react-aspect-ratio"

const AspectRatio = AspectRatioPrimitive.Root

export { AspectRatio }
```

FILE: artifacts/web-portal/src/components/ui/avatar.tsx
SIZE: 1,419 bytes

```
"use client"

import * as React from "react"
import * as AvatarPrimitive from "@radix-ui/react-avatar"

import { cn } from "@/lib/utils"

const Avatar = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Root
    ref={ref}
    className={cn(
      "relative flex h-10 w-10 shrink-0 overflow-hidden rounded-full",
      className
    )}
    {...props}
  />
))
Avatar.displayName = AvatarPrimitive.Root.displayName

const AvatarImage = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Image>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Image>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Image
    ref={ref}
    className={cn("aspect-square h-full w-full", className)}
    {...props}
  />
))
AvatarImage.displayName = AvatarPrimitive.Image.displayName

const AvatarFallback = React.forwardRef<
  React.ElementRef<typeof AvatarPrimitive.Fallback>,
  React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Fallback>
>(({ className, ...props }, ref) => (
  <AvatarPrimitive.Fallback
    ref={ref}
    className={cn(
      "flex h-full w-full items-center justify-center rounded-full bg-muted",
      className
    )}
    {...props}
  />
))
AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName
```

```
export { Avatar, AvatarImage, AvatarFallback }
```

FILE: artifacts/web-portal/src/components/ui/badge.tsx
SIZE: 1,522 bytes

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const badgeVariants = cva(
  // @replit
  // Whitespace-nowrap: Badges should never wrap.
  "whitespace-nowrap inline-flex items-center rounded-md border px-2.5 py-0.5 text-xs font-semibold transition-c
  olors focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2" +
  " hover-elevate ",
  {
    variants: {
      variant: {
        default:
          // @replit shadow-xs instead of shadow, no hover because we use hover-elevate
          "border-transparent bg-primary text-primary-foreground shadow-xs",
        secondary:
          // @replit no hover because we use hover-elevate
          "border-transparent bg-secondary text-secondary-foreground",
        destructive:
          // @replit shadow-xs instead of shadow, no hover because we use hover-elevate
          "border-transparent bg-destructive text-destructive-foreground shadow-xs",
          // @replit shadow-xs" - use badge outline variable
        outline: "text-foreground border [border-color:var(--badge-outline)]",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

export interface BadgeProps
  extends React.HTMLAttributes<HTMLDivElement>,
    VariantProps<typeof badgeVariants> {}

function Badge({ className, variant, ...props }: BadgeProps) {
  return (
    <div className={cn(badgeVariants({ variant }), className)} {...props} />
  )
}

export { Badge, badgeVariants }
```

FILE: artifacts/web-portal/src/components/ui/breadcrumb.tsx
SIZE: 2,712 bytes

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { ChevronRight, MoreHorizontal } from "lucide-react"

import { cn } from "@/lib/utils"

const Breadcrumb = React.forwardRef<
  HTMLElement,
  React.ComponentPropsWithoutRef<"nav"> & {
    separator?: React.ReactNode
  }
>(({ ...props }, ref) => <nav ref={ref} aria-label="breadcrumb" {...props} />)
Breadcrumb.displayName = "Breadcrumb"

const BreadcrumbList = React.forwardRef<
  HTMLOListElement,
  React.ComponentPropsWithoutRef<"ol">
>(({ className, ...props }, ref) => (
  <ol
    ref={ref}
    className={cn(
      "flex flex-wrap items-center gap-1.5 break-words text-sm text-muted-foreground sm:gap-2.5",
      className
    )}
    {...props}
  />
))
BreadcrumbList.displayName = "BreadcrumbList"

const BreadcrumbItem = React.forwardRef<
  HTMLLIElement,
  React.ComponentPropsWithoutRef<"li">
>(({ className, ...props }, ref) => (
  <li
    ref={ref}
    className={cn("inline-flex items-center gap-1.5", className)}
    {...props}
  />
))
BreadcrumbItem.displayName = "BreadcrumbItem"

const BreadcrumbLink = React.forwardRef<
  HTMLAnchorElement,
  React.ComponentPropsWithoutRef<"a"> & {
    asChild?: boolean
  }
>(({ asChild, className, ...props }, ref) => {
  const Comp = asChild ? Slot : "a"
```

```
  return (
    <Comp
      ref={ref}
      className={cn("transition-colors hover:text-foreground", className)}
      {...props}
    />
  )
})
BreadcrumbLink.displayName = "BreadcrumbLink"

const BreadcrumbPage = React.forwardRef<
  HTMLSpanElement,
  React.ComponentPropsWithoutRef<"span">
>(({ className, ...props }, ref) => (
  <span
    ref={ref}
    role="link"
    aria-disabled="true"
    aria-current="page"
    className={cn("font-normal text-foreground", className)}
    {...props}
  />
))
BreadcrumbPage.displayName = "BreadcrumbPage"

const BreadcrumbSeparator = ({
  children,
  className,
  ...props
}: React.ComponentProps<"li">) => (
  <li
    role="presentation"
    aria-hidden="true"
    className={cn("[&>svg]:w-3.5 [&>svg]:h-3.5", className)}
    {...props}
  >
    {children ?? <ChevronRight />}
  </li>
)
BreadcrumbSeparator.displayName = "BreadcrumbSeparator"

const BreadcrumbEllipsis = ({
  className,
  ...props
}: React.ComponentProps<"span">) => (
  <span
    role="presentation"
    aria-hidden="true"
    className={cn("flex h-9 w-9 items-center justify-center", className)}
    {...props}
  >
    <MoreHorizontal className="h-4 w-4" />
```

```
    <span className="sr-only">More</span>
  </span>
)
BreadcrumbEllipsis.displayName = "BreadcrumbElipssis"

export {
  Breadcrumb,
  BreadcrumbList,
  BreadcrumbItem,
  BreadcrumbLink,
  BreadcrumbPage,
  BreadcrumbSeparator,
  BreadcrumbEllipsis,
}
```

FILE: artifacts/web-portal/src/components/ui/button-group.tsx
SIZE: 2,209 bytes

```
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Separator } from "@/components/ui/separator"

const buttonGroupVariants = cva(
  "flex w-fit items-stretch has-[>[data-slot=button-group]]:gap-2 [&>*]:focus-visible:relative [&>*]:focus-visib
  le:z-10 has-[select[aria-hidden=true]:last-child]:[&>[data-slot=select-trigger]:last-of-type]:rounded-r-md [&>[d
  ata-slot=select-trigger]:not([class*='w-'])]:w-fit [&>input]:flex-1",
  {
    variants: {
      orientation: {
        horizontal:
          "[&>*:not(:first-child)]:rounded-l-none [&>*:not(:first-child)]:border-l-0 [&>*:not(:last-child)]:roun
  ded-r-none",
        vertical:
          "flex-col [&>*:not(:first-child)]:rounded-t-none [&>*:not(:first-child)]:border-t-0 [&>*:not(:last-chi
  ld)]:rounded-b-none",
      },
    },
    defaultVariants: {
      orientation: "horizontal",
    },
  }
)

function ButtonGroup({
  className,
  orientation,
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof buttonGroupVariants>) {
  return (
    <div
      role="group"
      data-slot="button-group"
      data-orientation={orientation}
      className={cn(buttonGroupVariants({ orientation }), className)}
      {...props}
    />
  )
}

function ButtonGroupText({
  className,
  asChild = false,
  ...props
}: React.ComponentProps<"div"> & {
  asChild?: boolean
```

```
}) {
  const Comp = asChild ? Slot : "div"

  return (
    <Comp
      className={cn(
        "bg-muted shadow-xs flex items-center gap-2 rounded-md border px-4 text-sm font-medium [&_svg:not([class
  *='size-'])]:size-4 [&_svg]:pointer-events-none",
        className
      )}
      {...props}
    />
  )
}

function ButtonGroupSeparator({
  className,
  orientation = "vertical",
  ...props
}: React.ComponentProps<typeof Separator>) {
  return (
    <Separator
      data-slot="button-group-separator"
      orientation={orientation}
      className={cn(
        "bg-input relative !m-0 self-stretch data-[orientation=vertical]:h-auto",
        className
      )}
      {...props}
    />
  )
}

export {
  ButtonGroup,
  ButtonGroupSeparator,
  ButtonGroupText,
  buttonGroupVariants,
}
```

FILE: artifacts/web-portal/src/components/ui/button.tsx
SIZE: 2,356 bytes

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const buttonVariants = cva(
  "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium transition-col
  ors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:pointer-events-none disable
  d:opacity-50 [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0" +
" hover-elevate active-elevate-2",
  {
    variants: {
      variant: {
        default:
           // @replit: no hover, and add primary border
           "bg-primary text-primary-foreground border border-primary-border",
        destructive:
          "bg-destructive text-destructive-foreground shadow-sm border-destructive-border",
        outline:
          // @replit Shows the background color of whatever card / sidebar / accent background it is inside of.
          // Inherits the current text color. Uses shadow-xs. no shadow on active
          // No hover state
          " border [border-color:var(--button-outline)] shadow-xs active:shadow-none ",
        secondary:
          // @replit border, no hover, no shadow, secondary border.
          "border bg-secondary text-secondary-foreground border border-secondary-border ",
        // @replit no hover, transparent border
        ghost: "border border-transparent",
        link: "text-primary underline-offset-4 hover:underline",
      },
      size: {
        // @replit changed sizes
        default: "min-h-9 px-4 py-2",
        sm: "min-h-8 rounded-md px-3 text-xs",
        lg: "min-h-10 rounded-md px-8",
        icon: "h-9 w-9",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
)

export interface ButtonProps
  extends React.ButtonHTMLAttributes<HTMLButtonElement>,
    VariantProps<typeof buttonVariants> {
```

```
  asChild?: boolean
}

const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
  ({ className, variant, size, asChild = false, ...props }, ref) => {
    const Comp = asChild ? Slot : "button"
    return (
      <Comp
        className={cn(buttonVariants({ variant, size, className }))}
        ref={ref}
        {...props}
      />
    )
  }
)
Button.displayName = "Button"

export { Button, buttonVariants }
```

FILE: artifacts/web-portal/src/components/ui/calendar.tsx
SIZE: 7,569 bytes

```
"use client"

import * as React from "react"
import {
  ChevronDownIcon,
  ChevronLeftIcon,
  ChevronRightIcon,
} from "lucide-react"
import { DayButton, DayPicker, getDefaultClassNames } from "react-day-picker"

import { cn } from "@/lib/utils"
import { Button, buttonVariants } from "@/components/ui/button"

function Calendar({
  className,
  classNames,
  showOutsideDays = true,
  captionLayout = "label",
  buttonVariant = "ghost",
  formatters,
  components,
  ...props
}: React.ComponentProps<typeof DayPicker> & {
  buttonVariant?: React.ComponentProps<typeof Button>["variant"]
}) {
  const defaultClassNames = getDefaultClassNames()

  return (
    <DayPicker
      showOutsideDays={showOutsideDays}
      className={cn(
        "bg-background group/calendar p-3 [--cell-size:2rem] [[data-slot=card-content]_&]:bg-transparent [[data-
slot=popover-content]_&]:bg-transparent",
        String.raw`rtl:**:[.rdp-button\_next>svg]:rotate-180`,
        String.raw`rtl:**:[.rdp-button\_previous>svg]:rotate-180`,
        className
      )}
      captionLayout={captionLayout}
      formatters={{
        formatMonthDropdown: (date) =>
          date.toLocaleString("default", { month: "short" }),
        ...formatters,
      }}
      classNames={{
        root: cn("w-fit", defaultClassNames.root),
        months: cn(
          "relative flex flex-col gap-4 md:flex-row",
          defaultClassNames.months
        ),
```

```
      month: cn("flex w-full flex-col gap-4", defaultClassNames.month),
      nav: cn(
        "absolute inset-x-0 top-0 flex w-full items-center justify-between gap-1",
        defaultClassNames.nav
      ),
      button_previous: cn(
        buttonVariants({ variant: buttonVariant }),
        "h-[--cell-size] w-[--cell-size] select-none p-0 aria-disabled:opacity-50",
        defaultClassNames.button_previous
      ),
      button_next: cn(
        buttonVariants({ variant: buttonVariant }),
        "h-[--cell-size] w-[--cell-size] select-none p-0 aria-disabled:opacity-50",
        defaultClassNames.button_next
      ),
      month_caption: cn(
        "flex h-[--cell-size] w-full items-center justify-center px-[--cell-size]",
        defaultClassNames.month_caption
      ),
      dropdowns: cn(
        "flex h-[--cell-size] w-full items-center justify-center gap-1.5 text-sm font-medium",
        defaultClassNames.dropdowns
      ),
      dropdown_root: cn(
        "has-focus:border-ring border-input shadow-xs has-focus:ring-ring/50 has-focus:ring-[3px] relative rou
nded-md border",
        defaultClassNames.dropdown_root
      ),
      dropdown: cn(
        "bg-popover absolute inset-0 opacity-0",
        defaultClassNames.dropdown
      ),
      caption_label: cn(
        "select-none font-medium",
        captionLayout === "label"
          ? "text-sm"
          : "[&>svg]:text-muted-foreground flex h-8 items-center gap-1 rounded-md pl-2 pr-1 text-sm [&>svg]:si
ze-3.5",
        defaultClassNames.caption_label
      ),
      table: "w-full border-collapse",
      weekdays: cn("flex", defaultClassNames.weekdays),
      weekday: cn(
        "text-muted-foreground flex-1 select-none rounded-md text-[0.8rem] font-normal",
        defaultClassNames.weekday
      ),
      week: cn("mt-2 flex w-full", defaultClassNames.week),
      week_number_header: cn(
        "w-[--cell-size] select-none",
        defaultClassNames.week_number_header
      ),
      week_number: cn(
```

```
        "text-muted-foreground select-none text-[0.8rem]",
        defaultClassNames.week_number
      ),
      day: cn(
        "group/day relative aspect-square h-full w-full select-none p-0 text-center [&:first-child[data-select
ed=true]_button]:rounded-l-md [&:last-child[data-selected=true]_button]:rounded-r-md",
        defaultClassNames.day
      ),
      range_start: cn(
        "bg-accent rounded-l-md",
        defaultClassNames.range_start
      ),
      range_middle: cn("rounded-none", defaultClassNames.range_middle),
      range_end: cn("bg-accent rounded-r-md", defaultClassNames.range_end),
      today: cn(
        "bg-accent text-accent-foreground rounded-md data-[selected=true]:rounded-none",
        defaultClassNames.today
      ),
      outside: cn(
        "text-muted-foreground aria-selected:text-muted-foreground",
        defaultClassNames.outside
      ),
      disabled: cn(
        "text-muted-foreground opacity-50",
        defaultClassNames.disabled
      ),
      hidden: cn("invisible", defaultClassNames.hidden),
      ...classNames,
    }}
    components={{
      Root: ({ className, rootRef, ...props }) => {
        return (
          <div
            data-slot="calendar"
            ref={rootRef}
            className={cn(className)}
            {...props}
          />
        )
      },
      Chevron: ({ className, orientation, ...props }) => {
        if (orientation === "left") {
          return (
            <ChevronLeftIcon className={cn("size-4", className)} {...props} />
          )
        }

        if (orientation === "right") {
          return (
            <ChevronRightIcon
              className={cn("size-4", className)}
              {...props}
```

```
              />
            )
          }

          return (
            <ChevronDownIcon className={cn("size-4", className)} {...props} />
          )
        },
        DayButton: CalendarDayButton,
        WeekNumber: ({ children, ...props }) => {
          return (
            <td {...props}>
              <div className="flex size-[--cell-size] items-center justify-center text-center">
                {children}
              </div>
            </td>
          )
        },
        ...components,
      }}
      {...props}
    />
  )
}

function CalendarDayButton({
  className,
  day,
  modifiers,
  ...props
}: React.ComponentProps<typeof DayButton>) {
  const defaultClassNames = getDefaultClassNames()

  const ref = React.useRef<HTMLButtonElement>(null)
  React.useEffect(() => {
    if (modifiers.focused) ref.current?.focus()
  }, [modifiers.focused])

  return (
    <Button
      ref={ref}
      variant="ghost"
      size="icon"
      data-day={day.date.toLocaleDateString()}
      data-selected-single={
        modifiers.selected &&
        !modifiers.range_start &&
        !modifiers.range_end &&
        !modifiers.range_middle
      }
      data-range-start={modifiers.range_start}
      data-range-end={modifiers.range_end}
```

```
      data-range-middle={modifiers.range_middle}
      className={cn(
        "data-[selected-single=true]:bg-primary data-[selected-single=true]:text-primary-foreground data-[range-
  middle=true]:bg-accent data-[range-middle=true]:text-accent-foreground data-[range-start=true]:bg-primary data-[
  range-start=true]:text-primary-foreground data-[range-end=true]:bg-primary data-[range-end=true]:text-primary-fo
  reground group-data-[focused=true]/day:border-ring group-data-[focused=true]/day:ring-ring/50 flex aspect-square
   h-auto w-full min-w-[--cell-size] flex-col gap-1 font-normal leading-none data-[range-end=true]:rounded-md data
  -[range-middle=true]:rounded-none data-[range-start=true]:rounded-md group-data-[focused=true]/day:relative grou
  p-data-[focused=true]/day:z-10 group-data-[focused=true]/day:ring-[3px] [&>span]:text-xs [&>span]:opacity-70",
        defaultClassNames.day,
        className
      )}
      {...props}
    />
  )
}

export { Calendar, CalendarDayButton }
```

FILE: artifacts/web-portal/src/components/ui/card.tsx
SIZE: 1,828 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Card = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn(
      "rounded-xl border bg-card text-card-foreground shadow",
      className
    )}
    {...props}
  />
))
Card.displayName = "Card"

const CardHeader = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("flex flex-col space-y-1.5 p-6", className)}
    {...props}
  />
))
CardHeader.displayName = "CardHeader"

const CardTitle = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("font-semibold leading-none tracking-tight", className)}
    {...props}
  />
))
CardTitle.displayName = "CardTitle"

const CardDescription = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
```

```
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
CardDescription.displayName = "CardDescription"

const CardContent = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
))
CardContent.displayName = "CardContent"

const CardFooter = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => (
  <div
    ref={ref}
    className={cn("flex items-center p-6 pt-0", className)}
    {...props}
  />
))
CardFooter.displayName = "CardFooter"

export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent }
```

FILE: artifacts/web-portal/src/components/ui/carousel.tsx
SIZE: 6,210 bytes

```
import * as React from "react"
import useEmblaCarousel, {
  type UseEmblaCarouselType,
} from "embla-carousel-react"
import { ArrowLeft, ArrowRight } from "lucide-react"

import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"

type CarouselApi = UseEmblaCarouselType[1]
type UseCarouselParameters = Parameters<typeof useEmblaCarousel>
type CarouselOptions = UseCarouselParameters[0]
type CarouselPlugin = UseCarouselParameters[1]

type CarouselProps = {
  opts?: CarouselOptions
  plugins?: CarouselPlugin
  orientation?: "horizontal" | "vertical"
  setApi?: (api: CarouselApi) => void
}

type CarouselContextProps = {
  carouselRef: ReturnType<typeof useEmblaCarousel>[0]
  api: ReturnType<typeof useEmblaCarousel>[1]
  scrollPrev: () => void
  scrollNext: () => void
  canScrollPrev: boolean
  canScrollNext: boolean
} & CarouselProps

const CarouselContext = React.createContext<CarouselContextProps | null>(null)

function useCarousel() {
  const context = React.useContext(CarouselContext)

  if (!context) {
    throw new Error("useCarousel must be used within a <Carousel />")
  }

  return context
}

const Carousel = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement> & CarouselProps
>(
  (
    {
      orientation = "horizontal",
```

```
      opts,
      setApi,
      plugins,
      className,
      children,
      ...props
    },
    ref
  ) => {
    const [carouselRef, api] = useEmblaCarousel(
      {
        ...opts,
        axis: orientation === "horizontal" ? "x" : "y",
      },
      plugins
    )
    const [canScrollPrev, setCanScrollPrev] = React.useState(false)
    const [canScrollNext, setCanScrollNext] = React.useState(false)

    const onSelect = React.useCallback((api: CarouselApi) => {
      if (!api) {
        return
      }

      setCanScrollPrev(api.canScrollPrev())
      setCanScrollNext(api.canScrollNext())
    }, [])

    const scrollPrev = React.useCallback(() => {
      api?.scrollPrev()
    }, [api])

    const scrollNext = React.useCallback(() => {
      api?.scrollNext()
    }, [api])

    const handleKeyDown = React.useCallback(
      (event: React.KeyboardEvent<HTMLDivElement>) => {
        if (event.key === "ArrowLeft") {
          event.preventDefault()
          scrollPrev()
        } else if (event.key === "ArrowRight") {
          event.preventDefault()
          scrollNext()
        }
      },
      [scrollPrev, scrollNext]
    )

    React.useEffect(() => {
      if (!api || !setApi) {
        return
```

```
      }

      setApi(api)
    }, [api, setApi])

    React.useEffect(() => {
      if (!api) {
        return
      }

      onSelect(api)
      api.on("reInit", onSelect)
      api.on("select", onSelect)

      return () => {
        api?.off("select", onSelect)
      }
    }, [api, onSelect])

    return (
      <CarouselContext.Provider
        value={{
          carouselRef,
          api: api,
          opts,
          orientation:
            orientation || (opts?.axis === "y" ? "vertical" : "horizontal"),
          scrollPrev,
          scrollNext,
          canScrollPrev,
          canScrollNext,
        }}
      >
        <div
          ref={ref}
          onKeyDownCapture={handleKeyDown}
          className={cn("relative", className)}
          role="region"
          aria-roledescription="carousel"
          {...props}
        >
          {children}
        </div>
      </CarouselContext.Provider>
    )
  }
)
Carousel.displayName = "Carousel"

const CarouselContent = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
```

```
>(({ className, ...props }, ref) => {
  const { carouselRef, orientation } = useCarousel()

  return (
    <div ref={carouselRef} className="overflow-hidden">
      <div
        ref={ref}
        className={cn(
          "flex",
          orientation === "horizontal" ? "-ml-4" : "-mt-4 flex-col",
          className
        )}
        {...props}
      />
    </div>
  )
})
CarouselContent.displayName = "CarouselContent"

const CarouselItem = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => {
  const { orientation } = useCarousel()

  return (
    <div
      ref={ref}
      role="group"
      aria-roledescription="slide"
      className={cn(
        "min-w-0 shrink-0 grow-0 basis-full",
        orientation === "horizontal" ? "pl-4" : "pt-4",
        className
      )}
      {...props}
    />
  )
})
CarouselItem.displayName = "CarouselItem"

const CarouselPrevious = React.forwardRef<
  HTMLButtonElement,
  React.ComponentProps<typeof Button>
>(({ className, variant = "outline", size = "icon", ...props }, ref) => {
  const { orientation, scrollPrev, canScrollPrev } = useCarousel()

  return (
    <Button
      ref={ref}
      variant={variant}
      size={size}
```

```
      className={cn(
        "absolute  h-8 w-8 rounded-full",
        orientation === "horizontal"
          ? "-left-12 top-1/2 -translate-y-1/2"
          : "-top-12 left-1/2 -translate-x-1/2 rotate-90",
        className
      )}
      disabled={!canScrollPrev}
      onClick={scrollPrev}
      {...props}
    >
      <ArrowLeft className="h-4 w-4" />
      <span className="sr-only">Previous slide</span>
    </Button>
  )
})
CarouselPrevious.displayName = "CarouselPrevious"

const CarouselNext = React.forwardRef<
  HTMLButtonElement,
  React.ComponentProps<typeof Button>
>(({ className, variant = "outline", size = "icon", ...props }, ref) => {
  const { orientation, scrollNext, canScrollNext } = useCarousel()

  return (
    <Button
      ref={ref}
      variant={variant}
      size={size}
      className={cn(
        "absolute h-8 w-8 rounded-full",
        orientation === "horizontal"
          ? "-right-12 top-1/2 -translate-y-1/2"
          : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90",
        className
      )}
      disabled={!canScrollNext}
      onClick={scrollNext}
      {...props}
    >
      <ArrowRight className="h-4 w-4" />
      <span className="sr-only">Next slide</span>
    </Button>
  )
})
CarouselNext.displayName = "CarouselNext"

export {
  type CarouselApi,
  Carousel,
  CarouselContent,
  CarouselItem,
```

```
  CarouselPrevious,
  CarouselNext,
}
```

FILE: artifacts/web-portal/src/components/ui/chart.tsx
SIZE: 10,763 bytes

```
import * as React from "react"
import * as RechartsPrimitive from "recharts"

import { cn } from "@/lib/utils"

// Format: { THEME_NAME: CSS_SELECTOR }
const THEMES = { light: "", dark: ".dark" } as const

export type ChartConfig = {
  [k in string]: {
    label?: React.ReactNode
    icon?: React.ComponentType
  } & (
    | { color?: string; theme?: never }
    | { color?: never; theme: Record<keyof typeof THEMES, string> }
  )
}

type ChartContextProps = {
  config: ChartConfig
}

const ChartContext = React.createContext<ChartContextProps | null>(null)

function useChart() {
  const context = React.useContext(ChartContext)

  if (!context) {
    throw new Error("useChart must be used within a <ChartContainer />")
  }

  return context
}

const ChartContainer = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<"div"> & {
    config: ChartConfig
    children: React.ComponentProps<
      typeof RechartsPrimitive.ResponsiveContainer
    >["children"]
  }
>(({ id, className, children, config, ...props }, ref) => {
  const uniqueId = React.useId()
  const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`

  return (
    <ChartContext.Provider value={{ config }}>
      <div
```

```
        data-chart={chartId}
        ref={ref}
        className={cn(
          "flex aspect-video justify-center text-xs [&_.recharts-cartesian-axis-tick_text]:fill-muted-foreground
   [&_.recharts-cartesian-grid_line[stroke='#ccc']]:stroke-border/50 [&_.recharts-curve.recharts-tooltip-cursor]:s
  troke-border [&_.recharts-dot[stroke='#fff']]:stroke-transparent [&_.recharts-layer]:outline-none [&_.recharts-p
  olar-grid_[stroke='#ccc']]:stroke-border [&_.recharts-radial-bar-background-sector]:fill-muted [&_.recharts-rect
  angle.recharts-tooltip-cursor]:fill-muted [&_.recharts-reference-line_[stroke='#ccc']]:stroke-border [&_.rechart
  s-sector[stroke='#fff']]:stroke-transparent [&_.recharts-sector]:outline-none [&_.recharts-surface]:outline-none
  ",
          className
        )}
        {...props}
      >
        <ChartStyle id={chartId} config={config} />
        <RechartsPrimitive.ResponsiveContainer>
          {children}
        </RechartsPrimitive.ResponsiveContainer>
      </div>
    </ChartContext.Provider>
  )
})
ChartContainer.displayName = "Chart"

const ChartStyle = ({ id, config }: { id: string; config: ChartConfig }) => {
  const colorConfig = Object.entries(config).filter(
    ([, config]) => config.theme || config.color
  )

  if (!colorConfig.length) {
    return null
  }

  return (
    <style
      dangerouslySetInnerHTML={{
        __html: Object.entries(THEMES)
          .map(
            ([theme, prefix]) => `
${prefix} [data-chart=${id}] {
${colorConfig
  .map(([key, itemConfig]) => {
    const color =
      itemConfig.theme?.[theme as keyof typeof itemConfig.theme] ||
      itemConfig.color
    return color ? `  --color-${key}: ${color};` : null
  })
  .join("\n")}
}
`
          )
          .join("\n"),
```

```
      }}
    />
  )
}

const ChartTooltip = RechartsPrimitive.Tooltip

const ChartTooltipContent = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<typeof RechartsPrimitive.Tooltip> &
    React.ComponentProps<"div"> & {
      hideLabel?: boolean
      hideIndicator?: boolean
      indicator?: "line" | "dot" | "dashed"
      nameKey?: string
      labelKey?: string
    }
>(
  (
    {
      active,
      payload,
      className,
      indicator = "dot",
      hideLabel = false,
      hideIndicator = false,
      label,
      labelFormatter,
      labelClassName,
      formatter,
      color,
      nameKey,
      labelKey,
    },
    ref
  ) => {
    const { config } = useChart()

    const tooltipLabel = React.useMemo(() => {
      if (hideLabel || !payload?.length) {
        return null
      }

      const [item] = payload
      const key = `${labelKey || item?.dataKey || item?.name || "value"}`
      const itemConfig = getPayloadConfigFromPayload(config, item, key)
      const value =
        !labelKey && typeof label === "string"
          ? config[label as keyof typeof config]?.label || label
          : itemConfig?.label

      if (labelFormatter) {
```

```
      return (
        <div className={cn("font-medium", labelClassName)}>
          {labelFormatter(value, payload)}
        </div>
      )
    }

    if (!value) {
      return null
    }

    return <div className={cn("font-medium", labelClassName)}>{value}</div>
  }, [
    label,
    labelFormatter,
    payload,
    hideLabel,
    labelClassName,
    config,
    labelKey,
  ])

  if (!active || !payload?.length) {
    return null
  }

  const nestLabel = payload.length === 1 && indicator !== "dot"

  return (
    <div
      ref={ref}
      className={cn(
        "grid min-w-[8rem] items-start gap-1.5 rounded-lg border border-border/50 bg-background px-2.5 py-1.5
text-xs shadow-xl",
        className
      )}
    >
      {!nestLabel ? tooltipLabel : null}
      <div className="grid gap-1.5">
        {payload
          .filter((item) => item.type !== "none")
          .map((item, index) => {
            const key = `${nameKey || item.name || item.dataKey || "value"}`
            const itemConfig = getPayloadConfigFromPayload(config, item, key)
            const indicatorColor = color || item.payload.fill || item.color

            return (
              <div
                key={item.dataKey}
                className={cn(
                  "flex w-full flex-wrap items-stretch gap-2 [&>svg]:h-2.5 [&>svg]:w-2.5 [&>svg]:text-muted-fo
reground",
```

```
    indicator === "dot" && "items-center"
  )}
>
  {formatter && item?.value !== undefined && item.name ? (
    formatter(item.value, item.name, item, index, item.payload)
  ) : (
    <>
      {itemConfig?.icon ? (
        <itemConfig.icon />
      ) : (
        !hideIndicator && (
          <div
            className={cn(
              "shrink-0 rounded-[2px] border-[--color-border] bg-[--color-bg]",
              {
                "h-2.5 w-2.5": indicator === "dot",
                "w-1": indicator === "line",
                "w-0 border-[1.5px] border-dashed bg-transparent":
                  indicator === "dashed",
                "my-0.5": nestLabel && indicator === "dashed",
              }
            )}
            style={
              {
                "--color-bg": indicatorColor,
                "--color-border": indicatorColor,
              } as React.CSSProperties
            }
          />
        )
      )}
      <div
        className={cn(
          "flex flex-1 justify-between leading-none",
          nestLabel ? "items-end" : "items-center"
        )}
      >
        <div className="grid gap-1.5">
          {nestLabel ? tooltipLabel : null}
          <span className="text-muted-foreground">
            {itemConfig?.label || item.name}
          </span>
        </div>
        {item.value && (
          <span className="font-mono font-medium tabular-nums text-foreground">
            {item.value.toLocaleString()}
          </span>
        )}
      </div>
    </>
  )}
</div>
```

```
              )
            })}
        </div>
      </div>
    )
  }
)
ChartTooltipContent.displayName = "ChartTooltip"

const ChartLegend = RechartsPrimitive.Legend

const ChartLegendContent = React.forwardRef<
  HTMLDivElement,
  React.ComponentProps<"div"> &
    Pick<RechartsPrimitive.LegendProps, "payload" | "verticalAlign"> & {
      hideIcon?: boolean
      nameKey?: string
    }
>(
  (
    { className, hideIcon = false, payload, verticalAlign = "bottom", nameKey },
    ref
  ) => {
    const { config } = useChart()

    if (!payload?.length) {
      return null
    }

    return (
      <div
        ref={ref}
        className={cn(
          "flex items-center justify-center gap-4",
          verticalAlign === "top" ? "pb-3" : "pt-3",
          className
        )}
      >
        {payload
          .filter((item) => item.type !== "none")
          .map((item) => {
            const key = `${nameKey || item.dataKey || "value"}`
            const itemConfig = getPayloadConfigFromPayload(config, item, key)

            return (
              <div
                key={item.value}
                className={cn(
                  "flex items-center gap-1.5 [&>svg]:h-3 [&>svg]:w-3 [&>svg]:text-muted-foreground"
                )}
              >
                {itemConfig?.icon && !hideIcon ? (
```

```
                <itemConfig.icon />
              ) : (
                <div
                  className="h-2 w-2 shrink-0 rounded-[2px]"
                  style={{
                    backgroundColor: item.color,
                  }}
                />
              )}
              {itemConfig?.label}
            </div>
          )
        })}
      </div>
    )
  }
)
ChartLegendContent.displayName = "ChartLegend"

// Helper to extract item config from a payload.
function getPayloadConfigFromPayload(
  config: ChartConfig,
  payload: unknown,
  key: string
) {
  if (typeof payload !== "object" || payload === null) {
    return undefined
  }

  const payloadPayload =
    "payload" in payload &&
    typeof payload.payload === "object" &&
    payload.payload !== null
      ? payload.payload
      : undefined

  let configLabelKey: string = key

  if (
    key in payload &&
    typeof payload[key as keyof typeof payload] === "string"
  ) {
    configLabelKey = payload[key as keyof typeof payload] as string
  } else if (
    payloadPayload &&
    key in payloadPayload &&
    typeof payloadPayload[key as keyof typeof payloadPayload] === "string"
  ) {
    configLabelKey = payloadPayload[
      key as keyof typeof payloadPayload
    ] as string
  }
```

```
  return configLabelKey in config
    ? config[configLabelKey]
    : config[key as keyof typeof config]
}

export {
  ChartContainer,
  ChartTooltip,
  ChartTooltipContent,
  ChartLegend,
  ChartLegendContent,
  ChartStyle,
}
```

FILE: artifacts/web-portal/src/components/ui/checkbox.tsx
SIZE: 1,031 bytes

```
import * as React from "react"
import * as CheckboxPrimitive from "@radix-ui/react-checkbox"
import { Check } from "lucide-react"

import { cn } from "@/lib/utils"

const Checkbox = React.forwardRef<
  React.ElementRef<typeof CheckboxPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof CheckboxPrimitive.Root>
>(({ className, ...props }, ref) => (
  <CheckboxPrimitive.Root
    ref={ref}
    className={cn(
      "grid place-content-center peer h-4 w-4 shrink-0 rounded-sm border border-primary shadow focus-visible:out
  line-none focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50 data-[sta
  te=checked]:bg-primary data-[state=checked]:text-primary-foreground",
      className
    )}
    {...props}
  >
    <CheckboxPrimitive.Indicator
      className={cn("grid place-content-center text-current")}
    >
      <Check className="h-4 w-4" />
    </CheckboxPrimitive.Indicator>
  </CheckboxPrimitive.Root>
))
Checkbox.displayName = CheckboxPrimitive.Root.displayName

export { Checkbox }
```

FILE: artifacts/web-portal/src/components/ui/collapsible.tsx
SIZE: 329 bytes

```
"use client"

import * as CollapsiblePrimitive from "@radix-ui/react-collapsible"

const Collapsible = CollapsiblePrimitive.Root

const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger

const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent

export { Collapsible, CollapsibleTrigger, CollapsibleContent }
```

FILE: artifacts/web-portal/src/components/ui/command.tsx
SIZE: 4,887 bytes

```
"use client"

import * as React from "react"
import { type DialogProps } from "@radix-ui/react-dialog"
import { Command as CommandPrimitive } from "cmdk"
import { Search } from "lucide-react"

import { cn } from "@/lib/utils"
import { Dialog, DialogContent } from "@/components/ui/dialog"

const Command = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive>
>(({ className, ...props }, ref) => (
  <CommandPrimitive
    ref={ref}
    className={cn(
      "flex h-full w-full flex-col overflow-hidden rounded-md bg-popover text-popover-foreground",
      className
    )}
    {...props}
  />
))
Command.displayName = CommandPrimitive.displayName

const CommandDialog = ({ children, ...props }: DialogProps) => {
  return (
    <Dialog {...props}>
      <DialogContent className="overflow-hidden p-0">
        <Command className="[&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-he
  ading]]:text-muted-foreground [&_[cmdk-group]:not([hidden])_~[cmdk-group]]:pt-0 [&_[cmdk-group]]:px-2 [&_[cmdk-i
  nput-wrapper]_svg]:h-5 [&_[cmdk-input-wrapper]_svg]:w-5 [&_[cmdk-input]]:h-12 [&_[cmdk-item]]:px-2 [&_[cmdk-item
  ]]:py-3 [&_[cmdk-item]_svg]:h-5 [&_[cmdk-item]_svg]:w-5">
          {children}
        </Command>
      </DialogContent>
    </Dialog>
  )
}

const CommandInput = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Input>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Input>
>(({ className, ...props }, ref) => (
  <div className="flex items-center border-b px-3" cmdk-input-wrapper="">
    <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
    <CommandPrimitive.Input
      ref={ref}
      className={cn(
```

```
        "flex h-10 w-full rounded-md bg-transparent py-3 text-sm outline-none placeholder:text-muted-foreground
  disabled:cursor-not-allowed disabled:opacity-50",
        className
      )}
      {...props}
    />
  </div>
))

CommandInput.displayName = CommandPrimitive.Input.displayName

const CommandList = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.List>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.List
    ref={ref}
    className={cn("max-h-[300px] overflow-y-auto overflow-x-hidden", className)}
    {...props}
  />
))

CommandList.displayName = CommandPrimitive.List.displayName

const CommandEmpty = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Empty>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Empty>
>((props, ref) => (
  <CommandPrimitive.Empty
    ref={ref}
    className="py-6 text-center text-sm"
    {...props}
  />
))

CommandEmpty.displayName = CommandPrimitive.Empty.displayName

const CommandGroup = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Group>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Group>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Group
    ref={ref}
    className={cn(
      "overflow-hidden p-1 text-foreground [&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:py-1.5 [&_[cmd
  k-group-heading]]:text-xs [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-heading]]:text-muted-foreground",
      className
    )}
    {...props}
  />
))
```

```
CommandGroup.displayName = CommandPrimitive.Group.displayName

const CommandSeparator = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 h-px bg-border", className)}
    {...props}
  />
))
CommandSeparator.displayName = CommandPrimitive.Separator.displayName

const CommandItem = React.forwardRef<
  React.ElementRef<typeof CommandPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof CommandPrimitive.Item>
>(({ className, ...props }, ref) => (
  <CommandPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default gap-2 select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none d
  ata-[disabled=true]:pointer-events-none data-[selected=true]:bg-accent data-[selected=true]:text-accent-foregrou
  nd data-[disabled=true]:opacity-50 [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
      className
    )}
    {...props}
  />
))

CommandItem.displayName = CommandPrimitive.Item.displayName

const CommandShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
CommandShortcut.displayName = "CommandShortcut"

export {
  Command,
  CommandDialog,
  CommandInput,
```

```
  CommandList,
  CommandEmpty,
  CommandGroup,
  CommandItem,
  CommandShortcut,
  CommandSeparator,
}
```

FILE: artifacts/web-portal/src/components/ui/context-menu.tsx
SIZE: 7,406 bytes

```
import * as React from "react"
import * as ContextMenuPrimitive from "@radix-ui/react-context-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const ContextMenu = ContextMenuPrimitive.Root

const ContextMenuTrigger = ContextMenuPrimitive.Trigger

const ContextMenuGroup = ContextMenuPrimitive.Group

const ContextMenuPortal = ContextMenuPrimitive.Portal

const ContextMenuSub = ContextMenuPrimitive.Sub

const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup

const ContextMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <ContextMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
  focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-accent-foreground",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </ContextMenuPrimitive.SubTrigger>
))
ContextMenuSubTrigger.displayName = ContextMenuPrimitive.SubTrigger.displayName

const ContextMenuSubContent = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data
  -[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-i
```

```
  n-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[si
  de=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 ori
  gin-[--radix-context-menu-content-transform-origin]",
      className
    )}
    {...props}
  />
))
ContextMenuSubContent.displayName = ContextMenuPrimitive.SubContent.displayName

const ContextMenuContent = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Content>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.Portal>
    <ContextMenuPrimitive.Content
      ref={ref}
      className={cn(
        "z-50 max-h-[--radix-context-menu-content-available-height] min-w-[8rem] overflow-y-auto overflow-x-hidd
  en rounded-md border bg-popover p-1 text-popover-foreground shadow-md data-[state=open]:animate-in data-[state=c
  losed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 da
  ta-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[s
  ide=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-context-menu-content-tran
  sform-origin]",
        className
      )}
      {...props}
    />
  </ContextMenuPrimitive.Portal>
))
ContextMenuContent.displayName = ContextMenuPrimitive.Content.displayName

const ContextMenuItem = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <ContextMenuPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:b
  g-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
ContextMenuItem.displayName = ContextMenuPrimitive.Item.displayName

const ContextMenuCheckboxItem = React.forwardRef<
```

```
  React.ElementRef<typeof ContextMenuPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <ContextMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <ContextMenuPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </ContextMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </ContextMenuPrimitive.CheckboxItem>
))
ContextMenuCheckboxItem.displayName =
  ContextMenuPrimitive.CheckboxItem.displayName

const ContextMenuRadioItem = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <ContextMenuPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <ContextMenuPrimitive.ItemIndicator>
        <Circle className="h-4 w-4 fill-current" />
      </ContextMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </ContextMenuPrimitive.RadioItem>
))
ContextMenuRadioItem.displayName = ContextMenuPrimitive.RadioItem.displayName

const ContextMenuLabel = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Label> & {
    inset?: boolean
  }
```

```
>(({ className, inset, ...props }, ref) => (
  <ContextMenuPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold text-foreground",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
ContextMenuLabel.displayName = ContextMenuPrimitive.Label.displayName

const ContextMenuSeparator = React.forwardRef<
  React.ElementRef<typeof ContextMenuPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <ContextMenuPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-border", className)}
    {...props}
  />
))
ContextMenuSeparator.displayName = ContextMenuPrimitive.Separator.displayName

const ContextMenuShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
ContextMenuShortcut.displayName = "ContextMenuShortcut"

export {
  ContextMenu,
  ContextMenuTrigger,
  ContextMenuContent,
  ContextMenuItem,
  ContextMenuCheckboxItem,
  ContextMenuRadioItem,
  ContextMenuLabel,
  ContextMenuSeparator,
  ContextMenuShortcut,
  ContextMenuGroup,
```

```
  ContextMenuPortal,
  ContextMenuSub,
  ContextMenuSubContent,
  ContextMenuSubTrigger,
  ContextMenuRadioGroup,
}
```

FILE: artifacts/web-portal/src/components/ui/dialog.tsx
SIZE: 3,835 bytes

```
import * as React from "react"
import * as DialogPrimitive from "@radix-ui/react-dialog"
import { X } from "lucide-react"

import { cn } from "@/lib/utils"

const Dialog = DialogPrimitive.Root

const DialogTrigger = DialogPrimitive.Trigger

const DialogPortal = DialogPrimitive.Portal

const DialogClose = DialogPrimitive.Close

const DialogOverlay = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Overlay
    ref={ref}
    className={cn(
      "fixed inset-0 z-50 bg-black/80  data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=
  closed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
  />
))
DialogOverlay.displayName = DialogPrimitive.Overlay.displayName

const DialogContent = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DialogPortal>
    <DialogOverlay />
    <DialogPrimitive.Content
      ref={ref}
      className={cn(
        "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
   bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-[state=closed]:animate-out data-[sta
  te=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 d
  ata-[state=closed]:slide-out-to-left-1/2 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-f
  rom-left-1/2 data-[state=open]:slide-in-from-top-[48%] sm:rounded-lg",
        className
      )}
      {...props}
    >
      {children}
```

```
      <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background tran
  sition-opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:po
  inter-events-none data-[state=open]:bg-accent data-[state=open]:text-muted-foreground">
        <X className="h-4 w-4" />
        <span className="sr-only">Close</span>
      </DialogPrimitive.Close>
    </DialogPrimitive.Content>
  </DialogPortal>
))
DialogContent.displayName = DialogPrimitive.Content.displayName

const DialogHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-1.5 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
DialogHeader.displayName = "DialogHeader"

const DialogFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
DialogFooter.displayName = "DialogFooter"

const DialogTitle = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Title
    ref={ref}
    className={cn(
      "text-lg font-semibold leading-none tracking-tight",
      className
    )}
    {...props}
  />
))
```

```
DialogTitle.displayName = DialogPrimitive.Title.displayName

const DialogDescription = React.forwardRef<
  React.ElementRef<typeof DialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DialogPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
DialogDescription.displayName = DialogPrimitive.Description.displayName

export {
  Dialog,
  DialogPortal,
  DialogOverlay,
  DialogTrigger,
  DialogClose,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
}
```

FILE: artifacts/web-portal/src/components/ui/drawer.tsx
SIZE: 3,007 bytes

```
import * as React from "react"
import { Drawer as DrawerPrimitive } from "vaul"

import { cn } from "@/lib/utils"

const Drawer = ({
  shouldScaleBackground = true,
  ...props
}: React.ComponentProps<typeof DrawerPrimitive.Root>) => (
  <DrawerPrimitive.Root
    shouldScaleBackground={shouldScaleBackground}
    {...props}
  />
)
Drawer.displayName = "Drawer"

const DrawerTrigger = DrawerPrimitive.Trigger

const DrawerPortal = DrawerPrimitive.Portal

const DrawerClose = DrawerPrimitive.Close

const DrawerOverlay = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Overlay
    ref={ref}
    className={cn("fixed inset-0 z-50 bg-black/80", className)}
    {...props}
  />
))
DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName

const DrawerContent = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DrawerPortal>
    <DrawerOverlay />
    <DrawerPrimitive.Content
      ref={ref}
      className={cn(
        "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-background",
        className
      )}
      {...props}
    >
      <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />
```

```
      {children}
    </DrawerPrimitive.Content>
  </DrawerPortal>
))
DrawerContent.displayName = "DrawerContent"

const DrawerHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)}
    {...props}
  />
)
DrawerHeader.displayName = "DrawerHeader"

const DrawerFooter = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn("mt-auto flex flex-col gap-2 p-4", className)}
    {...props}
  />
)
DrawerFooter.displayName = "DrawerFooter"

const DrawerTitle = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Title>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Title
    ref={ref}
    className={cn(
      "text-lg font-semibold leading-none tracking-tight",
      className
    )}
    {...props}
  />
))
DrawerTitle.displayName = DrawerPrimitive.Title.displayName

const DrawerDescription = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Description>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
```

```
))
DrawerDescription.displayName = DrawerPrimitive.Description.displayName

export {
  Drawer,
  DrawerPortal,
  DrawerOverlay,
  DrawerTrigger,
  DrawerClose,
  DrawerContent,
  DrawerHeader,
  DrawerFooter,
  DrawerTitle,
  DrawerDescription,
}
```

FILE: artifacts/web-portal/src/components/ui/dropdown-menu.tsx
SIZE: 7,606 bytes

```
"use client"

import * as React from "react"
import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const DropdownMenu = DropdownMenuPrimitive.Root

const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger

const DropdownMenuGroup = DropdownMenuPrimitive.Group

const DropdownMenuPortal = DropdownMenuPrimitive.Portal

const DropdownMenuSub = DropdownMenuPrimitive.Sub

const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup

const DropdownMenuSubTrigger = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <DropdownMenuPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-a
  ccent data-[state=open]:bg-accent [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto" />
  </DropdownMenuPrimitive.SubTrigger>
))
DropdownMenuSubTrigger.displayName =
  DropdownMenuPrimitive.SubTrigger.displayName

const DropdownMenuSubContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.SubContent
    ref={ref}
```

```
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data
  -[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-i
  n-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[si
  de=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 ori
  gin-[--radix-dropdown-menu-content-transform-origin]",
      className
    )}
    {...props}
  />
))
DropdownMenuSubContent.displayName =
  DropdownMenuPrimitive.SubContent.displayName

const DropdownMenuContent = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Content>
>(({ className, sideOffset = 4, ...props }, ref) => (
  <DropdownMenuPrimitive.Portal>
    <DropdownMenuPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 max-h-[var(--radix-dropdown-menu-content-available-height)] min-w-[8rem] overflow-y-auto overflow-
  x-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md",
        "data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state
  =open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-t
  op-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from
  -bottom-2 origin-[--radix-dropdown-menu-content-transform-origin]",
        className
      )}
      {...props}
    />
  </DropdownMenuPrimitive.Portal>
))
DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName

const DropdownMenuItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <DropdownMenuPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm outline-none t
  ransition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled
  ]:opacity-50 [&>svg]:size-4 [&>svg]:shrink-0",
      inset && "pl-8",
      className
    )}
```

```
    {...props}
  />
))
DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName

const DropdownMenuCheckboxItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <DropdownMenuPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none tr
  ansition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]
  :opacity-50",
      className
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.CheckboxItem>
))
DropdownMenuCheckboxItem.displayName =
  DropdownMenuPrimitive.CheckboxItem.displayName

const DropdownMenuRadioItem = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <DropdownMenuPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none tr
  ansition-colors focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]
  :opacity-50",
      className
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <DropdownMenuPrimitive.ItemIndicator>
        <Circle className="h-2 w-2 fill-current" />
      </DropdownMenuPrimitive.ItemIndicator>
    </span>
    {children}
  </DropdownMenuPrimitive.RadioItem>
```

```
))
DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName

const DropdownMenuLabel = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Label> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <DropdownMenuPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName

const DropdownMenuSeparator = React.forwardRef<
  React.ElementRef<typeof DropdownMenuPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <DropdownMenuPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-muted", className)}
    {...props}
  />
))
DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName

const DropdownMenuShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn("ml-auto text-xs tracking-widest opacity-60", className)}
      {...props}
    />
  )
}
DropdownMenuShortcut.displayName = "DropdownMenuShortcut"

export {
  DropdownMenu,
  DropdownMenuTrigger,
  DropdownMenuContent,
  DropdownMenuItem,
  DropdownMenuCheckboxItem,
```

```
  DropdownMenuRadioItem,
  DropdownMenuLabel,
  DropdownMenuSeparator,
  DropdownMenuShortcut,
  DropdownMenuGroup,
  DropdownMenuPortal,
  DropdownMenuSub,
  DropdownMenuSubContent,
  DropdownMenuSubTrigger,
  DropdownMenuRadioGroup,
}
```

FILE: artifacts/web-portal/src/components/ui/empty.tsx
SIZE: 2,396 bytes

```
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

function Empty({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty"
      className={cn(
        "flex min-w-0 flex-1 flex-col items-center justify-center gap-6 text-balance rounded-lg border-dashed p-
  6 text-center md:p-12",
        className
      )}
      {...props}
    />
  )
}

function EmptyHeader({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty-header"
      className={cn(
        "flex max-w-sm flex-col items-center gap-2 text-center",
        className
      )}
      {...props}
    />
  )
}

const emptyMediaVariants = cva(
  "mb-2 flex shrink-0 items-center justify-center [&_svg]:pointer-events-none [&_svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        icon: "bg-muted text-foreground flex size-10 shrink-0 items-center justify-center rounded-lg [&_svg:not(
  [class*='size-'])]:size-6",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

function EmptyMedia({
  className,
```

```
  variant = "default",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof emptyMediaVariants>) {
  return (
    <div
      data-slot="empty-icon"
      data-variant={variant}
      className={cn(emptyMediaVariants({ variant, className }))}
      {...props}
    />
  )
}

function EmptyTitle({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty-title"
      className={cn("text-lg font-medium tracking-tight", className)}
      {...props}
    />
  )
}

function EmptyDescription({ className, ...props }: React.ComponentProps<"p">) {
  return (
    <div
      data-slot="empty-description"
      className={cn(
        "text-muted-foreground [&>a:hover]:text-primary text-sm/relaxed [&>a]:underline [&>a]:underline-offset-4
  ",
        className
      )}
      {...props}
    />
  )
}

function EmptyContent({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="empty-content"
      className={cn(
        "flex w-full min-w-0 max-w-sm flex-col items-center gap-4 text-balance text-sm",
        className
      )}
      {...props}
    />
  )
}

export {
  Empty,
```

```
  EmptyHeader,
  EmptyTitle,
  EmptyDescription,
  EmptyContent,
  EmptyMedia,
}
```

FILE: artifacts/web-portal/src/components/ui/field.tsx
SIZE: 6,044 bytes

```
"use client"

import { useMemo } from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Label } from "@/components/ui/label"
import { Separator } from "@/components/ui/separator"

function FieldSet({ className, ...props }: React.ComponentProps<"fieldset">) {
  return (
    <fieldset
      data-slot="field-set"
      className={cn(
        "flex flex-col gap-6",
        "has-[>[data-slot=checkbox-group]]:gap-3 has-[>[data-slot=radio-group]]:gap-3",
        className
      )}
      {...props}
    />
  )
}

function FieldLegend({
  className,
  variant = "legend",
  ...props
}: React.ComponentProps<"legend"> & { variant?: "legend" | "label" }) {
  return (
    <legend
      data-slot="field-legend"
      data-variant={variant}
      className={cn(
        "mb-3 font-medium",
        "data-[variant=legend]:text-base",
        "data-[variant=label]:text-sm",
        className
      )}
      {...props}
    />
  )
}

function FieldGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="field-group"
      className={cn(
        "group/field-group @container/field-group flex w-full flex-col gap-7 data-[slot=checkbox-group]:gap-3 [&
```

```
  >[data-slot=field-group]]:gap-4",
        className
      )}
      {...props}
    />
  )
}

const fieldVariants = cva(
  "group/field data-[invalid=true]:text-destructive flex w-full gap-3",
  {
    variants: {
      orientation: {
        vertical: ["flex-col [&>*]:w-full [&>.sr-only]:w-auto"],
        horizontal: [
          "flex-row items-center",
          "[&>[data-slot=field-label]]:flex-auto",
          "has-[>[data-slot=field-content]]:[&>[role=checkbox],[role=radio]]:mt-px has-[>[data-slot=field-conten
  t]]:items-start",
        ],
        responsive: [
          "@md/field-group:flex-row @md/field-group:items-center @md/field-group:[&>*]:w-auto flex-col [&>*]:w-f
  ull [&>.sr-only]:w-auto",
          "@md/field-group:[&>[data-slot=field-label]]:flex-auto",
          "@md/field-group:has-[>[data-slot=field-content]]:items-start @md/field-group:has-[>[data-slot=field-c
  ontent]]:[&>[role=checkbox],[role=radio]]:mt-px",
        ],
      },
    },
    defaultVariants: {
      orientation: "vertical",
    },
  }
)

function Field({
  className,
  orientation = "vertical",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof fieldVariants>) {
  return (
    <div
      role="group"
      data-slot="field"
      data-orientation={orientation}
      className={cn(fieldVariants({ orientation }), className)}
      {...props}
    />
  )
}

function FieldContent({ className, ...props }: React.ComponentProps<"div">) {
```

```
  return (
    <div
      data-slot="field-content"
      className={cn(
        "group/field-content flex flex-1 flex-col gap-1.5 leading-snug",
        className
      )}
      {...props}
    />
  )
}

function FieldLabel({
  className,
  ...props
}: React.ComponentProps<typeof Label>) {
  return (
    <Label
      data-slot="field-label"
      className={cn(
        "group/field-label peer/field-label flex w-fit gap-2 leading-snug group-data-[disabled=true]/field:opaci
  ty-50",
        "has-[>[data-slot=field]]:w-full has-[>[data-slot=field]]:flex-col has-[>[data-slot=field]]:rounded-md h
  as-[>[data-slot=field]]:border [&>[data-slot=field]]:p-4",
        "has-data-[state=checked]:bg-primary/5 has-data-[state=checked]:border-primary dark:has-data-[state=chec
  ked]:bg-primary/10",
        className
      )}
      {...props}
    />
  )
}

function FieldTitle({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="field-label"
      className={cn(
        "flex w-fit items-center gap-2 text-sm font-medium leading-snug group-data-[disabled=true]/field:opacity
  -50",
        className
      )}
      {...props}
    />
  )
}

function FieldDescription({ className, ...props }: React.ComponentProps<"p">) {
  return (
    <p
      data-slot="field-description"
      className={cn(
```

```
        "text-muted-foreground text-sm font-normal leading-normal group-has-[[data-orientation=horizontal]]/fiel
  d:text-balance",
        "nth-last-2:-mt-1 last:mt-0 [[data-variant=legend]+&]:-mt-1.5",
        "[&>a:hover]:text-primary [&>a]:underline [&>a]:underline-offset-4",
        className
      )}
      {...props}
    />
  )
}

function FieldSeparator({
  children,
  className,
  ...props
}: React.ComponentProps<"div"> & {
  children?: React.ReactNode
}) {
  return (
    <div
      data-slot="field-separator"
      data-content={!!children}
      className={cn(
        "relative -my-2 h-5 text-sm group-data-[variant=outline]/field-group:-mb-2",
        className
      )}
      {...props}
    >
      <Separator className="absolute inset-0 top-1/2" />
      {children && (
        <span
          className="bg-background text-muted-foreground relative mx-auto block w-fit px-2"
          data-slot="field-separator-content"
        >
          {children}
        </span>
      )}
    </div>
  )
}

function FieldError({
  className,
  children,
  errors,
  ...props
}: React.ComponentProps<"div"> & {
  errors?: Array<{ message?: string } | undefined>
}) {
  const content = useMemo(() => {
    if (children) {
      return children
```

```
    }

    if (!errors) {
      return null
    }

    if (errors?.length === 1 && errors[0]?.message) {
      return errors[0].message
    }

    return (
      <ul className="ml-4 flex list-disc flex-col gap-1">
        {errors.map(
          (error, index) =>
            error?.message && <li key={index}>{error.message}</li>
        )}
      </ul>
    )
  }, [children, errors])

  if (!content) {
    return null
  }

  return (
    <div
      role="alert"
      data-slot="field-error"
      className={cn("text-destructive text-sm font-normal", className)}
      {...props}
    >
      {content}
    </div>
  )
}

export {
  Field,
  FieldLabel,
  FieldDescription,
  FieldError,
  FieldGroup,
  FieldLegend,
  FieldSeparator,
  FieldSet,
  FieldContent,
  FieldTitle,
}
```

FILE: artifacts/web-portal/src/components/ui/form.tsx
SIZE: 4,175 bytes

```
import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { Slot } from "@radix-ui/react-slot"
import {
  Controller,
  FormProvider,
  useFormContext,
  type ControllerProps,
  type FieldPath,
  type FieldValues,
} from "react-hook-form"

import { cn } from "@/lib/utils"
import { Label } from "@/components/ui/label"

const Form = FormProvider

type FormFieldContextValue<
  TFieldValues extends FieldValues = FieldValues,
  TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>
> = {
  name: TName
}

const FormFieldContext = React.createContext<FormFieldContextValue | null>(null)

const FormField = <
  TFieldValues extends FieldValues = FieldValues,
  TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>
>({
  ...props
}: ControllerProps<TFieldValues, TName>) => {
  return (
    <FormFieldContext.Provider value={{ name: props.name }}>
      <Controller {...props} />
    </FormFieldContext.Provider>
  )
}

const useFormField = () => {
  const fieldContext = React.useContext(FormFieldContext)
  const itemContext = React.useContext(FormItemContext)
  const { getFieldState, formState } = useFormContext()

  if (!fieldContext) {
    throw new Error("useFormField should be used within <FormField>")
  }

  if (!itemContext) {
```

```
    throw new Error("useFormField should be used within <FormItem>")
  }

  const fieldState = getFieldState(fieldContext.name, formState)

  const { id } = itemContext

  return {
    id,
    name: fieldContext.name,
    formItemId: `${id}-form-item`,
    formDescriptionId: `${id}-form-item-description`,
    formMessageId: `${id}-form-item-message`,
    ...fieldState,
  }
}

type FormItemContextValue = {
  id: string
}

const FormItemContext = React.createContext<FormItemContextValue | null>(null)

const FormItem = React.forwardRef<
  HTMLDivElement,
  React.HTMLAttributes<HTMLDivElement>
>(({ className, ...props }, ref) => {
  const id = React.useId()

  return (
    <FormItemContext.Provider value={{ id }}>
      <div ref={ref} className={cn("space-y-2", className)} {...props} />
    </FormItemContext.Provider>
  )
})
FormItem.displayName = "FormItem"

const FormLabel = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root>
>(({ className, ...props }, ref) => {
  const { error, formItemId } = useFormField()

  return (
    <Label
      ref={ref}
      className={cn(error && "text-destructive", className)}
      htmlFor={formItemId}
      {...props}
    />
  )
})
```

```
FormLabel.displayName = "FormLabel"

const FormControl = React.forwardRef<
  React.ElementRef<typeof Slot>,
  React.ComponentPropsWithoutRef<typeof Slot>
>(({ ...props }, ref) => {
  const { error, formItemId, formDescriptionId, formMessageId } = useFormField()

  return (
    <Slot
      ref={ref}
      id={formItemId}
      aria-describedby={
        !error
          ? `${formDescriptionId}`
          : `${formDescriptionId} ${formMessageId}`
      }
      aria-invalid={!!error}
      {...props}
    />
  )
})
FormControl.displayName = "FormControl"

const FormDescription = React.forwardRef<
  HTMLParagraphElement,
  React.HTMLAttributes<HTMLParagraphElement>
>(({ className, ...props }, ref) => {
  const { formDescriptionId } = useFormField()

  return (
    <p
      ref={ref}
      id={formDescriptionId}
      className={cn("text-[0.8rem] text-muted-foreground", className)}
      {...props}
    />
  )
})
FormDescription.displayName = "FormDescription"

const FormMessage = React.forwardRef<
  HTMLParagraphElement,
  React.HTMLAttributes<HTMLParagraphElement>
>(({ className, children, ...props }, ref) => {
  const { error, formMessageId } = useFormField()
  const body = error ? String(error?.message ?? "") : children

  if (!body) {
    return null
  }
```

```
  return (
    <p
      ref={ref}
      id={formMessageId}
      className={cn("text-[0.8rem] font-medium text-destructive", className)}
      {...props}
    >
      {body}
    </p>
  )
})
FormMessage.displayName = "FormMessage"

export {
  useFormField,
  Form,
  FormItem,
  FormLabel,
  FormControl,
  FormDescription,
  FormMessage,
  FormField,
}
```

FILE: artifacts/web-portal/src/components/ui/hover-card.tsx
SIZE: 1,237 bytes

```
import * as React from "react"
import * as HoverCardPrimitive from "@radix-ui/react-hover-card"

import { cn } from "@/lib/utils"

const HoverCard = HoverCardPrimitive.Root

const HoverCardTrigger = HoverCardPrimitive.Trigger

const HoverCardContent = React.forwardRef<
  React.ElementRef<typeof HoverCardPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof HoverCardPrimitive.Content>
>(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  <HoverCardPrimitive.Content
    ref={ref}
    align={align}
    sideOffset={sideOffset}
    className={cn(
      "z-50 w-64 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-[state=ope
  n]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[s
  tate=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:sl
  ide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radi
  x-hover-card-content-transform-origin]",
      className
    )}
    {...props}
  />
))
HoverCardContent.displayName = HoverCardPrimitive.Content.displayName

export { HoverCard, HoverCardTrigger, HoverCardContent }
```

FILE: artifacts/web-portal/src/components/ui/input-group.tsx
SIZE: 4,971 bytes

```
import * as React from "react"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"
import { Input } from "@/components/ui/input"
import { Textarea } from "@/components/ui/textarea"

function InputGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="input-group"
      role="group"
      className={cn(
        "group/input-group border-input dark:bg-input/30 shadow-xs relative flex w-full items-center rounded-md
  border outline-none transition-[color,box-shadow]",
        "h-9 has-[>textarea]:h-auto",

        // Variants based on alignment.
        "has-[>[data-align=inline-start]]:[&>input]:pl-2",
        "has-[>[data-align=inline-end]]:[&>input]:pr-2",
        "has-[>[data-align=block-start]]:h-auto has-[>[data-align=block-start]]:flex-col has-[>[data-align=block
  -start]]:[&>input]:pb-3",
        "has-[>[data-align=block-end]]:h-auto has-[>[data-align=block-end]]:flex-col has-[>[data-align=block-end
  ]]:[&>input]:pt-3",

        // Focus state.
        "has-[[data-slot=input-group-control]:focus-visible]:ring-ring has-[[data-slot=input-group-control]:focu
  s-visible]:ring-1",

        // Error state.
        "has-[[data-slot][aria-invalid=true]]:ring-destructive/20 has-[[data-slot][aria-invalid=true]]:border-de
  structive dark:has-[[data-slot][aria-invalid=true]]:ring-destructive/40",

        className
      )}
      {...props}
    />
  )
}

const inputGroupAddonVariants = cva(
  "text-muted-foreground flex h-auto cursor-text select-none items-center justify-center gap-2 py-1.5 text-sm fo
  nt-medium group-data-[disabled=true]/input-group:opacity-50 [&>kbd]:rounded-[calc(var(--radius)-5px)] [&>svg:not
  ([class*='size-'])]:size-4",
  {
    variants: {
      align: {
        "inline-start":
```

```
          "order-first pl-3 has-[>button]:ml-[-0.45rem] has-[>kbd]:ml-[-0.35rem]",
        "inline-end":
          "order-last pr-3 has-[>button]:mr-[-0.4rem] has-[>kbd]:mr-[-0.35rem]",
        "block-start":
          "[.border-b]:pb-3 order-first w-full justify-start px-3 pt-3 group-has-[>input]/input-group:pt-2.5",
        "block-end":
          "[.border-t]:pt-3 order-last w-full justify-start px-3 pb-3 group-has-[>input]/input-group:pb-2.5",
      },
    },
    defaultVariants: {
      align: "inline-start",
    },
  }
)

function InputGroupAddon({
  className,
  align = "inline-start",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof inputGroupAddonVariants>) {
  return (
    <div
      role="group"
      data-slot="input-group-addon"
      data-align={align}
      className={cn(inputGroupAddonVariants({ align }), className)}
      onClick={(e) => {
        if ((e.target as HTMLElement).closest("button")) {
          return
        }
        e.currentTarget.parentElement?.querySelector("input")?.focus()
      }}
      {...props}
    />
  )
}

const inputGroupButtonVariants = cva(
  "flex items-center gap-2 text-sm shadow-none",
  {
    variants: {
      size: {
        xs: "h-6 gap-1 rounded-[calc(var(--radius)-5px)] px-2 has-[>svg]:px-2 [&>svg:not([class*='size-'])]:size
  -3.5",
        sm: "h-8 gap-1.5 rounded-md px-2.5 has-[>svg]:px-2.5",
        "icon-xs":
          "size-6 rounded-[calc(var(--radius)-5px)] p-0 has-[>svg]:p-0",
        "icon-sm": "size-8 p-0 has-[>svg]:p-0",
      },
    },
    defaultVariants: {
      size: "xs",
```

```
    },
  }
)

function InputGroupButton({
  className,
  type = "button",
  variant = "ghost",
  size = "xs",
  ...props
}: Omit<React.ComponentProps<typeof Button>, "size"> &
  VariantProps<typeof inputGroupButtonVariants>) {
  return (
    <Button
      type={type}
      data-size={size}
      variant={variant}
      className={cn(inputGroupButtonVariants({ size }), className)}
      {...props}
    />
  )
}

function InputGroupText({ className, ...props }: React.ComponentProps<"span">) {
  return (
    <span
      className={cn(
        "text-muted-foreground flex items-center gap-2 text-sm [&_svg:not([class*='size-'])]:size-4 [&_svg]:poin
  ter-events-none",
        className
      )}
      {...props}
    />
  )
}

function InputGroupInput({
  className,
  ...props
}: React.ComponentProps<"input">) {
  return (
    <Input
      data-slot="input-group-control"
      className={cn(
        "flex-1 rounded-none border-0 bg-transparent shadow-none focus-visible:ring-0 dark:bg-transparent",
        className
      )}
      {...props}
    />
  )
}
```

```
function InputGroupTextarea({
  className,
  ...props
}: React.ComponentProps<"textarea">) {
  return (
    <Textarea
      data-slot="input-group-control"
      className={cn(
        "flex-1 resize-none rounded-none border-0 bg-transparent py-3 shadow-none focus-visible:ring-0 dark:bg-t
  ransparent",
        className
      )}
      {...props}
    />
  )
}

export {
  InputGroup,
  InputGroupAddon,
  InputGroupButton,
  InputGroupText,
  InputGroupInput,
  InputGroupTextarea,
}
```

FILE: artifacts/web-portal/src/components/ui/input-otp.tsx
SIZE: 2,143 bytes

```
import * as React from "react"
import { OTPInput, OTPInputContext } from "input-otp"
import { Minus } from "lucide-react"

import { cn } from "@/lib/utils"

const InputOTP = React.forwardRef<
  React.ElementRef<typeof OTPInput>,
  React.ComponentPropsWithoutRef<typeof OTPInput>
>(({ className, containerClassName, ...props }, ref) => (
  <OTPInput
    ref={ref}
    containerClassName={cn(
      "flex items-center gap-2 has-[:disabled]:opacity-50",
      containerClassName
    )}
    className={cn("disabled:cursor-not-allowed", className)}
    {...props}
  />
))
InputOTP.displayName = "InputOTP"

const InputOTPGroup = React.forwardRef<
  React.ElementRef<"div">,
  React.ComponentPropsWithoutRef<"div">
>(({ className, ...props }, ref) => (
  <div ref={ref} className={cn("flex items-center", className)} {...props} />
))
InputOTPGroup.displayName = "InputOTPGroup"

const InputOTPSlot = React.forwardRef<
  React.ElementRef<"div">,
  React.ComponentPropsWithoutRef<"div"> & { index: number }
>(({ index, className, ...props }, ref) => {
  const inputOTPContext = React.useContext(OTPInputContext)
  const { char, hasFakeCaret, isActive } = inputOTPContext.slots[index]

  return (
    <div
      ref={ref}
      className={cn(
        "relative flex h-9 w-9 items-center justify-center border-y border-r border-input text-sm shadow-sm tran
  sition-all first:rounded-l-md first:border-l last:rounded-r-md",
        isActive && "z-10 ring-1 ring-ring",
        className
      )}
      {...props}
    >
      {char}
```

```
      {hasFakeCaret && (
        <div className="pointer-events-none absolute inset-0 flex items-center justify-center">
          <div className="h-4 w-px animate-caret-blink bg-foreground duration-1000" />
        </div>
      )}
    </div>
  )
})
InputOTPSlot.displayName = "InputOTPSlot"

const InputOTPSeparator = React.forwardRef<
  React.ElementRef<"div">,
  React.ComponentPropsWithoutRef<"div">
>(({ ...props }, ref) => (
  <div ref={ref} role="separator" {...props}>
    <Minus />
  </div>
))
InputOTPSeparator.displayName = "InputOTPSeparator"

export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator }
```

FILE: artifacts/web-portal/src/components/ui/input.tsx
SIZE: 768 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Input = React.forwardRef<HTMLInputElement, React.ComponentProps<"input">>(
  ({ className, type, ...props }, ref) => {
    return (
      <input
        type={type}
        className={cn(
          "flex h-9 w-full rounded-md border border-input bg-transparent px-3 py-1 text-base shadow-sm transitio
  n-colors file:border-0 file:bg-transparent file:text-sm file:font-medium file:text-foreground placeholder:text-m
  uted-foreground focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allo
  wed disabled:opacity-50 md:text-sm",
          className
        )}
        ref={ref}
        {...props}
      />
    )
  }
)
Input.displayName = "Input"

export { Input }
```

FILE: artifacts/web-portal/src/components/ui/item.tsx
SIZE: 4,494 bytes

```
import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { Separator } from "@/components/ui/separator"

function ItemGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      role="list"
      data-slot="item-group"
      className={cn("group/item-group flex flex-col", className)}
      {...props}
    />
  )
}

function ItemSeparator({
  className,
  ...props
}: React.ComponentProps<typeof Separator>) {
  return (
    <Separator
      data-slot="item-separator"
      orientation="horizontal"
      className={cn("my-0", className)}
      {...props}
    />
  )
}

const itemVariants = cva(
  "group/item [a]:hover:bg-accent/50 focus-visible:border-ring focus-visible:ring-ring/50 [a]:transition-colors
  flex flex-wrap items-center rounded-md border border-transparent text-sm outline-none transition-colors duration
  -100 focus-visible:ring-[3px]",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        outline: "border-border",
        muted: "bg-muted/50",
      },
      size: {
        default: "gap-4 p-4 ",
        sm: "gap-2.5 px-4 py-3",
      },
    },
    defaultVariants: {
```

```
      variant: "default",
      size: "default",
    },
  }
)

function Item({
  className,
  variant = "default",
  size = "default",
  asChild = false,
  ...props
}: React.ComponentProps<"div"> &
  VariantProps<typeof itemVariants> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "div"
  return (
    <Comp
      data-slot="item"
      data-variant={variant}
      data-size={size}
      className={cn(itemVariants({ variant, size, className }))}
      {...props}
    />
  )
}

const itemMediaVariants = cva(
  "flex shrink-0 items-center justify-center gap-2 group-has-[[data-slot=item-description]]/item:translate-y-0.5
   group-has-[[data-slot=item-description]]/item:self-start [&_svg]:pointer-events-none",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        icon: "bg-muted size-8 rounded-sm border [&_svg:not([class*='size-'])]:size-4",
        image:
          "size-10 overflow-hidden rounded-sm [&_img]:size-full [&_img]:object-cover",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

function ItemMedia({
  className,
  variant = "default",
  ...props
}: React.ComponentProps<"div"> & VariantProps<typeof itemMediaVariants>) {
  return (
    <div
      data-slot="item-media"
```

```
      data-variant={variant}
      className={cn(itemMediaVariants({ variant, className }))}
      {...props}
    />
  )
}

function ItemContent({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-content"
      className={cn(
        "flex flex-1 flex-col gap-1 [&+[data-slot=item-content]]:flex-none",
        className
      )}
      {...props}
    />
  )
}

function ItemTitle({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-title"
      className={cn(
        "flex w-fit items-center gap-2 text-sm font-medium leading-snug",
        className
      )}
      {...props}
    />
  )
}

function ItemDescription({ className, ...props }: React.ComponentProps<"p">) {
  return (
    <p
      data-slot="item-description"
      className={cn(
        "text-muted-foreground line-clamp-2 text-balance text-sm font-normal leading-normal",
        "[&>a:hover]:text-primary [&>a]:underline [&>a]:underline-offset-4",
        className
      )}
      {...props}
    />
  )
}

function ItemActions({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-actions"
      className={cn("flex items-center gap-2", className)}
```

```
      {...props}
    />
  )
}

function ItemHeader({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-header"
      className={cn(
        "flex basis-full items-center justify-between gap-2",
        className
      )}
      {...props}
    />
  )
}

function ItemFooter({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="item-footer"
      className={cn(
        "flex basis-full items-center justify-between gap-2",
        className
      )}
      {...props}
    />
  )
}

export {
  Item,
  ItemMedia,
  ItemContent,
  ItemActions,
  ItemGroup,
  ItemSeparator,
  ItemTitle,
  ItemDescription,
  ItemHeader,
  ItemFooter,
}
```

FILE: artifacts/web-portal/src/components/ui/kbd.tsx
SIZE: 862 bytes

```
import { cn } from "@/lib/utils"

function Kbd({ className, ...props }: React.ComponentProps<"kbd">) {
  return (
    <kbd
      data-slot="kbd"
      className={cn(
        "bg-muted text-muted-foreground pointer-events-none inline-flex h-5 w-fit min-w-5 select-none items-cent
  er justify-center gap-1 rounded-sm px-1 font-sans text-xs font-medium",
        "[&_svg:not([class*='size-'])]:size-3",
        "[[data-slot=tooltip-content]_&]:bg-background/20 [[data-slot=tooltip-content]_&]:text-background dark:[
  [data-slot=tooltip-content]_&]:bg-background/10",
        className
      )}
      {...props}
    />
  )
}

function KbdGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <kbd
      data-slot="kbd-group"
      className={cn("inline-flex items-center gap-1", className)}
      {...props}
    />
  )
}

export { Kbd, KbdGroup }
```

FILE: artifacts/web-portal/src/components/ui/label.tsx
SIZE: 724 bytes

```
"use client"

import * as React from "react"
import * as LabelPrimitive from "@radix-ui/react-label"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const labelVariants = cva(
  "text-sm font-medium leading-none peer-disabled:cursor-not-allowed peer-disabled:opacity-70"
)

const Label = React.forwardRef<
  React.ElementRef<typeof LabelPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root> &
    VariantProps<typeof labelVariants>
>(({ className, ...props }, ref) => (
  <LabelPrimitive.Root
    ref={ref}
    className={cn(labelVariants(), className)}
    {...props}
  />
))
Label.displayName = LabelPrimitive.Root.displayName

export { Label }
```

FILE: artifacts/web-portal/src/components/ui/menubar.tsx
SIZE: 8,608 bytes

```
import * as React from "react"
import * as MenubarPrimitive from "@radix-ui/react-menubar"
import { Check, ChevronRight, Circle } from "lucide-react"

import { cn } from "@/lib/utils"

function MenubarMenu({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Menu>) {
  return <MenubarPrimitive.Menu {...props} />
}

function MenubarGroup({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Group>) {
  return <MenubarPrimitive.Group {...props} />
}

function MenubarPortal({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Portal>) {
  return <MenubarPrimitive.Portal {...props} />
}

function MenubarRadioGroup({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.RadioGroup>) {
  return <MenubarPrimitive.RadioGroup {...props} />
}

function MenubarSub({
  ...props
}: React.ComponentProps<typeof MenubarPrimitive.Sub>) {
  return <MenubarPrimitive.Sub data-slot="menubar-sub" {...props} />
}

const Menubar = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Root>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Root
    ref={ref}
    className={cn(
      "flex h-9 items-center space-x-1 rounded-md border bg-background p-1 shadow-sm",
      className
    )}
    {...props}
  />
))
```

```
Menubar.displayName = MenubarPrimitive.Root.displayName

const MenubarTrigger = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Trigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-3 py-1 text-sm font-medium outline-none focus:
  bg-accent focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-accent-foreground",
      className
    )}
    {...props}
  />
))
MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName

const MenubarSubTrigger = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubTrigger>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubTrigger> & {
    inset?: boolean
  }
>(({ className, inset, children, ...props }, ref) => (
  <MenubarPrimitive.SubTrigger
    ref={ref}
    className={cn(
      "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:bg-accent
  focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-accent-foreground",
      inset && "pl-8",
      className
    )}
    {...props}
  >
    {children}
    <ChevronRight className="ml-auto h-4 w-4" />
  </MenubarPrimitive.SubTrigger>
))
MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName

const MenubarSubContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.SubContent>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubContent>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.SubContent
    ref={ref}
    className={cn(
      "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data
  -[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-i
  n-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[si
  de=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 ori
  gin-[--radix-menubar-content-transform-origin]",
```

```
      className
    )}
    {...props}
  />
))
MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName

const MenubarContent = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Content>
>(
  (
    { className, align = "start", alignOffset = -4, sideOffset = 8, ...props },
    ref
  ) => (
    <MenubarPrimitive.Portal>
      <MenubarPrimitive.Content
        ref={ref}
        align={align}
        alignOffset={alignOffset}
        sideOffset={sideOffset}
        className={cn(
          "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md
   data-[state=open]:animate-in data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoo
  m-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-righ
  t-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-menubar-conten
  t-transform-origin]",
          className
        )}
        {...props}
      />
    </MenubarPrimitive.Portal>
  )
)
MenubarContent.displayName = MenubarPrimitive.Content.displayName

const MenubarItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Item> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <MenubarPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none focus:b
  g-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      inset && "pl-8",
      className
    )}
    {...props}
  />
```

```
))
MenubarItem.displayName = MenubarPrimitive.Item.displayName

const MenubarCheckboxItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.CheckboxItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.CheckboxItem>
>(({ className, children, checked, ...props }, ref) => (
  <MenubarPrimitive.CheckboxItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    checked={checked}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.CheckboxItem>
))
MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName

const MenubarRadioItem = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.RadioItem>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.RadioItem>
>(({ className, children, ...props }, ref) => (
  <MenubarPrimitive.RadioItem
    ref={ref}
    className={cn(
      "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none fo
  cus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50",
      className
    )}
    {...props}
  >
    <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
      <MenubarPrimitive.ItemIndicator>
        <Circle className="h-4 w-4 fill-current" />
      </MenubarPrimitive.ItemIndicator>
    </span>
    {children}
  </MenubarPrimitive.RadioItem>
))
MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName

const MenubarLabel = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Label>,
```

```
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Label> & {
    inset?: boolean
  }
>(({ className, inset, ...props }, ref) => (
  <MenubarPrimitive.Label
    ref={ref}
    className={cn(
      "px-2 py-1.5 text-sm font-semibold",
      inset && "pl-8",
      className
    )}
    {...props}
  />
))
MenubarLabel.displayName = MenubarPrimitive.Label.displayName

const MenubarSeparator = React.forwardRef<
  React.ElementRef<typeof MenubarPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <MenubarPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-muted", className)}
    {...props}
  />
))
MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName

const MenubarShortcut = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLSpanElement>) => {
  return (
    <span
      className={cn(
        "ml-auto text-xs tracking-widest text-muted-foreground",
        className
      )}
      {...props}
    />
  )
}
MenubarShortcut.displayname = "MenubarShortcut"

export {
  Menubar,
  MenubarMenu,
  MenubarTrigger,
  MenubarContent,
  MenubarItem,
  MenubarSeparator,
  MenubarLabel,
```

```
  MenubarCheckboxItem,
  MenubarRadioGroup,
  MenubarRadioItem,
  MenubarPortal,
  MenubarSubContent,
  MenubarSubTrigger,
  MenubarGroup,
  MenubarSub,
  MenubarShortcut,
}
```

FILE: artifacts/web-portal/src/components/ui/navigation-menu.tsx
SIZE: 5,124 bytes

```
import * as React from "react"
import * as NavigationMenuPrimitive from "@radix-ui/react-navigation-menu"
import { cva } from "class-variance-authority"
import { ChevronDown } from "lucide-react"

import { cn } from "@/lib/utils"

const NavigationMenu = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Root>
>(({ className, children, ...props }, ref) => (
  <NavigationMenuPrimitive.Root
    ref={ref}
    className={cn(
      "relative z-10 flex max-w-max flex-1 items-center justify-center",
      className
    )}
    {...props}
  >
    {children}
    <NavigationMenuViewport />
  </NavigationMenuPrimitive.Root>
))
NavigationMenu.displayName = NavigationMenuPrimitive.Root.displayName

const NavigationMenuList = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.List>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.List
    ref={ref}
    className={cn(
      "group flex flex-1 list-none items-center justify-center space-x-1",
      className
    )}
    {...props}
  />
))
NavigationMenuList.displayName = NavigationMenuPrimitive.List.displayName

const NavigationMenuItem = NavigationMenuPrimitive.Item

const navigationMenuTriggerStyle = cva(
  "group inline-flex h-9 w-max items-center justify-center rounded-md bg-background px-4 py-2 text-sm font-mediu
  m transition-colors hover:bg-accent hover:text-accent-foreground focus:bg-accent focus:text-accent-foreground fo
  cus:outline-none disabled:pointer-events-none disabled:opacity-50 data-[state=open]:text-accent-foreground data-
  [state=open]:bg-accent/50 data-[state=open]:hover:bg-accent data-[state=open]:focus:bg-accent"
)
```

```
const NavigationMenuTrigger = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <NavigationMenuPrimitive.Trigger
    ref={ref}
    className={cn(navigationMenuTriggerStyle(), "group", className)}
    {...props}
  >
    {children}{" "}
    <ChevronDown
      className="relative top-[1px] ml-1 h-3 w-3 transition duration-300 group-data-[state=open]:rotate-180"
      aria-hidden="true"
    />
  </NavigationMenuPrimitive.Trigger>
))
NavigationMenuTrigger.displayName = NavigationMenuPrimitive.Trigger.displayName

const NavigationMenuContent = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Content>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.Content
    ref={ref}
    className={cn(
      "left-0 top-0 w-full data-[motion^=from-]:animate-in data-[motion^=to-]:animate-out data-[motion^=from-]:f
  ade-in data-[motion^=to-]:fade-out data-[motion=from-end]:slide-in-from-right-52 data-[motion=from-start]:slide-
  in-from-left-52 data-[motion=to-end]:slide-out-to-right-52 data-[motion=to-start]:slide-out-to-left-52 md:absolu
  te md:w-auto ",
      className
    )}
    {...props}
  />
))
NavigationMenuContent.displayName = NavigationMenuPrimitive.Content.displayName

const NavigationMenuLink = NavigationMenuPrimitive.Link

const NavigationMenuViewport = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Viewport>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Viewport>
>(({ className, ...props }, ref) => (
  <div className={cn("absolute left-0 top-full flex justify-center")}>
    <NavigationMenuPrimitive.Viewport
      className={cn(
        "origin-top-center relative mt-1.5 h-[var(--radix-navigation-menu-viewport-height)] w-full overflow-hidd
  en rounded-md border bg-popover text-popover-foreground shadow data-[state=open]:animate-in data-[state=closed]:
  animate-out data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-90 md:w-[var(--radix-navigation-menu-viewp
  ort-width)]",
        className
      )}
      ref={ref}
```

```
      {...props}
    />
  </div>
))
NavigationMenuViewport.displayName =
  NavigationMenuPrimitive.Viewport.displayName

const NavigationMenuIndicator = React.forwardRef<
  React.ElementRef<typeof NavigationMenuPrimitive.Indicator>,
  React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Indicator>
>(({ className, ...props }, ref) => (
  <NavigationMenuPrimitive.Indicator
    ref={ref}
    className={cn(
      "top-full z-[1] flex h-1.5 items-end justify-center overflow-hidden data-[state=visible]:animate-in data-[
  state=hidden]:animate-out data-[state=hidden]:fade-out data-[state=visible]:fade-in",
      className
    )}
    {...props}
  >
    <div className="relative top-[60%] h-2 w-2 rotate-45 rounded-tl-sm bg-border shadow-md" />
  </NavigationMenuPrimitive.Indicator>
))
NavigationMenuIndicator.displayName =
  NavigationMenuPrimitive.Indicator.displayName

export {
  navigationMenuTriggerStyle,
  NavigationMenu,
  NavigationMenuList,
  NavigationMenuItem,
  NavigationMenuContent,
  NavigationMenuTrigger,
  NavigationMenuLink,
  NavigationMenuIndicator,
  NavigationMenuViewport,
}
```

FILE: artifacts/web-portal/src/components/ui/pagination.tsx
SIZE: 2,751 bytes

```
import * as React from "react"
import { ChevronLeft, ChevronRight, MoreHorizontal } from "lucide-react"

import { cn } from "@/lib/utils"
import { ButtonProps, buttonVariants } from "@/components/ui/button"

const Pagination = ({ className, ...props }: React.ComponentProps<"nav">) => (
  <nav
    role="navigation"
    aria-label="pagination"
    className={cn("mx-auto flex w-full justify-center", className)}
    {...props}
  />
)
Pagination.displayName = "Pagination"

const PaginationContent = React.forwardRef<
  HTMLUListElement,
  React.ComponentProps<"ul">
>(({ className, ...props }, ref) => (
  <ul
    ref={ref}
    className={cn("flex flex-row items-center gap-1", className)}
    {...props}
  />
))
PaginationContent.displayName = "PaginationContent"

const PaginationItem = React.forwardRef<
  HTMLLIElement,
  React.ComponentProps<"li">
>(({ className, ...props }, ref) => (
  <li ref={ref} className={cn("", className)} {...props} />
))
PaginationItem.displayName = "PaginationItem"

type PaginationLinkProps = {
  isActive?: boolean
} & Pick<ButtonProps, "size"> &
  React.ComponentProps<"a">

const PaginationLink = ({
  className,
  isActive,
  size = "icon",
  ...props
}: PaginationLinkProps) => (
  <a
    aria-current={isActive ? "page" : undefined}
```

```
    className={cn(
      buttonVariants({
        variant: isActive ? "outline" : "ghost",
        size,
      }),
      className
    )}
    {...props}
  />
)
PaginationLink.displayName = "PaginationLink"

const PaginationPrevious = ({
  className,
  ...props
}: React.ComponentProps<typeof PaginationLink>) => (
  <PaginationLink
    aria-label="Go to previous page"
    size="default"
    className={cn("gap-1 pl-2.5", className)}
    {...props}
  >
    <ChevronLeft className="h-4 w-4" />
    <span>Previous</span>
  </PaginationLink>
)
PaginationPrevious.displayName = "PaginationPrevious"

const PaginationNext = ({
  className,
  ...props
}: React.ComponentProps<typeof PaginationLink>) => (
  <PaginationLink
    aria-label="Go to next page"
    size="default"
    className={cn("gap-1 pr-2.5", className)}
    {...props}
  >
    <span>Next</span>
    <ChevronRight className="h-4 w-4" />
  </PaginationLink>
)
PaginationNext.displayName = "PaginationNext"

const PaginationEllipsis = ({
  className,
  ...props
}: React.ComponentProps<"span">) => (
  <span
    aria-hidden
    className={cn("flex h-9 w-9 items-center justify-center", className)}
    {...props}
```

```
  >
    <MoreHorizontal className="h-4 w-4" />
    <span className="sr-only">More pages</span>
  </span>
)
PaginationEllipsis.displayName = "PaginationEllipsis"

export {
  Pagination,
  PaginationContent,
  PaginationLink,
  PaginationItem,
  PaginationPrevious,
  PaginationNext,
  PaginationEllipsis,
}
```

FILE: artifacts/web-portal/src/components/ui/popover.tsx
SIZE: 1,342 bytes

```
import * as React from "react"
import * as PopoverPrimitive from "@radix-ui/react-popover"

import { cn } from "@/lib/utils"

const Popover = PopoverPrimitive.Root

const PopoverTrigger = PopoverPrimitive.Trigger

const PopoverAnchor = PopoverPrimitive.Anchor

const PopoverContent = React.forwardRef<
  React.ElementRef<typeof PopoverPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof PopoverPrimitive.Content>
>(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
  <PopoverPrimitive.Portal>
    <PopoverPrimitive.Content
      ref={ref}
      align={align}
      sideOffset={sideOffset}
      className={cn(
        "z-50 w-72 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-[state=o
  pen]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
  [state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:
  slide-in-from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--ra
  dix-popover-content-transform-origin]",
        className
      )}
      {...props}
    />
  </PopoverPrimitive.Portal>
))
PopoverContent.displayName = PopoverPrimitive.Content.displayName

export { Popover, PopoverTrigger, PopoverContent, PopoverAnchor }
```

FILE: artifacts/web-portal/src/components/ui/progress.tsx
SIZE: 792 bytes

```
"use client"

import * as React from "react"
import * as ProgressPrimitive from "@radix-ui/react-progress"

import { cn } from "@/lib/utils"

const Progress = React.forwardRef<
  React.ElementRef<typeof ProgressPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ProgressPrimitive.Root>
>(({ className, value, ...props }, ref) => (
  <ProgressPrimitive.Root
    ref={ref}
    className={cn(
      "relative h-2 w-full overflow-hidden rounded-full bg-primary/20",
      className
    )}
    {...props}
  >
    <ProgressPrimitive.Indicator
      className="h-full w-full flex-1 bg-primary transition-all"
      style={{ transform: `translateX(-${100 - (value || 0)}%)` }}
    />
  </ProgressPrimitive.Root>
))
Progress.displayName = ProgressPrimitive.Root.displayName

export { Progress }
```

FILE: artifacts/web-portal/src/components/ui/radio-group.tsx
SIZE: 1,410 bytes

```
import * as React from "react"
import * as RadioGroupPrimitive from "@radix-ui/react-radio-group"
import { Circle } from "lucide-react"

import { cn } from "@/lib/utils"

const RadioGroup = React.forwardRef<
  React.ElementRef<typeof RadioGroupPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Root>
>(({ className, ...props }, ref) => {
  return (
    <RadioGroupPrimitive.Root
      className={cn("grid gap-2", className)}
      {...props}
      ref={ref}
    />
  )
})
RadioGroup.displayName = RadioGroupPrimitive.Root.displayName

const RadioGroupItem = React.forwardRef<
  React.ElementRef<typeof RadioGroupPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Item>
>(({ className, ...props }, ref) => {
  return (
    <RadioGroupPrimitive.Item
      ref={ref}
      className={cn(
        "aspect-square h-4 w-4 rounded-full border border-primary text-primary shadow focus:outline-none focus-v
  isible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50",
        className
      )}
      {...props}
    >
      <RadioGroupPrimitive.Indicator className="flex items-center justify-center">
        <Circle className="h-3.5 w-3.5 fill-primary" />
      </RadioGroupPrimitive.Indicator>
    </RadioGroupPrimitive.Item>
  )
})
RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName

export { RadioGroup, RadioGroupItem }
```

FILE: artifacts/web-portal/src/components/ui/resizable.tsx
SIZE: 1,723 bytes

```
"use client"

import { GripVertical } from "lucide-react"
import * as ResizablePrimitive from "react-resizable-panels"

import { cn } from "@/lib/utils"

const ResizablePanelGroup = ({
  className,
  ...props
}: React.ComponentProps<typeof ResizablePrimitive.PanelGroup>) => (
  <ResizablePrimitive.PanelGroup
    className={cn(
      "flex h-full w-full data-[panel-group-direction=vertical]:flex-col",
      className
    )}
    {...props}
  />
)

const ResizablePanel = ResizablePrimitive.Panel

const ResizableHandle = ({
  withHandle,
  className,
  ...props
}: React.ComponentProps<typeof ResizablePrimitive.PanelResizeHandle> & {
  withHandle?: boolean
}) => (
  <ResizablePrimitive.PanelResizeHandle
    className={cn(
      "relative flex w-px items-center justify-center bg-border after:absolute after:inset-y-0 after:left-1/2 af
  ter:w-1 after:-translate-x-1/2 focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring focus-vis
  ible:ring-offset-1 data-[panel-group-direction=vertical]:h-px data-[panel-group-direction=vertical]:w-full data-
  [panel-group-direction=vertical]:after:left-0 data-[panel-group-direction=vertical]:after:h-1 data-[panel-group-
  direction=vertical]:after:w-full data-[panel-group-direction=vertical]:after:-translate-y-1/2 data-[panel-group-
  direction=vertical]:after:translate-x-0 [&[data-panel-group-direction=vertical]>div]:rotate-90",
      className
    )}
    {...props}
  >
    {withHandle && (
      <div className="z-10 flex h-4 w-3 items-center justify-center rounded-sm border bg-border">
        <GripVertical className="h-2.5 w-2.5" />
      </div>
    )}
  </ResizablePrimitive.PanelResizeHandle>
)
```

```
export { ResizablePanelGroup, ResizablePanel, ResizableHandle }
```

FILE: artifacts/web-portal/src/components/ui/scroll-area.tsx
SIZE: 1,642 bytes

```
import * as React from "react"
import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area"

import { cn } from "@/lib/utils"

const ScrollArea = React.forwardRef<
  React.ElementRef<typeof ScrollAreaPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.Root>
>(({ className, children, ...props }, ref) => (
  <ScrollAreaPrimitive.Root
    ref={ref}
    className={cn("relative overflow-hidden", className)}
    {...props}
  >
    <ScrollAreaPrimitive.Viewport className="h-full w-full rounded-[inherit]">
      {children}
    </ScrollAreaPrimitive.Viewport>
    <ScrollBar />
    <ScrollAreaPrimitive.Corner />
  </ScrollAreaPrimitive.Root>
))
ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName

const ScrollBar = React.forwardRef<
  React.ElementRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>,
  React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>
>(({ className, orientation = "vertical", ...props }, ref) => (
  <ScrollAreaPrimitive.ScrollAreaScrollbar
    ref={ref}
    orientation={orientation}
    className={cn(
      "flex touch-none select-none transition-colors",
      orientation === "vertical" &&
        "h-full w-2.5 border-l border-l-transparent p-[1px]",
      orientation === "horizontal" &&
        "h-2.5 flex-col border-t border-t-transparent p-[1px]",
      className
    )}
    {...props}
  >
    <ScrollAreaPrimitive.ScrollAreaThumb className="relative flex-1 rounded-full bg-border" />
  </ScrollAreaPrimitive.ScrollAreaScrollbar>
))
ScrollBar.displayName = ScrollAreaPrimitive.ScrollAreaScrollbar.displayName

export { ScrollArea, ScrollBar }
```

FILE: artifacts/web-portal/src/components/ui/select.tsx
SIZE: 5,745 bytes

```
"use client"

import * as React from "react"
import * as SelectPrimitive from "@radix-ui/react-select"
import { Check, ChevronDown, ChevronUp } from "lucide-react"

import { cn } from "@/lib/utils"

const Select = SelectPrimitive.Root

const SelectGroup = SelectPrimitive.Group

const SelectValue = SelectPrimitive.Value

const SelectTrigger = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <SelectPrimitive.Trigger
    ref={ref}
    className={cn(
      "flex h-9 w-full items-center justify-between whitespace-nowrap rounded-md border border-input bg-transpar
  ent px-3 py-2 text-sm shadow-sm ring-offset-background data-[placeholder]:text-muted-foreground focus:outline-no
  ne focus:ring-1 focus:ring-ring disabled:cursor-not-allowed disabled:opacity-50 [&>span]:line-clamp-1",
      className
    )}
    {...props}
  >
    {children}
    <SelectPrimitive.Icon asChild>
      <ChevronDown className="h-4 w-4 opacity-50" />
    </SelectPrimitive.Icon>
  </SelectPrimitive.Trigger>
))
SelectTrigger.displayName = SelectPrimitive.Trigger.displayName

const SelectScrollUpButton = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.ScrollUpButton>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollUpButton>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.ScrollUpButton
    ref={ref}
    className={cn(
      "flex cursor-default items-center justify-center py-1",
      className
    )}
    {...props}
  >
    <ChevronUp className="h-4 w-4" />
```

```
  </SelectPrimitive.ScrollUpButton>
))
SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName

const SelectScrollDownButton = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.ScrollDownButton>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollDownButton>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.ScrollDownButton
    ref={ref}
    className={cn(
      "flex cursor-default items-center justify-center py-1",
      className
    )}
    {...props}
  >
    <ChevronDown className="h-4 w-4" />
  </SelectPrimitive.ScrollDownButton>
))
SelectScrollDownButton.displayName =
  SelectPrimitive.ScrollDownButton.displayName

const SelectContent = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Content>
>(({ className, children, position = "popper", ...props }, ref) => (
  <SelectPrimitive.Portal>
    <SelectPrimitive.Content
      ref={ref}
      className={cn(
        "relative z-50 max-h-[--radix-select-content-available-height] min-w-[8rem] overflow-y-auto overflow-x-h
  idden rounded-md border bg-popover text-popover-foreground shadow-md data-[state=open]:animate-in data-[state=cl
  osed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 dat
  a-[state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[si
  de=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-select-content-transform-o
  rigin]",
        position === "popper" &&
          "data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-[side=right]:translate-x-1 data
  -[side=top]:-translate-y-1",
        className
      )}
      position={position}
      {...props}
    >
      <SelectScrollUpButton />
      <SelectPrimitive.Viewport
        className={cn(
          "p-1",
          position === "popper" &&
            "h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-width)]"
        )}
      >
```

```
        {children}
      </SelectPrimitive.Viewport>
      <SelectScrollDownButton />
    </SelectPrimitive.Content>
  </SelectPrimitive.Portal>
))
SelectContent.displayName = SelectPrimitive.Content.displayName

const SelectLabel = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Label>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Label>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.Label
    ref={ref}
    className={cn("px-2 py-1.5 text-sm font-semibold", className)}
    {...props}
  />
))
SelectLabel.displayName = SelectPrimitive.Label.displayName

const SelectItem = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Item>
>(({ className, children, ...props }, ref) => (
  <SelectPrimitive.Item
    ref={ref}
    className={cn(
      "relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-2 pr-8 text-sm outline-
  none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none data-[disabled]:opacity-50
  ",
      className
    )}
    {...props}
  >
    <span className="absolute right-2 flex h-3.5 w-3.5 items-center justify-center">
      <SelectPrimitive.ItemIndicator>
        <Check className="h-4 w-4" />
      </SelectPrimitive.ItemIndicator>
    </span>
    <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>
  </SelectPrimitive.Item>
))
SelectItem.displayName = SelectPrimitive.Item.displayName

const SelectSeparator = React.forwardRef<
  React.ElementRef<typeof SelectPrimitive.Separator>,
  React.ComponentPropsWithoutRef<typeof SelectPrimitive.Separator>
>(({ className, ...props }, ref) => (
  <SelectPrimitive.Separator
    ref={ref}
    className={cn("-mx-1 my-1 h-px bg-muted", className)}
    {...props}
```

```
  />
))
SelectSeparator.displayName = SelectPrimitive.Separator.displayName

export {
  Select,
  SelectGroup,
  SelectValue,
  SelectTrigger,
  SelectContent,
  SelectLabel,
  SelectItem,
  SelectSeparator,
  SelectScrollUpButton,
  SelectScrollDownButton,
}
```

FILE: artifacts/web-portal/src/components/ui/separator.tsx
SIZE: 756 bytes

```
import * as React from "react"
import * as SeparatorPrimitive from "@radix-ui/react-separator"

import { cn } from "@/lib/utils"

const Separator = React.forwardRef<
  React.ElementRef<typeof SeparatorPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof SeparatorPrimitive.Root>
>(
  (
    { className, orientation = "horizontal", decorative = true, ...props },
    ref
  ) => (
    <SeparatorPrimitive.Root
      ref={ref}
      decorative={decorative}
      orientation={orientation}
      className={cn(
        "shrink-0 bg-border",
        orientation === "horizontal" ? "h-[1px] w-full" : "h-full w-[1px]",
        className
      )}
      {...props}
    />
  )
)
Separator.displayName = SeparatorPrimitive.Root.displayName

export { Separator }
```

FILE: artifacts/web-portal/src/components/ui/sheet.tsx
SIZE: 4,280 bytes

```
"use client"

import * as React from "react"
import * as SheetPrimitive from "@radix-ui/react-dialog"
import { cva, type VariantProps } from "class-variance-authority"
import { X } from "lucide-react"

import { cn } from "@/lib/utils"

const Sheet = SheetPrimitive.Root

const SheetTrigger = SheetPrimitive.Trigger

const SheetClose = SheetPrimitive.Close

const SheetPortal = SheetPrimitive.Portal

const SheetOverlay = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Overlay
    className={cn(
      "fixed inset-0 z-50 bg-black/80  data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=
  closed]:fade-out-0 data-[state=open]:fade-in-0",
      className
    )}
    {...props}
    ref={ref}
  />
))
SheetOverlay.displayName = SheetPrimitive.Overlay.displayName

const sheetVariants = cva(
  "fixed z-50 gap-4 bg-background p-6 shadow-lg transition ease-in-out data-[state=closed]:duration-300 data-[st
  ate=open]:duration-500 data-[state=open]:animate-in data-[state=closed]:animate-out",
  {
    variants: {
      side: {
        top: "inset-x-0 top-0 border-b data-[state=closed]:slide-out-to-top data-[state=open]:slide-in-from-top"
  ,
        bottom:
          "inset-x-0 bottom-0 border-t data-[state=closed]:slide-out-to-bottom data-[state=open]:slide-in-from-b
  ottom",
        left: "inset-y-0 left-0 h-full w-3/4 border-r data-[state=closed]:slide-out-to-left data-[state=open]:sl
  ide-in-from-left sm:max-w-sm",
        right:
          "inset-y-0 right-0 h-full w-3/4 border-l data-[state=closed]:slide-out-to-right data-[state=open]:slid
  e-in-from-right sm:max-w-sm",
```

```
      },
    },
    defaultVariants: {
      side: "right",
    },
  }
)

interface SheetContentProps
  extends React.ComponentPropsWithoutRef<typeof SheetPrimitive.Content>,
    VariantProps<typeof sheetVariants> {}

const SheetContent = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Content>,
  SheetContentProps
>(({ side = "right", className, children, ...props }, ref) => (
  <SheetPortal>
    <SheetOverlay />
    <SheetPrimitive.Content
      ref={ref}
      className={cn(sheetVariants({ side }), className)}
      {...props}
    >
      <SheetPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background trans
  ition-opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:poi
  nter-events-none data-[state=open]:bg-secondary">
        <X className="h-4 w-4" />
        <span className="sr-only">Close</span>
      </SheetPrimitive.Close>
      {children}
    </SheetPrimitive.Content>
  </SheetPortal>
))
SheetContent.displayName = SheetPrimitive.Content.displayName

const SheetHeader = ({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col space-y-2 text-center sm:text-left",
      className
    )}
    {...props}
  />
)
SheetHeader.displayName = "SheetHeader"

const SheetFooter = ({
  className,
  ...props
```

```
}: React.HTMLAttributes<HTMLDivElement>) => (
  <div
    className={cn(
      "flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2",
      className
    )}
    {...props}
  />
)
SheetFooter.displayName = "SheetFooter"

const SheetTitle = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Title>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Title>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Title
    ref={ref}
    className={cn("text-lg font-semibold text-foreground", className)}
    {...props}
  />
))
SheetTitle.displayName = SheetPrimitive.Title.displayName

const SheetDescription = React.forwardRef<
  React.ElementRef<typeof SheetPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof SheetPrimitive.Description>
>(({ className, ...props }, ref) => (
  <SheetPrimitive.Description
    ref={ref}
    className={cn("text-sm text-muted-foreground", className)}
    {...props}
  />
))
SheetDescription.displayName = SheetPrimitive.Description.displayName

export {
  Sheet,
  SheetPortal,
  SheetOverlay,
  SheetTrigger,
  SheetClose,
  SheetContent,
  SheetHeader,
  SheetFooter,
  SheetTitle,
  SheetDescription,
}
```

FILE: artifacts/web-portal/src/components/ui/sidebar.tsx
SIZE: 21,846 bytes

```
"use client"

import * as React from "react"
import { Slot } from "@radix-ui/react-slot"
import { cva, VariantProps } from "class-variance-authority"
import { PanelLeftIcon } from "lucide-react"

import { useIsMobile } from "@/hooks/use-mobile"
import { cn } from "@/lib/utils"
import { Button } from "@/components/ui/button"
import { Input } from "@/components/ui/input"
import { Separator } from "@/components/ui/separator"
import {
  Sheet,
  SheetContent,
  SheetDescription,
  SheetHeader,
  SheetTitle,
} from "@/components/ui/sheet"
import { Skeleton } from "@/components/ui/skeleton"
import {
  Tooltip,
  TooltipContent,
  TooltipProvider,
  TooltipTrigger,
} from "@/components/ui/tooltip"

const SIDEBAR_COOKIE_NAME = "sidebar_state"
const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7
const SIDEBAR_WIDTH = "16rem"
const SIDEBAR_WIDTH_MOBILE = "18rem"
const SIDEBAR_WIDTH_ICON = "3rem"
const SIDEBAR_KEYBOARD_SHORTCUT = "b"

type SidebarContextProps = {
  state: "expanded" | "collapsed"
  open: boolean
  setOpen: (open: boolean) => void
  openMobile: boolean
  setOpenMobile: (open: boolean) => void
  isMobile: boolean
  toggleSidebar: () => void
}

const SidebarContext = React.createContext<SidebarContextProps | null>(null)

function useSidebar() {
  const context = React.useContext(SidebarContext)
  if (!context) {
```

```
    throw new Error("useSidebar must be used within a SidebarProvider.")
  }

  return context
}

function SidebarProvider({
  defaultOpen = true,
  open: openProp,
  onOpenChange: setOpenProp,
  className,
  style,
  children,
  ...props
}: React.ComponentProps<"div"> & {
  defaultOpen?: boolean
  open?: boolean
  onOpenChange?: (open: boolean) => void
}) {
  const isMobile = useIsMobile()
  const [openMobile, setOpenMobile] = React.useState(false)

  // This is the internal state of the sidebar.
  // We use openProp and setOpenProp for control from outside the component.
  const [_open, _setOpen] = React.useState(defaultOpen)
  const open = openProp ?? _open
  const setOpen = React.useCallback(
    (value: boolean | ((value: boolean) => boolean)) => {
      const openState = typeof value === "function" ? value(open) : value
      if (setOpenProp) {
        setOpenProp(openState)
      } else {
        _setOpen(openState)
      }

      // This sets the cookie to keep the sidebar state.
      document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState}; path=/; max-age=${SIDEBAR_COOKIE_MAX_AGE}`
    },
    [setOpenProp, open]
  )

  // Helper to toggle the sidebar.
  const toggleSidebar = React.useCallback(() => {
    return isMobile ? setOpenMobile((open) => !open) : setOpen((open) => !open)
  }, [isMobile, setOpen, setOpenMobile])

  // Adds a keyboard shortcut to toggle the sidebar.
  React.useEffect(() => {
    const handleKeyDown = (event: KeyboardEvent) => {
      if (
        event.key === SIDEBAR_KEYBOARD_SHORTCUT &&
        (event.metaKey || event.ctrlKey)
```

```
      ) {
        event.preventDefault()
        toggleSidebar()
      }
    }

    window.addEventListener("keydown", handleKeyDown)
    return () => window.removeEventListener("keydown", handleKeyDown)
  }, [toggleSidebar])

  // We add a state so that we can do data-state="expanded" or "collapsed".
  // This makes it easier to style the sidebar with Tailwind classes.
  const state = open ? "expanded" : "collapsed"

  const contextValue = React.useMemo<SidebarContextProps>(
    () => ({
      state,
      open,
      setOpen,
      isMobile,
      openMobile,
      setOpenMobile,
      toggleSidebar,
    }),
    [state, open, setOpen, isMobile, openMobile, setOpenMobile, toggleSidebar]
  )

  return (
    <SidebarContext.Provider value={contextValue}>
      <TooltipProvider delayDuration={0}>
        <div
          data-slot="sidebar-wrapper"
          style={
            {
              "--sidebar-width": SIDEBAR_WIDTH,
              "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,
              ...style,
            } as React.CSSProperties
          }
          className={cn(
            "group/sidebar-wrapper has-data-[variant=inset]:bg-sidebar flex min-h-svh w-full",
            className
          )}
          {...props}
        >
          {children}
        </div>
      </TooltipProvider>
    </SidebarContext.Provider>
  )
}
```

```
function Sidebar({
  side = "left",
  variant = "sidebar",
  collapsible = "offcanvas",
  className,
  children,
  ...props
}: React.ComponentProps<"div"> & {
  side?: "left" | "right"
  variant?: "sidebar" | "floating" | "inset"
  collapsible?: "offcanvas" | "icon" | "none"
}) {
  const { isMobile, state, openMobile, setOpenMobile } = useSidebar()

  if (collapsible === "none") {
    return (
      <div
        data-slot="sidebar"
        className={cn(
          "bg-sidebar text-sidebar-foreground flex h-full w-[var(--sidebar-width)] flex-col",
          className
        )}
        {...props}
      >
        {children}
      </div>
    )
  }

  if (isMobile) {
    return (
      <Sheet open={openMobile} onOpenChange={setOpenMobile} {...props}>
        <SheetContent
          data-sidebar="sidebar"
          data-slot="sidebar"
          data-mobile="true"
          className="bg-sidebar text-sidebar-foreground w-[var(--sidebar-width)] p-0 [&>button]:hidden"
          style={
            {
              "--sidebar-width": SIDEBAR_WIDTH_MOBILE,
            } as React.CSSProperties
          }
          side={side}
        >
          <SheetHeader className="sr-only">
            <SheetTitle>Sidebar</SheetTitle>
            <SheetDescription>Displays the mobile sidebar.</SheetDescription>
          </SheetHeader>
          <div className="flex h-full w-full flex-col">{children}</div>
        </SheetContent>
      </Sheet>
    )
```

```
  }

  return (
    <div
      className="group peer text-sidebar-foreground hidden md:block"
      data-state={state}
      data-collapsible={state === "collapsed" ? collapsible : ""}
      data-variant={variant}
      data-side={side}
      data-slot="sidebar"
    >
      {/* This is what handles the sidebar gap on desktop */}
      <div
        data-slot="sidebar-gap"
        className={cn(
          "relative w-[var(--sidebar-width)] bg-transparent transition-[width] duration-200 ease-linear",
          "group-data-[collapsible=offcanvas]:w-0",
          "group-data-[side=right]:rotate-180",
          variant === "floating" || variant === "inset"
            ? "group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)+var(--spacing-4))]"
            : "group-data-[collapsible=icon]:w-[var(--sidebar-width-icon)]"
        )}
      />
      <div
        data-slot="sidebar-container"
        className={cn(
          "fixed inset-y-0 z-10 hidden h-svh w-[var(--sidebar-width)] transition-[left,right,width] duration-200
 ease-linear md:flex",
          side === "left"
            ? "left-0 group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"
            : "right-0 group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar-width)*-1)]",
          // Adjust the padding for floating and inset variants.
          variant === "floating" || variant === "inset"
            ? "p-2 group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)+var(--spacing-4)+2px)]"
            : "group-data-[collapsible=icon]:w-[var(--sidebar-width-icon)] group-data-[side=left]:border-r group
-data-[side=right]:border-l",
          className
        )}
        {...props}
      >
        <div
          data-sidebar="sidebar"
          data-slot="sidebar-inner"
          className="bg-sidebar group-data-[variant=floating]:border-sidebar-border flex h-full w-full flex-col
group-data-[variant=floating]:rounded-lg group-data-[variant=floating]:border group-data-[variant=floating]:shad
ow-sm"
        >
          {children}
        </div>
      </div>
    </div>
  )
```

```
}

function SidebarTrigger({
  className,
  onClick,
  ...props
}: React.ComponentProps<typeof Button>) {
  const { toggleSidebar } = useSidebar()

  return (
    <Button
      data-sidebar="trigger"
      data-slot="sidebar-trigger"
      variant="ghost"
      size="icon"
      className={cn("h-7 w-7", className)}
      onClick={(event) => {
        onClick?.(event)
        toggleSidebar()
      }}
      {...props}
    >
      <PanelLeftIcon />
      <span className="sr-only">Toggle Sidebar</span>
    </Button>
  )
}

function SidebarRail({ className, ...props }: React.ComponentProps<"button">) {
  const { toggleSidebar } = useSidebar()

  // Note: Tailwind v3.4 doesn't support "in-" selectors. So the rail won't work perfectly.
  return (
    <button
      data-sidebar="rail"
      data-slot="sidebar-rail"
      aria-label="Toggle Sidebar"
      tabIndex={-1}
      onClick={toggleSidebar}
      title="Toggle Sidebar"
      className={cn(
        "hover:after:bg-sidebar-border absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2 transition-all ease-l
  inear group-data-[side=left]:-right-4 group-data-[side=right]:left-0 after:absolute after:inset-y-0 after:left-1
  /2 after:w-[2px] sm:flex",
        "in-data-[side=left]:cursor-w-resize in-data-[side=right]:cursor-e-resize",
        "[[data-side=left][data-state=collapsed]_&]:cursor-e-resize [[data-side=right][data-state=collapsed]_&]:
  cursor-w-resize",
        "hover:group-data-[collapsible=offcanvas]:bg-sidebar group-data-[collapsible=offcanvas]:translate-x-0 gr
  oup-data-[collapsible=offcanvas]:after:left-full",
        "[[data-side=left][data-collapsible=offcanvas]_&]:-right-2",
        "[[data-side=right][data-collapsible=offcanvas]_&]:-left-2",
        className
```

```
      )}
      {...props}
    />
  )
}

function SidebarInset({ className, ...props }: React.ComponentProps<"main">) {
  return (
    <main
      data-slot="sidebar-inset"
      className={cn(
        "bg-background relative flex w-full flex-1 flex-col",
        "md:peer-data-[variant=inset]:m-2 md:peer-data-[variant=inset]:ml-0 md:peer-data-[variant=inset]:rounded
  -xl md:peer-data-[variant=inset]:shadow-sm md:peer-data-[variant=inset]:peer-data-[state=collapsed]:ml-2",
        className
      )}
      {...props}
    />
  )
}

function SidebarInput({
  className,
  ...props
}: React.ComponentProps<typeof Input>) {
  return (
    <Input
      data-slot="sidebar-input"
      data-sidebar="input"
      className={cn("bg-background h-8 w-full shadow-none", className)}
      {...props}
    />
  )
}

function SidebarHeader({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-header"
      data-sidebar="header"
      className={cn("flex flex-col gap-2 p-2", className)}
      {...props}
    />
  )
}

function SidebarFooter({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-footer"
      data-sidebar="footer"
      className={cn("flex flex-col gap-2 p-2", className)}
```

```
      {...props}
    />
  )
}

function SidebarSeparator({
  className,
  ...props
}: React.ComponentProps<typeof Separator>) {
  return (
    <Separator
      data-slot="sidebar-separator"
      data-sidebar="separator"
      className={cn("bg-sidebar-border mx-2 w-auto", className)}
      {...props}
    />
  )
}

function SidebarContent({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-content"
      data-sidebar="content"
      className={cn(
        "flex min-h-0 flex-1 flex-col gap-2 overflow-auto group-data-[collapsible=icon]:overflow-hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarGroup({ className, ...props }: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-group"
      data-sidebar="group"
      className={cn("relative flex w-full min-w-0 flex-col p-2", className)}
      {...props}
    />
  )
}

function SidebarGroupLabel({
  className,
  asChild = false,
  ...props
}: React.ComponentProps<"div"> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "div"

  return (
```

```
    <Comp
      data-slot="sidebar-group-label"
      data-sidebar="group-label"
      className={cn(
        "text-sidebar-foreground/70 ring-sidebar-ring flex h-8 shrink-0 items-center rounded-md px-2 text-xs fon
  t-medium outline-hidden transition-[margin,opacity] duration-200 ease-linear focus-visible:ring-2 [&>svg]:h-4 [&
  >svg]:w-4 [&>svg]:shrink-0",
        "group-data-[collapsible=icon]:-mt-8 group-data-[collapsible=icon]:opacity-0",
        className
      )}
      {...props}
    />
  )
}

function SidebarGroupAction({
  className,
  asChild = false,
  ...props
}: React.ComponentProps<"button"> & { asChild?: boolean }) {
  const Comp = asChild ? Slot : "button"

  return (
    <Comp
      data-slot="sidebar-group-action"
      data-sidebar="group-action"
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
  absolute top-3.5 right-3 flex aspect-square w-5 items-center justify-center rounded-md p-0 outline-hidden transi
  tion-transform focus-visible:ring-2 [&>svg]:size-4 [&>svg]:shrink-0",
        // Increases the hit area of the button on mobile.
        "after:absolute after:-inset-2 md:after:hidden",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarGroupContent({
  className,
  ...props
}: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-group-content"
      data-sidebar="group-content"
      className={cn("w-full text-sm", className)}
      {...props}
    />
  )
```

```
}

function SidebarMenu({ className, ...props }: React.ComponentProps<"ul">) {
  return (
    <ul
      data-slot="sidebar-menu"
      data-sidebar="menu"
      className={cn("flex w-full min-w-0 flex-col gap-1", className)}
      {...props}
    />
  )
}

function SidebarMenuItem({ className, ...props }: React.ComponentProps<"li">) {
  return (
    <li
      data-slot="sidebar-menu-item"
      data-sidebar="menu-item"
      className={cn("group/menu-item relative", className)}
      {...props}
    />
  )
}

const sidebarMenuButtonVariants = cva(
  "peer/menu-button flex w-full items-center gap-2 overflow-hidden rounded-md p-2 text-left text-sm outline-hidd
  en ring-sidebar-ring transition-[width,height,padding] hover:bg-sidebar-accent hover:text-sidebar-accent-foregro
  und focus-visible:ring-2 active:bg-sidebar-accent active:text-sidebar-accent-foreground disabled:pointer-events-
  none disabled:opacity-50 group-has-data-[sidebar=menu-action]/menu-item:pr-8 aria-disabled:pointer-events-none a
  ria-disabled:opacity-50 data-[active=true]:bg-sidebar-accent data-[active=true]:font-medium data-[active=true]:t
  ext-sidebar-accent-foreground data-[state=open]:hover:bg-sidebar-accent data-[state=open]:hover:text-sidebar-acc
  ent-foreground group-data-[collapsible=icon]:w-8! group-data-[collapsible=icon]:h-8! group-data-[collapsible=ico
  n]:p-2! [&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "hover:bg-sidebar-accent hover:text-sidebar-accent-foreground",
        outline:
          "bg-background shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent hover:text-sideba
  r-accent-foreground hover:shadow-[0_0_0_1px_hsl(var(--sidebar-accent))]",
      },
      size: {
        default: "h-8 text-sm",
        sm: "h-7 text-xs",
        lg: "h-12 text-sm group-data-[collapsible=icon]:p-0!",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
```

```
)

function SidebarMenuButton({
  asChild = false,
  isActive = false,
  variant = "default",
  size = "default",
  tooltip,
  className,
  ...props
}: React.ComponentProps<"button"> & {
  asChild?: boolean
  isActive?: boolean
  tooltip?: string | React.ComponentProps<typeof TooltipContent>
} & VariantProps<typeof sidebarMenuButtonVariants>) {
  const Comp = asChild ? Slot : "button"
  const { isMobile, state } = useSidebar()

  const button = (
    <Comp
      data-slot="sidebar-menu-button"
      data-sidebar="menu-button"
      data-size={size}
      data-active={isActive}
      className={cn(sidebarMenuButtonVariants({ variant, size }), className)}
      {...props}
    />
  )

  if (!tooltip) {
    return button
  }

  if (typeof tooltip === "string") {
    tooltip = {
      children: tooltip,
    }
  }

  return (
    <Tooltip>
      <TooltipTrigger asChild>{button}</TooltipTrigger>
      <TooltipContent
        side="right"
        align="center"
        hidden={state !== "collapsed" || isMobile}
        {...tooltip}
      />
    </Tooltip>
  )
}
```

```
function SidebarMenuAction({
  className,
  asChild = false,
  showOnHover = false,
  ...props
}: React.ComponentProps<"button"> & {
  asChild?: boolean
  showOnHover?: boolean
}) {
  const Comp = asChild ? Slot : "button"

  return (
    <Comp
      data-slot="sidebar-menu-action"
      data-sidebar="menu-action"
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
  peer-hover/menu-button:text-sidebar-accent-foreground absolute top-1.5 right-1 flex aspect-square w-5 items-cent
  er justify-center rounded-md p-0 outline-hidden transition-transform focus-visible:ring-2 [&>svg]:size-4 [&>svg]
  :shrink-0",
        // Increases the hit area of the button on mobile.
        "after:absolute after:-inset-2 md:after:hidden",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
        "group-data-[collapsible=icon]:hidden",
        showOnHover &&
          "peer-data-[active=true]/menu-button:text-sidebar-accent-foreground group-focus-within/menu-item:opaci
  ty-100 group-hover/menu-item:opacity-100 data-[state=open]:opacity-100 md:opacity-0",
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuBadge({
  className,
  ...props
}: React.ComponentProps<"div">) {
  return (
    <div
      data-slot="sidebar-menu-badge"
      data-sidebar="menu-badge"
      className={cn(
        "text-sidebar-foreground pointer-events-none absolute right-1 flex h-5 min-w-5 items-center justify-cent
  er rounded-md px-1 text-xs font-medium tabular-nums select-none",
        "peer-hover/menu-button:text-sidebar-accent-foreground peer-data-[active=true]/menu-button:text-sidebar-
  accent-foreground",
        "peer-data-[size=sm]/menu-button:top-1",
        "peer-data-[size=default]/menu-button:top-1.5",
        "peer-data-[size=lg]/menu-button:top-2.5",
```

```
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuSkeleton({
  className,
  showIcon = false,
  ...props
}: React.ComponentProps<"div"> & {
  showIcon?: boolean
}) {
  // Random width between 50 to 90%.
  const width = React.useMemo(() => {
    return `${Math.floor(Math.random() * 40) + 50}%`
  }, [])

  return (
    <div
      data-slot="sidebar-menu-skeleton"
      data-sidebar="menu-skeleton"
      className={cn("flex h-8 items-center gap-2 rounded-md px-2", className)}
      {...props}
    >
      {showIcon && (
        <Skeleton
          className="size-4 rounded-md"
          data-sidebar="menu-skeleton-icon"
        />
      )}
      <Skeleton
        className="h-4 max-w-[var(--skeleton-width)] flex-1"
        data-sidebar="menu-skeleton-text"
        style={
          {
            "--skeleton-width": width,
          } as React.CSSProperties
        }
      />
    </div>
  )
}

function SidebarMenuSub({ className, ...props }: React.ComponentProps<"ul">) {
  return (
    <ul
      data-slot="sidebar-menu-sub"
      data-sidebar="menu-sub"
      className={cn(
```

```
        "border-sidebar-border mx-3.5 flex min-w-0 translate-x-px flex-col gap-1 border-l px-2.5 py-0.5",
        "group-data-[collapsible=icon]:hidden",
        className
      )}
      {...props}
    />
  )
}

function SidebarMenuSubItem({
  className,
  ...props
}: React.ComponentProps<"li">) {
  return (
    <li
      data-slot="sidebar-menu-sub-item"
      data-sidebar="menu-sub-item"
      className={cn("group/menu-sub-item relative", className)}
      {...props}
    />
  )
}

function SidebarMenuSubButton({
  asChild = false,
  size = "md",
  isActive = false,
  className,
  ...props
}: React.ComponentProps<"a"> & {
  asChild?: boolean
  size?: "sm" | "md"
  isActive?: boolean
}) {
  const Comp = asChild ? Slot : "a"

  return (
    <Comp
      data-slot="sidebar-menu-sub-button"
      data-sidebar="menu-sub-button"
      data-size={size}
      data-active={isActive}
      className={cn(
        "text-sidebar-foreground ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-accent-foreground
  active:bg-sidebar-accent active:text-sidebar-accent-foreground [&>svg]:text-sidebar-accent-foreground flex h-7 m
  in-w-0 -translate-x-px items-center gap-2 overflow-hidden rounded-md px-2 outline outline-2 outline-transparent
  outline-offset-2 focus-visible:ring-2 disabled:pointer-events-none disabled:opacity-50 aria-disabled:pointer-eve
  nts-none aria-disabled:opacity-50 [&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0",
        "data-[active=true]:bg-sidebar-accent data-[active=true]:text-sidebar-accent-foreground",
        size === "sm" && "text-xs",
        size === "md" && "text-sm",
        "group-data-[collapsible=icon]:hidden",
```

```
        className
      )}
      {...props}
    />
  )
}

export {
  Sidebar,
  SidebarContent,
  SidebarFooter,
  SidebarGroup,
  SidebarGroupAction,
  SidebarGroupContent,
  SidebarGroupLabel,
  SidebarHeader,
  SidebarInput,
  SidebarInset,
  SidebarMenu,
  SidebarMenuAction,
  SidebarMenuBadge,
  SidebarMenuButton,
  SidebarMenuItem,
  SidebarMenuSkeleton,
  SidebarMenuSub,
  SidebarMenuSubButton,
  SidebarMenuSubItem,
  SidebarProvider,
  SidebarRail,
  SidebarSeparator,
  SidebarTrigger,
  useSidebar,
}
```

FILE: artifacts/web-portal/src/components/ui/skeleton.tsx
SIZE: 266 bytes

```
import { cn } from "@/lib/utils"

function Skeleton({
  className,
  ...props
}: React.HTMLAttributes<HTMLDivElement>) {
  return (
    <div
      className={cn("animate-pulse rounded-md bg-primary/10", className)}
      {...props}
    />
  )
}

export { Skeleton }
```

FILE: artifacts/web-portal/src/components/ui/slider.tsx
SIZE: 1,037 bytes

```
import * as React from "react"
import * as SliderPrimitive from "@radix-ui/react-slider"

import { cn } from "@/lib/utils"

const Slider = React.forwardRef<
  React.ElementRef<typeof SliderPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof SliderPrimitive.Root>
>(({ className, ...props }, ref) => (
  <SliderPrimitive.Root
    ref={ref}
    className={cn(
      "relative flex w-full touch-none select-none items-center",
      className
    )}
    {...props}
  >
    <SliderPrimitive.Track className="relative h-1.5 w-full grow overflow-hidden rounded-full bg-primary/20">
      <SliderPrimitive.Range className="absolute h-full bg-primary" />
    </SliderPrimitive.Track>
    <SliderPrimitive.Thumb className="block h-4 w-4 rounded-full border border-primary/50 bg-background shadow t
  ransition-colors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:pointer-events
  -none disabled:opacity-50" />
  </SliderPrimitive.Root>
))
Slider.displayName = SliderPrimitive.Root.displayName

export { Slider }
```

FILE: artifacts/web-portal/src/components/ui/sonner.tsx
SIZE: 894 bytes

```
"use client"

import { useTheme } from "next-themes"
import { Toaster as Sonner } from "sonner"

type ToasterProps = React.ComponentProps<typeof Sonner>

const Toaster = ({ ...props }: ToasterProps) => {
  const { theme = "system" } = useTheme()

  return (
    <Sonner
      theme={theme as ToasterProps["theme"]}
      className="toaster group"
      toastOptions={{
        classNames: {
          toast:
            "group toast group-[.toaster]:bg-background group-[.toaster]:text-foreground group-[.toaster]:border
  -border group-[.toaster]:shadow-lg",
          description: "group-[.toast]:text-muted-foreground",
          actionButton:
            "group-[.toast]:bg-primary group-[.toast]:text-primary-foreground",
          cancelButton:
            "group-[.toast]:bg-muted group-[.toast]:text-muted-foreground",
        },
      }}
      {...props}
    />
  )
}

export { Toaster }
```

FILE: artifacts/web-portal/src/components/ui/spinner.tsx
SIZE: 331 bytes

```
import { Loader2Icon } from "lucide-react"

import { cn } from "@/lib/utils"

function Spinner({ className, ...props }: React.ComponentProps<"svg">) {
  return (
    <Loader2Icon
      role="status"
      aria-label="Loading"
      className={cn("size-4 animate-spin", className)}
      {...props}
    />
  )
}

export { Spinner }
```

FILE: artifacts/web-portal/src/components/ui/switch.tsx
SIZE: 1,148 bytes

```
import * as React from "react"
import * as SwitchPrimitives from "@radix-ui/react-switch"

import { cn } from "@/lib/utils"

const Switch = React.forwardRef<
  React.ElementRef<typeof SwitchPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof SwitchPrimitives.Root>
>(({ className, ...props }, ref) => (
  <SwitchPrimitives.Root
    className={cn(
      "peer inline-flex h-5 w-9 shrink-0 cursor-pointer items-center rounded-full border-2 border-transparent sh
  adow-sm transition-colors focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-visible:
  ring-offset-2 focus-visible:ring-offset-background disabled:cursor-not-allowed disabled:opacity-50 data-[state=c
  hecked]:bg-primary data-[state=unchecked]:bg-input",
      className
    )}
    {...props}
    ref={ref}
  >
    <SwitchPrimitives.Thumb
      className={cn(
        "pointer-events-none block h-4 w-4 rounded-full bg-background shadow-lg ring-0 transition-transform data
  -[state=checked]:translate-x-4 data-[state=unchecked]:translate-x-0"
      )}
    />
  </SwitchPrimitives.Root>
))
Switch.displayName = SwitchPrimitives.Root.displayName

export { Switch }
```

FILE: artifacts/web-portal/src/components/ui/table.tsx
SIZE: 2,859 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Table = React.forwardRef<
  HTMLTableElement,
  React.HTMLAttributes<HTMLTableElement>
>(({ className, ...props }, ref) => (
  <div className="relative w-full overflow-auto">
    <table
      ref={ref}
      className={cn("w-full caption-bottom text-sm", className)}
      {...props}
    />
  </div>
))
Table.displayName = "Table"

const TableHeader = React.forwardRef<
  HTMLTableSectionElement,
  React.HTMLAttributes<HTMLTableSectionElement>
>(({ className, ...props }, ref) => (
  <thead ref={ref} className={cn("[&_tr]:border-b", className)} {...props} />
))
TableHeader.displayName = "TableHeader"

const TableBody = React.forwardRef<
  HTMLTableSectionElement,
  React.HTMLAttributes<HTMLTableSectionElement>
>(({ className, ...props }, ref) => (
  <tbody
    ref={ref}
    className={cn("[&_tr:last-child]:border-0", className)}
    {...props}
  />
))
TableBody.displayName = "TableBody"

const TableFooter = React.forwardRef<
  HTMLTableSectionElement,
  React.HTMLAttributes<HTMLTableSectionElement>
>(({ className, ...props }, ref) => (
  <tfoot
    ref={ref}
    className={cn(
      "border-t bg-muted/50 font-medium [&>tr]:last:border-b-0",
      className
    )}
    {...props}
```

```
  />
))
TableFooter.displayName = "TableFooter"

const TableRow = React.forwardRef<
  HTMLTableRowElement,
  React.HTMLAttributes<HTMLTableRowElement>
>(({ className, ...props }, ref) => (
  <tr
    ref={ref}
    className={cn(
      "border-b transition-colors hover:bg-muted/50 data-[state=selected]:bg-muted",
      className
    )}
    {...props}
  />
))
TableRow.displayName = "TableRow"

const TableHead = React.forwardRef<
  HTMLTableCellElement,
  React.ThHTMLAttributes<HTMLTableCellElement>
>(({ className, ...props }, ref) => (
  <th
    ref={ref}
    className={cn(
      "h-10 px-2 text-left align-middle font-medium text-muted-foreground [&:has([role=checkbox])]:pr-0 [&>[role
  =checkbox]]:translate-y-[2px]",
      className
    )}
    {...props}
  />
))
TableHead.displayName = "TableHead"

const TableCell = React.forwardRef<
  HTMLTableCellElement,
  React.TdHTMLAttributes<HTMLTableCellElement>
>(({ className, ...props }, ref) => (
  <td
    ref={ref}
    className={cn(
      "p-2 align-middle [&:has([role=checkbox])]:pr-0 [&>[role=checkbox]]:translate-y-[2px]",
      className
    )}
    {...props}
  />
))
TableCell.displayName = "TableCell"

const TableCaption = React.forwardRef<
  HTMLTableCaptionElement,
```

```
  React.HTMLAttributes<HTMLTableCaptionElement>
>(({ className, ...props }, ref) => (
  <caption
    ref={ref}
    className={cn("mt-4 text-sm text-muted-foreground", className)}
    {...props}
  />
))
TableCaption.displayName = "TableCaption"

export {
  Table,
  TableHeader,
  TableBody,
  TableFooter,
  TableHead,
  TableRow,
  TableCell,
  TableCaption,
}
```

FILE: artifacts/web-portal/src/components/ui/tabs.tsx
SIZE: 1,877 bytes

```
import * as React from "react"
import * as TabsPrimitive from "@radix-ui/react-tabs"

import { cn } from "@/lib/utils"

const Tabs = TabsPrimitive.Root

const TabsList = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.List>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.List>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.List
    ref={ref}
    className={cn(
      "inline-flex h-9 items-center justify-center rounded-lg bg-muted p-1 text-muted-foreground",
      className
    )}
    {...props}
  />
))
TabsList.displayName = TabsPrimitive.List.displayName

const TabsTrigger = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Trigger>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Trigger
    ref={ref}
    className={cn(
      "inline-flex items-center justify-center whitespace-nowrap rounded-md px-3 py-1 text-sm font-medium ring-o
  ffset-background transition-all focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-vi
  sible:ring-offset-2 disabled:pointer-events-none disabled:opacity-50 data-[state=active]:bg-background data-[sta
  te=active]:text-foreground data-[state=active]:shadow",
      className
    )}
    {...props}
  />
))
TabsTrigger.displayName = TabsPrimitive.Trigger.displayName

const TabsContent = React.forwardRef<
  React.ElementRef<typeof TabsPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof TabsPrimitive.Content>
>(({ className, ...props }, ref) => (
  <TabsPrimitive.Content
    ref={ref}
    className={cn(
      "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus
  -visible:ring-offset-2",
```

```
      className
    )}
    {...props}
  />
))
TabsContent.displayName = TabsPrimitive.Content.displayName

export { Tabs, TabsList, TabsTrigger, TabsContent }
```

FILE: artifacts/web-portal/src/components/ui/textarea.tsx
SIZE: 649 bytes

```
import * as React from "react"

import { cn } from "@/lib/utils"

const Textarea = React.forwardRef<
  HTMLTextAreaElement,
  React.ComponentProps<"textarea">
>(({ className, ...props }, ref) => {
  return (
    <textarea
      className={cn(
        "flex min-h-[60px] w-full rounded-md border border-input bg-transparent px-3 py-2 text-base shadow-sm pl
  aceholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled
  :cursor-not-allowed disabled:opacity-50 md:text-sm",
        className
      )}
      ref={ref}
      {...props}
    />
  )
})
Textarea.displayName = "Textarea"

export { Textarea }
```

FILE: artifacts/web-portal/src/components/ui/toast.tsx
SIZE: 4,845 bytes

```
import * as React from "react"
import * as ToastPrimitives from "@radix-ui/react-toast"
import { cva, type VariantProps } from "class-variance-authority"
import { X } from "lucide-react"

import { cn } from "@/lib/utils"

const ToastProvider = ToastPrimitives.Provider

const ToastViewport = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Viewport>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Viewport
    ref={ref}
    className={cn(
      "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto sm:f
  lex-col md:max-w-[420px]",
      className
    )}
    {...props}
  />
))
ToastViewport.displayName = ToastPrimitives.Viewport.displayName

const toastVariants = cva(
  "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-hidden rounded
  -md border p-6 pr-8 shadow-lg transition-all data-[swipe=cancel]:translate-x-0 data-[swipe=end]:translate-x-[var
  (--radix-toast-swipe-end-x)] data-[swipe=move]:translate-x-[var(--radix-toast-swipe-move-x)] data-[swipe=move]:t
  ransition-none data-[state=open]:animate-in data-[state=closed]:animate-out data-[swipe=end]:animate-out data-[s
  tate=closed]:fade-out-80 data-[state=closed]:slide-out-to-right-full data-[state=open]:slide-in-from-top-full da
  ta-[state=open]:sm:slide-in-from-bottom-full",
  {
    variants: {
      variant: {
        default: "border bg-background text-foreground",
        destructive:
          "destructive group border-destructive bg-destructive text-destructive-foreground",
      },
    },
    defaultVariants: {
      variant: "default",
    },
  }
)

const Toast = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Root>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> &
```

```
    VariantProps<typeof toastVariants>
>(({ className, variant, ...props }, ref) => {
  return (
    <ToastPrimitives.Root
      ref={ref}
      className={cn(toastVariants({ variant }), className)}
      {...props}
    />
  )
})
Toast.displayName = ToastPrimitives.Root.displayName

const ToastAction = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Action>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Action
    ref={ref}
    className={cn(
      "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3 text-sm font-m
  edium ring-offset-background transition-colors hover:bg-secondary focus:outline-none focus:ring-2 focus:ring-rin
  g focus:ring-offset-2 disabled:pointer-events-none disabled:opacity-50 group-[.destructive]:border-muted/40 grou
  p-[.destructive]:hover:border-destructive/30 group-[.destructive]:hover:bg-destructive group-[.destructive]:hove
  r:text-destructive-foreground group-[.destructive]:focus:ring-destructive",
      className
    )}
    {...props}
  />
))
ToastAction.displayName = ToastPrimitives.Action.displayName

const ToastClose = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Close>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Close
    ref={ref}
    className={cn(
      "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity hover:text-foregrou
  nd focus:opacity-100 focus:outline-none focus:ring-2 group-hover:opacity-100 group-[.destructive]:text-red-300 g
  roup-[.destructive]:hover:text-red-50 group-[.destructive]:focus:ring-red-400 group-[.destructive]:focus:ring-of
  fset-red-600",
      className
    )}
    toast-close=""
    {...props}
  >
    <X className="h-4 w-4" />
  </ToastPrimitives.Close>
))
ToastClose.displayName = ToastPrimitives.Close.displayName
```

```
const ToastTitle = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Title>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Title
    ref={ref}
    className={cn("text-sm font-semibold", className)}
    {...props}
  />
))
ToastTitle.displayName = ToastPrimitives.Title.displayName

const ToastDescription = React.forwardRef<
  React.ElementRef<typeof ToastPrimitives.Description>,
  React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
>(({ className, ...props }, ref) => (
  <ToastPrimitives.Description
    ref={ref}
    className={cn("text-sm opacity-90", className)}
    {...props}
  />
))
ToastDescription.displayName = ToastPrimitives.Description.displayName

type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>

type ToastActionElement = React.ReactElement<typeof ToastAction>

export {
  type ToastProps,
  type ToastActionElement,
  ToastProvider,
  ToastViewport,
  Toast,
  ToastTitle,
  ToastDescription,
  ToastClose,
  ToastAction,
}
```

FILE: artifacts/web-portal/src/components/ui/toaster.tsx
SIZE: 772 bytes

```
import { useToast } from "@/hooks/use-toast"
import {
  Toast,
  ToastClose,
  ToastDescription,
  ToastProvider,
  ToastTitle,
  ToastViewport,
} from "@/components/ui/toast"

export function Toaster() {
  const { toasts } = useToast()

  return (
    <ToastProvider>
      {toasts.map(function ({ id, title, description, action, ...props }) {
        return (
          <Toast key={id} {...props}>
            <div className="grid gap-1">
              {title && <ToastTitle>{title}</ToastTitle>}
              {description && (
                <ToastDescription>{description}</ToastDescription>
              )}
            </div>
            {action}
            <ToastClose />
          </Toast>
        )
      })}
      <ToastViewport />
    </ToastProvider>
  )
}
```

FILE: artifacts/web-portal/src/components/ui/toggle-group.tsx
SIZE: 1,753 bytes

```
"use client"

import * as React from "react"
import * as ToggleGroupPrimitive from "@radix-ui/react-toggle-group"
import { type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"
import { toggleVariants } from "@/components/ui/toggle"

const ToggleGroupContext = React.createContext<
  VariantProps<typeof toggleVariants>
>({
  size: "default",
  variant: "default",
})

const ToggleGroup = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Root> &
    VariantProps<typeof toggleVariants>
>(({ className, variant, size, children, ...props }, ref) => (
  <ToggleGroupPrimitive.Root
    ref={ref}
    className={cn("flex items-center justify-center gap-1", className)}
    {...props}
  >
    <ToggleGroupContext.Provider value={{ variant, size }}>
      {children}
    </ToggleGroupContext.Provider>
  </ToggleGroupPrimitive.Root>
))

ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName

const ToggleGroupItem = React.forwardRef<
  React.ElementRef<typeof ToggleGroupPrimitive.Item>,
  React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Item> &
    VariantProps<typeof toggleVariants>
>(({ className, children, variant, size, ...props }, ref) => {
  const context = React.useContext(ToggleGroupContext)

  return (
    <ToggleGroupPrimitive.Item
      ref={ref}
      className={cn(
        toggleVariants({
          variant: context.variant || variant,
          size: context.size || size,
        }),
```

```
        className
      )}
      {...props}
    >
      {children}
    </ToggleGroupPrimitive.Item>
  )
})

ToggleGroupItem.displayName = ToggleGroupPrimitive.Item.displayName

export { ToggleGroup, ToggleGroupItem }
```

FILE: artifacts/web-portal/src/components/ui/toggle.tsx
SIZE: 1,486 bytes

```
import * as React from "react"
import * as TogglePrimitive from "@radix-ui/react-toggle"
import { cva, type VariantProps } from "class-variance-authority"

import { cn } from "@/lib/utils"

const toggleVariants = cva(
  "inline-flex items-center justify-center gap-2 rounded-md text-sm font-medium transition-colors hover:bg-muted
   hover:text-muted-foreground focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:po
  inter-events-none disabled:opacity-50 data-[state=on]:bg-accent data-[state=on]:text-accent-foreground [&_svg]:p
  ointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
  {
    variants: {
      variant: {
        default: "bg-transparent",
        outline:
          "border border-input bg-transparent shadow-sm hover:bg-accent hover:text-accent-foreground",
      },
      size: {
        default: "h-9 px-2 min-w-9",
        sm: "h-8 px-1.5 min-w-8",
        lg: "h-10 px-2.5 min-w-10",
      },
    },
    defaultVariants: {
      variant: "default",
      size: "default",
    },
  }
)

const Toggle = React.forwardRef<
  React.ElementRef<typeof TogglePrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof TogglePrimitive.Root> &
    VariantProps<typeof toggleVariants>
>(({ className, variant, size, ...props }, ref) => (
  <TogglePrimitive.Root
    ref={ref}
    className={cn(toggleVariants({ variant, size, className }))}
    {...props}
  />
))

Toggle.displayName = TogglePrimitive.Root.displayName

export { Toggle, toggleVariants }
```

FILE: artifacts/web-portal/src/components/ui/tooltip.tsx
SIZE: 1,267 bytes

```
"use client"

import * as React from "react"
import * as TooltipPrimitive from "@radix-ui/react-tooltip"

import { cn } from "@/lib/utils"

const TooltipProvider = TooltipPrimitive.Provider

const Tooltip = TooltipPrimitive.Root

const TooltipTrigger = TooltipPrimitive.Trigger

const TooltipContent = React.forwardRef<
  React.ElementRef<typeof TooltipPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof TooltipPrimitive.Content>
>(({ className, sideOffset = 4, ...props }, ref) => (
  <TooltipPrimitive.Portal>
    <TooltipPrimitive.Content
      ref={ref}
      sideOffset={sideOffset}
      className={cn(
        "z-50 overflow-hidden rounded-md bg-primary px-3 py-1.5 text-xs text-primary-foreground animate-in fade-
  in-0 zoom-in-95 data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=closed]:zoom-out-95 d
  ata-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-in-from-lef
  t-2 data-[side=top]:slide-in-from-bottom-2 origin-[--radix-tooltip-content-transform-origin]",
        className
      )}
      {...props}
    />
  </TooltipPrimitive.Portal>
))
TooltipContent.displayName = TooltipPrimitive.Content.displayName

export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider }
```

FILE: artifacts/web-portal/src/hooks/use-dashboard.ts
SIZE: 139 bytes

```
import { useGetDashboardKpis } from "@workspace/api-client-react";

export function useDashboardKpis() {
  return useGetDashboardKpis();
}
```

FILE: artifacts/web-portal/src/hooks/use-drivers.ts
SIZE: 1,505 bytes

```
import { useQueryClient } from "@tanstack/react-query";
import {
  useListDrivers,
  useCreateDriver as useCreateDriverGen,
  useUpdateDriver as useUpdateDriverGen,
  useDeleteDriver as useDeleteDriverGen,
  getListDriversQueryKey,
  useListDriverTasks,
  useUpdateDriverTask as useUpdateDriverTaskGen,
  getListDriverTasksQueryKey
} from "@workspace/api-client-react";

export function useDrivers() {
  return useListDrivers();
}

export function useCreateDriver() {
  const queryClient = useQueryClient();
  return useCreateDriverGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListDriversQueryKey() })
    }
  });
}

export function useUpdateDriver() {
  const queryClient = useQueryClient();
  return useUpdateDriverGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListDriversQueryKey() })
    }
  });
}

export function useDeleteDriver() {
  const queryClient = useQueryClient();
  return useDeleteDriverGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListDriversQueryKey() })
    }
  });
}

export function useDriverTasks(driverId: number) {
  return useListDriverTasks({ driverId }, { query: { enabled: !!driverId } as any });
}

export function useUpdateDriverTask() {
  const queryClient = useQueryClient();
```

```
  return useUpdateDriverTaskGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListDriverTasksQueryKey() })
    }
  });
}
```

FILE: artifacts/web-portal/src/hooks/use-missions.ts
SIZE: 1,041 bytes

```
import { useQueryClient } from "@tanstack/react-query";
import {
  useListMissions,
  useCreateMission as useCreateMissionGen,
  useUpdateMission as useUpdateMissionGen,
  useDeleteMission as useDeleteMissionGen,
  getListMissionsQueryKey
} from "@workspace/api-client-react";

export function useMissions() {
  return useListMissions();
}

export function useCreateMission() {
  const queryClient = useQueryClient();
  return useCreateMissionGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListMissionsQueryKey() })
    }
  });
}

export function useUpdateMission() {
  const queryClient = useQueryClient();
  return useUpdateMissionGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListMissionsQueryKey() })
    }
  });
}

export function useDeleteMission() {
  const queryClient = useQueryClient();
  return useDeleteMissionGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListMissionsQueryKey() })
    }
  });
}
```

FILE: artifacts/web-portal/src/hooks/use-mobile.tsx
SIZE: 565 bytes

```
import * as React from "react"

const MOBILE_BREAKPOINT = 768

export function useIsMobile() {
  const [isMobile, setIsMobile] = React.useState<boolean | undefined>(undefined)

  React.useEffect(() => {
    const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`)
    const onChange = () => {
      setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    }
    mql.addEventListener("change", onChange)
    setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
    return () => mql.removeEventListener("change", onChange)
  }, [])

  return !!isMobile
}
```

FILE: artifacts/web-portal/src/hooks/use-sites.ts
SIZE: 984 bytes

```
import { useQueryClient } from "@tanstack/react-query";
import {
  useListSites,
  useCreateSite as useCreateSiteGen,
  useUpdateSite as useUpdateSiteGen,
  useDeleteSite as useDeleteSiteGen,
  getListSitesQueryKey
} from "@workspace/api-client-react";

export function useSites() {
  return useListSites();
}

export function useCreateSite() {
  const queryClient = useQueryClient();
  return useCreateSiteGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListSitesQueryKey() })
    }
  });
}

export function useUpdateSite() {
  const queryClient = useQueryClient();
  return useUpdateSiteGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListSitesQueryKey() })
    }
  });
}

export function useDeleteSite() {
  const queryClient = useQueryClient();
  return useDeleteSiteGen({
    mutation: {
      onSuccess: () => queryClient.invalidateQueries({ queryKey: getListSitesQueryKey() })
    }
  });
}
```

FILE: artifacts/web-portal/src/hooks/use-toast.ts
SIZE: 3,895 bytes

```
import * as React from "react"

import type {
  ToastActionElement,
  ToastProps,
} from "@/components/ui/toast"

const TOAST_LIMIT = 1
const TOAST_REMOVE_DELAY = 1000000

type ToasterToast = ToastProps & {
  id: string
  title?: React.ReactNode
  description?: React.ReactNode
  action?: ToastActionElement
}

const actionTypes = {
  ADD_TOAST: "ADD_TOAST",
  UPDATE_TOAST: "UPDATE_TOAST",
  DISMISS_TOAST: "DISMISS_TOAST",
  REMOVE_TOAST: "REMOVE_TOAST",
} as const

let count = 0

function genId() {
  count = (count + 1) % Number.MAX_SAFE_INTEGER
  return count.toString()
}

type ActionType = typeof actionTypes

type Action =
  | {
      type: ActionType["ADD_TOAST"]
      toast: ToasterToast
    }
  | {
      type: ActionType["UPDATE_TOAST"]
      toast: Partial<ToasterToast>
    }
  | {
      type: ActionType["DISMISS_TOAST"]
      toastId?: ToasterToast["id"]
    }
  | {
      type: ActionType["REMOVE_TOAST"]
      toastId?: ToasterToast["id"]
```

```
    }

interface State {
  toasts: ToasterToast[]
}

const toastTimeouts = new Map<string, ReturnType<typeof setTimeout>>()

const addToRemoveQueue = (toastId: string) => {
  if (toastTimeouts.has(toastId)) {
    return
  }

  const timeout = setTimeout(() => {
    toastTimeouts.delete(toastId)
    dispatch({
      type: "REMOVE_TOAST",
      toastId: toastId,
    })
  }, TOAST_REMOVE_DELAY)

  toastTimeouts.set(toastId, timeout)
}

export const reducer = (state: State, action: Action): State => {
  switch (action.type) {
    case "ADD_TOAST":
      return {
        ...state,
        toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
      }

    case "UPDATE_TOAST":
      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === action.toast.id ? { ...t, ...action.toast } : t
        ),
      }

    case "DISMISS_TOAST": {
      const { toastId } = action

      // ! Side effects ! - This could be extracted into a dismissToast() action,
      // but I'll keep it here for simplicity
      if (toastId) {
        addToRemoveQueue(toastId)
      } else {
        state.toasts.forEach((toast) => {
          addToRemoveQueue(toast.id)
        })
      }
```

```
      return {
        ...state,
        toasts: state.toasts.map((t) =>
          t.id === toastId || toastId === undefined
            ? {
                ...t,
                open: false,
              }
            : t
        ),
      }
    }
    case "REMOVE_TOAST":
      if (action.toastId === undefined) {
        return {
          ...state,
          toasts: [],
        }
      }
      return {
        ...state,
        toasts: state.toasts.filter((t) => t.id !== action.toastId),
      }
  }
}

const listeners: Array<(state: State) => void> = []

let memoryState: State = { toasts: [] }

function dispatch(action: Action) {
  memoryState = reducer(memoryState, action)
  listeners.forEach((listener) => {
    listener(memoryState)
  })
}

type Toast = Omit<ToasterToast, "id">

function toast({ ...props }: Toast) {
  const id = genId()

  const update = (props: ToasterToast) =>
    dispatch({
      type: "UPDATE_TOAST",
      toast: { ...props, id },
    })
  const dismiss = () => dispatch({ type: "DISMISS_TOAST", toastId: id })

  dispatch({
    type: "ADD_TOAST",
```

```
    toast: {
      ...props,
      id,
      open: true,
      onOpenChange: (open) => {
        if (!open) dismiss()
      },
    },
  })

  return {
    id: id,
    dismiss,
    update,
  }
}

function useToast() {
  const [state, setState] = React.useState<State>(memoryState)

  React.useEffect(() => {
    listeners.push(setState)
    return () => {
      const index = listeners.indexOf(setState)
      if (index > -1) {
        listeners.splice(index, 1)
      }
    }
  }, [state])

  return {
    ...state,
    toast,
    dismiss: (toastId?: string) => dispatch({ type: "DISMISS_TOAST", toastId }),
  }
}

export { useToast, toast }
```

FILE: artifacts/web-portal/src/index.css
SIZE: 2,958 bytes

```
@import url('https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700&family=Outfit:wght@500;600;700;
  800&display=swap');
@import "tailwindcss";

@theme inline {
  --font-sans: 'Inter', sans-serif;
  --font-display: 'Outfit', sans-serif;

  --color-background: hsl(var(--background));
  --color-foreground: hsl(var(--foreground));
  --color-border: hsl(var(--border));
  --color-input: hsl(var(--input));
  --color-ring: hsl(var(--ring));

  --color-card: hsl(var(--card));
  --color-card-foreground: hsl(var(--card-foreground));

  --color-primary: hsl(var(--primary));
  --color-primary-foreground: hsl(var(--primary-foreground));

  --color-secondary: hsl(var(--secondary));
  --color-secondary-foreground: hsl(var(--secondary-foreground));

  --color-muted: hsl(var(--muted));
  --color-muted-foreground: hsl(var(--muted-foreground));

  --color-accent: hsl(var(--accent));
  --color-accent-foreground: hsl(var(--accent-foreground));

  --color-destructive: hsl(var(--destructive));
  --color-destructive-foreground: hsl(var(--destructive-foreground));

  --color-sidebar: hsl(var(--sidebar));
  --color-sidebar-foreground: hsl(var(--sidebar-foreground));
  --color-sidebar-primary: hsl(var(--sidebar-primary));

  --radius-sm: calc(var(--radius) - 4px);
  --radius-md: calc(var(--radius) - 2px);
  --radius-lg: var(--radius);
  --radius-xl: calc(var(--radius) + 4px);
}

:root {
  /* Clean Enterprise Light Theme */
  --background: 228 20% 98%;
  --foreground: 222 47% 11%;

  --card: 0 0% 100%;
  --card-foreground: 222 47% 11%;
```

```
  /* ACES Dark Navy */
  --primary: 212 100% 19%;
  --primary-foreground: 210 40% 98%;

  --secondary: 210 40% 96%;
  --secondary-foreground: 212 100% 19%;

  --muted: 210 40% 96%;
  --muted-foreground: 215 16% 47%;

  /* ACES Green */
  --accent: 149 100% 39%;
  --accent-foreground: 0 0% 100%;

  /* ACES Red */
  --destructive: 355 90% 46%;
  --destructive-foreground: 210 40% 98%;

  --border: 214 32% 91%;
  --input: 214 32% 91%;
  --ring: 212 100% 19%;

  /* Sidebar uses ACES Dark Navy */
  --sidebar: 212 100% 19%;
  --sidebar-foreground: 0 0% 100%;
  --sidebar-primary: 355 90% 46%;

  --radius: 0.75rem;
}

@layer base {
  * {
    @apply border-border;
  }

  body {
    @apply bg-background text-foreground antialiased font-sans selection:bg-primary/10 selection:text-primary;
  }

  h1, h2, h3, h4, h5, h6 {
    font-family: var(--font-display);
    @apply tracking-tight font-bold;
  }
}

/* Custom Scrollbar for a premium feel */
::-webkit-scrollbar {
  width: 8px;
  height: 8px;
}
::-webkit-scrollbar-track {
```

```
  background: transparent;
}
::-webkit-scrollbar-thumb {
  @apply bg-slate-300 rounded-full hover:bg-slate-400 transition-colors;
}

/* Utilities for glassmorphism */
.glass-panel {
  @apply bg-white/80 backdrop-blur-xl border border-white/20 shadow-xl shadow-slate-200/50;
}
.glass-dark {
  @apply bg-slate-900/80 backdrop-blur-xl border border-white/10 shadow-2xl;
}
```

FILE: artifacts/web-portal/src/lib/auth-context.tsx
SIZE: 2,161 bytes

```
import React, { createContext, useContext, useState, useEffect } from "react";
import { useLocation } from "wouter";

interface AuthUser {
  username?: string;
  role?: string;
  region?: string;
  driverId?: number;
  zone?: string;
  type: "admin" | "driver";
}

interface AuthContextType {
  user: AuthUser | null;
  loginAdmin: (username: string, role: string, region?: string) => void;
  loginDriver: (driverId: number, username: string) => void;
  logout: () => void;
}

const AuthContext = createContext<AuthContextType | undefined>(undefined);

export function AuthProvider({ children }: { children: React.ReactNode }) {
  const [user, setUser] = useState<AuthUser | null>(null);
  const [, setLocation] = useLocation();

  useEffect(() => {
    const stored = localStorage.getItem("aces_auth");
    if (stored) {
      try {
        const parsed = JSON.parse(stored);
        if (parsed.type === "admin" || parsed.type === "driver") {
          setUser(parsed);
        } else {
          localStorage.removeItem("aces_auth");
        }
      } catch (e) {
        localStorage.removeItem("aces_auth");
      }
    }
  }, []);

  const loginAdmin = (username: string, role: string, region?: string) => {
    const newUser: AuthUser = { type: "admin", username, role, region: region || "" };
    localStorage.setItem("aces_auth", JSON.stringify(newUser));
    setUser(newUser);
  };

  const loginDriver = (driverId: number, username: string) => {
    const newUser: AuthUser = { type: "driver", driverId, username };
```

```
    localStorage.setItem("aces_auth", JSON.stringify(newUser));
    setUser(newUser);
  };

  const logout = () => {
    const type = user?.type;
    localStorage.removeItem("aces_auth");
    setUser(null);
    if (type === "driver") {
      setLocation("/driver/login");
    } else {
      setLocation("/login");
    }
  };

  return (
    <AuthContext.Provider value={{ user, loginAdmin, loginDriver, logout }}>
      {children}
    </AuthContext.Provider>
  );
}

export function useAuth() {
  const context = useContext(AuthContext);
  if (!context) throw new Error("useAuth must be used within AuthProvider");
  return context;
}
```

FILE: artifacts/web-portal/src/lib/utils.ts
SIZE: 166 bytes

```
import { clsx, type ClassValue } from "clsx"
import { twMerge } from "tailwind-merge"

export function cn(...inputs: ClassValue[]) {
  return twMerge(clsx(inputs))
}
```

FILE: artifacts/web-portal/src/main.tsx
SIZE: 157 bytes

```
import { createRoot } from "react-dom/client";
import App from "./App";
import "./index.css";

createRoot(document.getElementById("root")!).render(<App />);
```

FILE: artifacts/web-portal/src/pages/admin/Admins.tsx
SIZE: 9,065 bytes

```
import { useState } from "react";
import { useListAdmins, useCreateAdmin, useUpdateAdmin, useDeleteAdmin } from "@workspace/api-client-react";
import { Card, CardContent } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Badge } from "@/components/ui/badge";
import { Dialog, DialogContent, DialogFooter, DialogHeader, DialogTitle } from "@/components/ui/dialog";
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from "@/components/ui/table";
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
import { Plus, Pencil, Trash2, ShieldCheck, UserCog } from "lucide-react";
import { useAuth } from "@/lib/auth-context";

type AdminForm = { name: string; username: string; email: string; password: string; position: string; role: stri
  ng; region: string };
const emptyForm: AdminForm = { name: "", username: "", email: "", password: "", position: "Admin", role: "supera
  dmin", region: "" };

const ROLE_CONFIG: Record<string, { label: string; color: string }> = {
  superadmin: { label: "Admin", color: "bg-primary/10 text-primary border-primary/20" },
  supervisor: { label: "Region Supervisor", color: "bg-amber-50 text-amber-700 border-amber-200" },
};

export default function AdminsPage() {
  const { user } = useAuth();
  const isSuperAdmin = user?.role === "superadmin";
  const { data: admins = [], refetch } = useListAdmins();
  const createMutation = useCreateAdmin();
  const updateMutation = useUpdateAdmin();
  const deleteMutation = useDeleteAdmin();
  const [query, setQuery] = useState("");
  const [dialogOpen, setDialogOpen] = useState(false);
  const [editId, setEditId] = useState<number | null>(null);
  const [form, setForm] = useState<AdminForm>(emptyForm);

  const filtered = admins.filter((a) =>
    a.name?.toLowerCase().includes(query.toLowerCase()) ||
    a.username?.toLowerCase().includes(query.toLowerCase())
  );

  const openCreate = () => { setEditId(null); setForm(emptyForm); setDialogOpen(true); };
  const openEdit = (a: any) => {
    setEditId(a.id);
    setForm({ name: a.name, username: a.username, email: a.email || "", password: "", position: a.position || "A
  dmin", role: (a as any).role || "superadmin", region: (a as any).region || "" });
    setDialogOpen(true);
  };

  const onSave = async () => {
```

```
  if (editId !== null) {
    const data: any = { name: form.name, username: form.username, email: form.email, position: form.position,
role: form.role, region: form.region };
    if (form.password) data.password = form.password;
    await updateMutation.mutateAsync({ id: editId, data });
  } else {
    await createMutation.mutateAsync({ data: { ...form } });
  }
  setDialogOpen(false);
  refetch();
};

const onDelete = async (id: number) => {
  if (!confirm("Delete this user?")) return;
  await deleteMutation.mutateAsync({ id });
  refetch();
};

return (
  <div className="space-y-6">
    <div className="flex items-center justify-between">
      <div>
        <h1 className="text-3xl font-bold text-slate-900">Admin Users</h1>
        <p className="text-slate-500 mt-1">Manage administrators and region supervisors</p>
      </div>
      {isSuperAdmin && (
        <Button onClick={openCreate} className="bg-primary text-white gap-2">
          <Plus className="w-4 h-4" /> Add User
        </Button>
      )}
    </div>

    <Card className="border-0 shadow-sm"><CardContent className="p-4">
      <Input placeholder="Search by name or username..." value={query} onChange={(e) => setQuery(e.target.valu
e)} className="max-w-xs" />
    </CardContent></Card>

    <Card className="border-0 shadow-sm overflow-hidden">
      <Table>
        <TableHeader>
          <TableRow className="bg-slate-50">
            <TableHead>#</TableHead>
            <TableHead>Name</TableHead>
            <TableHead>Username</TableHead>
            <TableHead>Email</TableHead>
            <TableHead>Role</TableHead>
            <TableHead>Region</TableHead>
            {isSuperAdmin && <TableHead>Actions</TableHead>}
          </TableRow>
        </TableHeader>
        <TableBody>
          {filtered.map((a, i) => {
```

```
            const roleCfg = ROLE_CONFIG[(a as any).role || "superadmin"] ?? ROLE_CONFIG.superadmin;
            return (
              <TableRow key={a.id}>
                <TableCell className="text-slate-500">{i + 1}</TableCell>
                <TableCell className="font-semibold">{a.name}</TableCell>
                <TableCell>{a.username}</TableCell>
                <TableCell>{a.email}</TableCell>
                <TableCell>
                  <Badge variant="outline" className={`text-xs font-medium ${roleCfg.color}`}>
                    {(a as any).role === "supervisor"
                      ? <><UserCog className="w-3 h-3 mr-1 inline" />Region Supervisor</>
                      : <><ShieldCheck className="w-3 h-3 mr-1 inline" />Admin</>
                    }
                  </Badge>
                </TableCell>
                <TableCell className="text-sm text-slate-600">
                  {(a as any).role === "supervisor" && (a as any).region
                    ? <span className="inline-block rounded-full px-2 py-0.5 text-xs font-medium bg-sky-50 tex
t-sky-700 border border-sky-100">{(a as any).region}</span>
                    : <span className="text-slate-300">—</span>
                  }
                </TableCell>
                {isSuperAdmin && (
                  <TableCell>
                    <div className="flex gap-2">
                      <Button size="icon" variant="ghost" onClick={() => openEdit(a)}><Pencil className="w-4 h
-4" /></Button>
                      <Button size="icon" variant="ghost" className="text-red-500" onClick={() => onDelete(a.i
d!)}><Trash2 className="w-4 h-4" /></Button>
                    </div>
                  </TableCell>
                )}
              </TableRow>
            );
          })}
          {filtered.length === 0 && (
            <TableRow><TableCell colSpan={6} className="text-center py-10 text-slate-400">No users found</Tabl
eCell></TableRow>
          )}
        </TableBody>
      </Table>
    </Card>

    <Dialog open={dialogOpen} onOpenChange={setDialogOpen}>
      <DialogContent>
        <DialogHeader><DialogTitle>{editId ? "Edit User" : "Add User"}</DialogTitle></DialogHeader>
        <div className="space-y-4">
          <div><Label>Name</Label><Input value={form.name} onChange={(e) => setForm((f) => ({ ...f, name: e.ta
rget.value }))} /></div>
          <div><Label>Username</Label><Input value={form.username} onChange={(e) => setForm((f) => ({ ...f, us
ername: e.target.value }))} /></div>
          <div><Label>Email</Label><Input type="email" value={form.email} onChange={(e) => setForm((f) => ({ .
```

```
  ..f, email: e.target.value }))} /></div>
            <div><Label>Password {editId && "(leave blank to keep current)"}</Label><Input type="password" value
  ={form.password} onChange={(e) => setForm((f) => ({ ...f, password: e.target.value }))} /></div>
            <div>
              <Label>Role</Label>
              <Select value={form.role} onValueChange={(v) => setForm((f) => ({ ...f, role: v, position: v === "
  supervisor" ? "Supervisor" : "Admin", region: v !== "supervisor" ? "" : f.region }))}>
                <SelectTrigger><SelectValue /></SelectTrigger>
                <SelectContent>
                  <SelectItem value="superadmin">
                    <div className="flex items-center gap-2"><ShieldCheck className="w-4 h-4 text-primary" />Adm
  in</div>
                  </SelectItem>
                  <SelectItem value="supervisor">
                    <div className="flex items-center gap-2"><UserCog className="w-4 h-4 text-amber-600" />Regio
  n Supervisor</div>
                  </SelectItem>
                </SelectContent>
              </Select>
            </div>
            {form.role === "supervisor" && (
              <div>
                <Label>Assigned Region</Label>
                <Select value={form.region} onValueChange={(v) => setForm((f) => ({ ...f, region: v }))}>
                  <SelectTrigger><SelectValue placeholder="Select region..." /></SelectTrigger>
                  <SelectContent>
                    <SelectItem value="CENTRAL">Central</SelectItem>
                    <SelectItem value="EAST">East</SelectItem>
                  </SelectContent>
                </Select>
              </div>
            )}
          </div>
          <DialogFooter>
            <Button variant="outline" onClick={() => setDialogOpen(false)}>Cancel</Button>
            <Button onClick={onSave} disabled={!form.name || !form.username || (!editId && !form.password)}>Save
  </Button>
          </DialogFooter>
        </DialogContent>
      </Dialog>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/admin/Dashboard.tsx
SIZE: 7,789 bytes

```
import { useDashboardKpis } from "@/hooks/use-dashboard";
import { Card, CardContent, CardHeader, CardTitle } from "@/components/ui/card";
import { Droplet, MapPin, Activity, Users, TrendingUp } from "lucide-react";
import { ResponsiveContainer, AreaChart, Area, XAxis, YAxis, Tooltip, CartesianGrid, PieChart, Pie, Cell } from
  "recharts";

export default function Dashboard() {
  const { data: kpis, isLoading } = useDashboardKpis();

  if (isLoading) {
    return (
      <div className="h-[60vh] flex items-center justify-center">
        <div className="animate-spin rounded-full h-12 w-12 border-b-2 border-primary"></div>
      </div>
    );
  }

  // Mock trend data since endpoint doesn't return full timeseries in the generated type
  const mockTrend = Array.from({ length: 7 }).map((_, i) => ({
    day: `Day ${i + 1}`,
    liters: Math.floor(Math.random() * 5000) + 1000
  }));

  const COLORS = ['hsl(var(--primary))', 'hsl(var(--accent))', 'hsl(var(--destructive))', '#F59E0B', '#8B5CF6'];

  return (
    <div className="space-y-6">
      <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-4 gap-6">
        <Card className="glass-panel border-0 overflow-hidden relative group">
          <div className="absolute top-0 right-0 p-4 opacity-10 group-hover:opacity-20 transition-opacity">
            <Droplet className="w-24 h-24 text-primary" />
          </div>
          <CardHeader className="pb-2">
            <CardTitle className="text-sm font-medium text-slate-500 uppercase tracking-wider">Liters Today</Car
  dTitle>
          </CardHeader>
          <CardContent>
            <div className="text-4xl font-display font-bold text-slate-900">
              {kpis?.litersToday?.toLocaleString() || 0} <span className="text-xl text-slate-400 font-sans">L</s
  pan>
            </div>
          </CardContent>
        </Card>

        <Card className="glass-panel border-0 overflow-hidden relative group">
          <div className="absolute top-0 right-0 p-4 opacity-10 group-hover:opacity-20 transition-opacity">
            <Activity className="w-24 h-24 text-accent" />
          </div>
          <CardHeader className="pb-2">
```

```
          <CardTitle className="text-sm font-medium text-slate-500 uppercase tracking-wider">30-Day Volume</CardTitle>
        </CardHeader>
        <CardContent>
          <div className="text-4xl font-display font-bold text-slate-900">
            {kpis?.liters30d?.toLocaleString() || 0} <span className="text-xl text-slate-400 font-sans">L</span>
          </div>
        </CardContent>
      </Card>

      <Card className="glass-panel border-0 overflow-hidden relative group">
        <div className="absolute top-0 right-0 p-4 opacity-10 group-hover:opacity-20 transition-opacity">
          <MapPin className="w-24 h-24 text-amber-500" />
        </div>
        <CardHeader className="pb-2">
          <CardTitle className="text-sm font-medium text-slate-500 uppercase tracking-wider">Active Missions</CardTitle>
        </CardHeader>
        <CardContent>
          <div className="text-4xl font-display font-bold text-slate-900">
            {kpis?.activeMissions || 0}
          </div>
        </CardContent>
      </Card>

      <Card className="glass-panel border-0 overflow-hidden relative group">
        <div className="absolute top-0 right-0 p-4 opacity-10 group-hover:opacity-20 transition-opacity">
          <Users className="w-24 h-24 text-purple-500" />
        </div>
        <CardHeader className="pb-2">
          <CardTitle className="text-sm font-medium text-slate-500 uppercase tracking-wider">Active Drivers</CardTitle>
        </CardHeader>
        <CardContent>
          <div className="text-4xl font-display font-bold text-slate-900">
            {kpis?.activeDrivers || 0}
          </div>
        </CardContent>
      </Card>
    </div>

    <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
      <Card className="glass-panel border-0 lg:col-span-2 shadow-xl shadow-slate-200/50">
        <CardHeader className="border-b border-slate-100 pb-4 mb-4 flex flex-row items-center justify-between">
          <CardTitle className="text-lg font-bold text-slate-800 flex items-center gap-2">
            <TrendingUp className="w-5 h-5 text-primary" />
            Fuel Pumping Trend
          </CardTitle>
        </CardHeader>
        <CardContent>
```

```
          <div className="h-[300px] w-full">
            <ResponsiveContainer width="100%" height="100%">
              <AreaChart data={mockTrend} margin={{ top: 10, right: 10, left: 0, bottom: 0 }}>
                <defs>
                  <linearGradient id="colorLiters" x1="0" y1="0" x2="0" y2="1">
                    <stop offset="5%" stopColor="hsl(var(--primary))" stopOpacity={0.3}/>
                    <stop offset="95%" stopColor="hsl(var(--primary))" stopOpacity={0}/>
                  </linearGradient>
                </defs>
                <CartesianGrid strokeDasharray="3 3" vertical={false} stroke="#E2E8F0" />
                <XAxis dataKey="day" axisLine={false} tickLine={false} tick={{fill: '#64748B', fontSize: 12}}
dy={10} />
                <YAxis axisLine={false} tickLine={false} tick={{fill: '#64748B', fontSize: 12}} />
                <Tooltip
                  contentStyle={{ borderRadius: '12px', border: 'none', boxShadow: '0 10px 25px -5px rgba(0, 0
, 0, 0.1)' }}
                />
                <Area type="monotone" dataKey="liters" stroke="hsl(var(--primary))" strokeWidth={3} fillOpacit
y={1} fill="url(#colorLiters)" />
              </AreaChart>
            </ResponsiveContainer>
          </div>
        </CardContent>
      </Card>

      <Card className="glass-panel border-0 shadow-xl shadow-slate-200/50">
        <CardHeader className="border-b border-slate-100 pb-4 mb-4">
          <CardTitle className="text-lg font-bold text-slate-800">Missions by Status</CardTitle>
        </CardHeader>
        <CardContent className="flex flex-col items-center justify-center">
          <div className="h-[250px] w-full">
            <ResponsiveContainer width="100%" height="100%">
              <PieChart>
                <Pie
                  data={kpis?.missionsByStatus || []}
                  cx="50%"
                  cy="50%"
                  innerRadius={60}
                  outerRadius={90}
                  paddingAngle={5}
                  dataKey="count"
                  nameKey="status"
                  stroke="none"
                >
                  {(kpis?.missionsByStatus || []).map((entry, index) => (
                    <Cell key={`cell-${index}`} fill={COLORS[index % COLORS.length]} />
                  ))}
                </Pie>
                <Tooltip
                  contentStyle={{ borderRadius: '12px', border: 'none', boxShadow: '0 4px 6px -1px rgba(0, 0,
0, 0.1)' }}
                />
```

```
                </PieChart>
              </ResponsiveContainer>
            </div>
            <div className="w-full mt-4 space-y-2">
              {(kpis?.missionsByStatus || []).map((entry, index) => (
                <div key={index} className="flex items-center justify-between text-sm">
                  <div className="flex items-center gap-2">
                    <div className="w-3 h-3 rounded-full" style={{ backgroundColor: COLORS[index % COLORS.length
  ] }} />
                    <span className="text-slate-600">{entry.status}</span>
                  </div>
                  <span className="font-bold text-slate-900">{entry.count}</span>
                </div>
              ))}
            </div>
          </CardContent>
        </Card>
      </div>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/admin/Drivers.tsx
SIZE: 16,801 bytes

```
import { useState, useRef } from "react";
import { useDrivers, useCreateDriver, useUpdateDriver, useDeleteDriver } from "@/hooks/use-drivers";
import { Card } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from "@/components/ui/table";
import { Dialog, DialogContent, DialogHeader, DialogTitle } from "@/components/ui/dialog";
import { Plus, Search, Trash2, Users, CheckCircle2, XCircle, Pencil, Camera, Loader2 } from "lucide-react";
import { useForm } from "react-hook-form";
import { zodResolver } from "@hookform/resolvers/zod";
import * as z from "zod";
import { Form, FormControl, FormField, FormItem, FormLabel, FormMessage } from "@/components/ui/form";
import { useToast } from "@/hooks/use-toast";
import { Switch } from "@/components/ui/switch";

const formSchema = z.object({
  name: z.string().min(1, "Driver name is required"),
  phone: z.string().optional(),
  email: z.string().email().optional().or(z.literal('')),
  zone: z.string().optional(),
  active: z.boolean().default(true),
  password: z.string().min(6, "Password must be at least 6 characters").optional().or(z.literal('')),
});

async function uploadImage(file: File): Promise<string> {
  const urlRes = await fetch("/api/storage/uploads/request-url", {
    method: "POST",
    headers: { "Content-Type": "application/json" },
    body: JSON.stringify({ name: file.name, size: file.size, contentType: file.type }),
  });
  if (!urlRes.ok) throw new Error("Failed to get upload URL");
  const { uploadURL, objectPath } = await urlRes.json();
  await fetch(uploadURL, { method: "PUT", headers: { "Content-Type": file.type }, body: file });
  return `/api/storage${objectPath}`;
}

export default function Drivers() {
  const { data: drivers, isLoading } = useDrivers();
  const createMutation = useCreateDriver();
  const updateMutation = useUpdateDriver();
  const deleteMutation = useDeleteDriver();
  const { toast } = useToast();

  const defaultDriverValues = { name: "", phone: "", email: "", zone: "", active: true, password: "" };

  const [searchTerm, setSearchTerm] = useState("");
  const [isDialogOpen, setIsDialogOpen] = useState(false);
  const [editDriverId, setEditDriverId] = useState<number | null>(null);
  const [pendingImageUrl, setPendingImageUrl] = useState<string | null>(null);
```

```
  const [previewUrl, setPreviewUrl] = useState<string | null>(null);
  const [imageUploading, setImageUploading] = useState(false);
  const fileInputRef = useRef<HTMLInputElement>(null);

  const form = useForm<z.infer<typeof formSchema>>({
    resolver: zodResolver(formSchema),
    defaultValues: defaultDriverValues,
  });

  const openCreate = () => {
    form.reset(defaultDriverValues);
    setEditDriverId(null);
    setPendingImageUrl(null);
    setPreviewUrl(null);
    setIsDialogOpen(true);
  };

  const openEdit = (driver: any) => {
    form.reset({
      name: driver.name,
      phone: driver.phone || "",
      email: driver.email || "",
      zone: driver.zone || "",
      active: driver.active,
      password: "",
    });
    setEditDriverId(driver.id);
    setPendingImageUrl(driver.imageUrl || null);
    setPreviewUrl(driver.imageUrl || null);
    setIsDialogOpen(true);
  };

  const handleImageSelect = async (e: React.ChangeEvent<HTMLInputElement>) => {
    const file = e.target.files?.[0];
    if (!file) return;
    setPreviewUrl(URL.createObjectURL(file));
    try {
      setImageUploading(true);
      const url = await uploadImage(file);
      setPendingImageUrl(url);
    } catch {
      toast({ title: "Image upload failed", variant: "destructive" });
      setPreviewUrl(null);
      setPendingImageUrl(null);
    } finally {
      setImageUploading(false);
    }
  };

  const onSubmit = (values: z.infer<typeof formSchema>) => {
    const payload = { ...values, imageUrl: pendingImageUrl ?? "" };
    if (editDriverId !== null) {
```

```
    updateMutation.mutate({ id: editDriverId, data: payload }, {
      onSuccess: () => {
        toast({ title: "Driver updated" });
        setIsDialogOpen(false);
        setEditDriverId(null);
      },
      onError: () => toast({ title: "Failed to update driver", variant: "destructive" }),
    });
  } else {
    createMutation.mutate({ data: payload }, {
      onSuccess: () => {
        toast({ title: "Driver added successfully" });
        setIsDialogOpen(false);
        form.reset();
      },
      onError: () => toast({ title: "Failed to add driver", variant: "destructive" }),
    });
  }
};

const filteredDrivers = drivers?.filter(d =>
  d.name.toLowerCase().includes(searchTerm.toLowerCase()) ||
  (d.zone?.toLowerCase().includes(searchTerm.toLowerCase()) ?? false)
);

const getInitials = (name: string) =>
  name.split(" ").map(n => n[0]).slice(0, 2).join("").toUpperCase();

return (
  <div className="space-y-6">
    <div className="flex flex-col sm:flex-row justify-between items-start sm:items-center gap-4">
      <div className="relative w-full sm:w-96">
        <Search className="absolute left-3 top-1/2 -translate-y-1/2 text-slate-400 w-5 h-5" />
        <Input
          placeholder="Search drivers by name or zone..."
          className="pl-10 h-12 bg-white border-slate-200 rounded-xl shadow-sm focus-visible:ring-primary/20"
          value={searchTerm}
          onChange={e => setSearchTerm(e.target.value)}
        />
      </div>

      <Button className="h-12 px-6 rounded-xl bg-primary hover:bg-primary/90 text-white shadow-lg shadow-prima
ry/25 transition-all" onClick={openCreate}>
        <Plus className="w-5 h-5 mr-2" />
        Add Driver
      </Button>

      <Dialog open={isDialogOpen} onOpenChange={(o) => { if (!o) { setIsDialogOpen(false); setEditDriverId(nul
l); } }}>
        <DialogContent className="sm:max-w-[440px] p-6 rounded-3xl">
          <DialogHeader className="mb-2">
            <DialogTitle className="text-2xl font-display text-slate-900">{editDriverId ? "Edit Driver" : "Add
```

```
 New Driver"}</DialogTitle>
          </DialogHeader>

          {/* Photo upload */}
          <div className="flex flex-col items-center gap-2 mb-4">
            <div
              className="relative w-20 h-20 rounded-2xl bg-slate-100 border-2 border-dashed border-slate-300 f
lex items-center justify-center overflow-hidden cursor-pointer hover:border-primary/50 transition-colors"
              onClick={() => fileInputRef.current?.click()}
            >
              {previewUrl ? (
                <img src={previewUrl} alt="Driver" className="w-full h-full object-cover" />
              ) : (
                <span className="text-2xl font-bold text-slate-400">
                  {form.watch("name") ? getInitials(form.watch("name")) : <Camera className="w-7 h-7 text-slat
e-400" />}
                </span>
              )}
              <div className="absolute inset-0 bg-black/30 flex items-center justify-center opacity-0 hover:op
acity-100 transition-opacity">
                {imageUploading ? <Loader2 className="w-5 h-5 text-white animate-spin" /> : <Camera className=
"w-5 h-5 text-white" />}
              </div>
            </div>
            <button
              type="button"
              onClick={() => fileInputRef.current?.click()}
              className="text-xs text-primary hover:underline font-medium"
              disabled={imageUploading}
            >
              {imageUploading ? "Uploading " : previewUrl ? "Change photo" : "Upload photo"}
            </button>
            <input ref={fileInputRef} type="file" accept="image/*" className="hidden" onChange={handleImageSel
ect} />
          </div>

          <Form {...form}>
            <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
              <FormField
                control={form.control}
                name="name"
                render={({ field }) => (
                  <FormItem>
                    <FormLabel>Full Name</FormLabel>
                    <FormControl>
                      <Input placeholder="e.g. John Doe" className="h-11 rounded-xl" {...field} />
                    </FormControl>
                    <FormMessage />
                  </FormItem>
                )}
              />
              <FormField
```

```
                  control={form.control}
                  name="email"
                  render={({ field }) => (
                    <FormItem>
                      <FormLabel>Email (For Login)</FormLabel>
                      <FormControl>
                        <Input placeholder="driver@aces.com" className="h-11 rounded-xl" {...field} />
                      </FormControl>
                      <FormMessage />
                    </FormItem>
                  )}
                />
                <FormField
                  control={form.control}
                  name="password"
                  render={({ field }) => (
                    <FormItem>
                      <FormLabel>Initial Password</FormLabel>
                      <FormControl>
                        <Input type="password" placeholder="******" className="h-11 rounded-xl" {...field} />
                      </FormControl>
                      <FormMessage />
                    </FormItem>
                  )}
                />
                <FormField
                  control={form.control}
                  name="phone"
                  render={({ field }) => (
                    <FormItem>
                      <FormLabel>Phone Number</FormLabel>
                      <FormControl>
                        <Input placeholder="e.g. +966 50 000 0000" className="h-11 rounded-xl" {...field} />
                      </FormControl>
                      <FormMessage />
                    </FormItem>
                  )}
                />
                <FormField
                  control={form.control}
                  name="zone"
                  render={({ field }) => (
                    <FormItem>
                      <FormLabel>Assigned Zone</FormLabel>
                      <FormControl>
                        <select className="w-full h-11 px-3 rounded-xl border border-input bg-background text-sm
" {...field}>
                          <option value="">Select zone...</option>
                          <option value="Central">Central</option>
                          <option value="East">East</option>
                        </select>
                      </FormControl>
```

```
                    <FormMessage />
                  </FormItem>
                )}
              />
              <FormField
                control={form.control}
                name="active"
                render={({ field }) => (
                  <FormItem className="flex flex-row items-center justify-between rounded-xl border border-sla
te-100 p-4 shadow-sm">
                    <div className="space-y-0.5">
                      <FormLabel className="text-base">Active Account</FormLabel>
                      <div className="text-sm text-slate-500">Allow driver to login</div>
                    </div>
                    <FormControl>
                      <Switch checked={field.value} onCheckedChange={field.onChange} />
                    </FormControl>
                  </FormItem>
                )}
              />
              <Button type="submit" className="w-full h-12 rounded-xl mt-2 text-base shadow-lg shadow-primary/
20" disabled={createMutation.isPending || updateMutation.isPending || imageUploading}>
                {(createMutation.isPending || updateMutation.isPending) ? "Saving..." : (editDriverId ? "Updat
e Driver" : "Save Driver")}
              </Button>
            </form>
          </Form>
        </DialogContent>
      </Dialog>
    </div>

    <Card className="glass-panel border-0 shadow-xl shadow-slate-200/50 overflow-hidden">
      <Table>
        <TableHeader className="bg-slate-50 border-b border-slate-100">
          <TableRow className="hover:bg-transparent">
            <TableHead className="font-semibold text-slate-600 h-12">Driver</TableHead>
            <TableHead className="font-semibold text-slate-600">Contact</TableHead>
            <TableHead className="font-semibold text-slate-600">Zone</TableHead>
            <TableHead className="font-semibold text-slate-600">Status</TableHead>
            <TableHead className="text-right font-semibold text-slate-600">Actions</TableHead>
          </TableRow>
        </TableHeader>
        <TableBody>
          {isLoading ? (
            <TableRow>
              <TableCell colSpan={5} className="h-32 text-center text-slate-500">Loading drivers...</TableCell
>
            </TableRow>
          ) : filteredDrivers?.length === 0 ? (
            <TableRow>
              <TableCell colSpan={5} className="h-32 text-center">
                <div className="flex flex-col items-center justify-center text-slate-400">
```

```
                <Users className="w-8 h-8 mb-2 opacity-50" />
                <p>No drivers found</p>
              </div>
            </TableCell>
          </TableRow>
        ) : (
          filteredDrivers?.map((driver) => (
            <TableRow key={driver.id} className="hover:bg-slate-50/50 transition-colors border-slate-50">
              <TableCell>
                <div className="flex items-center gap-3">
                  {(driver as any).imageUrl ? (
                    <img
                      src={(driver as any).imageUrl}
                      alt={driver.name}
                      className="w-9 h-9 rounded-xl object-cover flex-shrink-0"
                    />
                  ) : (
                    <div className="w-9 h-9 rounded-xl bg-primary/10 flex items-center justify-center flex-s
hrink-0">
                      <span className="text-xs font-bold text-primary">{getInitials(driver.name)}</span>
                    </div>
                  )}
                  <span className="font-medium text-slate-900">{driver.name}</span>
                </div>
              </TableCell>
              <TableCell>
                <div className="text-sm text-slate-900">{driver.email || '-'}</div>
                <div className="text-xs text-slate-500">{driver.phone || '-'}</div>
              </TableCell>
              <TableCell className="font-medium text-slate-700">{driver.zone || '-'}</TableCell>
              <TableCell>
                {driver.active ? (
                  <span className="inline-flex items-center gap-1.5 text-emerald-600 bg-emerald-50 px-2.5 py
-1 rounded-lg text-sm font-medium">
                    <CheckCircle2 className="w-4 h-4" /> Active
                  </span>
                ) : (
                  <span className="inline-flex items-center gap-1.5 text-slate-500 bg-slate-100 px-2.5 py-1
rounded-lg text-sm font-medium">
                    <XCircle className="w-4 h-4" /> Inactive
                  </span>
                )}
              </TableCell>
              <TableCell className="text-right">
                <div className="flex items-center justify-end gap-1">
                  <Button
                    variant="ghost"
                    size="icon"
                    className="h-8 w-8 text-slate-400 hover:text-primary hover:bg-primary/10 rounded-lg tran
sition-colors"
                    onClick={() => openEdit(driver)}
                  >
```

```
                      <Pencil className="w-4 h-4" />
                    </Button>
                    <Button
                      variant="ghost"
                      size="icon"
                      className="h-8 w-8 text-slate-400 hover:text-destructive hover:bg-destructive/10 rounded
  -lg transition-colors"
                      onClick={() => {
                        if (confirm('Delete this driver?')) {
                          deleteMutation.mutate({ id: driver.id }, {
                            onSuccess: () => toast({ title: "Deleted" })
                          });
                        }
                      }}
                    >
                      <Trash2 className="w-4 h-4" />
                    </Button>
                  </div>
                </TableCell>
              </TableRow>
            ))
          )}
        </TableBody>
      </Table>
    </Card>
  </div>
 );
}
```

FILE: artifacts/web-portal/src/pages/admin/Login.tsx
SIZE: 26,498 bytes

```
import { useState } from "react";
import { useAuth } from "@/lib/auth-context";
import { Input } from "@/components/ui/input";
import { Button } from "@/components/ui/button";
import { Card, CardContent } from "@/components/ui/card";
import { Lock, Mail, Loader2, ArrowRight } from "lucide-react";
import { useAdminLogin } from "@workspace/api-client-react";
import { useLocation } from "wouter";

const WIN_ROWS = [0, 1, 2, 3, 4, 5, 6, 7];
const WIN_COLS_3 = [0, 1, 2];
const WIN_COLS_4 = [0, 1, 2, 3];
const WIN_COLS_7 = [0, 1, 2, 3, 4, 5, 6];
const BRACE_ROWS = [230, 290, 350, 410, 470, 530, 590, 650, 710, 770, 830, 890];
const BRACE_DIAG = [230, 290, 350, 410, 470, 530, 590, 650, 710, 770, 830];
const SIGNAL_RADII = [40, 70, 100, 130];
const RING_RADII = [160, 220, 280];
const ROAD_MARKS = [100,200,300,400,500,600,700,800,900,1000,1100,1200,1300];
const NET_LINES: [number,number,number,number][] = [
  [590, 190, 1300, 165],
  [840, 110, 1300, 165],
  [355, 306, 1300, 165],
];

function RiyadhBackground() {
  return (
    <svg viewBox="-80 -80 1600 1060" preserveAspectRatio="xMidYMid slice" xmlns="http://www.w3.org/2000/svg" cla
  ssName="absolute inset-0 w-full h-full">
      <defs>
        <linearGradient id="skyGrad" x1="0" y1="0" x2="0" y2="1">
          <stop offset="0%" stopColor="#dbeafe" />
          <stop offset="45%" stopColor="#eff6ff" />
          <stop offset="100%" stopColor="#f0f9ff" />
        </linearGradient>
        <linearGradient id="groundGrad" x1="0" y1="0" x2="0" y2="1">
          <stop offset="0%" stopColor="#e2e8f0" />
          <stop offset="100%" stopColor="#cbd5e1" />
        </linearGradient>
        <radialGradient id="towerGlow" cx="50%" cy="50%" r="50%">
          <stop offset="0%" stopColor="#E30613" stopOpacity="0.12" />
          <stop offset="100%" stopColor="#E30613" stopOpacity="0" />
        </radialGradient>
        <radialGradient id="cityGlow" cx="50%" cy="30%" r="60%">
          <stop offset="0%" stopColor="#bfdbfe" stopOpacity="0.5" />
          <stop offset="100%" stopColor="#eff6ff" stopOpacity="0" />
        </radialGradient>
        <filter id="blur4"><feGaussianBlur stdDeviation="4" /></filter>
        <filter id="glow">
          <feGaussianBlur stdDeviation="3" result="blur" />
```

```
    <feMerge><feMergeNode in="blur" /><feMergeNode in="SourceGraphic" /></feMerge>
  </filter>
</defs>

{/* Sky */}
<rect x="-100" y="-100" width="1700" height="1200" fill="url(#skyGrad)" />
<ellipse cx="720" cy="680" rx="700" ry="200" fill="url(#cityGlow)" />

{/* Sun */}
<circle cx="200" cy="120" r="55" fill="#fef08a" opacity="0.7" filter="url(#blur4)" />
<circle cx="200" cy="120" r="38" fill="#fde047" opacity="0.55" />

{/* Clouds */}
<ellipse cx="380" cy="90" rx="90" ry="32" fill="white" opacity="0.85" />
<ellipse cx="420" cy="78" rx="65" ry="26" fill="white" opacity="0.9" />
<ellipse cx="340" cy="95" rx="55" ry="22" fill="white" opacity="0.8" />
<ellipse cx="900" cy="60" rx="80" ry="28" fill="white" opacity="0.75" />
<ellipse cx="940" cy="50" rx="55" ry="22" fill="white" opacity="0.8" />
<ellipse cx="1200" cy="100" rx="70" ry="24" fill="white" opacity="0.7" />
<ellipse cx="1240" cy="90" rx="50" ry="20" fill="white" opacity="0.75" />

{/* Ground */}
<rect x="-100" y="760" width="1700" height="300" fill="url(#groundGrad)" />
<rect x="-100" y="758" width="1700" height="3" fill="#94a3b8" opacity="0.4" />
{ROAD_MARKS.map((x, i) => (
  <rect key={i} x={x} y="800" width="60" height="4" rx="2" fill="#94a3b8" opacity="0.25" />
))}

{/* ?????? Al-Masjid an-Nabawi   Prophet's Mosque, Madinah ?????? */}

{/* ?? Mosque main body ?? */}
<rect x="10" y="692" width="400" height="68" fill="#e6ecf5" />
{/* Stepped roofline */}
<rect x="10" y="682" width="400" height="12" fill="#dde4ef" />

{/* Front arched arcade */}
{[0,1,2,3,4,5,6,7,8,9].map(i => (
  <path key={`nb${i}`}
    d={`M ${14+i*38} 760 L ${14+i*38} 732 Q ${33+i*38} 716 ${52+i*38} 732 L ${52+i*38} 760`}
    fill="#cdd7eb" />
))}

{/* ?? Green Dome (iconic, over Prophet's tomb) ?? */}
<ellipse cx="205" cy="678" rx="58" ry="32" fill="#6db98a" opacity="0.7" />
<ellipse cx="205" cy="675" rx="46" ry="26" fill="#7ec89a" opacity="0.8" />
<ellipse cx="205" cy="673" rx="34" ry="18" fill="#8fd4a8" opacity="0.85" />
{/* Drum base of dome */}
<rect x="163" y="678" width="84" height="14" fill="#c5d5e8" />
{/* Gold finial + crescent */}
<rect x="202" y="648" width="6" height="26" rx="2" fill="#c9a227" opacity="0.85" />
<path d="M197 647 Q205 634 213 647 Q205 640 197 647" fill="#c9a227" opacity="0.95" />
<circle cx="205" cy="631" r="3" fill="#c9a227" opacity="0.8" />
```

```
{/* ?? Secondary domes along roofline ?? */}
<ellipse cx="125" cy="688" rx="30" ry="17" fill="#dde6f0" />
<ellipse cx="285" cy="688" rx="30" ry="17" fill="#dde6f0" />
<ellipse cx="60" cy="694" rx="20" ry="13" fill="#e2e8f0" />
<ellipse cx="350" cy="694" rx="20" ry="13" fill="#e2e8f0" />
<ellipse cx="22" cy="698" rx="13" ry="9" fill="#e8edf5" />
<ellipse cx="392" cy="698" rx="13" ry="9" fill="#e8edf5" />

{/* ?? Outer tall minarets (pencil-shaped) ?? */}
{/* Far left */}
<rect x="14" y="558" width="13" height="202" fill="#dde4ef" />
<rect x="15" y="558" width="11" height="202" fill="#e4eaf5" />
<polygon points="14,558 20.5,536 27,558" fill="#cdd5e8" />
<circle cx="20" cy="532" r="4.5" fill="#c9a227" opacity="0.7" />
<ellipse cx="20" cy="537" rx="7" ry="4" fill="#d6dfee" />
{/* Far right */}
<rect x="393" y="558" width="13" height="202" fill="#dde4ef" />
<rect x="394" y="558" width="11" height="202" fill="#e4eaf5" />
<polygon points="393,558 399.5,536 406,558" fill="#cdd5e8" />
<circle cx="400" cy="532" r="4.5" fill="#c9a227" opacity="0.7" />
<ellipse cx="400" cy="537" rx="7" ry="4" fill="#d6dfee" />

{/* ?? Inner minarets ?? */}
{/* Left inner */}
<rect x="78" y="592" width="11" height="168" fill="#e2e8f0" />
<polygon points="78,592 83.5,578 89,592" fill="#d8e2f0" />
<circle cx="83" cy="574" r="3.5" fill="#c9a227" opacity="0.65" />
{/* Right inner */}
<rect x="331" y="592" width="11" height="168" fill="#e2e8f0" />
<polygon points="331,592 336.5,578 342,592" fill="#d8e2f0" />
<circle cx="336" cy="574" r="3.5" fill="#c9a227" opacity="0.65" />
{/* Centre-left */}
<rect x="148" y="610" width="9" height="150" fill="#e4eaf5" />
<polygon points="148,610 152.5,599 157,610" fill="#dde6f0" />
<circle cx="152" cy="596" r="3" fill="#c9a227" opacity="0.6" />
{/* Centre-right */}
<rect x="263" y="610" width="9" height="150" fill="#e4eaf5" />
<polygon points="263,610 267.5,599 272,610" fill="#dde6f0" />
<circle cx="267" cy="596" r="3" fill="#c9a227" opacity="0.6" />

{/* ?? Retractable umbrella shades (iconic courtyard feature) ?? */}
{[0,1,2,3].map(i => (
  <g key={`umb${i}`}>
    <line x1={68+i*80} y1="692" x2={68+i*80} y2="668" stroke="#94a3b8" strokeWidth="2" opacity="0.4" />
    <path d={`M ${32+i*80} 668 Q ${68+i*80} 652 ${104+i*80} 668`}
      fill="#d4dff0" opacity="0.65" />
    <line x1={32+i*80} y1="668" x2={104+i*80} y2="668"
      stroke="#b8c8de" strokeWidth="1" opacity="0.5" />
  </g>
))}
```

```
    {/* ?? Masjid al-Haram (Holy Mosque) ?? */}
    {/* Mosque outer body */}
    <rect x="435" y="698" width="310" height="62" fill="#e4eaf5" />
    {/* Arched arcade along front */}
    {[0,1,2,3,4,5,6,7].map(i => (
      <path key={`ma${i}`} d={`M ${441+i*36} 760 L ${441+i*36} 735 Q ${459+i*36} 720 ${477+i*36} 735 L ${477+i
*36} 760`}
        fill="#d0d9ed" />
    ))}
    {/* Central large dome */}
    <ellipse cx="590" cy="696" rx="54" ry="27" fill="#dde4ef" />
    <ellipse cx="590" cy="694" rx="42" ry="21" fill="#e6ecf7" />
    <path d="M584 669 Q590 659 596 669 Q590 663 584 669" fill="#c9a227" opacity="0.75" />
    {/* Secondary side domes */}
    <ellipse cx="507" cy="704" rx="32" ry="19" fill="#dde4ef" />
    <ellipse cx="673" cy="704" rx="32" ry="19" fill="#dde4ef" />
    <ellipse cx="455" cy="710" rx="20" ry="13" fill="#e2e8f0" />
    <ellipse cx="725" cy="710" rx="20" ry="13" fill="#e2e8f0" />
    {/* Outer tall minarets */}
    <rect x="435" y="642" width="12" height="118" fill="#dde4ef" />
    <path d="M435 642 L441 626 L447 642 Z" fill="#cbd5e1" />
    <circle cx="441" cy="622" r="3.5" fill="#c9a227" opacity="0.65" />
    <rect x="733" y="642" width="12" height="118" fill="#dde4ef" />
    <path d="M733 642 L739 626 L745 642 Z" fill="#cbd5e1" />
    <circle cx="739" cy="622" r="3.5" fill="#c9a227" opacity="0.65" />
    {/* Inner minarets */}
    <rect x="475" y="656" width="10" height="104" fill="#e2e8f0" />
    <path d="M475 656 L480 644 L485 656 Z" fill="#dde4ef" />
    <rect x="695" y="656" width="10" height="104" fill="#e2e8f0" />
    <path d="M695 656 L700 644 L705 656 Z" fill="#dde4ef" />

    {/* ?? Abraj Al-Bait (Makkah Clock Tower)   moved to far right near Kaaba ?? */}
    <g transform="translate(780, 0)">
      {/* Podium base */}
      <rect x="516" y="598" width="148" height="162" fill="#dde4ef" />
      {[0,1,2,3].map(r => [0,1,2,3].map(c => (
        <rect key={`pod${r}${c}`} x={522+c*34} y={606+r*36} width="24" height="22" rx="1" fill="#bfdbfe" opaci
ty="0.5" />
      )))}
      {/* Flanking hotel towers */}
      <rect x="491" y="522" width="32" height="238" fill="#e2e8f0" />
      <rect x="657" y="522" width="32" height="238" fill="#e2e8f0" />
      {[0,1,2,3,4,5].map(r => (
        <g key={`ht${r}`}>
          <rect x={495} y={530+r*36} width="22" height="22" rx="1" fill="#bfdbfe" opacity="0.5" />
          <rect x={661} y={530+r*36} width="22" height="22" rx="1" fill="#bfdbfe" opacity="0.5" />
        </g>
      ))}
      {/* Main clock tower shaft */}
      <rect x="557" y="190" width="66" height="410" fill="#e2e8f0" />
      <rect x="563" y="190" width="54" height="410" fill="#e8eef8" />
      {[0,1,2,3,4,5,6,7,8,9].map(r => (
```

```
        <g key={`cw${r}`}>
          <rect x={566} y={198+r*38} width="18" height="24" rx="1" fill="#bfdbfe" opacity="0.55" />
          <rect x={596} y={198+r*38} width="18" height="24" rx="1" fill="#bfdbfe" opacity="0.55" />
        </g>
      ))}
      {/* Crown battlements   drawn first so clock face renders on top */}
      <rect x="554" y="96" width="72" height="44" fill="#dde4ef" />
      {[0,1,2,3,4].map(i => (
        <rect key={`bat${i}`} x={554+i*14} y={84} width="10" height="14" rx="1" fill="#dde4ef" />
      ))}
      {/* Golden spire */}
      <rect x="587" y="64" width="6" height="22" rx="2" fill="#c9a227" opacity="0.65" />
      {/* Crescent */}
      <path d="M582 63 Q590 50 598 63 Q591 56 582 63" fill="#c9a227" opacity="0.85" />
      <circle cx="590" cy="47" r="3.5" fill="#E30613" opacity="0.85" filter="url(#glow)" />
      {/* Clock head   wide section */}
      <rect x="533" y="138" width="114" height="54" fill="#dde4ef" rx="2" />
      <rect x="537" y="142" width="106" height="46" fill="#e4eaf5" rx="2" />
      <rect x="533" y="188" width="114" height="5" fill="#c9a227" opacity="0.5" />
      {/* Clock face */}
      <circle cx="590" cy="165" r="42" fill="white" opacity="0.88" />
      <circle cx="590" cy="165" r="39" fill="#f5f8ff" />
      <circle cx="590" cy="165" r="35" fill="none" stroke="#1e3a6e" strokeWidth="2" opacity="0.3" />
      {[0,1,2,3,4,5,6,7,8,9,10,11].map(i => {
        const angle = (i * 30 - 90) * Math.PI / 180;
        const r1 = 30, r2 = i % 3 === 0 ? 23 : 27;
        return (
          <line key={`ctick${i}`}
            x1={590+r1*Math.cos(angle)} y1={165+r1*Math.sin(angle)}
            x2={590+r2*Math.cos(angle)} y2={165+r2*Math.sin(angle)}
            stroke="#1e3a6e" strokeWidth={i % 3 === 0 ? 2.5 : 1.2} opacity="0.4" />
        );
      })}
      <line x1="590" y1="165" x2="590" y2="145" stroke="#1e3a6e" strokeWidth="3" strokeLinecap="round" opacity
="0.5" />
      <line x1="590" y1="165" x2="610" y2="170" stroke="#E30613" strokeWidth="2.5" strokeLinecap="round" opaci
ty="0.6" />
      <circle cx="590" cy="165" r="3.5" fill="#1e3a6e" opacity="0.5" />
    </g>

    {/* ?? Riyadh Tower (tallest) ?? */}
    <rect x="800" y="202" width="80" height="558" fill="#dde6f0" />
    <line x1="835" y1="202" x2="835" y2="760" stroke="#94a3b8" strokeWidth="2" opacity="0.4" />
    <line x1="850" y1="202" x2="850" y2="760" stroke="#94a3b8" strokeWidth="2" opacity="0.4" />
    {[0,1,2,3,4,5,6,7,8,9,10,11].map(r => [0,1].map(c => (
      <rect key={`h${r}${c}`} x={810+c*32} y={212+r*45} width="22" height="28" rx="2" fill="#bfdbfe" opacity="
0.6" />
    )))}
    <rect x="812" y="182" width="56" height="22" fill="#e2e8f0" />
    <rect x="820" y="164" width="40" height="20" fill="#e2e8f0" />
    <rect x="827" y="150" width="26" height="16" fill="#dde6f0" />
    <line x1="840" y1="150" x2="840" y2="112" stroke="#94a3b8" strokeWidth="3" />
```

```
    <circle cx="840" cy="110" r="5" fill="#E30613" opacity="0.8" filter="url(#glow)" />

    {/* ?????? Masjid al-Haram + Holy Kaaba   Makkah (right side) ?????? */}

    {/* ?? Mosque outer body ?? */}
    <rect x="1155" y="693" width="285" height="67" fill="#e6ecf5" />
    <rect x="1155" y="683" width="285" height="12" fill="#dde4ef" />

    {/* Front arched arcade */}
    {[0,1,2,3,4,5,6,7].map(i => (
      <path key={`hka${i}`}
        d={`M ${1161+i*34} 760 L ${1161+i*34} 733 Q ${1178+i*34} 717 ${1195+i*34} 733 L ${1195+i*34} 760`}
        fill="#cdd7eb" />
    ))}

    {/* ?? Minarets of Masjid al-Haram ?? */}
    {/* Far left */}
    <rect x="1153" y="558" width="13" height="202" fill="#dde4ef" />
    <rect x="1154" y="558" width="11" height="202" fill="#e4eaf5" />
    <polygon points="1153,558 1159.5,536 1166,558" fill="#cdd5e8" />
    <circle cx="1160" cy="532" r="4.5" fill="#c9a227" opacity="0.7" />
    <ellipse cx="1160" cy="537" rx="7" ry="3.5" fill="#d6dfee" />
    {/* Centre-left */}
    <rect x="1223" y="590" width="11" height="170" fill="#e2e8f0" />
    <polygon points="1223,590 1228.5,577 1234,590" fill="#d8e2f0" />
    <circle cx="1229" cy="573" r="3.5" fill="#c9a227" opacity="0.65" />
    {/* Centre-right */}
    <rect x="1340" y="590" width="11" height="170" fill="#e2e8f0" />
    <polygon points="1340,590 1345.5,577 1351,590" fill="#d8e2f0" />
    <circle cx="1346" cy="573" r="3.5" fill="#c9a227" opacity="0.65" />
    {/* Far right */}
    <rect x="1422" y="558" width="13" height="202" fill="#dde4ef" />
    <rect x="1423" y="558" width="11" height="202" fill="#e4eaf5" />
    <polygon points="1422,558 1428.5,536 1435,558" fill="#cdd5e8" />
    <circle cx="1429" cy="532" r="4.5" fill="#c9a227" opacity="0.7" />
    <ellipse cx="1429" cy="537" rx="7" ry="3.5" fill="#d6dfee" />

    {/* ?? Domes along roofline ?? */}
    <ellipse cx="1270" cy="686" rx="30" ry="17" fill="#dde6f0" />
    <ellipse cx="1380" cy="686" rx="30" ry="17" fill="#dde6f0" />
    <ellipse cx="1193" cy="693" rx="20" ry="13" fill="#e2e8f0" />
    <ellipse cx="1438" cy="693" rx="20" ry="13" fill="#e2e8f0" />

    {/* ?? Marble Mataf (circumambulation courtyard) ?? */}
    <ellipse cx="1315" cy="722" rx="82" ry="38" fill="#f0f4f8" opacity="0.85" />
    <ellipse cx="1315" cy="720" rx="68" ry="31" fill="#f5f8fb" opacity="0.9" />
    <ellipse cx="1315" cy="720" rx="65" ry="28" fill="none" stroke="#c8d4e4" strokeWidth="1.2" opacity="0.55"
/>
    <ellipse cx="1315" cy="720" rx="52" ry="22" fill="none" stroke="#c8d4e4" strokeWidth="0.8" opacity="0.4" /
>

    {/* ?? The Holy Kaaba   centered in Mataf ?? */}
```

```
    {/* Kaaba center target: x=1315, bottom?y=718 (sitting on courtyard floor) */}
    {/* Front face: w=32, h=36 ? x=1299..1331, y=682..718 */}
    {/* Top offset: 10 right, 10 up ? top-left=(1299,682), top-right=(1331,682), TR+off=(1341,672), TL+off=(13
09,672) */}
    {/* Right face: (1331,682)?(1331,718)?(1341,708)?(1341,672) */}

    {/* Cube shadow on courtyard */}
    <ellipse cx="1315" cy="719" rx="22" ry="6" fill="#475569" opacity="0.18" />

    {/* Top face   lightest gray */}
    <polygon points="1299,682 1331,682 1341,672 1309,672" fill="#94a3b8" />
    {/* Front face   medium gray */}
    <rect x="1299" y="682" width="32" height="36" fill="#64748b" />
    {/* Right side face   darkest gray */}
    <polygon points="1331,682 1331,718 1341,708 1341,672" fill="#475569" />

    {/* Kiswa band on front face */}
    <rect x="1299" y="689" width="32" height="6" fill="#374151" />
    <rect x="1299" y="688" width="32" height="1.5" fill="#2d3748" opacity="0.7" />
    <rect x="1299" y="695" width="32" height="1.5" fill="#2d3748" opacity="0.7" />
    {/* Kiswa band on right face (perspective) */}
    <polygon points="1331,689 1341,679 1341,681 1331,691" fill="#2d3748" opacity="0.5" />
    <polygon points="1331,695 1341,685 1341,687 1331,697" fill="#2d3748" opacity="0.5" />

    {/* Door   bottom-center of front face (y=704..718) */}
    <rect x="1310" y="704" width="9" height="14" rx="1" fill="#4b5563" />
    <rect x="1311" y="705" width="7" height="12" rx="1" fill="#374151" />
    {/* Door arch at top of door */}
    <path d="M1310 705 Q1314.5 701 1319 705" fill="none" stroke="#4b5563" strokeWidth="1" />

    {/* Face edge highlights */}
    <polygon points="1299,682 1331,682 1341,672 1309,672" fill="none" stroke="#b0bec8" strokeWidth="0.8" opaci
ty="0.6" />
    <rect x="1299" y="682" width="32" height="36" fill="none" stroke="#6b7a8a" strokeWidth="0.8" />
    <polygon points="1331,682 1331,718 1341,708 1341,672" fill="none" stroke="#3d4f60" strokeWidth="0.8" />

    {/* ?????? GSM TOWER ?????? */}
    <ellipse cx="1100" cy="520" rx="140" ry="140" fill="url(#towerGlow)" filter="url(#blur4)" />

    {/* Lattice legs */}
    <line x1="1100" y1="200" x2="1027" y2="900" stroke="#94a3b8" strokeWidth="5" strokeLinecap="round" />
    <line x1="1100" y1="200" x2="1173" y2="900" stroke="#94a3b8" strokeWidth="5" strokeLinecap="round" />
    <line x1="1100" y1="200" x2="1100" y2="900" stroke="#94a3b8" strokeWidth="3" />

    {/* Horizontal braces */}
    {BRACE_ROWS.map((y, i) => {
      const sp = 6 + i * 6;
      return <line key={y} x1={1100-sp} y1={y} x2={1100+sp} y2={y} stroke="#94a3b8" strokeWidth="3" opacity="0
.7" />;
    })}

    {/* Diagonal braces */}
```

```
{BRACE_DIAG.map((y, i) => {
  const s1 = 6 + i * 6;
  const s2 = 6 + (i+1) * 6;
  return (
    <g key={y}>
      <line x1={1100-s1} y1={y} x2={1100+s2} y2={y+60} stroke="#94a3b8" strokeWidth="2" opacity="0.5" />
      <line x1={1100+s1} y1={y} x2={1100-s2} y2={y+60} stroke="#94a3b8" strokeWidth="2" opacity="0.5" />
    </g>
  );
})}

{/* Platform */}
<ellipse cx="1100" cy="212" rx="28" ry="8" fill="#94a3b8" />
<rect x="1072" y="206" width="56" height="10" rx="3" fill="#94a3b8" />

{/* Antenna mast */}
<rect x="1094" y="142" width="12" height="70" rx="3" fill="#94a3b8" />

{/* Side arms */}
<rect x="1056" y="167" width="44" height="8" rx="2" fill="#94a3b8" />
<rect x="1056" y="167" width="8" height="25" rx="2" fill="#cbd5e1" />
<rect x="1100" y="167" width="44" height="8" rx="2" fill="#94a3b8" />
<rect x="1136" y="167" width="8" height="25" rx="2" fill="#cbd5e1" />
<rect x="1058" y="177" width="6" height="30" rx="2" fill="#94a3b8" />
<rect x="1136" y="177" width="6" height="30" rx="2" fill="#94a3b8" />

{/* Top beacon */}
<circle cx="1100" cy="137" r="5" fill="#E30613" opacity="0.85" filter="url(#glow)" />
<circle cx="1100" cy="137" r="12" fill="#E30613" opacity="0.1" />

{/* Signal arcs   left */}
{SIGNAL_RADII.map((r, i) => (
  <path key={`sl${i}`}
    d={`M ${1100-r} 167 A ${r} ${r} 0 0 1 ${1100} ${167-r}`}
    fill="none" stroke="#E30613"
    strokeWidth={1.5 - i * 0.25}
    opacity={0.35 - i * 0.07}
    strokeDasharray={i % 2 === 0 ? undefined : "6 4"}
  />
))}
{/* Signal arcs   right */}
{SIGNAL_RADII.map((r, i) => (
  <path key={`sr${i}`}
    d={`M ${1100+r} 167 A ${r} ${r} 0 0 0 ${1100} ${167-r}`}
    fill="none" stroke="#E30613"
    strokeWidth={1.5 - i * 0.25}
    opacity={0.35 - i * 0.07}
    strokeDasharray={i % 2 === 0 ? undefined : "6 4"}
  />
))}
{/* Full signal rings */}
{RING_RADII.map((r, i) => (
```

```
        <circle key={`rr${i}`} cx="1100" cy="167" r={r}
          fill="none" stroke="#E30613" strokeWidth="0.8" opacity={0.08 - i * 0.02} />
      ))}

      {/* GSM label */}
      <text x="1100" y="718" textAnchor="middle" fill="#94a3b8" fontSize="11" fontFamily="monospace" fontWeight=
  "bold" letterSpacing="4" opacity="0.55">GSM</text>

      {/* Network connection lines from buildings to tower */}
      {NET_LINES.map(([x1,y1,x2,y2], i) => (
        <line key={i} x1={x1} y1={y1} x2={x2} y2={y2}
          stroke="#E30613" strokeWidth="0.8" opacity="0.1" strokeDasharray="8 6" />
      ))}
    </svg>
  );
}

export default function Login() {
  const { loginAdmin } = useAuth();
  const [, setLocation] = useLocation();
  const [username, setUsername] = useState("");
  const [password, setPassword] = useState("");
  const [error, setError] = useState("");

  const loginMutation = useAdminLogin();

  const handleLogin = (e: React.FormEvent) => {
    e.preventDefault();
    setError("");
    loginMutation.mutate({ data: { username, password } }, {
      onSuccess: (data) => {
        if (data.success) {
          loginAdmin(data.username || username, data.role || "superadmin", data.region || "");
          setLocation("/");
        } else {
          setError("Invalid credentials");
        }
      },
      onError: () => {
        setError("Invalid credentials. Please check your username and password.");
      }
    });
  };

  return (
    <div className="min-h-screen w-full flex relative overflow-hidden bg-[#eff6ff]">
      {/* SVG illustrated background */}
      <div className="absolute inset-0 z-0">
        <RiyadhBackground />
      </div>

      {/* Subtle gradient overlay */}
```

```
    <div className="absolute inset-0 z-0 bg-gradient-to-r from-white/60 via-white/30 to-transparent pointer-ev
ents-none" />

    <div className="relative z-10 w-full flex flex-col items-center justify-center px-6">
      <div className="mb-8 flex justify-center">
        <img
          src={`${import.meta.env.BASE_URL}images/aces-logo.png`}
          alt="ACES Logo"
          className="h-36 object-contain drop-shadow-md"
        />
      </div>

      <Card
        className="border border-slate-200 shadow-xl rounded-3xl p-2 w-full max-w-md backdrop-blur-xl bg-white
/90"
      >
        <CardContent className="p-8">
          <h1 className="text-3xl font-display font-bold text-slate-800 mb-2">Welcome Back</h1>
          <p className="text-slate-500 mb-8">Sign in to the ACES-MSD Fueling Web Portal.</p>

          <form onSubmit={handleLogin} className="space-y-5" autoComplete="off">
            {error && (
              <div className="bg-red-50 text-red-600 px-4 py-3 rounded-xl text-sm font-medium border border-re
d-200">
                {error}
              </div>
            )}

            <div className="space-y-1.5">
              <label className="text-sm font-semibold text-slate-600 ml-1">Username</label>
              <div className="relative">
                <Mail className="absolute left-4 top-1/2 -translate-y-1/2 w-5 h-5 text-slate-400" />
                <Input
                  value={username}
                  onChange={(e) => setUsername(e.target.value)}
                  autoComplete="off"
                  className="pl-12 h-14 rounded-xl bg-slate-50 border-slate-200 text-slate-800 placeholder:tex
t-slate-400 focus-visible:ring-red-400/40 focus-visible:bg-white transition-all text-base"
                  placeholder="Enter username"
                />
              </div>
            </div>

            <div className="space-y-1.5">
              <label className="text-sm font-semibold text-slate-600 ml-1">Password</label>
              <div className="relative">
                <Lock className="absolute left-4 top-1/2 -translate-y-1/2 w-5 h-5 text-slate-400" />
                <Input
                  type="password"
                  value={password}
                  onChange={(e) => setPassword(e.target.value)}
                  autoComplete="new-password"
```

```
                  className="pl-12 h-14 rounded-xl bg-slate-50 border-slate-200 text-slate-800 placeholder:tex
  t-slate-400 focus-visible:ring-red-400/40 focus-visible:bg-white transition-all text-base"
                  placeholder="        "
                />
              </div>
            </div>

            <div className="pt-2">
              <Button
                type="submit"
                disabled={loginMutation.isPending}
                className="w-full h-14 rounded-xl bg-[#E30613] hover:bg-[#c50511] text-white font-bold text-lg
   shadow-md shadow-red-200 transition-all group"
              >
                {loginMutation.isPending ? (
                  <Loader2 className="w-6 h-6 animate-spin" />
                ) : (
                  <>
                    Sign In to Portal
                    <ArrowRight className="w-5 h-5 ml-2 group-hover:translate-x-1 transition-transform" />
                  </>
                )}
              </Button>
            </div>
          </form>
        </CardContent>
      </Card>
    </div>
  </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/admin/Missions.tsx
SIZE: 24,915 bytes

```
import { useState } from "react";
import { useMissions, useCreateMission, useUpdateMission, useDeleteMission } from "@/hooks/use-missions";
import { Card, CardContent } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from "@/components/ui/table";
import { Badge } from "@/components/ui/badge";
import { Dialog, DialogContent, DialogHeader, DialogTitle } from "@/components/ui/dialog";
import { Sheet, SheetContent, SheetHeader, SheetTitle } from "@/components/ui/sheet";
import { Separator } from "@/components/ui/separator";
import { ScrollArea } from "@/components/ui/scroll-area";
import { Plus, Search, Trash2, FileText, Eye, CheckCircle, XCircle, RotateCcw, Camera, Droplet, Pencil } from "l
  ucide-react";
import { useAuth } from "@/lib/auth-context";
import { useForm } from "react-hook-form";
import { zodResolver } from "@hookform/resolvers/zod";
import * as z from "zod";
import { Form, FormControl, FormField, FormItem, FormLabel, FormMessage } from "@/components/ui/form";
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
import { useToast } from "@/hooks/use-toast";
import { useQuery, useQueryClient } from "@tanstack/react-query";
import { getListMissionsQueryKey } from "@workspace/api-client-react";

interface Driver { id: number; name: string; }

function useDrivers() {
  return useQuery<Driver[]>({
    queryKey: ["drivers"],
    queryFn: async () => {
      const res = await fetch(`${apiBase}/api/drivers`);
      if (!res.ok) return [];
      return res.json();
    },
  });
}

const statusColors: Record<string, string> = {
  "Creation": "bg-orange-100 text-orange-700 hover:bg-orange-200",
  "Finished by Driver": "bg-sky-100 text-sky-700 hover:bg-sky-200",
  "Task approved": "bg-emerald-100 text-emerald-700 hover:bg-emerald-200",
  "Reported by driver": "bg-rose-100 text-rose-700 hover:bg-rose-200",
  "Canceled": "bg-slate-100 text-slate-700 hover:bg-slate-200"
};

const formSchema = z.object({
  siteName: z.string().min(1, "Site name is required"),
  generator: z.string().optional(),
  project: z.string().optional(),
  missionStatus: z.string().min(1, "Status is required"),
```

```
  driverName: z.string().optional(),
  filledLiters: z.coerce.number().optional(),
});

const apiBase = import.meta.env.BASE_URL.replace(/\/$/, "");

interface DriverEntry {
  missionId: number;
  missionRef: string;
  siteName: string;
  driverName: string;
  litersBefore: number | null;
  litersAdded: number | null;
  completionDate: string | null;
  notes: string | null;
  odoBeforePhoto: string | null;
  odoAfterPhoto: string | null;
  tankBeforePhoto: string | null;
  tankAfterPhoto: string | null;
  submittedAt: string | null;
}

function PhotoThumb({ src, label, icon }: { src: string | null; label: string; icon: React.ReactNode }) {
  if (!src) {
    return (
      <div className="flex flex-col items-center gap-2">
        <div className="w-full h-32 rounded-xl bg-slate-100 border-2 border-dashed border-slate-200 flex flex-co
  l items-center justify-center gap-1.5">
          <div className="text-slate-300">{icon}</div>
          <span className="text-xs text-slate-400">No photo</span>
        </div>
        <span className="text-xs font-medium text-slate-500">{label}</span>
      </div>
    );
  }
  return (
    <div className="flex flex-col items-center gap-2">
      <img
        src={src}
        alt={label}
        className="w-full h-32 object-cover rounded-xl border border-slate-200 cursor-zoom-in"
        onClick={() => window.open(src, "_blank")}
        title="Click to view full size"
      />
      <span className="text-xs font-medium text-slate-500">{label}</span>
    </div>
  );
}

function MissionReviewSheet({
  missionId,
  missionRef,
```

```
  open,
  onClose,
}: {
  missionId: number | null;
  missionRef: string;
  open: boolean;
  onClose: () => void;
}) {
  const queryClient = useQueryClient();
  const { toast } = useToast();
  const [acting, setActing] = useState<"approve" | "reject" | "send-back" | null>(null);

  const { data: entry, isLoading } = useQuery<DriverEntry>({
    queryKey: ["mission-entry", missionId],
    queryFn: async () => {
      const res = await fetch(`${apiBase}/api/missions/${missionId}/entry`);
      if (!res.ok) throw new Error("Failed to load");
      return res.json();
    },
    enabled: !!missionId && open,
  });

  const doAction = async (action: "approve" | "reject" | "send-back") => {
    if (!missionId) return;
    setActing(action);
    try {
      const res = await fetch(`${apiBase}/api/missions/${missionId}/${action}`, {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({ approvedBy: "Admin" }),
      });
      if (!res.ok) throw new Error("Action failed");
      const labels: Record<string, string> = {
        approve: "Mission approved and added to report",
        reject: "Mission rejected",
        "send-back": "Mission sent back to driver",
      };
      toast({ title: labels[action] });
      queryClient.invalidateQueries({ queryKey: getListMissionsQueryKey() });
      queryClient.invalidateQueries({ queryKey: ["report-lines"] });
      onClose();
    } catch {
      toast({ title: "Action failed. Please try again.", variant: "destructive" });
    } finally {
      setActing(null);
    }
  };

  return (
    <Sheet open={open} onOpenChange={(v) => !v && onClose()}>
      <SheetContent side="right" className="w-full sm:max-w-2xl p-0 flex flex-col">
        <SheetHeader className="px-6 pt-6 pb-4 border-b border-slate-100">
```

```
          <SheetTitle className="text-xl font-bold text-slate-900">
            Driver Submission Review
          </SheetTitle>
          <p className="text-sm text-slate-500 mt-0.5">{missionRef}</p>
        </SheetHeader>

        <ScrollArea className="flex-1">
          <div className="px-6 py-5 space-y-6">
            {isLoading ? (
              <div className="flex items-center justify-center h-48 text-slate-400">
                Loading submission...
              </div>
            ) : !entry ? (
              <div className="flex flex-col items-center justify-center h-48 gap-3 text-slate-400">
                <FileText className="w-8 h-8 opacity-50" />
                <p className="text-sm">No driver submission found for this mission.</p>
              </div>
            ) : (
              <>
                {/* Driver info + entries */}
                <div className="bg-slate-50 rounded-2xl p-4 space-y-3">
                  <h3 className="text-sm font-bold text-slate-700 uppercase tracking-wider">Driver Details</h3>
                  <div className="grid grid-cols-2 gap-x-6 gap-y-2">
                    <div>
                      <p className="text-xs text-slate-500">Driver</p>
                      <p className="text-sm font-semibold text-slate-900">{entry.driverName || " "}</p>
                    </div>
                    <div>
                      <p className="text-xs text-slate-500">Site</p>
                      <p className="text-sm font-semibold text-slate-900">{entry.siteName || " "}</p>
                    </div>
                    <div>
                      <p className="text-xs text-slate-500">Liters Before</p>
                      <p className="text-sm font-semibold text-slate-900">
                        {entry.litersBefore != null ? `${entry.litersBefore} L` : " "}
                      </p>
                    </div>
                    <div>
                      <p className="text-xs text-slate-500">Liters Added</p>
                      <p className="text-sm font-bold text-emerald-700 text-base">
                        {entry.litersAdded != null ? `${entry.litersAdded} L` : " "}
                      </p>
                    </div>
                    <div>
                      <p className="text-xs text-slate-500">Completion Date</p>
                      <p className="text-sm font-semibold text-slate-900">
                        {entry.completionDate ? new Date(entry.completionDate).toLocaleDateString() : " "}
                      </p>
                    </div>
                    <div>
                      <p className="text-xs text-slate-500">Submitted At</p>
                      <p className="text-sm font-semibold text-slate-900">
```

```
            {entry.submittedAt ? new Date(entry.submittedAt).toLocaleString() : " "}
          </p>
        </div>
      </div>
      {entry.notes && (
        <div className="pt-1">
          <p className="text-xs text-slate-500">Notes</p>
          <p className="text-sm text-slate-700 mt-0.5">{entry.notes}</p>
        </div>
      )}
    </div>

    <Separator />

    {/* ODO Meter Photos */}
    <div>
      <div className="flex items-center gap-2 mb-3">
        <div className="w-7 h-7 rounded-lg bg-blue-100 flex items-center justify-center">
          <Camera className="w-4 h-4 text-blue-600" />
        </div>
        <h3 className="text-sm font-bold text-slate-700">ODO Meter</h3>
      </div>
      <div className="grid grid-cols-2 gap-3">
        <PhotoThumb
          src={entry.odoBeforePhoto}
          label="Before"
          icon={<Camera className="w-7 h-7" />}
        />
        <PhotoThumb
          src={entry.odoAfterPhoto}
          label="After"
          icon={<Camera className="w-7 h-7" />}
        />
      </div>
    </div>

    <Separator />

    {/* Tank Photos */}
    <div>
      <div className="flex items-center gap-2 mb-3">
        <div className="w-7 h-7 rounded-lg bg-sky-100 flex items-center justify-center">
          <Droplet className="w-4 h-4 text-sky-600" />
        </div>
        <h3 className="text-sm font-bold text-slate-700">Tank Readings</h3>
      </div>
      <div className="grid grid-cols-2 gap-3">
        <PhotoThumb
          src={entry.tankBeforePhoto}
          label="Before"
          icon={<Droplet className="w-7 h-7" />}
        />
```

```
                    <PhotoThumb
                      src={entry.tankAfterPhoto}
                      label="After"
                      icon={<Droplet className="w-7 h-7" />}
                    />
                  </div>
                </div>
              </>
            )}
          </div>
        </ScrollArea>

        {/* Action buttons */}
        <div className="px-6 py-4 border-t border-slate-100 bg-slate-50/80">
          <div className="grid grid-cols-3 gap-3">
            <Button
              className="h-11 gap-2 bg-emerald-600 hover:bg-emerald-700 text-white rounded-xl font-semibold shad
  ow-sm"
              onClick={() => doAction("approve")}
              disabled={!!acting}
            >
              <CheckCircle className="w-4 h-4" />
              {acting === "approve" ? "Approving..." : "Approve"}
            </Button>
            <Button
              variant="outline"
              className="h-11 gap-2 border-amber-300 text-amber-700 hover:bg-amber-50 rounded-xl font-semibold"
              onClick={() => doAction("send-back")}
              disabled={!!acting}
            >
              <RotateCcw className="w-4 h-4" />
              {acting === "send-back" ? "Sending..." : "Send Back"}
            </Button>
            <Button
              variant="outline"
              className="h-11 gap-2 border-red-200 text-red-600 hover:bg-red-50 rounded-xl font-semibold"
              onClick={() => doAction("reject")}
              disabled={!!acting}
            >
              <XCircle className="w-4 h-4" />
              {acting === "reject" ? "Rejecting..." : "Reject"}
            </Button>
          </div>
        </div>
      </SheetContent>
    </Sheet>
  );
}

function formatRegion(r?: string | null): string {
  if (!r) return "";
  const m: Record<string, string> = { CENTRAL: "Central", EAST: "East" };
```

```
  return m[r.toUpperCase()] ?? r;
}

export default function Missions() {
  const { user } = useAuth();
  const supervisorRegion = user?.role === "supervisor" ? (user.region || "") : "";
  const { data: missions, isLoading } = useMissions();
  const { data: drivers = [] } = useDrivers();
  const createMutation = useCreateMission();
  const updateMutation = useUpdateMission();
  const deleteMutation = useDeleteMission();
  const { toast } = useToast();

  const defaultMissionValues = { siteName: "", generator: "", project: "stc COW", missionStatus: "Creation", dri
  verName: "", filledLiters: 0 };

  const [searchTerm, setSearchTerm] = useState("");
  const [isDialogOpen, setIsDialogOpen] = useState(false);
  const [editMissionId, setEditMissionId] = useState<number | null>(null);
  const [reviewMission, setReviewMission] = useState<{ id: number; ref: string } | null>(null);

  const form = useForm<z.infer<typeof formSchema>>({
    resolver: zodResolver(formSchema),
    defaultValues: defaultMissionValues,
  });

  const openCreate = () => {
    form.reset(defaultMissionValues);
    setEditMissionId(null);
    setIsDialogOpen(true);
  };

  const openEdit = (mission: any) => {
    form.reset({
      siteName: mission.siteName,
      generator: mission.generator || "",
      project: mission.project || "stc COW",
      missionStatus: mission.missionStatus,
      driverName: mission.driverName || "",
      filledLiters: mission.filledLiters || 0,
    });
    setEditMissionId(mission.id);
    setIsDialogOpen(true);
  };

  const onSubmit = (values: z.infer<typeof formSchema>) => {
    if (editMissionId !== null) {
      updateMutation.mutate({ id: editMissionId, data: values }, {
        onSuccess: () => {
          toast({ title: "Mission updated" });
          setIsDialogOpen(false);
          setEditMissionId(null);
```

```
      },
      onError: () => toast({ title: "Failed to update mission", variant: "destructive" }),
    });
  } else {
    createMutation.mutate({ data: values }, {
      onSuccess: () => {
        toast({ title: "Mission created successfully" });
        setIsDialogOpen(false);
        form.reset();
      },
      onError: () => toast({ title: "Failed to create mission", variant: "destructive" }),
    });
  }
};

const filteredMissions = missions?.filter(m => {
  const matchSearch = m.siteName.toLowerCase().includes(searchTerm.toLowerCase()) ||
    (m.missionId?.toLowerCase() ?? "").includes(searchTerm.toLowerCase());
  const mRegion = (m as any).region || (m as any).city || "";
  const matchRegion = !supervisorRegion || mRegion.toUpperCase() === supervisorRegion.toUpperCase();
  return matchSearch && matchRegion;
});

return (
  <div className="space-y-6">
    <div className="flex flex-col sm:flex-row justify-between items-start sm:items-center gap-4">
      <div className="relative w-full sm:w-96">
        <Search className="absolute left-3 top-1/2 -translate-y-1/2 text-slate-400 w-5 h-5" />
        <Input
          placeholder="Search missions by site or ID..."
          className="pl-10 h-12 bg-white border-slate-200 rounded-xl shadow-sm focus-visible:ring-primary/20"
          value={searchTerm}
          onChange={e => setSearchTerm(e.target.value)}
        />
      </div>

      <div className="flex gap-2 items-start flex-wrap">
        <Button className="h-12 px-6 rounded-xl bg-primary hover:bg-primary/90 text-white shadow-lg shadow-pri
mary/25 transition-all" onClick={openCreate}>
          <Plus className="w-5 h-5 mr-2" />
          New Mission
        </Button>
        <Dialog open={isDialogOpen} onOpenChange={(o) => { if (!o) { setIsDialogOpen(false); setEditMissionId(
null); } }}>
          <DialogContent className="sm:max-w-[500px] p-6 rounded-3xl">
            <DialogHeader className="mb-4">
              <DialogTitle className="text-2xl font-display text-slate-900">{editMissionId ? "Edit Mission" :
"Create Mission"}</DialogTitle>
            </DialogHeader>
            <Form {...form}>
              <form onSubmit={form.handleSubmit(onSubmit)} className="space-y-4">
                <FormField
```

```
            control={form.control}
            name="siteName"
            render={({ field }) => (
              <FormItem>
                <FormLabel>Site Name</FormLabel>
                <FormControl>
                  <Input placeholder="e.g. COW531" className="h-11 rounded-xl" {...field} />
                </FormControl>
                <FormMessage />
              </FormItem>
            )}
          />
          <FormField
            control={form.control}
            name="driverName"
            render={({ field }) => (
              <FormItem>
                <FormLabel>Driver</FormLabel>
                <Select onValueChange={field.onChange} defaultValue={field.value}>
                  <FormControl>
                    <SelectTrigger className="h-11 rounded-xl">
                      <SelectValue placeholder="Select driver..." />
                    </SelectTrigger>
                  </FormControl>
                  <SelectContent>
                    <SelectItem value="unassigned">Unassigned</SelectItem>
                    {drivers.map((d) => (
                      <SelectItem key={d.id} value={d.name}>{d.name}</SelectItem>
                    ))}
                  </SelectContent>
                </Select>
                <FormMessage />
              </FormItem>
            )}
          />
          <FormField
            control={form.control}
            name="missionStatus"
            render={({ field }) => (
              <FormItem>
                <FormLabel>Status</FormLabel>
                <Select onValueChange={field.onChange} defaultValue={field.value}>
                  <FormControl>
                    <SelectTrigger className="h-11 rounded-xl">
                      <SelectValue placeholder="Select status" />
                    </SelectTrigger>
                  </FormControl>
                  <SelectContent>
                    <SelectItem value="Creation">Creation</SelectItem>
                    <SelectItem value="Finished by Driver">Finished by Driver</SelectItem>
                    <SelectItem value="Task approved">Task approved</SelectItem>
                  </SelectContent>
```

```
                    </Select>
                    <FormMessage />
                  </FormItem>
                )}
              />
              <Button type="submit" className="w-full h-12 rounded-xl mt-6 text-base shadow-lg shadow-primar
y/20" disabled={createMutation.isPending || updateMutation.isPending}>
                {(createMutation.isPending || updateMutation.isPending) ? "Saving..." : (editMissionId ? "Up
date Mission" : "Save Mission")}
              </Button>
            </form>
          </Form>
        </DialogContent>
      </Dialog>
    </div>
  </div>

  <Card className="glass-panel border-0 shadow-xl shadow-slate-200/50 overflow-hidden">
    <Table>
      <TableHeader className="bg-slate-50 border-b border-slate-100">
        <TableRow className="hover:bg-transparent">
          <TableHead className="font-semibold text-slate-600 h-12">Mission ID</TableHead>
          <TableHead className="font-semibold text-slate-600">Site</TableHead>
          <TableHead className="font-semibold text-slate-600">Region</TableHead>
          <TableHead className="font-semibold text-slate-600">Driver</TableHead>
          <TableHead className="font-semibold text-slate-600">Liters</TableHead>
          <TableHead className="font-semibold text-slate-600">Status</TableHead>
          <TableHead className="text-right font-semibold text-slate-600">Actions</TableHead>
        </TableRow>
      </TableHeader>
      <TableBody>
        {isLoading ? (
          <TableRow>
            <TableCell colSpan={7} className="h-32 text-center text-slate-500">Loading missions...</TableCel
l>
          </TableRow>
        ) : filteredMissions?.length === 0 ? (
          <TableRow>
            <TableCell colSpan={7} className="h-32 text-center">
              <div className="flex flex-col items-center justify-center text-slate-400">
                <FileText className="w-8 h-8 mb-2 opacity-50" />
                <p>No missions found</p>
              </div>
            </TableCell>
          </TableRow>
        ) : (
          filteredMissions?.map((mission) => (
            <TableRow key={mission.id} className="hover:bg-slate-50/50 transition-colors border-slate-50">
              <TableCell className="font-medium text-slate-900">{mission.missionId || `MSN-${mission.id}`}</
TableCell>
              <TableCell>
                <div className="font-medium text-slate-900">{mission.siteName}</div>
```

```
                </TableCell>
                <TableCell>
                  <span className="inline-block rounded-full px-2 py-0.5 text-xs font-medium bg-sky-50 text-sky-700 border border-sky-100">
                    {formatRegion((mission as any).region || mission.city) || ' '}
                  </span>
                </TableCell>
                <TableCell>{mission.driverName || 'Unassigned'}</TableCell>
                <TableCell className="font-medium text-slate-700">{mission.filledLiters || 0} L</TableCell>
                <TableCell>
                  <Badge variant="outline" className={`border-0 shadow-sm ${statusColors[mission.missionStatus] || statusColors['Creation']}`}>
                    {mission.missionStatus}
                  </Badge>
                </TableCell>
                <TableCell className="text-right">
                  <div className="flex items-center justify-end gap-1">
                    {mission.missionStatus === "Finished by Driver" && (
                      <Button
                        variant="ghost"
                        size="sm"
                        className="h-8 px-3 text-sky-600 hover:text-sky-700 hover:bg-sky-50 rounded-lg gap-1.5 font-medium text-xs"
                        onClick={() => setReviewMission({ id: mission.id!, ref: mission.missionId || `MSN-${mission.id}` })}
                      >
                        <Eye className="w-3.5 h-3.5" />
                        Review
                      </Button>
                    )}
                    <Button
                      variant="ghost"
                      size="icon"
                      className="h-8 w-8 text-slate-400 hover:text-primary hover:bg-primary/10 rounded-lg transition-colors"
                      onClick={() => openEdit(mission)}
                    >
                      <Pencil className="w-4 h-4" />
                    </Button>
                    <Button
                      variant="ghost"
                      size="icon"
                      className="h-8 w-8 text-slate-400 hover:text-destructive hover:bg-destructive/10 rounded-lg transition-colors"
                      onClick={() => {
                        if (confirm('Delete this mission?')) {
                          deleteMutation.mutate({ id: mission.id }, {
                            onSuccess: () => toast({ title: "Deleted" })
                          });
                        }
                      }}
                    >
```

```
                      <Trash2 className="w-4 h-4" />
                    </Button>
                  </div>
                </TableCell>
              </TableRow>
            ))
          )}
        </TableBody>
      </Table>
    </Card>

    <MissionReviewSheet
      missionId={reviewMission?.id ?? null}
      missionRef={reviewMission?.ref ?? ""}
      open={!!reviewMission}
      onClose={() => setReviewMission(null)}
    />
  </div>
 );
}
```

FILE: artifacts/web-portal/src/pages/admin/Notifications.tsx
SIZE: 4,820 bytes

```
import { useState } from "react";
import { useListDrivers, useCreateNotification, useListNotifications } from "@workspace/api-client-react";
import { Card, CardContent } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Textarea } from "@/components/ui/textarea";
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from "@/components/ui/table";
import { Send, Bell } from "lucide-react";
import { useAuth } from "@/lib/auth-context";

export default function NotificationsPage() {
  const { user } = useAuth();
  const { data: drivers = [] } = useListDrivers();
  const { data: notifications = [], refetch } = useListNotifications();
  const createMutation = useCreateNotification();
  const [driverName, setDriverName] = useState("All");
  const [title, setTitle] = useState("");
  const [message, setMessage] = useState("");
  const [submitting, setSubmitting] = useState(false);

  const onSubmit = async () => {
    if (!title.trim() || !message.trim()) return;
    setSubmitting(true);
    try {
      await createMutation.mutateAsync({
        data: {
          title: title.trim(),
          message: message.trim(),
          driverName: driverName === "All" ? undefined : driverName,
          sentBy: user?.username || "Admin",
        }
      });
      setTitle("");
      setMessage("");
      refetch();
    } finally {
      setSubmitting(false);
    }
  };

  return (
    <div className="space-y-6">
      <div>
        <h1 className="text-3xl font-bold text-slate-900">Notifications</h1>
        <p className="text-slate-500 mt-1">Send push notifications to drivers</p>
      </div>
```

```
    <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
      <Card className="border-0 shadow-sm">
        <CardContent className="p-6 space-y-4">
          <h2 className="font-semibold text-lg flex items-center gap-2"><Bell className="w-5 h-5 text-primary"
 /> Send Notification</h2>
          <div>
            <Label>Send To</Label>
            <Select value={driverName} onValueChange={setDriverName}>
              <SelectTrigger>
                <SelectValue />
              </SelectTrigger>
              <SelectContent>
                <SelectItem value="All">All Drivers</SelectItem>
                {drivers.filter(d => d.active).map((d) => (
                  <SelectItem key={d.id} value={d.name!}>{d.name}</SelectItem>
                ))}
              </SelectContent>
            </Select>
          </div>
          <div>
            <Label>Title</Label>
            <Input value={title} onChange={(e) => setTitle(e.target.value)} placeholder="Notification title" /
>
          </div>
          <div>
            <Label>Message</Label>
            <Textarea value={message} onChange={(e) => setMessage(e.target.value)} placeholder="Enter notifica
tion message..." rows={4} />
          </div>
          <Button onClick={onSubmit} disabled={submitting || !title.trim() || !message.trim()} className="w-fu
ll gap-2">
            <Send className="w-4 h-4" /> {submitting ? "Sending..." : "Send Notification"}
          </Button>
        </CardContent>
      </Card>

      <Card className="border-0 shadow-sm overflow-hidden">
        <CardContent className="p-4">
          <h2 className="font-semibold text-lg mb-4">Recent Notifications</h2>
          <Table>
            <TableHeader>
              <TableRow className="bg-slate-50">
                <TableHead>Title</TableHead>
                <TableHead>Driver</TableHead>
                <TableHead>Sent By</TableHead>
                <TableHead>Date</TableHead>
              </TableRow>
            </TableHeader>
            <TableBody>
              {notifications.slice(0, 10).map((n) => (
                <TableRow key={n.id}>
                  <TableCell className="font-medium">{n.title}</TableCell>
```

```
                    <TableCell>{n.driverName || "All"}</TableCell>
                    <TableCell>{n.sentBy}</TableCell>
                    <TableCell className="text-sm text-slate-500">
                      {n.createdAt ? new Date(n.createdAt).toLocaleDateString() : ""}
                    </TableCell>
                  </TableRow>
                ))}
                {notifications.length === 0 && (
                  <TableRow><TableCell colSpan={4} className="text-center py-8 text-slate-400">No notifications
  sent yet</TableCell></TableRow>
                )}
              </TableBody>
            </Table>
          </CardContent>
        </Card>
      </div>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/admin/Reports.tsx
SIZE: 17,505 bytes

```
import { useMemo, useState } from "react";
import { useQuery, useMutation, useQueryClient } from "@tanstack/react-query";
import { Card, CardContent } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Badge } from "@/components/ui/badge";
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from "@/components/ui/table";
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from "@/components/ui/select";
import { Dialog, DialogContent, DialogHeader, DialogTitle } from "@/components/ui/dialog";
import { Download, MapPin, Droplet, FileText, BarChart3, Pencil } from "lucide-react";
import { useAuth } from "@/lib/auth-context";
import { useToast } from "@/hooks/use-toast";

const apiBase = import.meta.env.BASE_URL.replace(/\/$/, "");

interface ReportLine {
  id: number;
  missionRef: string;
  siteName: string;
  region: string;
  project: string;
  driverName: string;
  litersAdded: number;
  completionDate: string | null;
  approvedAt: string | null;
  approvedBy: string;
  unitPrice: number;
  invoiceExported: boolean;
}

function formatRegion(r?: string | null): string {
  if (!r) return "";
  const m: Record<string, string> = { CENTRAL: "Central", EAST: "East" };
  return m[r.toUpperCase()] ?? r;
}

const REGION_COLORS: Record<string, string> = {
  "CENTRAL": "bg-blue-100 text-blue-700",
  "EAST": "bg-emerald-100 text-emerald-700",
};

export default function ReportsPage() {
  const queryClient = useQueryClient();
  const { toast } = useToast();
  const { data: reportLines = [], isLoading } = useQuery<ReportLine[]>({
    queryKey: ["report-lines"],
    queryFn: async () => {
      const res = await fetch(`${apiBase}/api/report-lines`);
```

```
    if (!res.ok) throw new Error("Failed to load");
    return res.json();
  },
});

const [fromDate, setFromDate] = useState("");
const [toDate, setToDate] = useState("");
const [siteQuery, setSiteQuery] = useState("");
const [editLine, setEditLine] = useState<ReportLine | null>(null);
const [editLiters, setEditLiters] = useState(0);
const { user } = useAuth();
const supervisorRegion = user?.role === "supervisor" ? (user.region || "") : "";

const updateLineMutation = useMutation({
  mutationFn: async ({ id, litersAdded }: { id: number; litersAdded: number }) => {
    const res = await fetch(`${apiBase}/api/report-lines/${id}`, {
      method: "PUT",
      headers: { "Content-Type": "application/json" },
      body: JSON.stringify({ litersAdded }),
    });
    if (!res.ok) throw new Error("Failed to update");
    return res.json();
  },
  onSuccess: () => {
    queryClient.invalidateQueries({ queryKey: ["report-lines"] });
    toast({ title: "Report line updated" });
    setEditLine(null);
  },
  onError: () => toast({ title: "Failed to update report line", variant: "destructive" }),
});
const [regionFilter, setRegionFilter] = useState("all");
const [unitPrice] = useState(0.63);
const vatRate = 0.15;

const REGIONS = ["CENTRAL", "EAST"];

const lines = useMemo(() => {
  const activeRegion = supervisorRegion || regionFilter;
  return reportLines
    .filter((l) => activeRegion === "all" || !activeRegion || l.region.toUpperCase() === activeRegion.toUpperC
ase())
    .filter((l) => !siteQuery || l.siteName?.toLowerCase().includes(siteQuery.toLowerCase()))
    .filter((l) => {
      if (!fromDate && !toDate) return true;
      const d = l.approvedAt ? new Date(l.approvedAt) : null;
      if (!d) return false;
      if (fromDate && d < new Date(fromDate)) return false;
      if (toDate && d > new Date(toDate + "T23:59:59")) return false;
      return true;
    })
    .map((l) => ({
      ...l,
```

```
      linePrice: l.litersAdded * unitPrice,
    }));
  }, [reportLines, fromDate, toDate, siteQuery, regionFilter, unitPrice]);

  // Group by region for summary
  const byRegion = useMemo(() => {
    const map: Record<string, { liters: number; lines: number; amount: number }> = {};
    for (const l of lines) {
      const r = l.region || "Unknown";
      if (!map[r]) map[r] = { liters: 0, lines: 0, amount: 0 };
      map[r].liters += l.litersAdded;
      map[r].lines += 1;
      map[r].amount += l.linePrice;
    }
    return Object.entries(map).sort((a, b) => b[1].liters - a[1].liters);
  }, [lines]);

  const subtotal = lines.reduce((s, l) => s + l.linePrice, 0);
  const vat = subtotal * vatRate;
  const total = subtotal + vat;
  const totalLiters = lines.reduce((s, l) => s + l.litersAdded, 0);

  const exportCSV = () => {
    const rows = [
      ["Mission", "Site", "Region", "Driver", "Approved Date", "Liters", "Unit Price", "Line Total"],
      ...lines.map((l) => [
        l.missionRef,
        l.siteName,
        l.region,
        l.driverName,
        l.approvedAt ? new Date(l.approvedAt).toLocaleDateString() : "",
        l.litersAdded,
        unitPrice.toFixed(2),
        l.linePrice.toFixed(2),
      ])
    ];
    const csv = rows.map((r) => r.join(",")).join("\n");
    const blob = new Blob([csv], { type: "text/csv" });
    const url = URL.createObjectURL(blob);
    const a = document.createElement("a");
    a.href = url;
    a.download = `aces-report-${Date.now()}.csv`;
    a.click();
  };

  return (
    <>
    <div className="space-y-6">
      <div className="flex items-center justify-between">
        <div>
          <h1 className="text-3xl font-bold text-slate-900">Reports</h1>
          <p className="text-slate-500 mt-1">Approved missions   fuel quantities by region for invoice preparati
```

```
on</p>
      </div>
      <Button onClick={exportCSV} variant="outline" className="gap-2 h-11 rounded-xl">
        <Download className="w-4 h-4" /> Export CSV
      </Button>
    </div>

    {/* Summary KPI cards */}
    <div className="grid grid-cols-2 sm:grid-cols-4 gap-4">
      <Card className="border-0 shadow-sm">
        <CardContent className="p-4">
          <p className="text-xs text-slate-500 uppercase tracking-wider font-semibold">Approved Tasks</p>
          <p className="text-2xl font-bold text-slate-900 mt-1">{lines.length}</p>
        </CardContent>
      </Card>
      <Card className="border-0 shadow-sm">
        <CardContent className="p-4">
          <p className="text-xs text-slate-500 uppercase tracking-wider font-semibold">Total Liters</p>
          <p className="text-2xl font-bold text-sky-700 mt-1">{totalLiters.toLocaleString()} L</p>
        </CardContent>
      </Card>
      <Card className="border-0 shadow-sm">
        <CardContent className="p-4">
          <p className="text-xs text-slate-500 uppercase tracking-wider font-semibold">Subtotal</p>
          <p className="text-2xl font-bold text-emerald-700 mt-1">{subtotal.toFixed(0)} SAR</p>
        </CardContent>
      </Card>
      <Card className="border-0 shadow-sm">
        <CardContent className="p-4">
          <p className="text-xs text-slate-500 uppercase tracking-wider font-semibold">Total + VAT</p>
          <p className="text-2xl font-bold text-primary mt-1">{total.toFixed(0)} SAR</p>
        </CardContent>
      </Card>
    </div>

    {/* Region summary */}
    {byRegion.length > 0 && (
      <Card className="border-0 shadow-sm overflow-hidden">
        <div className="px-4 pt-4 pb-2 flex items-center gap-2">
          <BarChart3 className="w-4 h-4 text-slate-500" />
          <h2 className="text-sm font-bold text-slate-700 uppercase tracking-wider">By Region</h2>
        </div>
        <div className="flex flex-wrap gap-3 px-4 pb-4">
          {byRegion.map(([region, data]) => (
            <div
              key={region}
              className="flex items-center gap-3 bg-slate-50 rounded-xl px-4 py-3 border border-slate-100"
            >
              <div className="w-8 h-8 rounded-lg bg-white border border-slate-200 flex items-center justify-ce
nter">
                <MapPin className="w-4 h-4 text-slate-500" />
              </div>
```

```
              <div>
                <p className="text-xs font-bold text-slate-700">{formatRegion(region) || "Unknown"}</p>
                <p className="text-xs text-slate-500">{data.lines} tasks • {data.liters.toLocaleString()} L</p
>
                <p className="text-xs font-semibold text-emerald-700">{data.amount.toFixed(0)} SAR</p>
              </div>
            </div>
          ))}
        </div>
      </Card>
    )}

    {/* Filters */}
    <Card className="border-0 shadow-sm">
      <CardContent className="p-4">
        <div className="flex flex-wrap gap-4">
          <div>
            <Label className="text-xs mb-1 block">From Date</Label>
            <Input type="date" value={fromDate} onChange={(e) => setFromDate(e.target.value)} className="w-40
h-9" />
          </div>
          <div>
            <Label className="text-xs mb-1 block">To Date</Label>
            <Input type="date" value={toDate} onChange={(e) => setToDate(e.target.value)} className="w-40 h-9"
 />
          </div>
          <div>
            <Label className="text-xs mb-1 block">Region</Label>
            {supervisorRegion ? (
              <div className="w-44 h-9 flex items-center px-3 rounded-md border border-slate-200 bg-slate-50 t
ext-sm text-slate-700 font-medium">
                {formatRegion(supervisorRegion)}
              </div>
            ) : (
              <Select value={regionFilter} onValueChange={setRegionFilter}>
                <SelectTrigger className="w-44 h-9">
                  <SelectValue placeholder="All regions" />
                </SelectTrigger>
                <SelectContent>
                  <SelectItem value="all">All Regions</SelectItem>
                  <SelectItem value="CENTRAL">Central</SelectItem>
                  <SelectItem value="EAST">East</SelectItem>
                </SelectContent>
              </Select>
            )}
          </div>
          <div>
            <Label className="text-xs mb-1 block">Site</Label>
            <Input placeholder="Filter by site..." value={siteQuery} onChange={(e) => setSiteQuery(e.target.va
lue)} className="w-48 h-9" />
          </div>
        </div>
```

```
      </CardContent>
    </Card>

    {/* Detail table */}
    <Card className="border-0 shadow-sm overflow-hidden">
      <Table>
        <TableHeader>
          <TableRow className="bg-slate-50">
            <TableHead className="text-xs font-bold text-slate-600 uppercase">#</TableHead>
            <TableHead className="text-xs font-bold text-slate-600 uppercase">Mission</TableHead>
            <TableHead className="text-xs font-bold text-slate-600 uppercase">Site</TableHead>
            <TableHead className="text-xs font-bold text-slate-600 uppercase">Region</TableHead>
            <TableHead className="text-xs font-bold text-slate-600 uppercase">Driver</TableHead>
            <TableHead className="text-xs font-bold text-slate-600 uppercase">Approved</TableHead>
            <TableHead className="text-right text-xs font-bold text-slate-600 uppercase">Liters</TableHead>
            <TableHead className="text-right text-xs font-bold text-slate-600 uppercase">Unit Price</TableHead
>
            <TableHead className="text-right text-xs font-bold text-slate-600 uppercase">Line Total</TableHead
>
            <TableHead className="text-right text-xs font-bold text-slate-600 uppercase">Edit</TableHead>
          </TableRow>
        </TableHeader>
        <TableBody>
          {isLoading ? (
            <TableRow>
              <TableCell colSpan={10} className="text-center py-10 text-slate-400">Loading report...</TableCel
l>
            </TableRow>
          ) : lines.length === 0 ? (
            <TableRow>
              <TableCell colSpan={10} className="text-center py-12">
                <div className="flex flex-col items-center gap-2 text-slate-400">
                  <FileText className="w-8 h-8 opacity-50" />
                  <p className="text-sm">No approved missions for the selected filters</p>
                  <p className="text-xs">Approve missions from the Missions page to populate the report</p>
                </div>
              </TableCell>
            </TableRow>
          ) : (
            lines.map((l, i) => (
              <TableRow key={l.id} className="hover:bg-slate-50/50">
                <TableCell className="text-slate-500 text-sm">{i + 1}</TableCell>
                <TableCell className="font-mono text-xs text-slate-600">{l.missionRef}</TableCell>
                <TableCell className="font-medium text-slate-900">{l.siteName}</TableCell>
                <TableCell>
                  <Badge variant="outline" className={`border-0 text-xs ${REGION_COLORS[(l.region || "").toUpp
erCase()] ?? "bg-slate-100 text-slate-600"}`}>
                    {formatRegion(l.region) || " "}
                  </Badge>
                </TableCell>
                <TableCell className="text-slate-700">{l.driverName || " "}</TableCell>
                <TableCell className="text-slate-500 text-sm">
```

```
                {l.approvedAt ? new Date(l.approvedAt).toLocaleDateString() : " "}
              </TableCell>
              <TableCell className="text-right font-medium text-sky-700">
                <span className="flex items-center justify-end gap-1">
                  <Droplet className="w-3 h-3" />
                  {l.litersAdded.toFixed(0)}
                </span>
              </TableCell>
              <TableCell className="text-right text-slate-600">{unitPrice.toFixed(2)}</TableCell>
              <TableCell className="text-right font-semibold text-slate-900">{l.linePrice.toFixed(2)}</Table
Cell>
              <TableCell className="text-right">
                <Button
                  variant="ghost"
                  size="icon"
                  className="h-7 w-7 text-slate-400 hover:text-primary hover:bg-primary/10 rounded-lg transi
tion-colors"
                  onClick={() => { setEditLine(l); setEditLiters(l.litersAdded); }}
                >
                  <Pencil className="w-3.5 h-3.5" />
                </Button>
              </TableCell>
            </TableRow>
          ))
        )}
      </TableBody>
    </Table>
  </Card>

  {/* Invoice totals */}
  {lines.length > 0 && (
    <Card className="border-0 shadow-sm ml-auto max-w-sm">
      <CardContent className="p-5 space-y-2">
        <h3 className="text-sm font-bold text-slate-700 uppercase tracking-wider mb-3">Invoice Summary</h3>
        <div className="flex justify-between text-sm">
          <span className="text-slate-500">Subtotal ({totalLiters.toLocaleString()} L)</span>
          <span className="font-medium">{subtotal.toFixed(2)} SAR</span>
        </div>
        <div className="flex justify-between text-sm">
          <span className="text-slate-500">VAT ({(vatRate * 100).toFixed(0)}%)</span>
          <span className="font-medium">{vat.toFixed(2)} SAR</span>
        </div>
        <div className="flex justify-between font-bold border-t pt-3 mt-2">
          <span>Total</span>
          <span className="text-primary text-lg">{total.toFixed(2)} SAR</span>
        </div>
      </CardContent>
    </Card>
  )}
</div>

{/* Edit report line dialog */}
```

```
    <Dialog open={!!editLine} onOpenChange={(o) => { if (!o) setEditLine(null); }}>
      <DialogContent className="sm:max-w-[360px] p-6 rounded-3xl">
        <DialogHeader className="mb-4">
          <DialogTitle className="text-xl font-display text-slate-900">Edit Report Line</DialogTitle>
        </DialogHeader>
        {editLine && (
          <div className="space-y-4">
            <div>
              <p className="text-xs text-slate-500 mb-1">Mission</p>
              <p className="text-sm font-mono text-slate-700">{editLine.missionRef}</p>
            </div>
            <div>
              <p className="text-xs text-slate-500 mb-1">Site</p>
              <p className="text-sm font-medium text-slate-800">{editLine.siteName}</p>
            </div>
            <div>
              <label className="text-xs text-slate-500 mb-1 block">Liters Added</label>
              <Input
                type="number"
                min={0}
                step={1}
                value={editLiters}
                onChange={(e) => setEditLiters(Number(e.target.value))}
                className="h-11 rounded-xl"
              />
            </div>
            <div className="flex gap-2 pt-2">
              <Button variant="outline" className="flex-1 h-11 rounded-xl" onClick={() => setEditLine(null)}>
                Cancel
              </Button>
              <Button
                className="flex-1 h-11 rounded-xl"
                disabled={updateLineMutation.isPending}
                onClick={() => updateLineMutation.mutate({ id: editLine.id, litersAdded: editLiters })}
              >
                {updateLineMutation.isPending ? "Saving..." : "Save"}
              </Button>
            </div>
          </div>
        )}
      </DialogContent>
    </Dialog>
    </>
  );
}
```

FILE: artifacts/web-portal/src/pages/admin/Settings.tsx
SIZE: 3,717 bytes

```
import { useState, useEffect } from "react";
import { useGetSettings, useUpdateSettings } from "@workspace/api-client-react";
import { Card, CardContent } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Settings2 } from "lucide-react";

export default function SettingsPage() {
  const { data: settings, refetch } = useGetSettings();
  const updateMutation = useUpdateSettings();
  const [form, setForm] = useState({
    fuelUnitPrice: 0.63,
    vatRate: 0.15,
    supplierName: "",
    supplierAddress: "",
    invoicePrefix: "INV-SEC-",
    invoiceSequence: 1,
  });
  const [saving, setSaving] = useState(false);
  const [saved, setSaved] = useState(false);

  useEffect(() => {
    if (settings) {
      setForm({
        fuelUnitPrice: settings.fuelUnitPrice ?? 0.63,
        vatRate: settings.vatRate ?? 0.15,
        supplierName: settings.supplierName ?? "",
        supplierAddress: settings.supplierAddress ?? "",
        invoicePrefix: settings.invoicePrefix ?? "INV-SEC-",
        invoiceSequence: settings.invoiceSequence ?? 1,
      });
    }
  }, [settings]);

  const onSave = async () => {
    setSaving(true);
    try {
      await updateMutation.mutateAsync({ data: form });
      setSaved(true);
      setTimeout(() => setSaved(false), 2000);
      refetch();
    } finally {
      setSaving(false);
    }
  };

  return (
    <div className="space-y-6">
```

```
    <div>
      <h1 className="text-3xl font-bold text-slate-900">Settings</h1>
      <p className="text-slate-500 mt-1">Configure application settings</p>
    </div>

    <Card className="border-0 shadow-sm max-w-2xl">
      <CardContent className="p-6 space-y-6">
        <h2 className="font-semibold text-lg flex items-center gap-2">
          <Settings2 className="w-5 h-5 text-primary" /> General Settings
        </h2>

        <div className="grid grid-cols-2 gap-4">
          <div>
            <Label>Fuel Unit Price (SAR/L)</Label>
            <Input type="number" step="0.01" value={form.fuelUnitPrice}
              onChange={(e) => setForm((f) => ({ ...f, fuelUnitPrice: Number(e.target.value) }))} />
          </div>
          <div>
            <Label>VAT Rate (%)</Label>
            <Input type="number" step="0.01" value={(form.vatRate * 100).toFixed(0)}
              onChange={(e) => setForm((f) => ({ ...f, vatRate: Number(e.target.value) / 100 }))} />
          </div>
        </div>

        <div>
          <Label>Supplier Name</Label>
          <Input value={form.supplierName} onChange={(e) => setForm((f) => ({ ...f, supplierName: e.target.val
ue }))} />
        </div>

        <div>
          <Label>Supplier Address</Label>
          <Input value={form.supplierAddress} onChange={(e) => setForm((f) => ({ ...f, supplierAddress: e.targ
et.value }))} />
        </div>

        <div className="grid grid-cols-2 gap-4">
          <div>
            <Label>Invoice Prefix</Label>
            <Input value={form.invoicePrefix} onChange={(e) => setForm((f) => ({ ...f, invoicePrefix: e.target
.value }))} />
          </div>
          <div>
            <Label>Invoice Sequence Start</Label>
            <Input type="number" value={form.invoiceSequence}
              onChange={(e) => setForm((f) => ({ ...f, invoiceSequence: Number(e.target.value) }))} />
          </div>
        </div>

        <Button onClick={onSave} disabled={saving} className="w-full">
          {saving ? "Saving..." : saved ? "Saved!" : "Save Settings"}
        </Button>
```

```
        </CardContent>
      </Card>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/admin/Sites.tsx
SIZE: 24,894 bytes

```
import { useState } from "react";
import { useQuery, useMutation, useQueryClient } from "@tanstack/react-query";
import { Card, CardContent } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Badge } from "@/components/ui/badge";
import { Table, TableBody, TableCell, TableHead, TableHeader, TableRow } from "@/components/ui/table";
import { Dialog, DialogContent, DialogHeader, DialogTitle, DialogTrigger } from "@/components/ui/dialog";
import { Plus, Search, Trash2, MapPin, Upload, CheckCircle2, XCircle, RefreshCw, AlertCircle, Pencil } from "luc
  ide-react";
import { useForm } from "react-hook-form";
import { zodResolver } from "@hookform/resolvers/zod";
import * as z from "zod";
import { Form, FormControl, FormField, FormItem, FormLabel, FormMessage } from "@/components/ui/form";
import { useToast } from "@/hooks/use-toast";
import { useAuth } from "@/lib/auth-context";

interface Site {
  id: number;
  name: string;
  region: string;
  district: string;
  city: string;
  cowStatus: string;
  siteLabel: string;
  lat: number | null;
  lng: number | null;
  nextFuelingPlan: string;
  lastFuelingDate: string;
  lastFuelingQty: number | null;
  active: boolean;
  currentLiters: number;
  assignedTechnicianId: number | null;
}

const apiBase = import.meta.env.BASE_URL.replace(/\/$/, "");

async function apiFetch(path: string, opts?: RequestInit) {
  const res = await fetch(`${apiBase}${path}`, {
    ...opts,
    headers: { "Content-Type": "application/json", ...opts?.headers },
  });
  return res;
}

const formSchema = z.object({
  name: z.string().min(1, "Site name is required"),
  region: z.string().optional(),
  district: z.string().optional(),
```

```
  city: z.string().optional(),
  cowStatus: z.string().optional(),
  siteLabel: z.string().optional(),
  lat: z.string().optional(),
  lng: z.string().optional(),
  nextFuelingPlan: z.string().optional(),
});

const COW_STATUS_COLORS: Record<string, string> = {
  "ON-AIR": "bg-emerald-50 text-emerald-700 border-emerald-200",
  "OFF-AIR": "bg-red-50 text-red-700 border-red-200",
  "MAINTENANCE": "bg-amber-50 text-amber-700 border-amber-200",
};

function formatRegion(r?: string | null): string {
  if (!r) return "";
  const m: Record<string, string> = { CENTRAL: "Central", EAST: "East" };
  return m[r.toUpperCase()] ?? r;
}

export default function Sites() {
  const queryClient = useQueryClient();
  const { user } = useAuth();
  const supervisorRegion = user?.role === "supervisor" ? (user.region || "") : "";
  const { toast } = useToast();
  const [searchTerm, setSearchTerm] = useState("");
  const [regionFilter, setRegionFilter] = useState("");
  const [isAddOpen, setIsAddOpen] = useState(false);
  const [isImportOpen, setIsImportOpen] = useState(false);
  const [csvText, setCsvText] = useState("");
  const [importResult, setImportResult] = useState<{ inserted: number; skipped: number; errors: string[]; total:
   number } | null>(null);
  const [importing, setImporting] = useState(false);
  const [syncing, setSyncing] = useState(false);
  const [syncResult, setSyncResult] = useState<{ inserted: number; updated: number; skipped: number; errors: str
  ing[]; total: number } | null>(null);

  const { data: sites = [], isLoading } = useQuery<Site[]>({
    queryKey: ["sites"],
    queryFn: async () => {
      const res = await apiFetch("/api/sites");
      if (!res.ok) throw new Error("Failed to fetch sites");
      return res.json();
    },
  });

  const [editSiteId, setEditSiteId] = useState<number | null>(null);

  const createMutation = useMutation({
    mutationFn: async (data: Record<string, unknown>) => {
      const res = await apiFetch("/api/sites", { method: "POST", body: JSON.stringify(data) });
      if (!res.ok) throw new Error("Failed to create site");
```

```
      return res.json();
    },
    onSuccess: () => {
      queryClient.invalidateQueries({ queryKey: ["sites"] });
      toast({ title: "Site created successfully" });
      setIsAddOpen(false);
      setEditSiteId(null);
      form.reset();
    },
    onError: () => toast({ title: "Failed to create site", variant: "destructive" }),
  });

  const updateMutation = useMutation({
    mutationFn: async ({ id, data }: { id: number; data: Record<string, unknown> }) => {
      const res = await apiFetch(`/api/sites/${id}`, { method: "PUT", body: JSON.stringify(data) });
      if (!res.ok) throw new Error("Failed to update site");
      return res.json();
    },
    onSuccess: () => {
      queryClient.invalidateQueries({ queryKey: ["sites"] });
      toast({ title: "Site updated successfully" });
      setIsAddOpen(false);
      setEditSiteId(null);
      form.reset();
    },
    onError: () => toast({ title: "Failed to update site", variant: "destructive" }),
  });

  const deleteMutation = useMutation({
    mutationFn: async (id: number) => {
      await apiFetch(`/api/sites/${id}`, { method: "DELETE" });
    },
    onSuccess: () => queryClient.invalidateQueries({ queryKey: ["sites"] }),
  });

  const defaultSiteValues = { name: "", region: "", district: "", city: "", cowStatus: "ON-AIR", siteLabel: "",
  lat: "", lng: "", nextFuelingPlan: "" };

  const form = useForm<z.infer<typeof formSchema>>({
    resolver: zodResolver(formSchema),
    defaultValues: defaultSiteValues,
  });

  const openAddSite = () => {
    form.reset(defaultSiteValues);
    setEditSiteId(null);
    setIsAddOpen(true);
  };

  const openEditSite = (site: any) => {
    form.reset({
      name: site.name,
```

```
      region: site.region || "",
      district: site.district || "",
      city: site.city || "",
      cowStatus: site.cowStatus || "ON-AIR",
      siteLabel: site.siteLabel || "",
      lat: site.lat != null ? String(site.lat) : "",
      lng: site.lng != null ? String(site.lng) : "",
      nextFuelingPlan: site.nextFuelingPlan || "",
    });
    setEditSiteId(site.id);
    setIsAddOpen(true);
  };

  const onSubmit = (values: z.infer<typeof formSchema>) => {
    const payload = {
      ...values,
      lat: values.lat ? parseFloat(values.lat) : undefined,
      lng: values.lng ? parseFloat(values.lng) : undefined,
      project: "stc COW",
      active: true,
    };
    if (editSiteId !== null) {
      updateMutation.mutate({ id: editSiteId, data: payload });
    } else {
      createMutation.mutate(payload);
    }
  };

  const handleSyncSheets = async () => {
    setSyncing(true);
    setSyncResult(null);
    try {
      const res = await apiFetch("/api/sites/sync-sheets", { method: "POST" });
      const result = await res.json();
      if (!res.ok) { toast({ title: result.error || "Sync failed", variant: "destructive" }); return; }
      setSyncResult(result);
      queryClient.invalidateQueries({ queryKey: ["sites"] });
      toast({ title: `Synced ${result.inserted + result.updated} sites (${result.inserted} new, ${result.updated
} updated)` });
    } catch {
      toast({ title: "Sync failed   check your connection", variant: "destructive" });
    } finally {
      setSyncing(false);
    }
  };

  const handleImport = async () => {
    if (!csvText.trim()) return;
    setImporting(true);
    setImportResult(null);
    try {
      const res = await apiFetch("/api/sites/import-csv", { method: "POST", body: JSON.stringify({ csv: csvText
```

```
  }) });
      const result = await res.json();
      if (!res.ok) { toast({ title: result.error || "Import failed", variant: "destructive" }); return; }
      setImportResult(result);
      queryClient.invalidateQueries({ queryKey: ["sites"] });
      toast({ title: `Imported ${result.inserted} sites successfully` });
    } catch {
      toast({ title: "Import failed", variant: "destructive" });
    } finally {
      setImporting(false);
    }
  };

  const regions = [...new Set(sites.map((s) => s.region).filter(Boolean))].sort();

  const filteredSites = sites.filter((s) => {
    const matchSearch = !searchTerm ||
      s.name.toLowerCase().includes(searchTerm.toLowerCase()) ||
      s.region?.toLowerCase().includes(searchTerm.toLowerCase()) ||
      s.city?.toLowerCase().includes(searchTerm.toLowerCase()) ||
      s.siteLabel?.toLowerCase().includes(searchTerm.toLowerCase());
    const activeRegion = supervisorRegion || regionFilter;
    const matchRegion = !activeRegion || s.region?.toUpperCase() === activeRegion.toUpperCase();
    return matchSearch && matchRegion;
  });

  const sampleCsv = `sitename,regionname,districtname,cityname,cowstatus,sitelabel,lat,lng,nextfuelingplan,lastf
  uelingdate,lastfuelingqty
COW531,Central,Al Olaya,Riyadh,ON-AIR,Label-A,24.6877,46.7219,2025-04-10,2025-03-25,500
COW532,Western,Al Aziziyah,Jeddah,OFF-AIR,Label-B,21.3891,39.8579,2025-04-12,2025-03-28,300`;

  return (
    <div className="space-y-6">
      {/* Header row */}
      <div className="flex flex-col sm:flex-row justify-between items-start sm:items-center gap-4">
        <div className="flex gap-3 flex-wrap">
          <div className="relative w-72">
            <Search className="absolute left-3 top-1/2 -translate-y-1/2 text-slate-400 w-4 h-4" />
            <Input
              placeholder="Search sites..."
              className="pl-10 h-11 bg-white border-slate-200 rounded-xl shadow-sm"
              value={searchTerm}
              onChange={(e) => setSearchTerm(e.target.value)}
            />
          </div>
          {supervisorRegion ? (
            <div className="h-11 px-3 rounded-xl border border-slate-200 bg-slate-50 text-sm text-slate-700 font
  -medium flex items-center">
              {formatRegion(supervisorRegion)}
            </div>
          ) : (
            <select
```

```
            className="h-11 px-3 rounded-xl border border-slate-200 bg-white text-sm text-slate-700 shadow-sm
focus:outline-none focus:ring-2 focus:ring-primary/20"
            value={regionFilter}
            onChange={(e) => setRegionFilter(e.target.value)}
          >
            <option value="">All Regions</option>
            {regions.map((r) => <option key={r} value={r}>{formatRegion(r)}</option>)}
          </select>
        )}
      </div>

      <div className="flex gap-2 flex-wrap">
        {/* Import CSV */}
        <Dialog open={isImportOpen} onOpenChange={(o) => { setIsImportOpen(o); if (!o) { setCsvText(""); setIm
portResult(null); } }}>
          <DialogTrigger asChild>
            <Button variant="outline" className="h-11 px-4 rounded-xl border-slate-200 gap-2">
              <Upload className="w-4 h-4" /> Import CSV
            </Button>
          </DialogTrigger>
          <DialogContent className="sm:max-w-2xl rounded-3xl p-6">
            <DialogHeader className="mb-4">
              <DialogTitle className="text-2xl font-display">Import Sites from CSV / Google Sheets</DialogTitl
e>
            </DialogHeader>

            <p className="text-sm text-slate-500 mb-3">
              Paste your CSV data below. Accepted column headers (case-insensitive):
            </p>
            <div className="flex flex-wrap gap-1.5 mb-4">
              {["sitename", "regionname", "districtname", "cityname", "cowstatus", "sitelabel", "lat", "lng",
"nextfuelingplan", "lastfuelingdate", "lastfuelingqty"].map((h) => (
                <span key={h} className="text-xs font-mono bg-slate-100 text-slate-700 px-2 py-0.5 rounded">{h
}</span>
              ))}
            </div>

            <div className="mb-3">
              <button
                className="text-xs text-primary underline"
                onClick={() => setCsvText(sampleCsv)}
              >
                Load sample CSV
              </button>
            </div>

            <textarea
              className="w-full h-48 font-mono text-xs p-3 border border-slate-200 rounded-xl bg-slate-50 focu
s:outline-none focus:ring-2 focus:ring-primary/20 resize-none"
              placeholder="Paste CSV here (first row = headers)..."
              value={csvText}
              onChange={(e) => setCsvText(e.target.value)}
```

```
            />

            {importResult && (
              <div className={`mt-3 p-3 rounded-xl text-sm ${importResult.errors.length > 0 ? "bg-amber-50 bor
der border-amber-200" : "bg-emerald-50 border border-emerald-200"}`}>
                <div className="font-semibold mb-1">
                  ? {importResult.inserted} inserted  •  {importResult.skipped} skipped  • 
; {importResult.total} total rows
                </div>
                {importResult.errors.map((e, i) => (
                  <div key={i} className="text-red-600 text-xs flex gap-1 mt-1">
                    <AlertCircle className="w-3.5 h-3.5 mt-0.5 shrink-0" /> {e}
                  </div>
                ))}
              </div>
            )}

            <Button
              className="w-full h-12 rounded-xl mt-4 text-base"
              onClick={handleImport}
              disabled={importing || !csvText.trim()}
            >
              {importing ? "Importing..." : "Import Sites"}
            </Button>
          </DialogContent>
        </Dialog>

        {/* Add Site */}
        <Button className="h-11 px-5 rounded-xl bg-primary hover:bg-primary/90 text-white shadow-lg shadow-pri
mary/25 gap-2" onClick={openAddSite}>
          <Plus className="w-4 h-4" /> Add Site
        </Button>
        <Dialog open={isAddOpen} onOpenChange={(o) => { if (!o) { setIsAddOpen(false); setEditSiteId(null); }
}}>
          <DialogContent className="sm:max-w-lg rounded-3xl p-6">
            <DialogHeader className="mb-4">
              <DialogTitle className="text-2xl font-display">{editSiteId ? "Edit Site" : "Add New Site"}</Dial
ogTitle>
            </DialogHeader>
            <Form {...form}>
              <form onSubmit={form.handleSubmit(onSubmit)} className="grid grid-cols-2 gap-3">
                <FormField control={form.control} name="name" render={({ field }) => (
                  <FormItem className="col-span-2">
                    <FormLabel>Site Name / ID *</FormLabel>
                    <FormControl><Input placeholder="e.g. COW531" className="h-11 rounded-xl" {...field} /></F
ormControl>
                    <FormMessage />
                  </FormItem>
                )} />
                <FormField control={form.control} name="region" render={({ field }) => (
                  <FormItem>
                    <FormLabel>Region</FormLabel>
```

```
                    <FormControl>
                      <select className="w-full h-11 px-3 rounded-xl border border-input bg-background text-sm
" {...field}>
                        <option value="">Select region...</option>
                        <option value="CENTRAL">Central</option>
                        <option value="EAST">East</option>
                      </select>
                    </FormControl>
                  </FormItem>
                )} />
                <FormField control={form.control} name="district" render={({ field }) => (
                  <FormItem>
                    <FormLabel>District</FormLabel>
                    <FormControl><Input placeholder="Al Olaya" className="h-11 rounded-xl" {...field} /></Form
Control>
                  </FormItem>
                )} />
                <FormField control={form.control} name="city" render={({ field }) => (
                  <FormItem>
                    <FormLabel>City</FormLabel>
                    <FormControl><Input placeholder="Riyadh" className="h-11 rounded-xl" {...field} /></FormCo
ntrol>
                  </FormItem>
                )} />
                <FormField control={form.control} name="cowStatus" render={({ field }) => (
                  <FormItem>
                    <FormLabel>COW Status</FormLabel>
                    <FormControl>
                      <select className="w-full h-11 px-3 rounded-xl border border-input bg-background text-sm
" {...field}>
                        <option value="ON-AIR">ON-AIR</option>
                        <option value="OFF-AIR">OFF-AIR</option>
                        <option value="MAINTENANCE">MAINTENANCE</option>
                      </select>
                    </FormControl>
                  </FormItem>
                )} />
                <FormField control={form.control} name="lat" render={({ field }) => (
                  <FormItem>
                    <FormLabel>Latitude</FormLabel>
                    <FormControl><Input placeholder="24.6877" className="h-11 rounded-xl" {...field} /></FormC
ontrol>
                  </FormItem>
                )} />
                <FormField control={form.control} name="lng" render={({ field }) => (
                  <FormItem>
                    <FormLabel>Longitude</FormLabel>
                    <FormControl><Input placeholder="46.7219" className="h-11 rounded-xl" {...field} /></FormC
ontrol>
                  </FormItem>
                )} />
                <FormField control={form.control} name="siteLabel" render={({ field }) => (
```

```
                  <FormItem>
                    <FormLabel>Site Label</FormLabel>
                    <FormControl><Input placeholder="Label-A" className="h-11 rounded-xl" {...field} /></FormC
ontrol>
                  </FormItem>
                )} />
                <FormField control={form.control} name="nextFuelingPlan" render={({ field }) => (
                  <FormItem>
                    <FormLabel>Next Fueling Plan</FormLabel>
                    <FormControl><Input placeholder="2025-04-10" className="h-11 rounded-xl" {...field} /></Fo
rmControl>
                  </FormItem>
                )} />
                <Button type="submit" className="col-span-2 h-12 rounded-xl mt-3 text-base shadow-lg shadow-pr
imary/20" disabled={createMutation.isPending || updateMutation.isPending}>
                  {(createMutation.isPending || updateMutation.isPending) ? "Saving..." : (editSiteId ? "Updat
e Site" : "Save Site")}
                </Button>
              </form>
            </Form>
          </DialogContent>
        </Dialog>
      </div>
    </div>

    {/* Stats row */}
    <div className="grid grid-cols-2 sm:grid-cols-4 gap-4">
      {[
        { label: "Total Sites", value: sites.length, color: "text-slate-900" },
        { label: "ON-AIR", value: sites.filter(s => s.cowStatus === "ON-AIR").length, color: "text-emerald-600
" },
        { label: "OFF-AIR", value: sites.filter(s => s.cowStatus === "OFF-AIR").length, color: "text-red-600"
},
        { label: "Regions", value: regions.length, color: "text-primary" },
      ].map((stat) => (
        <Card key={stat.label} className="glass-panel border-0 shadow-md">
          <CardContent className="p-4">
            <p className="text-xs text-slate-500 font-medium uppercase tracking-wide">{stat.label}</p>
            <p className={`text-3xl font-bold mt-1 ${stat.color}`}>{stat.value}</p>
          </CardContent>
        </Card>
      ))}
    </div>

    {/* Table */}
    <Card className="glass-panel border-0 shadow-xl shadow-slate-200/50 overflow-hidden">
      <Table>
        <TableHeader className="bg-slate-50 border-b border-slate-100">
          <TableRow className="hover:bg-transparent">
            <TableHead className="font-semibold text-slate-600 h-12">Site Name</TableHead>
            <TableHead className="font-semibold text-slate-600">Region</TableHead>
            <TableHead className="font-semibold text-slate-600">City / District</TableHead>
```

```
            <TableHead className="font-semibold text-slate-600">COW Status</TableHead>
            <TableHead className="font-semibold text-slate-600">Coordinates</TableHead>
            <TableHead className="font-semibold text-slate-600">Next Fueling</TableHead>
            <TableHead className="font-semibold text-slate-600">Last Fueling</TableHead>
            <TableHead className="text-right font-semibold text-slate-600">Actions</TableHead>
          </TableRow>
        </TableHeader>
        <TableBody>
          {isLoading ? (
            <TableRow>
              <TableCell colSpan={8} className="h-32 text-center text-slate-500">Loading sites...</TableCell>
            </TableRow>
          ) : filteredSites.length === 0 ? (
            <TableRow>
              <TableCell colSpan={8} className="h-32 text-center">
                <div className="flex flex-col items-center justify-center text-slate-400">
                  <MapPin className="w-8 h-8 mb-2 opacity-50" />
                  <p>{searchTerm || regionFilter ? "No sites match your filters" : "No sites yet   add one or
import from CSV"}</p>
                </div>
              </TableCell>
            </TableRow>
          ) : (
            filteredSites.map((site) => (
              <TableRow key={site.id} className="hover:bg-slate-50/50 transition-colors border-slate-50">
                <TableCell>
                  <div className="font-semibold text-slate-900">{site.name}</div>
                  {site.siteLabel && <div className="text-xs text-slate-400">{site.siteLabel}</div>}
                </TableCell>
                <TableCell className="text-slate-700">{formatRegion(site.region) || <span className="text-slat
e-300"> </span>}</TableCell>
                <TableCell>
                  <div className="text-sm text-slate-900">{site.city || " "}</div>
                  {site.district && <div className="text-xs text-slate-400">{site.district}</div>}
                </TableCell>
                <TableCell>
                  <span className={`inline-flex items-center gap-1 text-xs font-medium px-2.5 py-1 rounded-lg
border ${COW_STATUS_COLORS[site.cowStatus] ?? "bg-slate-50 text-slate-600 border-slate-200"}`}>
                    {site.cowStatus === "ON-AIR" ? <CheckCircle2 className="w-3 h-3" /> : <XCircle className="
w-3 h-3" />}
                    {site.cowStatus}
                  </span>
                </TableCell>
                <TableCell>
                  {site.lat != null && site.lng != null ? (
                    <a
                      href={`https://maps.google.com/?q=${site.lat},${site.lng}`}
                      target="_blank"
                      rel="noopener noreferrer"
                      className="text-xs text-primary hover:underline flex items-center gap-1"
                    >
                      <MapPin className="w-3 h-3" />
```

```
                      {site.lat.toFixed(4)}, {site.lng.toFixed(4)}
                    </a>
                  ) : <span className="text-slate-300 text-xs"> </span>}
                </TableCell>
                <TableCell className="text-sm text-slate-700">{site.nextFuelingPlan || <span className="text-s
  late-300"> </span>}</TableCell>
                <TableCell>
                  {site.lastFuelingDate ? (
                    <div>
                      <div className="text-sm text-slate-700">{site.lastFuelingDate}</div>
                      {site.lastFuelingQty != null && <div className="text-xs text-slate-400">{site.lastFuelin
  gQty} L</div>}
                    </div>
                  ) : <span className="text-slate-300 text-xs"> </span>}
                </TableCell>
                <TableCell className="text-right">
                  <div className="flex items-center justify-end gap-1">
                    <Button
                      variant="ghost"
                      size="icon"
                      className="h-8 w-8 text-slate-400 hover:text-primary hover:bg-primary/10 rounded-lg tran
  sition-colors"
                      onClick={() => openEditSite(site)}
                    >
                      <Pencil className="w-4 h-4" />
                    </Button>
                    <Button
                      variant="ghost"
                      size="icon"
                      className="h-8 w-8 text-slate-400 hover:text-destructive hover:bg-destructive/10 rounded
  -lg transition-colors"
                      onClick={() => {
                        if (confirm(‘Delete site "${site.name}"?‘)) {
                          deleteMutation.mutate(site.id, {
                            onSuccess: () => toast({ title: "Site deleted" }),
                          });
                        }
                      }}
                    >
                      <Trash2 className="w-4 h-4" />
                    </Button>
                  </div>
                </TableCell>
              </TableRow>
            ))
          )}
        </TableBody>
      </Table>
    </Card>
  </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/driver/DriverDashboard.tsx
SIZE: 5,202 bytes

```
import { useAuth } from "@/lib/auth-context";
import { useDriverTasks } from "@/hooks/use-drivers";
import { Card, CardContent } from "@/components/ui/card";
import { MapPin, Calendar, Droplets, ChevronRight, Clock } from "lucide-react";
import { Link } from "wouter";

const statusConfig: Record<string, { color: string, icon: React.ElementType }> = {
  "Creation": { color: "text-amber-500 bg-amber-500/10 border-amber-500/20", icon: Clock },
  "Finished by Driver": { color: "text-sky-500 bg-sky-500/10 border-sky-500/20", icon: Droplets },
  "Task approved": { color: "text-emerald-500 bg-emerald-500/10 border-emerald-500/20", icon: CheckCircle2 },
};

import { CheckCircle2 } from "lucide-react";

export default function DriverDashboard() {
  const { user } = useAuth();
  const { data: tasks, isLoading } = useDriverTasks(user?.driverId || 0);

  if (isLoading) {
    return (
      <div className="h-[50vh] flex flex-col items-center justify-center gap-4 text-slate-500">
        <div className="animate-spin rounded-full h-10 w-10 border-b-2 border-primary"></div>
        <p>Loading your routes...</p>
      </div>
    );
  }

  const activeTasks = tasks?.filter(t => t.status !== "Finished by Driver" && t.status !== "Task approved") || [
  ];
  const completedTasks = tasks?.filter(t => t.status === "Finished by Driver" || t.status === "Task approved") |
  | [];

  return (
    <div className="space-y-6 animate-in fade-in slide-in-from-bottom-4 duration-500">
      {/* Stats Summary */}
      <div className="grid grid-cols-2 gap-4">
        <div className="bg-slate-900 border border-slate-800 rounded-3xl p-5 shadow-lg shadow-black/20">
          <div className="text-3xl font-display font-bold text-white mb-1">{activeTasks.length}</div>
          <div className="text-xs text-slate-400 font-medium uppercase tracking-wider">Pending</div>
        </div>
        <div className="bg-primary/20 border border-primary/30 rounded-3xl p-5 shadow-lg shadow-primary/10">
          <div className="text-3xl font-display font-bold text-primary-foreground mb-1">{completedTasks.length}<
  /div>
          <div className="text-xs text-primary-foreground/70 font-medium uppercase tracking-wider">Completed</di
  v>
        </div>
      </div>

      <div className="space-y-4">
```

```
      <h2 className="text-lg font-display font-bold text-white flex items-center gap-2">
        Current Missions
        <span className="bg-slate-800 text-slate-300 text-xs px-2 py-0.5 rounded-full">{activeTasks.length}</s
pan>
      </h2>

      {activeTasks.length === 0 ? (
        <div className="text-center py-10 bg-slate-900/50 rounded-3xl border border-slate-800 border-dashed">
          <CheckCircle2 className="w-12 h-12 text-slate-700 mx-auto mb-3" />
          <p className="text-slate-500">You have no pending missions.</p>
        </div>
      ) : (
        <div className="space-y-4">
          {activeTasks.map(task => (
            <Link key={task.id} href={`/driver/mission/${task.id}`}>
              <Card className="bg-slate-900 border-slate-800 rounded-3xl overflow-hidden hover:bg-slate-800 tr
ansition-colors active:scale-[0.98] cursor-pointer">
                <CardContent className="p-0">
                  <div className="p-5 border-b border-slate-800">
                    <div className="flex justify-between items-start mb-3">
                      <div className="bg-slate-950 px-3 py-1 rounded-lg text-xs font-mono text-slate-400 borde
r border-slate-800">
                        {task.missionId || `MSN-${task.id}`}
                      </div>
                      <div className={`px-2.5 py-1 text-[10px] font-bold uppercase tracking-wider rounded-lg b
order ${statusConfig[task.status]?.color || statusConfig['Creation'].color}`}>
                        {task.status}
                      </div>
                    </div>
                    <h3 className="text-xl font-bold text-white mb-1">{task.siteName}</h3>
                    <div className="flex items-center text-sm text-slate-400 gap-4 mt-3">
                      <span className="flex items-center gap-1.5"><MapPin className="w-4 h-4 text-primary" />
Riyadh Zone</span>
                      <span className="flex items-center gap-1.5"><Calendar className="w-4 h-4 text-primary" /
> Today</span>
                    </div>
                  </div>
                  <div className="bg-slate-950/50 px-5 py-4 flex justify-between items-center group">
                    <div className="flex items-center gap-2 text-slate-300 font-medium">
                      <Droplets className="w-5 h-5 text-accent" />
                      Target: {task.requiredLiters || 0} L
                    </div>
                    <div className="w-8 h-8 rounded-full bg-slate-800 flex items-center justify-center group-h
over:bg-primary transition-colors">
                      <ChevronRight className="w-5 h-5 text-slate-400 group-hover:text-white" />
                    </div>
                  </div>
                </CardContent>
              </Card>
            </Link>
          ))}
        </div>
```

```
        )}
      </div>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/driver/DriverLogin.tsx
SIZE: 4,557 bytes

```
import { useState } from "react";
import { useAuth } from "@/lib/auth-context";
import { Input } from "@/components/ui/input";
import { Button } from "@/components/ui/button";
import { Mail, Lock, Loader2, ArrowRight } from "lucide-react";
import { useDriverLogin } from "@workspace/api-client-react";
import { useLocation } from "wouter";

export default function DriverLogin() {
  const { loginDriver } = useAuth();
  const [, setLocation] = useLocation();
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [error, setError] = useState("");

  const loginMutation = useDriverLogin();

  const handleLogin = (e: React.FormEvent) => {
    e.preventDefault();
    setError("");

    loginMutation.mutate({ data: { email, password } }, {
      onSuccess: (data) => {
        if (data.success && data.driverId) {
          loginDriver(data.driverId, data.name || email.split("@")[0]);
          setLocation("/driver/dashboard");
        } else {
          setError("Invalid email or password");
        }
      },
      onError: () => {
        setError("Invalid email or password. Please try again.");
      }
    });
  };

  return (
    <div className="min-h-screen w-full bg-slate-950 flex flex-col justify-center relative overflow-hidden sm:it
  ems-center">
      {/* Background Graphic for Mobile */}
      <div className="absolute inset-0 z-0">
        <img
          src={`${import.meta.env.BASE_URL}images/driver-bg.png`}
          alt="Abstract background"
          className="w-full h-full object-cover opacity-40 mix-blend-screen"
        />
        <div className="absolute inset-0 bg-gradient-to-t from-slate-950 via-slate-950/80 to-transparent" />
      </div>
```

```
    <div className="relative z-10 w-full max-w-md px-6 py-12 flex flex-col items-center">
      <div className="mb-8">
        <img
          src={`${import.meta.env.BASE_URL}images/aces-logo.png`}
          alt="ACES Logo"
          className="h-20 object-contain drop-shadow-2xl"
        />
      </div>

      <div className="w-full text-center mb-8">
        <h1 className="text-3xl font-display font-bold text-white mb-2">Driver Portal</h1>
        <p className="text-slate-400">Access your tasks and routes</p>
      </div>

      <form onSubmit={handleLogin} className="w-full space-y-4">
        {error && (
          <div className="bg-destructive/20 text-red-200 px-4 py-3 rounded-2xl text-sm font-medium border bord
er-destructive/30 text-center backdrop-blur-md">
            {error}
          </div>
        )}

        <div className="space-y-1">
          <div className="relative">
            <Mail className="absolute left-4 top-1/2 -translate-y-1/2 w-5 h-5 text-slate-500" />
            <Input
              value={email}
              onChange={(e) => setEmail(e.target.value)}
              className="pl-12 h-14 rounded-2xl bg-white/10 border-white/10 text-white placeholder:text-slate-
500 focus-visible:ring-primary focus-visible:bg-white/20 transition-all text-base backdrop-blur-md"
              placeholder="Driver Email"
            />
          </div>
        </div>

        <div className="space-y-1">
          <div className="relative">
            <Lock className="absolute left-4 top-1/2 -translate-y-1/2 w-5 h-5 text-slate-500" />
            <Input
              type="password"
              value={password}
              onChange={(e) => setPassword(e.target.value)}
              className="pl-12 h-14 rounded-2xl bg-white/10 border-white/10 text-white placeholder:text-slate-
500 focus-visible:ring-primary focus-visible:bg-white/20 transition-all text-base backdrop-blur-md"
              placeholder="Password"
            />
          </div>
        </div>

        <div className="pt-4">
          <Button
            type="submit"
```

```
            disabled={loginMutation.isPending}
            className="w-full h-14 rounded-2xl bg-primary hover:bg-primary/90 text-white font-bold text-lg sha
  dow-xl shadow-primary/30 transition-all group"
          >
            {loginMutation.isPending ? (
              <Loader2 className="w-6 h-6 animate-spin" />
            ) : (
              <>
                Sign In
                <ArrowRight className="w-5 h-5 ml-2 group-hover:translate-x-1 transition-transform" />
              </>
            )}
          </Button>
        </div>
      </form>
    </div>
  </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/driver/DriverMissionDetail.tsx
SIZE: 4,889 bytes

```
import { useEffect, useState } from "react";
import { useLocation, useParams } from "wouter";
import { Card, CardContent, CardHeader, CardTitle } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { Input } from "@/components/ui/input";
import { Label } from "@/components/ui/label";
import { Textarea } from "@/components/ui/textarea";
import { Badge } from "@/components/ui/badge";
import { ArrowLeft, Loader2 } from "lucide-react";
import { useAuth } from "@/lib/auth-context";

export default function DriverMissionDetail() {
  const { user } = useAuth();
  const params = useParams<{ id: string }>();
  const [, setLocation] = useLocation();
  const [task, setTask] = useState<any | null>(null);
  const [isLoading, setIsLoading] = useState(true);
  const [isSubmitting, setIsSubmitting] = useState(false);
  const [entry, setEntry] = useState({
    actualInTank: "",
    quantityAdded: "",
    observations: "",
  });

  useEffect(() => {
    const fetchTask = async () => {
      try {
        const res = await fetch(`/api/driver/tasks/${params.id}`);
        if (res.ok) setTask(await res.json());
      } finally {
        setIsLoading(false);
      }
    };
    fetchTask();
  }, [params.id]);

  const onSubmit = async () => {
    setIsSubmitting(true);
    try {
      await fetch(`/api/driver/tasks/${params.id}`, {
        method: "PUT",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({
          status: "completed",
          actualInTank: Number(entry.actualInTank),
          quantityAdded: Number(entry.quantityAdded),
          observations: entry.observations,
        }),
      });
```

```
    setLocation("/driver/dashboard");
  } finally {
    setIsSubmitting(false);
  }
};

if (isLoading) return (
  <div className="flex items-center justify-center h-48">
    <Loader2 className="w-8 h-8 animate-spin text-primary" />
  </div>
);

if (!task) return (
  <div className="text-center py-16 text-slate-500">Task not found</div>
);

const statusColors: Record<string, string> = {
  pending: "bg-orange-100 text-orange-700",
  in_progress: "bg-sky-100 text-sky-700",
  completed: "bg-emerald-100 text-emerald-700",
};

return (
  <div className="space-y-4">
    <div className="flex items-center gap-3">
      <Button variant="ghost" size="icon" onClick={() => setLocation("/driver/dashboard")}>
        <ArrowLeft className="w-5 h-5" />
      </Button>
      <h1 className="text-xl font-bold">Mission Detail</h1>
    </div>

    <Card className="border-0 shadow-sm">
      <CardHeader>
        <CardTitle className="text-lg">{task.siteName}</CardTitle>
        <Badge className={statusColors[task.status] || "bg-slate-100 text-slate-600"}>
          {task.status?.replace(/_/g, " ")}
        </Badge>
      </CardHeader>
      <CardContent className="space-y-2 text-sm">
        <div className="flex justify-between">
          <span className="text-slate-500">Mission ID</span>
          <span className="font-medium">{task.missionId || task.id}</span>
        </div>
        <div className="flex justify-between">
          <span className="text-slate-500">Required Liters</span>
          <span className="font-medium">{task.requiredLiters} L</span>
        </div>
        {task.notes && (
          <div className="pt-2">
            <span className="text-slate-500">Notes:</span>
            <p className="text-slate-700 mt-1">{task.notes}</p>
          </div>
```

```
          )}
        </CardContent>
      </Card>

      {task.status !== "completed" && (
        <Card className="border-0 shadow-sm">
          <CardContent className="p-4 space-y-4">
            <h2 className="font-semibold">Submit Fuel Entry</h2>
            <div>
              <Label>Actual Liters in Tank</Label>
              <Input type="number" value={entry.actualInTank} onChange={(e) => setEntry((f) => ({ ...f, actualIn
  Tank: e.target.value }))} placeholder="0" />
            </div>
            <div>
              <Label>Quantity Added (L)</Label>
              <Input type="number" value={entry.quantityAdded} onChange={(e) => setEntry((f) => ({ ...f, quantit
  yAdded: e.target.value }))} placeholder="0" />
            </div>
            <div>
              <Label>Observations</Label>
              <Textarea value={entry.observations} onChange={(e) => setEntry((f) => ({ ...f, observations: e.tar
  get.value }))} placeholder="Any notes or observations..." rows={3} />
            </div>
            <Button onClick={onSubmit} disabled={isSubmitting || !entry.actualInTank || !entry.quantityAdded} cl
  assName="w-full">
              {isSubmitting ? <Loader2 className="w-4 h-4 animate-spin mr-2" /> : null}
              Submit & Complete
            </Button>
          </CardContent>
        </Card>
      )}
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/driver/DriverNotifications.tsx
SIZE: 2,505 bytes

```
import { useEffect, useState } from "react";
import { Card, CardContent } from "@/components/ui/card";
import { Badge } from "@/components/ui/badge";
import { Bell, Loader2 } from "lucide-react";
import { useAuth } from "@/lib/auth-context";

interface DriverNotification {
  id: number;
  title: string;
  message: string;
  type: string;
  read: boolean;
  createdAt: string;
}

export default function DriverNotifications() {
  const { user } = useAuth();
  const [notifications, setNotifications] = useState<DriverNotification[]>([]);
  const [isLoading, setIsLoading] = useState(true);

  useEffect(() => {
    const load = async () => {
      try {
        const res = await fetch(`/api/driver/notifications?driverId=${user?.driverId}`);
        if (res.ok) setNotifications(await res.json());
      } finally {
        setIsLoading(false);
      }
    };
    if (user?.driverId) load();
  }, [user?.driverId]);

  const typeColors: Record<string, string> = {
    info: "bg-sky-100 text-sky-700",
    warning: "bg-amber-100 text-amber-700",
    success: "bg-emerald-100 text-emerald-700",
    error: "bg-red-100 text-red-700",
  };

  return (
    <div className="space-y-4">
      <h1 className="text-xl font-bold flex items-center gap-2">
        <Bell className="w-5 h-5 text-primary" /> Notifications
      </h1>
      {isLoading ? (
        <div className="flex justify-center py-10"><Loader2 className="w-6 h-6 animate-spin text-primary" /></di
v>
      ) : notifications.length === 0 ? (
        <div className="text-center py-16 text-slate-400">No notifications yet</div>
```

```
      ) : (
        <div className="space-y-3">
          {notifications.map((n) => (
            <Card key={n.id} className={`border-0 shadow-sm ${!n.read ? "border-l-4 border-primary" : ""}`}>
              <CardContent className="p-4">
                <div className="flex items-start justify-between gap-3">
                  <div>
                    <div className="font-semibold">{n.title}</div>
                    <div className="text-sm text-slate-600 mt-1">{n.message}</div>
                    <div className="text-xs text-slate-400 mt-2">
                      {n.createdAt ? new Date(n.createdAt).toLocaleString() : ""}
                    </div>
                  </div>
                  <Badge className={typeColors[n.type] || "bg-slate-100 text-slate-600"}>{n.type}</Badge>
                </div>
              </CardContent>
            </Card>
          ))}
        </div>
      )}
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/driver/DriverSettings.tsx
SIZE: 1,987 bytes

```
import { useAuth } from "@/lib/auth-context";
import { Card, CardContent, CardHeader, CardTitle } from "@/components/ui/card";
import { Button } from "@/components/ui/button";
import { LogOut, User, Smartphone } from "lucide-react";

export default function DriverSettings() {
  const { user, logout } = useAuth();

  return (
    <div className="space-y-4">
      <h1 className="text-xl font-bold">Settings</h1>

      <Card className="border-0 shadow-sm">
        <CardHeader>
          <CardTitle className="text-base flex items-center gap-2">
            <User className="w-5 h-5 text-primary" /> Profile
          </CardTitle>
        </CardHeader>
        <CardContent className="space-y-2 text-sm">
          <div className="flex justify-between">
            <span className="text-slate-500">Name</span>
            <span className="font-medium">{user?.username}</span>
          </div>
          <div className="flex justify-between">
            <span className="text-slate-500">Driver ID</span>
            <span className="font-medium">#{user?.driverId}</span>
          </div>
        </CardContent>
      </Card>

      <Card className="border-0 shadow-sm">
        <CardHeader>
          <CardTitle className="text-base flex items-center gap-2">
            <Smartphone className="w-5 h-5 text-primary" /> App Info
          </CardTitle>
        </CardHeader>
        <CardContent className="space-y-2 text-sm">
          <div className="flex justify-between">
            <span className="text-slate-500">Platform</span>
            <span className="font-medium">Web</span>
          </div>
          <div className="flex justify-between">
            <span className="text-slate-500">Version</span>
            <span className="font-medium">1.0.0</span>
          </div>
        </CardContent>
      </Card>

      <Button variant="destructive" className="w-full gap-2" onClick={logout}>
```

```
        <LogOut className="w-4 h-4" /> Sign Out
      </Button>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/not-found.tsx
SIZE: 711 bytes

```
import { Card, CardContent } from "@/components/ui/card";
import { AlertCircle } from "lucide-react";

export default function NotFound() {
  return (
    <div className="min-h-screen w-full flex items-center justify-center bg-gray-50">
      <Card className="w-full max-w-md mx-4">
        <CardContent className="pt-6">
          <div className="flex mb-4 gap-2">
            <AlertCircle className="h-8 w-8 text-red-500" />
            <h1 className="text-2xl font-bold text-gray-900">404 Page Not Found</h1>
          </div>

          <p className="mt-4 text-sm text-gray-600">
            Did you forget to add the page to the router?
          </p>
        </CardContent>
      </Card>
    </div>
  );
}
```

FILE: artifacts/web-portal/src/pages/PrivacyPolicy.tsx
SIZE: 5,851 bytes

```
export default function PrivacyPolicy() {
  return (
    <div style={{ fontFamily: "sans-serif", maxWidth: 800, margin: "0 auto", padding: "40px 24px", color: "#1a1a
  1a", lineHeight: 1.7 }}>
      <div style={{ marginBottom: 32 }}>
        <img src="/images/logo.png" alt="ACES Logo" style={{ height: 48, marginBottom: 16 }} />
        <h1 style={{ fontSize: 28, fontWeight: 700, margin: "0 0 4px" }}>Privacy Policy</h1>
        <p style={{ color: "#666", margin: 0 }}>ACES-MSD Fueling   Technician App</p>
        <p style={{ color: "#666", fontSize: 14, margin: "4px 0 0" }}>Last updated: May 2025</p>
      </div>

      <section style={{ marginBottom: 28 }}>
        <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>1. Overview</h2>
        <p>
          The ACES-MSD Fueling app ("App") is developed and operated by Advanced Communications and Electronics
  Systems Company ("ACES", "we", "our"). This App is intended exclusively for internal use by authorised ACES fiel
  d technicians and drivers. This Privacy Policy explains what data we collect, how it is used, and how it is prot
  ected.
        </p>
      </section>

      <section style={{ marginBottom: 28 }}>
        <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>2. Data We Collect</h2>
        <ul style={{ paddingLeft: 20 }}>
          <li><strong>Account information:</strong> Name, email address, and employee zone provided at login.</l
  i>
          <li><strong>Mission data:</strong> Fuel delivery records, odometer readings, tank readings, and missio
  n completion reports submitted through the App.</li>
          <li><strong>Photos:</strong> Images of odometer meters and fuel tank readings captured for mission doc
  umentation.</li>
          <li><strong>Location:</strong> GPS coordinates recorded when logging fuel delivery activities in the f
  ield.</li>
          <li><strong>Device token:</strong> A push notification token used to deliver mission alerts to your de
  vice.</li>
        </ul>
      </section>

      <section style={{ marginBottom: 28 }}>
        <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>3. How We Use Your Data
  </h2>
        <ul style={{ paddingLeft: 20 }}>
          <li>To assign, track, and complete fuel delivery missions.</li>
          <li>To generate operational reports for ACES management.</li>
          <li>To send push notifications about new or updated mission assignments.</li>
          <li>To maintain accurate records of field activities for audit and compliance purposes.</li>
        </ul>
      </section>

      <section style={{ marginBottom: 28 }}>
```

```
      <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>4. Camera &amp;amp; Photos</h2>
      <p>
        The App requests access to your device’s camera and photo library solely to photograph odometer readings and fuel tank levels as part of mission documentation. Images are uploaded securely to ACES internal servers and are not shared with any third parties.
      </p>
    </section>

    <section style={{ marginBottom: 28 }}>
      <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>5. Location</h2>
      <p>
        Location data is collected when you log a fuel delivery activity to record the site of the operation. Location access is used only while the App is in use and is not tracked in the background. Location data is stored on ACES internal servers and is not shared with third parties.
      </p>
    </section>

    <section style={{ marginBottom: 28 }}>
      <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>6. Data Sharing</h2>
      <p>
        We do not sell, rent, or share your personal data with any third parties. Data is accessible only to authorised ACES operations staff for internal management purposes.
      </p>
    </section>

    <section style={{ marginBottom: 28 }}>
      <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>7. Data Security</h2>
      <p>
        All data transmitted between the App and ACES servers is encrypted using HTTPS/TLS. Access to the system is protected by authenticated login credentials. We apply industry-standard security practices to protect your information.
      </p>
    </section>

    <section style={{ marginBottom: 28 }}>
      <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>8. Data Retention</h2>
      <p>
        Mission records and associated data are retained for as long as required for operational, audit, and legal compliance purposes. Employee account data is removed upon termination of employment or system access.
      </p>
    </section>

    <section style={{ marginBottom: 28 }}>
      <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>9. Your Rights</h2>
      <p>
        If you have questions about the data we hold about you or wish to request correction or deletion, please contact your ACES system administrator or reach us at the address below.
      </p>
    </section>

    <section style={{ marginBottom: 28 }}>
```

```
        <h2 style={{ fontSize: 18, fontWeight: 600, color: "#002D62", marginBottom: 8 }}>10. Contact</h2>
        <p>
          Advanced Communications and Electronics Systems Company<br />
          Saudi Arabia<br />
          Email: <a href="mailto:info@aces-co.com" style={{ color: "#002D62" }}>info@aces-co.com</a>
        </p>
      </section>

      <div style={{ borderTop: "1px solid #e5e7eb", paddingTop: 20, marginTop: 8, fontSize: 13, color: "#999" }}
  >
        &copy; {new Date().getFullYear()} Advanced Communications and Electronics Systems Company. All rights re
  served.
      </div>
    </div>
  );
}
```

FILE: artifacts/web-portal/tsconfig.json
SIZE: 520 bytes

```
{
  "extends": "../../tsconfig.base.json",
  "include": ["src/**/*"],
  "exclude": ["node_modules", "build", "dist", "**/*.test.ts"],
  "compilerOptions": {
    "noEmit": true,
    "jsx": "preserve",
    "lib": ["esnext", "dom", "dom.iterable"],
    "resolveJsonModule": true,
    "allowImportingTsExtensions": true,
    "moduleResolution": "bundler",
    "types": ["node", "vite/client"],
    "paths": {
      "@/*": ["./src/*"]
    }
  },
  "references": [
    {
      "path": "../../lib/api-client-react"
    }
  ]
}
```

FILE: artifacts/web-portal/vite.config.ts
SIZE: 1,762 bytes

```
import { defineConfig } from "vite";
import react from "@vitejs/plugin-react";
import tailwindcss from "@tailwindcss/vite";
import path from "path";
import runtimeErrorOverlay from "@replit/vite-plugin-runtime-error-modal";

const rawPort = process.env.PORT;

if (!rawPort) {
  throw new Error(
    "PORT environment variable is required but was not provided.",
  );
}

const port = Number(rawPort);

if (Number.isNaN(port) || port <= 0) {
  throw new Error(‘Invalid PORT value: "${rawPort}"‘);
}

const basePath = process.env.BASE_PATH;

if (!basePath) {
  throw new Error(
    "BASE_PATH environment variable is required but was not provided.",
  );
}

export default defineConfig({
  base: basePath,
  plugins: [
    react(),
    tailwindcss(),
    runtimeErrorOverlay(),
    ...(process.env.NODE_ENV !== "production" &&
    process.env.REPL_ID !== undefined
      ? [
          await import("@replit/vite-plugin-cartographer").then((m) =>
            m.cartographer({
              root: path.resolve(import.meta.dirname, ".."),
            }),
          ),
          await import("@replit/vite-plugin-dev-banner").then((m) =>
            m.devBanner(),
          ),
        ]
      : []),
  ],
  resolve: {
```

```
    alias: {
      "@": path.resolve(import.meta.dirname, "src"),
      "@assets": path.resolve(import.meta.dirname, "..", "..", "attached_assets"),
    },
    dedupe: ["react", "react-dom"],
  },
  root: path.resolve(import.meta.dirname),
  build: {
    outDir: path.resolve(import.meta.dirname, "dist/public"),
    emptyOutDir: true,
  },
  server: {
    port,
    host: "0.0.0.0",
    allowedHosts: true,
    fs: {
      strict: true,
      deny: ["**/.*"],
    },
  },
  preview: {
    port,
    host: "0.0.0.0",
    allowedHosts: true,
  },
});
```

FILE: babel.config.js
SIZE: 142 bytes

```
module.exports = function(api) {
  api.cache(true);
  return {
    presets: ['babel-preset-expo'],
    plugins: ['expo-router/babel']
  };
};
```

FILE: eas.json
SIZE: 343 bytes

```
{
  "cli": {
    "version": ">= 14.7.1",
    "appVersionSource": "remote"
  },
  "build": {
    "development": {
      "developmentClient": true,
      "distribution": "internal"
    },
    "preview": {
      "distribution": "internal"
    },
    "production": {
      "autoIncrement": true
    }
  },
  "submit": {
    "production": {}
  }
}
```

FILE: lib/api-client-react/package.json
SIZE: 265 bytes

```
{
  "name": "@workspace/api-client-react",
  "version": "0.0.0",
  "private": true,
  "type": "module",
  "exports": {
    ".": "./src/index.ts"
  },
  "dependencies": {
    "@tanstack/react-query": "catalog:"
  },
  "peerDependencies": {
    "react": ">=18"
  }
}
```

FILE: lib/api-client-react/src/custom-fetch.ts
SIZE: 11,219 bytes

```
export type CustomFetchOptions = RequestInit & {
  responseType?: "json" | "text" | "blob" | "auto";
};

export type ErrorType<T = unknown> = ApiError<T>;

export type BodyType<T> = T;

export type AuthTokenGetter = () => Promise<string | null> | string | null;

const NO_BODY_STATUS = new Set([204, 205, 304]);
const DEFAULT_JSON_ACCEPT = "application/json, application/problem+json";

// ---------------------------------------------------------------------------
// Module-level configuration
// ---------------------------------------------------------------------------

let _baseUrl: string | null = null;
let _authTokenGetter: AuthTokenGetter | null = null;

/**
 * Set a base URL that is prepended to every relative request URL
 * (i.e. paths that start with `/`).
 *
 * Useful for Expo bundles that need to call a remote API server.
 * Pass `null` to clear the base URL.
 */
export function setBaseUrl(url: string | null): void {
  _baseUrl = url ? url.replace(/\/+$/, "") : null;
}

/**
 * Register a getter that supplies a bearer auth token.  Before every fetch
 * the getter is invoked; when it returns a non-null string, an
 * `Authorization: Bearer <token>` header is attached to the request.
 *
 * Useful for Expo bundles making token-gated API calls.
 * Pass `null` to clear the getter.
 */
export function setAuthTokenGetter(getter: AuthTokenGetter | null): void {
  _authTokenGetter = getter;
}

function isRequest(input: RequestInfo | URL): input is Request {
  return typeof Request !== "undefined" && input instanceof Request;
}

function resolveMethod(input: RequestInfo | URL, explicitMethod?: string): string {
  if (explicitMethod) return explicitMethod.toUpperCase();
```

```
  if (isRequest(input)) return input.method.toUpperCase();
  return "GET";
}

// Use loose check for URL   some runtimes (e.g. React Native) polyfill URL
// differently, so ‘instanceof URL‘ can fail.
function isUrl(input: RequestInfo | URL): input is URL {
  return typeof URL !== "undefined" && input instanceof URL;
}

function applyBaseUrl(input: RequestInfo | URL): RequestInfo | URL {
  if (!_baseUrl) return input;
  const url = resolveUrl(input);
  // Only prepend to relative paths (starting with /)
  if (!url.startsWith("/")) return input;

  const absolute = ‘${_baseUrl}${url}‘;
  if (typeof input === "string") return absolute;
  if (isUrl(input)) return new URL(absolute);
  return new Request(absolute, input as Request);
}

function resolveUrl(input: RequestInfo | URL): string {
  if (typeof input === "string") return input;
  if (isUrl(input)) return input.toString();
  return input.url;
}

function mergeHeaders(...sources: Array<HeadersInit | undefined>): Headers {
  const headers = new Headers();

  for (const source of sources) {
    if (!source) continue;
    new Headers(source).forEach((value, key) => {
      headers.set(key, value);
    });
  }

  return headers;
}

function getMediaType(headers: Headers): string | null {
  const value = headers.get("content-type");
  return value ? value.split(";", 1)[0].trim().toLowerCase() : null;
}

function isJsonMediaType(mediaType: string | null): boolean {
  return mediaType === "application/json" || Boolean(mediaType?.endsWith("+json"));
}

function isTextMediaType(mediaType: string | null): boolean {
  return Boolean(
```

```
    mediaType &&
      (mediaType.startsWith("text/") ||
        mediaType === "application/xml" ||
        mediaType === "text/xml" ||
        mediaType.endsWith("+xml") ||
        mediaType === "application/x-www-form-urlencoded"),
  );
}

// Use strict equality: in browsers, ‘response.body‘ is ‘null‘ when the
// response genuinely has no content.  In React Native, ‘response.body‘ is
// always ‘undefined‘ because the ReadableStream API is not implemented
// even when the response carries a full payload readable via ‘.text()‘ or
// ‘.json()‘.  Loose equality (‘== null‘) matches both ‘null‘ and ‘undefined‘,
// which causes every React Native response to be treated as empty.
function hasNoBody(response: Response, method: string): boolean {
  if (method === "HEAD") return true;
  if (NO_BODY_STATUS.has(response.status)) return true;
  if (response.headers.get("content-length") === "0") return true;
  if (response.body === null) return true;
  return false;
}

function stripBom(text: string): string {
  return text.charCodeAt(0) === 0xfeff ? text.slice(1) : text;
}

function looksLikeJson(text: string): boolean {
  const trimmed = text.trimStart();
  return trimmed.startsWith("{") || trimmed.startsWith("[");
}

function getStringField(value: unknown, key: string): string | undefined {
  if (!value || typeof value !== "object") return undefined;

  const candidate = (value as Record<string, unknown>)[key];
  if (typeof candidate !== "string") return undefined;

  const trimmed = candidate.trim();
  return trimmed === "" ? undefined : trimmed;
}

function truncate(text: string, maxLength = 300): string {
  return text.length > maxLength ? ‘${text.slice(0, maxLength - 1)} ‘ : text;
}

function buildErrorMessage(response: Response, data: unknown): string {
  const prefix = ‘HTTP ${response.status} ${response.statusText}‘;

  if (typeof data === "string") {
    const text = data.trim();
    return text ? ‘${prefix}: ${truncate(text)}‘ : prefix;
```

```
  }

  const title = getStringField(data, "title");
  const detail = getStringField(data, "detail");
  const message =
    getStringField(data, "message") ??
    getStringField(data, "error_description") ??
    getStringField(data, "error");

  if (title && detail) return `${prefix}: ${title}   ${detail}`;
  if (detail) return `${prefix}: ${detail}`;
  if (message) return `${prefix}: ${message}`;
  if (title) return `${prefix}: ${title}`;

  return prefix;
}

export class ApiError<T = unknown> extends Error {
  readonly name = "ApiError";
  readonly status: number;
  readonly statusText: string;
  readonly data: T | null;
  readonly headers: Headers;
  readonly response: Response;
  readonly method: string;
  readonly url: string;

  constructor(
    response: Response,
    data: T | null,
    requestInfo: { method: string; url: string },
  ) {
    super(buildErrorMessage(response, data));
    Object.setPrototypeOf(this, new.target.prototype);

    this.status = response.status;
    this.statusText = response.statusText;
    this.data = data;
    this.headers = response.headers;
    this.response = response;
    this.method = requestInfo.method;
    this.url = response.url || requestInfo.url;
  }
}

export class ResponseParseError extends Error {
  readonly name = "ResponseParseError";
  readonly status: number;
  readonly statusText: string;
  readonly headers: Headers;
  readonly response: Response;
  readonly method: string;
```

```
  readonly url: string;
  readonly rawBody: string;
  readonly cause: unknown;

  constructor(
    response: Response,
    rawBody: string,
    cause: unknown,
    requestInfo: { method: string; url: string },
  ) {
    super(
      `Failed to parse response from ${requestInfo.method} ${response.url || requestInfo.url} ` +
        `(${response.status} ${response.statusText}) as JSON`,
    );
    Object.setPrototypeOf(this, new.target.prototype);

    this.status = response.status;
    this.statusText = response.statusText;
    this.headers = response.headers;
    this.response = response;
    this.method = requestInfo.method;
    this.url = response.url || requestInfo.url;
    this.rawBody = rawBody;
    this.cause = cause;
  }
}

async function parseJsonBody(
  response: Response,
  requestInfo: { method: string; url: string },
): Promise<unknown> {
  const raw = await response.text();
  const normalized = stripBom(raw);

  if (normalized.trim() === "") {
    return null;
  }

  try {
    return JSON.parse(normalized);
  } catch (cause) {
    throw new ResponseParseError(response, raw, cause, requestInfo);
  }
}

async function parseErrorBody(response: Response, method: string): Promise<unknown> {
  if (hasNoBody(response, method)) {
    return null;
  }

  const mediaType = getMediaType(response.headers);
```

```
  // Fall back to text when blob() is unavailable (e.g. some React Native builds).
  if (mediaType && !isJsonMediaType(mediaType) && !isTextMediaType(mediaType)) {
    return typeof response.blob === "function" ? response.blob() : response.text();
  }

  const raw = await response.text();
  const normalized = stripBom(raw);
  const trimmed = normalized.trim();

  if (trimmed === "") {
    return null;
  }

  if (isJsonMediaType(mediaType) || looksLikeJson(normalized)) {
    try {
      return JSON.parse(normalized);
    } catch {
      return raw;
    }
  }

  return raw;
}

function inferResponseType(response: Response): "json" | "text" | "blob" {
  const mediaType = getMediaType(response.headers);

  if (isJsonMediaType(mediaType)) return "json";
  if (isTextMediaType(mediaType) || mediaType == null) return "text";
  return "blob";
}

async function parseSuccessBody(
  response: Response,
  responseType: "json" | "text" | "blob" | "auto",
  requestInfo: { method: string; url: string },
): Promise<unknown> {
  if (hasNoBody(response, requestInfo.method)) {
    return null;
  }

  const effectiveType =
    responseType === "auto" ? inferResponseType(response) : responseType;

  switch (effectiveType) {
    case "json":
      return parseJsonBody(response, requestInfo);

    case "text": {
      const text = await response.text();
      return text === "" ? null : text;
    }
```

```
    case "blob":
      if (typeof response.blob !== "function") {
        throw new TypeError(
          "Blob responses are not supported in this runtime. " +
            "Use responseType \"json\" or \"text\" instead.",
        );
      }
      return response.blob();
  }
}

export async function customFetch<T = unknown>(
  input: RequestInfo | URL,
  options: CustomFetchOptions = {},
): Promise<T> {
  input = applyBaseUrl(input);
  const { responseType = "auto", headers: headersInit, ...init } = options;

  const method = resolveMethod(input, init.method);

  if (init.body != null && (method === "GET" || method === "HEAD")) {
    throw new TypeError(`customFetch: ${method} requests cannot have a body.`);
  }

  const headers = mergeHeaders(isRequest(input) ? input.headers : undefined, headersInit);

  if (
    typeof init.body === "string" &&
    !headers.has("content-type") &&
    looksLikeJson(init.body)
  ) {
    headers.set("content-type", "application/json");
  }

  if (responseType === "json" && !headers.has("accept")) {
    headers.set("accept", DEFAULT_JSON_ACCEPT);
  }

  // Attach bearer token when an auth getter is configured and no
  // Authorization header has been explicitly provided.
  if (_authTokenGetter && !headers.has("authorization")) {
    const token = await _authTokenGetter();
    if (token) {
      headers.set("authorization", `Bearer ${token}`);
    }
  }

  const requestInfo = { method, url: resolveUrl(input) };

  const response = await fetch(input, { ...init, method, headers });
```

```
  if (!response.ok) {
    const errorData = await parseErrorBody(response, method);
    throw new ApiError(response, errorData, requestInfo);
  }

  return (await parseSuccessBody(response, responseType, requestInfo)) as T;
}
```

FILE: lib/api-client-react/src/generated/api.schemas.ts
SIZE: 6,979 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */
export interface HealthStatus {
  status: string;
}

export interface Mission {
  id: number;
  missionId: string;
  siteName: string;
  generator?: string;
  project?: string;
  driverName?: string;
  assignedDriver?: string;
  createdDate?: string;
  filledLiters?: number;
  virtualCalculated?: number;
  actualInTank?: number;
  quantityAddedLastTask?: number;
  city?: string;
  notes?: string;
  missionStatus: string;
  createdBy?: string;
  technicianRemark?: string;
  technicianStatus?: string;
  reviewedBy?: string;
  reviewedAt?: string;
}

export interface CreateMissionInput {
  siteName: string;
  generator?: string;
  project?: string;
  assignedDriver?: string;
  driverName?: string;
  filledLiters?: number;
  virtualCalculated?: number;
  actualInTank?: number;
  quantityAddedLastTask?: number;
  city?: string;
  notes?: string;
  missionStatus: string;
  createdBy?: string;
}
```

```
export interface UpdateMissionInput {
  siteName?: string;
  generator?: string;
  project?: string;
  assignedDriver?: string;
  driverName?: string;
  filledLiters?: number;
  virtualCalculated?: number;
  actualInTank?: number;
  quantityAddedLastTask?: number;
  city?: string;
  notes?: string;
  missionStatus?: string;
}

export interface Driver {
  id: number;
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active: boolean;
  passwordHash?: string;
  imageUrl?: string;
}

export interface CreateDriverInput {
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
  password?: string;
}

export interface UpdateDriverInput {
  name?: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
  password?: string;
}

export interface Site {
  id: number;
  name: string;
  generator?: string;
  district?: string;
  city?: string;
  project?: string;
```

```
  cowStatus?: string;
  active?: boolean;
  currentLiters?: number;
  dailyVirtual?: number;
}

export interface CreateSiteInput {
  name: string;
  district?: string;
  city?: string;
  project?: string;
  cowStatus?: string;
  active?: boolean;
}

export interface UpdateSiteInput {
  name?: string;
  district?: string;
  city?: string;
  project?: string;
  cowStatus?: string;
  active?: boolean;
}

export interface Generator {
  id: number;
  name: string;
  site?: string;
  siteId?: number;
  dailyVirtual?: number;
  lastAvg?: number;
  rateOk?: boolean;
  active?: boolean;
}

export interface CreateGeneratorInput {
  name: string;
  site?: string;
  siteId?: number;
  dailyVirtual?: number;
  lastAvg?: number;
  rateOk?: boolean;
  active?: boolean;
}

export interface UpdateGeneratorInput {
  name?: string;
  site?: string;
  siteId?: number;
  dailyVirtual?: number;
  lastAvg?: number;
  rateOk?: boolean;
```

```
  active?: boolean;
}

export interface Notification {
  id: number;
  title: string;
  message: string;
  driverName?: string;
  sentBy?: string;
  createdAt?: string;
}

export interface CreateNotificationInput {
  title: string;
  message: string;
  driverName?: string;
  sentBy?: string;
}

export interface AppSettings {
  id?: number;
  fuelUnitPrice?: number;
  vatRate?: number;
  supplierName?: string;
  supplierAddress?: string;
  invoicePrefix?: string;
  invoiceSequence?: number;
}

export interface Admin {
  id: number;
  name: string;
  username: string;
  email?: string;
  position?: string;
}

export interface CreateAdminInput {
  name: string;
  username: string;
  email?: string;
  password: string;
  position?: string;
}

export interface UpdateAdminInput {
  name?: string;
  username?: string;
  email?: string;
  password?: string;
  position?: string;
}
```

```ts
export interface LoginInput {
  username: string;
  password: string;
}

export interface LoginResponse {
  success: boolean;
  role?: string;
  username?: string;
}

export type DashboardKpisMissionsByStatusItem = {
  status?: string;
  count?: number;
};

export type DashboardKpisMissionsByZoneItem = {
  zone?: string;
  count?: number;
};

export type DashboardKpisLitersByZoneItem = {
  zone?: string;
  liters?: number;
};

export type DashboardKpisMissionsByCategoryItem = {
  category?: string;
  count?: number;
};

export type DashboardKpisApprovedForInvoicingItem = {
  siteName?: string;
  liters?: number;
  date?: string;
};

export interface DashboardKpis {
  litersToday?: number;
  liters30d?: number;
  activeMissions?: number;
  activeDrivers?: number;
  missionsByStatus?: DashboardKpisMissionsByStatusItem[];
  missionsByZone?: DashboardKpisMissionsByZoneItem[];
  litersByZone?: DashboardKpisLitersByZoneItem[];
  missionsByCategory?: DashboardKpisMissionsByCategoryItem[];
  approvedForInvoicing?: DashboardKpisApprovedForInvoicingItem[];
}

export interface DriverLoginInput {
  email: string;
```

```
  password: string;
}

export interface DriverLoginResponse {
  success: boolean;
  driverId?: number;
  name?: string;
  email?: string;
  phone?: string;
  zone?: string;
  token?: string;
}

export interface DriverTask {
  id: number;
  driverId?: number;
  siteId?: number;
  siteName?: string;
  missionId?: string;
  scheduledAt?: string;
  status: string;
  requiredLiters?: number;
  actualInTank?: number;
  quantityAdded?: number;
  notes?: string;
  createdAt?: string;
}

export interface UpdateDriverTaskInput {
  status?: string;
  actualInTank?: number;
  quantityAdded?: number;
  notes?: string;
  observations?: string;
}

export interface DriverNotification {
  id: number;
  driverId?: number;
  title: string;
  message: string;
  type?: string;
  read?: boolean;
  createdAt?: string;
}

export interface Technician {
  id: number;
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
```

```
  active?: boolean;
}

export interface CreateTechnicianInput {
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
}

export interface UpdateTechnicianInput {
  name?: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
  password?: string;
}

export interface TechnicianLoginInput {
  email: string;
  password: string;
}

export interface TechnicianLoginResponse {
  success: boolean;
  technicianId?: number;
  name?: string;
  email?: string;
  zone?: string;
  token?: string;
}

export interface TechnicianFollowUpInput {
  technicianRemark?: string;
  technicianStatus?: string;
  reviewedBy?: string;
}

export interface RequestUploadUrlBody {
  /** @minLength 1 */
  name: string;
  /** @minimum 1 */
  size: number;
  /** @minLength 1 */
  contentType: string;
}

export interface RequestUploadUrlResponse {
  uploadURL: string;
  objectPath: string;
```

```
}

export type ListDriverTasksParams = {
  driverId: number;
};

export type ListDriverNotificationsParams = {
  driverId: number;
};

export type ListTechnicianMissionsParams = {
  zone?: string;
  status?: string;
};
```

FILE: lib/api-client-react/src/generated/api.ts
SIZE: 95,763 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */
import { useMutation, useQuery } from "@tanstack/react-query";
import type {
  MutationFunction,
  QueryFunction,
  QueryKey,
  UseMutationOptions,
  UseMutationResult,
  UseQueryOptions,
  UseQueryResult,
} from "@tanstack/react-query";

import type {
  Admin,
  AppSettings,
  CreateAdminInput,
  CreateDriverInput,
  CreateGeneratorInput,
  CreateMissionInput,
  CreateNotificationInput,
  CreateSiteInput,
  CreateTechnicianInput,
  DashboardKpis,
  Driver,
  DriverLoginInput,
  DriverLoginResponse,
  DriverNotification,
  DriverTask,
  Generator,
  HealthStatus,
  ListDriverNotificationsParams,
  ListDriverTasksParams,
  ListTechnicianMissionsParams,
  LoginInput,
  LoginResponse,
  Mission,
  Notification,
  RequestUploadUrlBody,
  RequestUploadUrlResponse,
  Site,
  Technician,
  TechnicianFollowUpInput,
  TechnicianLoginInput,
```

```
  TechnicianLoginResponse,
  UpdateAdminInput,
  UpdateDriverInput,
  UpdateDriverTaskInput,
  UpdateGeneratorInput,
  UpdateMissionInput,
  UpdateSiteInput,
  UpdateTechnicianInput,
} from "./api.schemas";

import { customFetch } from "../custom-fetch";
import type { ErrorType, BodyType } from "../custom-fetch";

type AwaitedInput<T> = PromiseLike<T> | T;

type Awaited<O> = O extends AwaitedInput<infer T> ? T : never;

type SecondParameter<T extends (...args: never) => unknown> = Parameters<T>[1];

/**
 * @summary Health check
 */
export const getHealthCheckUrl = () => {
  return `/api/healthz`;
};

export const healthCheck = async (
  options?: RequestInit,
): Promise<HealthStatus> => {
  return customFetch<HealthStatus>(getHealthCheckUrl(), {
    ...options,
    method: "GET",
  });
};

export const getHealthCheckQueryKey = () => {
  return [`/api/healthz`] as const;
};

export const getHealthCheckQueryOptions = <
  TData = Awaited<ReturnType<typeof healthCheck>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof healthCheck>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};
```

```
  const queryKey = queryOptions?.queryKey ?? getHealthCheckQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof healthCheck>>> = ({
    signal,
  }) => healthCheck({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof healthCheck>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type HealthCheckQueryResult = NonNullable<
  Awaited<ReturnType<typeof healthCheck>>
>;
export type HealthCheckQueryError = ErrorType<unknown>;

/**
 * @summary Health check
 */

export function useHealthCheck<
  TData = Awaited<ReturnType<typeof healthCheck>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof healthCheck>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getHealthCheckQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary List all missions
 */
export const getListMissionsUrl = () => {
  return `/api/missions`;
};

export const listMissions = async (
  options?: RequestInit,
): Promise<Mission[]> => {
```

```
  return customFetch<Mission[]>(getListMissionsUrl(), {
    ...options,
    method: "GET",
  });
};

export const getListMissionsQueryKey = () => {
  return [‘/api/missions‘] as const;
};

export const getListMissionsQueryOptions = <
  TData = Awaited<ReturnType<typeof listMissions>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listMissions>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListMissionsQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listMissions>>> = ({
    signal,
  }) => listMissions({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listMissions>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListMissionsQueryResult = NonNullable<
  Awaited<ReturnType<typeof listMissions>>
>;
export type ListMissionsQueryError = ErrorType<unknown>;

/**
 * @summary List all missions
 */

export function useListMissions<
  TData = Awaited<ReturnType<typeof listMissions>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listMissions>>,
    TError,
```

```
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListMissionsQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Create a mission
 */
export const getCreateMissionUrl = () => {
  return `/api/missions`;
};

export const createMission = async (
  createMissionInput: CreateMissionInput,
  options?: RequestInit,
): Promise<Mission> => {
  return customFetch<Mission>(getCreateMissionUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createMissionInput),
  });
};

export const getCreateMissionMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createMission>>,
    TError,
    { data: BodyType<CreateMissionInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createMission>>,
  TError,
  { data: BodyType<CreateMissionInput> },
  TContext
> => {
  const mutationKey = ["createMission"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
```

```
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createMission>>,
    { data: BodyType<CreateMissionInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createMission(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateMissionMutationResult = NonNullable<
  Awaited<ReturnType<typeof createMission>>
>;
export type CreateMissionMutationBody = BodyType<CreateMissionInput>;
export type CreateMissionMutationError = ErrorType<unknown>;

/**
 * @summary Create a mission
 */
export const useCreateMission = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createMission>>,
    TError,
    { data: BodyType<CreateMissionInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createMission>>,
  TError,
  { data: BodyType<CreateMissionInput> },
  TContext
> => {
  return useMutation(getCreateMissionMutationOptions(options));
};

/**
 * @summary Get a mission by ID
 */
export const getGetMissionUrl = (id: number) => {
  return `/api/missions/${id}`;
```

```
};

export const getMission = async (
  id: number,
  options?: RequestInit,
): Promise<Mission> => {
  return customFetch<Mission>(getGetMissionUrl(id), {
    ...options,
    method: "GET",
  });
};

export const getGetMissionQueryKey = (id: number) => {
  return [`/api/missions/${id}`] as const;
};

export const getGetMissionQueryOptions = <
  TData = Awaited<ReturnType<typeof getMission>>,
  TError = ErrorType<unknown>,
>(
  id: number,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof getMission>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getGetMissionQueryKey(id);

  const queryFn: QueryFunction<Awaited<ReturnType<typeof getMission>>> = ({
    signal,
  }) => getMission(id, { signal, ...requestOptions });

  return {
    queryKey,
    queryFn,
    enabled: !!id,
    ...queryOptions,
  } as UseQueryOptions<
    Awaited<ReturnType<typeof getMission>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type GetMissionQueryResult = NonNullable<
  Awaited<ReturnType<typeof getMission>>
```

```
>;
export type GetMissionQueryError = ErrorType<unknown>;

/**
 * @summary Get a mission by ID
 */

export function useGetMission<
  TData = Awaited<ReturnType<typeof getMission>>,
  TError = ErrorType<unknown>,
>(
  id: number,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof getMission>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getGetMissionQueryOptions(id, options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Update a mission
 */
export const getUpdateMissionUrl = (id: number) => {
  return `/api/missions/${id}`;
};

export const updateMission = async (
  id: number,
  updateMissionInput: UpdateMissionInput,
  options?: RequestInit,
): Promise<Mission> => {
  return customFetch<Mission>(getUpdateMissionUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateMissionInput),
  });
};

export const getUpdateMissionMutationOptions = <
  TError = ErrorType<unknown>,
```

```
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateMission>>,
    TError,
    { id: number; data: BodyType<UpdateMissionInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateMission>>,
  TError,
  { id: number; data: BodyType<UpdateMissionInput> },
  TContext
> => {
  const mutationKey = ["updateMission"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateMission>>,
    { id: number; data: BodyType<UpdateMissionInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return updateMission(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateMissionMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateMission>>
>;
export type UpdateMissionMutationBody = BodyType<UpdateMissionInput>;
export type UpdateMissionMutationError = ErrorType<unknown>;

/**
 * @summary Update a mission
 */
export const useUpdateMission = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateMission>>,
    TError,
```

```
    { id: number; data: BodyType<UpdateMissionInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateMission>>,
  TError,
  { id: number; data: BodyType<UpdateMissionInput> },
  TContext
> => {
  return useMutation(getUpdateMissionMutationOptions(options));
};

/**
 * @summary Delete a mission
 */
export const getDeleteMissionUrl = (id: number) => {
  return `/api/missions/${id}`;
};

export const deleteMission = async (
  id: number,
  options?: RequestInit,
): Promise<void> => {
  return customFetch<void>(getDeleteMissionUrl(id), {
    ...options,
    method: "DELETE",
  });
};

export const getDeleteMissionMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteMission>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof deleteMission>>,
  TError,
  { id: number },
  TContext
> => {
  const mutationKey = ["deleteMission"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
```

```
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof deleteMission>>,
    { id: number }
  > = (props) => {
    const { id } = props ?? {};

    return deleteMission(id, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DeleteMissionMutationResult = NonNullable<
  Awaited<ReturnType<typeof deleteMission>>
>;

export type DeleteMissionMutationError = ErrorType<unknown>;

/**
 * @summary Delete a mission
 */
export const useDeleteMission = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteMission>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof deleteMission>>,
  TError,
  { id: number },
  TContext
> => {
  return useMutation(getDeleteMissionMutationOptions(options));
};

/**
 * @summary List all drivers
 */
export const getListDriversUrl = () => {
  return `/api/drivers`;
};
```

```
export const listDrivers = async (options?: RequestInit): Promise<Driver[]> => {
  return customFetch<Driver[]>(getListDriversUrl(), {
    ...options,
    method: "GET",
  });
};

export const getListDriversQueryKey = () => {
  return [‘/api/drivers‘] as const;
};

export const getListDriversQueryOptions = <
  TData = Awaited<ReturnType<typeof listDrivers>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listDrivers>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListDriversQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listDrivers>>> = ({
    signal,
  }) => listDrivers({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listDrivers>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListDriversQueryResult = NonNullable<
  Awaited<ReturnType<typeof listDrivers>>
>;
export type ListDriversQueryError = ErrorType<unknown>;

/**
 * @summary List all drivers
 */

export function useListDrivers<
  TData = Awaited<ReturnType<typeof listDrivers>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listDrivers>>,
```

```
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListDriversQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Create a driver
 */
export const getCreateDriverUrl = () => {
  return `/api/drivers`;
};

export const createDriver = async (
  createDriverInput: CreateDriverInput,
  options?: RequestInit,
): Promise<Driver> => {
  return customFetch<Driver>(getCreateDriverUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createDriverInput),
  });
};

export const getCreateDriverMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createDriver>>,
    TError,
    { data: BodyType<CreateDriverInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createDriver>>,
  TError,
  { data: BodyType<CreateDriverInput> },
  TContext
> => {
  const mutationKey = ["createDriver"];
  const { mutation: mutationOptions, request: requestOptions } = options
```

```
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createDriver>>,
    { data: BodyType<CreateDriverInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createDriver(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateDriverMutationResult = NonNullable<
  Awaited<ReturnType<typeof createDriver>>
>;
export type CreateDriverMutationBody = BodyType<CreateDriverInput>;
export type CreateDriverMutationError = ErrorType<unknown>;

/**
 * @summary Create a driver
 */
export const useCreateDriver = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createDriver>>,
    TError,
    { data: BodyType<CreateDriverInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createDriver>>,
  TError,
  { data: BodyType<CreateDriverInput> },
  TContext
> => {
  return useMutation(getCreateDriverMutationOptions(options));
};

/**
 * @summary Update a driver
 */
export const getUpdateDriverUrl = (id: number) => {
```

```
  return `/api/drivers/${id}`;
};

export const updateDriver = async (
  id: number,
  updateDriverInput: UpdateDriverInput,
  options?: RequestInit,
): Promise<Driver> => {
  return customFetch<Driver>(getUpdateDriverUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateDriverInput),
  });
};

export const getUpdateDriverMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateDriver>>,
    TError,
    { id: number; data: BodyType<UpdateDriverInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateDriver>>,
  TError,
  { id: number; data: BodyType<UpdateDriverInput> },
  TContext
> => {
  const mutationKey = ["updateDriver"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateDriver>>,
    { id: number; data: BodyType<UpdateDriverInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return updateDriver(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
```

```
};

export type UpdateDriverMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateDriver>>
>;
export type UpdateDriverMutationBody = BodyType<UpdateDriverInput>;
export type UpdateDriverMutationError = ErrorType<unknown>;

/**
 * @summary Update a driver
 */
export const useUpdateDriver = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateDriver>>,
    TError,
    { id: number; data: BodyType<UpdateDriverInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateDriver>>,
  TError,
  { id: number; data: BodyType<UpdateDriverInput> },
  TContext
> => {
  return useMutation(getUpdateDriverMutationOptions(options));
};

/**
 * @summary Delete a driver
 */
export const getDeleteDriverUrl = (id: number) => {
  return `/api/drivers/${id}`;
};

export const deleteDriver = async (
  id: number,
  options?: RequestInit,
): Promise<void> => {
  return customFetch<void>(getDeleteDriverUrl(id), {
    ...options,
    method: "DELETE",
  });
};

export const getDeleteDriverMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
```

```
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteDriver>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof deleteDriver>>,
  TError,
  { id: number },
  TContext
> => {
  const mutationKey = ["deleteDriver"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof deleteDriver>>,
    { id: number }
  > = (props) => {
    const { id } = props ?? {};

    return deleteDriver(id, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DeleteDriverMutationResult = NonNullable<
  Awaited<ReturnType<typeof deleteDriver>>
>;

export type DeleteDriverMutationError = ErrorType<unknown>;

/**
 * @summary Delete a driver
 */
export const useDeleteDriver = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteDriver>>,
    TError,
    { id: number },
    TContext
```

```
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof deleteDriver>>,
  TError,
  { id: number },
  TContext
> => {
  return useMutation(getDeleteDriverMutationOptions(options));
};

/**
 * @summary List all sites
 */
export const getListSitesUrl = () => {
  return `/api/sites`;
};

export const listSites = async (options?: RequestInit): Promise<Site[]> => {
  return customFetch<Site[]>(getListSitesUrl(), {
    ...options,
    method: "GET",
  });
};

export const getListSitesQueryKey = () => {
  return [`/api/sites`] as const;
};

export const getListSitesQueryOptions = <
  TData = Awaited<ReturnType<typeof listSites>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<Awaited<ReturnType<typeof listSites>>, TError, TData>;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListSitesQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listSites>>> = ({
    signal,
  }) => listSites({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listSites>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListSitesQueryResult = NonNullable<
```

```
  Awaited<ReturnType<typeof listSites>>
>;
export type ListSitesQueryError = ErrorType<unknown>;

/**
 * @summary List all sites
 */

export function useListSites<
  TData = Awaited<ReturnType<typeof listSites>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<Awaited<ReturnType<typeof listSites>>, TError, TData>;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListSitesQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Create a site
 */
export const getCreateSiteUrl = () => {
  return `/api/sites`;
};

export const createSite = async (
  createSiteInput: CreateSiteInput,
  options?: RequestInit,
): Promise<Site> => {
  return customFetch<Site>(getCreateSiteUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createSiteInput),
  });
};

export const getCreateSiteMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createSite>>,
    TError,
    { data: BodyType<CreateSiteInput> },
    TContext
```

```
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createSite>>,
  TError,
  { data: BodyType<CreateSiteInput> },
  TContext
> => {
  const mutationKey = ["createSite"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createSite>>,
    { data: BodyType<CreateSiteInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createSite(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateSiteMutationResult = NonNullable<
  Awaited<ReturnType<typeof createSite>>
>;
export type CreateSiteMutationBody = BodyType<CreateSiteInput>;
export type CreateSiteMutationError = ErrorType<unknown>;

/**
 * @summary Create a site
 */
export const useCreateSite = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createSite>>,
    TError,
    { data: BodyType<CreateSiteInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createSite>>,
  TError,
```

```
  { data: BodyType<CreateSiteInput> },
  TContext
> => {
  return useMutation(getCreateSiteMutationOptions(options));
};

/**
 * @summary Update a site
 */
export const getUpdateSiteUrl = (id: number) => {
  return `/api/sites/${id}`;
};

export const updateSite = async (
  id: number,
  updateSiteInput: UpdateSiteInput,
  options?: RequestInit,
): Promise<Site> => {
  return customFetch<Site>(getUpdateSiteUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateSiteInput),
  });
};

export const getUpdateSiteMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateSite>>,
    TError,
    { id: number; data: BodyType<UpdateSiteInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateSite>>,
  TError,
  { id: number; data: BodyType<UpdateSiteInput> },
  TContext
> => {
  const mutationKey = ["updateSite"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };
```

```
  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateSite>>,
    { id: number; data: BodyType<UpdateSiteInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return updateSite(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateSiteMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateSite>>
>;
export type UpdateSiteMutationBody = BodyType<UpdateSiteInput>;
export type UpdateSiteMutationError = ErrorType<unknown>;

/**
 * @summary Update a site
 */
export const useUpdateSite = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateSite>>,
    TError,
    { id: number; data: BodyType<UpdateSiteInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateSite>>,
  TError,
  { id: number; data: BodyType<UpdateSiteInput> },
  TContext
> => {
  return useMutation(getUpdateSiteMutationOptions(options));
};

/**
 * @summary Delete a site
 */
export const getDeleteSiteUrl = (id: number) => {
  return `/api/sites/${id}`;
};

export const deleteSite = async (
  id: number,
  options?: RequestInit,
): Promise<void> => {
```

```
  return customFetch<void>(getDeleteSiteUrl(id), {
    ...options,
    method: "DELETE",
  });
};

export const getDeleteSiteMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteSite>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof deleteSite>>,
  TError,
  { id: number },
  TContext
> => {
  const mutationKey = ["deleteSite"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof deleteSite>>,
    { id: number }
  > = (props) => {
    const { id } = props ?? {};

    return deleteSite(id, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DeleteSiteMutationResult = NonNullable<
  Awaited<ReturnType<typeof deleteSite>>
>;

export type DeleteSiteMutationError = ErrorType<unknown>;

/**
 * @summary Delete a site
```

```
 */
export const useDeleteSite = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteSite>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof deleteSite>>,
  TError,
  { id: number },
  TContext
> => {
  return useMutation(getDeleteSiteMutationOptions(options));
};

/**
 * @summary List all generators
 */
export const getListGeneratorsUrl = () => {
  return `/api/generators`;
};

export const listGenerators = async (
  options?: RequestInit,
): Promise<Generator[]> => {
  return customFetch<Generator[]>(getListGeneratorsUrl(), {
    ...options,
    method: "GET",
  });
};

export const getListGeneratorsQueryKey = () => {
  return [`/api/generators`] as const;
};

export const getListGeneratorsQueryOptions = <
  TData = Awaited<ReturnType<typeof listGenerators>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listGenerators>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
```

```
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListGeneratorsQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listGenerators>>> = ({
    signal,
  }) => listGenerators({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listGenerators>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListGeneratorsQueryResult = NonNullable<
  Awaited<ReturnType<typeof listGenerators>>
>;
export type ListGeneratorsQueryError = ErrorType<unknown>;

/**
 * @summary List all generators
 */

export function useListGenerators<
  TData = Awaited<ReturnType<typeof listGenerators>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listGenerators>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListGeneratorsQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Create a generator
 */
export const getCreateGeneratorUrl = () => {
  return `/api/generators`;
};

export const createGenerator = async (
```

```
  createGeneratorInput: CreateGeneratorInput,
  options?: RequestInit,
): Promise<Generator> => {
  return customFetch<Generator>(getCreateGeneratorUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createGeneratorInput),
  });
};

export const getCreateGeneratorMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createGenerator>>,
    TError,
    { data: BodyType<CreateGeneratorInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createGenerator>>,
  TError,
  { data: BodyType<CreateGeneratorInput> },
  TContext
> => {
  const mutationKey = ["createGenerator"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createGenerator>>,
    { data: BodyType<CreateGeneratorInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createGenerator(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateGeneratorMutationResult = NonNullable<
  Awaited<ReturnType<typeof createGenerator>>
>;
```

```
export type CreateGeneratorMutationBody = BodyType<CreateGeneratorInput>;
export type CreateGeneratorMutationError = ErrorType<unknown>;

/**
 * @summary Create a generator
 */
export const useCreateGenerator = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createGenerator>>,
    TError,
    { data: BodyType<CreateGeneratorInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createGenerator>>,
  TError,
  { data: BodyType<CreateGeneratorInput> },
  TContext
> => {
  return useMutation(getCreateGeneratorMutationOptions(options));
};

/**
 * @summary Update a generator
 */
export const getUpdateGeneratorUrl = (id: number) => {
  return `/api/generators/${id}`;
};

export const updateGenerator = async (
  id: number,
  updateGeneratorInput: UpdateGeneratorInput,
  options?: RequestInit,
): Promise<Generator> => {
  return customFetch<Generator>(getUpdateGeneratorUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateGeneratorInput),
  });
};

export const getUpdateGeneratorMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateGenerator>>,
```

```
    TError,
    { id: number; data: BodyType<UpdateGeneratorInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateGenerator>>,
  TError,
  { id: number; data: BodyType<UpdateGeneratorInput> },
  TContext
> => {
  const mutationKey = ["updateGenerator"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateGenerator>>,
    { id: number; data: BodyType<UpdateGeneratorInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return updateGenerator(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateGeneratorMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateGenerator>>
>;
export type UpdateGeneratorMutationBody = BodyType<UpdateGeneratorInput>;
export type UpdateGeneratorMutationError = ErrorType<unknown>;

/**
 * @summary Update a generator
 */
export const useUpdateGenerator = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateGenerator>>,
    TError,
    { id: number; data: BodyType<UpdateGeneratorInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
```

```
}): UseMutationResult<
  Awaited<ReturnType<typeof updateGenerator>>,
  TError,
  { id: number; data: BodyType<UpdateGeneratorInput> },
  TContext
> => {
  return useMutation(getUpdateGeneratorMutationOptions(options));
};

/**
 * @summary Delete a generator
 */
export const getDeleteGeneratorUrl = (id: number) => {
  return `/api/generators/${id}`;
};

export const deleteGenerator = async (
  id: number,
  options?: RequestInit,
): Promise<void> => {
  return customFetch<void>(getDeleteGeneratorUrl(id), {
    ...options,
    method: "DELETE",
  });
};

export const getDeleteGeneratorMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteGenerator>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof deleteGenerator>>,
  TError,
  { id: number },
  TContext
> => {
  const mutationKey = ["deleteGenerator"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };
```

```
  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof deleteGenerator>>,
    { id: number }
  > = (props) => {
    const { id } = props ?? {};

    return deleteGenerator(id, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DeleteGeneratorMutationResult = NonNullable<
  Awaited<ReturnType<typeof deleteGenerator>>
>;

export type DeleteGeneratorMutationError = ErrorType<unknown>;

/**
 * @summary Delete a generator
 */
export const useDeleteGenerator = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteGenerator>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof deleteGenerator>>,
  TError,
  { id: number },
  TContext
> => {
  return useMutation(getDeleteGeneratorMutationOptions(options));
};

/**
 * @summary List all notifications
 */
export const getListNotificationsUrl = () => {
  return `/api/notifications`;
};

export const listNotifications = async (
  options?: RequestInit,
): Promise<Notification[]> => {
  return customFetch<Notification[]>(getListNotificationsUrl(), {
```

```
    ...options,
    method: "GET",
  });
};

export const getListNotificationsQueryKey = () => {
  return [‘/api/notifications‘] as const;
};

export const getListNotificationsQueryOptions = <
  TData = Awaited<ReturnType<typeof listNotifications>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listNotifications>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListNotificationsQueryKey();

  const queryFn: QueryFunction<
    Awaited<ReturnType<typeof listNotifications>>
  > = ({ signal }) => listNotifications({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listNotifications>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListNotificationsQueryResult = NonNullable<
  Awaited<ReturnType<typeof listNotifications>>
>;
export type ListNotificationsQueryError = ErrorType<unknown>;

/**
 * @summary List all notifications
 */

export function useListNotifications<
  TData = Awaited<ReturnType<typeof listNotifications>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listNotifications>>,
    TError,
    TData
```

```
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListNotificationsQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Send a notification
 */
export const getCreateNotificationUrl = () => {
  return `/api/notifications`;
};

export const createNotification = async (
  createNotificationInput: CreateNotificationInput,
  options?: RequestInit,
): Promise<Notification> => {
  return customFetch<Notification>(getCreateNotificationUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createNotificationInput),
  });
};

export const getCreateNotificationMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createNotification>>,
    TError,
    { data: BodyType<CreateNotificationInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createNotification>>,
  TError,
  { data: BodyType<CreateNotificationInput> },
  TContext
> => {
  const mutationKey = ["createNotification"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
```

```
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createNotification>>,
    { data: BodyType<CreateNotificationInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createNotification(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateNotificationMutationResult = NonNullable<
  Awaited<ReturnType<typeof createNotification>>
>;
export type CreateNotificationMutationBody = BodyType<CreateNotificationInput>;
export type CreateNotificationMutationError = ErrorType<unknown>;

/**
 * @summary Send a notification
 */
export const useCreateNotification = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createNotification>>,
    TError,
    { data: BodyType<CreateNotificationInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createNotification>>,
  TError,
  { data: BodyType<CreateNotificationInput> },
  TContext
> => {
  return useMutation(getCreateNotificationMutationOptions(options));
};

/**
 * @summary Get app settings
 */
export const getGetSettingsUrl = () => {
  return `/api/settings`;
};
```

```
export const getSettings = async (
  options?: RequestInit,
): Promise<AppSettings> => {
  return customFetch<AppSettings>(getGetSettingsUrl(), {
    ...options,
    method: "GET",
  });
};

export const getGetSettingsQueryKey = () => {
  return [‘/api/settings‘] as const;
};

export const getGetSettingsQueryOptions = <
  TData = Awaited<ReturnType<typeof getSettings>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof getSettings>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getGetSettingsQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof getSettings>>> = ({
    signal,
  }) => getSettings({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof getSettings>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type GetSettingsQueryResult = NonNullable<
  Awaited<ReturnType<typeof getSettings>>
>;
export type GetSettingsQueryError = ErrorType<unknown>;

/**
 * @summary Get app settings
 */

export function useGetSettings<
  TData = Awaited<ReturnType<typeof getSettings>>,
  TError = ErrorType<unknown>,
```

```
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof getSettings>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getGetSettingsQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Update app settings
 */
export const getUpdateSettingsUrl = () => {
  return `/api/settings`;
};

export const updateSettings = async (
  appSettings: AppSettings,
  options?: RequestInit,
): Promise<AppSettings> => {
  return customFetch<AppSettings>(getUpdateSettingsUrl(), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(appSettings),
  });
};

export const getUpdateSettingsMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateSettings>>,
    TError,
    { data: BodyType<AppSettings> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateSettings>>,
  TError,
  { data: BodyType<AppSettings> },
  TContext
```

```
> => {
  const mutationKey = ["updateSettings"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateSettings>>,
    { data: BodyType<AppSettings> }
  > = (props) => {
    const { data } = props ?? {};

    return updateSettings(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateSettingsMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateSettings>>
>;
export type UpdateSettingsMutationBody = BodyType<AppSettings>;
export type UpdateSettingsMutationError = ErrorType<unknown>;

/**
 * @summary Update app settings
 */
export const useUpdateSettings = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateSettings>>,
    TError,
    { data: BodyType<AppSettings> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateSettings>>,
  TError,
  { data: BodyType<AppSettings> },
  TContext
> => {
  return useMutation(getUpdateSettingsMutationOptions(options));
};

/**
```

```
 * @summary List all admin users
 */
export const getListAdminsUrl = () => {
  return `/api/admins`;
};

export const listAdmins = async (options?: RequestInit): Promise<Admin[]> => {
  return customFetch<Admin[]>(getListAdminsUrl(), {
    ...options,
    method: "GET",
  });
};

export const getListAdminsQueryKey = () => {
  return [`/api/admins`] as const;
};

export const getListAdminsQueryOptions = <
  TData = Awaited<ReturnType<typeof listAdmins>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listAdmins>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListAdminsQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listAdmins>>> = ({
    signal,
  }) => listAdmins({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listAdmins>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListAdminsQueryResult = NonNullable<
  Awaited<ReturnType<typeof listAdmins>>
>;
export type ListAdminsQueryError = ErrorType<unknown>;

/**
 * @summary List all admin users
 */
```

```
export function useListAdmins<
  TData = Awaited<ReturnType<typeof listAdmins>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listAdmins>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListAdminsQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Create an admin
 */
export const getCreateAdminUrl = () => {
  return `/api/admins`;
};

export const createAdmin = async (
  createAdminInput: CreateAdminInput,
  options?: RequestInit,
): Promise<Admin> => {
  return customFetch<Admin>(getCreateAdminUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createAdminInput),
  });
};

export const getCreateAdminMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createAdmin>>,
    TError,
    { data: BodyType<CreateAdminInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createAdmin>>,
```

```
  TError,
  { data: BodyType<CreateAdminInput> },
  TContext
> => {
  const mutationKey = ["createAdmin"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createAdmin>>,
    { data: BodyType<CreateAdminInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createAdmin(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateAdminMutationResult = NonNullable<
  Awaited<ReturnType<typeof createAdmin>>
>;
export type CreateAdminMutationBody = BodyType<CreateAdminInput>;
export type CreateAdminMutationError = ErrorType<unknown>;

/**
 * @summary Create an admin
 */
export const useCreateAdmin = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createAdmin>>,
    TError,
    { data: BodyType<CreateAdminInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createAdmin>>,
  TError,
  { data: BodyType<CreateAdminInput> },
  TContext
> => {
  return useMutation(getCreateAdminMutationOptions(options));
```

```
};

/**
 * @summary Update an admin
 */
export const getUpdateAdminUrl = (id: number) => {
  return `/api/admins/${id}`;
};

export const updateAdmin = async (
  id: number,
  updateAdminInput: UpdateAdminInput,
  options?: RequestInit,
): Promise<Admin> => {
  return customFetch<Admin>(getUpdateAdminUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateAdminInput),
  });
};

export const getUpdateAdminMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateAdmin>>,
    TError,
    { id: number; data: BodyType<UpdateAdminInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateAdmin>>,
  TError,
  { id: number; data: BodyType<UpdateAdminInput> },
  TContext
> => {
  const mutationKey = ["updateAdmin"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateAdmin>>,
    { id: number; data: BodyType<UpdateAdminInput> }
  > = (props) => {
```

```
    const { id, data } = props ?? {};

    return updateAdmin(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateAdminMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateAdmin>>
>;
export type UpdateAdminMutationBody = BodyType<UpdateAdminInput>;
export type UpdateAdminMutationError = ErrorType<unknown>;

/**
 * @summary Update an admin
 */
export const useUpdateAdmin = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateAdmin>>,
    TError,
    { id: number; data: BodyType<UpdateAdminInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateAdmin>>,
  TError,
  { id: number; data: BodyType<UpdateAdminInput> },
  TContext
> => {
  return useMutation(getUpdateAdminMutationOptions(options));
};

/**
 * @summary Delete an admin
 */
export const getDeleteAdminUrl = (id: number) => {
  return `/api/admins/${id}`;
};

export const deleteAdmin = async (
  id: number,
  options?: RequestInit,
): Promise<void> => {
  return customFetch<void>(getDeleteAdminUrl(id), {
    ...options,
    method: "DELETE",
  });
```

```
};

export const getDeleteAdminMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteAdmin>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof deleteAdmin>>,
  TError,
  { id: number },
  TContext
> => {
  const mutationKey = ["deleteAdmin"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof deleteAdmin>>,
    { id: number }
  > = (props) => {
    const { id } = props ?? {};

    return deleteAdmin(id, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DeleteAdminMutationResult = NonNullable<
  Awaited<ReturnType<typeof deleteAdmin>>
>;

export type DeleteAdminMutationError = ErrorType<unknown>;

/**
 * @summary Delete an admin
 */
export const useDeleteAdmin = <
  TError = ErrorType<unknown>,
  TContext = unknown,
```

```
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteAdmin>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof deleteAdmin>>,
  TError,
  { id: number },
  TContext
> => {
  return useMutation(getDeleteAdminMutationOptions(options));
};

/**
 * @summary Admin login
 */
export const getAdminLoginUrl = () => {
  return `/api/auth/login`;
};

export const adminLogin = async (
  loginInput: LoginInput,
  options?: RequestInit,
): Promise<LoginResponse> => {
  return customFetch<LoginResponse>(getAdminLoginUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(loginInput),
  });
};

export const getAdminLoginMutationOptions = <
  TError = ErrorType<void>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof adminLogin>>,
    TError,
    { data: BodyType<LoginInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof adminLogin>>,
  TError,
  { data: BodyType<LoginInput> },
  TContext
```

```
> => {
  const mutationKey = ["adminLogin"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof adminLogin>>,
    { data: BodyType<LoginInput> }
  > = (props) => {
    const { data } = props ?? {};

    return adminLogin(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type AdminLoginMutationResult = NonNullable<
  Awaited<ReturnType<typeof adminLogin>>
>;
export type AdminLoginMutationBody = BodyType<LoginInput>;
export type AdminLoginMutationError = ErrorType<void>;

/**
 * @summary Admin login
 */
export const useAdminLogin = <
  TError = ErrorType<void>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof adminLogin>>,
    TError,
    { data: BodyType<LoginInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof adminLogin>>,
  TError,
  { data: BodyType<LoginInput> },
  TContext
> => {
  return useMutation(getAdminLoginMutationOptions(options));
};

/**
```

```
 * @summary Get dashboard KPIs
 */
export const getGetDashboardKpisUrl = () => {
  return `/api/dashboard/kpis`;
};

export const getDashboardKpis = async (
  options?: RequestInit,
): Promise<DashboardKpis> => {
  return customFetch<DashboardKpis>(getGetDashboardKpisUrl(), {
    ...options,
    method: "GET",
  });
};

export const getGetDashboardKpisQueryKey = () => {
  return [`/api/dashboard/kpis`] as const;
};

export const getGetDashboardKpisQueryOptions = <
  TData = Awaited<ReturnType<typeof getDashboardKpis>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof getDashboardKpis>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getGetDashboardKpisQueryKey();

  const queryFn: QueryFunction<
    Awaited<ReturnType<typeof getDashboardKpis>>
  > = ({ signal }) => getDashboardKpis({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof getDashboardKpis>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type GetDashboardKpisQueryResult = NonNullable<
  Awaited<ReturnType<typeof getDashboardKpis>>
>;
export type GetDashboardKpisQueryError = ErrorType<unknown>;

/**
 * @summary Get dashboard KPIs
```

```
 */

export function useGetDashboardKpis<
  TData = Awaited<ReturnType<typeof getDashboardKpis>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof getDashboardKpis>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getGetDashboardKpisQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Driver login
 */
export const getDriverLoginUrl = () => {
  return `/api/driver/login`;
};

export const driverLogin = async (
  driverLoginInput: DriverLoginInput,
  options?: RequestInit,
): Promise<DriverLoginResponse> => {
  return customFetch<DriverLoginResponse>(getDriverLoginUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(driverLoginInput),
  });
};

export const getDriverLoginMutationOptions = <
  TError = ErrorType<void>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof driverLogin>>,
    TError,
    { data: BodyType<DriverLoginInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
```

```
}): UseMutationOptions<
  Awaited<ReturnType<typeof driverLogin>>,
  TError,
  { data: BodyType<DriverLoginInput> },
  TContext
> => {
  const mutationKey = ["driverLogin"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof driverLogin>>,
    { data: BodyType<DriverLoginInput> }
  > = (props) => {
    const { data } = props ?? {};

    return driverLogin(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DriverLoginMutationResult = NonNullable<
  Awaited<ReturnType<typeof driverLogin>>
>;
export type DriverLoginMutationBody = BodyType<DriverLoginInput>;
export type DriverLoginMutationError = ErrorType<void>;

/**
 * @summary Driver login
 */
export const useDriverLogin = <
  TError = ErrorType<void>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof driverLogin>>,
    TError,
    { data: BodyType<DriverLoginInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof driverLogin>>,
  TError,
  { data: BodyType<DriverLoginInput> },
  TContext
```

```
> => {
  return useMutation(getDriverLoginMutationOptions(options));
};

/**
 * @summary List tasks for a driver
 */
export const getListDriverTasksUrl = (params: ListDriverTasksParams) => {
  const normalizedParams = new URLSearchParams();

  Object.entries(params || {}).forEach(([key, value]) => {
    if (value !== undefined) {
      normalizedParams.append(key, value === null ? "null" : value.toString());
    }
  });

  const stringifiedParams = normalizedParams.toString();

  return stringifiedParams.length > 0
    ? `/api/driver/tasks?${stringifiedParams}`
    : `/api/driver/tasks`;
};

export const listDriverTasks = async (
  params: ListDriverTasksParams,
  options?: RequestInit,
): Promise<DriverTask[]> => {
  return customFetch<DriverTask[]>(getListDriverTasksUrl(params), {
    ...options,
    method: "GET",
  });
};

export const getListDriverTasksQueryKey = (params?: ListDriverTasksParams) => {
  return [`/api/driver/tasks`, ...(params ? [params] : [])] as const;
};

export const getListDriverTasksQueryOptions = <
  TData = Awaited<ReturnType<typeof listDriverTasks>>,
  TError = ErrorType<unknown>,
>(
  params: ListDriverTasksParams,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof listDriverTasks>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};
```

```
  const queryKey = queryOptions?.queryKey ?? getListDriverTasksQueryKey(params);

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listDriverTasks>>> = ({
    signal,
  }) => listDriverTasks(params, { signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listDriverTasks>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListDriverTasksQueryResult = NonNullable<
  Awaited<ReturnType<typeof listDriverTasks>>
>;
export type ListDriverTasksQueryError = ErrorType<unknown>;

/**
 * @summary List tasks for a driver
 */

export function useListDriverTasks<
  TData = Awaited<ReturnType<typeof listDriverTasks>>,
  TError = ErrorType<unknown>,
>(
  params: ListDriverTasksParams,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof listDriverTasks>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListDriverTasksQueryOptions(params, options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Get driver task by ID
 */
export const getGetDriverTaskUrl = (id: number) => {
  return `/api/driver/tasks/${id}`;
};
```

```
export const getDriverTask = async (
  id: number,
  options?: RequestInit,
): Promise<DriverTask> => {
  return customFetch<DriverTask>(getGetDriverTaskUrl(id), {
    ...options,
    method: "GET",
  });
};

export const getGetDriverTaskQueryKey = (id: number) => {
  return [‘/api/driver/tasks/${id}‘] as const;
};

export const getGetDriverTaskQueryOptions = <
  TData = Awaited<ReturnType<typeof getDriverTask>>,
  TError = ErrorType<unknown>,
>(
  id: number,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof getDriverTask>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getGetDriverTaskQueryKey(id);

  const queryFn: QueryFunction<Awaited<ReturnType<typeof getDriverTask>>> = ({
    signal,
  }) => getDriverTask(id, { signal, ...requestOptions });

  return {
    queryKey,
    queryFn,
    enabled: !!id,
    ...queryOptions,
  } as UseQueryOptions<
    Awaited<ReturnType<typeof getDriverTask>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type GetDriverTaskQueryResult = NonNullable<
  Awaited<ReturnType<typeof getDriverTask>>
>;
```

```ts
export type GetDriverTaskQueryError = ErrorType<unknown>;

/**
 * @summary Get driver task by ID
 */

export function useGetDriverTask<
  TData = Awaited<ReturnType<typeof getDriverTask>>,
  TError = ErrorType<unknown>,
>(
  id: number,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof getDriverTask>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getGetDriverTaskQueryOptions(id, options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Update driver task (submit fuel entry)
 */
export const getUpdateDriverTaskUrl = (id: number) => {
  return `/api/driver/tasks/${id}`;
};

export const updateDriverTask = async (
  id: number,
  updateDriverTaskInput: UpdateDriverTaskInput,
  options?: RequestInit,
): Promise<DriverTask> => {
  return customFetch<DriverTask>(getUpdateDriverTaskUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateDriverTaskInput),
  });
};

export const getUpdateDriverTaskMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
```

```
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateDriverTask>>,
    TError,
    { id: number; data: BodyType<UpdateDriverTaskInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateDriverTask>>,
  TError,
  { id: number; data: BodyType<UpdateDriverTaskInput> },
  TContext
> => {
  const mutationKey = ["updateDriverTask"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateDriverTask>>,
    { id: number; data: BodyType<UpdateDriverTaskInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return updateDriverTask(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateDriverTaskMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateDriverTask>>
>;
export type UpdateDriverTaskMutationBody = BodyType<UpdateDriverTaskInput>;
export type UpdateDriverTaskMutationError = ErrorType<unknown>;

/**
 * @summary Update driver task (submit fuel entry)
 */
export const useUpdateDriverTask = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateDriverTask>>,
    TError,
    { id: number; data: BodyType<UpdateDriverTaskInput> },
```

```
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateDriverTask>>,
  TError,
  { id: number; data: BodyType<UpdateDriverTaskInput> },
  TContext
> => {
  return useMutation(getUpdateDriverTaskMutationOptions(options));
};

/**
 * @summary Get notifications for a driver
 */
export const getListDriverNotificationsUrl = (
  params: ListDriverNotificationsParams,
) => {
  const normalizedParams = new URLSearchParams();

  Object.entries(params || {}).forEach(([key, value]) => {
    if (value !== undefined) {
      normalizedParams.append(key, value === null ? "null" : value.toString());
    }
  });

  const stringifiedParams = normalizedParams.toString();

  return stringifiedParams.length > 0
    ? `/api/driver/notifications?${stringifiedParams}`
    : `/api/driver/notifications`;
};

export const listDriverNotifications = async (
  params: ListDriverNotificationsParams,
  options?: RequestInit,
): Promise<DriverNotification[]> => {
  return customFetch<DriverNotification[]>(
    getListDriverNotificationsUrl(params),
    {
      ...options,
      method: "GET",
    },
  );
};

export const getListDriverNotificationsQueryKey = (
  params?: ListDriverNotificationsParams,
) => {
  return [`/api/driver/notifications`, ...(params ? [params] : [])] as const;
};
```

```ts
export const getListDriverNotificationsQueryOptions = <
  TData = Awaited<ReturnType<typeof listDriverNotifications>>,
  TError = ErrorType<unknown>,
>(
  params: ListDriverNotificationsParams,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof listDriverNotifications>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey =
    queryOptions?.queryKey ?? getListDriverNotificationsQueryKey(params);

  const queryFn: QueryFunction<
    Awaited<ReturnType<typeof listDriverNotifications>>
  > = ({ signal }) =>
    listDriverNotifications(params, { signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listDriverNotifications>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListDriverNotificationsQueryResult = NonNullable<
  Awaited<ReturnType<typeof listDriverNotifications>>
>;
export type ListDriverNotificationsQueryError = ErrorType<unknown>;

/**
 * @summary Get notifications for a driver
 */

export function useListDriverNotifications<
  TData = Awaited<ReturnType<typeof listDriverNotifications>>,
  TError = ErrorType<unknown>,
>(
  params: ListDriverNotificationsParams,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof listDriverNotifications>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
```

```
  },
): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListDriverNotificationsQueryOptions(params, options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary List all technicians
 */
export const getListTechniciansUrl = () => {
  return `/api/technicians`;
};

export const listTechnicians = async (
  options?: RequestInit,
): Promise<Technician[]> => {
  return customFetch<Technician[]>(getListTechniciansUrl(), {
    ...options,
    method: "GET",
  });
};

export const getListTechniciansQueryKey = () => {
  return [`/api/technicians`] as const;
};

export const getListTechniciansQueryOptions = <
  TData = Awaited<ReturnType<typeof listTechnicians>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listTechnicians>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey = queryOptions?.queryKey ?? getListTechniciansQueryKey();

  const queryFn: QueryFunction<Awaited<ReturnType<typeof listTechnicians>>> = ({
    signal,
  }) => listTechnicians({ signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listTechnicians>>,
```

```
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListTechniciansQueryResult = NonNullable<
  Awaited<ReturnType<typeof listTechnicians>>
>;
export type ListTechniciansQueryError = ErrorType<unknown>;

/**
 * @summary List all technicians
 */

export function useListTechnicians<
  TData = Awaited<ReturnType<typeof listTechnicians>>,
  TError = ErrorType<unknown>,
>(options?: {
  query?: UseQueryOptions<
    Awaited<ReturnType<typeof listTechnicians>>,
    TError,
    TData
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListTechniciansQueryOptions(options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Create a technician
 */
export const getCreateTechnicianUrl = () => {
  return `/api/technicians`;
};

export const createTechnician = async (
  createTechnicianInput: CreateTechnicianInput,
  options?: RequestInit,
): Promise<Technician> => {
  return customFetch<Technician>(getCreateTechnicianUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(createTechnicianInput),
  });
};
```

```
export const getCreateTechnicianMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createTechnician>>,
    TError,
    { data: BodyType<CreateTechnicianInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof createTechnician>>,
  TError,
  { data: BodyType<CreateTechnicianInput> },
  TContext
> => {
  const mutationKey = ["createTechnician"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof createTechnician>>,
    { data: BodyType<CreateTechnicianInput> }
  > = (props) => {
    const { data } = props ?? {};

    return createTechnician(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type CreateTechnicianMutationResult = NonNullable<
  Awaited<ReturnType<typeof createTechnician>>
>;
export type CreateTechnicianMutationBody = BodyType<CreateTechnicianInput>;
export type CreateTechnicianMutationError = ErrorType<unknown>;

/**
 * @summary Create a technician
 */
export const useCreateTechnician = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
```

```
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof createTechnician>>,
    TError,
    { data: BodyType<CreateTechnicianInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof createTechnician>>,
  TError,
  { data: BodyType<CreateTechnicianInput> },
  TContext
> => {
  return useMutation(getCreateTechnicianMutationOptions(options));
};

/**
 * @summary Technician login
 */
export const getTechnicianLoginUrl = () => {
  return `/api/technician/login`;
};

export const technicianLogin = async (
  technicianLoginInput: TechnicianLoginInput,
  options?: RequestInit,
): Promise<TechnicianLoginResponse> => {
  return customFetch<TechnicianLoginResponse>(getTechnicianLoginUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(technicianLoginInput),
  });
};

export const getTechnicianLoginMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof technicianLogin>>,
    TError,
    { data: BodyType<TechnicianLoginInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof technicianLogin>>,
  TError,
  { data: BodyType<TechnicianLoginInput> },
  TContext
> => {
```

```
  const mutationKey = ["technicianLogin"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof technicianLogin>>,
    { data: BodyType<TechnicianLoginInput> }
  > = (props) => {
    const { data } = props ?? {};

    return technicianLogin(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type TechnicianLoginMutationResult = NonNullable<
  Awaited<ReturnType<typeof technicianLogin>>
>;
export type TechnicianLoginMutationBody = BodyType<TechnicianLoginInput>;
export type TechnicianLoginMutationError = ErrorType<unknown>;

/**
 * @summary Technician login
 */
export const useTechnicianLogin = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof technicianLogin>>,
    TError,
    { data: BodyType<TechnicianLoginInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof technicianLogin>>,
  TError,
  { data: BodyType<TechnicianLoginInput> },
  TContext
> => {
  return useMutation(getTechnicianLoginMutationOptions(options));
};

/**
 * @summary List missions for technician follow-up
```

```
 */
export const getListTechnicianMissionsUrl = (
  params?: ListTechnicianMissionsParams,
) => {
  const normalizedParams = new URLSearchParams();

  Object.entries(params || {}).forEach(([key, value]) => {
    if (value !== undefined) {
      normalizedParams.append(key, value === null ? "null" : value.toString());
    }
  });

  const stringifiedParams = normalizedParams.toString();

  return stringifiedParams.length > 0
    ? `/api/technician/missions?${stringifiedParams}`
    : `/api/technician/missions`;
};

export const listTechnicianMissions = async (
  params?: ListTechnicianMissionsParams,
  options?: RequestInit,
): Promise<Mission[]> => {
  return customFetch<Mission[]>(getListTechnicianMissionsUrl(params), {
    ...options,
    method: "GET",
  });
};

export const getListTechnicianMissionsQueryKey = (
  params?: ListTechnicianMissionsParams,
) => {
  return [`/api/technician/missions`, ...(params ? [params] : [])] as const;
};

export const getListTechnicianMissionsQueryOptions = <
  TData = Awaited<ReturnType<typeof listTechnicianMissions>>,
  TError = ErrorType<unknown>,
>(
  params?: ListTechnicianMissionsParams,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof listTechnicianMissions>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey =
```

```
    queryOptions?.queryKey ?? getListTechnicianMissionsQueryKey(params);

  const queryFn: QueryFunction<
    Awaited<ReturnType<typeof listTechnicianMissions>>
  > = ({ signal }) =>
    listTechnicianMissions(params, { signal, ...requestOptions });

  return { queryKey, queryFn, ...queryOptions } as UseQueryOptions<
    Awaited<ReturnType<typeof listTechnicianMissions>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type ListTechnicianMissionsQueryResult = NonNullable<
  Awaited<ReturnType<typeof listTechnicianMissions>>
>;
export type ListTechnicianMissionsQueryError = ErrorType<unknown>;

/**
 * @summary List missions for technician follow-up
 */

export function useListTechnicianMissions<
  TData = Awaited<ReturnType<typeof listTechnicianMissions>>,
  TError = ErrorType<unknown>,
>(
  params?: ListTechnicianMissionsParams,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof listTechnicianMissions>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getListTechnicianMissionsQueryOptions(params, options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}

/**
 * @summary Technician follow-up on a mission
 */
export const getTechnicianFollowUpUrl = (id: number) => {
  return `/api/technician/missions/${id}/followup`;
};
```

```
export const technicianFollowUp = async (
  id: number,
  technicianFollowUpInput: TechnicianFollowUpInput,
  options?: RequestInit,
): Promise<Mission> => {
  return customFetch<Mission>(getTechnicianFollowUpUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(technicianFollowUpInput),
  });
};

export const getTechnicianFollowUpMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof technicianFollowUp>>,
    TError,
    { id: number; data: BodyType<TechnicianFollowUpInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof technicianFollowUp>>,
  TError,
  { id: number; data: BodyType<TechnicianFollowUpInput> },
  TContext
> => {
  const mutationKey = ["technicianFollowUp"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof technicianFollowUp>>,
    { id: number; data: BodyType<TechnicianFollowUpInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return technicianFollowUp(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};
```

```
export type TechnicianFollowUpMutationResult = NonNullable<
  Awaited<ReturnType<typeof technicianFollowUp>>
>;
export type TechnicianFollowUpMutationBody = BodyType<TechnicianFollowUpInput>;
export type TechnicianFollowUpMutationError = ErrorType<unknown>;

/**
 * @summary Technician follow-up on a mission
 */
export const useTechnicianFollowUp = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof technicianFollowUp>>,
    TError,
    { id: number; data: BodyType<TechnicianFollowUpInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof technicianFollowUp>>,
  TError,
  { id: number; data: BodyType<TechnicianFollowUpInput> },
  TContext
> => {
  return useMutation(getTechnicianFollowUpMutationOptions(options));
};

/**
 * @summary Update a technician
 */
export const getUpdateTechnicianUrl = (id: number) => {
  return `/api/technicians/${id}`;
};

export const updateTechnician = async (
  id: number,
  updateTechnicianInput: UpdateTechnicianInput,
  options?: RequestInit,
): Promise<Technician> => {
  return customFetch<Technician>(getUpdateTechnicianUrl(id), {
    ...options,
    method: "PUT",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(updateTechnicianInput),
  });
};

export const getUpdateTechnicianMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
```

```
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateTechnician>>,
    TError,
    { id: number; data: BodyType<UpdateTechnicianInput> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof updateTechnician>>,
  TError,
  { id: number; data: BodyType<UpdateTechnicianInput> },
  TContext
> => {
  const mutationKey = ["updateTechnician"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof updateTechnician>>,
    { id: number; data: BodyType<UpdateTechnicianInput> }
  > = (props) => {
    const { id, data } = props ?? {};

    return updateTechnician(id, data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type UpdateTechnicianMutationResult = NonNullable<
  Awaited<ReturnType<typeof updateTechnician>>
>;
export type UpdateTechnicianMutationBody = BodyType<UpdateTechnicianInput>;
export type UpdateTechnicianMutationError = ErrorType<unknown>;

/**
 * @summary Update a technician
 */
export const useUpdateTechnician = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof updateTechnician>>,
    TError,
    { id: number; data: BodyType<UpdateTechnicianInput> },
```

```
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof updateTechnician>>,
  TError,
  { id: number; data: BodyType<UpdateTechnicianInput> },
  TContext
> => {
  return useMutation(getUpdateTechnicianMutationOptions(options));
};

/**
 * @summary Delete a technician
 */
export const getDeleteTechnicianUrl = (id: number) => {
  return `/api/technicians/${id}`;
};

export const deleteTechnician = async (
  id: number,
  options?: RequestInit,
): Promise<void> => {
  return customFetch<void>(getDeleteTechnicianUrl(id), {
    ...options,
    method: "DELETE",
  });
};

export const getDeleteTechnicianMutationOptions = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteTechnician>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof deleteTechnician>>,
  TError,
  { id: number },
  TContext
> => {
  const mutationKey = ["deleteTechnician"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
```

```
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof deleteTechnician>>,
    { id: number }
  > = (props) => {
    const { id } = props ?? {};

    return deleteTechnician(id, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type DeleteTechnicianMutationResult = NonNullable<
  Awaited<ReturnType<typeof deleteTechnician>>
>;

export type DeleteTechnicianMutationError = ErrorType<unknown>;

/**
 * @summary Delete a technician
 */
export const useDeleteTechnician = <
  TError = ErrorType<unknown>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof deleteTechnician>>,
    TError,
    { id: number },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof deleteTechnician>>,
  TError,
  { id: number },
  TContext
> => {
  return useMutation(getDeleteTechnicianMutationOptions(options));
};

/**
 * @summary Request a presigned URL for file upload
 */
export const getRequestUploadUrlUrl = () => {
  return `/api/storage/uploads/request-url`;
};

export const requestUploadUrl = async (
```

```
  requestUploadUrlBody: RequestUploadUrlBody,
  options?: RequestInit,
): Promise<RequestUploadUrlResponse> => {
  return customFetch<RequestUploadUrlResponse>(getRequestUploadUrlUrl(), {
    ...options,
    method: "POST",
    headers: { "Content-Type": "application/json", ...options?.headers },
    body: JSON.stringify(requestUploadUrlBody),
  });
};

export const getRequestUploadUrlMutationOptions = <
  TError = ErrorType<void>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof requestUploadUrl>>,
    TError,
    { data: BodyType<RequestUploadUrlBody> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationOptions<
  Awaited<ReturnType<typeof requestUploadUrl>>,
  TError,
  { data: BodyType<RequestUploadUrlBody> },
  TContext
> => {
  const mutationKey = ["requestUploadUrl"];
  const { mutation: mutationOptions, request: requestOptions } = options
    ? options.mutation &&
      "mutationKey" in options.mutation &&
      options.mutation.mutationKey
      ? options
      : { ...options, mutation: { ...options.mutation, mutationKey } }
    : { mutation: { mutationKey }, request: undefined };

  const mutationFn: MutationFunction<
    Awaited<ReturnType<typeof requestUploadUrl>>,
    { data: BodyType<RequestUploadUrlBody> }
  > = (props) => {
    const { data } = props ?? {};

    return requestUploadUrl(data, requestOptions);
  };

  return { mutationFn, ...mutationOptions };
};

export type RequestUploadUrlMutationResult = NonNullable<
  Awaited<ReturnType<typeof requestUploadUrl>>
>;
```

```
export type RequestUploadUrlMutationBody = BodyType<RequestUploadUrlBody>;
export type RequestUploadUrlMutationError = ErrorType<void>;

/**
 * @summary Request a presigned URL for file upload
 */
export const useRequestUploadUrl = <
  TError = ErrorType<void>,
  TContext = unknown,
>(options?: {
  mutation?: UseMutationOptions<
    Awaited<ReturnType<typeof requestUploadUrl>>,
    TError,
    { data: BodyType<RequestUploadUrlBody> },
    TContext
  >;
  request?: SecondParameter<typeof customFetch>;
}): UseMutationResult<
  Awaited<ReturnType<typeof requestUploadUrl>>,
  TError,
  { data: BodyType<RequestUploadUrlBody> },
  TContext
> => {
  return useMutation(getRequestUploadUrlMutationOptions(options));
};

/**
 * @summary Serve an object entity from PRIVATE_OBJECT_DIR
 */
export const getGetStorageObjectUrl = (objectPath: string) => {
  return `/api/storage/objects/${objectPath}`;
};

export const getStorageObject = async (
  objectPath: string,
  options?: RequestInit,
): Promise<Blob> => {
  return customFetch<Blob>(getGetStorageObjectUrl(objectPath), {
    ...options,
    method: "GET",
  });
};

export const getGetStorageObjectQueryKey = (objectPath: string) => {
  return [`/api/storage/objects/${objectPath}`] as const;
};

export const getGetStorageObjectQueryOptions = <
  TData = Awaited<ReturnType<typeof getStorageObject>>,
  TError = ErrorType<void>,
>(
  objectPath: string,
```

```
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof getStorageObject>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
  },
) => {
  const { query: queryOptions, request: requestOptions } = options ?? {};

  const queryKey =
    queryOptions?.queryKey ?? getGetStorageObjectQueryKey(objectPath);

  const queryFn: QueryFunction<
    Awaited<ReturnType<typeof getStorageObject>>
  > = ({ signal }) =>
    getStorageObject(objectPath, { signal, ...requestOptions });

  return {
    queryKey,
    queryFn,
    enabled: !!objectPath,
    ...queryOptions,
  } as UseQueryOptions<
    Awaited<ReturnType<typeof getStorageObject>>,
    TError,
    TData
  > & { queryKey: QueryKey };
};

export type GetStorageObjectQueryResult = NonNullable<
  Awaited<ReturnType<typeof getStorageObject>>
>;
export type GetStorageObjectQueryError = ErrorType<void>;

/**
 * @summary Serve an object entity from PRIVATE_OBJECT_DIR
 */

export function useGetStorageObject<
  TData = Awaited<ReturnType<typeof getStorageObject>>,
  TError = ErrorType<void>,
>(
  objectPath: string,
  options?: {
    query?: UseQueryOptions<
      Awaited<ReturnType<typeof getStorageObject>>,
      TError,
      TData
    >;
    request?: SecondParameter<typeof customFetch>;
```

```
  },
): UseQueryResult<TData, TError> & { queryKey: QueryKey } {
  const queryOptions = getGetStorageObjectQueryOptions(objectPath, options);

  const query = useQuery(queryOptions) as UseQueryResult<TData, TError> & {
    queryKey: QueryKey;
  };

  return { ...query, queryKey: queryOptions.queryKey };
}
```

FILE: lib/api-client-react/src/index.ts
SIZE: 194 bytes

```
export * from "./generated/api";
export * from "./generated/api.schemas";
export { setBaseUrl, setAuthTokenGetter } from "./custom-fetch";
export type { AuthTokenGetter } from "./custom-fetch";
```

FILE: lib/api-client-react/tsconfig.json
SIZE: 251 bytes

```
{
  "extends": "../../tsconfig.base.json",
  "compilerOptions": {
    "composite": true,
    "declarationMap": true,
    "emitDeclarationOnly": true,
    "outDir": "dist",
    "rootDir": "src",
    "lib": ["dom", "es2022"]
  },
  "include": ["src"]
}
```

FILE: lib/api-spec/openapi.yaml
SIZE: 33,257 bytes

```yaml
openapi: 3.1.0
info:
  title: Api
  version: 0.1.0
  description: ACES Managed Services API
servers:
  - url: /api
    description: Base API path
tags:
  - name: health
    description: Health operations
  - name: missions
    description: Mission operations
  - name: drivers
    description: Driver operations
  - name: sites
    description: Site operations
  - name: generators
    description: Generator operations
  - name: notifications
    description: Notification operations
  - name: settings
    description: Settings operations
  - name: admins
    description: Admin user operations
  - name: storage
    description: Object storage upload and serving endpoints
paths:
  /healthz:
    get:
      operationId: healthCheck
      tags: [health]
      summary: Health check
      responses:
        "200":
          description: Healthy
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/HealthStatus"

  /missions:
    get:
      operationId: listMissions
      tags: [missions]
      summary: List all missions
      responses:
        "200":
          description: List of missions
```

```
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: "#/components/schemas/Mission"
    post:
      operationId: createMission
      tags: [missions]
      summary: Create a mission
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/CreateMissionInput"
      responses:
        "201":
          description: Created mission
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Mission"

  /missions/{id}:
    get:
      operationId: getMission
      tags: [missions]
      summary: Get a mission by ID
      parameters:
        - name: id
          in: path
          required: true
          schema:
            type: integer
      responses:
        "200":
          description: Mission
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Mission"
    put:
      operationId: updateMission
      tags: [missions]
      summary: Update a mission
      parameters:
        - name: id
          in: path
          required: true
          schema:
            type: integer
```

```
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/UpdateMissionInput"
    responses:
      "200":
        description: Updated mission
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Mission"
  delete:
    operationId: deleteMission
    tags: [missions]
    summary: Delete a mission
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    responses:
      "204":
        description: Deleted

/drivers:
  get:
    operationId: listDrivers
    tags: [drivers]
    summary: List all drivers
    responses:
      "200":
        description: List of drivers
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: "#/components/schemas/Driver"
  post:
    operationId: createDriver
    tags: [drivers]
    summary: Create a driver
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/CreateDriverInput"
    responses:
```

```
      "201":
        description: Created driver
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Driver"

  /drivers/{id}:
    put:
      operationId: updateDriver
      tags: [drivers]
      summary: Update a driver
      parameters:
        - name: id
          in: path
          required: true
          schema:
            type: integer
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/UpdateDriverInput"
      responses:
        "200":
          description: Updated driver
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Driver"
    delete:
      operationId: deleteDriver
      tags: [drivers]
      summary: Delete a driver
      parameters:
        - name: id
          in: path
          required: true
          schema:
            type: integer
      responses:
        "204":
          description: Deleted

  /sites:
    get:
      operationId: listSites
      tags: [sites]
      summary: List all sites
      responses:
        "200":
```

```
        description: List of sites
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: "#/components/schemas/Site"
    post:
      operationId: createSite
      tags: [sites]
      summary: Create a site
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/CreateSiteInput"
      responses:
        "201":
          description: Created site
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Site"

  /sites/{id}:
    put:
      operationId: updateSite
      tags: [sites]
      summary: Update a site
      parameters:
        - name: id
          in: path
          required: true
          schema:
            type: integer
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/UpdateSiteInput"
      responses:
        "200":
          description: Updated site
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Site"
    delete:
      operationId: deleteSite
      tags: [sites]
```

```
    summary: Delete a site
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    responses:
      "204":
        description: Deleted

  /generators:
    get:
      operationId: listGenerators
      tags: [generators]
      summary: List all generators
      responses:
        "200":
          description: List of generators
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: "#/components/schemas/Generator"
    post:
      operationId: createGenerator
      tags: [generators]
      summary: Create a generator
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/CreateGeneratorInput"
      responses:
        "201":
          description: Created generator
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Generator"

  /generators/{id}:
    put:
      operationId: updateGenerator
      tags: [generators]
      summary: Update a generator
      parameters:
        - name: id
          in: path
          required: true
```

```
        schema:
          type: integer
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/UpdateGeneratorInput"
    responses:
      "200":
        description: Updated generator
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Generator"
  delete:
    operationId: deleteGenerator
    tags: [generators]
    summary: Delete a generator
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    responses:
      "204":
        description: Deleted

/notifications:
  get:
    operationId: listNotifications
    tags: [notifications]
    summary: List all notifications
    responses:
      "200":
        description: List of notifications
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: "#/components/schemas/Notification"
  post:
    operationId: createNotification
    tags: [notifications]
    summary: Send a notification
    requestBody:
      required: true
      content:
        application/json:
          schema:
```

```
            $ref: "#/components/schemas/CreateNotificationInput"
    responses:
      "201":
        description: Created notification
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Notification"

/settings:
  get:
    operationId: getSettings
    tags: [settings]
    summary: Get app settings
    responses:
      "200":
        description: App settings
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/AppSettings"
  put:
    operationId: updateSettings
    tags: [settings]
    summary: Update app settings
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/AppSettings"
    responses:
      "200":
        description: Updated settings
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/AppSettings"

/admins:
  get:
    operationId: listAdmins
    tags: [admins]
    summary: List all admin users
    responses:
      "200":
        description: List of admins
        content:
          application/json:
            schema:
              type: array
              items:
```

```
              $ref: "#/components/schemas/Admin"
  post:
    operationId: createAdmin
    tags: [admins]
    summary: Create an admin
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/CreateAdminInput"
    responses:
      "201":
        description: Created admin
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Admin"

/admins/{id}:
  put:
    operationId: updateAdmin
    tags: [admins]
    summary: Update an admin
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/UpdateAdminInput"
    responses:
      "200":
        description: Updated admin
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Admin"
  delete:
    operationId: deleteAdmin
    tags: [admins]
    summary: Delete an admin
    parameters:
      - name: id
        in: path
        required: true
        schema:
```

```
          type: integer
    responses:
      "204":
        description: Deleted

/auth/login:
  post:
    operationId: adminLogin
    tags: [admins]
    summary: Admin login
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/LoginInput"
    responses:
      "200":
        description: Login successful
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/LoginResponse"
      "401":
        description: Invalid credentials

/dashboard/kpis:
  get:
    operationId: getDashboardKpis
    tags: [missions]
    summary: Get dashboard KPIs
    responses:
      "200":
        description: KPIs
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/DashboardKpis"

/driver/login:
  post:
    operationId: driverLogin
    tags: [drivers]
    summary: Driver login
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/DriverLoginInput"
    responses:
      "200":
```

```
        description: Driver login successful
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/DriverLoginResponse"
      "401":
        description: Invalid credentials

  /driver/tasks:
    get:
      operationId: listDriverTasks
      tags: [drivers]
      summary: List tasks for a driver
      parameters:
        - name: driverId
          in: query
          required: true
          schema:
            type: integer
      responses:
        "200":
          description: Driver tasks
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: "#/components/schemas/DriverTask"

  /driver/tasks/{id}:
    get:
      operationId: getDriverTask
      tags: [drivers]
      summary: Get driver task by ID
      parameters:
        - name: id
          in: path
          required: true
          schema:
            type: integer
      responses:
        "200":
          description: Driver task
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/DriverTask"
    put:
      operationId: updateDriverTask
      tags: [drivers]
      summary: Update driver task (submit fuel entry)
      parameters:
```

```
      - name: id
        in: path
        required: true
        schema:
          type: integer
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/UpdateDriverTaskInput"
    responses:
      "200":
        description: Updated task
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/DriverTask"

/driver/notifications:
  get:
    operationId: listDriverNotifications
    tags: [drivers]
    summary: Get notifications for a driver
    parameters:
      - name: driverId
        in: query
        required: true
        schema:
          type: integer
    responses:
      "200":
        description: Driver notifications
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: "#/components/schemas/DriverNotification"

/technicians:
  get:
    operationId: listTechnicians
    tags: [drivers]
    summary: List all technicians
    responses:
      "200":
        description: List of technicians
        content:
          application/json:
            schema:
              type: array
```

```
            items:
              $ref: "#/components/schemas/Technician"
  post:
    operationId: createTechnician
    tags: [drivers]
    summary: Create a technician
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/CreateTechnicianInput"
    responses:
      "201":
        description: Created technician
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Technician"

/technician/login:
  post:
    operationId: technicianLogin
    tags: [technician]
    summary: Technician login
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/TechnicianLoginInput"
    responses:
      "200":
        description: Login result
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/TechnicianLoginResponse"

/technician/missions:
  get:
    operationId: listTechnicianMissions
    tags: [technician]
    summary: List missions for technician follow-up
    parameters:
      - name: zone
        in: query
        schema:
          type: string
      - name: status
        in: query
        schema:
```

```
          type: string
    responses:
      "200":
        description: Missions list
        content:
          application/json:
            schema:
              type: array
              items:
                $ref: "#/components/schemas/Mission"

/technician/missions/{id}/followup:
  put:
    operationId: technicianFollowUp
    tags: [technician]
    summary: Technician follow-up on a mission
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/TechnicianFollowUpInput"
    responses:
      "200":
        description: Updated mission
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Mission"

/technicians/{id}:
  put:
    operationId: updateTechnician
    tags: [drivers]
    summary: Update a technician
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    requestBody:
      required: true
      content:
        application/json:
          schema:
```

```
            $ref: "#/components/schemas/UpdateTechnicianInput"
    responses:
      "200":
        description: Updated technician
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Technician"
  delete:
    operationId: deleteTechnician
    tags: [drivers]
    summary: Delete a technician
    parameters:
      - name: id
        in: path
        required: true
        schema:
          type: integer
    responses:
      "204":
        description: Deleted

/storage/uploads/request-url:
  post:
    tags: [storage]
    operationId: requestUploadUrl
    summary: Request a presigned URL for file upload
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/RequestUploadUrlBody'
    responses:
      '200':
        description: Presigned upload URL generated
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/RequestUploadUrlResponse'
      '400':
        description: Missing or invalid required fields
      '500':
        description: Failed to generate upload URL

/storage/objects/{objectPath}:
  get:
    tags: [storage]
    operationId: getStorageObject
    summary: Serve an object entity from PRIVATE_OBJECT_DIR
    parameters:
      - name: objectPath
```

```
          in: path
          required: true
          schema:
            type: string
      responses:
        '200':
          description: Object content streamed with correct Content-Type
          content:
            '*/*':
              schema:
                type: string
                format: binary
        '404':
          description: Object not found
        '500':
          description: Failed to serve object

components:
  schemas:
    HealthStatus:
      type: object
      properties:
        status:
          type: string
      required:
        - status

    Mission:
      type: object
      properties:
        id:
          type: integer
        missionId:
          type: string
        siteName:
          type: string
        generator:
          type: string
        project:
          type: string
        driverName:
          type: string
        assignedDriver:
          type: string
        createdDate:
          type: string
        filledLiters:
          type: number
        virtualCalculated:
          type: number
        actualInTank:
          type: number
```

```
      quantityAddedLastTask:
        type: number
      city:
        type: string
      notes:
        type: string
      missionStatus:
        type: string
      createdBy:
        type: string
      technicianRemark:
        type: string
      technicianStatus:
        type: string
      reviewedBy:
        type: string
      reviewedAt:
        type: string
    required:
      - id
      - missionId
      - siteName
      - missionStatus

  CreateMissionInput:
    type: object
    properties:
      siteName:
        type: string
      generator:
        type: string
      project:
        type: string
      assignedDriver:
        type: string
      driverName:
        type: string
      filledLiters:
        type: number
      virtualCalculated:
        type: number
      actualInTank:
        type: number
      quantityAddedLastTask:
        type: number
      city:
        type: string
      notes:
        type: string
      missionStatus:
        type: string
      createdBy:
```

```
        type: string
    required:
      - siteName
      - missionStatus

  UpdateMissionInput:
    type: object
    properties:
      siteName:
        type: string
      generator:
        type: string
      project:
        type: string
      assignedDriver:
        type: string
      driverName:
        type: string
      filledLiters:
        type: number
      virtualCalculated:
        type: number
      actualInTank:
        type: number
      quantityAddedLastTask:
        type: number
      city:
        type: string
      notes:
        type: string
      missionStatus:
        type: string

  Driver:
    type: object
    properties:
      id:
        type: integer
      name:
        type: string
      phone:
        type: string
      email:
        type: string
      zone:
        type: string
      active:
        type: boolean
      passwordHash:
        type: string
      imageUrl:
        type: string
```

```
    required:
      - id
      - name
      - active

  CreateDriverInput:
    type: object
    properties:
      name:
        type: string
      phone:
        type: string
      email:
        type: string
      zone:
        type: string
      active:
        type: boolean
      password:
        type: string
    required:
      - name

  UpdateDriverInput:
    type: object
    properties:
      name:
        type: string
      phone:
        type: string
      email:
        type: string
      zone:
        type: string
      active:
        type: boolean
      password:
        type: string

  Site:
    type: object
    properties:
      id:
        type: integer
      name:
        type: string
      generator:
        type: string
      district:
        type: string
      city:
        type: string
```

```
      project:
        type: string
      cowStatus:
        type: string
      active:
        type: boolean
      currentLiters:
        type: number
      dailyVirtual:
        type: number
    required:
      - id
      - name

  CreateSiteInput:
    type: object
    properties:
      name:
        type: string
      district:
        type: string
      city:
        type: string
      project:
        type: string
      cowStatus:
        type: string
      active:
        type: boolean
    required:
      - name

  UpdateSiteInput:
    type: object
    properties:
      name:
        type: string
      district:
        type: string
      city:
        type: string
      project:
        type: string
      cowStatus:
        type: string
      active:
        type: boolean

  Generator:
    type: object
    properties:
      id:
```

```
        type: integer
      name:
        type: string
      site:
        type: string
      siteId:
        type: integer
      dailyVirtual:
        type: number
      lastAvg:
        type: number
      rateOk:
        type: boolean
      active:
        type: boolean
    required:
      - id
      - name

  CreateGeneratorInput:
    type: object
    properties:
      name:
        type: string
      site:
        type: string
      siteId:
        type: integer
      dailyVirtual:
        type: number
      lastAvg:
        type: number
      rateOk:
        type: boolean
      active:
        type: boolean
    required:
      - name

  UpdateGeneratorInput:
    type: object
    properties:
      name:
        type: string
      site:
        type: string
      siteId:
        type: integer
      dailyVirtual:
        type: number
      lastAvg:
        type: number
```

```
      rateOk:
        type: boolean
      active:
        type: boolean

  Notification:
    type: object
    properties:
      id:
        type: integer
      title:
        type: string
      message:
        type: string
      driverName:
        type: string
      sentBy:
        type: string
      createdAt:
        type: string
    required:
      - id
      - title
      - message

  CreateNotificationInput:
    type: object
    properties:
      title:
        type: string
      message:
        type: string
      driverName:
        type: string
      sentBy:
        type: string
    required:
      - title
      - message

  AppSettings:
    type: object
    properties:
      id:
        type: integer
      fuelUnitPrice:
        type: number
      vatRate:
        type: number
      supplierName:
        type: string
      supplierAddress:
```

```
        type: string
      invoicePrefix:
        type: string
      invoiceSequence:
        type: integer
    required: []

  Admin:
    type: object
    properties:
      id:
        type: integer
      name:
        type: string
      username:
        type: string
      email:
        type: string
      position:
        type: string
    required:
      - id
      - name
      - username

  CreateAdminInput:
    type: object
    properties:
      name:
        type: string
      username:
        type: string
      email:
        type: string
      password:
        type: string
      position:
        type: string
    required:
      - name
      - username
      - password

  UpdateAdminInput:
    type: object
    properties:
      name:
        type: string
      username:
        type: string
      email:
        type: string
```

```
      password:
        type: string
      position:
        type: string

  LoginInput:
    type: object
    properties:
      username:
        type: string
      password:
        type: string
    required:
      - username
      - password

  LoginResponse:
    type: object
    properties:
      success:
        type: boolean
      role:
        type: string
      username:
        type: string
    required:
      - success

  DashboardKpis:
    type: object
    properties:
      litersToday:
        type: number
      liters30d:
        type: number
      activeMissions:
        type: integer
      activeDrivers:
        type: integer
      missionsByStatus:
        type: array
        items:
          type: object
          properties:
            status:
              type: string
            count:
              type: integer
      missionsByZone:
        type: array
        items:
          type: object
```

```
        properties:
          zone:
            type: string
          count:
            type: integer
    litersByZone:
      type: array
      items:
        type: object
        properties:
          zone:
            type: string
          liters:
            type: number
    missionsByCategory:
      type: array
      items:
        type: object
        properties:
          category:
            type: string
          count:
            type: integer
    approvedForInvoicing:
      type: array
      items:
        type: object
        properties:
          siteName:
            type: string
          liters:
            type: number
          date:
            type: string
  required: []

DriverLoginInput:
  type: object
  properties:
    email:
      type: string
    password:
      type: string
  required:
    - email
    - password

DriverLoginResponse:
  type: object
  properties:
    success:
      type: boolean
```

```
        driverId:
          type: integer
        name:
          type: string
        email:
          type: string
        phone:
          type: string
        zone:
          type: string
        token:
          type: string
      required:
        - success

    DriverTask:
      type: object
      properties:
        id:
          type: integer
        driverId:
          type: integer
        siteId:
          type: integer
        siteName:
          type: string
        missionId:
          type: string
        scheduledAt:
          type: string
        status:
          type: string
        requiredLiters:
          type: number
        actualInTank:
          type: number
        quantityAdded:
          type: number
        notes:
          type: string
        createdAt:
          type: string
      required:
        - id
        - status

    UpdateDriverTaskInput:
      type: object
      properties:
        status:
          type: string
        actualInTank:
```

```
        type: number
      quantityAdded:
        type: number
      notes:
        type: string
      observations:
        type: string

  DriverNotification:
    type: object
    properties:
      id:
        type: integer
      driverId:
        type: integer
      title:
        type: string
      message:
        type: string
      type:
        type: string
      read:
        type: boolean
      createdAt:
        type: string
    required:
      - id
      - title
      - message

  Technician:
    type: object
    properties:
      id:
        type: integer
      name:
        type: string
      phone:
        type: string
      email:
        type: string
      zone:
        type: string
      active:
        type: boolean
    required:
      - id
      - name

  CreateTechnicianInput:
    type: object
    properties:
```

```
      name:
        type: string
      phone:
        type: string
      email:
        type: string
      zone:
        type: string
      active:
        type: boolean
    required:
      - name

  UpdateTechnicianInput:
    type: object
    properties:
      name:
        type: string
      phone:
        type: string
      email:
        type: string
      zone:
        type: string
      active:
        type: boolean
      password:
        type: string

  TechnicianLoginInput:
    type: object
    properties:
      email:
        type: string
      password:
        type: string
    required:
      - email
      - password

  TechnicianLoginResponse:
    type: object
    properties:
      success:
        type: boolean
      technicianId:
        type: integer
      name:
        type: string
      email:
        type: string
      zone:
```

```
      type: string
    token:
      type: string
  required:
    - success

TechnicianFollowUpInput:
  type: object
  properties:
    technicianRemark:
      type: string
    technicianStatus:
      type: string
    reviewedBy:
      type: string

RequestUploadUrlBody:
  type: object
  required: [name, size, contentType]
  properties:
    name:
      type: string
      minLength: 1
    size:
      type: integer
      minimum: 1
    contentType:
      type: string
      minLength: 1

RequestUploadUrlResponse:
  type: object
  required: [uploadURL, objectPath]
  properties:
    uploadURL:
      type: string
    objectPath:
      type: string
```

FILE: lib/api-spec/orval.config.ts
SIZE: 1,803 bytes

```
import { defineConfig, InputTransformerFn } from "orval";
import path from "path";

const root = path.resolve(__dirname, "..", "..");
const apiClientReactSrc = path.resolve(root, "lib", "api-client-react", "src");
const apiZodSrc = path.resolve(root, "lib", "api-zod", "src");

// Our exports make assumptions about the title of the API being "Api" (i.e. generated output is ‘api.ts‘).
const titleTransformer: InputTransformerFn = (config) => {
  config.info ??= {};
  config.info.title = "Api";

  return config;
};

export default defineConfig({
  "api-client-react": {
    input: {
      target: "./openapi.yaml",
      override: {
        transformer: titleTransformer,
      },
    },
    output: {
      workspace: apiClientReactSrc,
      target: "generated",
      client: "react-query",
      mode: "split",
      baseUrl: "/api",
      clean: true,
      prettier: true,
      override: {
        fetch: {
          includeHttpResponseReturnType: false,
        },
        mutator: {
          path: path.resolve(apiClientReactSrc, "custom-fetch.ts"),
          name: "customFetch",
        },
      },
    },
  },
  zod: {
    input: {
      target: "./openapi.yaml",
      override: {
        transformer: titleTransformer,
      },
    },
```

```
    output: {
      workspace: apiZodSrc,
      client: "zod",
      target: "generated",
      schemas: { path: "generated/types", type: "typescript" },
      mode: "split",
      clean: true,
      prettier: true,
      override: {
        zod: {
          coerce: {
            query: ['boolean', 'number', 'string'],
            param: ['boolean', 'number', 'string'],
            body: ['bigint', 'date'],
            response: ['bigint', 'date'],
          },
        },
        useDates: true,
        useBigInt: true,
      },
    },
  },
});
```

FILE: lib/api-spec/package.json
SIZE: 197 bytes

```
{
  "name": "@workspace/api-spec",
  "version": "0.0.0",
  "private": true,
  "scripts": {
    "codegen": "orval --config ./orval.config.ts"
  },
  "devDependencies": {
    "orval": "^8.5.2"
  }
}
```

FILE: lib/api-zod/package.json
SIZE: 189 bytes

```
{
  "name": "@workspace/api-zod",
  "version": "0.0.0",
  "private": true,
  "type": "module",
  "exports": {
    ".": "./src/index.ts"
  },
  "dependencies": {
    "zod": "catalog:"
  }
}
```

FILE: lib/api-zod/src/generated/api.ts
SIZE: 20,943 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */
import * as zod from "zod";

/**
 * @summary Health check
 */
export const HealthCheckResponse = zod.object({
  status: zod.string(),
});

/**
 * @summary List all missions
 */
export const ListMissionsResponseItem = zod.object({
  id: zod.number(),
  missionId: zod.string(),
  siteName: zod.string(),
  generator: zod.string().optional(),
  project: zod.string().optional(),
  driverName: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  createdDate: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string(),
  createdBy: zod.string().optional(),
  technicianRemark: zod.string().optional(),
  technicianStatus: zod.string().optional(),
  reviewedBy: zod.string().optional(),
  reviewedAt: zod.string().optional(),
});
export const ListMissionsResponse = zod.array(ListMissionsResponseItem);

/**
 * @summary Create a mission
 */
export const CreateMissionBody = zod.object({
  siteName: zod.string(),
  generator: zod.string().optional(),
```

```
  project: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  driverName: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string(),
  createdBy: zod.string().optional(),
});

/**
 * @summary Get a mission by ID
 */
export const GetMissionParams = zod.object({
  id: zod.coerce.number(),
});

export const GetMissionResponse = zod.object({
  id: zod.number(),
  missionId: zod.string(),
  siteName: zod.string(),
  generator: zod.string().optional(),
  project: zod.string().optional(),
  driverName: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  createdDate: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string(),
  createdBy: zod.string().optional(),
  technicianRemark: zod.string().optional(),
  technicianStatus: zod.string().optional(),
  reviewedBy: zod.string().optional(),
  reviewedAt: zod.string().optional(),
});

/**
 * @summary Update a mission
 */
export const UpdateMissionParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateMissionBody = zod.object({
  siteName: zod.string().optional(),
```

```
  generator: zod.string().optional(),
  project: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  driverName: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string().optional(),
});

export const UpdateMissionResponse = zod.object({
  id: zod.number(),
  missionId: zod.string(),
  siteName: zod.string(),
  generator: zod.string().optional(),
  project: zod.string().optional(),
  driverName: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  createdDate: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string(),
  createdBy: zod.string().optional(),
  technicianRemark: zod.string().optional(),
  technicianStatus: zod.string().optional(),
  reviewedBy: zod.string().optional(),
  reviewedAt: zod.string().optional(),
});

/**
 * @summary Delete a mission
 */
export const DeleteMissionParams = zod.object({
  id: zod.coerce.number(),
});

/**
 * @summary List all drivers
 */
export const ListDriversResponseItem = zod.object({
  id: zod.number(),
  name: zod.string(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
```

```
  active: zod.boolean(),
  passwordHash: zod.string().optional(),
  imageUrl: zod.string().optional(),
});
export const ListDriversResponse = zod.array(ListDriversResponseItem);

/**
 * @summary Create a driver
 */
export const CreateDriverBody = zod.object({
  name: zod.string(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean().optional(),
  password: zod.string().optional(),
});

/**
 * @summary Update a driver
 */
export const UpdateDriverParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateDriverBody = zod.object({
  name: zod.string().optional(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean().optional(),
  password: zod.string().optional(),
});

export const UpdateDriverResponse = zod.object({
  id: zod.number(),
  name: zod.string(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean(),
  passwordHash: zod.string().optional(),
  imageUrl: zod.string().optional(),
});

/**
 * @summary Delete a driver
 */
export const DeleteDriverParams = zod.object({
  id: zod.coerce.number(),
});
```

```ts
/**
 * @summary List all sites
 */
export const ListSitesResponseItem = zod.object({
  id: zod.number(),
  name: zod.string(),
  generator: zod.string().optional(),
  district: zod.string().optional(),
  city: zod.string().optional(),
  project: zod.string().optional(),
  cowStatus: zod.string().optional(),
  active: zod.boolean().optional(),
  currentLiters: zod.number().optional(),
  dailyVirtual: zod.number().optional(),
});
export const ListSitesResponse = zod.array(ListSitesResponseItem);

/**
 * @summary Create a site
 */
export const CreateSiteBody = zod.object({
  name: zod.string(),
  district: zod.string().optional(),
  city: zod.string().optional(),
  project: zod.string().optional(),
  cowStatus: zod.string().optional(),
  active: zod.boolean().optional(),
});

/**
 * @summary Update a site
 */
export const UpdateSiteParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateSiteBody = zod.object({
  name: zod.string().optional(),
  district: zod.string().optional(),
  city: zod.string().optional(),
  project: zod.string().optional(),
  cowStatus: zod.string().optional(),
  active: zod.boolean().optional(),
});

export const UpdateSiteResponse = zod.object({
  id: zod.number(),
  name: zod.string(),
  generator: zod.string().optional(),
  district: zod.string().optional(),
  city: zod.string().optional(),
  project: zod.string().optional(),
```

```
  cowStatus: zod.string().optional(),
  active: zod.boolean().optional(),
  currentLiters: zod.number().optional(),
  dailyVirtual: zod.number().optional(),
});

/**
 * @summary Delete a site
 */
export const DeleteSiteParams = zod.object({
  id: zod.coerce.number(),
});

/**
 * @summary List all generators
 */
export const ListGeneratorsResponseItem = zod.object({
  id: zod.number(),
  name: zod.string(),
  site: zod.string().optional(),
  siteId: zod.number().optional(),
  dailyVirtual: zod.number().optional(),
  lastAvg: zod.number().optional(),
  rateOk: zod.boolean().optional(),
  active: zod.boolean().optional(),
});
export const ListGeneratorsResponse = zod.array(ListGeneratorsResponseItem);

/**
 * @summary Create a generator
 */
export const CreateGeneratorBody = zod.object({
  name: zod.string(),
  site: zod.string().optional(),
  siteId: zod.number().optional(),
  dailyVirtual: zod.number().optional(),
  lastAvg: zod.number().optional(),
  rateOk: zod.boolean().optional(),
  active: zod.boolean().optional(),
});

/**
 * @summary Update a generator
 */
export const UpdateGeneratorParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateGeneratorBody = zod.object({
  name: zod.string().optional(),
  site: zod.string().optional(),
  siteId: zod.number().optional(),
```

```
  dailyVirtual: zod.number().optional(),
  lastAvg: zod.number().optional(),
  rateOk: zod.boolean().optional(),
  active: zod.boolean().optional(),
});

export const UpdateGeneratorResponse = zod.object({
  id: zod.number(),
  name: zod.string(),
  site: zod.string().optional(),
  siteId: zod.number().optional(),
  dailyVirtual: zod.number().optional(),
  lastAvg: zod.number().optional(),
  rateOk: zod.boolean().optional(),
  active: zod.boolean().optional(),
});

/**
 * @summary Delete a generator
 */
export const DeleteGeneratorParams = zod.object({
  id: zod.coerce.number(),
});

/**
 * @summary List all notifications
 */
export const ListNotificationsResponseItem = zod.object({
  id: zod.number(),
  title: zod.string(),
  message: zod.string(),
  driverName: zod.string().optional(),
  sentBy: zod.string().optional(),
  createdAt: zod.string().optional(),
});
export const ListNotificationsResponse = zod.array(
  ListNotificationsResponseItem,
);

/**
 * @summary Send a notification
 */
export const CreateNotificationBody = zod.object({
  title: zod.string(),
  message: zod.string(),
  driverName: zod.string().optional(),
  sentBy: zod.string().optional(),
});

/**
 * @summary Get app settings
 */
```

```ts
export const GetSettingsResponse = zod.object({
  id: zod.number().optional(),
  fuelUnitPrice: zod.number().optional(),
  vatRate: zod.number().optional(),
  supplierName: zod.string().optional(),
  supplierAddress: zod.string().optional(),
  invoicePrefix: zod.string().optional(),
  invoiceSequence: zod.number().optional(),
});

/**
 * @summary Update app settings
 */
export const UpdateSettingsBody = zod.object({
  id: zod.number().optional(),
  fuelUnitPrice: zod.number().optional(),
  vatRate: zod.number().optional(),
  supplierName: zod.string().optional(),
  supplierAddress: zod.string().optional(),
  invoicePrefix: zod.string().optional(),
  invoiceSequence: zod.number().optional(),
});

export const UpdateSettingsResponse = zod.object({
  id: zod.number().optional(),
  fuelUnitPrice: zod.number().optional(),
  vatRate: zod.number().optional(),
  supplierName: zod.string().optional(),
  supplierAddress: zod.string().optional(),
  invoicePrefix: zod.string().optional(),
  invoiceSequence: zod.number().optional(),
});

/**
 * @summary List all admin users
 */
export const ListAdminsResponseItem = zod.object({
  id: zod.number(),
  name: zod.string(),
  username: zod.string(),
  email: zod.string().optional(),
  position: zod.string().optional(),
});
export const ListAdminsResponse = zod.array(ListAdminsResponseItem);

/**
 * @summary Create an admin
 */
export const CreateAdminBody = zod.object({
  name: zod.string(),
  username: zod.string(),
  email: zod.string().optional(),
```

```
  password: zod.string(),
  position: zod.string().optional(),
});

/**
 * @summary Update an admin
 */
export const UpdateAdminParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateAdminBody = zod.object({
  name: zod.string().optional(),
  username: zod.string().optional(),
  email: zod.string().optional(),
  password: zod.string().optional(),
  position: zod.string().optional(),
});

export const UpdateAdminResponse = zod.object({
  id: zod.number(),
  name: zod.string(),
  username: zod.string(),
  email: zod.string().optional(),
  position: zod.string().optional(),
});

/**
 * @summary Delete an admin
 */
export const DeleteAdminParams = zod.object({
  id: zod.coerce.number(),
});

/**
 * @summary Admin login
 */
export const AdminLoginBody = zod.object({
  username: zod.string(),
  password: zod.string(),
});

export const AdminLoginResponse = zod.object({
  success: zod.boolean(),
  role: zod.string().optional(),
  username: zod.string().optional(),
});

/**
 * @summary Get dashboard KPIs
 */
export const GetDashboardKpisResponse = zod.object({
```

```
  litersToday: zod.number().optional(),
  liters30d: zod.number().optional(),
  activeMissions: zod.number().optional(),
  activeDrivers: zod.number().optional(),
  missionsByStatus: zod
    .array(
      zod.object({
        status: zod.string().optional(),
        count: zod.number().optional(),
      }),
    )
    .optional(),
  missionsByZone: zod
    .array(
      zod.object({
        zone: zod.string().optional(),
        count: zod.number().optional(),
      }),
    )
    .optional(),
  litersByZone: zod
    .array(
      zod.object({
        zone: zod.string().optional(),
        liters: zod.number().optional(),
      }),
    )
    .optional(),
  missionsByCategory: zod
    .array(
      zod.object({
        category: zod.string().optional(),
        count: zod.number().optional(),
      }),
    )
    .optional(),
  approvedForInvoicing: zod
    .array(
      zod.object({
        siteName: zod.string().optional(),
        liters: zod.number().optional(),
        date: zod.string().optional(),
      }),
    )
    .optional(),
});

/**
 * @summary Driver login
 */
export const DriverLoginBody = zod.object({
  email: zod.string(),
```

```
  password: zod.string(),
});

export const DriverLoginResponse = zod.object({
  success: zod.boolean(),
  driverId: zod.number().optional(),
  name: zod.string().optional(),
  email: zod.string().optional(),
  phone: zod.string().optional(),
  zone: zod.string().optional(),
  token: zod.string().optional(),
});

/**
 * @summary List tasks for a driver
 */
export const ListDriverTasksQueryParams = zod.object({
  driverId: zod.coerce.number(),
});

export const ListDriverTasksResponseItem = zod.object({
  id: zod.number(),
  driverId: zod.number().optional(),
  siteId: zod.number().optional(),
  siteName: zod.string().optional(),
  missionId: zod.string().optional(),
  scheduledAt: zod.string().optional(),
  status: zod.string(),
  requiredLiters: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAdded: zod.number().optional(),
  notes: zod.string().optional(),
  createdAt: zod.string().optional(),
});
export const ListDriverTasksResponse = zod.array(ListDriverTasksResponseItem);

/**
 * @summary Get driver task by ID
 */
export const GetDriverTaskParams = zod.object({
  id: zod.coerce.number(),
});

export const GetDriverTaskResponse = zod.object({
  id: zod.number(),
  driverId: zod.number().optional(),
  siteId: zod.number().optional(),
  siteName: zod.string().optional(),
  missionId: zod.string().optional(),
  scheduledAt: zod.string().optional(),
  status: zod.string(),
  requiredLiters: zod.number().optional(),
```

```
  actualInTank: zod.number().optional(),
  quantityAdded: zod.number().optional(),
  notes: zod.string().optional(),
  createdAt: zod.string().optional(),
});

/**
 * @summary Update driver task (submit fuel entry)
 */
export const UpdateDriverTaskParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateDriverTaskBody = zod.object({
  status: zod.string().optional(),
  actualInTank: zod.number().optional(),
  quantityAdded: zod.number().optional(),
  notes: zod.string().optional(),
  observations: zod.string().optional(),
});

export const UpdateDriverTaskResponse = zod.object({
  id: zod.number(),
  driverId: zod.number().optional(),
  siteId: zod.number().optional(),
  siteName: zod.string().optional(),
  missionId: zod.string().optional(),
  scheduledAt: zod.string().optional(),
  status: zod.string(),
  requiredLiters: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAdded: zod.number().optional(),
  notes: zod.string().optional(),
  createdAt: zod.string().optional(),
});

/**
 * @summary Get notifications for a driver
 */
export const ListDriverNotificationsQueryParams = zod.object({
  driverId: zod.coerce.number(),
});

export const ListDriverNotificationsResponseItem = zod.object({
  id: zod.number(),
  driverId: zod.number().optional(),
  title: zod.string(),
  message: zod.string(),
  type: zod.string().optional(),
  read: zod.boolean().optional(),
  createdAt: zod.string().optional(),
});
```

```ts
export const ListDriverNotificationsResponse = zod.array(
  ListDriverNotificationsResponseItem,
);

/**
 * @summary List all technicians
 */
export const ListTechniciansResponseItem = zod.object({
  id: zod.number(),
  name: zod.string(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean().optional(),
});
export const ListTechniciansResponse = zod.array(ListTechniciansResponseItem);

/**
 * @summary Create a technician
 */
export const CreateTechnicianBody = zod.object({
  name: zod.string(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean().optional(),
});

/**
 * @summary Technician login
 */
export const TechnicianLoginBody = zod.object({
  email: zod.string(),
  password: zod.string(),
});

export const TechnicianLoginResponse = zod.object({
  success: zod.boolean(),
  technicianId: zod.number().optional(),
  name: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  token: zod.string().optional(),
});

/**
 * @summary List missions for technician follow-up
 */
export const ListTechnicianMissionsQueryParams = zod.object({
  zone: zod.coerce.string().optional(),
  status: zod.coerce.string().optional(),
});
```

```
export const ListTechnicianMissionsResponseItem = zod.object({
  id: zod.number(),
  missionId: zod.string(),
  siteName: zod.string(),
  generator: zod.string().optional(),
  project: zod.string().optional(),
  driverName: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  createdDate: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string(),
  createdBy: zod.string().optional(),
  technicianRemark: zod.string().optional(),
  technicianStatus: zod.string().optional(),
  reviewedBy: zod.string().optional(),
  reviewedAt: zod.string().optional(),
});
export const ListTechnicianMissionsResponse = zod.array(
  ListTechnicianMissionsResponseItem,
);

/**
 * @summary Technician follow-up on a mission
 */
export const TechnicianFollowUpParams = zod.object({
  id: zod.coerce.number(),
});

export const TechnicianFollowUpBody = zod.object({
  technicianRemark: zod.string().optional(),
  technicianStatus: zod.string().optional(),
  reviewedBy: zod.string().optional(),
});

export const TechnicianFollowUpResponse = zod.object({
  id: zod.number(),
  missionId: zod.string(),
  siteName: zod.string(),
  generator: zod.string().optional(),
  project: zod.string().optional(),
  driverName: zod.string().optional(),
  assignedDriver: zod.string().optional(),
  createdDate: zod.string().optional(),
  filledLiters: zod.number().optional(),
  virtualCalculated: zod.number().optional(),
  actualInTank: zod.number().optional(),
```

```
  quantityAddedLastTask: zod.number().optional(),
  city: zod.string().optional(),
  notes: zod.string().optional(),
  missionStatus: zod.string(),
  createdBy: zod.string().optional(),
  technicianRemark: zod.string().optional(),
  technicianStatus: zod.string().optional(),
  reviewedBy: zod.string().optional(),
  reviewedAt: zod.string().optional(),
});

/**
 * @summary Update a technician
 */
export const UpdateTechnicianParams = zod.object({
  id: zod.coerce.number(),
});

export const UpdateTechnicianBody = zod.object({
  name: zod.string().optional(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean().optional(),
  password: zod.string().optional(),
});

export const UpdateTechnicianResponse = zod.object({
  id: zod.number(),
  name: zod.string(),
  phone: zod.string().optional(),
  email: zod.string().optional(),
  zone: zod.string().optional(),
  active: zod.boolean().optional(),
});

/**
 * @summary Delete a technician
 */
export const DeleteTechnicianParams = zod.object({
  id: zod.coerce.number(),
});

/**
 * @summary Request a presigned URL for file upload
 */

export const RequestUploadUrlBody = zod.object({
  name: zod.string().min(1),
  size: zod.number().min(1),
  contentType: zod.string().min(1),
});
```

```ts
export const RequestUploadUrlResponse = zod.object({
  uploadURL: zod.string(),
  objectPath: zod.string(),
});

/**
 * @summary Serve an object entity from PRIVATE_OBJECT_DIR
 */
export const GetStorageObjectParams = zod.object({
  objectPath: zod.coerce.string(),
});
```

FILE: lib/api-zod/src/generated/types/admin.ts
SIZE: 251 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Admin {
  id: number;
  name: string;
  username: string;
  email?: string;
  position?: string;
}
```

FILE: lib/api-zod/src/generated/types/appSettings.ts
SIZE: 336 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface AppSettings {
  id?: number;
  fuelUnitPrice?: number;
  vatRate?: number;
  supplierName?: string;
  supplierAddress?: string;
  invoicePrefix?: string;
  invoiceSequence?: number;
}
```

FILE: lib/api-zod/src/generated/types/createAdminInput.ts
SIZE: 268 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateAdminInput {
  name: string;
  username: string;
  email?: string;
  password: string;
  position?: string;
}
```

FILE: lib/api-zod/src/generated/types/createDriverInput.ts
SIZE: 284 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateDriverInput {
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
  password?: string;
}
```

FILE: lib/api-zod/src/generated/types/createGeneratorInput.ts
SIZE: 314 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateGeneratorInput {
  name: string;
  site?: string;
  siteId?: number;
  dailyVirtual?: number;
  lastAvg?: number;
  rateOk?: boolean;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/createMissionInput.ts
SIZE: 483 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateMissionInput {
  siteName: string;
  generator?: string;
  project?: string;
  assignedDriver?: string;
  driverName?: string;
  filledLiters?: number;
  virtualCalculated?: number;
  actualInTank?: number;
  quantityAddedLastTask?: number;
  city?: string;
  notes?: string;
  missionStatus: string;
  createdBy?: string;
}
```

FILE: lib/api-zod/src/generated/types/createNotificationInput.ts
SIZE: 258 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateNotificationInput {
  title: string;
  message: string;
  driverName?: string;
  sentBy?: string;
}
```

FILE: lib/api-zod/src/generated/types/createSiteInput.ts
SIZE: 288 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateSiteInput {
  name: string;
  district?: string;
  city?: string;
  project?: string;
  cowStatus?: string;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/createTechnicianInput.ts
SIZE: 267 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface CreateTechnicianInput {
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/dashboardKpis.ts
SIZE: 1,029 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */
import type { DashboardKpisApprovedForInvoicingItem } from "./dashboardKpisApprovedForInvoicingItem";
import type { DashboardKpisLitersByZoneItem } from "./dashboardKpisLitersByZoneItem";
import type { DashboardKpisMissionsByCategoryItem } from "./dashboardKpisMissionsByCategoryItem";
import type { DashboardKpisMissionsByStatusItem } from "./dashboardKpisMissionsByStatusItem";
import type { DashboardKpisMissionsByZoneItem } from "./dashboardKpisMissionsByZoneItem";

export interface DashboardKpis {
  litersToday?: number;
  liters30d?: number;
  activeMissions?: number;
  activeDrivers?: number;
  missionsByStatus?: DashboardKpisMissionsByStatusItem[];
  missionsByZone?: DashboardKpisMissionsByZoneItem[];
  litersByZone?: DashboardKpisLitersByZoneItem[];
  missionsByCategory?: DashboardKpisMissionsByCategoryItem[];
  approvedForInvoicing?: DashboardKpisApprovedForInvoicingItem[];
}
```

FILE: lib/api-zod/src/generated/types/dashboardKpisApprovedForInvoicingItem.ts
SIZE: 249 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type DashboardKpisApprovedForInvoicingItem = {
  siteName?: string;
  liters?: number;
  date?: string;
};
```

FILE: lib/api-zod/src/generated/types/dashboardKpisLitersByZoneItem.ts
SIZE: 220 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type DashboardKpisLitersByZoneItem = {
  zone?: string;
  liters?: number;
};
```

FILE: lib/api-zod/src/generated/types/dashboardKpisMissionsByCategoryItem.ts
SIZE: 229 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type DashboardKpisMissionsByCategoryItem = {
  category?: string;
  count?: number;
};
```

FILE: lib/api-zod/src/generated/types/dashboardKpisMissionsByStatusItem.ts
SIZE: 225 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type DashboardKpisMissionsByStatusItem = {
  status?: string;
  count?: number;
};
```

FILE: lib/api-zod/src/generated/types/dashboardKpisMissionsByZoneItem.ts
SIZE: 221 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type DashboardKpisMissionsByZoneItem = {
  zone?: string;
  count?: number;
};
```

FILE: lib/api-zod/src/generated/types/driver.ts
SIZE: 311 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Driver {
  id: number;
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active: boolean;
  passwordHash?: string;
  imageUrl?: string;
}
```

FILE: lib/api-zod/src/generated/types/driverLoginInput.ts
SIZE: 210 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface DriverLoginInput {
  email: string;
  password: string;
}
```

FILE: lib/api-zod/src/generated/types/driverLoginResponse.ts
SIZE: 305 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface DriverLoginResponse {
  success: boolean;
  driverId?: number;
  name?: string;
  email?: string;
  phone?: string;
  zone?: string;
  token?: string;
}
```

FILE: lib/api-zod/src/generated/types/driverNotification.ts
SIZE: 303 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface DriverNotification {
  id: number;
  driverId?: number;
  title: string;
  message: string;
  type?: string;
  read?: boolean;
  createdAt?: string;
}
```

FILE: lib/api-zod/src/generated/types/driverTask.ts
SIZE: 424 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface DriverTask {
  id: number;
  driverId?: number;
  siteId?: number;
  siteName?: string;
  missionId?: string;
  scheduledAt?: string;
  status: string;
  requiredLiters?: number;
  actualInTank?: number;
  quantityAdded?: number;
  notes?: string;
  createdAt?: string;
}
```

FILE: lib/api-zod/src/generated/types/generator.ts
SIZE: 317 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Generator {
  id: number;
  name: string;
  site?: string;
  siteId?: number;
  dailyVirtual?: number;
  lastAvg?: number;
  rateOk?: boolean;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/healthStatus.ts
SIZE: 187 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface HealthStatus {
  status: string;
}
```

FILE: lib/api-zod/src/generated/types/index.ts
SIZE: 1,781 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export * from "./admin";
export * from "./appSettings";
export * from "./createAdminInput";
export * from "./createDriverInput";
export * from "./createGeneratorInput";
export * from "./createMissionInput";
export * from "./createNotificationInput";
export * from "./createSiteInput";
export * from "./createTechnicianInput";
export * from "./dashboardKpis";
export * from "./dashboardKpisApprovedForInvoicingItem";
export * from "./dashboardKpisLitersByZoneItem";
export * from "./dashboardKpisMissionsByCategoryItem";
export * from "./dashboardKpisMissionsByStatusItem";
export * from "./dashboardKpisMissionsByZoneItem";
export * from "./driver";
export * from "./driverLoginInput";
export * from "./driverLoginResponse";
export * from "./driverNotification";
export * from "./driverTask";
export * from "./generator";
export * from "./healthStatus";
export * from "./listDriverNotificationsParams";
export * from "./listDriverTasksParams";
export * from "./listTechnicianMissionsParams";
export * from "./loginInput";
export * from "./loginResponse";
export * from "./mission";
export * from "./notification";
export * from "./requestUploadUrlBody";
export * from "./requestUploadUrlResponse";
export * from "./site";
export * from "./technician";
export * from "./technicianFollowUpInput";
export * from "./technicianLoginInput";
export * from "./technicianLoginResponse";
export * from "./updateAdminInput";
export * from "./updateDriverInput";
export * from "./updateDriverTaskInput";
export * from "./updateGeneratorInput";
export * from "./updateMissionInput";
```

```
export * from "./updateSiteInput";
export * from "./updateTechnicianInput";
```

FILE: lib/api-zod/src/generated/types/listDriverNotificationsParams.ts
SIZE: 204 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type ListDriverNotificationsParams = {
  driverId: number;
};
```

FILE: lib/api-zod/src/generated/types/listDriverTasksParams.ts
SIZE: 196 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type ListDriverTasksParams = {
  driverId: number;
};
```

FILE: lib/api-zod/src/generated/types/listTechnicianMissionsParams.ts
SIZE: 219 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export type ListTechnicianMissionsParams = {
  zone?: string;
  status?: string;
};
```

FILE: lib/api-zod/src/generated/types/loginInput.ts
SIZE: 207 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface LoginInput {
  username: string;
  password: string;
}
```

FILE: lib/api-zod/src/generated/types/loginResponse.ts
SIZE: 228 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface LoginResponse {
  success: boolean;
  role?: string;
  username?: string;
}
```

FILE: lib/api-zod/src/generated/types/mission.ts
SIZE: 635 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Mission {
  id: number;
  missionId: string;
  siteName: string;
  generator?: string;
  project?: string;
  driverName?: string;
  assignedDriver?: string;
  createdDate?: string;
  filledLiters?: number;
  virtualCalculated?: number;
  actualInTank?: number;
  quantityAddedLastTask?: number;
  city?: string;
  notes?: string;
  missionStatus: string;
  createdBy?: string;
  technicianRemark?: string;
  technicianStatus?: string;
  reviewedBy?: string;
  reviewedAt?: string;
}
```

FILE: lib/api-zod/src/generated/types/notification.ts
SIZE: 283 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Notification {
  id: number;
  title: string;
  message: string;
  driverName?: string;
  sentBy?: string;
  createdAt?: string;
}
```

FILE: lib/api-zod/src/generated/types/requestUploadUrlBody.ts
SIZE: 296 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface RequestUploadUrlBody {
  /** @minLength 1 */
  name: string;
  /** @minimum 1 */
  size: number;
  /** @minLength 1 */
  contentType: string;
}
```

FILE: lib/api-zod/src/generated/types/requestUploadUrlResponse.ts
SIZE: 224 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface RequestUploadUrlResponse {
  uploadURL: string;
  objectPath: string;
}
```

FILE: lib/api-zod/src/generated/types/site.ts
SIZE: 364 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Site {
  id: number;
  name: string;
  generator?: string;
  district?: string;
  city?: string;
  project?: string;
  cowStatus?: string;
  active?: boolean;
  currentLiters?: number;
  dailyVirtual?: number;
}
```

FILE: lib/api-zod/src/generated/types/technician.ts
SIZE: 270 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface Technician {
  id: number;
  name: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/technicianFollowUpInput.ts
SIZE: 261 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface TechnicianFollowUpInput {
  technicianRemark?: string;
  technicianStatus?: string;
  reviewedBy?: string;
}
```

FILE: lib/api-zod/src/generated/types/technicianLoginInput.ts
SIZE: 214 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface TechnicianLoginInput {
  email: string;
  password: string;
}
```

FILE: lib/api-zod/src/generated/types/technicianLoginResponse.ts
SIZE: 295 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface TechnicianLoginResponse {
  success: boolean;
  technicianId?: number;
  name?: string;
  email?: string;
  zone?: string;
  token?: string;
}
```

FILE: lib/api-zod/src/generated/types/updateAdminInput.ts
SIZE: 271 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateAdminInput {
  name?: string;
  username?: string;
  email?: string;
  password?: string;
  position?: string;
}
```

FILE: lib/api-zod/src/generated/types/updateDriverInput.ts
SIZE: 285 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateDriverInput {
  name?: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
  password?: string;
}
```

FILE: lib/api-zod/src/generated/types/updateDriverTaskInput.ts
SIZE: 291 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateDriverTaskInput {
  status?: string;
  actualInTank?: number;
  quantityAdded?: number;
  notes?: string;
  observations?: string;
}
```

FILE: lib/api-zod/src/generated/types/updateGeneratorInput.ts
SIZE: 315 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateGeneratorInput {
  name?: string;
  site?: string;
  siteId?: number;
  dailyVirtual?: number;
  lastAvg?: number;
  rateOk?: boolean;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/updateMissionInput.ts
SIZE: 463 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateMissionInput {
  siteName?: string;
  generator?: string;
  project?: string;
  assignedDriver?: string;
  driverName?: string;
  filledLiters?: number;
  virtualCalculated?: number;
  actualInTank?: number;
  quantityAddedLastTask?: number;
  city?: string;
  notes?: string;
  missionStatus?: string;
}
```

FILE: lib/api-zod/src/generated/types/updateSiteInput.ts
SIZE: 289 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateSiteInput {
  name?: string;
  district?: string;
  city?: string;
  project?: string;
  cowStatus?: string;
  active?: boolean;
}
```

FILE: lib/api-zod/src/generated/types/updateTechnicianInput.ts
SIZE: 289 bytes

```
/**
 * Generated by orval v8.5.3 ?
 * Do not edit manually.
 * Api
 * ACES Managed Services API
 * OpenAPI spec version: 0.1.0
 */

export interface UpdateTechnicianInput {
  name?: string;
  phone?: string;
  email?: string;
  zone?: string;
  active?: boolean;
  password?: string;
}
```

FILE: lib/api-zod/src/index.ts
SIZE: 68 bytes

```
export * from "./generated/api";
export * from "./generated/types";
```

FILE: lib/api-zod/tsconfig.json
SIZE: 221 bytes

```
{
  "extends": "../../tsconfig.base.json",
  "compilerOptions": {
    "composite": true,
    "declarationMap": true,
    "emitDeclarationOnly": true,
    "outDir": "dist",
    "rootDir": "src"
  },
  "include": ["src"]
}
```

FILE: lib/db/drizzle.config.ts
SIZE: 352 bytes

```
import { defineConfig } from "drizzle-kit";
import path from "path";

if (!process.env.DATABASE_URL) {
  throw new Error("DATABASE_URL, ensure the database is provisioned");
}

export default defineConfig({
  schema: path.join(__dirname, "./src/schema/index.ts"),
  dialect: "postgresql",
  dbCredentials: {
    url: process.env.DATABASE_URL,
  },
});
```

FILE: lib/db/package.json
SIZE: 577 bytes

```
{
  "name": "@workspace/db",
  "version": "0.0.0",
  "private": true,
  "type": "module",
  "exports": {
    ".": "./src/index.ts",
    "./schema": "./src/schema/index.ts"
  },
  "scripts": {
    "push": "drizzle-kit push --config ./drizzle.config.ts",
    "push-force": "drizzle-kit push --force --config ./drizzle.config.ts"
  },
  "dependencies": {
    "drizzle-orm": "catalog:",
    "drizzle-zod": "^0.8.3",
    "pg": "^8.20.0",
    "zod": "catalog:"
  },
  "devDependencies": {
    "@types/node": "catalog:",
    "@types/pg": "^8.18.0",
    "drizzle-kit": "^0.31.9"
  }
}
```

FILE: lib/db/src/index.ts
SIZE: 416 bytes

```
import { drizzle } from "drizzle-orm/node-postgres";
import pg from "pg";
import * as schema from "./schema";

const { Pool } = pg;

if (!process.env.DATABASE_URL) {
  throw new Error(
    "DATABASE_URL must be set. Did you forget to provision a database?",
  );
}

export const pool = new Pool({ connectionString: process.env.DATABASE_URL });
export const db = drizzle(pool, { schema });

export * from "./schema";
```

FILE: lib/db/src/schema/admins.ts
SIZE: 837 bytes

```
import { pgTable, serial, text, timestamp } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const adminsTable = pgTable("admins", {
  id: serial("id").primaryKey(),
  name: text("name").notNull(),
  username: text("username").notNull().unique(),
  email: text("email").notNull().default(""),
  passwordHash: text("password_hash").notNull(),
  position: text("position").notNull().default("User"),
  role: text("role").notNull().default("superadmin"),
  region: text("region").notNull().default(""),
  createdAt: timestamp("created_at").defaultNow(),
});

export const insertAdminSchema = createInsertSchema(adminsTable).omit({ id: true, createdAt: true });
export type InsertAdmin = z.infer<typeof insertAdminSchema>;
export type Admin = typeof adminsTable.$inferSelect;
```

FILE: lib/db/src/schema/driver-entries.ts
SIZE: 892 bytes

```
import { pgTable, serial, text, real, timestamp, integer } from "drizzle-orm/pg-core";

export const driverEntriesTable = pgTable("driver_entries", {
  id: serial("id").primaryKey(),
  missionId: integer("mission_id").notNull(),
  missionRef: text("mission_ref").notNull().default(""),
  siteName: text("site_name").notNull().default(""),
  driverId: integer("driver_id"),
  driverName: text("driver_name").notNull().default(""),
  litersBefore: real("liters_before"),
  litersAdded: real("liters_added"),
  completionDate: timestamp("completion_date"),
  notes: text("notes").default(""),
  odoBeforePhoto: text("odo_before_photo"),
  odoAfterPhoto: text("odo_after_photo"),
  tankBeforePhoto: text("tank_before_photo"),
  tankAfterPhoto: text("tank_after_photo"),
  submittedAt: timestamp("submitted_at").defaultNow(),
});

export type DriverEntry = typeof driverEntriesTable.$inferSelect;
```

FILE: lib/db/src/schema/drivers.ts
SIZE: 2,427 bytes

```
import { pgTable, serial, text, boolean, timestamp, integer } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const driversTable = pgTable("drivers", {
  id: serial("id").primaryKey(),
  name: text("name").notNull(),
  phone: text("phone").notNull().default(""),
  email: text("email").notNull().default(""),
  zone: text("zone").notNull().default(""),
  active: boolean("active").notNull().default(true),
  passwordHash: text("password_hash").notNull().default(""),
  imageUrl: text("image_url").default(""),
  createdAt: timestamp("created_at").defaultNow(),
});

export const driverTasksTable = pgTable("driver_tasks", {
  id: serial("id").primaryKey(),
  driverId: integer("driver_id").notNull(),
  siteId: integer("site_id").notNull().default(0),
  siteName: text("site_name").notNull(),
  missionId: text("mission_id").notNull().default(""),
  scheduledAt: timestamp("scheduled_at").defaultNow(),
  status: text("status").notNull().default("pending"),
  requiredLiters: serial("required_liters"),
  actualInTank: serial("actual_in_tank"),
  quantityAdded: serial("quantity_added"),
  notes: text("notes").default(""),
  observations: text("observations").default(""),
  createdAt: timestamp("created_at").defaultNow(),
});

export const driverNotificationsTable = pgTable("driver_notifications", {
  id: serial("id").primaryKey(),
  driverId: integer("driver_id"),
  title: text("title").notNull(),
  message: text("message").notNull(),
  type: text("type").notNull().default("info"),
  read: boolean("read").notNull().default(false),
  createdAt: timestamp("created_at").defaultNow(),
});

export const insertDriverSchema = createInsertSchema(driversTable).omit({ id: true, createdAt: true });
export type InsertDriver = z.infer<typeof insertDriverSchema>;
export type Driver = typeof driversTable.$inferSelect;

export const insertDriverTaskSchema = createInsertSchema(driverTasksTable).omit({ id: true, createdAt: true });
export type InsertDriverTask = z.infer<typeof insertDriverTaskSchema>;
export type DriverTask = typeof driverTasksTable.$inferSelect;
```

```
export const insertDriverNotificationSchema = createInsertSchema(driverNotificationsTable).omit({ id: true, crea
  tedAt: true });
export type InsertDriverNotification = z.infer<typeof insertDriverNotificationSchema>;
export type DriverNotification = typeof driverNotificationsTable.$inferSelect;
```

FILE: lib/db/src/schema/generators.ts
SIZE: 893 bytes

```
import { pgTable, serial, text, boolean, real, integer, timestamp } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const generatorsTable = pgTable("generators", {
  id: serial("id").primaryKey(),
  name: text("name").notNull(),
  site: text("site").notNull().default(""),
  siteId: integer("site_id").default(0),
  dailyVirtual: real("daily_virtual").notNull().default(0),
  lastAvg: real("last_avg").notNull().default(0),
  rateOk: boolean("rate_ok").notNull().default(true),
  active: boolean("active").notNull().default(true),
  createdAt: timestamp("created_at").defaultNow(),
});

export const insertGeneratorSchema = createInsertSchema(generatorsTable).omit({ id: true, createdAt: true });
export type InsertGenerator = z.infer<typeof insertGeneratorSchema>;
export type Generator = typeof generatorsTable.$inferSelect;
```

FILE: lib/db/src/schema/index.ts
SIZE: 294 bytes

```
export * from "./missions";
export * from "./drivers";
export * from "./sites";
export * from "./generators";
export * from "./notifications";
export * from "./settings";
export * from "./admins";
export * from "./technicians";
export * from "./driver-entries";
export * from "./report-lines";
```

FILE: lib/db/src/schema/missions.ts
SIZE: 2,055 bytes

```
import { pgTable, serial, text, real, timestamp, boolean, integer } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const missionsTable = pgTable("missions", {
  id: serial("id").primaryKey(),
  missionId: text("mission_id").notNull().default(""),
  siteName: text("site_name").notNull(),
  generator: text("generator").notNull().default(""),
  project: text("project").notNull().default("stc COW"),
  driverName: text("driver_name").notNull().default(""),
  assignedDriver: text("assigned_driver").notNull().default(""),
  createdDate: timestamp("created_date").defaultNow(),
  filledLiters: real("filled_liters").notNull().default(0),
  virtualCalculated: real("virtual_calculated").notNull().default(0),
  actualInTank: real("actual_in_tank").notNull().default(0),
  quantityAddedLastTask: real("quantity_added_last_task").notNull().default(0),
  city: text("city").notNull().default(""),
  notes: text("notes").default(""),
  missionStatus: text("mission_status").notNull().default("Creation"),
  createdBy: text("created_by").notNull().default(""),
  technicianRemark: text("technician_remark").default(""),
  technicianStatus: text("technician_status").default("Pending"),
  reviewedBy: text("reviewed_by").default(""),
  reviewedAt: timestamp("reviewed_at"),
  assignedTechnicianId: integer("assigned_technician_id"),
  createdAt: timestamp("created_at").defaultNow(),
  // Driver field entries
  litersBefore: real("liters_before"),
  litersAdded: real("liters_added"),
  completionDate: timestamp("completion_date"),
  // Photo documentation (stored as base64 data URIs)
  odoBeforePhoto: text("odo_before_photo"),
  odoAfterPhoto: text("odo_after_photo"),
  tankBeforePhoto: text("tank_before_photo"),
  tankAfterPhoto: text("tank_after_photo"),
});

export const insertMissionSchema = createInsertSchema(missionsTable).omit({ id: true, createdAt: true });
export type InsertMission = z.infer<typeof insertMissionSchema>;
export type Mission = typeof missionsTable.$inferSelect;
```

FILE: lib/db/src/schema/notifications.ts
SIZE: 729 bytes

```
import { pgTable, serial, text, integer, timestamp } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const notificationsTable = pgTable("notifications", {
  id: serial("id").primaryKey(),
  title: text("title").notNull(),
  message: text("message").notNull(),
  driverName: text("driver_name"),
  sentBy: text("sent_by").notNull().default("Admin"),
  createdAt: timestamp("created_at").defaultNow(),
});

export const insertNotificationSchema = createInsertSchema(notificationsTable).omit({ id: true, createdAt: true
  });
export type InsertNotification = z.infer<typeof insertNotificationSchema>;
export type Notification = typeof notificationsTable.$inferSelect;
```

FILE: lib/db/src/schema/report-lines.ts
SIZE: 1,023 bytes

```
import { pgTable, serial, text, real, timestamp, integer, boolean } from "drizzle-orm/pg-core";

export const reportLinesTable = pgTable("report_lines", {
  id: serial("id").primaryKey(),
  missionId: integer("mission_id").notNull(),
  missionRef: text("mission_ref").notNull().default(""),
  siteName: text("site_name").notNull().default(""),
  region: text("region").notNull().default(""),
  project: text("project").notNull().default(""),
  driverName: text("driver_name").notNull().default(""),
  litersAdded: real("liters_added").notNull().default(0),
  completionDate: timestamp("completion_date"),
  approvedAt: timestamp("approved_at").defaultNow(),
  approvedBy: text("approved_by").notNull().default(""),
  unitPrice: real("unit_price").notNull().default(0.63),
  invoicePeriodStart: timestamp("invoice_period_start"),
  invoicePeriodEnd: timestamp("invoice_period_end"),
  invoiceExported: boolean("invoice_exported").notNull().default(false),
});

export type ReportLine = typeof reportLinesTable.$inferSelect;
```

FILE: lib/db/src/schema/settings.ts
SIZE: 928 bytes

```
import { pgTable, serial, real, text, integer, timestamp } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const settingsTable = pgTable("settings", {
  id: serial("id").primaryKey(),
  fuelUnitPrice: real("fuel_unit_price").notNull().default(0.63),
  vatRate: real("vat_rate").notNull().default(0.15),
  supplierName: text("supplier_name").notNull().default(""),
  supplierAddress: text("supplier_address").notNull().default(""),
  invoicePrefix: text("invoice_prefix").notNull().default("INV-SEC-"),
  invoiceSequence: integer("invoice_sequence").notNull().default(1),
  updatedAt: timestamp("updated_at").defaultNow(),
});

export const insertSettingsSchema = createInsertSchema(settingsTable).omit({ id: true, updatedAt: true });
export type InsertSettings = z.infer<typeof insertSettingsSchema>;
export type AppSettings = typeof settingsTable.$inferSelect;
```

FILE: lib/db/src/schema/sites.ts
SIZE: 1,282 bytes

```
import { pgTable, serial, text, boolean, real, timestamp, integer } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const sitesTable = pgTable("sites", {
  id: serial("id").primaryKey(),
  name: text("name").notNull(),
  region: text("region").default(""),
  district: text("district").notNull().default(""),
  city: text("city").notNull().default(""),
  project: text("project").notNull().default("stc COW"),
  cowStatus: text("cow_status").notNull().default("ON-AIR"),
  siteLabel: text("site_label").default(""),
  lat: real("lat"),
  lng: real("lng"),
  nextFuelingPlan: text("next_fueling_plan").default(""),
  lastFuelingDate: text("last_fueling_date").default(""),
  lastFuelingQty: real("last_fueling_qty"),
  active: boolean("active").notNull().default(true),
  currentLiters: real("current_liters").notNull().default(0),
  dailyVirtual: real("daily_virtual").notNull().default(0),
  assignedTechnicianId: integer("assigned_technician_id"),
  createdAt: timestamp("created_at").defaultNow(),
});

export const insertSiteSchema = createInsertSchema(sitesTable).omit({ id: true, createdAt: true });
export type InsertSite = z.infer<typeof insertSiteSchema>;
export type Site = typeof sitesTable.$inferSelect;
```

FILE: lib/db/src/schema/technicians.ts
SIZE: 1,186 bytes

```
import { pgTable, serial, text, boolean, timestamp } from "drizzle-orm/pg-core";
import { createInsertSchema } from "drizzle-zod";
import { z } from "zod/v4";

export const techniciansTable = pgTable("technicians", {
  id: serial("id").primaryKey(),
  name: text("name").notNull(),
  phone: text("phone").notNull().default(""),
  email: text("email").notNull().default(""),
  zone: text("zone").notNull().default(""),
  active: boolean("active").notNull().default(true),
  passwordHash: text("password_hash").notNull().default(""),
  // Push token registered via PUT /api/technicians/:id/fcm-token.
  // Both columns are written simultaneously by the API route.
  // expoPushToken (legacy) and fcmToken are identical in value
  // fcmToken is the canonical field; expoPushToken is kept for backward compat.
  expoPushToken: text("expo_push_token"),
  fcmToken: text("fcm_token"),
  createdAt: timestamp("created_at").defaultNow(),
});

export const insertTechnicianSchema = createInsertSchema(techniciansTable).omit({ id: true, createdAt: true });
export type InsertTechnician = z.infer<typeof insertTechnicianSchema>;
export type Technician = typeof techniciansTable.$inferSelect;
```

FILE: lib/db/tsconfig.json
SIZE: 244 bytes

```
{
  "extends": "../../tsconfig.base.json",
  "compilerOptions": {
    "composite": true,
    "declarationMap": true,
    "emitDeclarationOnly": true,
    "outDir": "dist",
    "rootDir": "src",
    "types": ["node"]
  },
  "include": ["src"]
}
```

FILE: package.json
SIZE: 167 bytes

```
{
  "main": "expo-router/entry",
  "dependencies": {
    "expo": "~54.0.33",
    "expo-router": "~6.0.23",
    "react": "catalog:",
    "react-native": "0.81.5"
  }
}
```

FILE: pnpm-workspace.yaml
SIZE: 4,673 bytes

```
packages:
  - artifacts/*
  - lib/*
  - lib/integrations/*
  - scripts

autoInstallPeers: false

catalog:
  '@replit/vite-plugin-cartographer': ^0.5.1
  '@replit/vite-plugin-dev-banner': ^0.1.1
  '@replit/vite-plugin-runtime-error-modal': ^0.0.6
  '@tailwindcss/vite': ^4.1.14
  '@tanstack/react-query': ^5.90.21
  '@types/node': ^25.3.3
  '@types/react': ^19.2.0
  '@types/react-dom': ^19.2.0
  '@vitejs/plugin-react': ^5.0.4
  class-variance-authority: ^0.7.1
  clsx: ^2.1.1
  drizzle-orm: ^0.45.1
  framer-motion: ^12.23.24
  lucide-react: ^0.545.0
  react: 19.1.0
  react-dom: 19.1.0
  tailwind-merge: ^3.3.1
  tailwindcss: ^4.1.14
  tsx: 4.21.0
  vite: ^7.3.2
  zod: ^3.25.76

minimumReleaseAge: 1440

minimumReleaseAgeExclude:
  - '@replit/*'
  - stripe-replit-sync
  - vite

onlyBuiltDependencies:
  - '@swc/core'
  - esbuild
  - msw
  - unrs-resolver

overrides:
  '@esbuild-kit/esm-loader': npm:tsx@^4.21.0
  '@expo/ngrok-bin>@expo/ngrok-bin-darwin-arm64': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-darwin-x64': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-freebsd-ia32': '-'
```

```
  '@expo/ngrok-bin>@expo/ngrok-bin-freebsd-x64': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-linux-arm': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-linux-arm64': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-linux-ia32': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-sunos-x64': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-win32-ia32': '-'
  '@expo/ngrok-bin>@expo/ngrok-bin-win32-x64': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-android-arm64': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-darwin-arm64': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-darwin-x64': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-freebsd-x64': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-linux-arm-gnueabihf': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-linux-arm64-gnu': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-linux-arm64-musl': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-linux-x64-musl': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-win32-arm64-msvc': '-'
  '@tailwindcss/oxide>@tailwindcss/oxide-win32-x64-msvc': '-'
  '@xmldom/xmldom': 0.8.10
  esbuild: 0.27.3
  esbuild>@esbuild/aix-ppc64: '-'
  esbuild>@esbuild/android-arm: '-'
  esbuild>@esbuild/android-arm64: '-'
  esbuild>@esbuild/android-x64: '-'
  esbuild>@esbuild/darwin-arm64: '-'
  esbuild>@esbuild/darwin-x64: '-'
  esbuild>@esbuild/freebsd-arm64: '-'
  esbuild>@esbuild/freebsd-x64: '-'
  esbuild>@esbuild/linux-arm: '-'
  esbuild>@esbuild/linux-arm64: '-'
  esbuild>@esbuild/linux-ia32: '-'
  esbuild>@esbuild/linux-loong64: '-'
  esbuild>@esbuild/linux-mips64el: '-'
  esbuild>@esbuild/linux-ppc64: '-'
  esbuild>@esbuild/linux-riscv64: '-'
  esbuild>@esbuild/linux-s390x: '-'
  esbuild>@esbuild/netbsd-arm64: '-'
  esbuild>@esbuild/netbsd-x64: '-'
  esbuild>@esbuild/openbsd-arm64: '-'
  esbuild>@esbuild/openbsd-x64: '-'
  esbuild>@esbuild/openharmony-arm64: '-'
  esbuild>@esbuild/sunos-x64: '-'
  esbuild>@esbuild/win32-arm64: '-'
  esbuild>@esbuild/win32-ia32: '-'
  esbuild>@esbuild/win32-x64: '-'
  lightningcss>lightningcss-android-arm64: '-'
  lightningcss>lightningcss-darwin-arm64: '-'
  lightningcss>lightningcss-darwin-x64: '-'
  lightningcss>lightningcss-freebsd-x64: '-'
  lightningcss>lightningcss-linux-arm-gnueabihf: '-'
  lightningcss>lightningcss-linux-arm64-gnu: '-'
  lightningcss>lightningcss-linux-arm64-musl: '-'
  lightningcss>lightningcss-linux-x64-musl: '-'
```

```
  lightningcss>lightningcss-win32-arm64-msvc: '-'
  lightningcss>lightningcss-win32-x64-msvc: '-'
  lodash: '>=4.18.0'
  path-to-regexp: '>=8.4.0'
  picomatch@2: '>=2.3.2'
  picomatch@4: '>=4.0.4'
  rollup>@rollup/rollup-android-arm-eabi: '-'
  rollup>@rollup/rollup-android-arm64: '-'
  rollup>@rollup/rollup-darwin-arm64: '-'
  rollup>@rollup/rollup-darwin-x64: '-'
  rollup>@rollup/rollup-freebsd-arm64: '-'
  rollup>@rollup/rollup-freebsd-x64: '-'
  rollup>@rollup/rollup-linux-arm-gnueabihf: '-'
  rollup>@rollup/rollup-linux-arm-musleabihf: '-'
  rollup>@rollup/rollup-linux-arm64-gnu: '-'
  rollup>@rollup/rollup-linux-arm64-musl: '-'
  rollup>@rollup/rollup-linux-loong64-gnu: '-'
  rollup>@rollup/rollup-linux-loong64-musl: '-'
  rollup>@rollup/rollup-linux-ppc64-gnu: '-'
  rollup>@rollup/rollup-linux-ppc64-musl: '-'
  rollup>@rollup/rollup-linux-riscv64-gnu: '-'
  rollup>@rollup/rollup-linux-riscv64-musl: '-'
  rollup>@rollup/rollup-linux-s390x-gnu: '-'
  rollup>@rollup/rollup-linux-x64-musl: '-'
  rollup>@rollup/rollup-openbsd-x64: '-'
  rollup>@rollup/rollup-openharmony-arm64: '-'
  rollup>@rollup/rollup-win32-arm64-msvc: '-'
  rollup>@rollup/rollup-win32-ia32-msvc: '-'
  rollup>@rollup/rollup-win32-x64-gnu: '-'
  rollup>@rollup/rollup-win32-x64-msvc: '-'
```

FILE: replit.md
SIZE: 5,821 bytes

ACES Managed Services   Platform Overview

Overview

pnpm workspace monorepo using TypeScript. Consists of three apps:
1. **Admin Web Portal**   operations management (missions, drivers, sites, technicians)
2. **Driver Mobile Web App**   driver daily tasks (part of web-portal artifact)
3. **Technician Native App**   Expo React Native app for field technicians (iOS & Android)

Stack

- **Monorepo tool**: pnpm workspaces
- **Node.js version**: 24
- **Package manager**: pnpm
- **TypeScript version**: 5.9
- **API framework**: Express 5
- **Database**: PostgreSQL + Drizzle ORM
- **Validation**: Zod (‘zod/v4‘), ‘drizzle-zod‘
- **API codegen**: Orval (from OpenAPI spec)
- **Build**: esbuild (CJS bundle)
- **Frontend**: React + Vite + Tailwind CSS + shadcn/ui
- **Routing**: Wouter (not react-router-dom)
- **Data fetching**: TanStack React Query (generated hooks)

Structure

‘‘‘text
artifacts/
??? api-server/   # Express API server (port from PORT env)
?   ??? src/routes/   # missions, drivers, sites, generators,
?   # notifications, settings, admins, technicians,
?   # dashboard, health, drivers (driver routes)
??? web-portal/   # React + Vite frontend
?   ??? src/
?   ??? pages/admin/ # Dashboard, Login, Missions, Sites, Drivers,
?   ?   # Generators, Reports, Notifications, Settings,
?   ?   # Admins, Technicians
?   ??? pages/driver/ # DriverLogin, DriverDashboard, DriverMissionDetail,
?   # DriverNotifications, DriverSettings
??? technician-app/   # Expo React Native app (iOS & Android)
    ??? app/   # Expo Router screens
    ?   ??? index.tsx   # Auth redirect
    ?   ??? login.tsx   # Login screen
    ?   ??? (tabs)/   # Tab navigation (Tasks, Alerts, Profile)
    ?   ??? mission/   # Mission detail + follow-up form
    ??? contexts/auth.tsx # Auth state (AsyncStorage)
    ??? lib/api.ts   # API fetch helper
    ??? constants/colors.ts # ACES brand colors
‘‘‘

```
lib/
??? api-spec/            # OpenAPI spec + Orval codegen config
??? api-client-react/    # Generated React Query hooks
??? api-zod/             # Generated Zod schemas from OpenAPI
??? db/                  # Drizzle ORM schema + DB connection
```

Authentication

- **Admin login**: ‘username=Bannaga‘, ‘password=Aces@6343‘, ‘role=superadmin‘
- Auth stored in localStorage (‘aces_auth‘ key) as JSON
- Admin type: ‘{ type: "admin", username, role }‘
- Driver type: ‘{ type: "driver", driverId, username }‘
- **Technician app**: auth stored in AsyncStorage (‘aces_tech_auth‘ key)
- Technician type: ‘{ technicianId, name, email, zone, token }‘
- Demo technician: ‘ahmed@aces-sa.com / Tech@1234‘
- Login redirects explicitly via ‘setLocation("/")‘ after success

ACES Branding

- Primary color (dark navy): ‘#002D62‘ ? HSL ‘212 100% 19%‘
- Accent (green): ‘#00C853‘ ? HSL ‘149 100% 39%‘
- Destructive (red): ‘#E30613‘ ? HSL ‘355 90% 46%‘
- Logo: ‘public/images/logo.png‘
- Auth background: ‘public/images/auth-bg.png‘
- Driver background: ‘public/images/driver-bg.png‘

Database Schema Tables

- ‘missions‘ fuel missions with status tracking
- ‘drivers‘ drivers with zones and password hashes
- ‘driverTasks‘ tasks assigned to drivers
- ‘driverNotifications‘ push notifications for drivers
- ‘sites‘ telecom tower sites
- ‘generators‘ generator assets at sites
- ‘notifications‘ admin-sent notifications
- ‘settings‘ global app settings (fuel price, VAT, invoice prefix)
- ‘admins‘ system administrators
- ‘technicians‘ technical staff

Mission Statuses

- **Creation** (orange) newly created
- **Finished by Driver** (sky) driver marked done
- **Task approved** (emerald) admin approved
- **Task returned to driver** (indigo) sent back for correction
- **Reported by driver** (rose) driver reported issue
- **Canceled** (gray) canceled mission

Driver Zones

- Mobily East Region

- COW East Region
- Mobily Central Region
- COW Central Region

API Routes

All routes under ‘/api‘ prefix:
- ‘GET/POST /api/missions‘ list/create missions
- ‘GET/PUT/DELETE /api/missions/:id‘
- ‘GET/POST /api/drivers‘ list/create drivers
- ‘GET/PUT/DELETE /api/drivers/:id‘
- ‘GET/POST /api/sites‘
- ‘GET/PUT/DELETE /api/sites/:id‘
- ‘GET/POST /api/generators‘
- ‘GET/PUT/DELETE /api/generators/:id‘
- ‘GET/POST /api/notifications‘
- ‘GET/PUT /api/settings‘
- ‘GET/POST /api/admins‘
- ‘GET/PUT/DELETE /api/admins/:id‘
- ‘GET/POST /api/technicians‘
- ‘GET/PUT/DELETE /api/technicians/:id‘
- ‘PUT /api/technicians/:id/expo-push-token‘ register Expo push token
- ‘GET /api/dashboard/kpis‘
- ‘POST /api/auth/login‘ admin login (SHA-256 password)
- ‘POST /api/driver/login‘ driver login
- ‘GET /api/driver/tasks?driverId=‘
- ‘GET/PUT /api/driver/tasks/:id‘
- ‘GET /api/driver/notifications?driverId=‘
- ‘POST /api/technician/login‘ technician app login
- ‘GET /api/technician/missions?technicianId=‘ filter by assigned technician
- ‘PUT /api/technician/missions/:id/followup‘ submit follow-up review

Password Hashing

Uses Node.js ‘crypto.createHash(’sha256’)‘, NOT bcrypt.

Rebuilding API Client

After modifying OpenAPI spec:
‘‘‘bash
cd lib/api-client-react && pnpm run generate
cd lib/api-client-react && pnpm tsc --build
‘‘‘

Seed Data

Admin: ‘Bannaga / Aces@6343‘ (superadmin)
Drivers: Gul Muhammad, Irfan, Pradeep Singh, MURALI.MUSAFMY, ZAFAR ABDUL SATTAR, Reaza
Sites: SGD66662, COWM38, COW531, COW591, A-25462C
Generators: 3172, 2371, 2370, 2368, 2367
Missions: MSN-001 through MSN-005

FILE: scripts/package.json
SIZE: 281 bytes

```
{
  "name": "@workspace/scripts",
  "version": "0.0.0",
  "private": true,
  "type": "module",
  "scripts": {
    "hello": "tsx ./src/hello.ts",
    "typecheck": "tsc -p tsconfig.json --noEmit"
  },
  "devDependencies": {
    "@types/node": "catalog:",
    "tsx": "catalog:"
  }
}
```

FILE: scripts/src/hello.ts
SIZE: 46 bytes

```
console.log("Hello from @workspace/scripts");
```

FILE: scripts/tsconfig.json
SIZE: 157 bytes

```
{
  "extends": "../tsconfig.base.json",
  "compilerOptions": {
    "outDir": "dist",
    "rootDir": "src",
    "types": ["node"]
  },
  "include": ["src"]
}
```

FILE: tsconfig.base.json
SIZE: 667 bytes

```
{
  "compilerOptions": {
    "isolatedModules": true,
    "lib": ["es2022"],
    "module": "esnext",
    "moduleResolution": "bundler",
    "noEmitOnError": true,
    "noFallthroughCasesInSwitch": true,
    "noImplicitOverride": false,
    "noImplicitReturns": true,
    "noUnusedLocals": false,
    "noImplicitAny": true,
    "noImplicitThis": true,
    "strictNullChecks": true,
    "strictFunctionTypes": false,
    "strictBindCallApply": true,
    "strictPropertyInitialization": true,
    "useUnknownInCatchVariables": true,
    "alwaysStrict": true,
    "skipLibCheck": true,
    "target": "es2022",
    "types": [],
    "customConditions": ["workspace"]
  }
}
```

FILE: tsconfig.json
SIZE: 236 bytes

```
{
  "extends": "./tsconfig.base.json",
  "compileOnSave": false,
  "files": [],
  "references": [
    {
      "path": "./lib/db"
    },
    {
      "path": "./lib/api-client-react"
    },
    {
      "path": "./lib/api-zod"
    }
  ]
}
```