

Лабораторная работа № 3.

Настройка DHCP-сервера

Данила Стариков
НПИбд-02-22

Российский университет дружбы народов имени Патриса Лумумбы

2024

Цель работы

- ▶ Приобретение практических навыков по установке и конфигурированию DHCP-сервера.

Конфигурирование DHCP-сервера

```
[root@server.dastarikov.net ~]# cd /etc/dhcp
cp /usr/share/doc/dhcp*/dhcpd.conf.example /etc/dhcp
mv /etc/dhcp/dhcpd.conf.example /etc/dhcp/dhcpd.conf
mv: overwrite '/etc/dhcp/dhcpd.conf'? y
[root@server.dastarikov.net dhcp]#
```

Рис.: Подготовка файла конфигурации.

Конфигурирование DHCP-сервера

```
[Unit]
Description=DHCPv4 Server Daemon
Documentation=man:dhcpd(8) man:dhcpd.conf(5)
Wants=network-online.target
After=network-online.target
After=time-sync.target

[Service]
Type=notify
EnvironmentFile=-/etc/sysconfig/dhcpd
ExecStart=/usr/sbin/dhcpd -f -cf /etc/dhcp/dhcpd.conf -user dhcpd -group dhcpd --no-pid eth1
StandardError=null

[Install]
WantedBy=multi-user.target
```

Рис.: Настройка dhcpd.

Конфигурирование DHCP-сервера

```
[root@server.dastarikov.net dhcp]# systemctl --system daemon-reload
systemctl enable dhcpd
Created symlink /etc/systemd/system/multi-user.target.wants/dhcpd.service → /etc/systemd/system/dhcpd.service.
[root@server.dastarikov.net dhcp]#
```

Рис.: Перезагрузка демона dhcpd.

Конфигурирование DHCP-сервера

```
$TTL 1D
@      IN SOA  @ server.dastarikov.net (
                                2024101901 ; serial
                                1D      ; refresh
                                1H      ; retry
                                1W      ; expire
                                3H      ; minimum
      NS  @
      A   192.168.1.1
$ORIGIN dastarikov.net.
server A   192.168.1.1
ns      A   192.168.1.1
dhcp    A   192.168.1.1
```

Рис.: Изменение файла прямой DNS-зоны.

Конфигурирование DHCP-сервера

```
$TTL 1D
@      IN SOA  @ server.dastarikov.net. (
                                2024101901      ; serial
                                1D      ; refresh
                                1H      ; retry
                                1W      ; expire
                                3H )   ; minimum

      NS      @
      A      192.168.1.1
      PTR     server.dastarikov.net
$ORIGIN 1.168.192.in-addr.arpa.
1      PTR     server.dastarikov.net.
1      PTR     ns.dastarikov.net.
1      PTR     dhcp.dastarikov.net.
```

Рис.: Изменение файла обратной DNS-зоны.

Конфигурирование DHCP-сервера

```
[root@server.dastarikov.net dhcp]# systemctl restart named
[root@server.dastarikov.net dhcp]# ping dhcp.dastarikov.net
PING dhcp.dastarikov.net (192.168.1.1) 56(84) bytes of data.
64 bytes from ns.dastarikov.net (192.168.1.1): icmp_seq=1 ttl=64 time=0.045 ms
64 bytes from dhcp.dastarikov.net (192.168.1.1): icmp_seq=2 ttl=64 time=0.084
ms
64 bytes from server.dastarikov.net (192.168.1.1): icmp_seq=3 ttl=64 time=0.12
6 ms
64 bytes from server.dastarikov.net (192.168.1.1): icmp_seq=4 ttl=64 time=0.12
9 ms
^C
--- dhcp.dastarikov.net ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3101ms
rtt min/avg/max/mdev = 0.045/0.096/0.129/0.034 ms
```

Рис.: Обращение к DHCP-серверу.

Конфигурирование DHCP-сервера

```
[root@server.dastarikov.net dhcp]# firewall-cmd --list-services
firewall-cmd --get-services
firewall-cmd --add-service=dhcp
firewall-cmd --add-service=dhcp --permanent
cockpit dhcpv6-client dns ssh
RH-Satellite-6 RH-Satellite-6-capsule afp amanda-client amanda-k5-client amqp amqps apcupsd audit ausweisapp2 ba
cula bacula-client bareos-director bareos-filedaemon bareos-storage bb bgp bitcoin bitcoin-rpc bitcoin-testnet b
itcoin-testnet-rpc bittorrent-lsd ceph ceph-exporter ceph-mon cfengine checkmk-agent cockpit collectd condor-col
lector cratedb ctdb dds dds-multicast dds-unicast dhcp dhcpv6 dhcpv6-client distcc dns dns-over-tls docker-regis
try docker-swarm dropbox-lansync elasticsearch etcd-client etcd-server finger foreman foreman-proxy freeipa-4 fr
eeipa-ldap freeipa-ldaps freeipa-replication freeipa-trust ftp galera ganglia-client ganglia-master git gpsd gra
fana gre high-availability http http3 https ident imap imaps ipfs ipp ipp-client ipsec irc ircs iscsi-target isn
s jenkins kadmin kdeconnect kerberos kibana klogin kpasswd kprop kshell kube-api kube-apiserver kube-control-pla
ne kube-control-plane-secure kube-controller-manager kube-controller-manager-secure kube-nodeport-services kube-
scheduler kube-scheduler-secure kube-worker kubelet kubelet-readonly kubelet-worker ldap ldaps libvirt libvirt-t
ls lightning-network llmnr llmnr-client llmnr-tcp llmnr-udp managesieve matrix mdns memcache minidlna mongodb mo
sh mountd mqtt-tls ms-wbt mssql murmur mysql nbd nebula netbios-ns netdata-dashboard nfs nfs3 nmea-0183 nrp
e ntp nut openvpn ovirt-imageio ovirt-storageconsole ovirt-vmconsole plex pncd pmpoxy pmwebapi pmwebapis pop3 p
op3s postgresql privoxy prometheus prometheus-node-exporter proxy-dhcp ps2link ps3netsrv ptp pulseaudio puppetma
ster quassel radius rdp redis redis-sentinel rpc-bind rquotad rsh rsyncd rtsp salt-master samba samba-client sam
ba-dc sane sip sips slp smtp smtp-submission smtps snmp snmptls snmptls-trap snmptrap spideroak-lansync spotify-
sync squid ssdp ssh steam-streaming svdrp svn syncthing syncthing-gui syncthing-relay synergy syslog syslog-tls
telnet tentacle tftp tile38 tinc tor-socks transmission-client upnp-client vdsml vnc-server warpinator wbem-http
wbem-https wireguard ws-discovery ws-discovery-client ws-discovery-tcp ws-discovery-udp wsman wsmans xdmcp xmpp-
bosh xmpp-client xmpp-local xmpp-server zabbix-agent zabbix-server zerotier
success
success
```

Рис.: Настройка межсетевого экрана для работы с DHCP.

Конфигурирование DHCP-сервера

```
[root@server.dastarikov.net dhcp]# restorecon -vR /etc
restorecon -vR /var/named
restorecon -vR /var/lib/dhcpd/
Relabeled /etc/systemd/system/dhcpd.service from unconfined_u:object_r:systemd_unit_file_t:s0 to unconfined_u:object_r:dhcpd_unit_file_t:s0
Relabeled /etc/sysconfig/network-scripts/ifcfg-eth1 from unconfined_u:object_r:user_tmp_t:s0 to unconfined_u:object_r:net_conf_t:s0
[root@server.dastarikov.net dhcp]#
```

Рис.: Восстановление контекста безопасности SELinux.

Анализ работы DHCP-сервера

```
→ vagrant make client-provision
Bringing machine 'client' up with 'virtualbox' provider...
==> client: Clearing any previously set forwarded ports...
==> client: Fixed port collision for 22 => 2222. Now on port 2200.
==> client: Clearing any previously set network interfaces...
==> client: Preparing network interfaces based on configuration...
    client: Adapter 1: nat
    client: Adapter 2: intnet
==> client: Forwarding ports...
    client: 22 (guest) => 2200 (host) (adapter 1)
==> client: Running 'pre-boot' VM customizations...
==> client: Booting VM...
==> client: Waiting for machine to boot. This may take a few minutes...
    client: SSH address: 127.0.0.1:2200
    client: SSH username: vagrant
    client: SSH auth method: password
```

Рис.: Фиксирование внесенных изменений и запуск виртуальной машины client.

Анализ работы DHCP-сервера

```
[dastarikov@client.dastarikov.net ~]$ ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.2.15 netmask 255.255.255.0 broadcast 10.0.2.255
    inet6 fe80::a00:27ff:fe4c:cc9c prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:4c:cc:9c txqueuelen 1000 (Ethernet)
    RX packets 1592 bytes 178414 (174.2 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 1474 bytes 226540 (221.2 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.1.30 netmask 255.255.255.0 broadcast 192.168.1.255
    inet6 fe80::a00:27ff:fe16:c3e7 prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:16:c3:e7 txqueuelen 1000 (Ethernet)
    RX packets 17 bytes 2944 (2.8 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 166 bytes 21528 (21.0 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 19 bytes 2146 (2.0 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 19 bytes 2146 (2.0 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

Настройка обновления DNS-зоны

```
zone "dastarikov.net" IN {  
    type master;  
    file "master/fz/dastarikov.net";  
    allow-update { 127.0.0.1; };  
};  
  
zone "1.168.192.in-addr.arpa" IN {  
    type master;  
    file "master/rz/192.168.1";  
    allow-update { 127.0.0.1; };  
};
```

Рис.: Обновление файла DNS-зоны на виртуальной машине server.

Настройка обновления DNS-зоны

```
[root@server.dastarikov.net fz]# ls  
dastarikov.net  dastarikov.net.jnl
```

Рис.: Проверка создания файла.

Выводы

- ▶ В результате выполнения лабораторной работы приобрели практические навыки по установке и конфигурированию DHCP-сервера.