R&T BiCMOS run2

Low Noise, Cryogenic Differential Amplifier

Prepared by: Bao TON

DESCRIPTION

This ASIC, fabricated using IHP technology, integrates three distinct circuits designed for cryogenic operation (77 K). It features two low-noise differential amplifiers: a fully integrated version with on-chip resistors and a flexible version utilizing external resistors. Both amplifiers deliver an ultralow noise floor of $1\,\mathrm{nV}/\sqrt{\mathrm{Hz}}$ and are optimized for promising low flicker noise at cryogenic temperatures. The bandwidth is specified at 25 MHz for the on-chip variant and 50 MHz for the external resistor configuration. Additionally, a large-geometry NMOS transistor ($W/L \approx 190,000$) is included for discrete characterization.

ABSOLUTE MAXIMUM RATINGS

Total Supply Voltage (V^+ to V^-)	5.15V
Input Current (Note 2)	±40mA
Operating Junction Temperature Range (Note 5)	−40°C to 125°C

BLOCK DIAGRAM



LNA 1 LNA 2 NMOS Block

PACKAGE



Bonding diagram with QFN24 package

TABLE 1: ELECTRICAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	NOTES	$T_A = 27°C$			SUB-GROUP	$-55°C \le T_A \le 125°C$			SUB-GROUP	UNITS
				MIN	TYP	MAX		MIN	TYP	MAX		
V_{OS}	Input Offset	$V_S = \pm 1.65V$			0.6	2	1			4	2,3	mV
	Voltage	$V_{CM} = V^-$ to V^+			2.5	6	1			9	2,3	mV
I_B	Input Bias	$V_S = \pm 1.65V$			8	18	1			20	2,3	μA
	Current	$V_{CM} = V^+$		-50	-23		1	-100			2,3	μA
	Input Noise	0.1 Hz to 10 Hz			8	18	1			20	2,3	μA
	Voltage	$V_{CM} = V^+$		-50	-23		1	-100			2,3	nV_{p-p}
SR	Slew Rate	$V_{in} \pm 1.25\ mV$ — LNA1		28	30	31	1	29	30	32	2,3	$V/\mu s$
		$V_{in} \pm 1.25\ mV$ — LNA2		39	36	42	1	38	39	40	2,3	$/\mu s$

TYPICAL PERFORMANCE CHARACTERISTICS

Slew Rate Measurement

Example of signal response @27° C



Slew Rate Calculate $(10\% - 90\%)$ Example



Slew Rate vs Temperature



Histogram of Slew Rate



Common-mode Rejection Ratio (CMRR)

CMRR LNA1



CMRR LNA2



Power Suppy Rejection Ratio

PSRR LNA1 (VCC)



PSRR LNA1 (VEE)



PSRR LNA2 (VCC)




PSRR LNA2 (VEE)
Avg
Min-Max
130
120
110
100
90
80
70
60
PSRR (dB)
10^1
10^3
10^5
10^7
Frequency (Hz)
T = 27 ° C