

Installing Gradle

Prerequisites

Gradle requires a Java JDK or JRE to be installed, version 6 or higher (to check, use `java -version`). Gradle ships with its own Groovy library, therefore Groovy does not need to be installed. Any existing Groovy installation is ignored by Gradle.

Gradle uses whatever JDK it finds in your path. Alternatively, you can set the `JAVA_HOME` environment variable to point to the installation directory of the desired JDK.

Download 下载发布包

<http://www.gradle.org/downloads>

You can download one of the Gradle distributions from the [Gradle web site](#).

Unpacking 解压缩包

The Gradle distribution comes packaged as a ZIP. The full distribution contains:

- The Gradle binaries.
- The user guide (HTML and PDF). 用户指南
- The DSL reference guide.
- The API documentation (Javadoc and Groovydoc).
- Extensive samples, including the examples referenced in the user guide, along with some complete and more complex builds you can use as a starting point for your own build.
- The binary sources. This is for reference only. If you want to build Gradle you need to download the source distribution or checkout the sources from the source repository. See the [Gradle web site](#) for details.

Environment variables 环境变量

For running Gradle, add `GRADLE_HOME/bin` to your `PATH` environment variable. Usually, this is sufficient to run Gradle. 这样能高效地运行Gradle

运行和测试你的安装

Running and testing your installation

You run Gradle via the `gradle` command. To check if Gradle is properly installed just type `gradle -v`. The output shows the Gradle version and also the local environment

configuration (Groovy, JVM version, OS, etc.). The displayed Gradle version should match the distribution you have downloaded.

JVM options JVM选项

JVM options for running Gradle can be set via environment variables. You can use either GRADLE_OPTS or JAVA_OPTS, or both. JAVA_OPTS is by convention an environment variable shared by many Java applications. A typical use case would be to set the HTTP proxy in JAVA_OPTS and the memory options in GRADLE_OPTS. Those variables can also be set at the beginning of the **gradle** or **gradlew** script.

Note that it's not currently possible to set JVM options for Gradle on the command line.

Getting help 获取帮助

You might check the user guide at [GRADLE_HOME/docs/userguide/userguide.html](#). It is also available on the [Gradle web site](#). Typing **gradle help** prints the command line help. Typing **gradle tasks** shows all the tasks of a Gradle build.