

Project creation

从“原型”创建项目，包括三个步骤：

Creating a project from an archetype involves three steps:

- the selection of the archetype, 原型的选择
- the configuration of that archetype, 原型的配置
- the effective creation of the project from the collected information.

从所收集的信息中有效创建项目

Usage

动手实践一下吧！！！！

Calling `archetype:generate` the plugin will first ask to choose the archetype from the internal catalog. Just enter the number of the archetype.

It then asks you to enter the values for the groupId, the artifactId and the version of the project to create and the base package for the sources.

It then asks for confirmation of the configuration and performs the creation of the project.

In the following example, we selected the quickstart archetype (default value, which is 15 here but may vary depending on the repository content) and set groupId to `com.company`, artifactId to `project`, version to `1.0` and package to `com.company.project`.

```
$ mvn archetype:generate mvn archetype:generate -Dfilter=quickstart
[INFO] Scanning for projects...
[INFO] Searching repository for plugin with prefix: 'archetype'.
[INFO] -----
[INFO] Building Maven Default Project
[INFO] task-segment: [archetype:create] (aggregator-style)
[INFO] -----
[INFO] Preparing archetype:generate
[INFO] No goals needed for project - skipping
[INFO] Setting property: classpath.resource.loader.class => 'org.codehaus.plexus.velocity.ContextClassLoaderResourceLoader'.
[INFO] Setting property: velocimacro.messages.on => 'false'.
[INFO] Setting property: resource.loader => 'classpath'.
[INFO] Setting property: resource.manager.logwhenfound => 'false'.
[INFO] [archetype:generate]
```

Choose archetype:

选择“原型”

```
1: internal -> org.appfuse.archetypes:appfuse-basic-jsf (AppFuse archetype for creating a web application with Hibernate, Spring and JSF)
2: internal -> org.appfuse.archetypes:appfuse-basic-spring (AppFuse archetype for creating a web application with Hibernate, Spring and Spring MVC)
3: internal -> org.appfuse.archetypes:appfuse-basic-struts (AppFuse archetype for creating a web application with Hibernate, Spring and Struts 2)
4: internal -> org.appfuse.archetypes:appfuse-basic-tapestry (AppFuse archetype for creating a web application with Hibernate, Spring and Ta
```

```
pestry 4)
5: internal -> org.appfuse.archetypes:appfuse-core (AppFuse archetype
for creating a jar application with Hibernate and Spring and XFire)
6: internal -> org.appfuse.archetypes:appfuse-modular-jsf (AppFuse arc
hetype for creating a modular application with Hibernate, Spring and J
SF)
7: internal -> org.appfuse.archetypes:appfuse-modular-spring (AppFuse
archetype for creating a modular application with Hibernate, Spring an
d Spring MVC)
8: internal -> org.appfuse.archetypes:appfuse-modular-struts (AppFuse
archetype for creating a modular application with Hibernate, Spring an
d Struts 2)
9: internal -> org.appfuse.archetypes:appfuse-modular-tapestry (AppFus
e archetype for creating a modular application with Hibernate, Spring
and Tapestry 4)
10: internal -> org.apache.maven.archetypes:maven-archetype-j2ee-simpl
e (A simple J2EE Java application)
11: internal -> org.apache.maven.archetypes:maven-archetype-marmalade-
mojo (A Maven plugin development project using marmalade)
12: internal -> org.apache.maven.archetypes:maven-archetype-mojo (A Ma
ven Java plugin development project)
13: internal -> org.apache.maven.archetypes:maven-archetype-portlet (A
simple portlet application)
14: internal -> org.apache.maven.archetypes:maven-archetype-profiles (
)
15: internal -> org.apache.maven.archetypes:maven-archetype-quickstart
()
16: internal -> org.apache.maven.archetypes:maven-archetype-site-simpl
e (A simple site generation project)
17: internal -> org.apache.maven.archetypes:maven-archetype-site (A mo
re complex site project)
18: internal -> org.apache.maven.archetypes:maven-archetype-webapp (A
simple Java web application)
19: internal -> org.apache.struts:struts2-archetype-starter (A starter
Struts 2 application with Sitemesh, DWR, and Spring)
20: internal -> org.apache.struts:struts2-archetype-blank (A minimal S
truts 2 application)
21: internal -> org.apache.struts:struts2-archetype-portlet (A minimal
Struts 2 application that can be deployed as a portlet)
22: internal -> org.apache.struts:struts2-archetype-dbportlet (A start
er Struts 2 portlet that demonstrates a simple CRUD interface with db
backing)
23: internal -> org.apache.struts:struts2-archetype-plugin (A Struts 2
plugin)
```

```
Choose a number or apply filter (format: [groupId:]artifactId, case se
nsitive contains): 15: Enter
Choose org.apache.maven.archetypes:maven-archetype-quickstart version:
```

```
1: 1.0-alpha-1
2: 1.0-alpha-2
3: 1.0-alpha-3
```

```

4: 1.0-alpha-4
5: 1.0
6: 1.1
Choose a number: 6: Enter
Define value for groupId: : com.company
Define value for artifactId: : project
Define value for version: : 1.0
Define value for package: : com.company.project
Confirm properties configuration: 确认“属性配置”
groupId: com.company
artifactId: project
version: 1.0
package: com.company.project
Y: : Enter

[INFO] -----
-----
[INFO] Using following parameters for creating OldArchetype: maven-arc
hetype-quickstart:RELEASE
[INFO] -----
-----
[INFO] Parameter: groupId, Value: com.company
[INFO] Parameter: packageName, Value: com.company.project
[INFO] Parameter: package, Value: com.company.project
[INFO] Parameter: artifactId, Value: project
[INFO] Parameter: basedir, Value: /home/local/rafale/projects/tmp
[INFO] Parameter: version, Value: 1.0
[INFO] OldArchetype created in dir: /home/local/rafale/projects/tmp/pr
oject
[INFO] -----
-----
[INFO] BUILD SUCCESSFUL
[INFO] -----
-----
[INFO] Total time: 54 seconds
[INFO] Finished at: Fri Aug 26 23:01:01 GMT 2011
[INFO] Final Memory: 10M/25M
[INFO] -----
-----

```

Here's the resulting tree of the created project

```

$ tree project
project
|-- pom.xml
`-- src
    |-- main
    |   |-- java
    |       |-- com
    |           |-- company
    |               |-- project
    |                   |-- App.java

```

```

-- test
-- java
-- com
-- company
-- project
-- AppTest.java

```

11 directories, 3 files

Filtering to reduce archetype list

As of version 2.1, you can reduce the list of displayed archetypes. The **filter** use the following format: `[groupId:]artifactId`. If you use single word without `:`, only `artifactId` will be checked. The **filtering** applied is a case sensitive contains on the `artifactId` (and `groupId` if set).

Two options

1. With a mojo parameter:

```
$ mvn archetype:generate -Dfilter=org.apache:struts
```

The displayed list will contain only **archetypes** with a **groupId** containing `org.apache` AND an **artifactId** containing `struts`

2. Through the prompt:

```
$ mvn archetype:generate
```

The full list is displayed and in the prompt response, you will be able to answer with a filter.

```
Choose a number or apply filter (format: [groupId:]artifactId, case sensitive contains): org.apache:struts
```

Notice that if your **filter** doesn't match any **archetype**, the previous list will be displayed again.