

archetype:generate

Full name:

org.apache.maven.plugins:maven-archetype-plugin:2.3:generate

Description: 从原型生成一个新项目

Generates a new project from an archetype, or updates the actual project if using a partial archetype. If the project is fully generated, it is generated in a directory corresponding to its artifactId. If the project is updated with a partial archetype, it is done in the current directory.

Attributes:

- Invokes the execution of the lifecycle phase `generate-sources` prior to executing itself.

Required Parameters

| Name | Type | Since | Description |
|------------------------------|---------|-------|---|
| <code>interactiveMode</code> | Boolean | - | User settings used to check the interactiveMode. Default value is: <code>\${settings.interactiveMode}</code> . User property is: <code>interactiveMode</code> . |

Optional Parameters

| Name | Type | Since | Description |
|----------------------------------|--------|-------|---|
| <code>archetypeArtifactId</code> | String | - | The archetype's artifactId. User property is: <code>archetypeArtifactId</code> . |
| <code>archetypeCatalog</code> | String | - | <p>The archetype catalogs to use to build a list and let the user choose from. It is a comma separated list of catalogs. Catalogs use the following schemes:</p> <ul style="list-style-type: none"> 'file://...' with <code>archetype-catalog.xml</code> automatically appended when pointing to a directory 'http://...' or 'https://...' with <code>archetype-catalog.xml</code> always appended 'local' which is the shortcut for 'file://~/.m2/archetype-catalog.xml' 'remote' which is the shortcut for Maven Central repository, ie 'http://repo.maven.apache.org/maven2' 'internal' which is an internal catalog <p>Since 2.0-alpha-5, default value is no longer <code>internal,local</code> but <code>remote,local</code>. If Maven Central repository catalog file is empty, <code>internal</code> catalog is used instead.</p> <p>Default value is: <code>remote,local</code>. User property is: <code>archetypeCatalog</code>.</p> |

archetypeGroupId

String

-

The archetype's groupId.

User property is: `archetypeGroupId`.

archetypeRepository

String

-

The archetype's repository.

User property is: `archetypeRepository`.

archetypeVersion

String

-

The archetype's version.

User property is: `archetypeVersion`.

basedir

File

-

(no description)

Default value is: `${basedir}`.

filter

String

2.1

Applying some filter on displayed archetypes list: format is

`artifactId` or `groupId:artifactId`.

- `org.apache:` -> displays all archetypes which contain `org.apache` in `groupId`
- `:jee` or `jee` -> displays all archetypes which contain jee in artifactId
- `org.apache:jee` -> displays all archetypes which contain `org.apache` in `groupId` AND `jee` in `artifactId`

User property is: `filter`.

goals

String

-

Additional goals to immediately run on the project created from the archetype.

User property is: `goals`.