

Question 5. Swap Consecutive Seat IDs | CASE Statement (Medium)
(AMAZON,APPLE,BLOOMBERG,UBER)

(REF :

<https://leetcode.com/problems/exchange-seats/description/?envType=study-plan-v2&envId=top-sql-50>)

Table: Seat

+-----+		
Column Name	Type	
+-----+		
id	int	
student	varchar	
+-----+		

id is the primary key (unique value) column for this table.

Each row of this table indicates the name and the ID of a student.

id is a continuous increment.

Write a solution to swap the seat id of every two consecutive students. If the number of students is odd, the id of the last student is not swapped.

Return the result table ordered by id in ascending order.

The result format is in the following example:

Example 1:

Input:

Seat table:

+---+-----+		
id	student	
+---+-----+		
1	Abbot	
2	Doris	
3	Emerson	
4	Green	
5	Jeames	
+---+-----+		

Output:

+---+-----+		
id	student	
+---+-----+		
1	Doris	
2	Abbot	
3	Green	
4	Emerson	
5	Jeames	
+---+-----+		

Explanation:

Note that if the number of students is odd, there is no need to change the last one's seat.

-- Insert statements for Seat table

```
INSERT INTO Seat (id, student) VALUES (1, 'Abbot');
INSERT INTO Seat (id, student) VALUES (2, 'Doris');
INSERT INTO Seat (id, student) VALUES (3, 'Emerson');
INSERT INTO Seat (id, student) VALUES (4, 'Green');
INSERT INTO Seat (id, student) VALUES (5, 'Jeames');
```

Solution :

Seat table:

id	student
1	Abbot
2	Doris
3	Emerson
4	Green
5	Jeames

```
SELECT CASE
WHEN id % 2 = 1 AND id < (select max(id) from seat)
THEN id + 1
WHEN id % 2 = 0 THEN id - 1
ELSE id
END AS id, student
FROM seat
ORDER BY id;
```