

Question 7 : Daily Leads and Partners | Counting Distinct Values with Grouping (Medium)

(REF :

<https://leetcode.com/explore/featured/card/sql-language/683/sql-syntax/4327/>)

Table: DailySales

Column Name	Type
date_id	date
make_name	varchar
lead_id	int
partner_id	int

There is no primary key (column with unique values) for this table. It may contain duplicates.

This table contains the date and the name of the product sold and the IDs of the lead and partner it was sold to.

The name consists of only lowercase English letters.

For each date_id and make_name, find the number of distinct lead_id's and distinct partner_id's.

Return the result table in any order.

The result format is in the following example.

Input:

DailySales table:

date_id	make_name	lead_id	partner_id
2020-12-8	toyota	0	1
2020-12-8	toyota	1	0
2020-12-8	toyota	1	2
2020-12-7	toyota	0	2
2020-12-7	toyota	0	1
2020-12-8	honda	1	2
2020-12-8	honda	2	1
2020-12-7	honda	0	1
2020-12-7	honda	1	2
2020-12-7	honda	2	1

Output:

date_id	make_name	unique_leads	unique_partners
2020-12-8	toyota	2	3
2020-12-7	toyota	1	2
2020-12-8	honda	2	2
2020-12-7	honda	3	2

Explanation:

For 2020-12-8, toyota gets leads = [0, 1] and partners = [0, 1, 2] while honda gets leads = [1, 2] and partners = [1, 2].

For 2020-12-7, toyota gets leads = [0] and partners = [1, 2] while honda gets leads = [0, 1, 2] and partners = [1, 2].

-- Insert data into DailySales table

```
INSERT INTO DailySales (date_id, make_name, lead_id, partner_id) VALUES
('2020-12-08', 'toyota', 0, 1),
('2020-12-08', 'toyota', 1, 0),
('2020-12-08', 'toyota', 1, 2),
('2020-12-07', 'toyota', 0, 2),
('2020-12-07', 'toyota', 0, 1),
('2020-12-08', 'honda', 1, 2),
('2020-12-08', 'honda', 2, 1),
('2020-12-07', 'honda', 0, 1),
('2020-12-07', 'honda', 1, 2),
('2020-12-07', 'honda', 2, 1);
```

Question 7 : Daily Leads and Partners | Counting Distinct Values with Grouping

(REF :

<https://leetcode.com/explore/featured/card/sql-language/683/sql-syntax/4327/>)

```
SELECT date_id,
make_name,
COUNT(DISTINCT lead_id) as unique_leads,
COUNT(DISTINCT partner_id) as unique_partners
FROM dailysales
GROUP BY date_id, make_name;
```