

In build functions

=====

- String
- Date
- Numeric
- other

String functions

=====

-- concat

```
select *, CONCAT(customer_fname,' ',customer_lname) as full_name from customers;
```

```
select *, CONCAT(customer_street , ' ', customer_city , ' ', 'customer_state' , ' ', customer_zip code)
as address from customers;
```

-- length

```
select *, LENGTH(customer_fname) as name_length
from customers;
```

```
select *
from customers
where LENGTH(customer_fname) = 8;
```

```
SELECT LENGTH(' Sumit Mittal ');
```

```
SELECT customer_id, LENGTH(customer_id)
FROM customers;
```

implement data quality checks

customer_state will be of 2 chars
customer_zipcode will be of 5 chars

```
SELECT count(*) from customers
where LENGTH(customer_state) !=2
OR LENGTH(customer_zipcode) !=5
```

-- LOWER / UPPER

```
select UPPER('SQL Champion Program')
```

-- SUBSTRING

```
select SUBSTRING('Hello World', 7 , 5);
```

```
select SUBSTRING('Hello World', 3);
```

```
select SUBSTRING('Hello World',-5);
```

```
select customer_fname, SUBSTRING(customer_fname,-4)
FROM customers;
```

```
select SUBSTRING('Hello World',1);
```

```
-- trim / ltrim / rtrim
```

```
select TRIM(' SQL Champion Program ');
```

```
-- find all the customers with leading or trailing spaces in customer_street
```

```
SELECT *
FROM customers
WHERE TRIM(customer_street) != customer_street;
```

```
SELECT *
FROM customers
WHERE TRIM(customer_city) != customer_city;
```

```
-- REPLACE
```

```
select REPLACE('Hello World' , 'World' , 'MySQL')
```

```
select customer_id, customer_fname, REPLACE(customer_state, 'CA' , 'CALIFORNIA')
FROM customers;
```

```
-- LOCATE / INSTR
```

```
SELECT LOCATE('World', 'Hello World') as position;
SELECT INSTR( 'Hello World' , 'World') as position;
SELECT LOCATE('l', 'Hello World') as position;
```

```
select *, SUBSTR(customer_street,1,LOCATE(' ',customer_street)-1) as street_number
from customers;
```