

Question 3: Customer Who Visited but Did Not Make Any Transactions |

Left Join with Aggregation (Medium)

(REF : <https://leetcode.com/explore/featured/card/sql-language/684/sql-relationship/4338/>)

Table: Visits

+-----+-----+	
Column Name	Type
+-----+-----+	
visit_id	int
customer_id	int
+-----+-----+	

visit_id is the column with unique values for this table.

This table contains information about the customers who visited the mall.

Table: Transactions

+-----+-----+	
Column Name	Type
+-----+-----+	
transaction_id	int
visit_id	int
amount	int
+-----+-----+	

transaction_id is column with unique values for this table.

This table contains information about the transactions made during the visit_id.

Write a solution to find the IDs of the users who visited without making any transactions and the number of times they made these types of visits.

Return the result table sorted in any order.

The result format is in the following example:

Example 1:

Input:

Visits

+-----+-----+	
visit_id	customer_id
+-----+-----+	
1	23
2	9
4	30
5	54
6	96
7	54
8	54
+-----+-----+	

Transactions

transaction_id	visit_id	amount
2	5	310
3	5	300
9	5	200
12	1	910
13	2	970

Output:

customer_id	count_no_trans
54	2
30	1
96	1

-- Insert statements for Visits table

```
INSERT INTO Visits (visit_id, customer_id) VALUES (1, 23);
INSERT INTO Visits (visit_id, customer_id) VALUES (2, 9);
INSERT INTO Visits (visit_id, customer_id) VALUES (4, 30);
INSERT INTO Visits (visit_id, customer_id) VALUES (5, 54);
INSERT INTO Visits (visit_id, customer_id) VALUES (6, 96);
INSERT INTO Visits (visit_id, customer_id) VALUES (7, 54);
INSERT INTO Visits (visit_id, customer_id) VALUES (8, 54);
```

-- Insert statements for Transactions table

```
INSERT INTO Transactions (transaction_id, visit_id, amount) VALUES (2, 5, 310);
INSERT INTO Transactions (transaction_id, visit_id, amount) VALUES (3, 5, 300);
INSERT INTO Transactions (transaction_id, visit_id, amount) VALUES (9, 5, 200);
INSERT INTO Transactions (transaction_id, visit_id, amount) VALUES (12, 1, 910);
INSERT INTO Transactions (transaction_id, visit_id, amount) VALUES (13, 2, 970);
```

=====

-- question 3

<https://leetcode.com/problems/customer-who-visited-but-did-not-make-any-transactions/editorial/>

Visits

-----+-----+		
visit_id	customer_id	
+-----+-----+		
1	23	
2	9	
4	30	
5	54	
6	96	
7	54	
8	54	
+-----+-----+		

Transactions

+-----+-----+-----+			
transaction_id	visit_id	amount	
+-----+-----+-----+			
2	5	310	
3	5	300	
9	5	200	
12	1	910	
13	2	970	
+-----+-----+-----+			

Output:

+-----+-----+		
customer_id	count_no_trans	
+-----+-----+		
54	2	
30	1	
96	1	
+-----+-----+		

in the left table but not in right

```
SELECT v.customer_id, COUNT(*) as count_no_trans
FROM
visits v
left join transactions t
on v.visit_id = t.visit_id
where t.visit_id is NULL
GROUP BY v.customer_id;
```