

ServoDatabase.com

Servo Specifications and Reviews

[All Servos](#) [Brands](#) [Compare \(0\)](#)



[Advanced Search](#)

[Servo Database](#) / [Hitec Servos](#) / [HS-225BB](#)

Hitec HS-225BB - Mighty Mini Servo

Specifications

Modulation:	Analog
Torque:	4.8V: 54.00 oz-in (3.89 kg-cm) 6.0V: 67.00 oz-in (4.82 kg-cm)
Speed:	4.8V: 0.14 sec/60° 6.0V: 0.11 sec/60°
Weight:	0.95 oz (26.9 g)
Dimensions:	Length: 1.27 in (32.3 mm) Width: 0.66 in (16.8 mm) Height: 1.22 in (31.0 mm)
Motor Type:	3-pole
Gear Type:	Plastic
Rotation/Support:	Single Bearing
Rotational Range:	(add)
Pulse Cycle:	20 ms
Pulse Width:	900-2100 µs
Connector Type:	(add)



Brand:	HITEC
Product Number:	31225S
Typical Price:	22.95 USD
Compare:	add+

Notes

- Hitec HS-225MG is the same servo, but with metal gears.

Reviews of Hitec HS-225BB

(2)

Willettfx January 1, 2016	Rating: Application(s): Animatronics Comments: Great servo have 8 of them. Prices \$17 each.
GT May 1, 2015	Rating: Application(s): .25 to .40 glow all surfaces Comments: Fantastic servo for medium size glow use. I do use at 6 volt.

Submit a review of Hitec HS-225BB