
Pattern recognition system

Exercise Project

REPORT ASSIGNMENT N°2

Student

Antoine HONORÉ
honore@kth.se

Student

Audrey BROUARD
brouard@kth.se



I

1. Below are represented the pitch and intensity profiles of the 3 songs provided.




FIGURE 1 – Pitches and Intensity for the 3 melodies

On the pitch profile we can notice that that's we hardly see the different "useful" pitches as the noise has a pitch of around 1000Hz. The important thing here is that the pitch reaches 1000Hz with a very low intensity. Which means that a threshold on intensity should be enough to get rid of the noise. If we zoom in we can clearly read the pitch values corresponding to different notes :




FIGURE 2 – Zoom

Here on the pitch profile we can distinguish different values of pitch between 100Hz and 300Hz, which corresponds to different notes, globally spread over 1.5 octave.

II Design of the feature extractor

II.1 Our decisions

In order to fulfil all the conditions listed in the subject, we designed our feature extractor as follows :

- First we extract the actual pitches by removing the noise around 1000Hz so that we only have the pitches containing a lot of information.
- Then we interpolate the vector thus obtained with a vector containing all the notes in the range 20Hz-20kHz. This last vector was built thanks to the constant ratio between 2 consecutive semitons. This way we obtain a vector containing the different notes played in the song, but so far we are dependant of the octave.
- To that purpose, we set a reference to remove the offset of the melody. The reference is defined as the first pitch which is not a silence. After that, we are able to determine of how many semitons above or below the reference the next pitches are located. We thus obtain a vector containing the variation of semiton from the reference for each pitch, and infinity when it's a silence.
- Finally, the duration of each note/silence will be determined by the number of time the source remains in the same state. To avoid temporal distortion issues (a singer might sing faster or slower than another one), we will define a vector containing the ratio between two notes durations.

II.2 Integration to PattRecClasses

The states correspond to the semitons offset. Let us consider an example : we extract such features [044440 – 1 – 1...]. This vector is a vector of frames and here the first one is the reference. The five following fours mean that this part of the signal has a pitch 4 semitons above the reference. The states come naturally to be integers representing an offset of semitons. The actual value of pitches in frame 2 to 5 are not the same, their distribution defines the distribution of state 4. The extraction of the offset is made in the function `find_offset`.

II.3 Example

Let us now consider a real example. Melody 1 and melody 2 are the same melody sung at a different level. Besides, the two songs do not have the same duration. To perform the test we followed these steps :

- Load the two songs ;
 - Run `GetMusicFeatures` with the default parameters on the two signals ;
 - Run `find_offset` on the two signals and get v_1 & v_2 , which represent the vectors of offset that we discussed about in the previous section.
- the plot of v_1 & v_2 is shown on figure 3.




FIGURE 3 – Blue : first melody Red : second melody

On the picture, we clearly see that the serie of semiton is the same. In the first melody, the singer hold the note longer than in the second. Besides, we can guess a constant difference between the two vectors.

On the contrary if we now had to the graphics the third melody, which is different from the 2 others, we can clearly see that the behaviour is completely different :

As the song sung is different, the notes are different too which explains why the offset obtained varies. This is the behaviour we expected from our feature extractor.




FIGURE 4 – Black : third melody, different from the 1 others

II.4 Weaknesses of our feature extractor

So far, our feature extractor can recognize a song sung even if it's transposed, thanks to the offset. It can also recognize the song even if it's sung slower or quicker than the original. However, for the moment our feature extractor doesn't take in account the ambient noise which can influence the pitch of the notes played.

TODO : plot the feature extracted from 2 identical melodies but transposed.