

Org Beamer quick reference card

Fabrice Niessen

March 27, 2014

Plan

Description

Welcome to **Org Beamer reference card**. It contains the reference documentation that describes how to **write presentations** using Org mode 8+ and the \LaTeX Beamer class (which allows producing **high quality PDF files** which are going to look on every computer exactly the way they looked on your computer).

Objectives

Preparing presentations with Org mode is different from preparing them with WYSWYG programs such as PowerPoint, Impress or Keynote, as they are created **like any other Org mode document**.

The obvious advantage of this approach is that **you don't have to know L^AT_EX** in order to use Org mode's Beamer export and **create presentations**.

Org mode presentations contain headings at different levels. By default, headings at the first outline level will become titles of the different slides (called frames in Beamer), and deeper levels will be used as structural environments.

Requirements

A working \LaTeX installation is required for exporting to PDF. If it is not yet installed on your system, install (for example) \TeX Live.

Library ox-beamer.el

Beamer back-end (for Org export engine)

Type:

```
M-x load-library RET ox-beamer RET
```

to load the Beamer back-end library, and to obtain **extra commands** in the \LaTeX export menu:

C-c C-e 1 B As \LaTeX buffer (Beamer).

C-c C-e 1 b As \LaTeX file (Beamer).

C-c C-e 1 P As PDF file (Beamer).

C-c C-e 1 0 As PDF file and open (Beamer).

Editing support

Type:

```
M-x org-beamer-mode RET
```

to load the minor mode `org-beamer-mode` **easing the edition** of the

Beamer-related keywords

The Beamer back-end introduces the following keywords:

```
#+BEAMER_THEME: Boadilla
```

which (for Boadilla) is equivalent to:

```
#+BEAMER_COLOR_THEME: dolphin  
#+BEAMER_FONT_THEME: default  
#+BEAMER_INNER_THEME: [shadow]rounded  
#+BEAMER_OUTER_THEME: infolines
```

Append any line of code in the \LaTeX preamble with:

```
#+BEAMER_HEADER:
```

XXX Is it [BEAMER-EXTRA] or [BEAMER-HEADER-EXTRA] in org-latex-classes?

Keywords

`ox-beamer.el` reads both `ATTR_LATEX` and `ATTR_BEAMER`, when it makes sense.

Properties

If you set

```
#+OPTIONS: H:2
```

then:

- **Second**-level headlines become the **frames**, and
- Top-level headlines become **sections** (listed in the **table of contents**, which is created by default).

Creating a frame

```
** A title  
  #+BEAMER: \framesubtitle{A subtitle}
```

Some content.

The “subtitle feature” does not have an Org syntax because it’s specific to one back-end only.

againframe

You can add an appendix to your talk by using the `\appendix` command. You should put frames and perhaps whole subsections into the appendix that you do not intend to show during your presentation, but which might be useful to answer a question. The `\appendix` command essentially just starts a new part named `\appendixname`. However, it also sets up certain hyperlinks. Like other parts, the appendix is kept separate from your actual talk.

column

columns

frame

- Headlines become frames when their level is equal to `org-beamer-frame-level` (or H value in the OPTIONS line).
- Though, if a headline in the current tree has a `BEAMER_env` property set to either `frame` or `fullframe`, its level overrides the variable.

- A `fullframe` is a frame with an ignored title
 - ▶ `frametitle` is set to the empty string

- A headline with an `ignoreheading` environment will have its contents only inserted in the output.
- ▶ Contents is not inserted in any `frame` environment...
- This special value is useful to have data between frames, or to properly close a `column` environment.

note

Explicit page breaking I

If the text does not fit on a single slide, all you have to do to automatically break up the frame into several frames, is set the option `allowframebreaks`:

```
** A long "frame" with breaks
:PROPERTIES:
:BEAMER_opt: allowframebreaks,label=
:END:
```

Until the Beamer issue #265 is solved, we need to unset the `framelabel` as shown above (`label=`).

Figures





Figure : The caption is *a*lways placed **below** the figure.

TikZ

[http://tex.stackexchange.com/questions/64075/
beamers-visible-inside-a-tikz-node](http://tex.stackexchange.com/questions/64075/beamers-visible-inside-a-tikz-node)

I'm very
happy.

TODO Specify 5cm


BMCOL

Two
lines.

One line (but aligned).

Multiple columns

Two
lines.



Result of an evaluation on two columns

2
... a fancy verbatim block ...

structureenv environment

- For highlighting text.
- To help the audience see the structure of your presentation.

Paragraph Heading.

block environment

Answered Questions

How many primes are there?

Open Questions

Is every even number the sum of two primes?

alertblock environment

- Inserts a block whose title is highlighted.
- Behaves like the block environment otherwise.

Wrong theorem

$1=2$.

exampleblock environment

- Inserts a block that is supposed to be an example.
- Behaves like the `block` environment otherwise.

Example

The set $\{1,2,3,5\}$ has four elements.

theorem environment

- Inserts a theorem.

Theorem

There is no largest prime number.

theorem environment

- Inserts a theorem.
- Simpler solution
 - ▶ More readable
 - ▶ Less powerful: you can't nest blocks of the same type with this syntax

Theorem

There is no largest prime number.

definition environment

- Behaves like the `theorem` environment, except that the `theorem style definition` is used.
- In this style, the body of a `theorem` is typeset in an upright font.

Definition (definition)

Contents of definition

example environment

- Behaves like the theorem environment, except that the theorem style `example` is used.
- A side-effect of using this theorem style is that the contents is put in an `exampleblock` instead of a `block`.

Example (Example)

Contents of example

example environment

- Simpler solution:

Contents of example

proof environment

- Typesets a proof.

proof.

- Suppose p were the largest prime number.
- But $q + 1$ is greater than 1, thus divisible by some prime number not in the first p numbers. □

proof environment

- Typesets a proof.

proof.

- Suppose p were the largest prime number.
- Let q be the product of the first p numbers.
- But $q + 1$ is greater than 1, thus divisible by some prime number not in the first p numbers. □

proof environment

- Typesets a proof.

proof.

- Suppose p were the largest prime number.
- Let q be the product of the first p numbers.
- Then $q + 1$ is not divisible by any of them.
- But $q + 1$ is greater than 1 , thus divisible by some prime number not in the first p numbers. □

beamercolorbox environment

- Create colored boxes.

Text

Contents of verse

verse environment

- Simpler solution:

Contents of verse

quotation environment

- Use `quote` or `quotation` to typeset quoted text.
- `quotation` has paragraph indentation.

Contents of quotation

quote environment

- Use `quote` or `quotation` to typeset quoted text.
- `quote` hasn't paragraph indentation.

Contents of quote

quote environment

- Use quote or quotation to typeset quoted text.
- quote hasn't paragraph indentation.
- Simpler solution:

Contents of quote

Verbatim

```
int main (void)
{
    std::vector<bool> is_prime (100, true);
    for (int i = 2; i < 100; i++)
        if (is_prime[i])
        {
            std::cout << i << " ";
            for (int j = i; j < 100;
                is_prime [j] = false, j+=i);
        }
    return 0;
}
```

Extra environments

For simple environments, use:

3 Test of a new environment

I think we should changes some environment placeholders:

- Introduce `%r` which would stand for the raw headline (without any processing)
- `%H` and `%U` would use the raw headline text instead.

The previous definition would become:

```
'("textpos1" "w" "\%r \%a {" "}" \')
```

WDYT?

- Environment options may be given using the `BEAMER_opt` property. They will be enclosed in square brackets and inserted where `%o` appears in the environment definition. (with an example, but I can't think of one now)
- Additional arguments may be written into the environment's headline, and inserted into the \LaTeX string using `%r` (raw headline text, no processing).

Overlay/action specification (act)

- Headlines support BEAMER_ACT properties.

Dynamic list are possible on a case by case basis :

```
- @@beamer:<1->@@ Item  
- @@beamer:<2->@@ Item
```

and as a frame property:

```
* Headline  
:PROPERTIES:  
:BEAMER_ACT: [+ -]  
:END:  
  
- Item  
- Item
```

Overlay/action specification (act)

- Headlines support BEAMER_ACT properties.
- It is translated as an overlay/action specification, or a default overlay specification when enclosed within square brackets.

Dynamic list are possible on a case by case basis :

```
- @@beamer:<1->@@ Item  
- @@beamer:<2->@@ Item
```

and as a frame property:

```
* Headline  
:PROPERTIES:  
:BEAMER_ACT: [+ -]  
:END:  
  
- Item  
- Item
```

Options for the current frame (opt)

- Headlines support BEAMER_OPT properties.

I'd still like to see something more like a “for-dummies” explanation of passing options and arguments to \LaTeX entities. I'm not saying the documentation is woefully inadequate (hardly that – Suvayu's page got me rather far, and I got stuck on a couple of details). My experience was: it never would have occurred to me on my own to use the headline text for \LaTeX code, and if there was a hint anywhere in the docs to suggest that this would be the way to go, I didn't find it. That's a conceptual leap that passed me by.

- This is for frames, and for environments within a frame
- It specifies options for the current frame or block, and will automatically be enclosed within square brackets.
- `fragile` option is added automatically
- You might want to put `allowframebreaks=0.9` there

Skip proof
nil

Summary

For further reading



A. Salomaa.

Formal Languages.

Academic Press, 1973.

For further reading



A. Salomaa.

Formal Languages.

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

Science of Computer Programming, 1(3):223–233, 1982.

For further reading



A. Salomaa.

Formal Languages.

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

Science of Computer Programming, 1(3):223–233, 1982.



E. Feldman and J. Owings, Jr.

A class of universal linear bounded automata.

Information Sciences, 6:187–190, 1973.

For further reading



A. Salomaa.

Formal Languages.

Academic Press, 1973.



E. Dijkstra.

Smoothsort, an alternative for sorting in situ.

Science of Computer Programming, 1(3):223–233, 1982.



E. Feldman and J. Owings, Jr.

A class of universal linear bounded automata.

Information Sciences, 6:187–190, 1973.



P. Jančar, F. Mráz, M. Plátek, and J. Vogel.

Restarting automata.

FCT Conference 1995, LNCS 985, pages 282–292. 1995.

Proof details

Text omitted in main talk.

More details

Even more additional material.

Abbreviations