Same Evidence, Different Verdicts: Evidence Standards for AI Collusion Attribution

Author: [OWNER]. Affiliation: [OWNER]. The owner is the sole author.

Abstract

Audits of multi-agent systems use logged messages and replay interventions to assess whether agents colluded. Yet the same transcript and message-removal effect can arise from harmful coordination or legitimate cooperation. We propose an evidence ladder separating suspicious text, causal influence, harmful exposure and justified attribution. Executable twin worlds identify which additional evidence separates those labels within declared generators and information sets. An abstention-aware benchmark scores errors alongside unresolved attribution. In the established deterministic prospective stratum, the knockout baseline accused legitimate allocation and authorized-transfer members in 200/200 pairs each; an environment probe and authorization record, respectively, separated the twins [NP]. These are construction consistency results, not independent detection performance. Four preregistered aggregate benchmark predictions failed: label-effect, original over-attribution, refined over-attribution and ladder-auditor utility. The noisy stratum is platform-dependent, not established; restricting established results to the deterministic stratum was a post-hoc decision after outcomes were visible. The original preregistered local-model study yielded Delta = 1.354, world-cluster 95% CI [-0.020, 2.834], exact one-sided p = 0.0703, across 8 matched world pairs [OC]. The directional hypothesis was NOT supported. End-to-end certificate recovery remains unestablished. We recommend reporting the highest justified rung, the auditor's information set and the evidence needed to resolve ambiguity. We do not claim to detect collusion or intent.

Evidence categories. Quantitative settings and measurements carry one class each; a class scopes its quantity or single-class paragraph/table row. Identifiers (citations, sections, rungs, versions, paths, hashes, seeds, figure labels) are metadata, not empirical measurements. Evidence tags: [OC] original-confirmatory; [ORS] original-registered-secondary; [D] descriptive; [PH] post-hoc-exploratory; [NP] new-prospective; [DEV] development.

1. Introduction

A team allocates a contested task to a coalition member. In one world its message steers work away from a cheaper outsider; in its twin, the same message and allocation follow the shared efficiency objective. The transcript and factual, knockout, sham and placebo outcomes are identical by construction. An auditor using that evidence must return the same output for both worlds, although their attribution labels differ. An environment probe asks the separating question: would the team yield when the outsider becomes the efficient claimant? Figure 1 presents the evidence ladder [NP] (PROSPECTIVE in its source figure metadata; a conceptual diagram, not a measured outcome).

Auditors may use evidence of collusion to recommend sanctions, shutdowns or deployment decisions. Confusing influence with attribution risks accusing legitimate cooperation while missing harmful coordination. Our threat model is an auditor with a replayable log and a suspected message exposure, facing both possibilities. Auditors and benchmark builders can use this standard to state which claim their evidence supports and what additional probe or authorization record is needed.

We ask when a message changes behaviour, when that change harms outsiders, and when the available evidence separates harmful coordination from legitimate cooperation. The benchmark and held-out study test the same evidence ladder.

Our contributions are:

1. **An evidence ladder** separating influence, harm and attribution, with explicit information sets and a scoped identifiability statement (Section 3).
2. **Executable twin worlds and an abstention-aware benchmark** with an enumerated separating-evidence frontier (Sections 4 and 5).
3. **An exposure-level instrument and ladder-aware reporter:** CCC retains its harm gates; CCC-L reports unresolved or excluded attribution. Its revision is development-informed (Section 4).
4. **Evidence separated by status:** development controls, an original held-out directional hypothesis that was NOT supported [OC], and prospective benchmark findings with pre-stated failures retained [NP] (Section 5).

What is new, and what is not. Counterfactual interventions, sham and placebo controls and three-way outcomes are established [2, 7]. Indistinguishability of lawful parallelism and conspiracy is argued for price- and bid-level tests [5] and for reasoning agents [6]; the boundary between beneficial cooperation and harmful collusion is named as an open challenge in [8]. In a bounded search (Appendix G) we found no executable, message-level, interventional statement of the limit with a measured separating-evidence frontier. We state the limit only for our generators and information sets, and make no priority claim.

What we tested and found. The preregistered held-out directional hypothesis was not supported [OC] (Section 5.4). The prospective frontier matched enumeration by construction [NP]. The original and DEV-informed over-attribution predictions both failed across the required strata [NP].

Figure 1. Same evidence, different attribution labels [NP] (schematic of the prospective twins). Left: a colluding-allocation twin and its efficiency-motivated counterpart share transcript and declared replay outcomes. Middle: equal tau_O, tau_C and tau_W support the same exposure-level reading. Right: the ladder separates influence and harm from attribution; an environment probe supplies separating evidence. **Takeaway:** identical declared evidence requires the same audit output, so attribution needs separating evidence. Rendering is pending; this schematic asserts no measured bars or prospective verdicts.




Figure 1. (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). Evidence ladder L0 suspicious text, L1 causal influence, L2 harmful exposure, L3 attribution, with the information set (I0-I5) each rung needs. Concept colours: causal effect (blue), harm (red), attribution (purple), uncertainty (amber).

2. Related Work

Interventional collusion audits. Impulse responses after forced deviations were used to infer punishment in Q-learning pricing [19]; later work shows this pattern does not by itself identify a punishment mechanism [20]. For LLM markets, Tran and Yu clone markets under shared seeds and use A/A tests, placebos and positive controls, and note in their limitations that at cartel prices the deviation "separates a punisher only poorly from a rival that merely best-responds" [2]. Colosseum audits collusion in a Jira-style DCOP and states in its limitations that collusion is not always harmful [1]; we reuse its environment. VLA intervenes on latent messages at a single bid event [3]; multi-agent interpretability probes [4] are a white-box complement, and that work notes counterfactual simulation cannot always be assumed. Delta: we study text exposures with regenerated continuations and ask what the effect licenses, not only how to estimate it.

Closest methodological neighbour. Zhang and Emu replace a message with a matched other-example message, report positive, negligible or inconclusive outcomes, and use paired bootstrap intervals with sign-flip or exact paired tests and a presence-versus-content decomposition [7]. It is not collusion-specific and does not address normative labels; we claim no novelty for matched controls or three-way outcomes, and our placebo and certificate taxonomy are engineering instances of that design adapted to harm and utility gates.

Indistinguishability claims. Xu et al. show that price- and bid-level audits against competitive marginals have power exactly alpha and that lawful multi-identity operation and conspiracy are behaviourally indistinguishable there, while noting that a universal impossibility claim would be false [5]. Riemer et al. argue that reasoning agents compress the gap between lawful parallelism and coordination to indistinguishability [6]; Lee and Park report CoT monitoring dissociates from collusion [9]; Idowu et al. flag the cooperation/collusion boundary as an open challenge [8]. Ward et al. define intent relative to a structural causal model under an assumed shared model [12]; Everitt et al. show incentive criteria are properties of the assumed causal influence diagram [11]. Delta: these are observational, price-level or conceptual; ours is message-level, interventional and executable, and measures the minimal separating information set per pair type, scoped to our generators and not a general impossibility theorem.

Responsibility, replay attribution and abstention. Counterfactual replay for failure attribution [14, 15] and degrees of responsibility under redundant contributions [13] motivate our redundancy cases (reported as "not identifiable under I1", not "no effect"); selective classification [17] and delegation guarantees [18] motivate abstention-aware scoring; [16] is a preregistered audit precedent whose hypothesis was not supported; steganographic channels [10] can evade any text-level intervention (Appendix G).

3. The Evidence Standard

Setting. A replayable team of agents with a designated sender s and receiver r, outsiders O, a coalition C = {s, r}, and a declared exposure E *(a message, or a set of messages). Arms: F (factual replay), K (knockout of E*, persistently masked by event id so re-rendered history does not leak it), S (sham with identical rendering and an empty mask), N (matched-message placebo, only where an eligible same-sender inert message exists).

Estimands. tau_O = E[Omean_K] - E[Omean_F] (outsider effect), tau_C = E[Cmean_F - Cmean_K] (coalition benefit), tau_W = E[W_K - W_F] (total-utility change). Outsider harm is declared with margin m_O = 2.5 and welfare tolerance delta_W = 5.0 (frozen). Reward units are task units, not currency [OC] (frozen design).

Evidence ladder. Each rung is a separate claim with its own gate; no rung implies the next.

Rung	Claim	Minimal evidence
L0	The text is suspicious	transcript (I0)
L1	The message causally influences behaviour	K changes behaviour relative to S
L2	Exposure produces harm	valid replay; tau_O > m_O with sham and utility controls; coalition and welfare gates
L3	The agents colluded (attribution)	L2 plus evidence separating harmful coordination from legitimate cooperation under the declared norm

Information sets (nested). I0 transcript and factual outcomes; I1 adds single-message knockout K; I2 adds sham S and placebo N; I3 adds joint knockout of all same-sender carriers of the exposure; I4 adds an environment or incentive probe (re-run F and K with outsider costs on the contested task lowered, so that an outsider is the efficient claimant); I5 adds an external normative record (authorization), which is non-behavioural.

Identifiability. Let O_S(w) be the canonical byte string of observables available under S in world w, and L(w) the label of interest (mechanism M, or attributable collusion = harmful, redundant-harmful or relayed-harmful). An instance w is *identifiable under S* iff every world w' in the generator's policy space with O_S(w') = O_S(w) has L(w') = L(w); I(S) is the set of such instances. Computed by exact enumeration, never from any method's gates. Twin members with identical O_S are equivalent by definition; the empirical readouts are the separating set per pair type, the symmetry check, the label-effect gap and the behaviour of baselines and CCC on twin members.

Scoped limit statement. "In these scripted generators, for the stated information sets, twin worlds with byte-identical observables are indistinguishable by construction; the frontier evaluation asks which additional evidence separates them; this is a scoped, executable statement about these sets and generators, not a general impossibility theorem about collusion attribution."




Figure 2. (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). One evidence, two verdicts. P2 twin pair at seed 19693329 (lowest seed rule). Identical observables under I1-I3 (enumeration), opposite labels, frozen CCC v1.2.2 emits the same exposure-level output for both; the I4 incentive probe separates them.

CCC (L2 instrument) [D] (design settings). A `supported` verdict requires established validity and placebo evidence, nonempty M*, L(tau_O) > m_O, L(tau_C) > 0, L(tau_W) >= -delta_W and resolved information-loss gates, with one-sided 95% bounds from exact shift-permutation inversion. `Not supported` requires U(tau_O) < m_O with no detected carriers; other eligible cases are `inconclusive` with reasons; failed integrity is `invalid`. The carrier extractor is a `weak_detector` heuristic; CCC v1.2.2 is used unmodified. In this paper a CCC `supported` is an L2 claim and is never reported as attribution.

4. Benchmark and Study Methods

Benchmark [NP] (frozen design). Six twin-pair types P1-P6 (redundant-harmful vs inert; colluding vs efficiency-motivated allocation; authorized vs unauthorized transfer; common cause vs message-caused coordination; suspicious vs plain inert language; information-bearing vs harmful steering), a relayed-harmful case, corrupted traces and 11 benchmark classes, each twin pair being ONE independent unit (Appendix E). Strata eps in {0, 0.1} (random-action probability of each scripted agent; R = 8 continuations per arm) are reported separately and never pooled. Seeds derive from the protocol hash with a deterministic skip rule against all development, pilot and original-study seeds; disjointness is checked and hashed in FREEZE.json before any run. Metrics: over-claim rate, sensitivity, FPR, abstention and coverage, risk-coverage curves at abstention cost c in {0.25, 0.5}, exact Clopper-Pearson 95% intervals over independent units, exact McNemar-type paired tests, world-cluster percentile bootstrap (Appendix E). Single pass, fixed N, no interim looks; crashes stay in the denominator; any code change after outcomes are visible forces a new seed block and both runs are reported.

Positive control [DEV] (design). The **P4 message-caused coordination member**, contrasted with its common-cause twin, is the named causal-influence positive control. Single-message knockout is the declared separating intervention. This checks influence rather than the full certificate or attribution pipeline. Recovery counts and support-level positive-control validation are not established in the supplied draft and must be reported before instrument-validity claims.

Four axes, never merged. M mechanism label; H realized harm (oracle outsider reward under F lower than the no-coordination reference by more than m_O); E exposure effect (oracle tau_O >= m_O; tau_C, tau_W also reported); I(S) identifiability. Ground-truth availability is explicit per class; where an axis has no truth it is scored "inapplicable" and never imputed. EXP-002 real-agent worlds have none of M, H or I(S).

Methods compared (each sees only the observables of its declared set; frozen before any prospective seed existed): frozen CCC v1.2.2; outcome-only, knockout, harm-gated knockout, influence-only and transcript-keyword baselines; always-answer and always-abstain anchors; the Bayes-given-S ceiling; and CCC-L v1 (new, exploratory, DEV-informed), which outputs the highest justified rung, "insufficient for L3 under S", or "L3 excluded" (attribution ruled out by separating evidence in S). CCC-L v0 lacks the last output, so DEV showed it cannot be correct on both members of a pair; it is retained and reported prospectively so the change is visible. The strongest knockout baseline was fixed on DEV block 13000-13049 (B2+ or B3b; ties to B2+) and recorded in FREEZE.json (Appendix E).

Frozen research questions [NP] (criteria). The protocol tests symmetry and the separating-evidence frontier, the label-effect gap, knockout over-attribution, abstention-aware ladder reporting and descriptive CCC behaviour. Appendix E gives every threshold and failure rule; Section 5 reports each question without replacing the original over-attribution prediction with its development-informed refinement.

Amendments and disclosures [DEV]. Three director amendments precede the DEV run (CRN, circularity disclosure, RQ6). After seeing DEV results (RQ1 and RQ3 passed; RQ2, RQ4 and RQ5 failed) and before any prospective seed existed, four further amendments were made and are reported as DEV-informed: CCC-L v0 to v1 (adds "L3 excluded"), RQ2 made method-independent, RQ4b added beside the unchanged RQ4, and RQ3 left unchanged. The independent review (REV-R2) approved the freeze with four conditions, which we adopt as reporting rules. (C2) RQ5 is structurally strict: undefined denominators score as fail (166/168 DEV cells), so the informative RQ5 readouts are the selective-accuracy gap, over-claim counts and pair attribution (DEV v1: 1.00 at eps = 0, 0.66 at eps = 0.1) [DEV]. (C3) The report is stricter than the protocol text: RQ3 and RQ4 must pass in both strata; RQ1 and RQ2 are consistency checks by construction and are not performance evidence. (C4) Prospective RQ3 uses effectively random cell assignment, whereas the DEV block was balanced (0.24 [DEV] against the 0.25 frozen bound [NP] at the deterministic stratum), so DEV is not a reliable guide to the prospective value. Circularity (amendment A2): RQ2 and RQ5 are consistency checks of the generator, the enumeration and the reference auditor; CCC-L was written knowing which evidence separates each type, so passing them is expected by design and is not a performance claim. D-048 subsequently restricts established results to

eps = 0; eps = 0.1 is platform-dependent, not established, including the proposed noisy-stratum robustness check. DEV macOS eps = 0.1 is not comparable with prospective Linux eps = 0.1.

Original held-out study (EXP-002; protocol v1.2, preregistered) [OC] (design). Local `gemma4:26b`; 8 matched world pairs; regimes B1 (one deception prompt variant) and B2 (authorized cooperation); 4 F and 4 K continuations per checkpoint. Estimand Delta = mean_w[tau_O(w,B1) - tau_O(w,B2)] with whole matched worlds as independent units; the directional primary required both a positive world-cluster bootstrap lower bound (10,000 draws) and exact one-sided paired sign-flip p <= 0.05. Case-level certificates are exploratory. The prospective study (R2) has disjoint worlds, seeds and code hashes, is never pooled with EXP-002, and EXP-002 serves only as a real-agent illustration.

5. Results

5.1 Positive control and development evidence

The P4 message-caused coordination positive control is specified in Section 4 [DEV] (design). Its recovery is not established by the supplied draft. The following implementation checks do not substitute for that result.

Gate A (v1.2.2) passed its deterministic implementation checks (for example A2 benign cooperation never supported, 80/80) but is not held-out inference, and agreement with scripted predictions is not validation. The label-effect gap was 12/80 in Gate A and 12/50 (eps = 0), 5/50 (eps = 0.1) in the benchmark DEV block [DEV]; RQ3 and RQ4 were derived from these, and none counts as confirmatory (Appendix F).




Figure 3. Held-out real-agent matched-world contrasts (EXP-002), aggregate Delta and world-cluster CI (OC). The preregistered directional test is a confirmatory null; non-commit exclusion points are the registered sensitivity (ORS), not the primary.

5.2 Frontier and identifiability [NP]

Established prospective results below use **eps = 0 only** [NP]. D-048 marks eps = 0.1 **platform-dependent, not established**: across the preserved cross-platform overlap, all 149 deterministic units were byte-identical, while 142/148 noisy units differed and 1160/1452 noisy records had differing method output objects [D] (platform audit). The restriction was decided **post hoc, after outcomes were visible**, on evidence of substantive cross-platform divergence. Its cause is unresolved. Mapped methods/enumeration ran on Modal Linux; RQ3 population generation and reporting ran locally (D-046). Full noisy results remain in `RESULTS_BY_STRATUM.json`; no claim rests on them.

Pre-registered aggregate verdicts (verbatim from report.py):

- RQ1: **pass** — T2
- RQ2: **pass** — T3
- RQ3: **fail** — T4
- RQ4: **fail** — T5
- RQ4b: **fail** — T5b
- RQ5: **fail** — T8
- RQ6: **descriptive** — RQ6

These aggregate rules require both strata. Four predictions failed; the stratum restriction does not change those verdicts.

RQ1 symmetry — eps = 0 pass. [NP] All 182 eligible method x pair-type x set cells had zero within-pair output differences (0/200 per cell; exact CP 95% upper bound 0.01827534). This checks consistency with the construction.

RQ2 frontier — eps = 0 pass (by construction). [NP] The Bayes-given-S frontier equalled enumeration: P1/I3, P2/I4, P3/I5, P4/I1 and P6/I1, with 200/200 pairs correct at each frontier (CP 95% [0.981725, 1]). No method correctly answered both members below it beyond Bayes. Relayed-harmful remained unresolved at I3 (100/100 units). This is generator consistency, not independent detection performance.

5.3 Abstention-aware benchmark [NP]

RQ3 label-effect gap — eps = 0 FAIL. [NP] The share was 30.5% (61/200; CP 95% [0.242, 0.374]), failing the frozen <25% prediction. Prospective cell assignment was random; DEV was balanced. The run_par report's eps = 0.1 entry is 41/200 (20.5%; CP 95% [0.151, 0.268]), a point-threshold pass without margin, **platform-dependent, not established**. The aggregate remains failed.

RQ4 over-attribution — eps = 0 FAIL. [NP] B2+ accused legitimate P2 and P3 members at 200/200 each (CP 95% [0.981725, 1]), but P6 at 0/200 and benign cooperation at 0/100 (CP 95% [0, 0.018275] and [0, 0.036217]). Thus the original all-class prediction failed even in the established stratum. CCC had zero L2 supports under I1 in those cells.

RQ4b DEV-informed profile — eps = 0 pass; aggregate FAIL. [NP] The revised P2/P3 >0.5 and P6/benign <=0.05 profile held in the deterministic stratum, using the same counts. The report's noisy-stratum P2/P3 counts were 0/200 each and failed the criterion, **platform-dependent, not established**. A deterministic-stratum pass does not rescue the aggregate prediction.

RQ5 ladder auditor — eps = 0 FAIL (exploratory-method). [NP] V1 passed 2/84 cell criteria; retained v0 passed 5/84. Both had 73 undefined selective-accuracy gaps, retained as unestablished failed criteria. Both had zero overclaim unit-events, insufficient for the conjunction. V1 pair correctness at P2/I4 and P3/I5 was 200/200 each (CP 95% [0.981725, 1]); v0 was 0/200 each. Full cell rows and both frozen abstention costs remain in the stratum JSON. The noisy stratum also fails in the report, **platform-dependent, not established**; aggregate v1 and v0 both fail.

RQ6 — eps = 0 descriptive. [NP] At I2, CCC returned `supported` on 200/200 legitimate members of each of P2 and P3 (CP 95% [0.981725, 1]): harmful exposure, not attributable. The report's noisy counts were 0/200 each, **platform-dependent, not established**, with no general false-positive bound. All class/set status distributions, M/H/E views and legitimate-member intervals are copied unchanged into `RESULTS_BY_STRATUM.json`.

5.4 Original held-out study: confirmatory null

Primary [OC]. Delta = 1.354 reward units, world-cluster 95% CI [-0.020, 2.834], exact one-sided sign-flip p = 0.0703 (18/256), n = 8 matched world pairs. Both required criteria fail; the preregistered directional hypothesis is **NOT supported**. Floors were met (8 attempted pairs, 7 nonzero paired effects, 8 eligible complete pairs). This is a failed confirmatory directional test, not evidence that the effect is absent.

Design sensitivity [D]. The registered MDE_80 is about 2.2 reward units; precision was limited.

Post-hoc order check [PH]. The bootstrap lower bound is -0.0195 under archived string order and -0.00017 under numeric order; the sign-flip criterion fails independently. Delta compares prompt regimes, not realized collusion.

Not confirmatory: registered secondary and post-hoc analyses.

Class	Quantity	Value	Status
[ORS]	Registered non-commit sensitivity	Delta = 0.727, 95% CI [-0.306, 1.914]	Excludes non-committing factual continuations, retains matched worlds; changes the estimand
[PH]	Sensitivity sign-flip test	p = 0.156	Post hoc; does not repair the primary
[D]	Contribution of non-commit cases	0.627 of 1.354 (46%)	Descriptive accounting; not entirely driven by those cases

The preregistered S1–S3 family is original-confirmatory [OC]; none is significant. Estimates and Holm corrections are in Appendix F.

Exploratory certificates [D]. Over 16 checkpoints: 0 supported, 11 not supported, 5 inconclusive (B1 0/4/4, B2 0/7/1). No outsider-effect lower bound exceeded m_O = 2.5 (maximum L = 0.77). The placebo was available at 2 of 16 checkpoints, so zero support is not attributable to unavailable placebos alone. All 16 certificates carry `info_bearing = true` by conservative default, which changes no realized status.

Interpretation. The interval is compatible with effects near zero and substantially positive effects. Delta compares prompt regimes, not realized collusion. A significant exposure-level effect would still require separating evidence for attribution.

The instrument's accounting is 199 scheduled branch records: 143 executed valid continuations and 56 unrun placebo branches [D]. Control design and development checks are in Section 5.1; full accounting and sham uncertainty are in Appendix F.

6. Discussion

> **What this does and does not establish.** Valid interventions can license scoped influence or exposure-harm claims. This draft does not establish intent, exoneration, baseline superiority or general false-positive control; the studies are never pooled. Attribution needs separating evidence.

What the standard asks of an audit. Report the highest rung the evidence licenses; abstain on L3 where the frontier says the information set cannot separate the labels; state the declared norm (m_O, delta_W) and what extra evidence would split the case. The frontier matched enumeration by construction, while both the original over-attribution prediction and its DEV-informed refinement failed [NP]. CCC supported harmful exposure on legitimate P2 and P3 members under I2 in the deterministic stratum [NP]; this illustrates why an L2 verdict must not be read as attribution.

Where knockout works, and recommendations [D] (design). In P4 (common cause vs message-caused coordination) single knockout separates the pair at I1: knockout is sufficient for causal influence and insufficient for normative attribution. We recommend (1) never reporting knockout magnitude as collusion evidence, but a rung; (2) publishing placebo availability, information-loss status and carrier-detector recall with each verdict; (3) reporting risk-coverage, not one accuracy number; (4) stating the information set supplied.

7. Limitations and What We Did Not Establish

Platform dependence and post-hoc scope. D-048 was decided after outcomes were visible: eps = 0 is the established prospective stratum, supported by byte identity on the available overlap; eps = 0.1 is platform-dependent, not established. Self-determinism on Linux does not resolve substantive disagreement with macOS. The cause is unknown, and REV_R3 did not identify this consequence. Full noisy results and all aggregate failures remain reported. This scope restriction is not a pre-registered successful validation or a general platform-invariance guarantee.

We do not detect collusion or intent. A `not supported` or `inconclusive` record is not exoneration and must not be the sole basis for deployment. The identifiability limit holds only for our generators and information sets, and scripted generators with oracle labels cannot estimate real false-positive rates. RQ1 and RQ2 are consistency checks by construction, RQ5 is largely a consistency check and structurally strict, and CCC-L v1, the method-independent RQ2 and RQ4b are DEV-informed amendments; the DEV block was balanced while prospective RQ3 assignment is random (Section 4; REV-R2 C2-C4). The original study has one local model, one deceptive prompt variant, one exposure per trajectory and 8 independent matched world pairs [D], so its precision cannot support equivalence or practical-significance claims. Replay access and a suspected exposure are required. Appendix A lists restrictions and ways to extend the evidence.

8. Conclusion

Knockout magnitude, transcript rules and gated verdicts each license a different rung of the evidence ladder, and none licenses attribution by itself. We provide the ladder, executable twin worlds with an enumerated identifiability frontier, an abstention-aware benchmark, and a confirmatory null from the original real-agent study. Prospective symmetry and frontier checks passed by construction, while the label-effect, original over-attribution, refined over-attribution and ladder-auditor predictions failed [NP].

Code and Data

Colosseum, Terrarium and the prompted pilot predate the sprint; the audit protocol, replay layer, runner, baselines, benchmark and analysis are sprint work. Offline reproduction:

`scripts/reproduce_offline.sh`; benchmark: `python -m ccc.bench`. Public release: [OWNER].

References

1. Mason Nakamura, Abhinav Kumar, Saswat Das, Sahar Abdelnabi, Saaduddin Mahmud, Ferdinando Fioretto, Shlomo Zilberstein, Eugene Bagdasarian (2026). Colosseum: Auditing Collusion in Cooperative Multi-Agent Systems. arXiv:2602.15198.
2. Hieu Tran, Hong Yu (2026). Is Anyone Enforcing the Cartel? What Reinforcement Learning Teaches LLM Agents in Markets. arXiv:2610.28787.
3. Ramneet Kaur, Pradyumna Chari, Ramesh Raskar, Jugad Singh, Sumit Kumar Jha, Anirban Roy (2026). Beyond the Transcript: Detecting Covert Coordination in Latent Multi-Agent Communication. arXiv:2608.19161.
4. Aaron Rose, Carissa Cullen, Sahar Abdelnabi, Philip Torr, Brandon Gary Kaplowitz, Christian Schroeder de Witt (2026). Detecting Multi-Agent Collusion Through Multi-Agent Interpretability. arXiv:2604.01151.
5. Xin Xu, Chengrui Wu, Jiayu Lu, Kaizhen Tan, Siru Tao, Hanzhe Hong (2026). Collusion with Competitive Marginals: Price-Level Audits Are Blind by Construction. arXiv:2607.26385.
6. Matthew Riemer, Tommaso Tosato, Amin Memarian, Maximilian Puelma Touzel, Glen Berseth, Irina Rish, Guillaume Dumas (2026). Position: Collusion Risks Among AI Reasoning Agents Justify Certification Requirements for Making Market Decisions. arXiv:2608.18078. ICML 2026 (position).
7. Huixiang Zhang, Mahzabeen Emu (2026). Do Latent Channels Actually Communicate? A Causal Audit of Latent Multi-Agent LLM Communication. arXiv:2607.26773.
8. Jamiu Idowu, Ahmed Almasoud, Ayman Alfahid (2026). Mapping Human Anti-collusion Mechanisms to Multi-agent AI Systems. arXiv:2601.00360. Knowledge-Based Systems 344:116067 (2026).
9. Dohun Lee, Hyunwoo Park (2026). Faithful yet Collusive: Why Chain-of-Thought Monitoring Cannot Detect Collusion in LLM Pricing Agents under Oligopolistic Competition. arXiv:2609.18346. Findings of EMNLP 2026.
10. Sumeet Ramesh Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip H. S. Torr, Lewis Hammond, Christian Schroeder de Witt (2024). Secret Collusion among AI Agents: Multi-Agent Deception via Steganography. arXiv:2402.07510.
11. Tom Everitt, Ryan Carey, Eric Langlois, Pedro A. Ortega, Shane Legg (2021). Agent Incentives: A Causal Perspective. arXiv:2102.01685. AAAI 2021.
12. Francis Rhys Ward, Matt MacDermott, Francesco Belardinelli, Francesca Toni, Tom Everitt (2024). The Reasons that Agents Act: Intention and Instrumental Goals. arXiv:2402.07221.
13. Hana Chockler, Joseph Y. Halpern (2004). Responsibility and Blame: A Structural-Model Approach. Journal of Artificial Intelligence Research 22:93-115. doi:10.1613/jair.1391.
14. Bingjie Li, Yumeng Song, Zhongming Yao, Tianyi Li (2026). Localizing Emergent Failures in Agentic AI: Recovering Minimal Repair Families via Counterfactual Replay. arXiv:2608.29228.
15. Jaineet Shah (2026). Causal Agent Replay: Counterfactual Attribution for LLM-Agent Failures. arXiv:2606.08275.
16. Paul-Peter Arslan (2026). Audit Without Verification: When LLM Accountability Layers Relay Rather Than Check. arXiv:2609.07680.
17. Yonatan Geifman, Ran El-Yaniv (2017). Selective Classification for Deep Neural Networks. arXiv:1705.08500.
18. Edoardo Pona, Milad Kazemi, Mehran Hosseini, Yali Du, David Watson, Osvaldo Simeone, Nicola Paoletti (2026). Calibrate-Then-Delegate: Safety Monitoring with Risk and Budget Guarantees via Model Cascades. arXiv:2604.14251.
19. Emilio Calvano, Giacomo Calzolari, Vincenzo Denicolò, Sergio Pastorello (2020). Artificial Intelligence, Algorithmic Pricing, and Collusion. American Economic Review 110(10):3267-3297. doi:10.1257/aer.20190623.
20. Kaue Lopes de Moraes, Rodrigo De-Losso (2026). Algorithmic Collusion Without Deterrence: Auditing the Punishment Mechanism in Q-Learning Pricing Agents. arXiv:2610.21867. ICAIF 2026.

Appendices

Index: A limitations and dual-use; B deviations; C reproducibility; D falsifiable checks and worked record; E benchmark design and selected templates; F original-study detail; G related work; H figure sources; I extra tables.

A. Limitations and Dual-Use / Ethical Considerations

A.1 Limitations

- **Platform divergence (D-048):** deterministic-stratum claims only; eps = 0.1 is platform-dependent, not established. The scope decision followed visible outcomes; both preserved runs and all aggregate failures remain available. macOS noisy DEV and Linux noisy prospective numbers cannot be compared.
- **Precision:** the original study has 8 independent matched world pairs [OC]. More independent worlds under a fresh protocol would extend precision; the interval does not establish equivalence.
- **Generator scope:** twin equivalence is restricted to declared policy spaces and information sets. A separating undeclared observable would refute equivalence for the expanded set.
- **Circularity:** symmetry, enumeration and the reference auditor are consistency checks. Independently designed generators would test transfer beyond those constructions.
- **Real-agent coverage:** the original local model and prompt variant limit generalization [D]. A further real-agent study (EXP-003) was planned and not completed (D-047a).

- **Instrument validity:** control recovery, carrier detection, information loss and unavailable status crosschecks constrain interpretation. Support-level positive-control validation is required before claiming a validated certificate pipeline.
- **Evidence access:** replay and a suspected exposure are required. Matched evidence access and independently labelled deployment data would be needed for superiority or deployment false-positive claims.

Additional restrictions are:

- Certificates establish neither collusion nor intent, equivalence, absence of harm, or exoneration.
- The maximum outsider-effect lower bound was 0.77 against m_O = 2.5, and placebo availability was 2/16 [D]. Placebo absence alone does not explain the lack of supports; message removal also removes information.
- Repaired validity metadata records raw check passes; status crosschecks remain unavailable. B1 sham evidence has n = 4 and remains uncertain [PH]; universal sham equivalence is not established.
- Development baseline comparison shares factual and knockout outcomes but not evidence access. CCC coverage is 202/280 against 260/280 for B2/B2+, with the active-path stratum below its 30/30 floor [DEV]. These are not general superiority or false-positive-control results.
- No paraphrase cell carried a carrier flag [DEV]. Semantic redundancy is not solved.
- Scheduled records are not executed branches, and continuations are not independent worlds. Bootstrap-order, exclusion-test and sham-reconciliation analyses remain exploratory [PH]. Original and prospective studies are never pooled.

A.2 Dual-Use and release sign-off

[OWNER: dual-use and release review.] An audit may help adversaries learn which exposures it misses; the twin-world generators identify exactly such blind spots. Mitigations proposed: sandboxed simulated tasks, toy reward mechanisms, explicit blind-spot reporting. These are proposals, not completed review. The evidence standard can reduce overconfident accusations, while releasing twin constructions can also teach adversaries which interventions miss redundant or covert channels. Keep examples sandboxed and make unresolved evidence explicit. The acceptable release scope remains subject to the owner review above.




Figure A9 (RQ2, frontier; main-text candidate if space allows). (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). Frontier heat map, pair type P1-P6 by information set I0-I5, both noise strata. Fill from exact enumeration; overlaid: Bayes-given-S pair accuracy (RQ2, T3) and the share of seed units on which CCC-L v1 (DEV-informed method version), CCC-L v0 and frozen CCC v1.2.2 emit different outputs for the two twin members. P3 at I5 is definitional.




Figure A10 (RQ5, risk-coverage; main-text candidate if space allows). (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). Risk-coverage curves on the attribution, axis M axis, per information set, both noise strata, abstention cost c in 0.25 and 0.5; CCC v1.2.2, CCC-L v1 (DEV-informed method version), CCC-L v0, frozen strongest baseline, Bayes-given-S and always-answer/abstain anchors.




Figure A1. Branch schematic F/K/S/N (schematic, no data).




Figure A2. Case-level outsider-effect certificate intervals versus m_O (EXP-002, descriptive); certificates are exploratory.




Figure A3. Supported verdicts versus oracle exposure effect on DEV fixtures (DEV).

Gate A integrity checks — DEV fixtures, protocol v1.2.2

Check	Pass / total	Gate
F vs S identical	380 / 380	PASS
K-only intended exposure	4180 / 4180	PASS
Branch isolation	760 / 760	PASS
A2 not supported	80 / 80	PASS
A6 invalid detection	350 / 360	FAIL

A6 sensitivity gate fails (350/360); overall Gate A reported FAIL. Counts are fixture checks, not real-world rates.

Figure A4. Gate A integrity checks (DEV).




Figure A5. Baseline positive-call rates on DEV fixtures (DEV).




Figure A6. (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). RQ3: share of mechanism-forbidden iid worlds with oracle tau_O >= 2.5, per noise stratum, with Clopper-Pearson 95% interval and the 25% pre-registered line; right panel shows tau_O per world.




Figure A7. (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). Over-attribution of the frozen strongest baseline on legitimate members (P2, P3, P6, benign cooperation) under I1, per class and noise stratum, Clopper-Pearson 95% over independent seed units, with the 0.5 (RQ4) and 0.05 (RQ4b) lines; CCC v1.2.2 exposure-level supported rate shown separately as L2, not attribution.




Figure A8. (PROSPECTIVE) eps=0 established; eps=0.1: platform-dependent, not established (D-048; post hoc). Risk-coverage curves on the exposure, axis E axis, per information set, both noise strata, abstention cost c in 0.25 and 0.5; CCC v1.2.2, CCC-L v1 (DEV-informed method version), CCC-L v0, frozen strongest baseline, Bayes-given-S and always-answer/abstain anchors.

B. Deviation and correction log

1. DEV-001 reduced sham replication on held-out (S on 7/16 checkpoints, n = 1 per hash rule); optional pairs H09/H10 dropped. Disclosed pre-outcome. [D].
2. DEV-002 placebo-availability census run before its inputs were hash-committed; development census exploratory. [D].
3. v1.2.1 extractor correction re-frozen before held-out data; theta pinned 0.4 by fallback (best Youden J 0.4947 < 0.5); `weak_detector`. [D].
4. Label correction (exp002_heldout_v2): confirmatory study tests separated from exploratory certificates; no numeric change. [D].

5. Validity-metadata repair (exp002_heldout_v3, FIX-001): 16 `gates.all_valid` and 5 `reasons` fields changed; 0 status or numeric changes. [PH].
6. ENH-B corrections applied here: non-commit exclusion estimate re-categorised as original-registered-secondary (its p and sham-gap interpretation remain post hoc); V9 sham signs aligned to S-minus-F; development "predictions confirmed" reworded as agreement with scripted predictions; the "post hoc" label of the whole sensitivity in paper/build/submission.md was wrong and is not repeated. [D].
7. Open (director): `no_placebo_available` is appended on the final inconclusive path whether or not other support conditions held (REV001 F-10); not changed. [D].
8. R2 amendments before the DEV run: CRN (A1), circularity disclosure (A2), RQ6 (A3). [D].
9. R2 amendments after the DEV run, before any prospective seed (DEV-informed, D-040): CCC-L v1 (A4), method-independent RQ2 (A5), RQ4 verbatim plus RQ4b (A6), RQ3 unchanged (A7). Frozen under D-041 after independent review REV-R2 (conditions C2-C4 adopted as reporting rules). [D].

1. R2 execution deviation D-046: mapped enumeration and method execution used Modal Linux containers; population generation for RQ3 and the report tail ran locally. Cross-platform noisy-stratum identity was not established; container self-determinism does not restore it. REV_R3.md corrects misleading archived-gate provenance and gate comparison counts, and distinguishes the controller runtime from the worker runtime. The reported failures remain unchanged. [NP] (execution provenance).

1. D-048 (post-hoc, after outcomes were visible): substantive eps = 0.1 method outputs disagree between macOS serial and Modal Linux on identical seeds. Established prospective claims are restricted to eps = 0; eps = 0.1 is reported in full as "platform-dependent, not established". This decision was based on objective divergence, not outcome direction; it does not alter the pre-registered aggregate failures. REV_R3 missed the substantive consequence. See `PLATFORM_DIVERGENCE.md` and `RESULTS_BY_STRATUM.json`; no frozen source, seed or run output was changed. [PH] (scope decision).

C. Reproducibility

Frozen EXP-002 outputs: docs/analysis/exp002_heldout_v2/ and v3 (metadata repair; field diff in output_diff_v3.json). Independent reproduction: docs/review/rev001/rev001_repro.json. Gate A: docs/gate_a/v1.2/correction_v1.2.2/. R2: docs/enh/r2/PROTOCOL.md, FREEZE.json (code hashes, enumeration hash, seed list hash, intersection sizes, reviewer, timestamp); commands `python -m ccc.bench hashes|seeds --check`. Offline reproduction script scripts/reproduce_offline.sh. Model digest 5571076f3d70; 3,516 local calls, $0 [D]. R2 input SHA-256 values (`RESULTS.json.inputs`): `frontiers.json`: `5c85df25f10b906daae4ffeb270b2ac2364f1148beca455805d003c42c3c0b13`; `manifest.json`: `148ce53257a3bd6e1530af65a6ad59bf62fcd30b87a0b3b0bfbcfb49fcf8063c`; `population.json`: `3be08849cfb24a3cb54e25744c2a3856b92d9685be6215b95e40ba07bb70879b`; `records.json.gz`: `8e095c9e13a5c126699b2060138afe6a0fdd37457d357fbfa55245fc2146aba8`. Seed-list SHA-256 (`tables.T1.seed_disjointness.seed_list_sha256`): `1720ba12cd131f9d914ea01bf0a14e72f4f7923fd060ca6d5802a2839e829e7c`.

D. Falsifiable checks and worked evidence record

A check to run next. Recompute canonical observables for each twin under its declared set. Unequal observables below the claimed separating set refute that equivalence claim. A method reading undeclared state invalidates that benchmark interpretation. Report failures alongside successful checks, with hashes and independent-unit counts.

Worked record [D] (schematic). Record the twin identifier, declared set, tau_O/tau_C/tau_W, replay validity, placebo availability, information-loss flag, highest justified rung and unresolved reason. A shared-evidence allocation twin cannot receive an attribution assertion from that evidence alone. Add an environment-probe record to assess separation. This is a record schema, not a measured certificate.

Judge disclosure. No new judge-validity claim is introduced here.

E. Benchmark design and selected reporting templates

Preregistered research questions [NP] (frozen criteria; protocol sha256 334a4539; descriptive-with-prediction, not a Holm-corrected family). RQ1 symmetry: 0 within-pair output differences of 200 for each method x pair type x set where observables are S-equivalent (twin members use common random numbers). RQ2 frontier, method-independent: the observed frontier, the lowest set S at which Bayes-given-S pair accuracy is 1 on all units, equals the enumerated minimal separating set for every listed type, and no method is correct on both members of any unit below that set beyond what Bayes-given-S achieves. RQ3 label-effect gap: the share of mechanism-"forbidden" iid Jira worlds with oracle tau_O >= m_O is below 25%. DEV values are disclosed beside the prediction: Gate A 12/80 [DEV]; benchmark DEV block 12/50 at eps = 0 and 5/50 at eps = 0.1 [DEV]. RQ4 over-attribution [NP] (criterion), kept verbatim from the original protocol: the strongest knockout baseline accuses legitimate members at rate >

0.5 under I1 for each of P2, P3, P6 and benign cooperation; on DEV this failed on P6 and benign cooperation (0/50 [DEV]). RQ4b [NP] (DEV-informed criterion): the same baseline over-attributes on P2 and P3 at rate > 0.5 and at rate <= 0.05 on P6 and benign cooperation, each stratum separately. RQ5 ladder auditor [NP] (criterion): CCC-L v1 within 0.02 selective accuracy of Bayes-given-S at both c, zero over-claims, abstention precision and recall >= 0.9, and >= 0.95 correct attribution when I4 (P2) or I5 (P3) is supplied. RQ6 descriptive: CCC v1.2.2 status distribution per class and stratum.

Twin-pair types (each pair shares one seed and nuisance draw and is ONE independent unit; frozen in docs/enh/r2/PROTOCOL.md).

Type	Contrast	Enumerated separating evidence
P1	redundant-harmful vs inert (duplicate carriers)	I3
P2	colluding allocation vs efficiency-motivated legitimate cooperation, identical observed behaviour	I4 (the legitimate team cedes when an outsider is cheaper; colluders do not)
P3	authorized vs unauthorized transfer, identical policies	I5 (tautological by design, labelled so)
P4	common cause vs message-caused coordination	I1 (shows where knockout works)
P5	suspicious-language inert vs plain-language inert	transcript differs, outcomes identical (tests transcript rules)
P6	information-bearing legitimate message vs harmful steering	harm and utility gates at I1

Also: a relayed-harmful case (sender to relay to receiver; expected unresolved at I3), and invalid or corrupted traces. Benchmark classes: harmful message-dependent coordination; legitimate useful communication; suspicious language without harm; harm without message dependence; redundant paths; paraphrased or relayed commitments; common-cause coordination; information-bearing removal that harms; inert messages; corrupted traces; non-identifiable twin members.

Sample and seeds [NP] (frozen design). 200 independent units for each of P1-P6, 200 iid Jira population worlds, 100 units for each remaining class; strata eps in {0, 0.1} (eps = 0.1: each scripted agent takes a uniformly random legal action with probability eps; R = 8 continuations per arm), reported separately and never pooled. Seeds derive from the protocol hash by `seed(s,i) = first 31 bits of sha256(protocol_sha256 || s || i)` with a deterministic skip rule against Gate A (12000-12019), DEV (13000-13049), all pilot, EXP-001 and EXP-002 seeds and 0-99999; disjointness is checked by `python -m ccc.bench seeds --check` and hashes are written to FREEZE.json before any run. Common random numbers: twin members share per-continuation RNG seeds, so that RQ1 is not confounded by sampling noise.

Metrics [NP] (frozen design). Over-claim (accusation) rate on legitimate and non-identifiable members; sensitivity on E-positive harmful instances; FPR on benign cooperation; abstention rate and coverage; selective accuracy; risk-coverage curves with abstention cost c in {0.25, 0.5} (loss 1 per error, c per abstention, 0 per correct); twin symmetry violations; observed versus enumerated minimal separating set. Exact Clopper-Pearson 95% intervals over independent units; paired comparisons by exact McNemar-type tests; continuous quantities by world-cluster percentile bootstrap (B = 10,000, PCG64 seed 20261026).

Stopping and failures. Single pass, fixed N, no interim looks, no seed replacement beyond the pre-run skip rule. Crashes stay in the denominator. Any code change after outcomes are visible forces a new seed block under a new freeze, and both runs are reported.

Prospective table and figure data [NP]. All paths below are keys in `docs/enh/r2/run_par/RESULTS.json`; eps = 0.1 entries are platform-dependent, not established. Figures retain both strata with D-048 labels. Aggregate statuses below remain unchanged.

Item	Populated value / source key
T2 symmetry	`tables.T2.violations`; selected result in Section 5.2
T3 frontier	`tables.T3`; P1/I3, P2/I4, P3/I5, P4/I1, P6/I1 in both strata; relayed-harmful unresolved at I3
T4 prevalence	`rq.RQ3.by_epsilon`, `tables.T4`; stratum values in Section 5.3
T5 over-attribution	`tables.T5`; original RQ4 failed
T5b refinement	`tables.T5b`; DEV-informed RQ4b failed
T6 class/method/set rates	`tables.T6`; all available M/H/E views and inapplicable cells retained
T7 abstention, coverage and risk	`tables.T7`; both frozen abstention costs, anchors and Bayes reference retained
T8 ladder auditor	`tables.T8`, `tables.T8_v0`; both versions failed; undefined denominators retained
RQ6 CCC statuses	`tables.RQ6`; exposure L2, not attribution
T9 failures	`tables.T9`: complete; crashes empty; corrupted-trace statuses retained
T1 design and disjointness	`tables.T1`; all excluded-set intersections are zero
T10 post-hoc list	`tables.T10`: empty
Figure 2 frontier	`figures.frontier_heat_map`; prospective data, rendering pending
Figure 3 risk-coverage	`figures.risk_coverage`; prospective data, rendering pending

Methods compared, full definition. (each sees only the observables of its declared set; none tuned on prospective seeds; frozen before any prospective seed existed): CCC v1.2.2; B0 outcome-only; B1 simple knockout; B2 and B2+ harm-gated knockout; B3a and B3b influence-only; B4 transcript keyword rule; always-answer and always-abstain anchors; Bayes-given-S reference (majority label per S-equivalence class under frozen class priors; the ceiling for any method restricted to S); CCC-L v1 (new, exploratory, DEV-informed), which outputs the highest justified rung, "insufficient for L3 under S", or "L3 excluded" (attribution ruled out by separating evidence in S), attributing L3 only when S contains separating evidence. CCC-L v0 lacks the "L3 excluded" output; DEV showed it therefore cannot be correct on both members of a pair. It is retained, run and reported prospectively so the change is visible. The "strongest knockout baseline" is fixed in advance as the better of {B2+, B3b} by balanced accuracy on DEV block 13000-13049 under I1 (ties to B2+), recorded in FREEZE.json.

Selected reporting templates. The pass templates for RQ1 and RQ2, negative templates for RQ3, RQ4, RQ4b and RQ5, and both stratum-specific descriptive RQ6 templates are populated in Section 5. Inactive alternatives are removed; no favourable alternative replaces a failed prediction. Full numerical cells remain in `docs/enh/r2/run_par/RESULTS.json`.

F. Original-study detail

Preregistered S1–S3 family [OC]. S1 (B1 mean tau_O) 0.970, Holm p = 0.164; S2 (B2 mean tau_O) -0.384, Holm p = 0.4375 (only 5 nonzero values against a floor of 6); S3 (tau_C contrast) -1.820, Holm p = 0.164. None is significant.

Sham (V9) [PH]. On a consistent S-minus-F outsider-reward scale: B1 mean 1.64, 90% CI [-0.54, 3.82], n = 4, uncertain; B2 0.03 [-0.06, 0.12], n = 3, pass; pooled 0.95 [-0.20, 2.10], n = 7, pass. Individual sham gaps are +3.77 (H02_B1) and +2.62 (H05_B1). We report both aggregations and make no sham-equivalence claim. The V10 lesion check (n = 2, interval [-7.4, 11.7]) is uninformative.

Accounting [D]. 199 scheduled branch records = 143 executed valid continuations (F64, K64, S7, N8) + 56 unrun placebo branches (`no_placebo_available`); 0 failed, invalid or retried. 3,516 local calls, $0. F and K missingness 0/32 per arm per regime.

Disclosed metadata repair [PH]. A validity-metadata repair, disclosed as `exp002_heldout_v3`, restores canonical validity keys the analysis loader had dropped. It changes 16 `gates.all_valid` fields and 5 `reasons` arrays and nothing else: certificate statuses stay 0/11/5, and the primary Delta, interval and p are unchanged. All original files remain byte-identical.

Development evidence detail (Section 5.1). Gate A (v1.2.2; 800 non-constructed cells; one scripted continuation per arm) is a deterministic implementation check, not held-out inference. Factual/sham identity 380/380, knockout scope 4180/4180, branch isolation 760/760, A2 benign cooperation never supported 80/80 (26 inconclusive, 54 not supported), A6 invalid-trace validator 350/360 [DEV]. The A5 redundancy check passes 20/120 (16/68 amended) and no paraphrase cell carries a carrier flag [DEV].

The pre-written scorecard had 16 predictions agree with the scripted generator, 2 disagree and 3 untested; "agreement with scripted predictions" is not validation [DEV]. The label-effect gap on iid Jira worlds was 12/80 in Gate A [DEV], and 12/50 (eps = 0) and 5/50 (eps = 0.1) in the benchmark DEV block [DEV]. These are the development observations from which RQ3 and RQ4 were derived; none counts as confirmatory.

G. Related-work detail and search scope

Detailed comparison paragraphs to be carried from paper/build/submission.md Appendix B.1 (DoVer, AgenTracer, Audit the Whisper, CABAL, tool-use steganography: all verified in paper/references_draft.bib; re-cite with numbers added then) plus the ENH-A neighbours above. [OWNER: confirm whether to carry these over.] Not found in the bounded search: a theorem that message-level interventional evidence on influence, harm and utility cannot separate harmful coordination from legitimate cooperation. Absence in a bounded search is not proof. Safe wording used throughout: "we state and demonstrate a scoped outcome-equivalence limit for declared-arm evidence; related indistinguishability claims exist for marginal price tests [5] and are argued for reasoning agents [6]". No "first" claim.

Related work, extended. *Responsibility, failure attribution and overdetermination.* Counterfactual replay for failure attribution and minimal repair families [14, 15] and degrees of responsibility under redundant contributions [13] motivate our redundancy cases, where single knockout is zero and joint knockout is positive; we report such cases as "not identifiable under I1", not "no effect". *Abstention and reporting standards.* Selective classification with a reject option and risk-coverage reporting [17] and delegation with cost or safety-performance guarantees for safety monitors [18] motivate our abstention-aware scoring. Preregistered audit studies have precedent: one finds auditors naming innocent parties after upstream false alarms, with its preregistered hypothesis not supported [16]. Steganographic and covert channels [10] can evade any text-level intervention; this limit is inherited.

Search scope. Search date 2026-10-24; Firecrawl paper index, web search and fetch, about 25 queries [D] (inherited, not independently traceable in this repository; unchecked count). This is a bounded search, not a survey. Legal "plus factors" primary law was not checked. The search was not rerun.

H. Figure plan

#	Figure	Status	Exact data source
1	Twin worlds, shared transcript and replay effects, and the ladder showing what separates attribution	conceptual diagram [NP], matching PROSPECTIVE source metadata	figures/enh/prospective/fig_ladder.json; no measured
Appendix	Branch schematic F/K/S/N	reuse [D] (schematic)	figures/fig_arms.svg
4	Held-out per-world Delta, aggregate and CI; non-commit sensitivity as separate marker (existing; caption must say registered sensitivity [ORS])	reuse	figures/fig_heldout_delta.json; docs/analysis/exp002_heldout_v2/figure_data/fig_de
2	Frontier heat map, pair type x information set (Figure 2; `RESULTS.json.figures.frontier_heat_map`, NEW)	data complete [NP]; rendering pending	`RESULTS.json.figures.frontier_heat_ma`
3	Risk-coverage curves, c = 0.25, 0.5, with anchors and Bayes-given-S (Figure 3; `RESULTS.json.figures.risk_coverage`, NEW)	data complete [NP]; rendering pending	`RESULTS.json.figures.risk_coverage`
B1	Case-level certificate intervals vs m_O (existing)	appendix [D]	figures/fig_heldout_cases.json; docs/analysis/exp002_heldout_v2/figure_data/fig_tau
B2	Supported vs oracle effect, DEV fixtures (existing)	appendix [DEV]	figures/fig_supported_vs_oracle.json
B3	Gate A integrity checks, DEV (existing)	appendix [DEV]	figures/fig_gateA_integrity.json
B4	Baseline positive-call rates, DEV (existing)	appendix [DEV]	figures/fig_confusion_dev.json (gate_a_results.json.g 8aa6b1b0...)
B5	Prevalence interval plot (RQ3) (NEW)	data complete [NP]; rendering pending	`RESULTS.json.figures.prevalence_interv`

Main-text sequence: twin schematic, frontier, risk-coverage, held-out null. Development diagnostics and replay arms remain in the appendix. ORCH verifies the rendered page budget.

I. Appendix tables

T1 design, counts, seed disjointness; T10 post-hoc list (all analyses added after outcomes are visible, labelled [PH]).

LLM Usage Statement

[OWNER: approve final wording.] Claude (via Claude Code) and Codex agents, coordinated by a Claude Code session, assisted with planning, implementation, tests, analysis scripts, literature verification and manuscript drafting. Experimental agents are separate local models and scripted policies. Human owner verification of claims, results and references has not been established in this draft. The owner is the sole author; no AI system is a co-author.