

Final Project

Steps to perform Music Data analysis:

- 1) Generation of data using python scripts.
- 2) Starting of all necessary daemons.
- 3) Populating look up into HBase.
- 4) Perform Data Enrichment Filter.
- 5) Perform Data Formatting.
- 6) Perform Data Enrichment
- 7) Perform Data Analysis.

1).Generation of data using python scripts:

We have generated data simulation using python scripts. Those scripts are

generate_web_data.py

generate_mob_data.py

Data coming from web applications reside in **/home/acadgild/examples/music/data/web** and has xml format.

Whereas data coming from mobile applications reside in **/home/acadgild/examples/music /data/mob** and has text format.

We have created master file “**music_project_master.sh**” which does data simulation through python scripts. Please find below steps which is part of **music_project_master.sh**:

```
# Create data
echo "Preparing to execute python scripts to generate data..."

rm -r /home/acadgild/examples/music/data/web

rm -r /home/acadgild/examples/music/data/mob

mkdir -p /home/acadgild/examples/music/data/web

mkdir -p /home/acadgild/examples/music/data/mob

python /home/acadgild/examples/music/generate_web_data.py
python /home/acadgild/examples/music/generate_mob_data.py

echo "Data Generated Successfully !"
```

It will remove **web** and **mob** directories if they present and then it will create **web** and **mob** directories. After creating directories, it will execute the **python** scripts.

```
[acadgild@localhost music]$ ./music_project_master.sh
Preparing to execute python scripts to generate data...
rm: cannot remove '/home/acadgild/examples/music/data/web': No such file or directory
rm: cannot remove '/home/acadgild/examples/music/data/mob': No such file or directory
Data Generated Successfully !
Starting the daemons
```

2). Starting all necessary daemons:

To start all required daemons, we have created a unix shell script “**start-daemons.sh**”.

Below is the code present in the script:

```
#!/bin/bash

rm -r /home/acadgild/examples/music/logs
mkdir -p /home/acadgild/examples/music/logs

if [ -f "/home/acadgild/examples/music/logs/current-batch.txt" ]
then
    echo "Batch File Found!"
else
    echo -n "1" > "/home/acadgild/examples/music/logs/current-batch.txt"
fi

chmod 775 /home/acadgild/examples/music/logs/current-batch.txt
echo "After chmod"
batchid=`cat /home/acadgild/examples/music/logs/current-batch.txt`
echo "After batchid-->> "$batchid
LOGFILE=/home/acadgild/examples/music/logs/log_batch_$batchid

echo "Starting daemons" >> $LOGFILE

start-all.sh
start-hbase.sh
mr-jobhistory-daemon.sh start historyserver

cat /home/acadgild/examples/music/logs/current-batch.txt
```

Here it will remove the **logs** directory if it is present and it will create **logs** directory under **home/acadgild/examples/music/**.

Later, it will check for **current-batch.txt** file inside **logs** directory, if it is present then it will print “**Batch File Found!**”, it will create it with content in it is “**1**”.

After this, **log_batch_1** file will be created under **logs** directory.



| | | |
|-------------------|----------|---------------------|
| examples | 1 item | folder |
| music | 17 items | folder |
| data | 2 items | folder |
| logs | 2 items | folder |
| current-batch.txt | 1 byte | plain text document |
| log_batch_1 | 17 bytes | plain text document |

Then it will start all hadoop daemons, hbase daemons, jobHistoryserver.

We have executed the script **start-deamons.sh** which was there in **music_project_master.sh**. The below screenshot shows the daemons started.

```

[acadm@localhost music]$ ./music_project_master.sh
Preparing to execute python scripts to generate data...
Data Generated Successfully !
Starting the daemons....
After chmod
After batchid--> 1
This script is Deprecated. Instead use start-dfs.sh and start-yarn.sh
18/11/25 18:19:34 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Starting namenodes on [localhost]
localhost: starting namenode, logging to /home/acadm/install/hadoop/hadoop-2.6.5/logs/hadoop-acadm-namenode-localhost.localdomain.out
localhost: starting datanode, logging to /home/acadm/install/hadoop/hadoop-2.6.5/logs/hadoop-acadm-datanode-localhost.localdomain.out
Starting secondary namenodes [0.0.0.0]
0.0.0.0: starting secondarynamenode, logging to /home/acadm/install/hadoop/hadoop-2.6.5/logs/hadoop-acadm-secondarynamenode-localhost.localdomain.out
18/11/25 18:21:06 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
starting yarn daemons
starting resourcemanager, logging to /home/acadm/install/hadoop/hadoop-2.6.5/logs/yarn-acadm-resourcemanager-localhost.localdomain.out
localhost: starting nodemanager, logging to /home/acadm/install/hadoop/hadoop-2.6.5/logs/yarn-acadm-nodemanager-localhost.localdomain.out
localhost: starting zookeeper, logging to /home/acadm/install/hbase/hbase-1.2.6/logs/hbase-acadm-zookeeper-localhost.localdomain.out
starting master, logging to /home/acadm/install/hbase/hbase-1.2.6/logs/hbase-acadm-master-localhost.localdomain.out
starting regionserver, logging to /home/acadm/install/hbase/hbase-1.2.6/logs/hbase-acadm-1-regionserver-localhost.localdomain.out
starting historyserver, logging to /home/acadm/install/hadoop/hadoop-2.6.5/logs/mapred-acadm-historyserver-localhost.localdomain.out
19568 ResourceManager
9344 SecondaryNameNode
9666 NodeManager
10390 -- process information unavailable
10487 Jps
10216 HQuorumPeer
9179 DataNode
7613 RunJar
10461 JobHistoryServer
9085 NameNode
All hadoop daemons started !

```

3) Populate lookup tables into HBase:

By using the “**populate-lookup.sh**” script, we will create below lookup tables in HBase.

These tables we are using for **Data formatting, Data enrichment and Data Analysis** stage.

| Sr # | Table name | Description | Related file |
|------|------------------|---|------------------|
| 1 | Station_geo_map | Contains mapping of a geo_cd with station_id | stn-geocd.txt |
| 2 | Subscribed_users | contains user_id,subscription_start_date and subscription_end_date . Contains details only for subscribed users user-subscn.txt | user-subscn.txt |
| 3 | Song_artist_map | Contains mapping of song_id with artist_id Along with royalty associated with each play of the song | song-artist.txt |
| 4 | User_artists | Contains an array of artist_id(s) followed by user_id | User_artists.txt |

populate-lookup.sh script will create the above tables in **Hbase** and populate the data into the tables using data files which were created using **python** scripts.

Below is the code present in **populate-lookup.sh**:

```
#!/bin/bash

batchid=`cat /home/acadgild/examples/music/logs/current-batch.txt`

LOGFILE=/home/acadgild/examples/music/logs/log_batch_${batchid}

echo "Creating LookUp Tables" >> $LOGFILE

echo "disable 'station-geo-map'" | hbase shell
echo "drop 'station-geo-map'" | hbase shell
echo "disable 'subscribed-users'" | hbase shell
echo "drop 'subscribed-users'" | hbase shell
echo "disable 'song-artist-map'" | hbase shell
echo "drop 'song-artist-map'" | hbase shell

echo "create 'station-geo-map', 'geo'" | hbase shell
echo "create 'subscribed-users', 'subscn'" | hbase shell
echo "create 'song-artist-map', 'artist'" | hbase shell

echo "Populating LookUp Tables" >> $LOGFILE

file="/home/acadgild/examples/music/lookupfiles/stn-geocd.txt"
```

```

while IFS= read -r line
do
    stnid=`echo $line | cut -d',' -f1`
    geocd=`echo $line | cut -d',' -f2`
    echo "put 'station-geo-map', '$stnid', 'geo:geo_cd', '$geocd'" | hbase
    shell
done <"$file"

```

```

file="/home/acadgild/examples/music/lookupfiles/song-artist.txt"
while IFS= read -r line
do
    songid=`echo $line | cut -d',' -f1`
    artistid=`echo $line | cut -d',' -f2`
    echo "put 'song-artist-map', '$songid', 'artist:artistid',
'$artistid'" | hbase shell
done <"$file"

```

```

file="/home/acadgild/examples/music/lookupfiles/user-subscn.txt"
while IFS= read -r line
do
    userid=`echo $line | cut -d',' -f1`
    startdt=`echo $line | cut -d',' -f2`
    enddt=`echo $line | cut -d',' -f3`
    echo "put 'subscribed-users', '$userid', 'subscn:startdt', '$startdt'"
| hbase shell
    echo "put 'subscribed-users', '$userid', 'subscn:enddt', '$enddt'" |
hbase shell
done <"$file"

```

On executing the above script using **music_project_master.sh**, tables will be created in HBase and data will be populated into it.

First we will **disable** the tables and then **drop** them if they present.

```
[acadgild@localhost music]$ ./music_project_master.sh
Preparing to execute python scripts to generate data...
Data Generated Successfully !
Starting the daemons....
12514 Jps
5095 DataNode
5257 SecondaryNameNode
6377 JobHistoryServer
5001 NameNode
5484 ResourceManager
5583 NodeManager
11985 Main
6131 HQuorumPeer
7380 Main
6196 HMaster
7576 RunJar
6297 HRegionServer
All hadoop daemons started !
Upload the look up tables now in Hbase...
2018-11-25 22:01:21,718 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

disable 'station-geo-map'
0 row(s) in 6.0110 seconds

2018-11-25 22:02:19,615 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

drop 'station-geo-map'
0 row(s) in 5.0480 seconds

2018-11-25 22:03:16,646 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

disable 'subscribed-users'
0 row(s) in 5.7790 seconds

2018-11-25 22:04:14,135 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

drop 'subscribed-users'
0 row(s) in 3.9400 seconds

2018-11-25 22:05:08,393 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

disable 'song-artist-map'
0 row(s) in 5.0760 seconds

2018-11-25 22:06:01,334 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

drop 'song-artist-map'
0 row(s) in 4.2220 seconds

2018-11-25 22:06:55,326 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
```


Now we have created the HBase tables: **song-artist-map**, **station-geo-map** and **subscribed-users** successfully.

```
create 'station-geo-map', 'geo'
0 row(s) in 4.9870 seconds

Hbase::Table - station-geo-map
2018-11-25 22:07:51,435 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

create 'subscribed-users', 'subscn'
0 row(s) in 4.1690 seconds

Hbase::Table - subscribed-users
2018-11-25 22:08:46,537 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

create 'song-artist-map', 'artist'
0 row(s) in 3.8860 seconds
```

We are populating values into these Hbase tables as shown below:

```
put 'station-geo-map', 'ST414', 'geo:geo_cd', 'E'
0 row(s) in 3.8320 seconds

2018-11-25 22:23:10,832 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

put 'song-artist-map', 'S200', 'artist:artistid', 'A300'
0 row(s) in 3.7040 seconds

2018-11-25 22:24:08,925 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

put 'song-artist-map', 'S201', 'artist:artistid', 'A301'
0 row(s) in 3.2920 seconds

2018-11-25 22:25:10,175 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
```

```

put 'song-artist-map', 'S209', 'artist:artistid', 'A305'
0 row(s) in 4.0930 seconds

2018-11-25 22:32:36,734 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

put 'subscribed-users', 'U100', 'subscn:startdt', '1465230523'
0 row(s) in 3.0470 seconds

2018-11-25 22:33:32,170 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

put 'subscribed-users', 'U100', 'subscn:enddt', '1465130523'
0 row(s) in 3.1590 seconds

put 'subscribed-users', 'U114', 'subscn:startdt', '1465230523'
0 row(s) in 3.0850 seconds

2018-11-25 22:58:53,236 WARN [main] util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java
classes where applicable
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 1.2.6, rUnknown, Mon May 29 02:25:32 CDT 2017

put 'subscribed-users', 'U114', 'subscn:enddt', '1468130523'
0 row(s) in 3.7300 seconds

Done with data population in look up tables !
Lets do some data formatting now....
data formatting complete !
Creating hive tables on top of hbase tables for data enrichment and filtering...
Hive table with Hbase Mapping Complete !
Let us do data enrichment as per the requirement...
Data Enrichment Complete
Lets run some use cases now...
USE CASES COMPLETE !!
You have new mail in /var/spool/mail/acadgild
[acadgild@localhost music]$

```

After successful execution of **populate-lookup.sh** script, we can check the created tables in Hbase shell as shown below:

```

hbase(main):003:0> list
TABLE
song-artist-map
station-geo-map
subscribed-users
3 row(s) in 0.0760 seconds

=> ["song-artist-map", "station-geo-map", "subscribed-users"]
hbase(main):004:0>

```

By using **scan** command in Hbase shell we can check data present in created tables.


```
hbase(main):004:0> scan 'song-artist-map'
ROW COLUMN+CELL
S200 column=artist:artistid, timestamp=1543164807417, value=A300
S201 column=artist:artistid, timestamp=1543164866620, value=A301
S202 column=artist:artistid, timestamp=1543164926501, value=A302
S203 column=artist:artistid, timestamp=1543164980111, value=A303
S204 column=artist:artistid, timestamp=1543165033053, value=A304
S205 column=artist:artistid, timestamp=1543165089853, value=A301
S206 column=artist:artistid, timestamp=1543165144395, value=A302
S207 column=artist:artistid, timestamp=1543165199454, value=A303
S208 column=artist:artistid, timestamp=1543165260920, value=A304
S209 column=artist:artistid, timestamp=1543165315755, value=A305
10 row(s) in 0.4070 seconds
```

```
hbase(main):005:0> scan 'station-geo-map'
ROW COLUMN+CELL
ST400 column=geo:geo_cd, timestamp=1543163994349, value=A
ST401 column=geo:geo_cd, timestamp=1543164045677, value=AU
ST402 column=geo:geo_cd, timestamp=1543164097718, value=AP
ST403 column=geo:geo_cd, timestamp=1543164150140, value=J
ST404 column=geo:geo_cd, timestamp=1543164201956, value=E
ST405 column=geo:geo_cd, timestamp=1543164254010, value=A
ST406 column=geo:geo_cd, timestamp=1543164307498, value=AU
ST407 column=geo:geo_cd, timestamp=1543164359403, value=AP
ST408 column=geo:geo_cd, timestamp=1543164419644, value=E
ST409 column=geo:geo_cd, timestamp=1543164471464, value=E
ST410 column=geo:geo_cd, timestamp=1543164523143, value=A
ST411 column=geo:geo_cd, timestamp=1543164581321, value=A
ST412 column=geo:geo_cd, timestamp=1543164636704, value=AP
ST413 column=geo:geo_cd, timestamp=1543164692614, value=J
ST414 column=geo:geo_cd, timestamp=1543164750154, value=E
15 row(s) in 0.8260 seconds
```

```
hbase(main):006:0> scan 'subscribed-users'
ROW COLUMN+CELL
U100 column=subscn:enddt, timestamp=1543165427485, value=1465130523
U100 column=subscn:startdt, timestamp=1543165372203, value=1465230523
U101 column=subscn:enddt, timestamp=1543165537252, value=1475130523
U101 column=subscn:startdt, timestamp=1543165481364, value=1465230523
U102 column=subscn:enddt, timestamp=1543165652132, value=1475130523
U102 column=subscn:startdt, timestamp=1543165596036, value=1465230523
U103 column=subscn:enddt, timestamp=1543165762187, value=1475130523
U103 column=subscn:startdt, timestamp=1543165706373, value=1465230523
U104 column=subscn:enddt, timestamp=1543165876472, value=1475130523
U104 column=subscn:startdt, timestamp=1543165819437, value=1465230523
U105 column=subscn:enddt, timestamp=1543165990192, value=1475130523
U105 column=subscn:startdt, timestamp=1543165933738, value=1465230523
U106 column=subscn:enddt, timestamp=1543166105300, value=1485130523
U106 column=subscn:startdt, timestamp=1543166048901, value=1465230523
U107 column=subscn:enddt, timestamp=1543166219261, value=1455130523
U107 column=subscn:startdt, timestamp=1543166161744, value=1465230523
U108 column=subscn:enddt, timestamp=1543166335213, value=1465230623
U108 column=subscn:startdt, timestamp=1543166283882, value=1465230523
U109 column=subscn:enddt, timestamp=1543166438666, value=1475130523
U109 column=subscn:startdt, timestamp=1543166386509, value=1465230523
U110 column=subscn:enddt, timestamp=1543166540650, value=1475130523
U110 column=subscn:startdt, timestamp=1543166489525, value=1465230523
U111 column=subscn:enddt, timestamp=1543166641403, value=1475130523
U111 column=subscn:startdt, timestamp=1543166591658, value=1465230523
U112 column=subscn:enddt, timestamp=1543166742516, value=1475130523
U112 column=subscn:startdt, timestamp=1543166691461, value=1465230523
U113 column=subscn:enddt, timestamp=1543166845562, value=1485130523
U113 column=subscn:startdt, timestamp=1543166793388, value=1465230523
U114 column=subscn:enddt, timestamp=1543166949011, value=1468130523
U114 column=subscn:startdt, timestamp=1543166896508, value=1465230523
15 row(s) in 0.5990 seconds
```

4) Perform Data Enrichment Filtering:

Now we need to link these lookup tables in hive using the Hbase Storage Handler.

With the help of “**data_enrichment_filtering_schema.sh**” file we will create hive tables on the top of Hbase tables using “**create_hive_hbase_lookup.hql**”.

Creating Hive Tables on the top of Hbase:

With the help of Hbase storage handler & SerDe properties, we are creating the hive external tables by matching the columns of Hbase tables to hive tables.

data_enrichment_filtering_schema.sh script will run the “**create_hive_hbase_lookup.hql**” which will create the HIVE external tables with the help of Hbase storage handler & SerDe properties. The hive external tables will match the columns of Hbase tables to HIVE tables.

data_enrichment_filtering_schema.sh script :

```
#!/bin/bash

batchid=`cat /home/acadgild/examples/music/logs/current-
batch.txt`
LOGFILE=/home/acadgild/examples/music/logs/log_batch_${batchi
d}

echo "Creating hive tables on top of hbase tables for
data enrichment and filtering..." >> $LOGFILE

hive -f
/home/acadgild/examples/music/create_hive_hbase_lookup.hql
```

“**create_hive_hbase_lookup.hql**” script :

```
CREATE DATABASE IF NOT EXISTS
project; USE project;

create external table if not exists
station_geo_map (
station_id String,
geo_cd string
)

STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'
with serdeproperties
("hbase.columns.mapping"=":key,geo:geo_cd")
tblproperties("hbase.table.name"="station-geo-map");

create external table if not exists subscribed_users
(
```

```

user_id STRING,
subscn_start_dt STRING,
subscn_end_dt STRING
)
STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'
with serdeproperties
("hbase.columns.mapping"=":key,subscn:startdt,subscn:enddt")
tblproperties("hbase.table.name"="subscribed-users");
create external table if not exists
song_artist_map (
song_id STRING,
artist_id STRING
)
STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'
with serdeproperties
("hbase.columns.mapping"=":key,artist:artistid")
tblproperties("hbase.table.name"="song-artist-map");

```

We are running **data_enrichment_filtering_schema.sh** script through the execution of **music_project_master.sh** script

The below screenshot we can see tables are getting created in hive by running the “**data_enrichment_filtering_schema.sh** file”.

Below you could see that three tables are created in project database in hive. They are :

Song_artist_map

Station_geo_map

Subscribed_users

Below screenshot shows **Hive** tables on top of **Hbase**.

```
hive> show databases;  
OK  
default  
project  
Time taken: 33.773 seconds, Fetched: 2 row(s)  
hive> use project;  
OK  
Time taken: 0.135 seconds  
hive> show tables;  
OK  
song_artist_map  
station_geo_map  
subscribed_users  
Time taken: 0.236 seconds, Fetched: 3 row(s)
```

Select * from song_artist_map:

```
hive> select * from song_artist_map;  
OK  
S200      A300  
S201      A301  
S202      A302  
S203      A303  
S204      A304  
S205      A301  
S206      A302  
S207      A303  
S208      A304  
S209      A305  
Time taken: 13.536 seconds, Fetched: 10 row(s)
```

Select * from station_geo_map:

```
hive> select * from station_geo_map;  
OK  
ST400    A  
ST401    AU  
ST402    AP  
ST403    J  
ST404    E  
ST405    A  
ST406    AU  
ST407    AP  
ST408    E  
ST409    E  
ST410    A  
ST411    A  
ST412    AP  
ST413    J  
ST414    E  
Time taken: 2.495 seconds, Fetched: 15 row(s)
```

Select * from subscribed_users:

```
hive> select * from subscribed_users;  
OK  
U100     1465230523    1465130523  
U101     1465230523    1475130523  
U102     1465230523    1475130523  
U103     1465230523    1475130523  
U104     1465230523    1475130523  
U105     1465230523    1475130523  
U106     1465230523    1485130523  
U107     1465230523    1455130523  
U108     1465230523    1465230623  
U109     1465230523    1475130523  
U110     1465230523    1475130523  
U111     1465230523    1475130523  
U112     1465230523    1475130523  
U113     1465230523    1485130523  
U114     1465230523    1468130523  
Time taken: 2.174 seconds, Fetched: 15 row(s)  
hive> █
```


5) Perform Data Formatting:

In this stage, we are merging the data coming from both web applications and mobile applications and create a common table for analysing purpose and create partitioned data based on batchid, since we are running this scripts for every 3 hours.

dataformatting.sh script :

```
#!/bin/bash

batchid=`cat /home/acadgild/examples/music/logs/current-
batch.txt` LOGFILE=/home/acadgild/examples/music
/logs/log_batch_$batchid

echo "Running script for data formatting..." >> $LOGFILE

spark-submit --packages com.databricks:spark-xml_2.10:0.4.1 \
--class DataFormatting \
--master local[2] \
/home/acadgild/examples/music/MusicDataAnalysis/target/scala-
2.11/musicdataanalysis_2.11-1.0.jar $batchid
```

DataFormatting.scala Program :

```
import org.apache.spark.{SparkConf,
SparkContext} import org.apache.spark.sql

object DataFormatting {

  def main(args: Array[String]): Unit = {

    val conf = new SparkConf().setAppName("Data Formatting")

    val sc = new SparkContext(conf)

    val sqlContext = new
    org.apache.spark.sql.hive.HiveContext(sc)

    val batchId = args(0)

    val create_hive_table = """CREATE TABLE IF NOT
    EXISTS project.formatted_input

    (

    User_id STRING,
```

```

Song_id STRING,

Artist_id STRING,

Timestamp STRING,

Start_ts STRING,

End_ts STRING,

Geo_cd STRING,

Station_id STRING,

Song_end_type INT,

Like INT,

Dislike INT

)

PARTITIONED BY

(batchid INT)

ROW FORMAT DELIMITED

FIELDS TERMINATED BY ','

"""

```

```

val load_mob_data = s"""LOAD DATA LOCAL INPATH
'file:///home/acadgild/examples/music/data/mob/file
.txt' INTO TABLE project.formatted_input PARTITION
(batchid='$batchId') """

val load_web_data = s"""INSERT INTO project.formatted_input

PARTITION(batchid='$batchId')

SELECT user_id,

song_id,

artist_id,

unix_timestamp(timestamp,'yyyy-MM-dd

HH:mm:ss') AS timestamp,

unix_timestamp(start_ts,'yyyy-MM-dd

HH:mm:ss') AS start_ts,

unix_timestamp(end_ts,'yyyy-MM-dd

```

```

HH:mm:ss') AS end_ts,

        geo_cd,

        station_id,

        song_end_type,

        like,

        dislike

FROM web_data

"""

    try {

        val xmlData =

sqlContext.read.format("com.databricks.spark.xml").option("row
Tag",

"record").load("file:///home/acadgild/examples/music/data/web/
file.x

ml")

        xmlData.createOrReplaceTempView("web_data")

        sqlContext.sql(create_hive_table)

        sqlContext.sql(load_mob_data)

        sqlContext.sql(load_web_data)

    }

    catch{

        case e: Exception=>e.printStackTrace()

    }

}

}

```

We have build.sbt file inside **MusicDataAnalysis** folder to create jar file:

```
[acadgild@localhost music]$ cd MusicDataAnalysis
[acadgild@localhost MusicDataAnalysis]$ ls -ls
total 8
4 -rw-rw-r--. 1 acadgild acadgild 802 Dec 1 18:34 build.sbt
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec 1 18:34 src
```

Below is the command to create jar file in verbose mode:

sbt -v package

```
[acadgild@localhost MusicDataAnalysis]$ sbt -v package
[process_args] java version = '1.8'
# Executing command line:
java
-Xmx1024m
-Xms1024m
-XX:ReservedCodeCacheSize=128m
-XX:MaxMetaspaceSize=256m
-jar
/usr/share/sbt/bin/sbt-launch.jar
package

Getting org.scala-sbt sbt 1.0.4 (this may take some time)...
downloading https://repo1.maven.org/maven2/org/scala-sbt/sbt/1.0.4/sbt-1.0.4.jar ...
[SUCCESSFUL ] org.scala-sbt#sbt;1.0.4!sbt.jar (910ms)
downloading https://repo1.maven.org/maven2/org/scala-lang/scala-library/2.12.4/scala-library-2.12.4.jar ...
[SUCCESSFUL ] org.scala-lang#scala-library;2.12.4!scala-library.jar (22703ms)
downloading https://repo1.maven.org/maven2/org/scala-sbt/main_2.12/1.0.4/main_2.12-1.0.4.jar ...
[SUCCESSFUL ] org.scala-sbt#main_2.12;1.0.4!main_2.12.jar (6609ms)
downloading https://repo1.maven.org/maven2/org/scala-sbt/logic_2.12/1.0.4/logic_2.12-1.0.4.jar ...
[SUCCESSFUL ] org.scala-sbt#logic_2.12;1.0.4!logic_2.12.jar (632ms)
downloading https://repo1.maven.org/maven2/org/scala-sbt/actions_2.12/1.0.4/actions_2.12-1.0.4.jar ...
[SUCCESSFUL ] org.scala-sbt#actions_2.12;1.0.4!actions_2.12.jar (1258ms)
downloading https://repo1.maven.org/maven2/org/scala-sbt/main-settings_2.12/1.0.4/main-settings_2.12-1.0.4.jar ...
[SUCCESSFUL ] org.scala-sbt#main-settings_2.12;1.0.4!main-settings_2.12.jar (2525ms)
```

Finally Jar file gets created as highlighted below:

```
[info] Done updating.
[info] Compiling 3 Scala sources to /home/acadgild/examples/music/MusicDataAnalysis/target/scala-2.11/classes ...
[info] Non-compiled module 'compiler-bridge_2.11' for Scala 2.11.8. Compiling...
[info] Compilation completed in 107.731s.
[warn] there were three deprecation warnings; re-run with -deprecation for details
[warn] one warning found
[info] Done compiling.
[warn] Multiple main classes detected. Run 'show discoveredMainClasses' to see the list
[info] Packaging /home/acadgild/examples/music/MusicDataAnalysis/target/scala-2.11/musicdataanalysis_2.11-1.0.jar ...
[info] Done packaging.
[success] Total time: 1147 s, completed Dec 1, 2018 7:12:42 PM
You have new mail in /var/spool/mail/acadgild
[acadgild@localhost MusicDataAnalysis]$
```

Below is the location of Jar file which gets created under **/MusicDataAnalysis/target/scala-2.11:**

```
[acadgild@localhost MusicDataAnalysis]$ ls -ls
total 16
4 -rw-rw-r--. 1 acadgild acadgild 802 Dec 1 18:34 build.sbt
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec 1 18:52 project
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec 1 18:34 src
4 drwxrwxr-x. 4 acadgild acadgild 4096 Dec 1 18:58 target
You have new mail in /var/spool/mail/acadgild
[acadgild@localhost MusicDataAnalysis]$ cd target
[acadgild@localhost target]$ ls -ls
total 8
4 drwxrwxr-x. 4 acadgild acadgild 4096 Dec 1 19:12 scala-2.11
4 drwxrwxr-x. 4 acadgild acadgild 4096 Dec 1 18:53 streams
[acadgild@localhost target]$ cd scala-2.11
[acadgild@localhost scala-2.11]$ ls -ls
total 16
4 drwxrwxr-x. 2 acadgild acadgild 4096 Dec 1 19:12 classes
8 -rw-rw-r--. 1 acadgild acadgild 8183 Dec 1 19:12 musicdataanalysis_2.11-1.0.jar
4 drwxrwxr-x. 5 acadgild acadgild 4096 Dec 1 19:10 resolution-cache
```

Scala programs related to data lies in the location below:

```
[acadgild@localhost MusicDataAnalysis]$ ls -ls
total 16
4 -rw-rw-r--. 1 acadgild acadgild 802 Dec 1 18:34 build.sbt
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec 1 18:52 project
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec 1 18:34 src
4 drwxrwxr-x. 4 acadgild acadgild 4096 Dec 1 18:58 target
[acacgild@localhost MusicDataAnalysis]$ cd src
[acacgild@localhost src]$ ls -ls
total 4
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec 1 18:34 main
[acacgild@localhost src]$ cd main
[acacgild@localhost main]$ ls -ls
total 4
4 drwxrwxr-x. 2 acadgild acadgild 4096 Dec 1 18:40 scala
[acacgild@localhost main]$ cd scala
[acacgild@localhost scala]$ ls -ls
total 20
8 -rw-rw-r--. 1 acadgild acadgild 4814 Dec 1 18:34 DataAnalysis.scala
4 -rw-rw-r--. 1 acadgild acadgild 3264 Dec 1 18:34 DataEnrichment.scala
4 -rw-rw-r--. 1 acadgild acadgild 2620 Dec 1 18:40 DataFormatting.scala
```

We are executing master script which internally calls **dataformatting.sh** which performs data formatting:

```
[acacgild@localhost music]$ ./music_project_master.sh
Preparing to execute python scripts to generate data...
Data Generated Successfully !
Starting the daemons....
13921 ResourceManager
14722 HRegionServer
14019 NodeManager
14791 JobHistoryServer
14631 HMaster
14571 HQuorumPeer
29232 RunJar
17489 Main
24311 RunJar
13692 SecondaryNameNode
30268 Jps
13502 DataNode
13407 NameNode
All hadoop daemons started !
Upload the look up tables now in Hbase...
Done with data population in look up tables !
Lets do some data formatting now....
Ivy Default Cache set to: /home/acacgild/.ivy2/cache
The jars for the packages stored in: /home/acacgild/.ivy2/jars
:: loading settings :: url = jar:file:/home/acacgild/install/spark/spark-2.2.1-bin-hadoop2.7/jars/ivy-2.4.0.jar!org/apache/ivy/core/settings/ivysettings.xml
com.databricks#spark-xml_2.10 added as a dependency
:: resolving dependencies :: org.apache.spark#spark-submit-parent;1.0
  confs: [default]
  found com.databricks#spark-xml_2.10;0.4.1 in central
  :: resolution report :: resolve 1398ms :: artifacts dl 34ms
  :: modules in use:
  com.databricks#spark-xml_2.10;0.4.1 from central in [default]
  +-+-----+
  |      conf      | number | search | dwnlded | evicted | number | dwnlded |
  +-+-----+
  |      default   |      1 |      0 |      0 |      0 |      1 |      0 |
  +-+-----+
  :: retrieving :: org.apache.spark#spark-submit-parent
  confs: [default]
  0 artifacts copied, 1 already retrieved (0kB/93ms)
18/12/01 20:15:29 INFO spark.SparkContext: Running Spark version 2.2.1
18/12/01 20:15:31 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
18/12/01 20:15:33 WARN util.Utils: Your hostname, localhost.localdomain resolves to a loopback address: 127.0.0.1; using 192.168.0.102 instead (on interface eth15)
18/12/01 20:15:33 WARN util.Utils: Set SPARK_LOCAL_IP if you need to bind to another address
18/12/01 20:15:33 INFO spark.SparkContext: Submitted application: Data Formatting
18/12/01 20:15:33 INFO spark.SecurityManager: Changing view acls to: acadgild
18/12/01 20:15:33 INFO spark.SecurityManager: Changing modify acls to: acadgild
18/12/01 20:15:33 INFO spark.SecurityManager: Changing view acls groups to:
18/12/01 20:15:33 INFO spark.SecurityManager: Changing modify acls groups to:
18/12/01 20:15:33 INFO spark.SecurityManager: SecurityManager: authentication disabled; ui acls disabled; users with view permissions: Set(acadgild); groups with view permissions: Set(acadgild); users with modify permissions: Set(acadgild); groups with modify permissions: Set()
18/12/01 20:15:36 INFO util.Utils: Successfully started service 'sparkDriver' on port 35422.
18/12/01 20:15:36 INFO spark.SparkEnv: Registering MapOutputTracker
```



```

18/12/01 20:17:20 INFO metastore.HiveMetaStore: 0: get database: project
18/12/01 20:17:20 INFO HiveMetaStore.audit: ugi=acagdild ip=unknown-ip-addr cmd=get_database: project
18/12/01 20:17:20 INFO metastore.HiveMetaStore: 0: get table : db=project tbl=formatted_input
18/12/01 20:17:20 INFO HiveMetaStore.audit: ugi=acagdild ip=unknown-ip-addr cmd=get_table : db=project tbl=formatted_input
18/12/01 20:17:20 INFO metastore.HiveMetaStore: 0: get table : db=project tbl=formatted_input
18/12/01 20:17:20 INFO HiveMetaStore.audit: ugi=acagdild ip=unknown-ip-addr cmd=get_table : db=project tbl=formatted_input
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: int
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: string
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: string
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: string
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: string
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: string
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: string
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: int
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: int
18/12/01 20:17:20 INFO parser.CatalystSqlParser: Parsing command: int
18/12/01 20:17:20 INFO spark.SparkContext: Invoking stop() from shutdown hook
18/12/01 20:17:21 INFO server.AbstractConnector: Stopped Spark@15dd1d35(HTTP/1.1,[http/1.1]){0.0.0.0:4040}
18/12/01 20:17:21 INFO ui.SparkUI: Stopped Spark web UI at http://192.168.0.102:4040
18/12/01 20:17:21 INFO spark.MapOutputTrackerMasterEndpoint: MapOutputTrackerMasterEndpoint stopped!
18/12/01 20:17:21 INFO memory.MemoryStore: MemoryStore cleared
18/12/01 20:17:21 INFO storage.BlockManager: BlockManager stopped
18/12/01 20:17:21 INFO storage.BlockManagerMaster: BlockManagerMaster stopped
18/12/01 20:17:21 INFO scheduler.OutputCommitCoordinator$OutputCommitCoordinatorEndpoint: OutputCommitCoordinator stopped!
18/12/01 20:17:21 INFO spark.SparkContext: Successfully stopped SparkContext
18/12/01 20:17:21 INFO util.ShutdownHookManager: Shutdown hook called
18/12/01 20:17:21 INFO util.ShutdownHookManager: Deleting directory /tmp/spark-3a3b142c-3ae0-4ae8-8bbb-4a3289f36a9b
data formatting complete !
creating hive tables on top of hbase tables for data enrichment and filtering...
Hive table with Hbase Mapping Complete !
Let us do data enrichment as per the requirement...
Data Enrichment Complete
Lets run some use cases now...
USE CASES COMPLETE !!
You have new mail in /var/spool/mail/acagdild

```

Below hive table **formatted_input** gets created which contains all data which gets merged from web and mobile applications (file.txt and file.xml):

select * from formatted_input;

```

hive> show tables;
OK
formatted_input
song_artist_map
station_geo_map
subscribed_users
Time taken: 0.221 seconds, Fetched: 4 row(s)
hive> select * from formatted_input;
OK
U120 S203 A302 1495130523 1475130523 1465230523 AP ST410 3 0 1 1
U106 S203 A303 1495130523 1465130523 1485130523 AU ST403 0 1 0 1
U119 S204 A302 1475130523 1485130523 1475130523 E ST403 0 0 1 1
U108 S200 A301 1475130523 1485130523 1485130523 U ST410 2 0 1 1
U115 S202 A305 1475130523 1475130523 1465130523 A ST403 2 0 0 1
S206 A304 1495130523 1485130523 1475130523 AU ST404 1 1 1 1
U101 S202 A300 1495130523 1475130523 1485130523 AU ST406 3 0 1 1
U105 S208 A301 1465230523 1465230523 1475130523 U ST400 3 1 1 1
U101 S201 A302 1465230523 1465130523 1475130523 ST412 1 0 0 1
U112 S203 1465130523 1465130523 1475130523 E ST406 0 1 1 1
U110 S209 A303 1495130523 1475130523 1475130523 U ST406 0 1 0 1
U100 S207 A300 1475130523 1485130523 1485130523 E ST413 1 1 1 1
U103 S202 A301 1465130523 1475130523 1485130523 A ST404 1 1 1 1
U109 S203 A301 1465130523 1485130523 1485130523 E ST415 1 1 0 1
U102 S204 A301 1465230523 1485130523 1475130523 E ST411 0 0 0 1
U111 S200 A303 1495130523 1465230523 1465230523 E ST404 2 0 0 1
U107 S205 A301 1465130523 1475130523 1465230523 AU ST409 1 1 0 1
U114 S210 A302 1465130523 1465230523 1475130523 A ST409 0 0 1 1
U109 S200 A301 1465230523 1485130523 1485130523 AP ST407 0 0 0 1
U110 S200 A300 1465230523 1485130523 1475130523 AP ST404 1 1 1 1
U105 S205 A300 1465490556 1462863262 1462863262 E ST407 0 1 1 1
U100 S205 A304 1468094889 1468094889 1465490556 AU ST415 2 0 1 1
U100 S203 A302 1462863262 1468094889 1465490556 A ST403 0 0 0 1
U119 S202 A304 1462863262 1465490556 1462863262 A ST408 3 1 1 1
U114 S210 A305 1494297562 1468094889 1465490556 AP ST409 2 1 0 1
NULL S202 A304 1462863262 1462863262 1465490556 A ST415 0 1 1 1
U109 S204 A300 1468094889 1494297562 1494297562 AU ST403 3 0 1 1

```

In the above screenshot, we could see that formatted input data with some **null** values in user_id, artist_id and geo_cd columns which we will fill the enrichment script based on rules of enrichment for artist_id and geo_cd only.

Data Formatting phase is executed successfully by loading both mobile and web data and partitioned based on batchid.

6) Perform Data Enrichment:

In this phase we will enrich the data coming from web and mobile applications using the lookup table stored in Hbase and divide the records based on the enrichment rules into 'pass' and 'fail' records.

Rules for data enrichment:

1. If any of like or dislike is NULL or absent, consider it as 0.
2. If fields like Geo_cd and Artist_id are NULL or absent, consult the lookup tables for fields Station_id and Song_id respectively to get the values of Geo_cd and Artist_id.
3. If corresponding lookup entry is not found, consider that record to be invalid

So based on the enrichment rules we will fill the null geo_cd and artist_id values with the help of corresponding lookup values in song-artist-map and station-geo-map tables in Hive-Hbase tables.

data_enrichment.sh script :

```
#!/bin/bash

batchid=`cat /home/acadgild/examples/music/logs/current-
batch.txt`
LOGFILE=/home/acadgild/examples/music/logs/log_batch_${batchid}
VALIDDIR=/home/acadgild/examples/music/processed_dir/valid/bat
ch_${batchid}
INVALIDDIR=/home/acadgild/examples/music/processed_dir/invalid
/batch_${batch id}

echo "Running script for data enrichment and filtering..." >>
$LOGFILE

spark-submit --class DataEnrichment \

--master local[2] \

--jars /home/acadgild/install/hive/apache-hive-2.3.2-
bin/lib/hive-hbase-handler-
2.3.2.jar,/home/acadgild/install/hive/apache-hive-2.3.2-
bin/lib/hbase-client-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hbase-common-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-2.3.2-bin/lib/hbase-
hadoop-compat-
```

```
1.1.1.jar,/home/acadgild/install/hive/apache-hive-2.3.2-bin/lib/hbase-
server-1.1.1.jar,/home/acadgild/install/hive/apache-hive-2.3.2-
bin/lib/hbase-protocol-1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/zookeeper-3.4.6.jar,/home/acadgild/install/hive/apache-
hive-2.3.2-bin/lib/guava-
14.0.1.jar,/home/acadgild/install/hive/apache-hive-2.3.2-
bin/lib/htrace-core-3.1.0-incubating.jar \
/home/acadgild/examples/music/MusicDataAnalysis/target/scala-
2.11/musicdataanalysis_2.11-1.0.jar $batchid
```

```
if [ ! -d "$VALIDDIR" ]
```

```
then
```

```
mkdir -p "$VALIDDIR"
```

```
fi
```

```
if [ ! -d "$INVALIDDIR" ]
```

```
then
```

```
mkdir -p "$INVALIDDIR"
```

```
fi
```

```
echo "Copying valid and invalid records in local file
system..." >> $LOGFILE
```

```
hadoop fs -get
```

```
/user/hive/warehouse/project.db/enriched_data/batchid=$batchid
/status=pass/
```

```
* $VALIDDIR
hadoop fs -
get
```

```
/user/hive/warehouse/project.db/enriched_data/batchid=$batchid
/status=fail/
```

```
* $INVALIDDIR
```

```
echo "Deleting older valid and invalid records from local
file system..." >> $LOGFILE
```

```
find /home/acadgild/examples/music/processed_dir/ -mtime +7 -
exec rm {} \;
```

DataEnrichment.scala Program :

```
import org.apache.spark.{SparkConf,
SparkContext} import
org.apache.spark.sql

object DataEnrichment {

  def main(args: Array[String]): Unit = {

    val conf = new SparkConf().setAppName("Data Formatting")

    val sc = new SparkContext(conf)

    val sqlContext = new
    org.apache.spark.sql.hive.HiveContext(sc)

    val batchId = args(0)

    val create_hive_table = """CREATE TABLE IF NOT EXISTS
    enriched_data

        (

            User_id STRING,

            Song_id STRING,

            Artist_id STRING,

            Timestamp STRING,

            Start_ts STRING,

            End_ts STRING,

            Geo_cd STRING,

            Station_id STRING,

            Song_end_type INT,

            Like INT,

            Dislike INT

        )

    PARTITIONED BY

    (batchid INT,

    status STRING)
```

STORED AS ORC

"""

```
val load_data = s"""INSERT OVERWRITE TABLE
    enriched_data PARTITION
    (batchid, status)

    SELECT

        i.user_id,

        i.song_id,
        sa.artist_id,
        i.timestamp,
        i.start_ts,
        i.end_ts,
        sg.geo_cd,
        i.station_id,

        IF (i.song_end_type IS NULL, 3, i.song_end_type) AS
song_end_type,

        IF (i.like IS NULL, 0, i.like) AS like,

        IF (i.dislike IS NULL, 0, i.dislike) AS
dislike, i.batchid,

        IF((i.like=1 AND i.dislike=1)

        OR i.user_id IS NULL
        OR i.song_id IS NULL
        OR i.timestamp IS NULL

        OR i.start_ts IS NULL
        OR i.end_ts IS NULL
        OR i.geo_cd IS NULL
        OR i.user_id=''
        OR i.song_id=''

        OR i.timestamp=''
        OR i.start_ts=')
```



```

        OR i.end_ts=''
        OR i.geo_cd=''
        OR sg.geo_cd IS NULL

        OR sg.geo_cd=''
        OR sa.artist_id IS NULL

        OR sa.artist_id='', 'fail', 'pass') AS
status FROM formatted_input i LEFT OUTER
JOIN

station_geo_map sg ON i.station_id = sg.station_id

        LEFT OUTER JOIN song_artist_map sa ON i.song_id =
sa.song_id

        WHERE i.batchid=$batchId
        """

    try {

        sqlContext.sql("SET hive.auto.convert.join=false")

        sqlContext.sql("SET hive.exec.dynamic.partition.mode=nonstrict")
        sqlContext.sql("USE project")
        sqlContext.sql(create_hive_table)
        sqlContext.sql(load_data)

    }
    catch{
        case e: Exception=>e.printStackTrace()
    }
}
}

```

We have executed `data_enrichment.sh` script by calling `music_project_master.sh` batch file as shown below:

```
[acadgild@localhost music]$ ./music_project_master.sh
Preparing to execute python scripts to generate data...
Data Generated Successfully !
Starting the daemons....
15888 RunJar
4528 HMaster
3890 NameNode
3298 NameNode
5011 RunJar
3555 SecondaryNameNode
3417 DataNode
4714 JobHistoryServer
4635 HRegionServer
4460 HQuorumPeer
17007 Jps
3791 ResourceManager
All hadoop daemons started !
Upload the look up tables now in Hbase...
Done with data population in look up tables !
Lets do some data formatting now....
data formatting complete !
Creating hive tables on top of hbase tables for data enrichment and filtering...
Hive table with Hbase Mapping Complete !
Let us do data enrichment as per the requirement...
18/12/02 15:25:32 INFO spark.SparkContext: Running Spark version 2.2.1
18/12/02 15:25:35 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
18/12/02 15:25:36 WARN util.Utils: Your hostname, localhost.localdomain resolves to a loopback address: 127.0.0.1; using 192.168.0.100 in stead (on interface eth15)
18/12/02 15:25:36 WARN util.Utils: Set SPARK_LOCAL_IP if you need to bind to another address
18/12/02 15:25:37 INFO spark.SparkContext: Submitted application: Data Formatting
18/12/02 15:25:37 INFO spark.SecurityManager: Changing view acls to: acadgild
18/12/02 15:25:37 INFO spark.SecurityManager: Changing modify acls to: acadgild
18/12/02 15:25:37 INFO spark.SecurityManager: Changing view acls groups to:
18/12/02 15:25:37 INFO spark.SecurityManager: Changing modify acls groups to:
18/12/02 15:25:37 INFO spark.SecurityManager: SecurityManager: authentication disabled; ui acls disabled; users with view permissions: Set(acadgild); groups with view permissions: Set()
18/12/02 15:25:40 INFO util.Utils: Successfully started service 'sparkDriver' on port 36466.

18/12/02 15:28:44 INFO HiveMetaStore.audit: ugi=acadgild ip=unknown-ip-addr cmd=get_database: project
18/12/02 15:28:44 INFO metastore.HiveMetaStore: 0: get table : db=project tbl=enriched_data
18/12/02 15:28:44 INFO HiveMetaStore.audit: ugi=acadgild ip=unknown-ip-addr cmd=get_table : db=project tbl=enriched_data
18/12/02 15:28:44 INFO metastore.HiveMetaStore: 0: get table : db=project tbl=enriched_data
18/12/02 15:28:44 INFO HiveMetaStore.audit: ugi=acadgild ip=unknown-ip-addr cmd=get_table : db=project tbl=enriched_data
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: int
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: string
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: int
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: int
18/12/02 15:28:44 INFO parser.CatalystSqlParser: Parsing command: int
18/12/02 15:28:44 INFO spark.SparkContext: Invoking stop() from shutdown hook
18/12/02 15:28:44 INFO server.AbstractConnector: Stopped Spark@33ba7d11(HTTP/1.1,[http/1.1]){0.0.0.0:4040}
18/12/02 15:28:44 INFO ui.SparkUI: Stopped Spark web UI at http://192.168.0.100:4040
18/12/02 15:28:45 INFO spark.MapOutputTrackerMasterEndpoint: MapOutputTrackerMasterEndpoint stopped!
18/12/02 15:28:45 INFO memory.MemoryStore: MemoryStore cleared
18/12/02 15:28:45 INFO storage.BlockManager: BlockManager stopped
18/12/02 15:28:45 INFO storage.BlockManagerMaster: BlockManagerMaster stopped
18/12/02 15:28:45 INFO scheduler.OutputCommitCoordinator$OutputCommitCoordinatorEndpoint: OutputCommitCoordinator stopped!
18/12/02 15:28:45 INFO spark.SparkContext: Successfully stopped SparkContext
18/12/02 15:28:45 INFO util.ShutdownHookManager: Shutdown hook called
18/12/02 15:28:45 INFO util.ShutdownHookManager: Deleting directory /tmp/spark-c8afaf1-ed1c-4784-a537-66d2b0ea2e65
18/12/02 15:28:53 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
18/12/02 15:29:06 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Data Enrichment Complete
lets run some use cases now...
USE CASES COMPLETE !!
You have new mail in /var/spool/mail/acadgild
[acadgild@localhost music]$
```

In the above step Data Enrichment is completed.

Let's have a look at the data enrichment table that got created.

```

hive> show databases;
OK
default
project
Time taken: 4.22 seconds, Fetched: 2 row(s)
hive> use project;
OK
Time taken: 0.116 seconds
hive> show tables;
OK
enriched_data
formatted_input
song_artist_map
station_geo_map
subscribed_users
Time taken: 0.251 seconds, Fetched: 5 row(s)

```

In the below screenshot, we have data for data enrichment table where we filled the null values of artist_id and geo_cd of formatted input with the help of lookup tables.

```

hive> select * from enriched_data;
OK
U111 S201 A301 1465490556 1494297562 1465490556 J ST403 1 1 1 1 fail
U101 S201 A301 1465230523 1465130523 1475130523 AP ST412 1 0 0 1 fail
U100 S202 A303 1475130523 1485130523 J ST413 1 1 1 1 fail
U103 S202 A302 1465130523 1475130523 E ST404 1 1 1 1 fail
U119 S202 A302 1462863262 1465490556 1462863262 E ST408 3 1 1 1 fail
NULL S202 A302 1462863262 1462863262 1465490556 NULL ST415 0 1 1 1 fail
S206 A302 1495130523 1485130523 1475130523 E ST404 1 1 1 1 fail
U105 S208 A304 1465230523 1465230523 1475130523 A ST400 3 1 1 1 fail
U114 S210 NULL 1465130523 1465230523 1475130523 E ST409 0 0 1 1 fail
U114 S210 NULL 1494297562 1468094889 1465490556 E ST409 2 1 0 1 fail
U108 S205 A301 1462863262 1468094889 1465490556 A ST410 1 1 1 1 fail
U105 S205 A301 1465490556 1462863262 1462863262 AP ST407 0 1 1 1 fail
U100 S205 A301 1468094889 1468094889 1465490556 NULL ST415 2 0 1 1 fail
U110 S200 A300 1465230523 1485130523 1475130523 E ST404 1 1 1 1 fail
U113 S203 A303 1465490556 1465490556 1468094889 AP ST407 0 0 0 1 fail
U109 S203 A303 1465130523 1485130523 1485130523 NULL ST415 1 1 0 1 fail
U114 S203 A303 1494297562 1462863262 1468094889 NULL ST415 3 1 0 1 fail
U112 S203 A303 1465130523 1465130523 1475130523 AU ST406 0 1 1 1 fail
U106 S201 A301 1468094889 1462863262 1462863262 J ST403 2 0 1 1 pass
U106 S207 A303 1494297562 1494297562 1468094889 E ST404 3 0 1 1 pass
U117 S202 A302 1462863262 1465490556 1465490556 E ST404 0 1 0 1 pass
U115 S202 A302 1475130523 1475130523 1465130523 J ST403 2 0 0 1 pass
U101 S202 A302 1495130523 1475130523 1485130523 AU ST406 3 0 1 1 pass
U102 S204 A304 1494297562 1462863262 1465490556 E ST414 3 1 0 1 pass
U119 S204 A304 1475130523 1485130523 1475130523 J ST403 0 0 1 1 pass
U109 S204 A304 1468094889 1494297562 1494297562 J ST403 3 0 1 1 pass
U103 S204 A304 1462863262 1465490556 1465490556 A ST410 3 0 1 1 pass
U102 S204 A304 1465230523 1485130523 1475130523 A ST411 0 0 0 1 pass
U104 S209 A305 1465490556 1462863262 1494297562 AP ST407 0 0 1 1 pass
U110 S209 A305 1495130523 1475130523 1475130523 AU ST406 0 1 0 1 pass
U116 S206 A302 1465490556 1462863262 1468094889 E ST409 0 1 0 1 pass
U118 S206 A302 1465490556 1462863262 1462863262 A ST411 1 0 1 1 pass
U107 S205 A301 1465130523 1475130523 1465230523 E ST409 1 1 0 1 pass
U104 S205 A301 1462863262 1468094889 1468094889 E ST409 2 0 0 1 pass

```

At the end, script will automatically divide the records based on status **pass & fail** and dump the result into **processed_dir** folder with **valid** and **invalid** folders as shown below:

```

[acadgild@localhost music]$ cd processed_dir/
[acadgild@localhost processed_dir]$ ls -ls
total 8
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec  2 13:43 invalid
4 drwxrwxr-x. 3 acadgild acadgild 4096 Dec  2 13:43 valid
[acadgild@localhost processed_dir]$ cd valid
[acadgild@localhost valid]$ ls -ls
total 4
4 drwxrwxr-x. 2 acadgild acadgild 4096 Dec  2 13:43 batch_1
[acadgild@localhost valid]$ cd batch_1/
You have new mail in /var/spool/mail/acadgild
[acadgild@localhost batch_1]$ ls -ls
total 36
4 -rw-r--r--. 1 acadgild acadgild 1027 Dec  2 13:43 part-00020-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1028 Dec  2 13:43 part-00033-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1180 Dec  2 13:43 part-00057-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1262 Dec  2 13:43 part-00087-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1155 Dec  2 13:43 part-00095-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1119 Dec  2 13:43 part-00107-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1157 Dec  2 13:43 part-00165-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1135 Dec  2 13:43 part-00177-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1179 Dec  2 13:43 part-00199-ee135a99-53c0-4842-a147-c3209a4bf222.c000
[acadgild@localhost batch_1]$ cd ..
[acadgild@localhost valid]$ cd ..
[acadgild@localhost processed_dir]$ cd invalid
[acadgild@localhost invalid]$ ls -ls
total 4
4 drwxrwxr-x. 2 acadgild acadgild 4096 Dec  2 13:44 batch_1
[acadgild@localhost invalid]$ cd batch_1/
You have new mail in /var/spool/mail/acadgild
[acadgild@localhost batch_1]$ ls -ls
total 36
4 -rw-r--r--. 1 acadgild acadgild 1145 Dec  2 13:44 part-00020-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1001 Dec  2 13:44 part-00033-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1206 Dec  2 13:44 part-00057-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1006 Dec  2 13:44 part-00107-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1008 Dec  2 13:44 part-00160-ee135a99-53c0-4842-a147-c3209a4bf222.c000
4 -rw-r--r--. 1 acadgild acadgild 1151 Dec  2 13:44 part-00161-ee135a99-53c0-4842-a147-c3209a4bf222.c000

```

Enrichment phase is executed successfully by applying all the rules of enrichment.

7).Perform Data Analysis:

In this stage, we will do analysis on enriched data using Spark SQL and run the program using **Spark-Submit** command.

Data analysis.sh script file :

```
#!/bin/bash

batchid=`cat
/home/acadgild/examples/music/logs/current-
batch.txt`
LOGFILE=/home/acadgild/examples/music/logs/log_batch_
h_$batchid

echo "Running script for data analysis..." >>
$LOGFILE

spark-submit --class DataAnalysis --master local[2] \
--jars /home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hive-hbase-handler-
2.3.2.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hbase-client-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hbase-common-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hbase-hadoop-compat-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hbase-server-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/hbase-protocol-
1.1.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/zookeeper-
3.4.6.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/guava-
14.0.1.jar,/home/acadgild/install/hive/apache-hive-
2.3.2-bin/lib/htrace-core-3.1.0-incubating.jar \
/home/acadgild/examples/music/MusicDataAnalysis/target/scala-2.11/musicdataanalysis_2.11-1.0.jar
$batchid

sh /home/acadgild/examples/music/data_export.sh

echo "Incrementing batchid..." >> $LOGFILE

batchid=`expr $batchid + 1`

echo -n $batchid >
/home/acadgild/examples/music/logs/current-batch.txt
```


Problem Statements :-

1. Determine top 10 station_id(s) where maximum number of songs were played, which were liked by unique users.
2. Determine total duration of songs played by each type of user, where type of user can be 'subscribed' or 'unsubscribed'. An unsubscribed user is the one whose record is either not present in Subscribed_users lookup table or has subscription_end_date earlier than the timestamp of the song played by him.
3. Determine top 10 connected artists. Connected artists are those whose songs are most listened by the unique users who follow them.
4. Determine top 10 songs who have generated the maximum revenue. Royalty applies to a song only if it was liked or was completed successfully or both.
5. Determine top 10 unsubscribed users who listened to the songs for the longest duration.

Spark Source Code:

We have created below Scala file for creating tables for each query (problem statement wise).

DataAnalysis.scala program:

```
import org.apache.spark.{SparkConf,
SparkContext} import org.apache.spark.sql

object DataAnalysis {

  def main(args: Array[String]): Unit = {

    val conf = new SparkConf().setAppName("Data Analysis")
    val sc = new SparkContext(conf)
    val sqlContext = new
    org.apache.spark.sql.hive.HiveContext(sc)
    val batchId = args(0)

    // Problem 1: Determine top 10 station_id(s) where maximum
number of songs were played, which were liked by unique
users.

    val create_top_10_stations = """CREATE TABLE IF NOT
    EXISTS top_10_stations

    (
    station_id STRING,
```

```

total_distinct_songs_played INT,
distinct_user_count INT

)

PARTITIONED BY (batchid INT)

ROW FORMAT DELIMITED

FIELDS TERMINATED BY ','

STORED AS TEXTFILE""

val load_top_10_stations = s""INSERT OVERWRITE
TABLE top_10_stations

PARTITION(batchid='$batchId')

SELECT

station_id,

COUNT(DISTINCT song_id) AS total_distinct_songs_played,

COUNT(DISTINCT user_id) AS distinct_user_count

FROM enriched_data

WHERE status='pass'

AND batchid='$batchId'

AND like=1

GROUP BY station_id

ORDER BY total_distinct_songs_played
DESC LIMIT 10""

// Problem 2: Determine total duration of songs played by each
type of user, where type of user can be 'subscribed' or
'unsubscribed'. An unsubscribed user is the one whose record
is either not present in Subscribed_users lookup table or has
subscription_end_date earlier than the timestamp of the song
played by him.

val create_users_behaviour = ""CREATE TABLE IF NOT
EXISTS users_behaviour

(

user_type STRING,
```

```

duration INT
)

PARTITIONED BY (batchid INT)

ROW FORMAT DELIMITED

FIELDS TERMINATED BY ','

STORED AS TEXTFILE"""

val load_users_behaviour = s"""INSERT OVERWRITE
TABLE users_behaviour

PARTITION(batchid='$batchId')

SELECT

CASE WHEN (su.user_id IS NULL OR CAST(ed.timestamp AS
DECIMAL(20,0))

> CAST(su.subscn_end_dt AS DECIMAL(20,0))) THEN 'UNSUBSCRIBED'

WHEN (su.user_id IS NOT NULL AND CAST(ed.timestamp AS
DECIMAL(20,0))

<= CAST(su.subscn_end_dt AS DECIMAL(20,0))) THEN 'SUBSCRIBED'
END AS user_type,

SUM(ABS(CAST(ed.end_ts AS DECIMAL(20,0))-CAST(ed.start_ts AS
DECIMAL(20,0)))) AS duration

FROM enriched_data ed

LEFT OUTER JOIN subscribed_users su

ON ed.user_id=su.user_id

WHERE ed.status='pass'

AND ed.batchid='$batchId'

GROUP BY CASE WHEN (su.user_id IS NULL OR
CAST(ed.timestamp AS DECIMAL(20,0)) >
CAST(su.subscn_end_dt AS DECIMAL(20,0))) THEN
'UNSUBSCRIBED'

WHEN (su.user_id IS NOT NULL AND CAST(ed.timestamp AS
DECIMAL(20,0)) <= CAST(su.subscn_end_dt AS DECIMAL(20,0)))
THEN 'SUBSCRIBED' END"""

```

//Problem 3: Determine top 10 connected artists. Connected artists are those whose songs are most listened by the unique users who follow them.

```
val create_connected_artists = """CREATE TABLE IF NOT
EXISTS connected_artists

(
artist_id STRING,
user_count INT
)

PARTITIONED BY (batchid INT)

ROW FORMAT DELIMITED

FIELDS TERMINATED BY ','

STORED AS TEXTFILE"""

val load_connected_artists = s"""INSERT OVERWRITE
TABLE connected_artists

PARTITION(batchid='$batchId')

SELECT

ua.artist_id,

COUNT(DISTINCT ua.user_id) AS user_count

FROM

(

SELECT user_id, artist_id FROM users_artists
LATERAL VIEW explode(artists_array) artists AS artist_id
) ua

INNER JOIN

(

SELECT artist_id, song_id, user_id

FROM enriched_data

WHERE status='pass'

AND batchid='$batchId'
```

```
) ed
ON ua.artist_id=ed.artist_id
AND ua.user_id=ed.user_id
GROUP BY ua.artist_id
ORDER BY user_count DESC
LIMIT 10"""
```

//Problem 4: Determine top 10 songs who have generated the maximum revenue. Royalty applies to a song only if it was liked or was completed successfully or both.

```
val create_top_10_royalty_songs = """CREATE TABLE IF NOT
EXISTS top_10_royalty_songs
```

```
(
song_id STRING,
duration INT
)
PARTITIONED BY (batchid INT)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY ','
STORED AS TEXTFILE"""
```

```
val load_top_10_royalty_songs = s"""INSERT OVERWRITE
TABLE top_10_royalty_songs
```

```
PARTITION(batchid='$batchId')
SELECT song_id,
SUM(ABS(CAST(end_ts AS DECIMAL(20,0))-
CAST(start_ts AS DECIMAL(20,0)))) AS duration
FROM enriched_data
WHERE status='pass'
AND batchid='$batchId'
AND (like=1 OR song_end_type=0)
GROUP BY song_id
ORDER BY duration DESC
```

```
LIMIT 10"""
```

//Problem 5: Determine top 10 unsubscribed users who listened to the songs for the longest duration.

```
val create_top_10_unsubscribed_users = """CREATE TABLE IF NOT EXISTS top_10_unsubscribed_users
```

```
(
```

```
user_id STRING,
```

```
duration INT
```

```
)
```

```
PARTITIONED BY (batchid INT)
```

```
ROW FORMAT DELIMITED
```

```
FIELDS TERMINATED BY ','
```

```
STORED AS TEXTFILE"""
```

```
val load_top_10_unsubscribed_users = s"""INSERT OVERWRITE TABLE top_10_unsubscribed_users
```

```
PARTITION(batchid='$batchId')
```

```
SELECT
```

```
ed.user_id,
```

```
SUM(ABS(CAST(ed.end_ts AS DECIMAL(20,0))-CAST(ed.start_ts AS DECIMAL(20,0)))) AS duration
```

```
FROM enriched_data ed
```

```
LEFT OUTER JOIN subscribed_users su
```

```
ON ed.user_id=su.user_id
```

```
WHERE ed.status='pass'
```

```
AND ed.batchid='$batchId'
```

```
AND (su.user_id IS NULL OR (CAST(ed.timestamp AS DECIMAL(20,0)) > CAST(su.subscn_end_dt AS DECIMAL(20,0)))) GROUP BY ed.user_id
```

```
ORDER BY duration DESC
```



```
LIMIT 10"""

    try {

        sqlContext.sql("SET hive.auto.convert.join=false")
        sqlContext.sql("USE project")
        sqlContext.sql(create_top_10_stations)
        sqlContext.sql(load_top_10_stations)
        sqlContext.sql(create_users_behaviour)
        sqlContext.sql(load_users_behaviour)

        sqlContext.sql(create_connected_artists)
        sqlContext.sql(load_connected_artists)
        sqlContext.sql(create_top_10_royalty_songs)
        sqlContext.sql(load_top_10_royalty_songs)
        sqlContext.sql(create_top_10_unsubscribed_users)
        sqlContext.sql(load_top_10_unsubscribed_users)

    }

    catch{

        case e: Exception=>e.printStackTrace()

    }

}

}
```

We are executing `Data_analysis.sh` script by running `music_project_master.sh` script file.

```
[acadgild@localhost music]$ ./music_project_master.sh
Preparing to execute python scripts to generate data...
Data Generated Successfully !
Starting the daemons....
5152 NodeManager
15505 RunJar
4610 RunJar
4691 HRegionServer
3923 NameNode
4531 HQuorumPeer
4580 HMaster
4084 DataNode
4999 ResourceManager
4344 SecondaryNameNode
3835 JobHistoryServer
17325 Jps
All hadoop daemons started !
Upload the look up tables now in Hbase...
Done with data population in look up tables !
Let's do some data formatting now....
data formatting complete !
Creating hive tables on top of hbase tables for data enrichment and filtering...
Hive table with Hbase Mapping Complete !
Let us do data enrichment as per the requirement...
Data Enrichment Complete
Let's run some use cases now...
18/12/09 15:40:57 INFO spark.SparkContext: Running Spark version 2.2.1
18/12/09 15:41:03 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
18/12/09 15:41:06 WARN util.Utils: Your hostname, localhost.localdomain resolves to a loopback address: 127.0.0.1; using 192.168.0.100 instead (on interface eth15)
18/12/09 15:41:06 WARN util.Utils: Set SPARK_LOCAL_IP if you need to bind to another address
18/12/09 15:41:07 INFO spark.SparkContext: Submitted application: Data Analysis
18/12/09 15:41:07 INFO spark.SecurityManager: Changing view acls to: acadgild
18/12/09 15:41:07 INFO spark.SecurityManager: Changing modify acls to: acadgild
18/12/09 15:41:07 INFO spark.SecurityManager: Changing view acls groups to:

18/12/09 15:45:58 INFO parser.CatalystSqlParser: Parsing command: string
18/12/09 15:45:58 INFO metastore.HiveMetaStore: 0: get table : db=project tbl=top_10_unsubscribed_users
18/12/09 15:45:58 INFO HiveMetaStore.audit: ugi=acadgild ip=unknown-ip-addr cmd=get_table : db=project tbl=top_10_unsubscribed_users
18/12/09 15:45:58 INFO parser.CatalystSqlParser: Parsing command: int
18/12/09 15:45:58 INFO parser.CatalystSqlParser: Parsing command: string
18/12/09 15:45:58 INFO parser.CatalystSqlParser: Parsing command: int
18/12/09 15:45:59 INFO common.FileUtils: Creating directory if it doesn't exist: hdfs://localhost:8020/user/hive/warehouse/project.db/top_10_unsubscribed_users/,hive-staging hive: 2018-12-09 15:45:59.012 7240998144222739209-1
18/12/09 15:45:59 INFO output.FileOutputCommitter: File Output Committer Algorithm version is 1
18/12/09 15:45:59 INFO datasources.SQLHadoopMapReduceCommitProtocol: Using output committer class org.apache.hadoop.mapreduce.lib.output.FileOutputCommitter
18/12/09 15:45:59 INFO aggregate.HashAggregateExec: spark.sql.codegen.aggregate.map.twolevel.enable is set to true, but current version of codegened fast hashmap does not support this aggregate.
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned shuffle 9
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned shuffle 10
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 439
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 431
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 429
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 438
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 433
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 428
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 437
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 432
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 427
18/12/09 15:45:59 INFO storage.BlockManagerInfo: Removed broadcast_21_piece0 on 192.168.0.100:45515 in memory (size: 13.4 KB, free: 413.8 MB)
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 434
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 435
18/12/09 15:45:59 INFO storage.BlockManagerInfo: Removed broadcast_19_piece0 on 192.168.0.100:45515 in memory (size: 24.9 KB, free: 413.8 MB)
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 430
18/12/09 15:45:59 INFO spark.ContextCleaner: Cleaned accumulator 436

Warning: /home/acadgild/install/sqoop/sqoop-1.4.6.bin_hadoop-2.0.4-alpha/./hcatalog does not exist! HCatalog jobs will fail.
Please set $HCAT_HOME to the root of your HCatalog installation.
Warning: /home/acadgild/install/sqoop/sqoop-1.4.6.bin_hadoop-2.0.4-alpha/./accumulo does not exist! Accumulo imports will fail.
Please set $ACCUMULO_HOME to the root of your Accumulo installation.
18/12/09 16:21:09 INFO sqoop.Sqoop: Running Sqoop version: 1.4.6
18/12/09 16:21:09 WARN tool.BaseSqoopTool: Setting your password on the command-line is insecure. Consider using -P instead.
18/12/09 16:21:10 INFO manager.MySQLManager: Preparing to use a MySQL streaming resultset.
18/12/09 16:21:10 INFO tool.CodeGenTool: Beginning code generation
Sun Dec 09 16:21:12 IST 2018 WARN: Establishing SSL connection without server's identity verification is not recommended. According to MySQL 5.5.45+, 5.6.26+ and 5.7.6+ requirements SSL connection must be established by default if explicit option isn't set. For compliance with existing applications not using SSL the verifyServerCertificate property is set to 'false'. You need either to explicitly disable SSL by setting useSSL=false, or set useSSL=true and provide truststore for server certificate verification.
18/12/09 16:21:19 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM 'top_10_stations' AS t LIMIT 1
18/12/09 16:21:19 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM 'top_10_stations' AS t LIMIT 1
18/12/09 16:21:19 INFO orm.CompilationManager: HADOOP_MAPRED_HOME is /home/acadgild/install/hadoop/hadoop-2.6.5
Note: /tmp/sqoop-acadgild/compile/2e7e412a7c900121d658a47478733800/top_10_stations.java uses or overrides a deprecated API.
Note: Recompile with -Xlint:deprecation for details.
18/12/09 16:21:32 INFO orm.CompilationManager: Writing jar file: /tmp/sqoop-acadgild/compile/2e7e412a7c900121d658a47478733800/top_10_stations.jar
18/12/09 16:21:32 INFO mapreduce.ExportJobBase: Beginning export of top_10_stations
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
18/12/09 16:21:33 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
18/12/09 16:21:34 INFO Configuration.deprecation: mapred.jar is deprecated. Instead, use mapreduce.job.jar
18/12/09 16:21:41 INFO Configuration.deprecation: mapred.reduce.tasks.speculative.execution is deprecated. Instead, use mapreduce.reduce.speculative
18/12/09 16:21:41 INFO Configuration.deprecation: mapred.map.tasks.speculative.execution is deprecated. Instead, use mapreduce.map.speculative
18/12/09 16:21:41 INFO Configuration.deprecation: mapred.map.tasks is deprecated. Instead, use mapreduce.job.maps
```

Problem 1:

Determine top 10 station_id(s) where maximum number of songs were played, which were liked by unique users.

| station_id |
|------------|
| ST407 |
| ST414 |
| ST411 |
| ST402 |
| ST406 |
| ST405 |

Problem 2:

Determine total duration of songs played by each type of user, where type of user can be 'subscribed' or 'unsubscribed'. An unsubscribed user is the one whose record is either not present in Subscribed_users lookup table or has subscription_end_date earlier than the timestamp of the song played by him.

| user_type | duration |
|--------------|-----------|
| SUBSCRIBED | 93861594 |
| UNSUBSCRIBED | 105594881 |

Problem 3:

Determine top 10 connected artists. Connected artists are those whose songs are most listened by the unique users who follow them.

| artist_id |
|-----------|
| A303 |
| A302 |
| A300 |

Problem 4:

Determine top 10 songs who have generated the maximum revenue. Royalty applies to a song only if it was liked or was completed successfully or both

| song_id |
|---------|
| S208 |
| S207 |
| S206 |
| S209 |
| S200 |
| S204 |
| S202 |
| S205 |

Problem 5:

Determine top 10 unsubscribed users who listened to the songs for the longest duration.

| user_id |
|---------|
| U117 |
| U118 |
| U110 |
| U120 |
| U115 |
| U107 |
| U108 |
| U109 |
| U106 |
| U100 |

We could see below that all tables have also been created in the Hive :

```
hive> use project;
OK
Time taken: 0.098 seconds
hive> show tables;
OK
connected_artists
enriched_data
formatted_input
song_artist_map
station_geo_map
subscribed_users
top_10_royalty_songs
top_10_stations
top_10_unsubscribed_users
users_artists
users_behaviour
Time taken: 0.407 seconds, Fetched: 11 row(s)
hive>
```

We have also verified that all the spark queries creating the tables for each query. So Data Analysis using Spark is executed successfully.

The data analysis result is shown in the Hive tables below in the screen shot:

Below is the output of **top_10_stations** table:

```
hive> Select * From top_10_stations;
OK
top_10_stations.station_id    top_10_stations.total_distinct_songs_played    top_10_stations.distinct_user_count    top_10_stations.batchid
ST407 2 3 1
ST414 1 1 1
ST411 1 1 1
ST402 1 2 1
ST406 1 1 1
ST405 1 1 1
Time taken: 0.336 seconds, Fetched: 6 row(s)
```

Below is the output of **users_behaviour** table:

```
hive> Select * From users_behaviour;
OK
users_behaviour.user_type    users_behaviour.duration    users_behaviour.batchid
SUBSCRIBED 93861594 1
UNSUBSCRIBED 105594881 1
Time taken: 0.274 seconds, Fetched: 2 row(s)
```

Below is the output of **connected_artists** table:

```
hive> Select * From connected_artists;
OK
connected_artists.artist_id    connected_artists.user_count    connected_artists.batchid
A303 2 1
A302 2 1
A300 1 1
Time taken: 0.225 seconds, Fetched: 3 row(s)
```


Below is the output of **top_10_royalty_songs** table:

```
hive> Select * From top_10_royalty_songs;
OK
top_10_royalty_songs.song_id    top_10_royalty_songs.duration    top_10_royalty_songs.batchid
S208      22627294      1
S207      20000000      1
S206      19900000      1
S209      15254588      1
S200      9900000 1
S204      2604333 1
S202      100000 1
S205      0 1
Time taken: 0.237 seconds, Fetched: 8 row(s)
```

Below is the output of **top_10_unsubscribed_users** table:

```
hive> Select * From top_10_unsubscribed_users;
OK
top_10_unsubscribed_users.user_id    top_10_unsubscribed_users.duration    top_10_unsubscribed_users.batchid
U117      20000000      1
U118      20000000      1
U110      20000000      1
U120      12627294      1
U115      12527294      1
U107      10000000      1
U108      5231627 1
U109      2604333 1
U106      2604333 1
U100      0 1
```

Now we need to export all the data to the MYSQL using sqoop, by executing **data_export.sh** script file:

By using **data_export.sh** script file, we are going to export the data from the hive tables into mysql using Sqoop export.

```
#!/bin/bash

batchid=`cat /home/acadgild/examples/music/logs/current-
batch.txt`
LOGFILE=/home/acadgild/examples/music/logs/log_batch_${batchid}

echo "Creating mysql tables if not present..." >> $LOGFILE

mysql -u root -pRoot@123

</home/acadgild/examples/music/create_schema.sql

echo "Running sqoop job for data export..." >> $LOGFILE

sqoop export \

--connect
jdbc:mysql://localhost/project \ -
-username 'root' \

--password 'Root@123' \
```



```

--table 'top_10_stations' \
--export-dir

'/user/hive/warehouse/project.db/top_10_stations/batchid=$batchid/part-00000' \
--input-fields-terminated-by ',' \
-m 1

sqoop export \
--connect
jdbc:mysql://localhost/project \ -
-username 'root' \

--password 'Root@123' \
--table 'song_duration' \
--export-dir

'/user/hive/warehouse/project.db/users_behaviour/batchid=$batchid/part-00000' \
--input-fields-terminated-by ',' \
-m 1

sqoop export \

--connect
jdbc:mysql://localhost/project \ -
-username 'root' \

--password 'Root@123' \
--table 'connected_artists' \
--export-dir

'/user/hive/warehouse/project.db/connected_artists/batchid=$batchid/part-00000' \
--input-fields-terminated-by ',' \
-m 1

```

```
sqoop export \  
  
--connect  
jdbc:mysql://localhost/project \ -  
-username 'root' \  
  
--password 'Root@123' \  
--table 'top_10_royalty_songs' \  
--export-dir  
  
'/user/hive/warehouse/project.db/top_10_royalty_songs/batchid=  
$batchid/part  
-00000' \  
--input-fields-terminated-by ',' \  
-m 1
```

```
sqoop export \  
  
--connect  
jdbc:mysql://localhost/project \ -  
-username 'root' \  
  
--password 'Root@123' \  
--table 'top_10_unsubscribed_users' \  
--export-dir  
  
'/user/hive/warehouse/project.db/top_10_unsubscribed_users/bat  
chid=$batchid  
/part-00000' \  
--input-fields-terminated-by ',' \  
-m 1
```

Below schema will create the database and tables in the MySQL:

create_schema.sql file :

```
CREATE DATABASE IF NOT EXISTS project;  
  
USE project;  
  
CREATE TABLE IF NOT EXISTS top_10_stations  
(  
    station_id VARCHAR(50),  
    total_distinct_songs_played INT,  
    distinct_user_count INT  
);  
  
CREATE TABLE IF NOT EXISTS  
song_duration (  
    user_id VARCHAR(50),  
    user_type VARCHAR(50),  
    song_id VARCHAR(50),  
    artist_id VARCHAR(50),  
    total_duration DOUBLE  
);  
  
CREATE TABLE IF NOT EXISTS  
connected_artists (  
    artist_id VARCHAR(50),  
    total_distinct_songs INT,  
    user_count INT  
);  
  
CREATE TABLE IF NOT EXISTS  
top_10_royalty_songs (  
    song_id VARCHAR(50),  
    artist_id VARCHAR(50),  
    duration DOUBLE  
);
```

```
CREATE TABLE IF NOT EXISTS
top_10_unsubscribed_users (
user_id VARCHAR(50),
song_id VARCHAR(50),
artist_id VARCHAR(50),
duration DOUBLE
);
```

Below we could see that data exported successfully into the MYSQL Database for all the 5 queries:

The sqoop export command exported the tables from the hive and it stored in the Mysql. The below screen shot show the successful Sqoop export from hive to mysql. The data stored in the Mysql is shown in below screenshots:

```
Warning: /home/acadgild/install/sqoop/sqoop-1.4.6.bin_hadoop-2.0.4-alpha../hcatalog does not exist! HCatalog jobs will fail.
Please set $HCAT_HOME to the root of your HCatalog installation.
Warning: /home/acadgild/install/sqoop/sqoop-1.4.6.bin_hadoop-2.0.4-alpha../accumulo does not exist! Accumulo imports will fail.
Please set $ACCUMULO_HOME to the root of your Accumulo installation.
18/12/09 16:21:09 INFO sqoop.Sqoop: Running Sqoop version: 1.4.6
18/12/09 16:21:09 WARN tool.BaseSqoopTool: Setting your password on the command-line is insecure. Consider using -P instead.
18/12/09 16:21:10 INFO manager.MySQLManager: Preparing to use a MySQL streaming resultset.
18/12/09 16:21:10 INFO tool.CodeGenTool: Beginning code generation
Sun Dec 09 16:21:12 IST 2018 WARN: Establishing SSL connection without server's identity verification is not recommended. According to My
SQL 5.5.45+, 5.6.26+ and 5.7.6+ requirements SSL connection must be established by default if explicit option isn't set. For compliance w
ith existing applications not using SSL the verifyServerCertificate property is set to 'false'. You need either to explicitly disable SSL
by setting useSSL=false, or set useSSL=true and provide truststore for server certificate verification.
18/12/09 16:21:19 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM 'top_10_stations' AS t LIMIT 1
18/12/09 16:21:19 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM 'top_10_stations' AS t LIMIT 1
18/12/09 16:21:19 INFO orm.CompilationManager: HADOOP_MAPRED_HOME is /home/acadgild/install/hadoop/hadoop-2.6.5
Note: /tmp/sqoop-acadgild/compile/2e7e412a7c900121d658a47478733800/top_10_stations.java uses or overrides a deprecated API.
Note: Recompile with -Xlint:deprecation for details.
18/12/09 16:21:32 INFO orm.CompilationManager: Writing jar file: /tmp/sqoop-acadgild/compile/2e7e412a7c900121d658a47478733800/top_10_stat
ions.jar
18/12/09 16:21:32 INFO mapreduce.ExportJobBase: Beginning export of top_10_stations
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/i
mpl/StaticLoggerBinder.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder
.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.
SLF4J: Actual binding is of type [org.slf4j.impl.Log4jLoggerFactory]
18/12/09 16:21:33 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where
applicable
18/12/09 16:21:34 INFO Configuration.deprecation: mapred.jar is deprecated. Instead, use mapreduce.job.jar
18/12/09 16:21:41 INFO Configuration.deprecation: mapred.reduce.tasks.speculative.execution is deprecated. Instead, use mapreduce.reduce.
speculative
18/12/09 16:21:41 INFO Configuration.deprecation: mapred.map.tasks.speculative.execution is deprecated. Instead, use mapreduce.map.specul
ative
```

```
18/12/09 16:21:54 INFO mapreduce.Job: Running job: job_1544335926739_0007
18/12/09 16:22:51 INFO mapreduce.Job: Job job_1544335926739_0007 running in uber mode : false
18/12/09 16:22:51 INFO mapreduce.Job: map 0% reduce 0%
18/12/09 16:23:32 INFO mapreduce.Job: map 100% reduce 0%
18/12/09 16:23:33 INFO mapreduce.Job: Job job_1544335926739_0007 completed successfully
18/12/09 16:23:34 INFO mapreduce.Job: Counters: 30
File System Counters
  FILE: Number of bytes read=0
  FILE: Number of bytes written=127642
  FILE: Number of read operations=0
  FILE: Number of large read operations=0
  FILE: Number of write operations=0
  HDFS: Number of bytes read=266
  HDFS: Number of bytes written=0
  HDFS: Number of read operations=4
  HDFS: Number of large read operations=0
  HDFS: Number of write operations=0
Job Counters
  Launched map tasks=1
  Data-local map tasks=1
  Total time spent by all maps in occupied slots (ms)=34906
  Total time spent by all reduces in occupied slots (ms)=0
  Total time spent by all map tasks (ms)=34906
  Total vcore-milliseconds taken by all map tasks=34906
  Total megabyte-milliseconds taken by all map tasks=35743744
Map-Reduce Framework
  Map input records=5
  Map output records=5
  Input split bytes=213
  Spilled Records=0
  Failed Shuffles=0
  Merged Map outputs=0
  GC time elapsed (ms)=322
  CPU time spent (ms)=7550
  Physical memory (bytes) snapshot=121122816
  Virtual memory (bytes) snapshot=2061332480
```

```

Total committed heap usage (bytes)=62980096
File Input Format Counters
  Bytes Read=0
File Output Format Counters
  Bytes Written=0
18/12/09 16:23:34 INFO mapreduce.ExportJobBase: Transferred 266 bytes in 112.788 seconds (2.3584 bytes/sec)
18/12/09 16:23:34 INFO mapreduce.ExportJobBase: Exported 5 records.
Warning: /home/acadgild/install/sqoop/sqoop-1.4.6.bin_hadoop-2.0.4-alpha../hcatalog does not exist! HCatalog jobs will fail.
Please set $HCAT_HOME to the root of your HCatalog installation.
Warning: /home/acadgild/install/sqoop/sqoop-1.4.6.bin_hadoop-2.0.4-alpha../accumulo does not exist! Accumulo imports will fail.
Please set $ACCUMULO_HOME to the root of your Accumulo installation.
18/12/09 16:23:44 INFO sqoop.Sqoop: Running Sqoop version: 1.4.6
18/12/09 16:23:44 WARN tool.BaseSqoopTool: Setting your password on the command-line is insecure. Consider using -P instead.
18/12/09 16:23:46 INFO manager.MySQLManager: Preparing to use a MySQL streaming resultset.
18/12/09 16:23:46 INFO tool.CodeGenTool: Beginning code generation
Sun Dec 09 16:23:47 IST 2018 WARN: Establishing SSL connection without server's identity verification is not recommended. According to MySQL 5.5.45+, 5.6.26+ and 5.7.6+ requirements SSL connection must be established by default if explicit option isn't set. For compliance with existing applications not using SSL the verifyServerCertificate property is set to 'false'. You need either to explicitly disable SSL by setting useSSL=false, or set useSSL=true and provide truststore for server certificate verification.
18/12/09 16:23:53 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM 'song_duration' AS t LIMIT 1
18/12/09 16:23:53 INFO manager.SqlManager: Executing SQL statement: SELECT t.* FROM 'song_duration' AS t LIMIT 1
18/12/09 16:23:53 INFO orm.CompilationManager: HADOOP_MAPRED_HOME is /home/acadgild/install/hadoop/hadoop-2.6.5
Note: /tmp/sqoop-acadgild/compile/b6353bd5b73c4f37c3f559414c34192f/song_duration.java uses or overrides a deprecated API.
Note: Recompile with -Xlint:deprecation for details.
18/12/09 16:24:18 INFO orm.CompilationManager: Writing jar file: /tmp/sqoop-acadgild/compile/b6353bd5b73c4f37c3f559414c34192f/song_duration.jar
18/12/09 16:24:18 INFO mapreduce.ExportJobBase: Beginning export of song_duration
SLF4J: Class path contains multiple SLF4J bindings.
SLF4J: Found binding in [jar:file:/home/acadgild/install/hadoop/hadoop-2.6.5/share/hadoop/common/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder.class]
SLF4J: Found binding in [jar:file:/home/acadgild/install/hbase/hbase-1.2.6/lib/slf4j-log4j12-1.7.5.jar!/org/slf4j/impl/StaticLoggerBinder.class]
SLF4J: See http://www.slf4j.org/codes.html#multiple_bindings for an explanation.

```

The **project** database had been exported from hive (HDFS) and the below screen shot shows all tables:

```

mysql> use project;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
+-----+
| Tables_in_project |
+-----+
| connected_artists |
| song_duration      |
| top_10_royalty_songs |
| top_10_stations    |
| top_10_unsubscribed_users |
+-----+
5 rows in set (0.02 sec)

```

Output from **top_10_stations** table in mysql is shown below:

```

mysql> Select * From top_10_stations;
+-----+-----+-----+
| station_id | total_distinct_songs_played | distinct_user_count |
+-----+-----+-----+
| ST407      | 2 | 3 |
| ST414      | 1 | 1 |
| ST411      | 1 | 1 |
| ST402      | 1 | 2 |
| ST406      | 1 | 1 |
| ST405      | 1 | 1 |
+-----+-----+-----+
6 rows in set (0.00 sec)

```


Output from **users_behaviour** table in mysql is shown below:

```
mysql> Select * From users_behaviour;
```

| user_type | duration |
|--------------|-----------|
| SUBSCRIBED | 93861594 |
| UNSUBSCRIBED | 105594881 |

2 rows in set (0.00 sec)

Output from **connected_artists** table in mysql is shown below:

```
mysql> Select * From connected_artists;
```

| artist_id | user_count |
|-----------|------------|
| A303 | 2 |
| A302 | 2 |
| A300 | 1 |

3 rows in set (0.00 sec)

Output from **top_10_royalty_songs** table in mysql is shown below:

```
mysql> Select * From top_10_royalty_songs;
```

| song_id | duration |
|---------|----------|
| S208 | 22627294 |
| S207 | 20000000 |
| S206 | 19900000 |
| S209 | 15254588 |
| S200 | 9900000 |
| S204 | 2604333 |
| S202 | 100000 |
| S205 | 0 |

8 rows in set (0.00 sec)

Output from **top_10_unsubscribed_users** table in mysql is shown below:

```
mysql> Select * From top_10_unsubscribed_users;
```

| user_id | duration |
|---------|----------|
| U117 | 20000000 |
| U118 | 20000000 |
| U110 | 20000000 |
| U120 | 12627294 |
| U115 | 12527294 |
| U107 | 10000000 |
| U108 | 5231627 |
| U109 | 2604333 |
| U106 | 2604333 |
| U100 | 0 |

10 rows in set (0.01 sec)

Job Scheduling :

Now after exporting data into MySQL, **batchid** will be incremented to additional 1 means one batch of data operations is successfully completed and new batch of data will be loaded for the analysis after every 3 hours.

Part of Data analysis.sh file :

```
sh /home/acadgild/examples/music/data_export.sh

echo "Incrementing batchid..." >> $LOGFILE

batchid=`expr $batchid + 1`

echo -n $batchid >/home/acadgild/examples/music/logs/current-
batch.txt
```

We can check logs to track the behaviour of the operations we have done on the data and overcome failures (if any) we could see the **batchid** gets incremented by 1 in **current-batch.txt**

```
[acadgild@localhost logs]$ pwd
/home/acadgild/examples/music/logs
[acadgild@localhost logs]$ ls -ls
total 52
4 -rwxrwxr-x. 1 acadgild acadgild  2 Dec  9 17:18 current-batch.txt
4 -rw-rw-r--. 1 acadgild acadgild 522 Dec  9 16:21 log batch 1

[acadgild@localhost logs]$ cat current-batch.txt
2
```

Conclusion:

Hence all the use cases and analysis of Music company has been completed.