



CS23336-Introduction to Python Programming

Started on Monday, 21 October 2024, 10:44 PM

State Finished

Completed on Wednesday, 23 October 2024, 1:48 PM

Time taken 1 day 15 hours

Marks 10.00/10.00

Grade **100.00** out of 100.00

Question 1

Correct

Mark 1.00 out of 1.00

☐ Flag question

Question text

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

- For example, "ACGAATTCCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string `s` that represents a **DNA sequence**, return all the **10-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

Example 1:

Input: `s = "AAAAACCCCCAAAAACCCCCAAAAAGGGTTT"`

Output: `["AAAAACCCCC", "CCCCAAAAA"]`

Example 2:

Input: `s = "AAAAAAAAAAAAA"`

Output: `["AAAAAAAAA"]`

For example:

Input

Result

AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCAAAAA
---------------------------------	-------------------------

Answer:(penalty regime: 0 %)

```
s=input()
n=set()
p=set()
for i in range(len(s)-9):
    c=s[i:i+10]
    if c in n:
        p.add(c)
    else:
        n.add(c)
s=list(p)
for i in range(len(s)):
    print(s[i])
```

Feedback

Input	Expected	Got
AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC AAAAACCCCC CCCCCAAAAA CCCCCAAAAA	
AAAAAAAAAAAAA	AAAAAAAAAA AAAAAAAAAA	

Passed all tests!


Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of 1.00

☐  Flag question

Question text

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1


```
import re
a=input()
a=a.lower()
b=input()
b=b.lower()
c=re.findall(r'[a-z]+' ,a)
d=re.findall(r'[a-z]',b)
res=0
for i in d:
    for j in c:
        if i not in j:
            pass
        else:
            c.remove(j)
print(len(c))
```

Feedback

Input	Expected Got	
hello world ad	1	1
Welcome to REC e	1	1
Faculty Upskilling in Python Programming ak	2	2

Passed all tests!
Correct
Marks for this submission: 1.00/1.00.

Question 3

Correct
Mark 1.00 out of 1.00
☐  Flag question

Question text

Given an array of integers nums containing n + 1 integers where each integer is in the range [1, n] inclusive. There is only **one repeated number** in nums, return *this repeated number*. Solve the problem using set.

Example 1:

Input: nums = [1,3,4,2,2]
Output: 2

Example 2:

Input: nums = [3,1,3,4,2]
Output: 3

For example:

Input	Result
1 3 4 4 2 4	

Answer:(penalty regime: 0 %)

```

a=input()
a=tuple(a)
n=tuple(i for i in a if
i.strip())
b=set(a)
for i in b:
    if n.count(i)>=2:
        print(i)
        break

```

Feedback

Input	Expected	Got
1 3 4 4 2	4	4
1 2 2 3 4 5 6 7 2	2	2

Passed all tests!


Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of 1.00

☐  Flag question

Question text

You are given an integer tuple `nums` containing distinct numbers. Your task is to perform a sequence of operations on this tuple until it becomes empty. The operations are defined as follows:

1. If the first element of the tuple has the smallest value in the entire tuple, remove it.
2. Otherwise, move the first element to the end of the tuple.

You need to return an integer denoting the number of operations required to make the tuple empty.

Constraints

- The input tuple `nums` contains distinct integers.
- The operations must be performed using tuples and sets to maintain immutability and efficiency.
- Your function should accept the tuple `nums` as input and return the total number of operations as an integer.

Example:

Input: `nums = (3, 4, -1)`

Output: 5

Explanation:

Operation 1: `[3, 4, -1]` -> First element is not the smallest, move to the end -> `[4, -1, 3]`

Operation 2: `[4, -1, 3]` -> First element is not the smallest, move to the end -> `[-1, 3, 4]`

Operation 3: `[-1, 3, 4]` -> First element is the smallest, remove it -> `[3, 4]`

Operation 4: `[3, 4]` -> First element is the smallest, remove it -> `[4]`

Operation 5: `[4]` -> First element is the smallest, remove it -> `[]`

Total operations: 5

For example:

Test

Result

```
print(count_operations((3, 4, -1))) 5
```

Answer:(penalty regime: 0 %)

```
def
count_operations(nu
ms: tuple) -> int:
    # Your
implementation here
    op=0
    nums=list(nums)
    while len(nums):
        if
nums[0]==min(num
s):

nums.remove(nums[
0])

        op+=1
    else:
        t=nums[0]
```

Reset answer

Feedback

Test	Expected Got	
print(count_operations((3, 4, -1)))	5	5
print(count_operations((1, 2, 3, 4, 5)))	5	5
print(count_operations((5, 4, 3, 2, 1)))	15	15
print(count_operations((42,)))	1	1
print(count_operations((-2, 3, -5, 4, 1)))	11	11

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 5

Correct
Mark 1.00 out of 1.00
☐ Flag question

Question text

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.
The next two lines contain the space-separated integer arrays to be compared.

[Sample](#) Input:

```
5 4
1 2 8 6 5
2 6 8 10
```

[Sample](#) Output:

```
1 5 10
```

3

[Sample](#) Input:

5 5

1 2 3 4 5

1 2 3 4 5

[Sample](#) Output:

NO SUCH ELEMENTS

For example:

Input	Result
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3
5 5 1 2 3 4 5 1 2 3 4 5	NO SUCH ELEMENTS

Answer:(penalty regime: 0 %)

```
import re
a=input()
b=input()
c=input()
b=(re.findall(r'[0-9]+' ,b))
c=(re.findall(r'[0-9]+' ,c))
b=set(b)
c=set(c)
d=b^c
b={0}
for i in d:
    b.add(int(i))
b.discard(0)
b=list(b)
b.sort()
if len(b)==0:
```

Feedback

Input	Expected	Got
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3	1 5 10 3
3 3 10 10 10 10 11 12	11 12 2	11 12 2
5 5 1 2 3 4 5 1 2 3 4 5	NO SUCH ELEMENTS	NO SUCH ELEMENTS

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.








Question 6

Question text

Given an array of strings `words`, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the **American keyboard**:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".

~ 1	! 2	@ 3	# 4	\$ 5	% 6	^ 7	& 8	* 9	(0) -	+ =	 Backspace	
Tab  	Q	W	E	R	T	Y	U	I	O	P	{ [}]	 \ _
Caps Lock 	A	S	D	F	G	H	J	K	L	: ;	" '	Enter 	
Shift 		Z	X	C	V	B	N	M	< ,	> .	? /	Shift 	
Ctrl	Win Key	Alt								Alt	Win Key	Menu	Ctrl

Example 1:

Input: words = ["Hello","Alaska","Dad","Peace"]
Output: ["Alaska","Dad"]

Example 2:

Input: words = ["omk"]
Output: []

Example 3:

Input: words = ["adsdf","sfd"]
Output: ["adsdf","sfd"]

For example:

Input Result

```
4
Hello
Alaska
Alaska
Dad
Peace
```

```
2
adsdf adsdf
afd afd
```

Answer:(penalty regime: 0 %)

```
a=int(input())
b=()
b=list(b)
r1=
{'q','w','e','r','t','y','u',
'i','o','p'}
r2=
{'a','s','d','f','g','h','j',
'k','l'}
r3=
{'z','x','c','v','b','n','
m'}
for i in range(a):
    c=input()
    f=set(c.lower())
    if f.issubset(r1):
        b.append(c)
    elif f.issubset(r2):
```

Feedback

Input Expected Got

4		
Hello	Alaska	Alaska
Alaska	Dad	Dad
Dad		
Peace		

1		
omk	No words	No words

2		
adsfd	adsfd	adsfd
afd	afd	afd

Passed all tests!


Correct

Marks for this submission: 1.00/1.00.

Question 7

Correct

Mark 1.00 out of 1.00

☐  Flag question

Question text

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1 2 2 3 4

Output:

1 2 3 4

Example Input:

6
1 1 2 2 3 3

Output:

1 2 3

For example:

Input Result

5
1
2 1 2 3 4
2
3
4

Answer:(penalty regime: 0 %)

```
a=int(input())
b=[]
for i in range(a):
    f=int(input())
    b.append(f)
c=set(b)
b=tuple(c)
print(*b)
```

Feedback

Input Expected Got

5
1
2 1 2 3 4 1 2 3 4
2
3
4

6
1
1
2 1 2 3 1 2 3
2
3
3

5
11
22 11 22 11 22
11
22
11


10
1
2
3

4
5 1 2 3 4 5 1 2 3 4 5
1
2
3
4
5

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 8

Correct
Mark 1.00 out of 1.00
☐  Flag question

Question text

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

For example:

Input	Result
01010101010	Yes
010101 10101	No

Answer:(penalty regime: 0 %)

```
a=input()
b=set(a)
c={'1','0'}
if c==b:
    print("Yes")
else:
    print("No")
```

Feedback


Input	Expected	Got
01010101010	Yes	Yes

REC123	No	No
010101 10101	No	No

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 9

Correct
Mark 1.00 out of 1.00
☐  Flag question

Question text

Check if a set is a subset of another set.

Example:

Sample Input1:

mango apple
mango orange
mango

output1:

yes

set3 is subset of set1 and set2

input2:

mango orange
banana orange
grapes

output2:

no



For example:

Test	Input	Result
1	mango apple mango orange mango	yes set3 is subset of set1 and set2
2	mango orange banana orange grapes	No

Answer:(penalty regime: 0 %)

```
s1=set(input().strip().split())
s2=set(input().strip().split())
s3=set(input().strip().split())
if s3.issubset(s1) and s3.issubset(s2):
    print('yes')
    print("set3 is subset of set1 and set2")
else:
    print('No')
```

Feedback

Test	Input	Expected	Got
1	mango apple mango orange mango	yes set3 is subset of set1 and set2	yes set3 is subset of set1 and set2
2	mango orange banana orange grapes	No	No

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 10

Correct
Mark 1.00 out of 1.00
☐ Flag question

Question text

Given a tuple and a positive integer k, the task is to find the count of distinct pairs in the tuple whose sum is equal to **K**.

Examples:

Input: t = (5, 6, 5, 7, 7, 8), K = 13
Output: 2
Explanation:
Pairs with sum K(= 13) are { (5, 8), (6, 7), (6, 7) }.
Therefore, distinct pairs with sum K(= 13) are { (5, 8), (6, 7) }.
Therefore, the required output is 2.

For example:

Input	Result
1,2,1,2,5 3	1
1,2 0	0

Answer:(penalty regime: 0 %)

```
a=input()
b=int(input())
a=set(a)
a.remove(',')
a=tuple(a)
res=0
for i in a:
    for j in
range(a.index(i),len(a)
):
    if
int(i)+int(a[j])==b:
        res+=1
print(res)
```

Feedback

Input	Expected	Got
5,6,5,7,7,8 13	2	2
1,2,1,2,5 3	1	1
1,2 0	0	0

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Save the state of the flags

[Finish review](#)
[Skip Quiz navigation](#)

Quiz navigation

[Question 1 This page](#) [Question 2 This page](#) [Question 3 This page](#) [Question 4 This page](#) [Question 5 This page](#) [Question 6 This page](#) [Question 7 This page](#) [Question 8 This page](#) [Question 9 This page](#) [Question 10 This page](#) [Show one page at a time](#)[Finish review](#)