



CS23336-Introduction to Python Programming

Started on Wednesday, 4 September 2024, 2:16 PM

State Finished

Completed on Wednesday, 4 September 2024, 2:39 PM

Time taken 23 mins 34 secs

Marks 5.00/5.00

Grade **100.00** out of 100.00

Question 1

Correct

Mark 1.00 out of 1.00

☐ Flag question

Question text

complete function to implement coin change making problem i.e. finding the minimum number of coins of certain denominations that add up to given amount of money.

The only available coins are of values 1, 2, 3, 4

Input Format:

Integer input from stdin.

Output Format:

return the minimum number of coins required to meet the given target.

Example Input:

16

Output:

4

Explanation:

We need only 4 coins of value 4 each

Example Input:

25

Output:

7

Explanation:

We need 6 coins of 4 value, and 1 coin of 1 value

Answer:(penalty regime: 0 %)

```
def coinChange(n):
    c=0
    coin=[4,3,2,1]
    for i in coin:
        while(n>=i):
            n-=i
            c=c+1
    return c
```

Reset answer

Feedback

Test

Expected Got

print(coinChange(16)) 4

4

Passed all tests!


Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of 1.00

☐  Flag question

Question text

A strobogrammatic number is a number that looks the same when rotated 180 degrees (looked at upside down).

Write a program to determine if a number is strobogrammatic. The number is represented as a string.

Example 1:

Input:

69

Output:

true

Example 2:

Input:

88

Output:

true

Example 3:

Input:

962

Output:

false

Example 4:

Input:

1

Output:

true

For example:

| Test | Result |
|-----------------------------|--------|
| print(Strobogrammatic(69)) | true |
| print(Strobogrammatic(962)) | false |

Answer:(penalty regime: 0 %)

```
def
Strobogrammatic(n):
    n=str(n)
    r=
    {'0':'0','1':'1','6':'9','8':
'8','9':'6'}
    for i in
range(len(n)//2+1):
        if n[i] not in r or
r[n[i]]!=n[-i-1]:
            return "false"
    return "true"
```

Reset answer


Feedback

| Test | Expected | Got |
|-----------------------------|----------|-------|
| print(Strobogrammatic(69)) | true | true |
| print(Strobogrammatic(88)) | true | true |
| print(Strobogrammatic(962)) | false | false |

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 3

Correct
Mark 1.00 out of 1.00
☐  Flag question

Question text

An e-commerce company plans to give their customers a special discount for Christmas. They are planning to offer a flat discount. The discount value is calculated as the sum of all the prime digits in the total bill amount.

Write an algorithm to find the discount value for the given total bill amount.

Constraints

1 <= orderValue< 10e100000

Input

The input consists of an integer orderValue, representing the total bill amount.

Output

Print an integer representing the discount value for the given total bill amount.

Example Input

578

Output

12

For example:

| Test | Result |
|-------------------------------|--------|
| print(christmasDiscount(578)) | 12 |

Answer:(penalty regime: 0 %)

```
def
christmasDiscount(n):
    c=0
    while(n>=1 and
n<=10**100000):
        for i in str(n):
            if i in'2357':
                c=c+int(i)
        return c
```

Reset answer

Feedback

| Test | Expected Got |
|-------------------------------|--------------|
| print(christmasDiscount(578)) | 12 |

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 4

Correct
Mark 1.00 out of 1.00
☐ Flag question

Question text

Write a function that returns the value of a+aa+aaa+aaaa with a given digit as the value of a.
Suppose the following input is supplied to the program:

Then, the output should be:

9+99+999+9999=11106

Sample Input Format:

9

Sample Output format:

11106

For example:

| Test | Result |
|--------------------------------|---|
| <pre>print(Summation(8))</pre> | 9872 |
| Answer:(penalty regime: 0 %) | |
| | <pre>def Summation(n): a1=int(str(n)) a2=int(str(n)*2) a3=int(str(n)*3) a4=int(str(n)*4) return a1+a2+a3+a4</pre> |
| <div>Reset answer</div> | |

Feedback

| Test | Expected | Got |
|---------------------------------|----------|----------|
| <pre>print(Summation(8))</pre> | 9872 | 9872 |
| <pre>print(Summation(10))</pre> | 10203040 | 10203040 |

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 5

Correct
Mark 1.00 out of 1.00
☐ Flag question

Question text

A number is considered to be ugly if its only prime factors are 2, 3 or 5.
[1, 2, 3, 4, 5, 6, 8, 9, 10, 12, 15, ...] is the sequence of ugly numbers.

Task:

complete the function which takes a number n as input and checks if it's an ugly number.

return ugly if it is ugly, else return not ugly

Hint:

An ugly number U can be expressed as: $U = 2^a * 3^b * 5^c$, where a, b and c are nonnegative integers.

For example:

| Test | Result |
|----------------------|----------|
| print(checkUgly(6)) | ugly |
| print(checkUgly(21)) | not ugly |

Answer:(penalty regime: 0 %)

```
def checkUgly(n):
    if n<0:
        return "not ugly"
    for p in [2,3,5]:
        while n%p==0:
            n=n//p
    if n==1:
        return "ugly"
    else:
        return "not ugly"
```

Reset answer

Feedback

| Test | Expected | Got |
|----------------------|----------|----------|
| print(checkUgly(6)) | ugly | ugly |
| print(checkUgly(21)) | not ugly | not ugly |

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Save the state of the flags

[Finish review](#)
[Skip Quiz navigation](#)

Quiz navigation

[Question 1 This page](#) [Question 2 This page](#) [Question 3 This page](#) [Question 4 This page](#) [Question 5 This page](#)
[Show one page at a time](#)[Finish review](#)