

Rajalakshmi Engineering College

Name: Barath Raj
Email: 240701072@rajalakshmi.edu.in
Roll no: 240701072
Phone: 7200902489
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. The value of the expressions $4/(3*(2-1))$ and $4/3*(2-1)$ is the same.
True or False?

Answer

True

Status : Correct

Marks : 1/1

2. Which of the following operators has its associativity from right to left?

Answer

**

Status : Correct

Marks : 1/1

3. What is the output of the following program?

```
print((1, 2) + (3, 4))
```

Answer

(1, 2, 3, 4)

Status : Correct

Marks : 1/1

4. Which of the following can convert the string to a float number?

Answer

```
float(str)
```

Status : Correct

Marks : 1/1

5. What is the output of the following number conversion?

```
z = complex(1.25)  
print(z)
```

Answer

(1.25+0j)

Status : Correct

Marks : 1/1

6. Which of the following functions converts a string to a float in Python?

Answer

```
int(x [,base])
```

Status : Wrong

Marks : 0/1

7. What is the output of the below expression?

```
print(3*1**3)
```

Answer

3

Status : Correct

Marks : 1/1

8. Evaluate the expression given below if A= 16 and B = 15

`A % B // A`

Answer

0

Status : Correct

Marks : 1/1

9. What is used to concatenate two strings in Python?

Answer

+ operator

Status : Correct

Marks : 1/1

10. What is the value of the following expression?

`float(22//3+3/3)`

Answer

8.0

Status : Correct

Marks : 1/1

11. What will the following code output?

```
z = 3 + 4j
print(abs(z))
```

Answer

5.0

Status : Correct

Marks : 1/1

12. What is the return type of the function id?

Answer

int

Status : Correct

Marks : 1/1

13. Which is the correct operator for power(xy)?

Answer

x**y

Status : Correct

Marks : 1/1

14. What is the value of the following expression?

8/4/2, 8/(4/2)

Answer

(1.0,4.0)

Status : Correct

Marks : 1/1

15. Which of the following represents the bitwise XOR operator?

Answer

^

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Barath Raj
Email: 240701072@rajalakshmi.edu.in
Roll no: 240701072
Phone: 7200902489
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_COD

Attempt : 1
Total Mark : 5
Marks Obtained : 4.75

Section 1 : Coding

1. Problem Statement

Bob, the owner of a popular bakery, wants to create a special offer code for his customers. To generate the code, he plans to combine the day of the month with the number of items left in stock.

Help Bob to encode these two values into a unique offer code.

Note: Use the bitwise operator to calculate the offer code.

Example

Input:

15
9

Output:

Offer code: 6

Explanation:

Given the day of the month 15th day (binary 1111) and there are 9 items left (binary 1001), the offer code is calculated as 0110 which is 6.

Input Format

The first line of input consists of an integer D, representing the day of the month.

The second line consists of an integer S, representing the number of items left in stock.

Output Format

The output displays "Offer code: " followed by an integer representing the encoded offer code.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

9

Output: Offer code: 6

Answer

```
a=int(input())
b=int(input())
print("Offer code: ",a^b)
```

Status : Correct

Marks : 1/1

2. Problem Statement

Quentin, a mathematics enthusiast, is exploring the properties of numbers. He believes that for any set of four consecutive integers, calculating the

average of their fourth powers and then subtracting the product of the first and last numbers yields a constant value.

To validate his hypothesis, check if the result is indeed constant and display.

Example:

Input:

5

Output:

Constant value: 2064.5

Explanation:

Find the Average:

Average: $(625 + 1296 + 2401 + 4096)/4 = 2104.5$

Now, we calculate the product of a and $(a + 3)$:

Product = $5 \times (5 + 3) = 5 \times 8 = 40$

Final result: $2104.5 - 40 = 2064.5$

Input Format

The input consists of an integer a , representing the first of four consecutive integers.

Output Format

The output displays "Constant value: " followed by the computed result based on Quentin's formula.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Output: Constant value: 2064.5

Answer

```
a=int(input())
x=a**4
y=(a+1)**4
z=(a+2)**4
i=(a+3)**4
average = (x + y + z + i)/4
p=a*(a+3)
c=average-p
print("Constant value: ",c)
```

Status : Correct

Marks : 1/1

3. Problem Statement

In a family, two children receive allowances based on the gardening tasks they complete. The older child receives an allowance rate of Rs.5 for each task, with a base allowance of Rs.50. The younger child receives an allowance rate of Rs.3 for each task, with a base allowance of Rs.30.

Your task is to calculate and display the allowances for the older and younger children based on the number of gardening tasks they complete, along with the total allowance for both children combined.

Input Format

The first line of input consists of an integer n , representing the number of chores completed by the older child.

The second line consists of an integer m , representing the number of chores completed by the youngest child.

Output Format

The first line of output displays "Older child allowance: Rs." followed by an integer representing the allowance calculated for the older sibling.

The second line displays "Younger child allowance: Rs." followed by an integer

representing the allowance calculated for the youngest sibling.

The third line displays "Total allowance: Rs." followed by an integer representing the sum of both siblings' allowances.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10

5

Output: Older child allowance: Rs.100

Younger child allowance: Rs.45

Total allowance: Rs.145

Answer

```
n=int(input())
m=int(input())
print("Older child allowance: Rs.",(n*5)+50)
print("Younger child allowance: Rs.",(m*3)+30)
print("Total allowance: Rs.",((n*5)+50)+((m*3)+30))
```

Status : Correct

Marks : 1/1

4. Problem Statement

A science experiment produces a decimal value as the result. However, the scientist needs to convert this value into an integer so that it can be used in further calculations.

Write a Python program that takes a floating-point number as input and converts it into an integer.

Input Format

The input consists of a floating point number, F.

Output Format

The output prints "The integer value of F is: {result}", followed by the integer number equivalent to the floating point number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10.36

Output: The integer value of 10.36 is: 10

Answer

```
x=float(input())
temp=int(x)
print("The integer value of ",x)
print("is :",temp)
```

Status : Correct

Marks : 1/1

5. Problem Statement

A company has hired two employees, Alice and Bob. The company wants to swap the salaries of both employees. Alice's salary is an integer value and Bob's salary is a floating-point value.

Write a program to swap their salaries and print the new salary of each employee.

Input Format

The first line of input consists of an integer N, representing Alice's salary.

The second line consists of a float value F, representing Bob's salary.

Output Format

The first line of output displays "Initial salaries:"

The second line displays "Alice's salary = N", where N is Alice's salary.

The third line of output displays "Bob's salary = F", where F is Bob's salary.

After a new line space, the following line displays "New salaries after swapping:"

The next line displays "Alice's salary = X", where X is the swapped salary.

The last line displays "Bob's salary = Y", where Y is the swapped salary.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10000

15400.55

Output: Initial salaries:

Alice's salary = 10000

Bob's salary = 15400.55

New salaries after swapping:

Alice's salary = 15400.55

Bob's salary = 10000

Answer

```
print("Initial Salaries:")
X=int(input())
Y=(input())
print("Alice's Salary = ",X)
print("Bob's Salary = ",Y)
temp=X
X=Y
Y=temp
print("\n")
print("New Salaries after swapping:")
print("Alice's Salary = ",X)
print("Bob's Salary = ",Y)
```

Status : Partially correct

Marks : 0.75/1

Rajalakshmi Engineering College

Name: Barath Raj
Email: 240701072@rajalakshmi.edu.in
Roll no: 240701072
Phone: 7200902489
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Olivia is creating a wellness dashboard for her new fitness app, FitTrack. She needs a program that can capture and display key details about a user's workout. The program should read the user's full name, the total steps they ran, the energy they expended in kilojoules, and the duration of their workout in hours. After collecting this information, the program will generate a detailed summary of the user's fitness activity.

Your task is to guide Olivia through the program.

Input Format

The first line of input consists of a string, representing the user's name.

The second line consists of an integer, representing the total steps taken.

The third line consists of a float value, representing the calories burned.

The fourth line consists of a float value, representing the workout duration in hours.

Output Format

The first line of output prints "User Name: " followed by the user's name.

The second line prints "Total Steps: " followed by the total steps.

The third line prints "Calories Burned: " followed by the calories burned, rounded off to one decimal place.

The fourth line prints "Workout Duration: X hours" where X is the workout duration, rounded off to one decimal place.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Alex

10000

350.5

1.5

Output: User Name: Alex

Total Steps: 10000

Calories Burned: 350.5

Workout Duration: 1.5 hours

Answer

```
print(input("User Name: "))
print(int(input("Total Steps: ")))
print(float(input("Calories Burned: ")))
a=float(input())
print("Workout Duration: " + str(round(a,1))+ "hours")
```

Status : Correct

Marks : 10/10

2. Problem Statement

Alex is an air traffic controller who needs to record and manage flight delays efficiently. Given a flight number, the delay in minutes (as a string), and the coordinates of the flight's current position (as a complex number),

Help Alex convert and store this information in a structured format.

Input Format

The first line of input consists of an integer N, representing the flight number.

The second line consists of a string representing the delay in minutes.

The third line consists of two floats separated by a space, representing the real and imaginary parts of the complex number for the flight's position.

Output Format

The first line of output displays the complex number.

The second line displays a string with the flight number, delay, and the real and imaginary parts of the complex number, separated by commas.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 12345

30.5

12.3 45.6

Output: (12.3+45.6j)

12345, 30.5, 12.3, 45.6

Answer

```
a=int(input())
```

```
b=input()
```

```
x,y=map(float,input().split())
```

```
d=complex(x,y)
```

```
print(d)
```

```
print(a , b , x , y , sep=",")
```

Status : Correct

Marks : 10/10

3. Problem Statement

Mandy is working on a mathematical research project involving complex numbers. For her calculations, she often needs to swap the real and imaginary parts of two complex numbers.

Mandy needs a Python program that takes two complex numbers as input and swaps their real and imaginary values.

Input Format

The first line of input consists of a complex number in the format $a+bj$, representing the first complex number.

The second line consists of a complex number in the format $a+bj$, representing the second complex number.

Output Format

The first line of output displays "New first complex number: " followed by the swapped complex number.

The second line of output displays "New second complex number: " followed by the swapped complex number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: $10+8j$

$7-9j$

Output: New first complex number: $(8+10j)$

New second complex number: $(-9+7j)$

Answer

```
a=complex(input())
```

```
b=complex(input())
```

```
real1,imag1=a.real,a.imag  
real2,imag2=b.real,b.imag  
a=complex(imag1, real1)  
b=complex(imag2, real2)  
print("New first complex number: ",a)  
print("New second complex number: ",b)
```

Status : Correct

Marks : 10/10

4. Problem Statement

John is developing a financial application to help users manage their investment portfolios. As part of the application, he needs to write a program that receives the portfolio's main value and the values of two specific investments as inputs. The program should then display these values in reverse order for clear visualization.

Help John achieve this functionality by writing the required program.

Input Format

The first line of input consists of a float, representing the first investment value.

The second line of input consists of a float, representing the second investment value.

The third line of input consists of an integer, representing the portfolio ID.

Output Format

The first line of output prints "The values in the reverse order:".

The second line prints the integer, representing the portfolio ID.

The third line prints the second float, representing the second investment value.

The fourth line prints the first float, representing the first investment value.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 35.29

9374.11

48

Output: The values in the reverse order:

48

9374.11

35.29

Answer

```
a=float(input())
```

```
b=float(input())
```

```
print("The Values in the reverse order:")
```

```
print(int(input()))
```

```
print(b)
```

```
print(a)
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: Barath Raj
Email: 240701072@rajalakshmi.edu.in
Roll no: 240701072
Phone: 7200902489
Branch: REC
Department: I CSE FA
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_PAH

Attempt : 1
Total Mark : 6
Marks Obtained : 5.9

Section 1 : Coding

1. Problem Statement

Oliver is planning a movie night with his friends and wants to download a high-definition movie. He knows the file size of the movie in megabytes (MB) and his internet speed in megabits per second (Mbps). To ensure the movie is ready in time, Oliver needs to calculate the download time.

Your task is to write a program that calculates the download time and displays it in hours, minutes, and seconds.

Example

Input:

MB = 800

mbps = 40

Output:

Download Time: 0 hours, 2 minutes, and 40 seconds

Explanation:

Convert the file size to bits ($800 \text{ MB} * 8 \text{ bits/byte} = 6400 \text{ megabits}$) and divide it by the download speed ($6400 \text{ Mbps} / 40 \text{ Mbps} = 160 \text{ seconds}$). Now, convert the download time in seconds to hours, minutes, and seconds: 160 seconds is equal to 2 minutes and 40 seconds. So, the download time is 0 hours, 2 minutes and 40 seconds.

Input Format

The first line of input consists of an integer N, representing the file size in megabytes (MB).

The second line consists of an integer S, representing the network speed in megabits per second (mbps).

Output Format

The output prints "Download Time: X hours, Y minutes, and Z seconds", where X, Y, and Z are integers representing the hours, minutes, and seconds respectively.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 180

3

Output: Download Time: 0 hours, 8 minutes, and 0 seconds

Answer

```
a=int(input())
b=int(input())
c=a*8
sec=c/b
hours=sec/3600
s=sec%3600
h=s/60
```

```
m=s%60
print("Download Time:" ,int(hours),"hours","," ,int(h),
"minutes",","and",int(m),"seconds")
```

Status : Correct

Marks : 1/1

2. Problem Statement

Ella, an avid TV show enthusiast, is planning a binge-watching marathon for a new series. She has a specific routine: after watching a set number of episodes, she takes a short break.

She is provided with the following information:

Each episode of the series has a fixed duration of 45 minutes. After a certain number of episodes, there is a break of 15 minutes.

Ella wants to know the total time she will need to watch the entire series, including the breaks. Your task is to help Ella by calculating the total viewing time.

Input Format

The first line of input consists of an integer E, representing the total number of episodes in the series.

The second line consists of an integer B, representing the number of episodes watched before taking a break.

Output Format

The output prints an integer representing the total viewing time required to watch the entire series, including the breaks.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
2

Output: 255 minutes

Answer

```
def t(e,b):  
    a=45  
    f=15  
    c=e*a  
    d=(e-1)//b  
    c+=d*f  
    return c  
e=int(input())  
b=int(input())  
print(f"{t(e,b)} minutes")
```

Status : Correct

Marks : 1/1

3. Problem Statement

Mandy is debating with her friend Rachel about an interesting mathematical claim. Rachel asserts that for any positive integer n , the ratio of the sum of n and its triple to the integer itself is always 4. Mandy, intrigued by this statement, decides to validate it using logical operators and basic arithmetic.

She wants to confirm if the statement holds true for any positive integer n .

Input Format

The input consists of a positive integer n , representing the integer to be tested.

Output Format

The first line of output displays "Sum:" followed by an integer representing the calculated sum.

The second line displays "Rachel's statement is: " followed by a Boolean value indicating whether Rachel's statement is correct.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 12

Output: Sum: 48

Rachel's statement is: True

Answer

```
a=int(input())
sum=a*4
print("Sum:",sum)
print("Rachel's statement is: True")
```

Status : Correct

Marks : 1/1

4. Problem Statement

Shawn, a passionate baker, is planning to bake cookies for a large party. His original recipe makes 15 cookies, with the following ingredient quantities: 2.5 cups of flour, 1 cup of sugar, and 0.5 cups of butter.

Write a program to calculate the amounts of flour, sugar, and butter needed for a different number of cookies. Provide the ingredient quantities for a specified number of cookies, maintaining the original proportions of the recipe.

Input Format

The input consists of an integer n , representing the number of cookies.

Output Format

The first line prints "Flour: X cups" where X represents the amount of flour required for n cookies, as a double value rounded to two decimal places.

The second line prints "Sugar: Y cups" where Y represents the amount of Sugar required for n , as a double value rounded to two decimal places.

The third line prints "Butter: Z cups" where Z represents the amount of flour required for n , as a double value rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

Output: Flour: 2.50 cups

Sugar: 1.00 cups

Butter: 0.50 cups

Answer

```
a=int(input())
flour=2.50
sugar=1.00
butter=0.50
b=(a/15)*flour
c=(a/15)*sugar
d=(a/15)*butter
f=round(b,2)
g=round(c,2)
h=round(d,2)
print(f"Flour:{f:.2f} cups")
print(f"Sugar:{g:.2f} cups")
print(f"Butter:{h:.2f} cups")
```

Status : Correct

Marks : 1/1

5. Problem Statement

Liam works at a car dealership and is responsible for recording the details of cars that arrive at the showroom. To make his job easier, he wants a program that can take the car's make, model, and price, and display the information in a formatted summary.

Assist him in the program.

Input Format

The first line of input contains a string, representing the car make.

The second line contains a string, representing the car model.

The third line contains a float value, representing the car price.

Output Format

The first line of output prints "Car Make: ", followed by the car make.

The second line prints "Car Model: ", followed by the car model.

The third line prints "Price: ", followed by the car price, formatted to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Toyota

Camry

23450.75

Output: Car Make: Toyota

Car Model: Camry

Price: Rs.23450.75

Answer

```
a=input()
```

```
b=input()
```

```
c=float(input())
```

```
print("Car Make:",a)
```

```
print("Car Model:",b)
```

```
print(f"Price: Rs.{c:.2f}")
```

Status : Correct

Marks : 1/1

6. Problem Statement

A smart home system tracks the temperature and humidity of each room. Create a program that takes the room name (string), temperature (float), and humidity (float).

Display the room's climate details.

Input Format

The first line of input consists of a string, representing the room name.

The second line consists of a float value, representing the temperature.

The third line consists of a float value, representing the humidity.

Output Format

The first line of output prints "Room: " followed by the room name (string).

The second line prints "Temperature: " followed by the temperature (float) formatted to two decimal places.

The third line prints "Humidity: " followed by the humidity (float) formatted to two decimal places and a percentage sign (%).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: Living Room

23.45

45.78

Output: Room: Living Room

Temperature: 23.45

Humidity: 45.78%

Answer

```
a=input()
b=float(input())
c=float(input())
print("Room:",a)
print("Temperature:",b)
print(f"Humidity: {c:.2f}%")
```

Status : Partially correct

Marks : 0.9/1