Day 3

HTML & CSS

→ tag.

no use

if

change it to important using css

CSS

What is CSS?

It is used to style your responsive web page.

All

Types of CSS → 3

i). Inline → Written within the tag.

✓ 2). Internal → Written within the page ..

✓ 3). External → CSS is written seperately.

→ <link>

Selectors → 4

→ class → .

→ id → #

→ Tag(element) → Tag

→ Universal → *

.link {

text-decoration : none.

}

#style1 { }

<a href = " " class = " link style1 "

div {

height : 100px;

width : 100px;

}

Styling priorities

→ ① internal → Priority2
② inline → Priority1

→ ① external → Priority2
② inline → Priority1

→ ① internal → } No priority unless
② external → } we see the codebase

→ <link type="stylesheet" href="external.css"/>

<style>

<style>

<link type="stylesheet" href="external.css"/>

① internal : Priority2

① internal : Priority1
② external : Priority2

① internal : Priority2
② external : Priority3
③ inline : Priority1

② external : Priority1

① internal : Priority3.
② external : Priority2
③ inline : Priority1

Intermediate CSS

BoxModel
General term : Frontend ✓
Precise term : Information / Content ✓





① Is your padding coming towards your content or outwards & the content? outwards.

Box Model → content will not move outwards

padding: 10 px →

② Margin: 5px → Towards your Content

③ Border: 5px solid grey → Towards your content

Positioning

① relative ✓
② absolute ✓

(B) fix

position: Fixed ⇒ It is going to fix the position of the content.

position: relative ⇒

position: absolute ⇒ can't be worked independently. This absolute is dependent on your relative position.