

UNIVERSITY OF TEXAS AT ARLINGTON
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

4308/5360

ARTIFICIAL INTELLIGENCE I

FALL 2020

PROGRAMMING ASSIGNMENT 0

1 Introduction

This assignment will cover the following topics:

- A mini-Unix tutorial.
- A mini-Python tutorial.
- An overview of assignment grading. Each Python programming assignment includes an autograder for you to run yourself.

The Python programming assignments for this class assume you are using Python version 2.7.

Files to edit: You will fill in portions of `addition.py`, `buyLotsOfFruit.py`, and `shopSmart.py` during the assignment.

2 Unix Basics

Here are basic commands to navigate a Unix system and edit files.

File/directory manipulation:

When you open a terminal window, you're placed at a command prompt:

```
[cse5360-ta@nova ~]$
```

The prompt shows your username, the host you are logged onto, and your current location in the directory structure (i.e. your path). The tilde character is shorthand for your home directory. Note that your prompt may look slightly different. To make a directory, use the `mkdir` command. Use the command `cd` to change to that directory:

```
[cse5360-ta@nova ~]$ mkdir foo
[cse5360-ta@nova ~]$ cd foo
[cse5360-ta@nova ~/foo]$
```

Use the `ls` command to see a listing of the contents of a directory, and the command `touch` to create an empty file:

```
[cse5360-ta@nova ~/foo]$ ls
[cse5360-ta@nova ~/foo]$ touch hello_world
[cse5360-ta@nova ~/foo]$ ls
hello_world
[cse5360-ta@nova ~/foo]$ cd ..
[cse5360-ta@nova ~]$
```

Download 'python_basics.zip' into your home directory. Use the `unzip` command to extract the contents of the zip file:

```
[cse5360-ta@nova ~]$ ls *.zip
python_basics.zip
[cse5360-ta@nova ~]$ unzip python_basics.zip
[cse5360-ta@nova ~]$ cd python_basics
[cse5360-ta@nova ~/python_basics]$ ls
foreach.py
helloWorld.py
listcomp.py
listcomp2.py
quickSort.py
shop.py
shopTest.py
```

The following are additional useful Unix commands:

- `cp` copies a file or files.
- `rm` removes (deletes) a file.
- `mv` moves a file (i.e. cut/paste instead of copy/paste).
- `man` displays documentation for a command.
- `pwd` prints your current path.
- `xterm` opens a new terminal window.
- `firefox` opens a web browser.
- Press ‘Ctrl-c’ to kill a running process.
- Append `&` to a command to run it in the background.
- `fg` brings a program running in the background to the foreground.

Emacs text editor:

Emacs is a customizable text editor which has some nice features specifically tailored for programmers. However, you can use any other text editor that you may prefer (such as vim, pico, or joe on Unix; or Notepad on Windows; or TextWrangler on OS X; and many more).

To run Emacs, type `emacs` at a command prompt:

```
[cse5360-ta@nova ~/python_basics]$ emacs helloWorld.py &
[1] 3262
```

Here we gave the argument `helloWorld.py` which will either open that file for editing if it exists, or create it otherwise. Emacs notices that this is a Python source file (because of the `.py` ending) and enters Python-mode, which is supposed to help you write code. When editing this file you may notice some of that text becomes automatically colored. This is syntax highlighting to help you distinguish items such as keywords, variables, strings, and comments. Pressing Enter, Tab, or Backspace may cause the cursor to jump to weird locations. This occurs because Python is very picky about indentation and Emacs is predicting the proper tabbing that you should use.

Some basic Emacs editing commands (`C-` means “while holding the Ctrl-key”):

- `C-x C-s` saves the current file.
- `C-x C-f` opens a file or creates a new file if it doesn’t exist.
- `C-k` cuts a line and adds it to the clipboard.
- `C-y` pastes the contents of the clipboard.
- `C-_` performs an undo.

- C-g aborts a half-entered command.

You can also copy and paste using just the mouse. Using the left button, select a region of text to copy. Then, click the middle button to paste.

There are two ways you can use Emacs to develop Python code. The most straightforward way is to use it just as a text editor. Create and edit Python files in Emacs, then run Python to test the code somewhere else (e.g. in a terminal window). Alternatively, you can run Python inside Emacs. See the options under “Python” in the menubar, or type C-c ! to start a Python interpreter in a split screen. (Use C-x o to switch between the split screens, or just click if C-x doesn’t work.)

3 Python Basics

Python is an interpreted, object-oriented language that shares some features with both Java and Scheme. This tutorial will walk through the primary syntactic constructions in Python using short examples. We encourage you to type all Python code shown in the tutorial onto your own machine. Make sure it responds the same way. You may find the Troubleshooting subsection helpful if you run into problems. It contains a list of the frequent problems previous students have encountered when following this tutorial.

Invoking the interpreter:

Python can be run in one of two modes. It can either be used *interactively*, via an interpreter, or it can be called from the command line to execute a *script*. We will first use the Python interpreter interactively.

You invoke the interpreter by entering python at the Unix command prompt. Note that you may have to type python2.4, python2.5, python2.6, or python2.7, rather than python, depending on your machine:

```
[cse5360-ta@nova ~]$ python
Python 2.6.5 (r265:79063, Jan 14 2011, 14:20:15)
[GCC 4.4.1] on sunos5
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

Operators:

The Python interpreter can be used to evaluate expressions, for example simple arithmetic expressions. If you enter such expressions at the prompt (>>>) they will be evaluated and the result will be returned on the next line:

```
>>> 1 + 1
2
>>> 2 * 3
6
```

Boolean operators also exist in Python to manipulate the primitive **True** and **False** values:

```
>>> 1==0
False
>>> not (1==0)
True
>>> (2==2) and (2==3)
False
>>> (2==2) or (2==3)
```

True

Strings:

Like Java, Python has a built in string type. The + operator is overloaded to do string concatenation on string values:

```
>>> 'artificial' + "intelligence"
'artificialintelligence'
```

There are many built-in methods which allow you to manipulate strings:

```
>>> 'artificial'.upper()
'ARTIFICIAL'
>>> 'HELP'.lower()
'help'
>>> len('Help')
4
```

Notice that we can use either single quotes ' ' or double quotes " " to surround a string. This allows for easy nesting of strings. We can also store expressions into variables:

```
>>> s = 'hello world'
>>> print s
hello world
>>> s.upper()
'HELLO WORLD'
>>> len(s.upper())
11
>>> num = 8.0
>>> num += 2.5
>>> print num
10.5
```

In Python, you do not have declare variables before you assign to them.

Exercise using dir and help:

Learn about the methods Python provides for strings. To see what methods Python provides for a datatype, use the dir and help commands:

```
>>> s = 'abc'
>>> dir(s)
['__add__', '__class__', '__contains__', '__delattr__', '__doc__', '__eq__', '__ge__', '__getattribute__',
'__getitem__', '__getnewargs__', '__getslice__', '__gt__', '__hash__', '__init__', '__le__', '__len__',
'__lt__', '__mod__', '__mul__', '__ne__', '__new__', '__reduce__', '__reduce_ex__', '__repr__', '__rmod__',
'__rmul__', '__setattr__', '__str__', 'capitalize', 'center', 'count', 'decode', 'encode', 'endswith',
'expandtabs', 'find', 'index', 'isalnum', 'isalpha', 'isdigit', 'islower', 'isspace', 'istitle',
'isupper', 'join', 'ljust', 'lower', 'lstrip', 'replace', 'rfind', 'rindex', 'rjust', 'rsplit',
'rstrip', 'split', 'splitlines', 'startswith', 'strip', 'swapcase', 'title', 'translate',
'upper', 'zfill']
>>> help(s.find)
```

Help on built-in function find:

```
find(...)
S.find(sub [,start [,end]]) -> int
```

Return the lowest index in S where substring sub is found, such that sub is contained within s[start,end]. Optional arguments start and end are interpreted as in slice notation.

Return -1 on failure.

```
>> s.find('b')
1
```

Try out some of the string functions listed in `dir` (ignore those with underscores '_' around the method name).

Built-in data structures:

Python comes equipped with some useful built-in data structures that are broadly similar to Java's collections package.

Lists:

Lists store a sequence of mutable items:

```
>>> fruits = ['apple', 'orange', 'pear', 'banana']
>>> fruits[0]
'apple'
```

We can use the + operator to do list concatenation:

```
>>> otherFruits = ['kiwi', 'strawberry']
>>> fruits + otherFruits
>>> ['apple', 'orange', 'pear', 'banana', 'kiwi', 'strawberry']
```

Python also allows negative-indexing from the back of the list. For instance, `fruits[-1]` will access the last element 'banana':

```
>>> fruits[-2]
'pear'
>>> fruits.pop()
'banana'
>>> fruits
['apple', 'orange', 'pear']
>>> fruits.append('grapefruit')
>>> fruits
['apple', 'orange', 'pear', 'grapefruit']
>>> fruits[-1] = 'pineapple'
>>> fruits
['apple', 'orange', 'pear', 'pineapple']
```

We can also index multiple adjacent elements using the slice operator. For instance, `fruits[1:3]`, returns a list containing the elements at position 1 and 2. In general, `fruits[start:stop]` will get the elements in `start`, `start+1`, ..., `stop-1`. We can also do `fruits[start:]` which returns all elements starting from the `start` index. Also `fruits[:end]` will return all elements before the element at position `end`:

```
>>> fruits[0:2]
['apple', 'orange']
>>> fruits[:3]
['apple', 'orange', 'pear']
>>> fruits[2:]
['pear', 'pineapple']
>>> len(fruits)
4
```

The items stored in lists can be any Python data type. So for instance we can have lists of lists:

```
>>> lstOfLsts = [['a','b','c'],[1,2,3],['one','two','three']]
>>> lstOfLsts[1][2]
3
>>> lstOfLsts[0].pop()
'c'
>>> lstOfLsts
[['a', 'b'],[1, 2, 3],['one', 'two', 'three']]
```

Exercise using lists:

Play with some of the list functions. You can find the methods you can call on an object via the `dir` command and get information about them via the `help` command:

```
>>> dir(list)
['_add_', '_class_', '_contains_', '_delattr_', '_delitem_', '_delslice_', '_doc_',
'_eq_', '_ge_', '_getattribute_', '_getitem_', '_getslice_', '_gt_', '_hash_', '_iadd_',
'_imul_', '_init_', '_iter_', '_le_', '_len_', '_lt_', '_mul_', '_ne_', '_new_', '_reduce',
'_reduce_ex_', '_repr_', '_reversed_', '_rmul_', '_setattr_', '_setitem_', '_setslice_',
'_str_', 'append', 'count', 'extend', 'index', 'insert', 'pop', 'remove', 'reverse', 'sort']

>>> help(list.reverse)
Help on built-in function reverse:

reverse(...)
L.reverse() -- reverse *IN PLACE*

>>> lst = ['a','b','c']
>>> lst.reverse()
>>> ['c','b','a']
```

Note: Ignore functions with underscores “_” around the names; these are private helper methods. Press ‘q’ to back out of a help screen.

Tuples:

A data structure similar to the list is the *tuple*, which is like a list except that it is immutable once it is created (i.e. you cannot change its content after creation). Tuples are surrounded with parentheses while lists have square brackets.

```
>>> pair = (3,5)
>>> pair[0]
3
```

```

>>> x,y = pair
>>> x
3
>>> y
5
>>> pair[1] = 6
TypeError: object does not support item assignment

```

The attempt to modify an immutable structure raised an exception. Exceptions indicate errors, e.g. index out of bounds errors, type errors, etc. will all report exceptions in this way.

Sets:

A *set* is another data structure that serves as an unordered list with no duplicate items. Below, we show how to create a set, add items to the set, test if an item is in the set, and perform common set operations (difference, intersection, union).

```

>>> shapes = ['circle','square','triangle','circle']
>>> setOfShapes = set(shapes)
>>> setOfShapes
set(['circle','square','triangle'])
>>> setOfShapes.add('polygon')
>>> setOfShapes
set(['circle','square','triangle','polygon'])
>>> 'circle' in setOfShapes
True
>>> 'rhombus' in setOfShapes
False
>>> favoriteShapes = ['circle','triangle','hexagon']
>>> setOfFavoriteShapes = set(favoriteShapes)
>>> setOfShapes - setOfFavoriteShapes
set(['square','polyon'])
>>> setOfShapes & setOfFavoriteShapes
set(['circle','triangle'])
>>> setOfShapes | setOfFavoriteShapes
set(['circle','square','triangle','polygon','hexagon'])

```

Note: Objects in the set are unordered; you cannot assume that their traversal or print order will be the same across machines!

Dictionaries:

The last built-in data structure is the *dictionary* which stores a map from one type of object (the key) to another (the value). The key must be an immutable type (string, number, or tuple). The value can be any Python data type.

Note: In the example below, the printed order of the keys returned by Python could be different than what is shown. The reason is that unlike lists which have a fixed ordering, a dictionary is simply a hash table for which there is no fixed ordering of the keys (like `HashMaps` in Java). The order of the keys depends on exactly how the hashing algorithm maps keys to buckets, and will usually seem arbitrary. Your code should not rely on key ordering and you should not be surprised if even a small modification to how your

code uses a dictionary results in a new key ordering.

```
>>> studentIds = {'knuth': 42.0, 'turing': 56.0, 'nash': 92.0}
>>> studentIds['turing']
56.0
>>> studentIds['nash'] = 'ninety-two'
>>> studentIds
{'knuth': 42.0, 'turing': 56.0, 'nash': 'ninety-two'}
>>> del studentIds['knuth']
>>> studentIds
{'turing': 56.0, 'nash': 'ninety-two'}
>>> studentIds['knuth'] = [42.0, 'forty-two']
>>> studentIds
{'knuth': [42.0, 'forty-two'], 'turing': 56.0, 'nash': 'ninety-two'}
>>> studentIds.keys()
['knuth', 'turing', 'nash']
>>> studentIds.values()
[[42.0, 'forty-two'], 56.0, 'ninety-two']
>>> studentIds.items()
[('knuth', [42.0, 'forty-two']), ('turing', 56.0), ('nash', 'ninety-two')]
>>> len(studentIds)
3
```

As with nested lists, you can also create dictionaries of dictionaries.

Exercise using dictionaries:

Use `dir` and `help` to learn about the functions you can call on dictionaries.

Writing scripts:

Now that you've got a handle on using Python interactively, let's write a simple Python script that demonstrates Python's for loop. Open the file called `foreach.py` and update it with the following code:

```
# This is what a comment looks like
fruits = ['apples', 'oranges', 'pears', 'bananas']
for fruit in fruits:
    print fruit + ' for sale'

fruitPrices = {'apples': 2.00, 'oranges': 1.50, 'pears': 1.75}
for fruit, price in fruitPrices.items():
    if price < 2.00:
        print '%s cost %f a pound' % (fruit, price)
    else:
        print fruit + ' are too expensive!'
```

At the command line, use the following command in the directory containing `foreach.py`:

```
[cse5360-ta@nova ~/tutorial]$ python foreach.py
apples for sale
oranges for sale
pears for sale
```



```
bananas for sale
oranges cost 1.500000 a pound
pears cost 1.750000 a pound
apples are too expensive!
```

Remember that the print statements listing the costs may be in a different order on your screen than in this tutorial; that's due to the fact that we're looping over dictionary keys which are unordered. To learn more about control structures (e.g. `if` and `else`) in Python, check out the official Python tutorial section on this topic.

If you like functional programming you might also like `map` and `filter`:

```
>>> map(lambda x: x * x, [1,2,3])
[1, 4, 9]
>>> filter(lambda x: x > 3, [1,2,3,4,5,4,3,2,1])
[4, 5, 4]
```

The next snippet of code demonstrates Python's list comprehension construction:

```
nums = [1,2,3,4,5,6]
plusOneNums = [x+1 for x in nums]
oddNums = [x for x in nums if x % 2 == 1]
print oddNums
oddNumsPlusOne = [x+1 for x in nums if x % 2 == 1]
print oddNumsPlusOne
```

This code is in a file called `listcomp.py`, which you can run:

```
[cse5360-ta@nova ~]$ python listcomp.py
[1,3,5]
[2,4,6]
```

Exercise using list comprehensions:

Write a list comprehension which, from a list, generates a lowercased version of each string that has length greater than five. You can find the solution in `listcomp2.py`.

Beware of indentation:

Unlike many other languages, Python uses the indentation in the source code for interpretation. So for instance, for the following script:

```
if 0 == 1:
    print 'We are in a world of arithmetic pain'
print 'Thank you for playing'
```

will output

Thank you for playing

But if we had written the script as:

```
if 0 == 1:
    print 'We are in a world of arithmetic pain'
    print 'Thank you for playing'
```

there would be no output. The moral of the story is be careful how you indent! It's best to use four spaces for indentation, that's what the course code uses.

Tabs vs spaces:

Since Python uses indentation for code evaluation, it needs to keep track of the level of indentation across code blocks. This means that if your Python file switches from using tabs as indentation to spaces as indentation, the Python interpreter will not be able to resolve the ambiguity of the indentation level and it will throw an exception. Even though the code can be lined up visually in your text editor, Python "sees" a change in indentation and most likely will throw an exception (or rarely, produce unexpected behavior).

This most commonly happens when opening up a Python file that uses an indentation scheme that is opposite from what your text editor uses (i.e. your text editor uses spaces and the file uses tabs). When you write new lines in a code block there will be a mix of tabs and spaces even though the whitespace is aligned.

Writing functions:

As in Java, in Python you can define your own functions:

```
fruitPrices = 'apples': 2.00, 'oranges': 1.50, 'pears': 1.75
```

```
def buyFruit(fruit, numPounds):
    if fruit not in fruitPrices:
        print "Sorry we don't have %s" % (fruit)
    else:
        cost = fruitPrices[fruit] * numPounds
        print "That will be %f please" % (cost)
```

```
# Main Function
if __name__ == '__main__':
    buyFruit('apples',2.4)
    buyFruit('coconuts',2)
```

Rather than having a main function as in Java, the `__name__ == '__main__'` check is used to delimit expressions which are executed when the file is called as a script from the command line. The code after the main check is thus the same sort of code you would put in a main function in Java.

Save this script as `fruit.py` and run it:

```
[cse5360-ta@nova ~]$ python fruit.py
That will be 4.800000 please
Sorry we don't have coconuts
```

Advanced exercise:

Write a `quickSort` function in Python using list comprehensions. Use the first element as the pivot. You can find the solution in `quickSort.py`.

Object basics:

Although this isn't a course in object-oriented programming, you'll have to use some objects in the programming assignments, thus it's worth covering the basics of objects in Python. An object encapsulates data and provides functions for interacting with that data.

Defining classes:

Here's an example of defining a class named FruitShop:

```
class FruitShop:

    def __init__(self, name, fruitPrices):
        """
            name: Name of the fruit shop

            fruitPrices: Dictionary with keys as fruit
                        strings and prices for values e.g.
                        {'apples': 2.00, 'oranges': 1.50, 'pears': 1.75}
        """
        self.fruitPrices = fruitPrices
        self.name = name
        print 'Welcome to the %s fruit shop' % (name)

    def getCostPerPound(self, fruit):
        """
            fruit: Fruit string
            Returns cost of 'fruit', assuming 'fruit'
            is in our inventory or None otherwise
        """
        if fruit not in self.fruitPrices:
            print "Sorry we don't have %s" % (fruit)
            return None
        return self.fruitPrices[fruit]

    def getPriceOfOrder(self, orderList):
        """
            orderList: List of (fruit, numPounds) tuples
            Returns cost of orderList. If any of the fruit are
        """
        totalCost = 0.0
        for fruit, numPounds in orderList:
            costPerPound = self.getCostPerPound(fruit)
            if costPerPound != None:
                totalCost += numPounds * costPerPound
        return totalCost

    def getName(self):
        return self.name
```

The FruitShop class has some data such as the name of the shop and the prices per pound of some fruit. It also provides functions, or methods, on this data. What advantages are there to wrapping this data in a class? The advantages are the following:

- Encapsulating the data prevents it from being altered or used inappropriately.
- The abstraction that objects provide makes it easier to write general purpose code.

Using objects:

How do we make an object and use it? Make sure you have the `FruitShop` implementation in `shop.py`. We then import the code from this file (making it accessible to other scripts) using `import shop`, since `shop.py` is the name of the file. Then, we can create `FruitShop` objects as follows:

```
import shop

shopName = 'the Berkeley Bowl'
fruitPrices = {'apples': 1.00, 'oranges': 1.50, 'pears': 1.75}
berkeleyShop = shop.FruitShop(shopName, fruitPrices)
applePrice = berkeleyShop.getCostPerPound('apples')
print applePrice
print('Apples cost $%.2f at %s.' % (applePrice, shopName))

otherName = 'the Stanford Mall'
otherFruitPrices = {'kiwis':6.00, 'apples': 4.50, 'peaches': 8.75}
otherFruitShop = shop.FruitShop(otherName, otherFruitPrices)
otherPrice = otherFruitShop.getCostPerPound('apples')
print otherPrice
print('Apples cost $%.2f at %s.' % (otherPrice, otherName))
print("My, that's expensive!")
```

This code is in `shopTest.py`; you can run it like this:

```
[cse5360-ta@nova ~]$ python shopTest.py
Welcome to the Berkeley Bowl fruit shop
1.0
Apples cost $1.00 at the Berkeley Bowl.
Welcome to the Stanford Mall fruit shop
4.5
Apples cost $4.50 at the Stanford Mall.
My, that's expensive!
```

So what just happened? The `import shop` statement told Python to load all of the functions and classes in `shop.py`. The line `berkeleyShop = shop.FruitShop(shopName, fruitPrices)` constructs an *instance* of the `FruitShop` class defined in `shop.py`, by calling the `__init__` function in that class. Note that we only passed two arguments in, while `__init__` seems to take three arguments: (**self**, **name**, **fruitPrices**). The reason for this is that all methods in a class have **self** as the first argument. The **self** variable's value is automatically set to the object itself; when calling a method, you only supply the remaining arguments. The **self** variable contains all the data (**name** and **fruitPrices**) for the current specific instance (similar to **this** in Java). The print statements use the substitution operator (described in the Python docs if you're curious).

Static vs instance variables:

The following example illustrates how to use static and instance variables in Python. Create the `person_class.py` containing the following code:

```
class Person:
    population = 0
    def __init__(self, myAge):
```

```

        self.age = myAge
    Person.population += 1
def get_population(self):
    return Person.population
def get_age(self):
    return self.age

```

We first compile the script:

```
[cse5360-ta@nova ~]$ python person_class.py
```

Now use the class as follows:

```

>>> import person_class
>>> p1 = person_class.Person(12)
>>> p1.get_population()
1
>>> p2 = person_class.Person(63)
>>> p1.get_population()
2
>>> p2.get_population()
2
>>> p1.get_age()
12
>>> p2.get_age()
63

```

In the code above, `age` is an instance variable and `population` is a static variable. `population` is shared by all instances of the `Person` class, whereas each instance has its own `age` variable.

More Python tips and tricks:

This tutorial has briefly touched on some major aspects of Python that will be relevant to the course. Here are some more useful tidbits.

Use `range` to generate a sequence of integers, useful for generating traditional indexed `for` loops:

```

for index in range(3):
    print lst[index]

```

After importing a file, if you edit a source file, the changes will not be immediately propagated in the interpreter. For this, use the `reload` command:

```
>>> reload(shop)
```

Troubleshooting:

These are some problems (and their solutions) that new Python learners commonly encounter.

- Problem:** ImportError: No module named py
Solution: When using `import`, do not include the “.py” from the filename. For example, you should say `import shop` NOT `import shop.py`.
- Problem:** NameError: name ‘MY VARIABLE’ is not defined
 Even after importing you may see this.
Solution: To access a member of a module, you have to type `MODULE NAME.MEMBER NAME`, where

MODULE NAME is the name of the .py file, and MEMBER NAME is the name of the variable (or function) you are trying to access.

- **Problem:** TypeError: 'dict' object is not callable

Solution: Dictionary lookups are done using square brackets: [and] NOT parenthesis (and).

- **Problem:** ValueError: too many values to unpack

Solution: Make sure the number of variables you are assigning in a **for** loop matches the number of elements in each item of the list. Likewise for working with tuples.

For example, if pair is a tuple of two elements (e.g. `pair = ('apple', 2.0)`) then the following code would cause the “too many values to unpack error”:

```
(a,b,c) = pair
```

Here is a problematic scenario involving a for loop:

```
pairList = [('apples', 2.00), ('oranges', 1.50), ('pears', 1.75)]
```

```
for fruit, price, color in pairList:
```

```
    print '%s fruit costs %f and is the color %s' % (fruit, price, color)
```

- **Problem:** AttributeError: 'list' object has no attribute 'length' (or something similar)

Solution: Finding length of lists is done using `len(NAME OF LIST)`.

- **Problem:** Changes to a file are not taking effect.

Solution: Make sure you are saving all your files after any changes. If you are editing a file in a window different from the one you are using to execute Python, make sure you `reload(YOUR_MODULE)` to guarantee your changes are being reflected, `reload` works similarly to `import`.

More references:

The place to go for more Python information is www.python.org. A good reference book is “Learning Python”.

4 Autograding

To get you familiarized with the autograder, we will ask you to code, test, and submit solutions for three questions. You can download all of the files associated the autograder tutorial are contained in tutorial.zip. Unzip this file and examine its contents:

```
[cse5360-ta@nova ~]$ unzip tutorial.zip
[cse5360-ta@nova ~]$ cd tutorial
[cse5360-ta@nova ~/tutorial]$ ls
addition.py
autograder.py
buyLotsOfFruit.py
grading.py
projectParams.py
shop.py
shopSmart.py
testClasses.py
testParser.py
test_cases
tutorialTestClasses.py
```

This contains a number of files you'll edit or run:

- `addition.py`: Source file for question 1.

- `buyLotsOfFruit.py`: Source file for question 2.
- `shop.py`: Source file for question 3.
- `shopSmart.py`: Source file for question 3.
- `autograder.py`: Autograding script (see below).

and others you can ignore:

- `test_cases`: Directory that contains the test cases for each question.
- `grading.py`: Autograder code.
- `testClasses.py`: Autograder code.
- `tutorialTestClasses.py`: Test classes for this particular project.
- `projectParams.py`: Project parameters.

The command `python autograder.py` grades your solution to all three problems. If we run it before editing any files we get a page or two of output:

```
[cse5360-ta@nova ~/tutorial]$ python autograder.py
Starting on 1-21 at 23:39:51
```

Question q1

```
=====
*** FAIL: test_cases/q1/addition1.test
***     add(a,b) must return the sum of a and b
***     student result:  "0"
***     correct result:  "2"
*** FAIL: test_cases/q1/addition2.test
***     add(a,b) must return the sum of a and b
***     student result:  "0"
***     correct result:  "5"
*** FAIL: test_cases/q1/addition3.test
***     add(a,b) must return the sum of a and b
***     student result:  "0"
***     correct result:  "7.9"
*** Tests failed.
```

Question q1: 0/1

Question q2

```
=====
*** FAIL: test_cases/q2/food_price1.test
***     buyLotsOfFruit must compute the correct cost of the order
***     student result:  "0.0"
***     correct result:  "12.25"
*** FAIL: test_cases/q2/food_price2.test
***     buyLotsOfFruit must compute the correct cost of the order
***     student result:  "0.0"
***     correct result:  "14.75"
*** FAIL: test_cases/q2/food_price3.test
***     buyLotsOfFruit must compute the correct cost of the order
***     student result:  "0.0"
***     correct result:  "6.4375"
*** Tests failed.
```

Question q2: 0/1

Question q3

=====

Welcome to shop1 fruit shop

Welcome to shop2 fruit shop

*** FAIL: test_cases/q3/select_shop1.test

*** shopSmart(order, shops) must select the cheapest shop

*** student result: "None"

*** correct result: "<FruitShop: shop1>"

Welcome to shop1 fruit shop

Welcome to shop2 fruit shop

*** FAIL: test_cases/q3/select_shop2.test

*** shopSmart(order, shops) must select the cheapest shop

*** student result: "None"

*** correct result: "<FruitShop: shop2>"

Welcome to shop1 fruit shop

Welcome to shop2 fruit shop

Welcome to shop3 fruit shop

*** FAIL: test_cases/q3/select_shop3.test

*** shopSmart(order, shops) must select the cheapest shop

*** student result: "None"

*** correct result: "<FruitShop: shop3>"

*** Tests failed.

Question q3: 0/1

Finished at 23:39:51

Provisional grades

=====

Question q1: 0/1

Question q2: 0/1

Question q3: 0/1

Total: 0/3

Your grades are NOT yet registered. To register your grades, make sure to follow your instructor's guidelines to receive credit on your project.

For each of the three questions, this shows the results of that question's tests, the questions grade, and a final summary at the end. Since you haven't yet solved the questions, all the tests fail. As you solve each question you may find some tests pass while other fail. When all tests pass for a question, you get full credit.

Looking at the results for question 1, you can see that it has failed three tests with the error message "add(a,b) must return the sum of a and b". The answer your code gives is always 0, but the correct answer is different. We'll fix that in the next section.

5 Question 1: Addition

Open `addition.py` and look at the definition of `add`:

```
def add(a, b):
    "Return the sum of a and b"
    "*** YOUR CODE HERE ***"
    return 0
```

The tests called this with `a` and `b` set to different values, but the code always returned zero. Modify this definition to read:

```
def add(a, b):
    "Return the sum of a and b"
    print "Passed a=%s and b=%s, returning a+b=%s" % (a,b,a+b)
    return a+b
```

Now rerun the autograder (omitting the results for questions 2 and 3):

```
[cse5360-ta@nova ~/tutorial]$ python autograder.py -q q1
Starting on 1-21 at 23:52:05
```

```
Question q1
=====
Passed a=1 and b=1, returning a+b=2
*** PASS: test_cases/q1/addition1.test
***     add(a,b) returns the sum of a and b
Passed a=2 and b=3, returning a+b=5
*** PASS: test_cases/q1/addition2.test
***     add(a,b) returns the sum of a and b
Passed a=10 and b=-2.1, returning a+b=7.9
*** PASS: test_cases/q1/addition3.test
***     add(a,b) returns the sum of a and b
```

```
### Question q1:  1/1 ###
```

```
Finished at 23:41:01
```

```
Provisional grades
```

```
=====
```

```
Question q1:  1/1
Question q2:  0/1
Question q3:  0/1
```

```
-----
```

```
Total:  1/3
```

You now pass all tests, getting full credit for question 1. Notice the new lines “Passed a=...” which appear before “*** PASS: ...”. These are produced by the print statement in `add`. You can use print statements like that to output information useful for debugging. You can also run the autograder with the option `--mute` to temporarily hide such lines as follows:

```
[cse5360-ta@nova ~/tutorial]$ python autograder.py -q q1 --mute
Starting on 1-22 at 14:15:33
```

Question q1

=====

```
*** PASS: test_cases/q1/addition1.test
***      add(a,b) returns the sum of a and b
*** PASS: test_cases/q1/addition2.test
***      add(a,b) returns the sum of a and b
*** PASS: test_cases/q1/addition3.test
***      add(a,b) returns the sum of a and b
```

Question q1: 1/1

6 Question 2: buyLotsOfFruit function

Add a `buyLotsOfFruit(orderList)` function to `buyLotsOfFruit.py` which takes a list of `(fruit,pound)` tuples and returns the cost of your list. If there is some fruit in the list which doesn't appear in `fruitPrices`, then it should print an error message and return `None`. Please do not change the `fruitPrices` variable.

Run the command `python autograder.py` until question 2 passes all tests and you get full credit. Each test will confirm that `buyLotsOfFruit(orderList)` returns the correct answer given various possible inputs. For example, `test_cases/q2/food.price1.test` tests whether:

Cost of `[('apples', 2.0), ('pears', 3.0), ('limes', 4.0)]` is 12.25

7 Question 3: shopSmart function

Fill in the function `shopSmart(orders,shops)` in `shopSmart.py` which takes an `orderList` (like the kind passed in to `FruitShop.getPriceOfOrder`) and a list of `FruitShop`, and returns the `FruitShop` where your order costs the least amount in total. Please don't change the file name or variable names. Note that we will provide the `shop.py` implementation as a "support" file, therefore you don't need to submit yours.

Run the command `python autograder.py` until question 3 passes all tests and you get full credit. Each test will confirm that `shopSmart(orders,shops)` returns the correct answer given various possible inputs. For example, with the following variable definitions:

```
orders1 = [('apples',1.0), ('oranges',3.0)]
orders2 = [('apples',3.0)]
dir1 = 'apples': 2.0, 'oranges':1.0
shop1 = shop.FruitShop('shop1',dir1)
dir2 = 'apples': 1.0, 'oranges': 5.0
shop2 = shop.FruitShop('shop2',dir2)
shops = [shop1, shop2]
```

`test_cases/q3/select_shop1.test` tests whether:

```
shopSmart.shopSmart(orders1, shops) == shop1
```

and `test_cases/q3/select_shop2.test` tests whether:

```
shopSmart.shopSmart(orders2, shops) == shop2
```