

```

'''
    Bardia Mojra

    @link https://github.com/ZwEin27/Hierarchical-Clustering/blob/master/hclust.py
'''

import numpy as np
import matplotlib.pyplot as plt
import sys
import math
import os
import heapq
import itertools
import pdb

D= [(170,57,32),(190,95,28),(150,45,35),(168,65,29),(175,78,26),(185,90,32),
    (171,65,28),(155,48,31),(165,60,27),(182,80,30),(175,69,28),(178,80,27),
    (160,50,31),(170,72,30)]

Y = ['W', 'M', 'W', 'M', 'M', 'M', 'W', 'W', 'W', 'M', 'W', 'M', 'W', 'M']

def get_data(data, label):
    Xlist = list()
    for x in data:
        Xlist.append(np.asarray(x))
    X = np.asarray(Xlist)
    print(label+':')
    print(X)
    print('\n')
    return X

'''
def euclidean_distance(self, row_A, row_B):
    dist = 0.0
    diffList = list()
    for i in range(len(row_A[0])):
        diff = 0.0
        diff = row_A[0][i]-row_B[i]
        diffList.append(diff)
        dist += (diff)**2
    dist = math.sqrt(dist)
    return round(dist, self.precision)
'''

class Hierarchical_Clustering:
    def __init__(self, ipt_data, k, linkage='single'):
        self.input_file_name = ipt_data
        self.k = k
        self.dataset = None
        self.linkage = linkage
        self.dataset_size = 0
        self.dimension = 0
        self.heap = []
        self.clusters = []
        #self.gold_standard = {}

    def initialize(self):
        """ Initialize and check parameters

```

```

"""
# check file exist and if it's a file or dir
if not os.path.isfile(self.input_file_name):
    self.quit("Input file doesn't exist or it's not a file")
self.dataset, self.clusters = self.load_data(self.input_file_name)
self.dataset_size = len(self.dataset)
if self.dataset_size == 0:
    self.quit("Input file doesn't include any data")
if self.k == 0:
    self.quit("k = 0, no cluster will be generated")
if self.k > self.dataset_size:
    self.quit("k is larger than the number of existing clusters")
self.dimension = len(self.dataset[0]["data"])
if self.dimension == 0:
    self.quit("dimension for dataset cannot be zero")

def euclidean_distance(self, data_point_one, data_point_two):
    """
    euclidean distance: https://en.wikipedia.org/wiki/Euclidean\_distance
    assume that two data points have same dimension

    """
    size = len(data_point_one)
    result = 0.0
    for i in range(size):
        f1 = float(data_point_one[i])    # feature for data one
        f2 = float(data_point_two[i])    # feature for data two
        tmp = f1 - f2
        result += pow(tmp, 2)
    result = math.sqrt(result)
    return result

def compute_pairwise_distance(self, dataset):
    result = []
    dataset_size = len(dataset)
    for i in range(dataset_size-1):    # ignore last i
        for j in range(i+1, dataset_size):    # ignore duplication
            dist = self.euclidean_distance(dataset[i]["data"], dataset[j]["data"])

            # duplicate dist, need to be remove, and there is no difference to use tuple only
            # leave second dist here is to take up a position for tie selection
            result.append( (dist, [dist, [[i], [j]]]) )
    return result

def build_priority_queue(self, distance_list):
    if self.linkage == 'single':
        heapq.heapify(distance_list)
    elif self.linkage == 'complete':
        heapq._heapify_max(distance_list)
    else:
        print("error - heapq not properly assigned.")
    self.heap = distance_list
    return self.heap

def compute_centroid_two_clusters(self, current_clusters, data_points_index):
    size = len(data_points_index)
    dim = self.dimension
    centroid = [0.0]*dim

```

```

for index in data_points_index:
    dim_data = current_clusters[str(index)]["centroid"]
    for i in range(dim):
        centroid[i] += float(dim_data[i])
for i in range(dim):
    centroid[i] /= size
return centroid

```

```

def compute_centroid(self, dataset, data_points_index):
    size = len(data_points_index)
    dim = self.dimension
    centroid = [0.0]*dim
    for idx in data_points_index:
        dim_data = dataset[idx]["data"]
        for i in range(dim):
            centroid[i] += float(dim_data[i])
    for i in range(dim):
        centroid[i] /= size
    return centroid

```

```

def hierarchical_clustering(self):
    """
    Main Process for hierarchical clustering
    """
    dataset = self.dataset
    current_clusters = self.clusters
    old_clusters = []
    heap = hc.compute_pairwise_distance(dataset)
    heap = hc.build_priority_queue(heap)

    while len(current_clusters) > self.k:
        if self.linkage == 'single':
            dist, m_item = heapq.heappop(heap) # get min distance
        elif self.linkage == 'complete':
            dist, m_item = heapq._heappop_max(heap) # get max distance
        else:
            print("error - heapq not properly assigned.")

        # pair_dist = m_item[0]
        pair_data = m_item[1]
        #pdb.set_trace()
        # judge if include old cluster
        if not self.valid_heap_node(m_item, old_clusters):
            continue

        print('> merging '+str(m_item[1][0][0])+ ' & '+str(m_item[1][1][0])) \
            +' with distance of '+str(rnd(m_item[0], 3)))
        new_cluster = {}
        new_cluster_elements = sum(pair_data, [])
        new_cluster_cendroid = self.compute_centroid(dataset, new_cluster_elements)

        new_cluster_elements.sort()
        new_cluster.setdefault("centroid", new_cluster_cendroid)
        new_cluster.setdefault("elements", new_cluster_elements)
        for pair_item in pair_data:
            old_clusters.append(pair_item)
            del current_clusters[str(pair_item)]
        self.add_heap_entry(heap, new_cluster, current_clusters)
        current_clusters[str(new_cluster_elements)] = new_cluster
        current_clusters = sorted(current_clusters)
    )

```

```

    return current_clusters

def valid_heap_node(self, heap_node, old_clusters):
    pair_dist = heap_node[0]
    pair_data = heap_node[1]
    for old_cluster in old_clusters:
        if old_cluster in pair_data:
            return False
    return True

def add_heap_entry(self, heap, new_cluster, current_clusters):
    for ex_cluster in current_clusters.values():
        new_heap_entry = []
        dist = self.euclidean_distance(ex_cluster["centroid"], new_cluster["centroid"])
        new_heap_entry.append(dist)
        new_heap_entry.append([new_cluster["elements"], ex_cluster["elements"]])
        heapq.heappush(heap, (dist, new_heap_entry))

'''
def evaluate(self, current_clusters):
    gold_standard = self.gold_standard
    current_clustes_pairs = []

    for (current_cluster_key, current_cluster_value) in current_clusters.items():
        tmp = list(itertools.combinations(current_cluster_value["elements"], 2))
        current_clustes_pairs.extend(tmp)
    tp_fp = len(current_clustes_pairs)

    gold_standard_pairs = []
    for (gold_standard_key, gold_standard_value) in gold_standard.items():
        tmp = list(itertools.combinations(gold_standard_value, 2))
        gold_standard_pairs.extend(tmp)
    tp_fn = len(gold_standard_pairs)
    tp = 0.0
    for ccp in current_clustes_pairs:
        if ccp in gold_standard_pairs:
            tp += 1
    if tp_fp == 0:
        precision = 0.0
    else:
        precision = tp/tp_fp
    if tp_fn == 0:
        precision = 0.0
    else:
        recall = tp/tp_fn
    return precision, recall
'''

''' Helper Functions
'''
def load_data(self, input_file_name):
    """
    load data and do some preparations
    """
    input_file = open(input_file_name, 'r')
    dataset = []
    clusters = {}

```

```

gold_standard = {}
id = 0
for line in input_file:
    line = line.strip('\n')
    row = str(line)
    row = row.split(",")
    iris_class = row[-1]

    data = {}
    data.setdefault("id", id)    # duplicate
    data.setdefault("data", row[:-1])
    data.setdefault("class", row[-1])
    dataset.append(data)

    clusters_key = str([id])
    clusters.setdefault(clusters_key, {})
    clusters[clusters_key].setdefault("centroid", row[:-1])
    clusters[clusters_key].setdefault("elements", [id])

    #gold_standard.setdefault(iris_class, [])
    #gold_standard[iris_class].append(id)
    id += 1
return dataset, clusters #, gold_standard

def quit(self, err_desc):
    raise SystemExit('\n'+ "PROGRAM EXIT: " + err_desc + ', please check your in
put' + '\n')

def loaded_dataset(self):
    """
    use for test only
    """
    return self.dataset

def display(self, current_clusters):
    print()
    print('final clusters:')
    clusters = current_clusters
    for cluster in clusters:
        print(cluster)

def get_clusters(clus_set):
    clusters = list()
    for cluster in clus_set:
        clus = cluster.replace('[', '')
        clus = clus.replace(']', '')
        clus = clus.replace(' ', '')
        clusList = clus.split(',')
        clusList = [ int(n) for n in clusList]
        clusters.append(clusList)
    return clusters

def rnd(num, precision):
    return math.floor(num * 10**precision)/10**precision

def get_GT(y):
    pdb.set_trace()

    return y

```

```

.....
"""
"""
Main Method
"""
.....
"""
if __name__ == '__main__':
    '''Pseudo code for part 2:
    - Mix the two datasets to create a new combined dataset, lets call it allD.
    - Use previous implementation to cluster similar data points into two classes,
    S, M, and W.
    - For the two clusters, count the majority class to label the entire cluster.
    - Then, for each cluster, remove unlabeled data and use logistic regression
    to train each cluster on labeled data.

    '''
    ...

```