

# MakerBot/Cleaning Up Point Cloud Meshes in Meshlab For 3D Printing

---


## Purpose

Cleaning up a point cloud mesh of an object in Meshlab so that it can be printed using a 3D printer.


## Deleting Unwanted Background Points

---

1. Open the file that was taken from the Kinect in MeshLab.




Output Mesh




Select Points

2. Select either the desired points or the unwanted points using the **Select Vertices** tool. Rotate the mesh to make selecting easier.




Rotate the mesh to select points for deletion

3. If a selection is made around the points you want to keep, then invert the selection using Filter -> Render -> Invert Selection. Press **ctrl + delete** to delete unwanted points from the mesh.




Delete selected vertices



4. Use **Export as...** (.ply) to save progress. Saving it at this point provides a good backup point, and the image is zoomed and centered when re-opened from the new file.

Or, select the points to be kept points, invert the selection, and delete the unwanted points




Save the mesh (Use export mesh as... choose .ply)

## Rendering the Object

---


### Option "A"

5a. Under the **Filters** tab in the navigation menu choose **Sampling -> Poisson-disk Sampling**. In the **Number of Samples**, pick between 60000 and 100000 sample points (sometimes the system crashes.) Remember to check the **Base Mesh Subsampling** box or you will get an error.




Poisson-disk Sampling

6a. Once the sampling has completed, a new layer will be added. Open the layers window under **View -> Open Layer Dialog** and make sure the **Poisson-disk Samples** layer is highlighted.




Add two zeros to the Number of Samples and check Base Mesh Subsampling




Show Layer Window and select Poisson-disk Samples layer

7a. Next, go to **Filters -> Normals, Curvatures and Orientation -> Compute normals for point sets**. In the new window, put a number greater than 15 for the **Number of Neighbors**.




Compute Normals for Point Set




More than 15 for Number of Neighbors

8a. Click **Apply** and manually **Close** that menu.




Apply




Close menu

9a. Then, go to **Filters -> Points -> Surface Reconstruction Poisson**. This will create a new layer called Poisson Mesh. From there you can add surfaces to the Model.




Surface Reconstruction Poisson



Set the Octree Depth to 9 or 10

10a. Finally save the model in a .obj file format to be opened in Maya or Blender.




Export the mesh as .obj

Note: Meshlab can export the mesh as a .stl file for 3D printing with the MakerBot. However, further 3D modeling is required to create a base, ground layer, or support platform for the object before a printable code can be generated by the Replicator-G software used by the MakerBot.

## Option B

5b. Distribute normals using **Render -> Show Vertex Normals**. This will create normals pointing backwards, so they will need to be recomputed so that the normals are facing forward.



Getting normals

6b. Recompute normals using **Filter > Point Set -> Compute normals for point sets**, change number to 16 for the number of neighbors and also check the box for **Flip Normals**. Change the

camera to -1000 so that the sampling program knows that the cloud point data was taken from a large distance, this would give it a better idea where the normals should go.


7b. Turn on layers from the top menu bar **View -> Open Layer Dialog**.

8b. Now create a subset of the point cloud, go to **Filters > Sampling > Poisson -Disk sampling**, change the **Number of Samples** to 5000 and check the box for **Base Mesh Subsampling**. This will create an even sampling distribution of the cloud points, and will give a general surface to work with.

9b. Click the **Poisson-disk Samples** layer. Now go to **Filters > Point Set > Surface Reconstruction: Poisson**, set parameters, 12 for **Octree Depth** and 7 for **Solver Divide**, these numbers can be changed depending on the scale of the original point cloud mesh. Make the numbers bigger if the point cloud is big.


10b. Turn on the **Light** found within the tool bar and also turn on **Smoothing** which is next to the light button.

11b. Now approximate more normals using the point cloud to add more detail. This time distribute points by going to **Filter > Re-meshing-simplification and reconstruction > Use sub-division algorithm called LS3 loop**. This algorithm will add more detail to the mesh. Sub-sample it three times by setting **Iterations** = 3



adding more detail

12b. Use **File -> Export as...** to save the final version of the mesh which can be printed using a 3d printer.



final image

---

Retrieved from "[https://en.wikiversity.org/w/index.php?title=MakerBot/Cleaning\\_Up\\_Point\\_Cloud\\_Meshes\\_in\\_Meshlab\\_For\\_3D\\_Printing&oldid=2223524](https://en.wikiversity.org/w/index.php?title=MakerBot/Cleaning_Up_Point_Cloud_Meshes_in_Meshlab_For_3D_Printing&oldid=2223524)"

---

This page was last edited on 16 October 2020, at 02:54.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy.