

Lecture 7 – Review Inductive Sets of Data & Recursive Procedures



T. METIN SEZGIN

1

Nugget



Recursion is important

2

Recursion is important

- Recursion is important
 - Syntax in programming languages is nested
- Data definitions can be recursive
- Procedure definitions can be recursive

```

Program ::= Expression
         [a-program (exp1)]

Expression ::= Number
            [const-exp (num)]

Expression ::= - (Expression , Expression)
            [diff-exp (exp1 exp2)]

Expression ::= zero? (Expression)
            [zero?-exp (exp1)]

Expression ::= if Expression then Expression else Expression
            [if-exp (exp1 exp2 exp3)]

Expression ::= Identifier
            [var-exp (var)]

Expression ::= let Identifier = Expression in Expression
            [let-exp (var exp1 body)]

```

Figure 3.2 Syntax for the LET language

3

Nugget

We can define data recursively

4

Defining list of integers

Definition 1.1.3 (list of integers, top-down) A Scheme list is a list of integers if and only if either

1. it is the empty list, or
2. it is a pair whose car is an integer and whose cdr is a list of integers.

Definition 1.1.4 (list of integers, bottom-up) The set *List-of-Int* is the smallest set of Scheme lists satisfying the following two properties:

1. $() \in \text{List-of-Int}$, and
2. if $n \in \text{Int}$ and $l \in \text{List-of-Int}$, then $(n . l) \in \text{List-of-Int}$.

Definition 1.1.5 (list of integers, rules of inference)

$$\begin{array}{c} () \in \text{List-of-Int} \\ \\ \frac{n \in \text{Int} \quad l \in \text{List-of-Int}}{(n . l) \in \text{List-of-Int}} \end{array}$$

5

Grammar example

• Lambda Calculus

Definition 1.1.8 (lambda expression)

$$\begin{array}{l} \text{LcExp} ::= \text{Identifier} \\ \quad ::= (\text{lambda } (\text{Identifier}) \text{ LcExp}) \\ \quad ::= (\text{LcExp } \text{LcExp}) \end{array}$$

where an identifier is any symbol other than `lambda`.

• Concepts

- Variables
- Bound variable

6

Nugget



We can use prove properties of
recursively defined data

7

Induction Example



- **Prove that binary trees have odd number of nodes**
 - Use structural induction
- **Define IH(k)**
 - Any tree of size k has odd number of elements
- **Prove**
 - base case
 - inductive step

Definition 1.1.7 (binary tree)

$Bintree ::= Int \mid (Symbol \ Bintree \ Bintree)$

8

Lecture 8

Recursive Procedures

T. METIN SEZGIN

9

Lecture Nuggets

- We can write programs recursively
 - We can apply the smaller sub-problem principle (wishful thinking)
 - Examples
- If needed we can make use of Auxiliary procedures
- Sometimes it is easier to write more general procedures

10

Nugget



We can solve problems using
recursion

11

Deriving Recursive Programs



- Recursive programs are easy to write if you follow two principles
 - Smaller-sub-problem principle (aka divide and conquer).
 - Follow the Grammar principle

The Smaller-Subproblem Principle

If we can reduce a problem to a smaller subproblem, we can call the procedure that solves the problem to solve the subproblem.

Follow the Grammar!

When defining a procedure that operates on inductively defined data, the structure of the program should be patterned after the structure of the data.

12

Recursive Procedure Example

- Write a new function `list-length`
- Everyone should be able to go this far

```
list-length : List → Int
usage: (list-length l) = the length of l
(define list-length
  (lambda (lst)
    ...))
```

- Let the definition of `list` guide you

List ::= () | (Scheme value . List)

```
list-length : List → Int
usage: (list-length l) = the length of l
(define list-length
  (lambda (lst)
    (if (null? lst)
        0
        ...)))
```



```
list-length : List → Int
usage: (list-length l) = the length of l
(define list-length
  (lambda (lst)
    (if (null? lst)
        0
        (+ 1 (list-length (cdr lst)))))))
```

13

Nugget

If needed, we can use auxiliary procedures

18

subst



subst

The procedure `subst` should take three arguments: two symbols, `new` and `old`, and an s-list, `slist`. All elements of `slist` are examined, and a new list is returned that is similar to `slist` but with all occurrences of `old` replaced by instances of `new`.

```
> (subst 'a 'b '((b c) (b () d)))
((a c) (a () d))
```

19

How do we go about the implementation?



The Smaller-Subproblem Principle

If we can reduce a problem to a smaller subproblem, we can call the procedure that solves the problem to solve the subproblem.

Follow the Grammar!

When defining a procedure that operates on inductively defined data, the structure of the program should be patterned after the structure of the data.

20

How do we go about the implementation?

- The grammar

$$S\text{-list} ::= (\{S\text{-exp}\}^*)$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

$$S\text{-list} ::= ()$$

$$::= (S\text{-exp} \ . \ S\text{-list})$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

- The procedure

```
subst : Sym × Sym × S-list → S-list
(define subst
  (lambda (new old slist)
    ...))

subst-in-s-exp : Sym × Sym × S-exp → S-exp
(define subst-in-s-exp
  (lambda (new old sexp)
    ...))
```

21

How do we go about the implementation?

- The grammar

$$S\text{-list} ::= (\{S\text{-exp}\}^*)$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

$$S\text{-list} ::= ()$$

$$::= (S\text{-exp} \ . \ S\text{-list})$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

- The procedure

```
subst : Sym × Sym × S-list → S-list
(define subst
  (lambda (new old slist)
    (if (null? slist)
        '()
        ...)))
```

22

How do we go about the implementation?

- The grammar

$$S\text{-list} ::= (\{S\text{-exp}\}^*)$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

$$S\text{-list} ::= ()$$

$$::= (S\text{-exp} . S\text{-list})$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

- The procedure

```
subst : Sym × Sym × S-list → S-list
(define subst
  (lambda (new old slist)
    (if (null? slist)
        '()
        (cons
         (subst-in-s-exp new old (car slist))
         (subst new old (cdr slist))))))
```

23

How do we go about the implementation?

- The grammar

$$S\text{-list} ::= (\{S\text{-exp}\}^*)$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

$$S\text{-list} ::= ()$$

$$::= (S\text{-exp} . S\text{-list})$$

$$S\text{-exp} ::= \text{Symbol} \mid S\text{-list}$$

- The procedure

```
subst : Sym × Sym × S-list → S-list
(define subst
  (lambda (new old slist)
    (if (null? slist)
        '()
        (cons
         (subst-in-s-exp new old (car slist))
         (subst new old (cdr slist))))))

subst-in-s-exp : Sym × Sym × S-exp → S-exp
(define subst-in-s-exp
  (lambda (new old sexp)
    (if (symbol? sexp)
        (if (eqv? sexp old) new sexp)
        (subst new old sexp))))
```

24

Things to note

- The procedures are mutually recursive
- The trick of decomposing procedures for each syntactic type is important
 - Simplifies our design

```
S-list ::= ()
        ::= (S-exp . S-list)
S-exp ::= Symbol | S-list
```

```
subst : Sym × Sym × S-list → S-list
(define subst
  (lambda (new old slist)
    (if (null? slist)
        '()
        (cons
         (subst-in-s-exp new old (car slist))
         (subst new old (cdr slist))))))
```

```
subst-in-s-exp : Sym × Sym × S-exp → S-exp
(define subst-in-s-exp
  (lambda (new old sexp)
    (if (symbol? sexp)
        (if (eqv? sexp old) new sexp)
        (subst new old sexp)))))
```

25

Take home message

Follow the Grammar

More precisely:

- Write one procedure for each nonterminal in the grammar. The procedure will be responsible for handling the data corresponding to that nonterminal, and nothing else.
- In each procedure, write one alternative for each production corresponding to that nonterminal. You may need additional case structure, but this will get you started. For each nonterminal that appears in the right-hand side, write a recursive call to the procedure for that nonterminal.

26

Nugget



Sometimes it is easier to write more general procedures

27

A more complex example



- Consider the procedure **number-elements**
- This procedure should take a list $(v_0 \ v_1 \ v_2 \ \dots)$ and return $((0 \ v_0) \ (1 \ v_1) \ \dots)$.
- Remember the grammar

$$\begin{aligned} S\text{-list} &::= () \\ &::= (S\text{-exp} \ . \ S\text{-list}) \\ S\text{-exp} &::= \text{Symbol} \mid S\text{-list} \end{aligned}$$
- The problem
 - No obvious way to build `(number-elements lst)` from `(number-elements (cdr lst))`
- The solution
 - Implement something *more general*
 - Implement **number-elements-from**

$$\text{number-elements-from} : \text{Listof}(\text{SchemeVal}) \times \text{Int} \rightarrow \text{Listof}(\text{List}(\text{Int}, \text{SchemeVal}))$$

28

number-elements-from

number-elements-from : $Listof(SchemeVal) \times Int \rightarrow Listof(List(Int, SchemeVal))$

usage: (number-elements-from '(v₀ v₁ v₂ ...) n)
 = ((n v₀) (n+1 v₁) (n+2 v₂) ...)
 (define number-elements-from
 (lambda (lst n)
 (if (null? lst) '()
 (cons
 (list n (car lst))
 (number-elements-from (cdr lst) (+ n 1))))))

number-elements : $List \rightarrow Listof(List(Int, SchemeVal))$
 (define number-elements
 (lambda (lst)
 (number-elements-from lst 0)))

- How are the arguments different?
- What purpose do they serve?
 - Input list
 - Context argument (inherited attribute)

29

The take home message

Follow the grammar

When following the grammar doesn't help...

Generalize

30

Another example

- Consider **list-sum**

```
list-sum : Listof(Int) → Int
(define list-sum
  (lambda (loi)
    (if (null? loi)
        0
        (+ (car loi)
            (list-sum (cdr loi)))))))
```

- How about vector sum?
- You can't take cdr of vectors!

31

How do we go about the implementation?

Follow the grammar

When following the grammar doesn't help...

Generalize

32

vector-sum



```

partial-vector-sum : Vectorof(Int) × Int → Int
usage: if  $0 \leq n < \text{length}(v)$ , then
      (partial-vector-sum v n) =  $\sum_{i=0}^{i=n} v_i$ 

(define partial-vector-sum
  (lambda (v n)
    (if (zero? n)
        (vector-ref v 0)
        (+ (vector-ref v n)
            (partial-vector-sum v (- n 1))))))

vector-sum : Vectorof(Int) → Int
usage: (vector-sum v) =  $\sum_{i=0}^{i=\text{length}(v)-1} v_i$ 

(define vector-sum
  (lambda (v)
    (let ((n (vector-length v)))
      (if (zero? n)
          0
          (partial-vector-sum v (- n 1))))))

```

33

Problem set o



- EOPL Exercises
 - 1.1, 1.4, 1.6, 1.12, 1.21, 1.26, 1.34, 1.36

34