


	General Table	
PART NO.	DESCRIPTION	QUANTITY
J-01	JOE'S CNC 4X4 Hybrid TOP ASSEMBLY	
J-01a	TIMING BELT PULLEY ASSEMBLY	
J-02	BED ASSEMBLY	1
J-03	BASE STAND	1
J-04	Y-AXIS SIDE SUPPORTS W/ V-BEARING RAIL ASSEMBLY	2
J-05	Y-AXIS CARRIAGE	2
J-06	Y-AXIS MOTOR AND FLANGE BEARING MOUNT	4
J-07	X-AXIS V-BEARING RAIL ASSEMBLY	1
J-08	X-AXIS V-BEARING SLIDE	1
J-09	X-AXIS MOTOR AND FLANGE BEARING MOUNT	2
J-09a	X-AXIS 80/20 FRONT SUPPORT	4
J-10	Z-AXIS CARRIAGE	1
J-11	Z-AXIS MOTOR AND FLANGE BEARING MOUNT	1
J-12	Z-AXIS SLIDE	1
	ROUTER MOUNT, Obtained from K2CNC	1

Joe's CNC 4x4 Hybrid

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
JOE CANTRILL. ANY REPRODUCTION IN
PART OR AS A WHOLE WITHOUT THE
WRITTEN PERMISSION IS PROHIBITED.

J-01



JOE'S CNC 4X4 HYBRID

Parts Description	Supplier	Quantity
8020 T Slot Aluminum Extrusion 25 S 25-5010 x 72	http://8020inc.com	3
8020 T Slot Hardware T Nuts 10 S 3382 (25pcs) N	http://8020inc.com	6
()		
1018 Carbon Steel Acme Threaded Rod 1/2"-10 5-Start (2tpi) #99030A704	http://www.mcmaster.com	3
1018 Carbon Steel Acme Threaded Rod 1/2"-8 2-Start (4tpi) #99030A316	http://www.mcmaster.com	1
ACME Anti-Backlash Leadnuts - 1/2"-10 ACME 5 Start (2 turns per inch)	www.dumpstorene.com	3
ACME Anti-Backlash Leadnuts - 1/2"-8 ACME 2 Start (4 turns per inch)	www.dumpsterene.com	3
	www.dumpstercnc.com	1
Add a 1-3/16" machined square flange	www.dumpstercnc.com	4
1/4 Bore no kw LoveJoy L050 Jaw Coupling Hub Model #990-4044	http://use-enco.com	4
1/2 Bore no kw LoveJoy L050 Jaw Coupling Hub / Model #990-4046	http://use-enco.com	4
LoveJoy Spider	http://use-enco.com	4
1/2" Bore 4 Bolt Flange Bearing Seller: TheBigBearingStore	www.ebay.com	7
GW2X Size 2 Guide Wheel Sealed V Bearing	http://www.superiorbearing.com	16
Concentric bushing for V-groove wheel #2	http://www.cadcamcadcam.com	4
Eccentric bushing for V-groove wheel #2	http://www.cadcamcadcam.com	4
Skate Bearing 5/16" bore		2
3/4" x 3/4" x 1/8" angle iron 72"	Home Depot	6
1/8"x1"x36" Flat Aluminum	Home Depot	3
Superstrut (Unistrut) 1-5/8" x 1-5/8" x 10' 12Ga. Standard Length	Home Depot	5
Superstrut (Unistrut) 1-5/8" x 15/16" x 10' 14Ga. Standard Length	Home Depot	6
90 Degree Angle Superstrut (Unistrut) 1/2" two hole brackets	Home Depot	20
90 Degree Angle Superstrut (Unistrut) 1/2" four hole brackets	Home Depot	8
1/2" Spring Nut Bags (5 pieces)	Home Depot	14
1/4" Spring Nut Bags (5 pieces)	Home Depot	6
4/4 4/0 1.	D 11 1	
1/4" x 1/2" machine screws	Boltdepot.com	58
1/4" x 3/4" Bolts	Boltdepot.com	36
1/4" x 1-1/4" Bolts	Boltdepot.com	26
1/4" x 1-1/2" Bolts	Boltdepot.com	48
1/4" x 2" Bolts	Boltdepot.com	14
1/4" x 3" Bolts	Boltdepot.com	8

Parts Description	Supplier	Quantity
4 / 4	Dultiland	00
1/4" - 20 nuts	Boltdepot.com	68
1/4" - Flat Washers	Boltdepot.com	175
1/4" - Lock Washers	Boltdepot.com	303
3/8" x 2" Bolts	Boltdepot.com	24
3/8" x 2.5" Bolts	Boltdepot.com	8
3/8" - Flat Washers	Boltdepot.com	44
3/8" - Lock Washers	Boltdepot.com	64
3/8" - Nuts	Boltdepot.com	40
5/16" x 5" Bolts	Boltdepot.com	1
5/16" washers	Boltdepot.com	2
5/16" Lock Washers	Boltdepot.com	1
5/16" Nuts	Boltdepot.com	1
1/2" x 1" Bolts	Boltdepot.com	44
1/2" x 1-1/2" Bolts	Boltdepot.com	25
1/2" x 2" Bolts	Boltdepot.com	4
1/2" x 2-1/2" Bolts	Boltdepot.com	2
1/2" Washers	Boltdepot.com	44
1/2" Lock Washers	Boltdepot.com	70
Hitachi Router 2.25 hp	www.Lowes.com	1
Hitachi Router Mount	www.k2cnc.com	1
Timing Belt L 3/8" Pitch Belt 141" - QB-L14175-050	www.econobelt.com	1
Timing Belt Pulley L 1/4" bore QPELN50015F08	www.econobelt.com	2
Timing Belt Pulley L 1/4" bore QPELN50015F10	www.econobelt.com	1

NOTE:


1. As always it is better to get more than you need of hardware so you do not run short.


2. You may also want to purchase hardware in Bulk to save money.


3. Due to some Manufacturers the Bolt lengths may vary slightly, so it is Suggested to purchase a few 1/4"-20 x 1" bolts


Joe's CNC 4x4 Hybrid


Bill of Materials






























Y-Axis Flange Bearing Mount H.D.P.E.




Y-Axis Motor and Flange Bearing Side Plate H.D.P.E.




Y-Axis Motor and Flange Bearing Side Plate H.D.P.E.

Y-Axis Motor and Flange Bearing Assembly Templates


			UNLESS OTHERWISE SPECIFIED:		NAME	DATE					
			DIMENSIONS ARE IN INCHES	DRAWN	J.R.C.	01-01-07					
			TOLERANCES: FRACTIONAL ±	CHECKED			TITLE:			N 1 \bigcirc	
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.				J(oe's C	INC	,
			THREE PLACE DECIMAL ±						4 1 1 1		- 1
PROPRIETARY AND CONFIDENTIAL			INTERPRET GEOMETRIC TOLERANCING PER:					<u>4</u>	<u>x4 Hyk</u>	<u> </u>	_
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			MATERIAL	COMMENTS:			SIZE [DWG.	NO.		REV
JOE CANTRILL, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D		J-0	6	
	APPLIC	ATION					SCALE	: 1:1	WEIGHT:	SHEE	T 2 OF 2
Δ											



Rear View



Isometric View





Front View Template


Y-Axis Anti-Backlash Nut Housing


Note: 2 parts needed


			UNLESS OTHERWISE SPECIFIED:		NAME	DATE					
			DIMENSIONS ARE IN INCHES	DRAWN	J.R.C.	01-01-07					
			TOLERANCES: FRACTIONAL±	CHECKED			TITLE:		N 1 \bigcirc		
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.				JO	e's C	ИC	
			THREE PLACE DECIMAL ±					$\frac{1}{4x}$	<u>Л Цу/</u>	<u>arid</u>	•
PROPRIETARY AND CONFIDENTIAL			INTERPRET GEOMETRIC TOLERANCING PER:				_	<u>47</u>	4 1191	<u>JIIU</u>	ı
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			MATERIAL	COMMENTS:			_	DWG. N			REV
JOE CANTRILL, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D		J-06	a	
	APPLIC	CATION					SCALE	E: 2:1		SHEET	1 OF 1
Δ			,								




















X-Axis Motor and Flange Bearing Side Plate H.D.P.E.


X-Axis Motor and Flange Bearing Side Plate H.D.P.E.


X-Axis Flange Bearing Mount H.D.P.E.

X-Axis Motor Mount H.D.P.E.

X-Axis Motor and Flange Bearing Mount Templates

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
			DIMENSIONS ARE IN INCHES	DRAWN	J.R.C.	01-01-08				
			TRACIONAL:	CHECKED			TITLE:			
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.] .	Joe's C	JNC	,
			THREE PLACE DECIMAL ±				-			_
PROPRIETARY AND CONFIDENTIAL			INTERPRET GEOMETRIC					<u>4x4 Hy</u>	<u>bric</u>	<u>1</u>
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			TOLERANCING PER: MATERIAL	COMMENTS:			SIZE DWG	. NO.		REV
JOE CANTRILL, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D	J-()9	
	APPLIC	CATION					SCALE: 1:1	WEIGHT:	SHEET 2	2 OF 2
Δ '							1	-		








X-Axis 80/20 Front Support Template


X-AXIS 80/20 FRONT SUPPORT

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
			DIMENSIONS ARE IN INCHES	DRAWN						
			TOLERANCES: FRACTIONAL±	CHECKED			TITLE:	•		
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.				JOE	e's Cl	VC
			THREE PLACE DECIMAL ±	MFG APPR.					Llvh	rid
DDODDIETADY AND CONFIDENTIAL			INTERPRET GEOMETRIC	Q.A.				<u>4x4</u>	<u>пук</u>	<u> </u>
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF JOE CANTRILL, ANY REPRODUCTION			TOLERANCING PER: MATERIAL	COMMENTS:			SIZE C	DWG. NO.	1.00	REV
IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D	_	J-09a	3
	APPLIC	CATION					SCALE	: 1:1 WEIGHT	Γ: SI	HEET 1 OF 1
Δ.			·				1		•	












<u>Isometric Bottom View</u> <u>Motor and Flange Bearing mount</u>



<u>Bottom View</u> <u>Motor and Flange Bearing mount</u>




	BOM	Table	
ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	Z-Axis Flange Bearing Mount	Z-Axis Flange Bearing Mount	1
2	Z-Axis Motor Mount	Z-Axis Motor Mount	1
3	Regular FW 0.25	1/4" Flat Washer	8
4	Z-Axis Motor Support Walls	Z-Axis Motor Support Walls	2
5	Regular LW 0.25	1/4" Lock Washer	8
6	HBOLT 0.2500-20x1.5x0.75-N	Hex Bolt 1/4"-20 x 1-1/2" x 3/4" thread	8



ITEM No.


<u>Isometric Top View - Motor mount</u>




<u> Top View - Motor mount</u>


Z-Axis Motor and Flange Bearing Mount

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
			DIMENSIONS ARE IN INCHES	DRAWN	J.R.C.	01-01-08				
			TOLERANCES: FRACTIONAL ±	CHECKED			TITLE:			
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.			J	oe's C		
			THREE PLACE DECIMAL ±					x4 Hy/	hrid	-
PROPRIETARY AND CONFIDENTIAL			INTERPRET GEOMETRIC TOLERANCING PER:				<u> </u>	74 1 y 	OHO	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			MATERIAL	COMMENTS:			SIZE DWG	i. NO.	44	REV
JOE CANTRILL, ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D	J-	11	
	APPLIC	CATION					SCALE: 1:1	WEIGHT:	SHEE	T 1 OF 2
Δ	2		·	Т	·		1			






Z-Axis Flange Bearing Plate Template




Z-Axis Motor Side Support Walls Template




Z-Axis Motor Mount Plate Template


Z-Axis Motor and Flange Bearing Mount Dimensional and Template plan


			UNLESS OTHERWISE SPECIFIED:		NAME	DATE				
-			DIMENSIONS ARE IN INCHES	DRAWN	J.R.C.	01-01-08				
			TOLERANCES: FRACTIONAL±	CHECKED			TITLE:		10	
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.] JO6	e's CN		
			THREE PLACE DECIMAL ±				$\frac{1}{\sqrt{\sqrt{2}}}$	l Hyh	\overline{rid}	
PROPRIETARY AND CONFIDENTIAL			INTERPRET GEOMETRIC TOLERANCING PER:				4 1 4 1	<u>FIIYO</u>	<u>11U</u>	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF JOE CANTRILL ANY REPRODUCTION			MATERIAL MATERIAL	COMMENTS:			SIZE DWG. NO		_	REV
IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH	1			D	J-1	1	
	APPLIC	CATION					SCALE: 1:1		SHEET	2 OF 2
Δ.	2						1			





RACK & PINION ADDENDUM SHEETS






Y-Axis Cam Adjuster Assembly (x2)


Isometric View


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	0.50in Cam Adjuster		1
2	HBOLT 0.2500- 20x2x0.75-S		1
3	Regular FW 0.25		1
4	Regular LW 0.25		1
5	HNUT 0.2500-20-D-N		1



Upper Left
Y-Axis Bearing Assembly
Isometric View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	HBOLT 0.3750-		1
	16x3.5x3.5-S		
2	Regular FW 0.375		2
3	V-Bearing No.2	V-Bearing - No.2	1
4	HNUT 0.3750-16-D-N		2
5	Regular LW 0.375		1
6	0.375 locknut	1/4 inch locknut	1





Lower Y-Axis Bearing Assembly (x2)
Isometric View

1/4 inch locknut

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	HBOLT 0.3750- 16x2.5x2.5-S		1
2	Regular FW 0.375		2
3	V-Bearing No.2	V-Bearing - No.2	1
4	HNUT 0.3750-16-D-N		2
5	Regular LW 0.375		1


3


7.500 0.625 0.625


Y-Axis V-Bearing Preasure Plate (x4)
Scale 1:1


Y-AXIS CARRIAGE Assembly Parts


_							
			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	R&P ADDENDUM
			DIMENSIONS ARE IN INCHES	DRAWN			KAI ADDLINDUM
			TOLERANCES: FRACTIONAL±	CHECKED			Joe's CNC
			ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ±	ENG APPR.			4 4 1 1 1
			THREE PLACE DECIMAL ±	MFG APPR.			4x4 Hybrid
			INTERPRET GEOMETRIC	Q.A.			Rack and Pinion
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS			TOLERANCING PER:	COMMENTS:			
DRAWING IS THE SOLE PROPERTY OF			MATERIAL				SIZE DWG. NO REV
JOE CANTRILL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH	_			D R&P J-10
	APPLI	CATION					SCALE: 2:1 SHEET 2 OF 3


















X-Axis Carriage Front View

6



4

5



X-Axis Carriage Isometric Front View

7


8

X-Axis Carriage Isometric Rear View

1


X-AXIS CARRIAGE W/ BEARING ASSEMBLIES

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE)ENIDITI	١ ٨
			TOLERANCES: FRACTIONAL±	DRAWN			R&P ADDENDU TITLE: Joe's CNC		<u> </u>
				CHECKED					
				ENG APPR.					
			THREE PLACE DECIMAL ±	MFG APPR.			4X4 F	lybrid	
DRODDISTA DV AND CONFIDENTIAL			INTERPRET GEOMETRIC	Q.A.			Rack ar	nd Pinic	n
PROPRIETARY AND CONFIDENTIAL			TOLERANCING PER:	COMMENTS:					
E INFORMATION CONTAINED IN THIS RAWING IS THE SOLE PROPERTY OF			MATERIAL				SIZE DWG. NO.		REV
E CANTRILL. ANY REPRODUCTION IN R. R. TOR AS A WHOLE WITHOUT THE RITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH	_			D R&P J	-10	
	APPLI	CATION					SCALE: 1:5	SHEET	1 OF 4




X-Axis V-Bearing Bottom Assembly (x2)
Isometric View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	V-Bearing No.2	V-Bearing - No.2	2
2	HNUT 0.3750-16-D-N		8
3	Regular FW 0.375		2
4	Regular LW 0.375		1
5	0.375 x 7.5in Threaded Rod		1
6	0.375 locknut	1/4 inch locknut	1




Z-Axis V-Bearing Concentric Assembly Isometric View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	V-Bearing No.2	V-Bearing - No.2	1
2	V-Bearring Concentric Bushing	V-Bearring Concentric Bushing	1
3	HBOLT 0.2500- 20x3.25x0.75-S		1
4	Regular LW 0.25		2
5	Regular FW 0.25		1
6	HNUT 0.2500-20-D-N		1




Z-Axis V-Bearing Eccentric Assembly Isometric View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	V-Bearing No.2	V-Bearing - No.2	1
2	HBOLT 0.2500- 20x3.25x0.75-S		1
3	Regular LW 0.25		2
4	Regular FW 0.25		1
5	HNUT 0.2500-20-D-N		1
6	V-Bearring Eccentric Bushing	V-Bearring Eccentric Bushing	1




X-Axis V-Bearing Top Left Assembly Isometric View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	0.375 x 8in Threaded Rod		1
2	V-Bearing No.2	V-Bearing - No.2	2
3	HNUT 0.3750-16-D-N		8
4	Regular FW 0.375		2
5	0.375 locknut	1/4 inch locknut	2
6	Regular LW 0.375		1



X-Axis Cam Adjuster Assembly
Isometric View


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	0.50in Cam Adjuster		1
2	0.25 locknut		1
3	0.25x7.5 threaded rod		1
4	Regular FW 0.25		1
5	Regular LW 0.25		1
6	HNUT 0.2500-20-D-N		1



X&Z-Axis V-Bearing Pressure Plate (x6)
Isometric View


4

3



X-Axis V-Bearing Top Right Assembly Isometric View


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	0.375 x 8in Threaded Rod		1
2	V-Bearing No.2	V-Bearing - No.2	2
3	HNUT 0.3750-16-D-N		7
4	Regular FW 0.375		3
5	0.375 locknut	1/4 inch locknut	2




X-Axis V-Bearing Pressure Plate (x7)
Isometric View

X-AXIS CARRIAGE ASSEMBLY PARTS

			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	R&P ADDE	VIDI IVA
			DIMENSIONS ARE IN INCHES	DRAWN			KAI ADDL	ואטטואו
			TOLERANCES: FRACTIONAL ±	CHECKED			Joe's CNC	
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.			4 4 1 1 1 1	
			THREE PLACE DECIMAL ±	MFG APPR.			4x4 Hyk	orid
			INTERPRET GEOMETRIC	Q.A.			Rack and	Pinion
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS			TOLERANCING PER: MATERIAL	COMMENTS:				
DRAWING IS THE SOLE PROPERTY OF JOE CANTRILL, ANY REPRODUCTION IN			MATERIAL				SIZE DWG. NO.	REV
PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D R&P J-1	10
	APPLIC	CATION					SCALE: 1:1	SHEET 2 OF 4




X-Axis Carriage Front Plate
3/4" MDF




X-Axis Carriage Front Plate
3/4" MDF

X-AXIS CARRIAGE Template PARTS


			LIN II FOR OTHERWISE OPEOURIED					
			UNLESS OTHERWISE SPECIFIED		NAME	DATE	⊢ R&P ADDEN	
			DIMENSIONS ARE IN INCHES	DRAWN			KOI ADDLIN	DOIN
			TOLERANCES: FRACTIONAL±	CHECKED			TITLE: Joe's CN	
			ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG APPR.			1063 CIVC	
			THREE PLACE DECIMAL ±	MFG APPR.			4x4 Hybi	ria
			INTERPRET GEOMETRIC	Q.A.			Rack and F	Pinion
PROPRIETARY AND CONFIDENTIAL			TOLERANCING PER:	COMMENTS:			Rack and I	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF			MATERIAL				SIZE DWG. NO.	REV
JOE CANTRILL. ANY REPRODUCTION IN							DODI11	1
PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	NEXT ASSY	USED ON	FINISH				D R&P J-10	J
	APPLIC	CATION					SCALE: 1:1	SHEET 4 OF 4







Z-Axis Motor and Flange Bearing Assembly Isometric View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	Z-Axis Motor Mount	Z-Axis Motor Mount	1
2	Regular FW 0.25	1/4" Flat Washer	4
3	Regular LW 0.25	1/4" Lock Washer	4
4	HBOLT 0.2500- 20x1.5x0.75-N Nema23 Motor with	Hex Bolt 1/4"-20 x 1-1/2" x 3/4" thread	4
5	Nema23 Motor with Lovejoy Couplers		1
6	Regular LW 0.375		12
7	Regular LW 0.25		4
8	Z-Axis Motor Support Walls	Z-Axis Motor Support Walls	1
9	Z-Axis Motor Support Walls	Z-Axis Motor Support Walls	2
10	Flange Bearing	3-1/2" x 3-1/2" 4 Hole Flange Bearing 1/2" bore	2
11	Z-Axis Flange Bearing Mount	Z-Axis Flange Bearing Mount	1
12	HBOLT 0.2500- 20x1.5x0.75-S		8
13	HBOLT 0.3125- 18x2x0.875-N		4
14	HBOLT 0.3750- 16x2.5x1-N		4
15	Regular FW 0.375		8
16	HNUT 0.3750-16-D-N		8




Z-Axis Middle Flange Bearing Support






Z-Axis Flange Bearing Mount



Z-Axis Motor Support walls



Z-Axis Motor and Flange Bearing Assembly W/ ASSEMBLIES

			UNLESS OTHERWISE SPECIFIED	:	NAME	DATE		EVIDIIVA	
			DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL± ANGULAR: MACH± BEND± TWO PLACE DECIMAL± THREE PLACE DECIMAL±	DRAWN			R&P ADDENDUM		
				CHECKED			Joe's CNC	CNC	
				ENG APPR.			4 4 1 1 1 1		
				MFG APPR.			4x4 Hybrid		
ROPRIETARY AND CONFIDENTIAL			INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.			Rack and	ck and Pinion	
INFORMATION CONTAINED IN THIS WING IS THE SOLE PROPERTY OF CANTRILL. ANY REPRODUCTION IN TOR AS A WHOLE WITHOUT THE ITEN PERMISSION IS PROHIBITED.			MATERIAL COMMENTS:				SIZE DWG. NO.	REV	
	NEXT ASSY	USED ON	FINISH				D R&P J-		
	APPLICATION						SCALE: 1:1	SHEET 1 OF 1	