
EE116C/CS151B Fall 2017

Instructor: Professor Lei He

TA: Yuan Liang



. . . .


Definition of Instruction set architecture (ISA, or IS, or Instruction set) from Wiki:

An instruction set architecture (ISA) is a group of commands for a CPU in machine language.

It is an abstract model of a computer.

Different computers have different instruction sets.

Format:



Serves as an interface between software and hardware

Types of ISA:

CISC (Complex Instruction Set Computers) large # of instructions Advantage: many specialized instructions optimized at the instructions level Disadvantage: various CPI Intel's x86 (1978)

RISC (Reduced Instruction Set Computers)

relatively fewer instructions
Advantage:
 same CPI -> enable pipelining and parallelism
Disadvantage:
 more instructions.
 more registers for intermediate results.
MIPS

Registers in MIPS:

What is register:

Inside processor, use for frequently accessed data and fast calculation.

How many registers in MIPS:


32

How large are them:

32bit

How they work:

Load values from memory into registers Store result from register to memory



Registers in MIPS:

```
C code:

f = (g + h) - (i + j);

Compiled MIPS code:

add $t0, $s1, $s2

add $t1, $s3, $s4
```


sub \$s0, \$t0, \$t1

Instructions in MIPS

Instructions formats are hard encoded in binary

For MIPS instructions

Encoded as 32-bit instruction words Small number of formats encoding operation code (opcode), register numbers, ...



Instructions in MIPS

R-format Instructions

ор	rs	rt	rd	shamt	funct
6 bits	5 bits	5 bits	5 bits	5 bits	6 bits

op: operation code (opcode)


rs: first source register number


rt: second source register number

rd: destination register number

shamt: shift amount (00000 for now)

funct: function code (extends opcode)





Instructions in MIPS

I-format Instructions

ор	rs	rt	constant or address
6 bits	5 bits	5 bits	16 bits

op: operation code (opcode)

rs: first source register number

rt: destination or source register number

Constant: -2^{15} to $+2^{15} - 1$

Address: offset added to base address in rs

lw \$s1, 100(\$s2)



35	18	17	100

beq \$s1, \$s2, 100



4	17	18	25

Instructions in MIPS

J-format Instructions

	ор	address
	6 bits	26 bits
op: operation code (opcode)		j 10000
Address: abs	olute address	
	2	2500


Instructions in MIPS

How does processor know what kind of instructions it is?

And how to parse it.

- arithmetic
 - add, subtract, multiply, divide, ...
- logical
 - and, or, shift left, shift right, ...
- data transfer
 - load word, store word
- conditional branch
 - beq & bne are PC-relative, since most targets are nearby
- unconditional jump
 - jump, jump register, branch and link

The big picture:



What is ISA ISA style ISA for MIPS

ISA in processor