

Python from Scratch

Python For Loops

Lesson 16

- **Python For Loops**
- **Looping Through a String**
- **The break Statement**
- **The continue Statement**
- **The range() Function**
- **Else in For Loop**
- **Nested Loops**
- **The pass Statement**
- **Python - For Loops Exercises**

Python For Loops

Python For Loops

A **for** loop is used for iterating over a sequence (that is either a list, a tuple, a dictionary, a set, or a string).

This is less like the **for** keyword in other programming languages, and works more like an iterator method as found in other object-orientated programming languages.

With the **for** loop we can execute a set of statements, once for each item in a list, tuple, set etc.

Example

Print each fruit in a fruit list:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    print(x)
```

The **for** loop does not require an indexing variable to set beforehand.

Looping Through a String

Even strings are iterable objects, they contain a sequence of characters:

Example

Loop through the letters in the word "banana":

```
for x in "banana":
    print(x)
```

The break Statement

With the **break** statement we can stop the loop before it has looped through all the items:

Example

Exit the loop when **x** is "banana":

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    print(x)
    if x == "banana":
        break
```

Example

Exit the loop when **x** is "banana", but this time the break comes before the print:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    if x == "banana":
        break
    print(x)
```

The continue Statement

With the **continue** statement we can stop the current iteration of the loop, and continue with the next:

Example

Do not print banana:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    if x == "banana":
        continue
    print(x)
```

The range() Function

To loop through a set of code a specified number of times, we can use the `range()` function,

The `range()` function returns a sequence of numbers, starting from 0 by default, and increments by 1 (by default), and ends at a specified number.

Example

Using the `range()` function:

```
for x in range(6):  
    print(x)
```

Note that `range(6)` is not the values of 0 to 6, but the values 0 to 5.

The `range()` function defaults to 0 as a starting value, however it is possible to specify the starting value by adding a parameter: `range(2, 6)`, which means values from 2 to 6 (but not including 6):

Example

Using the start parameter:

```
for x in range(2, 6):  
    print(x)
```

The `range()` function defaults to increment the sequence by 1, however it is possible to specify the increment value by adding a third parameter: `range(2, 30, 3)`:

Example

Increment the sequence with 3 (default is 1):

```
for x in range(2, 30, 3):  
    print(x)
```

Else in For Loop

The **else** keyword in a **for** loop specifies a block of code to be executed when the loop is finished:

Example

Print all numbers from 0 to 5, and print a message when the loop has ended:

```
for x in range(6):  
    print(x)  
else:  
    print("Finally finished!")
```

Note: The **else** block will NOT be executed if the loop is stopped by a **break** statement.

Example

Break the loop when **x** is 3, and see what happens with the **else** block:

```
for x in range(6):  
    if x == 3: break  
    print(x)  
else:  
    print("Finally finished!")
```

Nested Loops

A nested loop is a loop inside a loop.

The "inner loop" will be executed one time for each iteration of the "outer loop":

Example

Print each adjective for every fruit:

```
adj = ["red", "big", "tasty"]
fruits = ["apple", "banana", "cherry"]

for x in adj:
    for y in fruits:
        print(x, y)
```

The pass Statement

`for` loops cannot be empty, but if you for some reason have a `for` loop with no content, put in the `pass` statement to avoid getting an error.

Example

```
for x in [0, 1, 2]:
    pass
```

Test Yourself With Exercises

Exercise:

Loop through the items in the `fruits` list.

```
fruits = ["apple", "banana", "cherry"]
 x  fruits
print(x)
```