

```

<chs>          ::= <churras>
<churras>      ::= <if> <churras> | <for> <churras> | <while> <churras> | <
    declaracao> <churras> | <entrada> <churras> | <saida> <churras> | <
    atribuicao> <churras> |  $\epsilon$ 
<declaracao>   ::= tipo id ;
<while>        ::= rodizio <exp> { <churras> }
<for>          ::= grelhar id <exp> { <churras> }
<if>           ::= ta_no_ponto? <exp> { <churras> } <if_comp>
<if_comp>      ::= queimou { <churras> } |  $\epsilon$ 
<entrada>      ::= espetar id ;
<saida>        ::= servir <out> <saida_comp>
<saida_comp>   ::= , <out> <saida_comp> | ;
<out>          ::= char | string | id | servido | <exp>
<atribuicao>    ::= id = <exp> ;
<exp>          ::= <logical-or>
<logical-or>   ::= <logical-and> <or-tail>
<or-tail>      ::= || <logical-and> <or-tail> |  $\epsilon$ 
<logical-and>  ::= <comparison> <and-tail>
<and-tail>     ::= && <comparison> <and-tail> |  $\epsilon$ 
<comparison>   ::= <additive> <comp-tail>
<comp-tail>    ::= == <additive> | != <additive> | < <additive> | > <additive> |
    <= <additive> | >= <additive> |  $\epsilon$ 
<additive>     ::= <term> <add-tail>
<add-tail>     ::= + <term> <add-tail> | - <term> <add-tail> |  $\epsilon$ 
<term>         ::= <factor> <term-tail>
<term-tail>    ::= * <factor> <term-tail> | / <factor> <term-tail> | % <factor>
    <term-tail> |  $\epsilon$ 
<factor>       ::= <unary> <factor-tail>
<factor-tail>  ::= ** <unary> <factor-tail> |  $\epsilon$ 
<unary>        ::= - <unary> | ! <unary> | <primary>
<primary>      ::= id | int | ( <exp> )

```