Electro-Hydraulic Servo Universal Testing Machine

Hung Ta Instrument | Model: HT-9501

Where structural integrity meets laboratory precision.



PRODUCT OVERVIEW

With wide range of function and application, suitable for research, inspection, and testing in the field of metal, rubber, plastic, leather, cable and wire, textile, fiber, paper, PE, construction materials, electric appliance, petrochemical, transportation, automobile, package, polymer, aerospace and more. FDC55 high strength casting material with high stiffness axle materials for strong structure, high stability, and long durability. Hydraulic system adopts high efficiency pump and high conversational servo valve with excellent filtration. High accuracy loadcell with accuracy of load reaching ±0.005%, force accuracy reaches ±0.5 class. Close-loop fuzzy servo control matched with high precision servo valve.

Category
Universal Testing Machine

KEY FEATURES / SPECIFICATIONS

Capacity	300 ~ 4,000 kN	**Load Accuracy**	±1% (Class 1), optional ±0.5%
Force Resolution	1/200,000 (Hung Ta Interface Card)	**Drive System**	Electro-hydraulic servo
Tests	Tensile, compression, shear, bending, peeling	**Loading Speed**	=100 max. (60 Hz)
Crosshead Speed	150 ~ 300 mm/min	**Optional**	Environmental chamber, extensometer, furnace

TYPICAL APPLICATIONS

Steel mills • Metal manufacturers • Construction materials • Automotive • Petrochemical • Aerospace

REFERENCED STANDARDS

ASTM E4 | ASTM E8-04 | ISO 7500-1-2004 | ISO 6892-1 | GB/T 228-2010 | DIN 5122 | JIS B7721

CONFIGURATION & QUOTATION

Tell us the sample material, dimensions, required test method, standard and capacity. We will check the suitable machine, fixture and configuration before quotation.

Product image is for identification. Confirm exact model configuration and supplied accessories before order.