ARMSTRONG

WDS-20

Dual Column Touchscreen Tensile Testing Machine



Product illustration. Supplied grips and accessories depend on the confirmed configuration.

500 kgf
Rated test load

1-500 mm/min
Test speed

800 mm
Travel excluding grips

Request your WDS-20 quotation

012-628 0096 | hungtatest@yahoo.com

Malaysia team in Seremban | Click to enquire on WhatsApp

ARMSTRONG WDS-20

A servo-driven, dual-column system for tensile testing in factory QC and material testing laboratories. Touchscreen control keeps test setup and live force readings together.

Technical specifications

Parameter	Specification
Capacity	500 kgf (approximately 4.9 kN)
Control	TS7003L touchscreen measurement and control system
Drive System	Servo motor, dual-column frame
Tests	Tensile; compression with suitable fixtures
Test speed	1-500 mm/min
Maximum travel	800 mm excluding grips
Force Accuracy	+/-1% per supplied manual; verify configured range
Force Resolution	1/25,000
Force units	kg, N, lb
Machine dimensions	1010 x 490 x 1730 mm
Weight	Approximately 150 kg
Power supply	Single-phase 220 V; confirm electrical rating before installation

Confirm your test configuration

- Specimen material, dimensions and expected maximum force.
- Grip type, jaw faces and specimen holding requirements.
- Compression fixtures and measurement needs, if required.

Electrical rating must be confirmed against the supplied machine nameplate before installation. Grips reduce the usable specimen clearance.

Specifications are reference values for configuration review. Final capacity, fixtures, software functions and supplied accessories must be agreed in the quotation. Calibration scope and documentation are confirmed separately.

Request your WDS-20 quotation

012-628 0096 | hungtatest@yahoo.com

Malaysia team in Seremban | Click to enquire on WhatsApp