Armstrong / PRODUCT CATALOGUE

WDS-20

Dual Column Touchscreen Tensile Testing Machine

Servo-driven tensile testing with touchscreen control for laboratory and factory QC.



Product overview

The ARMSTRONG WDS-20 is a dual-column touchscreen tensile testing machine with a servo motor and TS7003L measurement and control system. Select the force range, specimen grips and test settings for your material and application. The controller supports tensile and compression test directions; compression testing requires the appropriate fixtures. Confirm the supplied capacity and accessories in the quotation.

Technical specifications

Capacity	500 kgf (approximately 4.9 kN)
Control	TS7003L touchscreen measurement and control system
Drive System	Servo motor, dual-column frame
Tests	Tensile; compression with suitable fixtures
Test speed	1-500 mm/min
Maximum travel	800 mm excluding grips
Force Accuracy	+/-1% per supplied manual; verify configured range
Force Resolution	1/25,000
Force units	kg, N, lb
Machine dimensions	1010 x 490 x 1730 mm
Weight	Approximately 150 kg
Power supply	Single-phase 220 V; confirm electrical rating before installation

Typical applications

Factory quality control / Material testing laboratories / Specimen tensile testing

Configuration & quotation

Send the specimen material and dimensions, required force range, test method and factory location. Confirm the supplied machine, fixtures and accessories in the quotation.

Specifications are reference values for configuration review. Contact Hung Ta Instrument for the current supplied configuration.